CLAIMS

1. A system comprising an elevator speed limiter (10) and a steel cable anti-stripping device (4), characterized in that,

the elevator speed limiter (10) comprises a base (2), a cable wheel (1) and a steel cable (5), wherein the steel cable anti-stripping device (4) is fixedly installed on the base (2) of the elevator speed limiter (10), and the cable wheel (1) that is wound with the steel cable (5) inside its cable groove (6) is rotatably installed on the base (2); and the steel cable anti-stripping device (4) is so configured that a portion thereof covers an outer peripheral portion of the cable wheel (1), so as to prevent the steel cable (5) from moving out of the cable groove (6) of the cable wheel (1),

a gap between the steel cable anti-stripping device (4) and an outermost surface of the outer peripheral portion of the cable wheel (1) is 2 mm or less, and

a gap between the steel cable anti-stripping device (4) and an outer surface of an outermost steel cable (5) is 3 mm or less, wherein the gap between the steel cable anti-stripping device (4) and the outermost surface of the outer peripheral portion of the cable wheel (1), is smaller than the gap between the steel cable anti-stripping device (4) and the outer surface of the outermost steel cable (5).

2. The system as claimed in claim 1, characterized in that,

there are two steel cable anti-stripping devices (4) corresponding to an entrance where the steel cable (5) enters the cable groove (6) and an exit where the steel cable leaves the cable groove (6), wherein the entrance is a place where the steel cable (5) enters the cable groove (6), and the exit is a place where the steel cable (5) comes out of the cable groove (6).

3. The system as claimed in any one of claim 1 or 2, characterized in that,

the steel cable anti-stripping device (4) is provided on a flange (7) arranged on the base (2) of the elevator speed limiter (10).

4. The system as claimed in any one of claim 1 or 2, characterized in that,

the steel cable anti-stripping device (4) is formed to have an L-shaped cross section, one side of the L-shape being fixed to the base (2) of the elevator speed limiter (10) by a fixing mechanism.

5. The system as claimed in any one of claims 1-4, wherein the elevator speed limiter (10) further comprises an actuating switch (3).