

Description

Technical Field

This invention relates to a hollow tubular plastic core for an elastically shrinkable tubular cover to be applied as a covering around an electrical cable or the like.

Background Art

A hollow tubular plastic core for an elastically shrinkable tubular cover must have sufficient strength to resist the shrinkage force of the cover member and retain its tubular shape, and it must be easily removed by breaking into a continuous strip with simple manual work. Known hollow plastic cores for elastically shrinkable tubular covers include one in which a continuous helical cut is made in the wall along the entire length of a tube, as disclosed in United States Patent No. 515,798, and one in which a plastic strip is wound in a helix to make a tubular form with the edges of the strip abutted, and the abutted edges being ultrasonically spot welded.

It has been found to be impractical to make the tubular plastic core by making a continuous helical cut in a tube having a uniform wall thickness because of the problems of maintaining the cut at a given depth due to variations in the roundness and the wall thickness of the core and the movement of a cutter in cutting. A cut that is too deep does not provide sufficient strength to resist the shrinkage force of the tubular cover member or to prevent the tubular structure from deforming the core which might not permit a cable to be inserted. A cut that is too shallow does not permit the core to be manually broken into a strip with sufficient ease.

It is necessary in the process of forming a plastic strip into a tube by abutting its edges to be certain that the edges align properly, and the manufacturing process is, therefore, complex. Furthermore, due to its helical winding, the core can be broken into a strip only in one direction (an attempt to break it in the opposite direction will get the core tangled). The directional property of such a plastic core has to be taken into consideration in use, causing inconvenience in certain applications.

Disclosure of Invention

In accordance with the present invention as it is set out in the Claim, there is provided a hollow tubular plastic core having a plurality of lugs extending longitudinally on its inner wall. A continuous helical cut made in the wall from the exterior surface thereof along its entire length severs the tube into a continuous strip with only the lugs connected axially along the length of the tube. One end of the strip is broken free from the tube for a distance and extends back through the tube.

Brief Description of Drawings

In the Drawing:

Figure 1 is a partially sectioned side elevation

view illustrating a device for covering a portion of a cable to be connected employing the hollow tubular plastic core of this invention, with the core partially removed;

Figure 2 is a perspective view of one embodiment of the hollow tubular plastic core of this invention;

Figure 3A is a cross-sectional view taken generally along line A—A' of Figure 2; and Figures 3B, 3C and 3D are similar views illustrating alternative forms of lugs on the inner wall.

Detailed Description

Figure 1 shows two cable ends, each comprising a stranded conductor 4 and an insulating covering 3. The insulation is cut away and the conductors 4 joined together end-to-end by suitable means not shown but which may typically consist of a compressed or indented metal sleeve or a close-fitting metal tube with set-screw retainers. The joint or splice may be covered with insulating mastic or tape, here omitted for clarity of illustration.

The cover assembly illustrated in Figure 1 comprises an elastic tubular cover member 1 supported in a highly radially stretched condition on a hollow tubular plastic core 2 constructed in accordance with the present invention. The assembly is slipped over one of the wire ends prior to joining the two ends. After the splice is completed, the assembly is slid into position over the splice area and the plastic core 2 is removed to permit the elastic cover to contract and form a tight fit. Figure 1 illustrates the assembly after the core has been partially removed.

The hollow tubular core 2 of the invention is a cylindrical plastic tube having an internal diameter greater than the external diameter of the object to be covered, such as the cable joint illustrated in Figure 1. The plastic tube has a plurality of circumferentially spaced, axially extending lugs on its inner wall. Two forms of lugs in the shape of rectangular and rounded ribs 6 are illustrated in Figures 3A and 3B, respectively. Two alternative forms of ribs formed by indentations in the wall of the core to form rectangular or rounded internal protrusions 7 are illustrated in Figures 3C and 3D, respectively. The wall of the hollow plastic core is preferably 0.5 to 2.5 mm thick with the lugs about 0.5 mm tall.

A continuous helical cut 5 is made in the wall of the tube from the exterior surface thereof to sever the tube into a continuous strip 2 with only the lugs 6 or 7 remaining connected axially along the length of the tube. The standard for the depth of the cut is preferably set as being a little deeper than the wall thickness of the hollow plastic core where there are no lugs (e.g. 0.1 to 0.2 mm deeper than the wall thickness). The lugs (which are preferably about 0.5 mm tall) will then not be cut even when the cut is deeper than the standard, and it has been found that the lugs still provide sufficient resistance to the shrinkage force of the elastic cover member 1 to retain the shape of the tubular structure. Furthermore, with the standard

(21)

cut extending into the lugs, even when the cut is shallower than the standard, the wall of the portion where there are no lugs can be reliably cut completely in production so that the core can manually be broken into a continuous strip with ease.

One end of the strip 2 is broken away from the tube during manufacture and fed back through the tube to provide an exposed free end. In use, the free end can then be pulled on manually to break the strip 2 and remove it from the cover member 1, as illustrated in Figure 1.

The core is preferably made of a versatile plastic, for example, either polypropylene, polyethylene or polyvinyl chloride may be used. The cylindrical tube is preferably extruded with a plurality of the lugs extending longitudinally on the inner wall. As illustrated in Figure 3, the lugs may be rectangular or curved in cross-section and while they are preferably formed on a uniform thickness tubular wall as illustrated in Figures 3A and 3B, they may also take the form of longitudinal indentations in a uniform thickness wall as illustrated in Figures 3C and 3D. The continuous helical cut 5 made in the tube wall along its entire length may be made by a process similar to that of screw cutting.

Claim

A hollow tubular plastic core (2) for supporting an elastic tubular cover member (1) in a highly radially stretched condition so that the cover member can be positioned over a generally cylindrical object and the core removed to permit the cover member to contract to conform to the outer surface of the object (3), the core being a plastic tube (2) with an internal diameter greater than the external diameter of the object to be covered and being breakable into a continuous strip (2) by pulling on a free end of the strip that extends back through the tube, characterized in that said tube has a plurality of circumferentially spaced, axially extending lugs (6 or 7) on the inner wall of said tube and that a continuous helical cut (5) in the wall of said tube from the exterior surface thereof severs said tube into said continuous strip (2) with only the lugs connected axially along the length of said tube.

Patentanspruch

Hohler rohrförmiger Kern (2) aus Kunststoff

zum Abstützen einer elastischen schlauchförmigen Hülle (1) in radial stark gespanntem Zustand, so daß die Hülle über einem allgemein zylindrischen Gegenstand angeordnet und dann der Kern entfernt werden und die Hülle sich unter Anpassung an die Außenwandung des Gegenstandes (3) zusammenziehen kann, wobei der Kern ein Kunststoffrohr (2) ist, dessen Innendurchmesser größer ist als der Außendurchmesser des zu umhüllenden Gegenstandes, und der Kern unter Bildung eines ununterbrochenen Bandes (2) aufgebrochen werden kann, indem an dem freien Ende des sich durch das Rohr rückwärts erstreckenden Bandes gezogen wird, dadurch gekennzeichnet, an der Innenwandung des Rohrs eine Mehrzahl von axialen Vorsprüngen (6 oder 7) in der Umfangsrichtung in Abständen voneinander angeordnet sind und daß in der Wand des Rohrs ein sich von dessen Außenwandung erstreckender, ununterbrochener wendelförmiger Einschnitt (5) ausgebildet ist, der das Rohr unter Bildung des ununterbrochenen Bandes (2) derart durchsetzt, daß nur die Lappen über die Länge des Rohrs axial durchgehen.

Revendication

Noyau tubulaire creux (2) en matière plastique destiné à supporter un élément formant gaine (1) tubulaire en matière élastique dans un état d'étiage radial important, de manière que cet élément formant gaine puisse être disposé sur un objet d'allure générale cylindrique et que le noyau puisse être enlevé pour permettre à cet élément formant gainé de se contracter pour se conformer à la surface externe de l'objet (3), le noyau étant constitué par un tube en matière plastique (2) d'un diamètre interne supérieur au diamètre externe de l'objet à envelopper et pouvant être déchiré sous forme d'une bande continue (2) par traction sur une extrémité libre de cette bande, qui s'étend vers l'arrière à travers le tube, caractérisé en ce que ce tube présente une série d'oreilles (6 ou 7) s'étendant axialement et espacées suivant la circonférence sur la paroi interne de ce tube, et en ce qu'une coupure hélicoïdale continue (5) pratiquée dans la paroi de ce tube depuis la surface extérieure de celui-ci subdivise ce tube en la bande continue (2), seules les oreilles étant connectées axialement suivant la longueur de ce tube.

55

60

65

3

(21)

cut extending into the lugs, even when the cut is shallower than the standard, the wall of the portion where there are no lugs can be reliably cut completely in production so that the core can manually be broken into a continuous strip with ease.

One end of the strip 2 is broken away from the tube during manufacture and fed back through the tube to provide an exposed free end. In use, the free end can then be pulled on manually to break the strip 2 and remove it from the cover member 1, as illustrated in Figure 1.

The core is preferably made of a versatile plastic, for example, either polypropylene, polyethylene or polyvinyl chloride may be used. The cylindrical tube is preferably extruded with a plurality of the lugs extending longitudinally on the inner wall. As illustrated in Figure 3, the lugs may be rectangular or curved in cross-section and while they are preferably formed on a uniform thickness tubular wall as illustrated in Figures 3A and 3B, they may also take the form of longitudinal indentations in a uniform thickness wall as illustrated in Figures 3C and 3D. The continuous helical cut 5 made in the tube wall along its entire length may be made by a process similar to that of screw cutting.

Claim

A hollow tubular plastic core (2) for supporting an elastic tubular cover member (1) in a highly radially stretched condition so that the cover member can be positioned over a generally cylindrical object and the core removed to permit the cover member to contract to conform to the outer surface of the object (3), the core being a plastic tube (2) with an internal diameter greater than the external diameter of the object to be covered and being breakable into a continuous strip (2) by pulling on a free end of the strip that extends back through the tube, characterized in that said tube has a plurality of circumferentially spaced, axially extending lugs (6 or 7) on the inner wall of said tube and that a continuous helical cut (5) in the wall of said tube from the exterior surface thereof severs said tube into said continuous strip (2) with only the lugs connected axially along the length of said tube.

Patentanspruch

Hohler rohrförmiger Kern (2) aus Kunststoff

zum Abstützen einer elastischen schlauchförmigen Hülle (1) in radial stark gespanntem Zustand, so daß die Hülle über einem allgemein zylindrischen Gegenstand angeordnet und dann der Kern entfernt werden und die Hülle sich unter Anpassung an die Außenwandung des Gegenstandes (3) zusammenziehen kann, wobei der Kern ein Kunststoffrohr (2) ist, dessen Innendurchmesser größer ist als der Außendurchmesser des zu umhüllenden Gegenstandes, und der Kern unter Bildung eines ununterbrochenen Bandes (2) aufgebrochen werden kann, indem an dem freien Ende des sich durch das Rohr rückwärts erstreckenden Bandes gezogen wird, dadurch gekennzeichnet, an der Innenwandung des Rohrs eine Mehrzahl von axialen Vorsprüngen (6 oder 7) in der Umfangsrichtung in Abständen voneinander angeordnet sind und daß in der Wand des Rohrs ein sich von dessen Außenwandung erstreckender, ununterbrochener wendelförmiger Einschnitt (5) ausgebildet ist, der das Rohr unter Bildung des ununterbrochenen Bandes (2) derart durchsetzt, daß nur die Lappen über die Länge des Rohrs axial durchgehen.

Revendication

Noyau tubulaire creux (2) en matière plastique destiné à supporter un élément formant gaine (1) tubulaire en matière élastique dans un état d'étiage radial important, de manière que cet élément formant gaine puisse être disposé sur un objet d'allure générale cylindrique et que le noyau puisse être enlevé pour permettre à cet élément formant gainé de se contracter pour se conformer à la surface externe de l'objet (3), le noyau étant constitué par un tube en matière plastique (2) d'un diamètre interne supérieur au diamètre externe de l'objet à envelopper et pouvant être déchiré sous forme d'une bande continue (2) par traction sur une extrémité libre de cette bande, qui s'étend vers l'arrière à travers le tube, caractérisé en ce que ce tube présente une série d'oreilles (6 ou 7) s'étendant axialement et espacées suivant la circonférence sur la paroi interne de ce tube, et en ce qu'une coupure hélicoïdale continue (5) pratiquée dans la paroi de ce tube depuis la surface extérieure de celui-ci subdivise ce tube en la bande continue (2), seules les oreilles étant connectées axialement suivant la longueur de ce tube.



* C L M S *