

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
5 December 2002 (05.12.2002)

PCT

(10) International Publication Number
WO 02/097918 A1

(51) International Patent Classification⁷: **H01Q 1/40**, 9/16

(21) International Application Number: PCT/US02/16919

(22) International Filing Date: 30 May 2002 (30.05.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/870,232 30 May 2001 (30.05.2001) US

(71) Applicant (for all designated States except US): **ADS CORPORATION** [US/US]; 5030 Bradford Drive, Building 1, Suite 210, Huntsville, AL 35805 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **PECORA, Jr., Ronald, A.** [US/US]; 26 Gage Drive, East Falmouth, MA, 02536 (US).


(74) Agents: **VILLACORTA, Gilberto, M.** et al.; KATTEN MUCHIN ZAVIS ROSENMAN, Customer No 27160, 525 West Monroe Street, suite 1600, Chicago, IL 60661-3693 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: LOW PROFILE ANTENNA



(57) Abstract: A dipole antenna is constructed of flexible conductive elements (1, 2). These elements are encased in a flexible protective covering (3) or attached to a semi-rigid substrate. This covering (3) protects the antenna during handling, transport, and installation. The conductive elements (1, 2) and the protective covering (3) may be further encased or embedded in an external protective covering (4). The final external protective covering (4) serves as an adhesive to permanently attach the antenna to a mounting surface (7). When installed on the mounting surface, the antenna has a low profile with respect to the mounting surface (7).



WO 02/097918 A1



Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.