

DESCRIPTION

[TITLE OF THE INVENTION] CARTRIDGE AND
ELECTROPHOTOGRAPHIC IMAGE FORMING APPARATUS

5 [FIELD OF THE INVENTION]

[0001] The present invention relates to an electrophotographic image forming apparatus (image forming apparatus) and a cartridge detachably mountable to a main assembly of the image forming apparatus.

[0002] Here, the image forming apparatus forms an image on a recording
10 material using an electrophotographic image forming process. Examples of the image forming apparatus includes an electrophotographic copying machine, an electrophotographic printer (laser beam printer, LED printer or the like), a facsimile machine and a word processor, for example.

[0003] A cartridge contains an electrophotographic photosensitive drum
15 (photosensitive drum) as a photosensitive member which is an image bearing member, and at least one of process means (developer carrying member (developing roller) for example) actable on the photosensitive drum, which are unified into a unit detachably mountable to a main assembly of the image forming apparatus. In examples of the cartridge, the photosensitive drum and
20 the developing roller are unified into a cartridge, or the photosensitive drum and the developing roller are unified into respective cartridges. The former comprising the photosensitive drum and the developing roller is called a process cartridge. One of the latter which comprises the photosensitive drum is called a drum cartridge, and the other comprising the developing roller is called a
25 developing cartridge.

[0004] The main assembly of the image forming apparatus is the part of the image forming apparatus excluding the cartridge or cartridges.

[BACKGROUND ART]

[0005] In a conventional image forming apparatus, a process cartridge type is employed in which the photosensitive drum and process means actable on the photosensitive drum and the developing roller are unified into a cartridge which is detachably mountable to the main assembly of the image forming apparatus.

[0006] With the process cartridge type, a maintenance operations for the image forming apparatus can be carried out by the user without relying on a service person, and therefore, the operability is remarkably improved.

[0007] For this reason, the process cartridge type is widely used in the image forming apparatuses.

[0008] Japanese Laid-open Patent Application 2008-233867, for example, discloses a process cartridge which is usable an electrophotographic image formation type electrophotographic image forming apparatus and which is capable of being mounted and dismounted relative to a main assembly of the electrophotographic image forming apparatus provided with a driving shaft, in a direction substantially perpendicular to an axis of the driving shaft.

[SUMMARY OF THE INVENTION]

[Problem to be solved by the invention]

[0009] The present invention provides an improvement of the prior-art and provides a cartridge which is detachably mountable to a main assembly of the electrophotographic image forming apparatus in which a developer carrying member is capable of being contacted to and spaced from the photosensitive member.

[0010] It is a object of the present invention to provide a cartridge in which a coupling member is engageable with a main assembly driving shaft when the cartridge is mounted to a main assembly and when the developer carrying

member is moved from a retracted position to a developing position.

[0011] It is another object of the present invention to provide a cartridge in which a coupling member is disengageable from a main assembly driving shaft when the cartridge is dismounted from a main assembly and when the developer
5 carrying member is moved from a developing position to a retracted position.

It is a further object of the present invention to provide a cartridge in which a coupling member is engageable with a main assembly driving shaft when the developer carrying member moves from a retracted position to a developing position, and in which the coupling member is disengageable from the main
10 assembly driving shaft when the cartridge is dismounted from the main assembly.

[Means for solving the problem]

[0012] According to an aspect of the present invention, there is provided a cartridge mountable, along a predetermined mounting path, to a main assembly of the electrophotographic image forming apparatus including a photosensitive
15 member on which a latent image is capable of being formed and including a main assembly driving shaft, wherein said cartridge is movable in the main assembly between a developing position at a terminal end of said mounting path and a retracted position retracted from the developing position in a direction different from the mounting path, said cartridge comprising:

20 a developer carrying member capable of developing the latent image while being in contact with the photosensitive member when said cartridge is in the developing position; and

a coupling member capable of inclining relative to a rotational axis of said developer carrying member, wherein said coupling member is capable of
25 taking a reference attitude in which a drive transmission is capable from the main assembly driving shaft to said developer carrying member when said cartridge is in the developing position, an at-mounting attitude inclined relative to the

rotational axis of said developer carrying member to engage with the main assembly driving shaft when said cartridge moves along the mounting path, and an at-spaced attitude inclined relative to the rotational axis of said developer carrying member in a direction different from that in the at-mounting attitude.

5 [0013] According to another aspect of the present invention, there is provided a cartridge mountable, along a predetermined mounting path, to a main assembly of the electrophotographic image forming apparatus including a main assembly driving shaft, said cartridge comprising:

10 a photosensitive member on which a latent image is capable of being formed;

a developer carrying member capable of developing the latent image and the movable between a developing position contacting said photosensitive member to develop the latent image and a retracted position retracted from the contacting position; and

15 a coupling member capable of inclining relative to a rotational axis of said developer carrying member, wherein said coupling member is capable of taking a reference attitude in which the drive transmission is capable from the main assembly driving shaft to said developer carrying member when said developer carrying member is in the developing position in a state that said
20 cartridge is mounted at a terminal end of the mounting path, an at-mounting attitude inclined relative to the rotational axis of said developer carrying member to engage with the main assembly driving shaft when said cartridge moves along the mounting path, an at-spaced attitude inclined relative to the rotational axis of said developer carrying member in a direction different from that in the at-
25 mounting attitude to engage with the main assembly side driving shaft when said developer carrying member moves from the retracted position to the developing position in the state that said cartridge is mounted at the end portion of the

mounting path.

[0014] According to a further aspect of the present invention, there is provided a cartridge detachably mountable to an electrophotographic image forming apparatus, said cartridge comprising:

- 5 i) a rotatable developer carrying member;
- ii) a coupling member for transmitting a rotational force to said developer carrying member and capable of taking a reference attitude parallel with a rotational axis of said developer carrying member and offset therefrom, a first inclination attitude inclined toward said developer carrying member, and a
- 10 second inclination attitude inclined in a direction different from that in the first inclination attitude;
- iii) an urging portion for urging said coupling member to incline rotational axis of said coupling member relative to the rotational axis of said developer carrying member; and
- 15 iv) a movable portion capable of taking a first movement position for causing said coupling member to take the first inclination attitude and a second movement position for causing said coupling member to take the second inclination attitude.

[0015] According to a further aspect of the present invention, there is provided a cartridge detachably mountable to an electrophotographic image forming apparatus, said cartridge comprising:

- i) a rotatable developer carrying member;
- ii) a coupling member for transmitting a rotational force to said developer carrying member and capable of taking a reference position in parallel
- 25 with a rotational axis of said developer carrying member, a first inclination attitude inclined from the reference position in a predetermined direction, a second inclination attitude inclined in a direction different from the

predetermined direction of said first inclination attitude;

iii) an urging portion for urging said coupling member to incline rotational axis of said coupling member relative to the rotational axis of said developer carrying member; and

5 iv) a movable portion capable of taking a first movement position for causing said coupling member to take the first inclination attitude and a second movement position for causing said coupling member to take the second inclination attitude.

[0016] According to a further aspect of the present invention, there is
10 provided a cartridge detachably mountable to an electrophotographic image forming apparatus, said cartridge comprising:

i) a rotatable developer carrying member;

ii) a coupling member for transmitting a rotational force to said
15 developer carrying member and capable of taking a reference attitude parallel with a rotational axis of said developer carrying member and offset therefrom, a first inclination attitude inclined toward said developer carrying member, and a second inclination attitude inclined in a direction different from that in the first inclination attitude;

iii) an urging member for urging said coupling member to incline it to
20 the first inclination attitude; and

iv) a movable member movable to cause said coupling member to take the first inclination attitude or the second inclination attitude.

[0017] According to a further aspect of the present invention, there is
25 provided an electrophotographic image forming apparatus for forming an image on a recording material, said apparatus comprising:

i) a main assembly including a photosensitive member and which a latent image is capable of being formed, and including a main assembly driving

shaft; and

ii) a cartridge mountable, along a predetermined mounting path, to the main assembly, wherein said cartridge is movable in the main assembly between a developing position at a terminal end of said mounting path and a retracted position retracted from the developing position in a direction different from the mounting path, said cartridge including,

ii-i) a developer carrying member capable of developing the latent image while being in contact with the photosensitive member when said cartridge is in the developing position; and

ii-ii) a coupling member capable of inclining relative to a rotational axis of said developer carrying member, wherein said coupling member is capable of taking a reference attitude in which a drive transmission is capable from the main assembly driving shaft to said developer carrying member when said cartridge is in the developing position, an at-mounting attitude inclined relative to the rotational axis of said developer carrying member to engage with the main assembly driving shaft when said cartridge is moved along the mounting path, and an at-spaced attitude inclined relative to the rotational axis of said developer carrying member in a direction different from that in the at-mounting attitude when said cartridge is moved from the retracted position to the developing position.

[0018] According to a further aspect of the present invention, there is provided an electrophotographic image forming apparatus for forming an image on a recording material, said apparatus comprising:

i) a main assembly including a main assembly driving shaft; and

ii) a cartridge mountable to the main assembly along a predetermined mounting path;

ii-i) a photosensitive member on which a latent image is capable of

being formed;

ii -ii) a developer carrying member capable of developing the latent image and the movable between a developing position in which said developer carrying member contacts said photosensitive member to develop the latent
5 image and a retracted position retracted from the contacting position, in a state that said cartridge is mounted to said main assembly; and

ii-iii) a coupling member capable of inclining relative to a rotational axis of said developer carrying member, wherein said coupling member is capable of taking a reference attitude in which the drive transmission is capable
10 from the main assembly driving shaft to said developer carrying member when said developer carrying member is in the developing position, an at-mounting attitude inclined relative to the rotational axis of said developer carrying member to engage with the main assembly side driving shaft when said cartridge is moved along the mounting path, and an at-spaced attitude inclined relative to the
15 rotational axis of said developer carrying member in a direction different from that in the at-mounting attitude to engage with the main assembly side driving shaft when said developer carrying member is moved from the retracted position to the developing position.

[0019] According to a further aspect of the present invention, there is
20 provided a cartridge mountable, along a predetermined mounting path, to a main assembly of the electrophotographic image forming apparatus including a photosensitive member on which a latent image is capable of being formed and including a main assembly driving shaft, wherein said cartridge is movable in the main assembly between a developing position at a terminal end of said mounting
25 path and a retracted position retracted from the developing position in a direction different from the mounting path, said cartridge comprising:

a developer carrying member capable of developing the latent image

while being in contact with the photosensitive member when said cartridge is in the developing position; and

a coupling member capable of inclining relative to a rotational axis of said developer carrying member, wherein said coupling member is capable of taking a reference attitude in which a drive transmission is capable from the main assembly driving shaft to said developer carrying member when said cartridge is in the developing position, an at-dismounting attitude inclined relative to the rotational axis of said developer carrying member to disengage from the main assembly side driving shaft when said cartridge is dismounted from the main assembly by being moved along the mounting path from the developing position in the direction opposite from that in the mounting, and at-spaced attitude inclined relative to the rotational axis of said developer carrying member in a direction different from that in the at-dismounting attitude to disengage from the main assembly side driving shaft when said cartridge is moved from the developing position to the retracted position.

[0020] According to a further aspect of the present invention, there is provided a cartridge mountable, along a predetermined mounting path, to a main assembly of the electrophotographic image forming apparatus including a main assembly driving shaft, said cartridge comprising:

a photosensitive member on which a latent image is capable of being formed;

a developer carrying member capable of developing the latent image and the movable between a developing position contacting said photosensitive member to develop the latent image and a retracted position retracted from the contacting position; and

a coupling member capable of inclining relative to a rotational axis of said developer carrying member, wherein said coupling member is capable of

taking a reference attitude in which a drive transmission is capable from the main assembly driving shaft to said developer carrying member when said cartridge is in the developing position in a state that said cartridge is mounted to a terminal end of the mounting path, an at-dismounting attitude inclined relative to the rotational axis of said developer carrying member to disengage from the main assembly side driving shaft when said cartridge is dismounted from the main assembly by being moved along the mounting path from the terminal end in the direction opposite from that in the mounting, and an at-spaced attitude inclined relative to the rotational axis of said developer carrying member in a direction different from that in the at-dismounting attitude to disengage from the main assembly side driving shaft when said developer carrying member is moved from the developing position to the retracted position in the state that said cartridge is mounted to the terminal end.

[0021] According to a further aspect of the present invention, there is provided a cartridge mountable, along a predetermined mounting path, to a main assembly of the electrophotographic image forming apparatus including a photosensitive member on which a latent image is capable of being formed and including a main assembly driving shaft, wherein said cartridge is movable in the main assembly between a developing position at a terminal end of said mounting path and a retracted position retracted from the developing position in a direction different from the mounting path, said cartridge comprising:

a developer carrying member capable of developing the latent image while being in contact with the photosensitive member when said cartridge is in the developing position; and

a coupling member capable of inclining relative to a rotational axis of said developer carrying member, wherein said coupling member is capable of taking a reference attitude in which a drive transmission is capable from the main

assembly driving shaft to said developer carrying member when said cartridge is in the developing position, an at-dismounting attitude inclined relative to the rotational axis of said developer carrying member to disengage from the main assembly side driving shaft when said cartridge is dismounted from the main assembly by being moved along the mounting path from the developing position in the direction opposite from that in the mounting, and an at-spaced attitude inclined relative to the rotational axis of said developer carrying member in a direction different from that in the at-dismounting attitude to engage with the main assembly side driving shaft when said cartridge is moved from the retracted position to the developing position.

[0022] According to a further aspect of the present invention, there is provided a cartridge mountable, along a predetermined mounting path, to a main assembly of the electrophotographic image forming apparatus including a main assembly driving shaft, said cartridge comprising:

15 a photosensitive member on which a latent image is capable of being formed;

a developer carrying member capable of developing the latent image and the movable between a developing position contacting said photosensitive member to develop the latent image and a retracted position retracted from the contacting position; and

20 a coupling member capable of inclining relative to a rotational axis of said developer carrying member, wherein said coupling member is capable of taking a reference attitude in which a drive transmission is capable from the main assembly driving shaft to said developer carrying member when said cartridge is in the developing position in a state that said cartridge is mounted to a terminal end of the mounting path, an at-dismounting attitude inclined relative to the rotational axis of said developer carrying member to disengage from the main

assembly side driving shaft when said cartridge is dismounted from the main assembly by being moved along the mounting path from the terminal end in the direction opposite from that in the mounting, and an at-spaced attitude inclined relative to the rotational axis of said developer carrying member in a direction
5 different from that in the at-dismounting attitude to engage with the main assembly side driving shaft when said developer carrying member is moved from the retracted position to the developing position in the state that said cartridge is mounted to the terminal end.

10 [Effect of the invention]

[0023] According to the present invention, there is provided a cartridge in which a coupling member is engageable with a main assembly driving shaft when the cartridge is mounted to a main assembly and when the developer carrying member is moved from a retracted position to a developing position.

15 [0024] According to another aspect of the present invention, there is provided a cartridge in which a coupling member is disengageable from a main assembly driving shaft when the cartridge is dismounted from a main assembly and when the developer carrying member is moved from a developing position to a retracted position.

20 According to a further aspect of the present invention, there is provided a cartridge in which a coupling member is engageable with a main assembly driving shaft when the developer carrying member moves from a retracted position to a developing position, and in which the coupling member is disengageable from the main assembly driving shaft when the cartridge is
25 dismounted from the main assembly.

[BRIEF DESCRIPTION OF THE DRAWINGS]

[0025] Figure 1 is a side view of a developing cartridge B1 per se (spontaneous state) according to a first embodiment of the present invention before the developing cartridge B1 is mounted to a main assembly A1.

[0026] Figure 2 is a schematic sectional side view of an electrophotographic image forming apparatus according to the first embodiment of the present invention.

[0027] Figure 3 is a schematic sectional view of the developing cartridge B1 and a drum cartridge C according to the first embodiment of the present invention.

[0028] Figure 4 is a schematic perspective view of the developing cartridge B1 according to the first embodiment of the present invention as seen from a driving side.

[0029] Figure 5 is a schematic perspective view of the developing cartridge B1 according to the first embodiment of the present invention as seen from a non-driving side.

[0030] Part (a) of Figure 6 is a schematic perspective view as seen from driving side according to the first embodiment of the present invention, in which the driving side of the developing cartridge B1 is exploded, and part (b) of Figure 6 is a schematic perspective view as seen from the non-driving side according to the first embodiment of the present invention, in which the driving side of the developing cartridge B1 is exploded.

[0031] Part (a) of Figure 7 is a schematic perspective view as seen from the driving side, in which the non-driving side of the developing cartridge B1 is exploded, and part (b) of Figure 7 is a schematic perspective view as seen from the non-driving side according to the first embodiment of the present invention, in which the non-driving side of the developing cartridge B1 is exploded.

[0032] Part (a) of Figure 8 is a illustration of peripheral parts of a coupling member 180 in an embodiment of the present invention, part (b) of Figure 8 is an

illustration of peripheral parts of the coupling member 180 in an embodiment of the present invention, part (c) of Figure 8 is an illustration of engagement between the coupling member 180 and a main assembly side driving member 100 in an embodiment of the present invention, and (d) is an illustration of the engagement between the coupling member 180 and the main assembly side driving member 100 in an embodiment of the present invention, and part (e) illustrates an engagement state between the coupling member 180 and the main assembly side driving member 100 according to the first embodiment of the present invention.

10 [0033] Figure 9 is a schematic perspective view and a side view illustrating assembling of a coupling lever 55 and a coupling lever spring 56 to a development side cover 34 according to the first embodiment of the present invention.

[0034] Figure 10 illustrates a schematic perspective view and a side view illustrating assembling of the development side cover 34 according to the first embodiment of the present invention.

[0035] Figure 11 is an illustration of the developing cartridge B1 according to the first embodiment of the present invention in the state that the developing cartridge B1 is mounted in the main assembly A1, and a photosensitive drum 10 and the developing roller 13 are spaced from each other (spaced state).

[0036] Figure 12 is an illustration of the developing cartridge B1 according to the first embodiment of the present invention in the state before the developing cartridge B1 is mounted to the main assembly A1, that is, the developing cartridge B1 per se is in the spontaneous state.

25 [0037] Figure 13 is a view as seen from a longitudinal section illustrating the engagement state between the coupling member 180 and the main assembly side driving member 100, in the first embodiment of the present invention.

[0038] Figure 14 is a sectional view illustrating attitudes of the coupling member until the coupling member 180 becomes coaxial with a main assembly driving member 100 in the first embodiment of the present invention.

5 [0039] Figure 15 is an illustration of an inclination attitude (reference attitude D0) of a development coupling 180 when the mounting of the developing cartridge B1 to the main assembly A1 is completed, in the first embodiment of the present invention.

[0040] Figure 16 illustrates a relationship between the coupling member 180, a drive input gear 27 and a driving side development bearing 36 in the first
10 embodiment of the present invention.

[0041] Part (a) of Figure 17 is a schematic perspective view of the drum cartridge C as seen from the non-driving side, according to the first embodiment of the present invention, and part (b) of Figure 17 is a schematic perspective view of the drum cartridge C with a drum frame 21, a drum shaft reception 30 and a
15 drum shaft 54 and so on are omitted, according to the first embodiment of the present invention.

[0042] Figure 18 is a schematic perspective view of the main assembly A1 as seen from the non-driving side according to the first embodiment of the present invention.

20 [0043] Figure 19 is a schematic perspective view of the main assembly A1 as seen from the driving side, according to the first embodiment of the present invention.

[0044] Figure 20 is an illustration of mounting process of the developing cartridge B1 to the main assembly A1 according to the first embodiment of the
25 present invention.

[0045] Figure 21 is a schematic perspective view of peripheral configurations of a driving side swing guide 80 and a driving side urging member 82 in the first

embodiment of the present invention.

[0046] Figure 22 is a sectional view illustrating operations of the coupling lever 55 and the coupling member 180 in the process of mounting the developing cartridge B1 to the main assembly A in the first embodiment of the present invention.

[0047] Figure 23 is an illustration of positions of the coupling lever 55 and the coupling member 180 when the mounting of the developing cartridge B1 to the main assembly A is completed.

[0048] Figure 24 is a sectional view showing the relationship of the forces around the coupling member 180 when an annular portion 180f of the coupling member 180 contacts the main assembly side driving member 100.

[0049] Figure 25 is a illustration of a driving side contacting/spacing lever 70 and peripheral configurations thereof in the first embodiment of the present invention.

[0050] Figure 26 is a front view of a developing cartridge according to the first embodiment of the present invention.

[0051] Figure 27 is a perspective view of a driving-side side plate in the first embodiment of the present invention.

[0052] Figure 28 is a perspective view of a non-driving-side side plate in the first embodiment of the present invention.

[0053] Figure 29 is a side view of driving sides of the developing cartridge and a driving side swing guide in the first embodiment of the present invention.

[0054] Figure 30 is a side view of driving sides of the developing cartridge and a driving side swing guide in the first embodiment of the present invention.

[0055] Figure 31 is a side view of a non-driving side of the developing cartridge and a non-driving side swing guide in the first embodiment of the present invention.

[0056] Figure 32 is a illustration of engagement states between the coupling member 180 and the main assembly driving member 100 in a contacted-developing-device-state in the spaced-developing-device-state in the first embodiment of the present invention.

5 [0057] Figure 33 is a illustration of engagement states between the coupling member 180 and the main assembly driving member 100 in a contacted-developing-device-state in the spaced-developing-device-state in the first embodiment of the present invention, as seen from a driving-side side surface.

[0058] Figure 34 illustrates a coupling lever 955 and a coupling lever spring
10 956 mounted to a driving side drum bearing 930, in a second embodiment of the present invention.

[0059] Figure 35 is a perspective view illustrating the developing cartridge B1 and the drum cartridge C a unified into a combined process cartridge P, according to the second embodiment of the present invention.

15 [0060] Figure 36 is a view of the developing cartridge B1 swing relative to the drum cartridge C, as seen from the driving side, according to the second embodiment of the present invention.

[0061] Figure 37 shows attitudes of the coupling lever 955 and the coupling member 180 in a process cartridge P according to the second embodiment of the
20 present invention.

[0062] Figure 38 is a schematic perspective view of the main assembly A1 seen from the non-driving side according to the second embodiments of the present invention.

[0063] Figure 39 is a schematic perspective view of the main assembly A1 as
25 seen from the driving side, according to the second embodiment of the present invention.

[0064] Figure 40 is an illustration of the process cartridge P according to the

second embodiment of the present invention when it is being mounted to the main assembly A1.

[0065] Figure 41 is an illustration of the process cartridge P mounted completely to the main assembly A1, according to the second embodiment of the present invention.

[0066] Figure 42 is views of the developing cartridge B1 of the process cartridge P and the photosensitive drum 10 in which the developing cartridge B1 is in a development pressing state and in a spaced-developing-device-state.

[0067] Figure 43 is a schematic perspective view in the state for mounting a coupling spring 3185, a coupling lever 355 and a coupling lever spring 356 to a development side cover 334, according to a third embodiment of the present invention.

[0068] Figure 44 is a schematic perspective view in the state that the coupling lever 355, the coupling lever spring 356 and the coupling spring 3185 are mounted to the development side cover 334, according to the third embodiment of the present invention.

[0069] Figure 45 is a view of the developing cartridge B1 according to the third embodiment of the present invention, as seen from the driving side when the image forming operation can be carried out in the main assembly A1.

[0070] Figure 46 shows a first inclination attitude D1 of the coupling member 180 according to the third embodiment of the present invention.

[0071] Figure 47 shows a second inclination attitude D2 of the coupling member 180 according to the third embodiment of the present invention.

[0072] Figure 48 is a schematic perspective view of the state for mounting a coupling lever spring 456, a coupling lever 455 and a coupling spring 4185 to a development side cover 434 according to a fourth embodiment of the present invention.

[0073] Figure 49 is a view of the coupling lever 455, the coupling lever spring 456 and the coupling spring 4185 mounted to the development side cover 434 in the fourth embodiment the present invention.

[0074] Figure 50 is a view of the developing cartridge B1 according to the
5 fourth embodiment of the present invention as seen from the driving side in the state that the image formation can be carried out in the main assembly A1.

[0075] Figure 51 shows a first inclination attitude D1 of the coupling member 180 according to the fourth embodiment of the present invention.

[0076] Figure 52 shows a second inclination attitude D2 of the coupling
10 member 180 according to the fourth embodiment of the present invention.

[0077] Figure 53 is a schematic perspective view in the state before a spring 5185 and a spring 555 are assembled to a development side cover 534 in a fifth embodiment of the present invention.

[0078] Figure 54 is a view of the spring 555 and the spring 5185 mounted to the
15 development side cover 534 in the fifth embodiment of the present invention, as seen from the driving side.

[0079] Figure 55 shows a state in which the developing cartridge B1 is operable for image formation in the main assembly A1, in the fifth embodiment of the present invention.

[0080] Figure 56 shows the first inclination attitude D1 of the coupling member
20 180 in the fifth embodiment of the present invention.

[0081] Figure 57 shows the second inclination attitude D2 of the coupling member 180 in the fifth embodiment of the present invention.

[0082] Figure 58 is a schematic perspective view illustrating a state for
25 assembling a spring 6185 and a spring 555 to a development side cover 634 in a sixth embodiment of the present invention.

[0083] Figure 59 is a view of a spring 655, a rotatable member 656 and the

spring 6185 mounted to the side cover 634, as seen from the non-driving side, in the sixth embodiment of the present invention.

[0084] Figure 60 is a view of the developing cartridge B1 in the state that it is capable of image forming operation in the main assembly A1 in the sixth
5 embodiment of the present invention.

[0085] Figure 61 shows the first inclination attitude D1 of the coupling member 180 in the sixth embodiment of the present invention.

[0086] Figure 62 shows a state in which the coupling member 180 takes the second inclination attitude D2 in the sixth embodiment of the present invention.

10 [0087] Figure 63 is a schematic perspective view showing a state for mounting a coupling spring 7185, a coupling lever 755 and a coupling lever spring 756 to a development side cover 734 in a seventh embodiment of the present invention.

[0088] Figure 64 shows a state in which a lever 755, a spring 756 and a spring 7185 are mounted to a side cover 734, as seen from the non-driving side, in the
15 seventh embodiment of the present invention.

[0089] Figure 65 shows a state in which the developing cartridge B1 is operable for image formation in the main assembly A1 in the seventh embodiment of the present invention.

[0090] Figure 66 shows the first inclination attitude D1 of the coupling member
20 180 in the seventh embodiment of the present invention.

[0091] Figure 67 shows the state of the coupling member 180 taking the second inclination attitude D2 in the seventh embodiment of the present invention.

[0092] Figure 68 shows a state for assembling a coupling spring 8185, a coupling lever 855 and a coupling lever spring 856 to a development side cover
25 834 in the eighth embodiment of the present invention.

[0093] Figure 69 shows a state as seen from the driving side, in which a lever 855, a lever spring 856 and a coupling spring 8185 are to the development side

cover 834 in the eighth embodiment of the present invention.

[0094] Figure 70 shows a state in which the developing cartridge B1 is operable for image formation in the main assembly A1, in the eighth embodiment of the present invention.

5 [0095] Figure 71 shows the first inclination attitude D1 of the coupling member 180 in the eighth embodiment of the present invention.

[0096] Figure 72 shows a state in which the coupling member 180 takes the second inclination attitude D2 in the eighth embodiment of the present invention.

[0097] Figure 73 shows a state in which the coupling member 180 takes the
10 second inclination attitude D2 in a ninth embodiment of the present invention.

[0098] Part (a) of Figure 74 shows a coupling spring 10185 mounted to a development side cover 1034, part (b) of Figure 74 shows the second inclination attitude D2 of the coupling member 180, and part (c) of Figure 74 shows the first inclination attitude D1 of the coupling member 180, in a tenth embodiment of the
15 present invention.

[0099] Part (a) of Figure 75 shows a coupling spring 11185 and a lever 1155 mounted to a development side cover 1134, part (b) of Figure 75 shows the second inclination attitude D2 of the coupling member 180, and part (c) of Figure 75 shows the first inclination attitude D1 of the coupling member 180, in an
20 eleventh embodiment of the present invention.

[0100] Part (a) of Figure 76 shows a coupling spring 12185 and a lever 1255 mounted to a development side cover 1234, part (b) of Figure 76 shows the second inclination attitude D2 of the coupling member 180, and part (c) of Figure 76 shows the first inclination attitude D1 of the coupling member 180, in a
25 twelfth embodiment of the present invention

[DESCRIPTION OF THE EMBODIMENTS]

[0101] A cartridge and an image forming apparatus according to the present invention will be described in conjunction with the accompanying drawings. The following description will be made as to a drum cartridge and a developing cartridge which are detachably mountable to the above-described main assembly of the image forming apparatus. In the following description, a longitudinal direction of the drum cartridge or the developing cartridge is a direction of a rotational axis L1 of the photosensitive drum or a direction of a rotational axis L9 of the developing roller, respectively. The rotational axis L1 of the photosensitive drum and the rotational axis L9 of the developing roller are perpendicular to the feeding direction of the recording material. A widthwise direction of the drum cartridge or the developing cartridge is a direction substantially perpendicular to the rotational axis L1 of the photosensitive drum or a direction substantially perpendicular to the rotational axis L9 of the developing roller. In this embodiment, the direction in which the drum cartridge and the developing cartridge are mounted to and dismantled from the main assembly of the laser beam printer is a widthwise direction of the cartridges. The reference numerals in the following description is for the reference to the drawings and do not limit the structures.

[Embodiment 1]

(1) general arrangement of image forming apparatus:

[0102] Referring first to Figure 2, a general arrangement of the image forming apparatus according to an embodiment of the present invention will be described. Figure 2 is a schematic sectional side view of the image forming apparatus.

[0103] The image forming apparatus shown in Figure 2 forms a image on a recording material 2 with a developer t through an electrophotographic image forming process in accordance with image information supplied from external

equipment such as a personal computer. The image forming apparatus comprises a main assembly A1, a developing cartridge B1 and a drum cartridge C. The developing cartridge B1 and the drum cartridge C are detachably mounted to the main assembly A1 by the user. That is, these cartridges are mountable to a
5 dismountable from the main assembly A1. The recording material 2 is recording paper, label paper, an OHP sheet, textile or the like, for example. The developing cartridge B1 comprises a developing roller 13 and so on, and the drum cartridge C comprises a photosensitive drum 10 and a charging roller 11 and so on.

10 [0104] A surface of the photosensitive drum 10 is uniformly charged by the charging roller 11 supplied with a voltage from the main assembly A1. Then, a laser beam L modulated in accordance with image information is projected from an optical means 1 onto the charged photosensitive drum 10 so that an electrostatic latent image is formed on the photosensitive drum 10 in accordance
15 with the image information. The electrostatic latent image is developed with the developer t by developing means which will be described hereinafter. As a result, a developer image is formed on the surface of the photosensitive drum 10.

[0105] On the other hand, the recording material 2 accommodated in a sheet feeding tray 4 is singled out by the function of a sheet feeding roller 3a and a
20 separation pad 3b press-contacted thereto, in synchronism with the formation of the developer image. The recording material 2 is fed along a feeding guide 3d to a transfer roller 6 as transferring means. The transfer roller 6 is urged to contact the surface of the photosensitive drum 10.

[0106] Then, the recording material 2 passes through a transfer nip 6a formed
25 between the photosensitive drum 10 and the transfer roller 6. At this time, the transfer roller 6 is supplied with a voltage having a plurality opposite to that of the developer image, so that the developer image is transferred from the surface

of the photosensitive drum 10 onto the recording material 2.

[0107] The recording material 2 having the transferred developer image is fed into a fixing means 5 while being regulated by a feeding guide 3f. The fixing means 5 includes a driving roller 5a and a fixing roller 5c containing a heater 5b.

5 While the recording material 2 passing through a nip 5d between the driving roller 5a and the fixing roller 5c, the recording material 2 receives heat and pressure, by which the developer image transferred onto the recording material 2 is fixed on the recording material 2. In this manner, the image is formed on the recording material 2.

10 [0108] Thereafter, the recording material 2 is fed by a pair of discharging rollers 3g to be discharged to the discharging portion 3h.

(2) Electrophotographic image forming process:

[0109] Referring to Figure 3, an electrophotographic image forming process used in the embodiment of the present invention will be described. Figure 3 is a schematic sectional view of the developing cartridge B1 and the drum cartridge C.

[0110] As shown in Figure 3, the developing cartridge B1 includes a developing container 16 as a cartridge frame (or development side supporting frame), the developing roller 13 as the developing means, a developing blade 15 and so on. The drum cartridge C includes a drum frame 21 as a photosensitive member side supporting frame, the photosensitive drum 10, the charging roller 11 and so on.

[0111] The developer t is accommodated in a developer accommodating portion 16a of the developing container 16. A developer feeding member 17 rotatably supported by the developing container 16 rotates in a direction indicated by an arrow X17. By this, the developer t is discharged into a developing chamber 16c through the opening 16b of the developing container 16. The

developing container 16 includes a developing roller 13 containing a magnet roller 12. More specifically, the developing roller 13 includes a shaft portion 13e and a rubber portion 13d. The shaft portion 13e is made of electroconductive aluminum or the like and has an elongated cylindrical shape, and the longitudinally central portion is coated with the rubber portion 13d (Figure 6). The rubber portion 13d coats the shaft portion 13e so that the outer configuration thereof is coaxial with the shaft portion 13e. The developing roller 13 attracts the developer t onto the surface of the developing roller 13 in the developing chamber 16c by a magnetic force of the magnet roller 12. The developing blade 15 includes a supporting member 15a of metal plate and an elastic member 15b of urethane rubber and SUS plate or the like. The elastic member 15b is elastically contacted to the developing roller 13 at a predetermined contact pressure. By the developing roller 13 rotating in a rotational moving direction X5, an amount of the developer t deposited on the surface of the developing roller 13 is regulated. By this, the developer t is triboelectrically charged. That is, a developer layer is formed on the surface of the developing roller 13. The developing roller 13 supplied with the voltage from the main assembly A1 is rotated in the rotational moving direction X5 in contact with the photosensitive drum 10 to supply the developer t to the developing zone of the photosensitive drum 10.

[0112] In the case of a contact-type developing system as in this embodiment, if the developing roller 13 is always in contact with the photosensitive drum 10 (Figure 3), there is a likelihood that the rubber portion 13b of the developing roller 13 deforms. For this reason, it is preferable that the developing roller 13 is kept spaced from the photosensitive drum 10 in the non-development period.

[0113] To an outer peripheral surface of the photosensitive drum 10, a charging roller 11 rotatably supported by a frame 21 is contacted and is urged toward the

photosensitive drum 10. The charging roller 11 uniformly charges the surface of the photosensitive drum 10 by a voltage applied from the main assembly A1. The voltage applied to the charging roller 11 is selected so that a potential difference between the charging roller 11 and the surface of the photosensitive drum 10 is not less than a discharge start voltage. In this embodiment, a DC voltage of -1300V is applied as the charging bias voltage. By this, the surface of the photosensitive drum 10 is uniformly charged to the charged potential (dark portion potential) of -700V. In this embodiment, the charging roller 11 is rotated independently of the rotation of the photosensitive drum 10, as will be described in detail hereinafter. By the laser beam L emitted from the optical means 1, an electrostatic latent image is formed on the photosensitive drum 10. Thereafter, the developer t is transferred correspondingly to the electrostatic latent image on the photosensitive drum 10, by which the electrostatic latent image is visualized into a developed image on the photosensitive drum 10.

15

(3) Structure of cleaner-less system:

[0114] The cleaner-less system employed in this embodiment will be described.
[0115] In this embodiment, no cleaning member for removing, from the surface of the photosensitive drum 10, untransferred residual developer t2 remaining on the photosensitive drum 10 without being transferred is provided.

20

[0116] As shown in Figure 3, the photosensitive drum 10 is rotated in a direction indicated by an arrow C5. The untransferred residual developer t2 remaining on the surface of the photosensitive drum 10 after the image transfer step is charged to a negative polarity by the discharge of the charging roller in an upstream gap 11b, similarly to the photosensitive drum. The upstream gap 11b exists at a position upstream of a charging nip 11a where the charging roller 11 and the photosensitive drum 10 are contacted to each other, with respect to the

25

rotational direction C5 of the photosensitive drum 10. At this time, the surface of the photosensitive drum 10 is charged to -700V. The untransferred residual developer t2 charged to the negative polarity passes through the charging nip 11a without depositing on the charging roller 11 because of the potential difference relationship (-700V of the surface potential of the photosensitive drum 10, and -1300V of the potential of the charging roller 11).

[0117] The untransferred residual developer t2 having passed through the charging nip 11a reaches the laser projection position d. The amount of the untransferred residual developer t2 is not so large as to block the laser beam L supplied from the optical means. Therefore, it does not influence the formation of the electrostatic latent image on the photosensitive drum 10. The untransferred residual developer t2 which has passed through the laser projection position d and which is in a non-exposed portion (the portion of the surface of the photosensitive drum 10 not exposed to the laser projection) is collected onto the developing roller 13 by an electrostatic force in the development nip 13k which is a contact portion between the developing roller 13 and the photosensitive drum 10. On the other hand, the untransferred residual developer t2 in the exposed portion (the portion of the surface of the photosensitive drum 10 exposed to the laser projection) is not electrostatically collected and remains on the surface of the photosensitive drum 10. However, a part of such untransferred residual developer t2 is collected by a physical force due to the peripheral speed difference between the developing roller 13 and the photosensitive drum 10.

[0118] In this manner, the untransferred residual developer t2 remaining on the photosensitive drum 10 without being transferred onto the paper is mostly collected into the developing container 16. The untransferred residual developer t2 collected in the developing container 16 is mixed with the developer t existing in the developing container 16 and is reused for the development.

[0119] In this embodiment, in order to pass the untransferred residual developer t2 through the charging nip 11a without being deposited on the charging roller 11, the following two structures are employed.

[0120] The first is the provision of a light electrical discharging member 8
 5 between the transfer roller 6 and the charging roller 11. The light electrical discharging member 8 is disposed upstream of the charging nip 11a with respect to a rotational direction (arrow C5) of the photosensitive drum 10. The light electrical discharging member 8 discharges, by light, the surface potential of the of the photosensitive drum 10 after the passage through the transfer nip 6a to
 10 stably discharge in the above-described upstream gap 11b. By the light electrical discharging member 8, the potential of the photosensitive drum 10 before the charging becomes about -150V over the length of the photosensitive drum 10. In this manner, the uniform discharging can be effected in the charging operation, so that the untransferred residual developer t2 can be
 15 uniformly charged to the negative polarity.

[0121] The second is the provision of a predetermined peripheral speed difference between the charging roller 11 and the photosensitive drum 10. The reason for this is as follows. Most of the toner is charged to the negative polarity by the above-described discharge, but a small amount of the
 20 untransferred residual developer t2 is not charged to the negative polarity. Such untransferred residual developer t2 may be deposited on the charging roller 11 in the charging nip 11a. However, the provision of the predetermined peripheral speed difference between the charging roller 11 and the photosensitive drum 10, a sliding action is provided between the photosensitive drum 10 and the charging
 25 roller 11, by which the above-described untransferred residual developer t2 can be charged to the negative polarity. By this, the deposition of the untransferred residual developer t2 on the charging roller 13 can be suppressed. In this

embodiment, a charging roller gear 69 (Figure 17, the detailed description will be made hereinafter) is provided at a longitudinal one end portion of the charging roller 11, and the gear 69 is engaged with a driving side flange 24 (Figure 17, the detailed description will be made hereinafter) provided at the same longitudinal one end portion of the photosensitive drum 10. Therefore, the charging roller 11 is rotated by the rotation of the photosensitive drum 10. The peripheral speed of the surface of the charging roller 11 is 105 - 120 % relative to the peripheral speed of the surface of the photosensitive drum 10.

10 (4) Structure of developing cartridge B1:

<General arrangement of developing cartridge B1>

[0122] Referring to the drawings, the structure of the developing cartridge B1 according to an embodiment of the present invention will be described. In the following description, a side, with respect to the longitudinal direction, at which a rotational force is transmitted to the developing cartridge B1 from the main assembly A1 is called "driving side". The opposite sides is called "non-driving side". Figure 4 is a schematic perspective view of the developing cartridge B1 as seen from the driving side. Figure 5 is a schematic perspective view of the developing cartridge B1 as seen from the non-driving side. Part (a) of Figure 6 is a exploded schematic perspective view of the driving side of the developing cartridge B1 as seen from the driving side, and part (b) is a schematic perspective view thereof as seen from the non-driving side. Part (a) of Figure 7 is a exploded schematic perspective view of the non-driving side of the developing cartridge B1 as seen from the non-driving side, and part (b) is a schematic perspective view thereof as seen from the driving side.

[0123] As shown in Figures 6 and 7, the developing cartridge B1 includes a developing roller 13 as a developer carrying member and the developing blade 15

and so on. The developing blade 15 is fixed on the developing container 16 by a screw 51 and a screw 52 at the driving side end portion 15a1 and the non-driving side end portion 15a2 with respect to the longitudinal direction of the supporting member 15a. In the opposite end portions of the developing container 16, there are provided a driving side developing device bearing 36 and a non-driving side developing device bearing 46, respectively. Each of the bearings (36, 46) is a part of the container or a frame in a broad sense, except the case otherwise stated. The developing roller 13 is rotatably supported by a driving side end portion 13a engaged with a hole 36a of the driving side developing device bearing 36 and by a non-driving side end portion 13c engaged with a supporting portion 46f of the non-driving side bearing 46. In the driving side end portion 13a of the developing roller 13 (outside of the driving side developing device bearing 36 with respect to the longitudinal direction), a developing roller gear 29 is provided coaxially with the developing roller 13, and they are engaged with each other so that the developing roller 13 and the developing roller gear 29 can be integrally rotated (Figure 4).

[0124] The driving side developing device bearing 36 rotatably supports a drive input gear 27 at a position outside the developing container 16 with respect to the longitudinal direction. Drive input gear 27 is engaged with the developing roller gear 29. A coupling member 180 is provided coaxially with the drive input gear 27.

[0125] The driving side extreme end of the developing cartridge B1 is provided with a development side cover 34 as an end member. The development side cover 34 covers the drive input gear 27 and the longitudinally outside position. The coupling member 180 is projected in the longitudinal direction to the outside through the hole 34a of the development side cover 34. The coupling member 180 is engageable with a main assembly side driving member 100 provided in the

main assembly A1 to receive the rotational force. The rotational force is transmitted to a rotational force receiving portion 27d1 (Figure 8) of the drive input gear 27 and to a rotation receiving portion 27d2 (unshown) through rotational force transmitting portions 180c1, 180c2 of the coupling member 180.

5 As a result, the rotational force received by the coupling member 180 is transmitted to the developing roller 13 as a rotatable member through the drive input gear 27 and the developing roller gear 29. There is provided play between the rotational force receiving portions 27d1, 27d2 and the rotational force transmitting portions 180c1, 180c2. That is, the coupling member 180 is
10 rotatable without rotating the drive input gear 27. By the structure, the coupling member 180 is movable (rotatable, swingable or whirling) to any angle.

[0126] The driving side developing device bearing 36 is provided with a first movable member 120. The first movable member 120 includes a driving side contacting and spacing lever 70 as a first main assembly portion and a driving
15 side development urging spring 71 as a first elastic portion. The non-driving side developing device bearing 46 is provided with a second movable member 121. The second movable member 121 includes a non-driving side contacting and spacing lever 72 as a second main assembly portion and a non-driving side development urging spring 73 as a second elastic portion. The coupling
20 member 180 and the neighborhood structures thereof will be described in detail.

[0127] As shown in Figure 6, in the driving side of the developing cartridge B1, the coupling member 180, the drive input gear 27, the elastic member (coupling spring 185) as an urging member are provided. In other words, the spring 185 is an urging elastic member. The coupling member 180 is engaged with the main
25 assembly side driving member 100 provided in the main assembly A1 to receive the rotational force.

[0128] More particularly, as shown in part (b) of Figure 8, the coupling member

180 includes a free end portion 180a as a first end portion, a connection end portion (supported portion (portion-to-be-supported)) 180b as a second end portion, a guide portion 180d as a connecting portion for connecting the free end portion 180a and the connection end portion 180b. The free end portion 180a is
 5 provided with rotational force receiving portions 180a1, 180a2, and an expanding portion having a conical portion 180g as a recess. The supported portion 180b includes rotational force transmitting portions 180c1 and 180c2.

[0129] On the hand, the main assembly side driving member 100 as a main assembly side driving shaft includes a projection 100g provided at a free end
 10 portion with respect to the axis L4 and rotational force applying portions 100a1 and 100a2 projecting in a direction perpendicular to the axis L3 at a rear side of the free end.

[0130] The free end portion 180a (rotational force receiving portions 180a1, 180a2) of the coupling member 180 is projected outwardly beyond a driving side
 15 end portion 27a of the drive input gear 27 in the longitudinal direction of the developing cartridge B1. When the main assembly side driving member 100 rotates about the rotational axis L4 in a direction indicated by an arrow X6 (forward rotating direction), the rotational force applying portion 100a1 abuts to the rotational force receiving portion 180a1, and the rotational force applying
 20 portion 100a2 abuts to the rotational force receiving portion 180a2. By this, the rotational force is transmitted from the main assembly side driving member 100 to the coupling member 180.

[0131] A maximum outer diameter of at least a part the connecting portion 180d in a cross section (in a plane perpendicular to the rotational axis of the
 25 coupling portion 180) is smaller than a distance between the rotational force receiving portion 180a1 and the rotational force receiving portion 180a2. In other words, a maximum rotation radius of the at least a part of the connecting

portion 180d in the cross section is smaller than a distance between a radially inside of the rotational force receiving portion 180a1 and the rotational axis of the coupling member.

- [0132] As shown in part (b) of Figure 8 and part (e) of Figure 8, the supported portion 180b of the coupling member 180 has a substantially spherical shape. The supported portion 180b is movably (pivotably, swingably,) supported by a supporting portion 27b of an inner surface of the drive input gear 27. The rotational force transmitting portion 180c1 contacts the rotational force receiving portion 27d1 of the drive input gear 27. Similarly, the rotational force transmitting portion 180c2 contacts the rotational force receiving portion 27d2 of the drive input gear 27. By this, the drive input gear 27 is driven by the coupling member 180 receiving the driving force from the main assembly side driving member 100 as the main assembly driving shaft, so that the drive input gear 27 rotates in the forward direction X6 about the rotational axis L3.
- [0133] As shown in part (c) of Figure 8, the rotational axis L4 of the main assembly side driving member 100 and the rotational axis L3 of the drive input gear 27 are coaxial with each other. However, as shown in part (d) of Figure 8, the rotational axis L4 of the main assembly side driving member 100 and the rotational axis L3 of the drive input gear 27 may be slightly deviated parallel from the co-axis. In such a case, the rotational force can be transmitted from the main assembly side driving member 100 to the coupling member 180 with the rotational axis L2 of the coupling member 180 inclined relative to the rotational axis L3 of the drive input gear 27. Furthermore, the rotational axis L3 of the drive input gear 27 may be slightly deviated with an angle from the co-axis relative to the rotational axis L4 of the main assembly side driving member 100. In such a case, the rotational force can be transmitted from the main assembly side driving member 100 to the coupling member 180 with the rotational axis L2

of the coupling member 180 inclined relative to the rotational axis L4 of the main assembly side driving member 100.

[0134] In addition, as shown in part (a) of Figure 8, the drive input gear 27 is provided integrally with the gear portion 27c which may be a helical gear or a spur gear coaxially with the rotational axis L3 of the drive input gear 27. The gear portion 27c is engaged with the gear portion 29a of the developing roller gear 29. Because the developing roller gear 29 rotates integrally with the developing roller 13, the rotational force of the drive input gear 27 is transmitted to the developing roller 13 through the developing roller gear 29. Then, the developing roller 13 rotates in the rotational moving direction X5 about the rotational axis L9.

<Assembling of driving-side side cover and peripheral parts>

[0135] The description will be made as to the development side cover 34 and the movable member (coupling lever 55 and coupling lever spring 56) provided at the driving side end portion of the developing cartridge B1. The lever 55 is the movable member in the narrow sense, and the combination of the lever 55 and the spring 56 is the movable member in the broad sense. In other words, the spring 55 is an elastic member for movement.

[0136] Figure 9 is a schematic perspective view and a side view illustrating the assembling of the lever 55 and the spring 56 to the development side cover 34.

[0137] The lever 55 and the spring 56 are mounted to the inside of the development side cover 34 with respect to the longitudinal direction of the developing cartridge B1. The lever 55 is supported movably relative to the cover 34. A cylindrical lever positioning boss 34m of the cover 34 is engaged with a hole portion 55c of the lever 55. As a result, the lever 55 is supported so as to be rotatable relative to the cover 34 about a rotational axis L11. The spring

56 is a coil spring having one end portion engaged with the lever 55 and the other end engaged with the cover 34. More particularly, an operation arm 56a spring 56 is engaged with a spring hook portion 55b of the lever 55, and a fixed arm 56c of the spring 56 is engaged with a spring hook portion 34s of the cover 34 (part (c) of Figure 9).

[0138] To the outside of the cover 34 of the developing cartridge B1 with respect to the longitudinal direction, a coupling spring 185 is mounted (part (b) of Figure 10).

[0139] The mounting of the lever 55 and the spring 56 on the cover 34 will be described. First, the cylindrical boss 55a of the lever 55 and the cylindrical portion 56d of the spring 56 are engaged with each other (part (a) of Figure 9). At this time, the operation arm 56a of the spring 56 is engaged with the spring hook portion 55b of the lever 55. In addition, the fixed arm 56c of the spring 56 is deformed in the direction of an arrow X11 about the rotational axis L11. Then, the hole portion 55c of the lever 55 is fitted around the lever positioning boss 34m of the cover 34 (parts (a) - (b) of Figure 9). In this fitting movement, the retaining portion 55d of the lever 55 does not interfere with the portion-to-be-retained 34n of the cover 34. More particularly, as shown in part (b) of Figure 9, as seen in the longitudinal direction of the developing cartridge B1, the retaining portion 55d of the lever 55 and the portion-to-be-retained 34n of the development side cover 34 are not overlapped with each other.

[0140] In the state shown in part (b) of Figure 9, the fixed arm 56c of the spring 56 is deformed in the direction of the arrow X11, as described hereinbefore. When the fixed arm 56c of the spring 56 is released, as shown in part (b) of Figure 9, the fixed arm 56c is engaged with the spring hook portion 34s of the development side cover 34, so that the urging force provided by the deformation of the fixed arm 56c of the spring 56 is received by the spring hook portion 34s,

as shown in part (c) of Figure 9. As a result, the fixed arm 56c of the spring 56 receives a reaction force in the direction of the arrow X11 from the spring hook portion 34s of the cover 34. Furthermore, the lever 55 receives an urging force from the spring 56 at the spring hook portion 55b. Therefore, the lever 55
5 rotates about the rotational axis L11 in the direction indicated by the arrow X11, so that a rotation regulating portion 55y of the lever 55 is prevented in the rotation of the position where it abuts to a regulating surface 34y of the development side cover 34 (parts (a) - (c) of Figure 9). Thus, the assembling of the lever 55 and the spring 56 to the cover 34 is completed.

10 [0141] At this time, the retaining portion 55d of the lever 55 is overlapped with the portion-to-be-retained 34n of the cover 34, as seen in the longitudinal direction of the developing cartridge B1. Thus, the movement of the lever 55 in the longitudinal direction is limited, and only the rotation about the rotational axis X11 is permitted. Part (d) of Figure 9 is a sectional view of the retaining portion
15 55d of the coupling lever 55.

<Assembling of development side cover 34>

[0142] As shown in Figure 10, the movable member (coupling lever 55 and coupling lever spring 56) is mounted on the development side cover 34. The
20 development side cover 34 is fixed at a position outside of the driving side developing device bearing 36 with respect to the longitudinal direction of the developing cartridge B1. More particularly, a positioning portion 34r1 of the development side cover 34 and a positioned portion (portion to be positioned) 36e1 of the driving side bearing 36 are engaged with each other, and a
25 positioning portion 34r2 and a positioned portion (portion to be positioned) 36e2 are engaged with each other. By this, the position of the development side cover 34 is determined relative to the driving side developing device bearing 36.

[0143] The fixing of the development side cover 34 to the driving side developing device bearing 36 may be made by screw, adhesive material or the like, and the fixing method is not limited to a particular one.

[0144] When the development side cover 34 is assembled, the rotational force
 5 receiving portion 180a1 of the coupling member 180, the rotational force receiving portion 180a2, the portion-to-be-guided 180d and so on are exposed through the hole 34a of the development side cover 34 to the outside with respect to the longitudinal direction of the developing cartridge B1 (Figures 4 and 6). The portion-to-be-guided 180d of the coupling member 180 is contacted by a
 10 guide portion 55e, as the movable portion, of the coupling lever 55 as the movable member. As described hereinbefore, the coupling lever 55 is urged by the urging force about the rotational axis L11 in the direction of the arrow X11. By this, the coupling member 180 receives an urging force F2 from the coupling lever 55 (Figure 7).

15 [0145] In addition, the coupling spring 185 is provided on the development side cover 34. The spring 185 is a coil spring, and has one end portion contacted to the development side cover 36 and the other end portion contacted to the coupling member 180. More particularly, a positioning portion 185a of the spring 185 is supported by a spring supporting portion 34h of the development
 20 side cover 34. The fixed arm 185b of the coupling spring 185 is fixed to the spring engaging portion 34j of the development side cover 34. Furthermore, the operation arm 185c of the coupling spring 185 is contacted to the portion-to-be-guided 180d of the coupling member 180. The operation arm 185c of the coupling spring 185 applies an urging force about a rotational axis X12 of the
 25 positioning portion 185a in the direction indicated by an arrow L12. By this, the coupling member 180 receives the urging force F1b from the coupling spring 185 (Figure 10).

[0146] The coupling member 180 receiving the urging force F2 from the coupling lever 55 and the urging force F1b from the coupling spring 185 is held in the attitude (rotational axis L2) inclined relative to the rotational axis L3 of the drive input gear 27 (part (b) of Figure 10). The structure and the function of the force with which the inclination attitude of the coupling member 180 is maintained at this time will be described in <Relationship of forces applied to the coupling member 180 in second inclination attitude D2 > hereinafter.

<Basic operation of coupling member 180>

[0147] Referring to Figure 16, the basic operation of the coupling member 180 in the state of the developing cartridge B1 will be described.

[0148] Part (a) of Figure 16 is an enlarged view illustrating the relationship between the coupling member 180, the drive input gear 27 and the driving side developing device bearing 36 in the longitudinal section. Part (b) of Figure 16 is a perspective view of the driving side developing device bearing 36. Part (c) of Figure 16 is a perspective view of the drive input gear 27.

[0149] The supported portion 180b of the coupling member 180 is provided in an inside 27t of the drive input gear 27. The supported portion 180b is sandwiched between a regulating portion 27s of the drive input gear 27 and a coupling regulating portion 36s of the driving side developing device bearing 36. A diameter r180 of the supported portion 180b of the coupling member 180 has the following relationship relative to a width r27 of the regulating portion 27s of the drive input gear 27 as measured in the direction X180 and a width r36 of the coupling regulating portion 36s of the driving side developing device bearing 36 as measured in the direction X180.

The diameter r180 of the supported portion 180b > the width r27 of the regulating portion 27s of the drive input gear 27 as measured in the direction

X180.

The diameter $r180$ of the supported portion 180b > the width $r36$ of the coupling regulating portion 36s of the driving side developing device bearing 36 as measured in the direction X180.

5 With this structure, the coupling member 180 is limited in the longitudinal direction indicated by an arrow Y180 by the supported portion 180b contacting the regulating portion 27s of the drive input gear 27 or the coupling regulating portion 36s of the driving side developing device bearing 36. In the perpendicular direction indicated by an arrow X180, the coupling member 180 is
10 limited by the supported portion 180b limited in the range of the inside 27t of the drive input gear 27. That is, the coupling member 180 is limited both in the longitudinal direction Y180 and in the direction perpendicular thereto X180, but it can be inclined about the center 180s of the supported portion 180 in the direction R180.

15

<Inclination attitude of coupling member 180>

[0150] An inclining operation of the coupling member 180 will be described.

[0151] As described hereinbefore, the coupling member 180 receives the driving force from the main assembly side driving member 100 of the main
20 assembly A1 and is rotatable about the rotation axis L2. The rotational axis L2 of the coupling member 180 during the drive transmission is set so as to be coaxial with the rotational axis L3 of the drive input gear 27. It has been described that depending on the variation or the like of the part dimensions, the rotational axis L2 of the coupling member 180 is not coaxial with the rotational axis L3 of
25 the drive input gear 27, that is, they may be slightly deviated.

[0152] With the structure of this embodiment, the (rotational axis L2 of) the coupling member 180 is capable of taking a reference attitude D0, a first

inclination attitude D1 and a second inclination attitude D2.

[0153] Referring to part (a) of Figure 8 and part (a) of Figure 16, the reference attitude D0 (drive-transmittable attitude) will be described. In the reference attitude D0, the rotational axis L2 of the coupling member 180 is coaxial or
 5 parallel with the rotational axis L3 of the drive input gear 27. At this time, the developing cartridge B1 (developing roller 13) is in the main assembly A1 and is positioned at a developing position (contacting position) capable of developing a latent image on the photosensitive drum.

In this embodiment, the rotational axis L2 of the coupling member
 10 180 at the time of the reference attitude D0 taken is offset (not co-axial) relative to the rotational axis of the developing roller 13. By this, the length of the developing cartridge B1 can be shortened. However, the rotational axis L2 and the rotational axis of the developing roller 13 may be made coaxial without offset.

[0154] Referring to Figure 11, the first inclination attitude D1 (at-spaced
 15 attitude) will be described. The first inclination attitude D1 is taken in the state that the developing cartridge B1 is in the main assembly A1 and that the developing roller 13 is in a retracted position (spacing position) retracted from the photosensitive drum 10, and in this attitude, the coupling member 180 is directed in a predetermined direction. More particularly, the coupling member is
 20 directed toward the main assembly side driving member 100 as the main assembly driving shaft. That is, when the developing cartridge B1 (developing roller 13) is in the retracted position (spacing position), the free end portion 180a (rotational force receiving portions 180a1, 180a2) of the coupling member 180 is directed toward the main assembly side driving member 100 of the main
 25 assembly A1 (spaced state and contact state or the like will be described in detail hereinafter). In other words, as seen along the rotational axis of the developing roller 13, the rotational axis of the coupling member 180 is inclined substantially

toward the developing roller 13 (photosensitive drum 10) in this attitude. The rotational axis of the coupling member 180 at this time is -5° (θ_3) away in the clockwise direction (+) from a reference line connecting a pivoting center (inclination center) of the coupling member 180 and the rotational axis of the developing roller 13. In other words, the absolute value of the angle θ_3 is approx. 5° . The angle θ_3 may be any between approx. -30° and $+20^\circ$.

Therefore, the angle between the rotational axis of the coupling member 180 and the line connecting the pivoting center of the coupling member 180 and the rotational axis of the developing roller 13 is satisfactory if it is within approx. 30° .
 [0155] When the coupling member 180 takes the first inclination attitude D1 (at-spaced attitude), the angle between the rotational axis L2 of the coupling member and the rotational axis of the developing roller 13 (or the rotational axis L3 of the drive input gear 27) is preferably any within the range of approx. 20° to approx. 60° . In this embodiment, the angle is approx. 35° .

[0156] Referring to Figure 12, the second inclination attitude D2 (at-mounting attitude) will be described. The second inclination attitude D2 is taken in the process of mounting the developing cartridge B1 to the main assembly A1 along a mounting path, and in this attitude, the free end portion 180a of the coupling member 180 is directed toward the main assembly side driving member 100 (the attitude or the like in the mounting operation will be described in detail hereinafter). The rotational axis of the coupling member 180 at this time is -70° (θ_4) away in the clockwise direction (+) from a reference line connecting a pivoting center of the coupling member 180 and the rotational axis of the developing roller 13. The angle θ_4 may be any between approx. 45° and 95° .

As seen along the rotational axis of the developing roller 13, the inclining directions of the coupling member (rotational axis) in the first inclination attitude D1 (at-spaced attitude) and the second inclination attitude D2

(at-mounting attitude) are substantially crossed with each other. That is, the attitudes D1 and D2 may be substantially the same or substantially opposite directions relative to the reference D0.

More particularly, the angle formed between the first inclination attitude D1 (at-spaced attitude) and the second inclination attitude D2 (at-mounting attitude) is preferably a value in the range of approx. 20° to approx. 150°. Furthermore, the angle θ_5 may be any in the range of approx. 30° to approx. 120°. In this embodiment, the angle θ_5 is substantially 75°. In this embodiment, as seen along the rotational axis of the developing roller 13, the rotational axis of the coupling member 180 is inclined approximately to the opposite side from the developing blade 15. In other words, as seen along the rotational axis of the developing roller 13, the rotational axis L2 of the coupling member 180 is inclined in the direction substantially perpendicular to the direction toward the developing roller.

[0157] When the coupling member 180 takes the second inclination attitude D2 (at-mounting attitude), the angle between the rotational axis L2 of the coupling member and the rotational axis (or the rotational axis L3 of the drive input gear 27) of the developing roller 13 is preferably a value in the range of approx. 20° to approx. 60°. In this embodiment, the sample is approx. 35°.

[0158] An engaging relation between the coupling member 180 and the driving side developing device bearing 36 will be described. Figure 13 shows a relationship between the driving side developing device bearing 36 and the coupling member 180.

[0159] Part (a) of Figure 13 is a perspective view showing the positions of a bearing 36 and the coupling member 180. Part (b) of Figure 13 is a view of the bearing 36 as seen from a driving side. Part (c) of Figure 13 is a sectional view taken along a line KA of part (b) of Figure 13, and part (d) of Figure 13 is a

sectional view taken along a line KB Of part (b) of Figure 13.

[0160] As shown in part (a) of Figure 13, the coupling member 180 is provided with a phase regulation boss 180e as a positioned portion (projected portion) coaxial with the rotational axis L2, at a end portion opposite from the free end portion 180a. On the other hand, the bearing 36 is provided with a phase regulating portion 36kb in the form of a recess. Particularly, the phase regulating portion 36kb is provided with a first inclination regulating portion 36kb1 recessed in a direction of an arrow K1a from the center of the rotational axis L3 of the drive input gear 27, and a second inclination regulating portion 36kb2 recessed in the direction of an arrow K2a. The first inclination regulating portion 36kb1 functions as an at-spaced positioning portion for determining the position of the coupling member 180 in the at-spaced attitude. The second inclination regulating portion 36kb2 functions as an at-mounting positioning portion for determining the position of the coupling member 180 in the at-mounting attitude. The phase regulation boss 180e of the coupling member 180 as the positioned portion is disposed in the phase regulating portion 36kb of the driving side developing device bearing 36. That is, the position of the phase regulation boss 180e of the coupling member 180 is regulated by the phase regulating portion 36kb of the driving side developing device bearing 36. In other words, the phase regulation boss 180e of the coupling member 180 is movable in the phase regulating portion 36kb of the driving side developing device bearing 36, and particularly to the first inclination regulating portion 36kb1 and the second inclination regulating portion 36kb2. When the phase regulation boss 180e of the coupling member 180 is moved to the first inclination regulating portion 36kb1, the free end portion 180a (rotational force receiving portions 180a1, 180a2) of the coupling member 180 and the portion-to-be-guided 180d is inclined in the direction indicated by an arrow K1b which is opposed to

the direction of the arrow K1a. Thus, at this time, the coupling member 180 takes the first inclination attitude D1. When the phase regulation boss 180e of the coupling member 180 moved to the second inclination regulating portion 36kb2, the free end portion 180a of the coupling member 180 and the portion-to-be-guided 180d as the connecting portion are inclined in the direction of an arrow K2b which is opposed to the arrow K2a. Thus, the coupling member 180 takes the second inclination attitude D2. The angle between the arrow K1b and the arrow K2b (the angle between the first inclination regulating portion 36kb1 and the second inclination regulating portion 36kb2) is preferably approx. 30° - approx. 120°. In this embodiment, it is approx. 75°. This second inclination attitude D2 (at-mounting attitude) is substantially the same as the at-dismounting attitude with which the coupling member 180 and the main assembly side driving member 100 are disengaged from each other when the developing cartridge B1 is dismounted.

The above-described at-mounting positioning portion functions also as an at-dismounting positioning portion.

<Relationship of forces applied to the coupling member 180 in the reference attitude D0>

[0161] Referring to Figures 22 and 23, the reference attitude D0 of the coupling member 180 will be described.

[0162] Figure 23 shows the positions of the coupling lever 55 and the coupling member 180 when the mounting of the developing cartridge B1 to the main assembly A is completed. That is, this Figure shows the state in which the developing cartridge B1 has been completely inserted to the end in the main assembly A. Part (a) of Figure 23 is a side view as seen in the driving side, part (b) of Figure 23 is a side view as seen in a direction of arrow X20 of part (a) of

Figure 23, and part (c) of Figure 23 is a side view of a section taken along a line X30 of part (b) of Figure 23 as seen from the non-driving side direction.

[0163] When the mounting of the developing cartridge B1 to the main assembly A1 is completed, the coupling member 180 is engaged with the main assembly side driving member 100. At this time, the rotational axis L2 of the coupling member 180, the rotational axis L4 of the main assembly side driving member 100 and the rotational axis L3 of the development input gear 27 are coaxial with each other. In other words, the rotational force receiving portion 180a of the coupling member 180 and the rotational force applying portion 100a of the main assembly side driving member 100 are engageable with each other (Figure 8).

[0164] Referring to Figure 14, the motion of the coupling member 180 until the coupling member 180 becomes coaxial with the main assembly side driving member 100 will be described. Figure 14 is sectional views illustrating the attitudes of the coupling member until coupling member 180 becomes coaxial with the main assembly driving member 100. Part (a) of Figure 14 is a sectional view in the state that the coupling member 180 is out of contact from the main assembly driving member 100, and part (b) of Figure 14 is a sectional view at the instance when the coupling member contacts to the main assembly driving member 100. Part (c) of Figure 14 is a sectional views in the state that the coupling member 180 is coaxial with the main assembly side driving member 100.

[0165] As shown in part (a) of Figure 14, in the state that the coupling member 180 is not contacted to the main assembly driving member 100, it is inclined toward the main assembly side driving member 100 (downstream with respect to the mounting direction) about the center 180s of the supported portion 180b of the coupling member 180. With this attitude maintained, the coupling member 180 advances toward the main assembly driving member 100 in the direction of the arrow X60 (Figure 14). Then, the recessed conical portion 180g inside an

annular portion 180f and the projection 100g of the free end of the main assembly side driving member 100 are engaged to each other. When the coupling member 180 further advances in the direction of the arrow X60 (Figure 14), the inclination of the coupling member 180 decreases about the center 180s of the supported portion 180b of the coupling member 180. As a result, the rotational axis L2 of the coupling member 180, the rotational axis L4 of the main assembly side driving member 100 and the rotational axis L3 of the input gear 27 become coaxial with each other. The force applied to the coupling member 180 in this series of the motion will be described in detail hereinafter.

[0166] The state in which the rotational axis L2 of the coupling member 180 and the rotational axis L3 of the development input gear 27 are coaxial with each other represents the reference attitude D0 coupling member 180. The inclination angle θ_2 of the coupling member 180 at this time is preferably 0° , but the drive transmission is possible if the inclination angle θ_2 is within substantially 15° . At this time, the phase regulation boss 180e of the coupling member 180 separates from the second inclination regulating portion 36kb2 of the driving side developing device bearing 36 and does not contact any part of the phase regulating portion 36b of the driving side developing device bearing 36 (part (c) of Figure 23). The guide portion 55e of the coupling lever 55 as the movable portion is held in the state that it is completely retracted from the portion-to-be-guided 180d of the coupling member 180 (part (a) of Figure 23). Thus, the coupling member 180 contacts the two parts, namely the coupling spring 185 and the main assembly side driving member 100, by which the inclination angle (θ_2) is determined. In such a case, even in the case that the mounting of the developing cartridge B1 to the main assembly A1 is completed, the inclination angle (θ_2) of the coupling member 180 may not be $\theta_2=0^\circ$.

[0167] Referring to Figure 15, the inclination attitude (reference attitude D0) of

the development coupling 180 at the time when the mounting of the developing cartridge B1 to the main assembly A1 is completed will be described.

[0168] Figure 15 shows the state of engagement between the coupling member 180 and the main assembly side driving member 100. Part (a) of Figure 15 and
 5 part (b) of Figure 15 are a side view and a sectional view in the state that the rotational axis L3 of the drive input gear 27 and the rotational axis L4 of the main assembly side driving member 100 are coaxial with each other, and with the rotational axis L2 of the coupling member 180.

[0169] The portion-to-be-guided 180d of the coupling member 180 receives an
 10 urging force (part (d) of Figure 23) in the direction of an arrow F1 from the coupling spring 185. At this time, the conical portion 180g is in contact with the projection 100g at points 180g1 and 180g2. As a result, the attitude of the coupling member 180 relative to the main assembly side driving member 100 is regulated by the points 180g1 and 180g2 of the conical portion 180g. That is,
 15 the rotational axis L2 of the coupling member 180 is coaxial with the rotational axis L4 of the main assembly side driving member 100.

[0170] When the main assembly side driving member 100 of the main assembly A1 rotates in the state, the rotational force applying portion 100a of the main assembly A1 and the rotational force receiving portion 180a of the coupling
 20 member 180 are engaged to each other, so that the driving force is transmitted from the main assembly A1 to the coupling member 180 (Figure 8).

[0171] In part (c) of Figure 15, the rotational axis L3 of the drive input gear 27 and the rotational axis L4 of the main assembly side driving member 100 are coaxial with each other, but the rotational axis L2 of the coupling member 180 is
 25 inclined. Depending on the variations of the dimensions of the parts, the point 180g2 of the conical portion 180g does not contact the projection 100g of the main assembly side driving member 100, although the point 180g1 of the conical

portion 180g contacts to the projection 100g. That is, by the portion-to-be-guided 180d of the coupling member 180 receiving the urging force from the coupling spring 185 in the direction of the arrow F1, the rotational axis L2 of the coupling member 180 may incline. Therefore, in part (c) of Figure 15, the point
 5 180g1 of the conical portion 180g of the coupling member 180 contacts the projection 100g of the main assembly side driving member 100, so that the attitude of the coupling member 180 is regulated. That is, the rotational axis L2 of the coupling member 180 is inclined relative to the rotational axis L4 of the main assembly side driving member 100. In other words, the inclination angle
 10 (θ_2) of the coupling member 180 is not $\theta_2=0^\circ$.

[0172] Part (d) of Figure 15 shows the state in which the rotational axis L2 of the coupling member 180 is inclined when the rotational axis L3 of the drive input gear 27 and the rotational axis L4 of the main assembly side driving member 100 are not coaxial with each other because of the variation of the
 15 dimensions of the parts. Also in this case, the guide portion 180d of the coupling member 180 receives the coupling spring 185 as in the case shown in part (c) of Figure 15. By this, the rotational axis L2 of the coupling member 180 slightly inclines. That is, the inclination angle (θ_2) of the coupling member 180 is not $\theta_2=0^\circ$. However, similarly to the case of part (c) of Figure 15, the point
 20 180g1 of the conical portion 180g of the coupling member 180 contacts to the projection 100g of the main assembly side driving member 100, by which the attitude of the coupling member 180 is regulated.

[0173] In any case of the states shown in parts (c) and (d) of Figure 15, when the main assembly side driving member 100 of the main assembly A1 is rotated,
 25 the rotational force applying portion 100a of the main assembly A1 and the rotational force receiving portion 180a of the coupling member 180 are engaged with each other. And, the driving force is transmitted from the main assembly

A1 to the coupling member 180.

[0174] As described above, in the state that the mounting of the developing cartridge B1 to the main assembly A1 is completed, the rotational axis L2 of the coupling member 180 may be coaxial or not coaxial with the rotational axis L3 of the drive input gear 27. In any case, however, when the main assembly side driving member 100 of the main assembly A1 rotates, the rotational force applying portion 100a of the main assembly A1 is brought into engagement with the rotational force receiving portion 180a of the coupling member 180, so that the driving force is transmitted from the main assembly A1 to the coupling member 180. The attitude in which the mounting of the developing cartridge B1 to the main assembly A1 is completed such that the coupling member 180 is capable of receiving the driving force from the rotational force applying portion 100a of the main assembly A1 is called the reference attitude D0. The inclination angle is selected so that the rotational force applying portion 100a of the main assembly side driving member 100 is not disengaged from the rotational force receiving portion 180a of the coupling member 180. That is, the inclination angle θ_2 is within substantially 15° .

[0175] The first inclination attitude D1 of the coupling member 180 and the second inclination attitude D2 thereof will be described in detail.

<Relationship of the forces applied to the coupling member 180 in the first inclination attitude D1>

[0176] Referring to Figure 11, the relationship of the forces applied to the coupling member 180 in the first inclination attitude D1 will be described.

[0177] Part (a) of Figure 11 is a side view of the developing cartridge B1 in the state that the mounting of the developing cartridge B1 to the main assembly A1 is completed and the photosensitive drum 10 and the developing roller 13 are

spaced from each other.

[0178] Part (b) of Figure 11 is a sectional view showing the position of the phase regulation boss 180e of the coupling member 180 in the phase regulating portion 36kb of the driving side developing device bearing 36 as seen in the direction from the non-driving side toward the driving side of the developing cartridge B1.

[0179] Part (c) of Figure 11 is a sectional view taken at the position of the portion-to-be-guided 180d as the portion-to-be-urged of the portion-to-be-guided 180d of the coupling member 180 and as seen from the driving side in the longitudinal direction of the developing cartridge B1.

[0180] The coupling lever 55 receives an urging force for the rotation in the direction of the arrow X11 about the rotational axis L11, from the coupling lever spring 56 (Figure 10). When the developing cartridge B1 is in the mounted position in the main assembly A1, the movement in the direction of the arrow X11 is limited by an abutting portion 80y provided in the main assembly A1. More particularly, by the contact between the abutting portion 80y and the rotation regulating portion 55y of the coupling lever 55, the position of the coupling lever 55 is limited against the urging force of the coupling lever spring 56. The abutting portion 80y is integral with a driving side swing guide 80 (part (b) of Figure 21). At this time, the guide portion 55e of the coupling lever 55 is in the position retracted from the portion-to-be-guided 180d of the coupling member 180. In the first inclination attitude D1 in the embodiment, the guide portion 55e is spaced from the coupling member 180 and placed in a first movement position (retracted position). In other words, by the guide portion 55e placed in this position, the coupling member 180 is permitted to take the first inclination attitude D1 by the urging portion 185d. However, the guide portion 55e at this time may be contacted to the coupling member 180. As regards the

contact between the coupling lever 55 and the abutting portion 80y, the detailed description will be made in the description of the mounting and dismounting process of the developing cartridge B1 hereinafter.

[0181] On the other hand, to the portion-to-be-guided 180d of the coupling member 180, a guide portion 185d as the urging portion of the coupling spring 185 as the urging member contacts, and a force F1a is applied (the guide portion 185d directly urges the portion-to-be-guided 180d). Thus, the portion-to-be-guided 180d of the coupling member 180 receives a force in the direction of inclination in arrow F1a direction (part (c) of Figure 11). In other words, the coupling member 18 receives the force almost inclining toward the developing roller 13. At this time, the phase regulation boss 180e of the coupling member 180 is guided by a guide portion 36kb1a, a guide portion 36kb1b and a guide portion 36kb1c of the driving side developing device bearing 36. As a result, the boss 180e moves to the first inclination regulating portion 36kb1. That is, the phase regulation boss 180e of the coupling member 180 inclines in the direction of the arrow K1a (part (b) of Figure 11), but the free end portion 180a of the coupling member 180 and the portion-to-be-guided 180d as the connecting portion incline in the direction of the arrow K1b (part (a) of Figure 11). The position of the movable member (lever 55) or the guide portion 55e as the movable portion is called the first movement position or retracted position (the position retracted from a reference position which will be described hereinafter). The attitude of the coupling member 180 at this time is the first inclination attitude (at-spaced attitude) D1 of the coupling member 180. When the position of the movable member (lever 55) or the guide portion 55e as the movable portion in the image forming operation (part (a) of Figure 16) is called a movement reference position, the first movement position and the movement reference position are the same in this embodiment.

[0182] The inclining direction of the guide portion 185d as the urging portion of the coupling spring 185 may be perpendicular to the inclining direction of the coupling member 180 (K1b in part (a) of Figure 11). The inclining direction of the coupling member 180 (K1b in Figure 11) is in the direction of causing the phase regulation boss 180e of the coupling member 180 to abut to the first inclination regulating portion 36kb1. By doing so, the urging force of the coupling spring 185 necessary for retaining the coupling member 180 in the first inclination attitude D1 can be reduced. However, this is not necessary if the coupling member 180 can be retained in the first inclination attitude D1 by properly adjusting the urging force of the coupling spring 185, for example.

<Relationship of forces applied to coupling member 180 in the second inclination attitude D2>

[0183] Referring to Figure 12, the relationship of the forces applied to the coupling member 180 in the second inclination attitude D2 will be described.

[0184] Figure 12 shows a state before the developing cartridge B1 is mounted to the main assembly A1. Part (a) of Figure 12 is a side view of the developing cartridge B1 per se (spontaneous state). Part (b) of Figure 12 is a sectional view showing a position of the phase regulation boss 180e of the coupling member 180 in the phase regulating portion 36kb of the driving side developing device bearing 36 as seen from the non-driving side of the developing cartridge B1. Part (c) of Figure 12 is a sectional view of the portion-to-be-guided 180d of the coupling member 180 as seen from the driving side in the longitudinal direction of the developing cartridge B1. At this time, to the portion-to-be-guided 180d of the coupling member 180, the guide portion 55e of the coupling lever 55 and the guide portion 185d of the coupling spring 185 are contacted. In this state, the rotation regulating portion 55y of the coupling lever 55 is not contacted to the

abutting portion 80y (part (a) of Figure 11) of the main assembly A (part (a) of Figure 12). Therefore, the coupling lever 55 receives an urging force from the coupling lever spring 56 in the direction of rotation about the rotational axis L11 in the direction of the arrow X11. As a result, the guide portion 55e contacts the
 5 portion-to-be-guided 180d of the coupling member 180.

[0185] As described hereinbefore, the portion-to-be-guided 180d as the connecting portion of the coupling member 180 receives the force in the direction of inclination to the direction of the arrow F3. At this time, the phase regulation boss 180e of the coupling member 180 in the form of a projection is guided by a
 10 guide portion 36kb2a, guide portion 36kb2b and a guide portion 36kb2c of the driving side developing device bearing 36. As a result, the boss 180e moves to the second inclination regulating portion 36kb2. That is, the boss 180e of the coupling member 180 is inclined in the direction of the arrow K2a (part (b) of Figure 12). On the other hand, the rotational force receiving portion 180a and
 15 the portion-to-be-guided 180d of the coupling member 180 are inclined in the direction of the arrow K2b (part (a) of Figure 12). The position of the guide portion 55e as the movable member (lever 55) or the movable portion is called a second movement position (urging position or movement reference position). At this time, the guide portion 55e urges the portion-to-be-guided 180d of the
 20 coupling member 180. In other words, the guide portion 55e inclines the coupling member downwardly against an elastic force of the spring 185. The attitude of the coupling member 180 at this time is called second inclination attitude D2 of the coupling member.

25 (5) Overview of drum cartridge C:

[0186] Referring to Figure 17, the structure of the drum cartridge C will be described. Part (a) of Figure 17 is a schematic perspective view of the drum

cartridge C as seen from the non-driving side. Part (b) of Figure 17 is a schematic perspective view with the frame 21, a drum shaft reception 30 and a drum shaft 54 or the like (unshown) omitted, for the convenience of the illustration of the peripheral portions of the photosensitive drum 10 and a charging roller 11. As shown in Figure 17, the drum cartridge C includes the photosensitive drum 10, the charging roller 11 and so on. The charging roller 11 is rotatably supported by charging roller bearings 67a and 67b, and is urged to the photosensitive drum 10 by a charging roller urging members 68a and 68b.

[0187] To a driving side end portion 10a of the photosensitive drum 10, the driving side flange 24 is integrally fixed, and to a non-driving side end portion 10b of the photosensitive drum 10, a non-driving side flange 28 is integrally fixed. The driving side flange 24 and the non-driving side flange 28 are mounted coaxially with the photosensitive drum 10. In this embodiment, the driving side flange 24 and the non-driving side flange 28 are fixed to the photosensitive drum 10 by clamping, bonding or the like. To the driving side end portion of the drum frame 21, the drum bearing 30 is fixed, and to the non-driving side end portion, the drum shaft 54 is fixed, by means of screws, bonding, press-fitting or the like. The driving side flange 24 integrally fixed to the photosensitive drum 10 is rotatably supported by the drum bearing reception 30. The non-driving side flange 28 integrally fixed to the photosensitive drum 10 is rotatably supported by the drum shaft 54.

[0188] One longitudinal end portion of the charging roller 11 is provided with the charging roller gear 69, which is engaged with the gear portion 24g of the driving side flange 24. A driving side end portion 24a of the drum flange 24 is capable of receiving the rotational force from the main assembly A1 (unshown). By this, the charging roller 11 is rotated by the rotation of the photosensitive drum 10. As described hereinbefore, the peripheral speed of the surface of the

charging roller 11 is approx. 105 - 120 % relative to the peripheral speed of the surface of the photosensitive drum 10.

(6) Mounting and dismounting structure of developing cartridge B1 relative to main assembly A1:

[0189] Referring to the drawings, the mounting method of the developing cartridge B1 to the main assembly A1 will be described.

[0190] Figure 18 is a schematic perspective view of the main assembly A1 as seen from the non-driving side, and Figure 19 is a schematic perspective view of the main assembly A1 as seen from the driving side. Figure 20 is an illustration of the process of mounting the developing cartridge B1 to the main assembly A1, as seen from the driving side.

[0191] As shown in Figure 18, the non-driving side development bearing 46 is provided at the non-driving side of the developing cartridge B1. The non-driving side developing device bearing 46 is provided with a portion-to-be-guided 46d. The portion-to-be-guided 46d includes a positioning portion 46b and a rotation preventing portion 46c.

[0192] As shown in Figure 19, the non-driving side of the developing cartridge B1 is provided with a driving-side side cover 34. The driving-side side cover 34 is provided with a portion-to-be-guided 34d. The portion-to-be-guided 34d includes a positioning portion 34b and a rotation preventing portion 34c.

[0193] As shown in Figure 18, on the other hand, the driving side of the main assembly A1 is provided with a driving-side side plate 90 constituting a part of a casing of the main assembly A1. The driving-side side plate 90 is provided with the driving side guiding member 92 and the driving side swing guide 80.

[0194] The driving side swing guide 80 is movable (swingable) together with the developing cartridge B1 in the main assembly A1. The details of the driving

side swing guide 80 will be described hereinafter.

[0195] The driving side guiding member 92 includes a first guide portion 92a, a second guide portion 92b and a third guide portion 92c. The first guide portion 92a of the driving side guiding member 92 includes a mounting-and-dismounting path X1a extending along a mounting-and-dismounting path of the developing cartridge B1. The second guide portion 92b of the driving side guiding member 92 includes a groove configuration portion of a mounting-and-dismounting path X1b extending along the mounting-and-dismounting path of the developing cartridge B1. The third guide portion 92c of the driving side guiding member 92 includes a groove configuration portion of a mounting-and-dismounting path X3 extending along the mounting-and-dismounting path of the drum cartridge C.

[0196] The driving side swing guide 80 is provided with a first guide portion 80a and a second guide portion 80b. The first guide portion 80a of the driving side swing guide 80 includes a groove configuration extending along a mounting-and-dismounting path X2a of the developing cartridge B1 on an extension of the first guide portion 92a of the driving side guiding member 92. The second guide portion 80b of the driving side swing guide 80 includes a groove configuration portion extending along a mounting-and-dismounting path X2b of the developing cartridge B1 on an extension of the second guide portion 92b of the driving side guiding member 92.

[0197] As shown in Figure 19, the non-driving side of the main assembly A1 is provided with a non-driving-side side plate 91 constituting a part of the casing of the main assembly A1. The non-driving side guiding member 92 is provided with a non-driving side guiding member 93 and a non-driving side swing guide 81. The non-driving side swing guide 81 is movable (swingable) similarly to the driving side swing guide 80. The non-driving side guiding member 93 includes a first guide portion 93a and a second guide portion 93b.

[0198] The first guide portion 93a of the driving side guiding member 93 is provided with a groove configuration portion of a mounting-and-dismounting path XH1a extending along the mounting-and-dismounting path of the developing cartridge B1. The second guide portion 93b of the driving side
 5 guiding member 93 includes a groove configuration portion of a mounting-and-dismounting path XH3 extending along the mounting-and-dismounting path of the drum cartridge C. The non-driving side swing guide 81 includes a guide portion 81a. The guide portion 81a of the non-driving side swing guide 81 includes a groove configuration portion of a mounting-and-dismounting path
 10 XH2a extending along the mounting-and-dismounting path of the developing cartridge B1 on an extension of the first guide portion 93a of the non-driving side guiding member 93.

[0199] The details of the driving side swing guide 80 and the non-driving side swing guide 81 will be described hereinafter.

15

<Mounting of developing cartridge B1 to main assembly device A1>

[0200] The mounting method of the developing cartridge B1 to the main assembly A1 will be described. As shown in Figures 18 and 19, the opening and closing main assembly cover 94 provided at a top portion of the main
 20 assembly A1 is rotated in an opening direction D1, by which the inside of the main assembly A1 is exposed.

[0201] Thereafter, the portion-to-be-guided 46d (Figure 18) of the non-driving side bearing 46 of the developing cartridge B1 is brought into engagement with the first guide portion 93a (Figure 19) of the non-driving side guiding member 93
 25 of the main assembly A1. Simultaneously, the portion-to-be-guided 34d (Figure 19) of the development side cover 34 of the developing cartridge B1 is brought into engagement with the first guide portion 92a (Figure 18) of the driving side

guiding member 92 of the main assembly A1. By this, the developing cartridge B1 is inserted into the main assembly A1 along the mounting-and-dismounting path X1a and the mounting-and-dismounting path XH1a provided by the first guide portion 92a of the driving side guiding member 92 and the first guide
 5 portion 93a of the non-driving side guiding member 93.

[0202] When the developing cartridge B1 is inserted into the main assembly A1, the coupling member 180 is in the above-described second inclination attitude D2, as described hereinbefore. The coupling member 180 is inserted to the second guide portion 92b of the driving side guiding member 92, while keeping the
 10 second inclination attitude D2. More particularly, there is a gap between the coupling member 180 and the second guide portion 92b of the driving side guiding member 92, and the coupling member 180 keeps the second inclination attitude D2 in the process of the developing cartridge B1 being inserted into the main assembly A1 along the mounting-and-dismounting paths X1b, XH1b.

15 [0203] The developing cartridge B1 inserted into the main assembly A1 along the mounting-and-dismounting paths X1a, XH1a is further inserted into the main assembly A1 along the mounting-and-dismounting paths X2a, XH2a provided by the first guide portion 80a of the driving side swing guide 80 and the guide portion 81a of the non-driving side swing guide 81. In more detail, the portion-
 20 to-be-guided 34d provided on the development side cover 34 is relayed from the first guide portion 92a of the driving side guiding member 92 to the first guide portion 80a of the driving side swing guide 80, with the mounting process. Similarly, in the non-driving side, the portion-to-be-guided 46d provided on the non-driving side developing device bearing 46 is relayed from the first guide
 25 portion 93a of the non-driving side guiding member 93 to the guide portion 81a, with the mounting process.

[0204] The coupling member 180 provided on the driving side end portion of

the developing cartridge B1 is relayed from the second guide portion 92b of the driving side guiding member 92 to the second guide portion 80b of the driving side swing guide 80 while keeping the second inclination attitude D2. Similarly to the above-described, there is a gap between the coupling member 180 and the
5 second guide portion 80b of the driving side swing guide 80.

<Positioning of developing cartridge B1>

[0205] The description will be made as to the positioning of the developing cartridge B1 by the driving side swing guide 80 and the non-driving side swing
10 guide 81 inside the main assembly A1. The driving side and the non-driving side have fundamentally the same structures, and therefore, the driving side of the developing cartridge B1 will be described. Figure 20 shows the states of the developing cartridge B1 and the driving side swing guide 80 in the process of mounting the developing cartridge B1 to the main assembly A1.

15 [0206] Part (a) of Figure 20 shows the state in which the portion-to-be-guided 34d provided on the development side cover 34 is guided by the first guide portion 80a of the driving side swing guide 80, and the developing cartridge B1 is on the mounting-and-dismounting path X2a.

[0207] Part (b) of Figure 20 shows the state in which the developing cartridge
20 B1 is further advanced from the position shown in part (a) of Figure 20, and in which the positioning portion 34b of the portion-to-be-guided 34d of the development side cover 34 contacts, at a point P1, a positioning portion 82a of a driving side urging member 82 provided on the driving side swing guide 80.

[0208] Figure 21 is a schematic perspective view illustrating a driving side
25 swing guide 80 and a peripheral configuration of the driving side urging member 82. Part (a) of Figure 21 is a perspective view as seen from the driving side, and part (b) of Figure 21 is a perspective view as seen from the non-driving side.

Part (c) of Figure 21 is an exploded perspective view of the driving side swing guide 80, the driving side urging member 82 and a driving side urging spring 83. Parts (d) and (e) of Figure 21 is an enlarged detailed illustration around the driving side urging member 82.

5 [0209] As shown in parts (a) and (b) of Figure 21, the driving side urging member 82 further includes a hole portion 82b, a seat 82c and a regulating portion 82d in addition to the positioning portion 82a. As shown in part (c) of Figure 21, the hole portion 82b is engaged the with a boss portion 80c of the driving side swing guide 80 and is supported rotatably about the boss portion 80c.

10 Furthermore, to the seat 82c the, one end portion 83c of the driving side urging spring 83 which is a compression spring is contacted. As shown in part (d) of Figure 21, the other end portion 83d of the driving side urging spring 83 contacts the seat 80d of the driving side swing guide 80. By this, the driving side urging member 82 is applied by the urging force F82 in the rotational direction of an

15 arrow Ra1 about the boss portion 80c of the driving side swing guide 80. The driving side urging member 82 is limited in the rotation in the direction of the arrow Ra1 by the regulating portion 82d thereof abutting to the rotation regulating portion 80e provided on the driving side swing guide 80. As shown in part (e) of Figure 21, the driving side urging member 82 supported rotatably by

20 the driving side swing guide 80 is rotatable in the direction of an arrow Ra2 against the urging force F82 of the driving side urging spring 83. It is rotatable about the arrow Ra2 to a position where a top end portion 82e of the driving side urging member 82 does not project beyond a guide surface 80w of the driving side swing guide 80.

25

[0210] Part (c) of Figure 20 shows a state in which the developing cartridge B1 is further advanced from the position shown in part (a) of Figure 20. In this

state, the portion-to-be-guided 34d of the development side cover 34 integral with the positioning portion 34b and the rotation preventing portion 34c contacts a front side inclined surface 82w of the driving side urging member 82, so that driving side urging member 82 is pressed down in the direction indicated by an arrow Ra2. More in detail, the portion-to-be-guided 34d of the development side cover 34 contacts and the front side inclined surface 82w of the driving side urging member 82 to press the driving side urging member 82, so that the driving side urging member 82 rotates in the clockwise direction (arrow Ra2 direction) about the boss portion 80c of the driving side swing guide 80 against the urging force F82 of the driving side urging spring 83. Part (c) of Figure 20 shows the state in which the positioning portion 34b of the driving-side side cover 34 contacts the top end portion 82e of the driving side urging member 82. At this time, the regulating portion 82d of the driving side urging member 82 is spaced from the rotation regulating portion 80e of the driving side swing guide 80.

[0211] Part (d) of Figure 20 shows a state in which the developing cartridge B1 is further advanced from the position of part (c) of Figure 20, and in which the positioning portion 34b of the driving-side side cover 34 contacts a positioning portion 80f of the driving side swing guide 80. As described hereinbefore, the driving side urging member 82 receives the urging force F82 in the rotational direction of the arrow Ra1 about the boss portion 80c of the driving side swing guide 80. Therefore, a rear side inclined surface 82s of the driving side urging member 82 urges the positioning portion 34b of the driving-side side cover 34 by the urging force F4. As a result, the positioning portion 34b contacts the positioning portion 80f of the driving side swing guide 80 at the point P3 without space therebetween. By this, the driving side of the developing cartridge B1 is positioned to the driving side swing guide 80.

[0212] The positioning between the positioning portion 46d of the non-driving

side developing device bearing 46 and the non-driving side swing guide 81 is similar to the positioning in the driving side (therefore, the description will be omitted). By this, the developing cartridge B1 is positioned in place by the driving side swing guide 80 and the non-driving side swing guide 81.

5

<Operation of coupling member 180 in the mounting process of developing cartridge B1>

- [0213] Referring to Figures 22, 23 and 24, the operation of the coupling member 180 in the mounting process of the developing cartridge B1 W
- 10 illustration be described.
- [0214] In the state before mounting the developing cartridge B1 to the main assembly A1, the coupling member 180 is in the second inclination attitude D2. The developing cartridge B1 is inserted into the main assembly A1 while the coupling member 180 keeps the second inclination attitude D2. Part (a) of
- 15 Figure 22 shows the state in which the developing cartridge B1 is mounted to the main assembly A1, and it is in the mounting-and-dismounting path X2a provided by the driving side swing guide 80 and the non-driving side swing guide 81. Part (e) of Figure 22 is a view of the elements shown in part (a) of Figure 22, as seen in a direction of an arrow X50. Also when the developing cartridge B1 is
- 20 on the mounting-and-dismounting path X2a, the coupling member 180 takes the second inclination attitude D2. At this time, the rotational force receiving portion 180a of the coupling member 180 is directed toward the main assembly side driving member 100 of the main assembly A1 (mounting direction of developing cartridge B1). In other words, in this embodiment, the rotational
- 25 axis L2 of the coupling member 180 is directed substantially opposite from the developing blade 15. In other words, as the developing cartridge B1 is seen in the direction from the driving side toward the non-driving side along the

rotational axis of the developing roller 13, it will suffice if the rotational axis L2 of the coupling member 180 is within approx. 35° - approx. 125° away in the clockwise direction from a line connecting the rotational axis of the developing roller and the pivoting center of the coupling member 180. In this embodiment, the angle is approx. 80° . More specifically, the second inclination regulating portion 36kb2 of the driving side developing device bearing 36 is formed such that before the coupling member 180 contacts to the main assembly side driving member 100, the coupling member 180 inclines toward the main assembly side driving member 100 about the center 180s of the supported portion 180b (Figures 13 and 16 and Figure 12).

[0215] Part (b) of Figure 22 shows a state in which the developing cartridge B1 is inserted to the mounting-and-dismounting path X2a from the position shown in part (a) of Figure 22. Part (f) of Figure 22 is a view of the elements shown in part (b) of Figure 22, as seen in a direction of an arrow X50. At this time, the annular portion 180f of the coupling member 180 contacts the main assembly side driving member 100. From the state shown in part (a) of Figure 22 to the state shown in part (b) of Figure 22, the coupling member 180 keeps the inclination toward the main assembly side driving member 100. Therefore, the coupling member 180 can be easily engaged with the main assembly side driving shaft 100. The coupling member 180 keeps the second inclination attitude D2 by the portion-to-be-guided 180d receiving the resultant force F3 from the coupling lever 55 and the coupling spring 185 (Figure 12).

[0216] For the explanation, a angle formed between the rotational axis L3 of the drive input gear 27 and the rotational axis L2 of the coupling member 180 (inclination angle) when the coupling member 180 takes the second inclination attitude D2 is $\theta 2a$ (part (b) of Figure 22).

[0217] Part (c) of Figure 22 shows a state in which the developing cartridge B1

is inserted to the mounting-and-dismounting path X2a from the position shown in part (b) of Figure 22. Part (g) of Figure 22 is a view of the elements shown in part (c) of Figure 22, as seen in a direction of an arrow X50. Figure 24 is a sectional view showing a force relation toward the coupling member 180 at the time when the annular portion 180f of the coupling member 180 contacts to the main assembly side driving member 100.

[0218] In part (b) of Figure 22, the rotation regulating portion 55y of the coupling lever 55 contacts the abutting portion 80y of the driving side swing guide 80. From the state shown in part (b) of Figure 22 to the state shown in part (c) of Figure 22, the annular portion 180f of the coupling member 180 contacts the main assembly side driving member 100. As a result, the inclination angle of the coupling member 180 is $\theta 2b (\leq \theta 2a)$. In more detail, the coupling member 180 receives the force F100 at the contact position from the main assembly side driving member 100. When the force F100 is directed against the force F3 which is received by the coupling member 180 before, and is larger than the force F3, the inclination angle of the coupling member 180 decreases. That is, the rotational axis L2 of the coupling member 180 becomes relatively closer to a line parallel with the rotational axis L3 of the drive input gear 27. That is, the inclination angle of the coupling member 180 about the center 180s of the supported portion 180b changes toward the arrow X181, and $\theta 2b < \theta 2a$ (parts (b) of Figures 16 and 22, part (c) of Figure 22, and part (a) of Figure 24). At this time, the coupling member 180 contacts to the four parts, namely, the coupling lever 55, the coupling spring 185, the main assembly side driving member 100 and the phase regulating portion 36kb of the driving side developing device bearing 36, so that the inclination angle ($\theta 2b$) is determined.

[0219] As shown in part (b) of Figure 24, when the force received by the coupling member 180 from the main assembly side driving member 100 at the

contact portion 180f is directed against the force F3, but is smaller than the force F3, or when the force is not directed against the force F3, the inclination angle of the coupling member 180 does not change. That is, $\theta_{2b} = \theta_{2a}$, and therefore, the main assembly side driving member 100 moves in the direction of the rotational axis L4 within the range of play determined by the part dimension variation within the tolerance.

[0220] Part (d) of Figure 22 shows a state in which the developing cartridge B1 is further inserted in the direction of the mounting-and-dismounting path X2a from the position shown in part (c) of Figure 22. Part (h) of Figure 22 is a view of the elements shown in part (d) of Figure 22, as seen in a direction of an arrow X50. At this time, the rotation regulating portion 55y of the coupling lever 55 contacts the abutting portion 80y of the driving side swing guide 80. Therefore, with the insertion of the developing cartridge B1 in the direction of the mounting-and-dismounting path X2a, the coupling lever 55 rotates relatively in a direction of an arrow X11b about the rotational axis L11 in the developing cartridge B1. At this time, the guide portion 55e of the coupling lever 55 also rotates in the direction of the arrow X11b about the rotational axis L11. As a result, the inclination angle of the coupling member 180 decreases along the guide portion 55e of the coupling lever 55 as the coupling member 180 receives the urging force of the coupling spring 185 ($\theta_{2c} < \theta_{2b}$). At this time, the coupling member 180 contacts the three parts, namely the coupling spring 185, the main assembly side driving member 100 and the phase regulating portion 36kb of the driving side developing device bearing 36, so that the inclination angle (θ_{2c}) is determined.

[0221] Figure 23 shows a state in which the developing cartridge B1 is further inserted in the direction of the mounting-and-dismounting path X2a from the position shown in part (d) of Figure 22 and in which the mounting of the

developing cartridge B1 to the main assembly A1 is completed. At this time, the coupling member 180 is in engagement with the main assembly side driving member 100 and takes the reference attitude D0 (inclination angle of coupling member 180 is $\theta_2=0^\circ$).

- 5 [0222] At this time, the phase regulation boss 180e of the coupling member 180 is disengaged from the second inclination regulating portion 36b2 of the driving side developing device bearing 36, and does not contact any part of the phase regulating portion 36b of the driving side developing device bearing 36 (part (c) of Figure 23). The guide portion 55e of the coupling lever 55 is kept in the state
- 10 completely retracted from the portion-to-be-guided 180d of the coupling member 180. Thus, the coupling member 180 contacts the two parts, namely the coupling spring 185 and the main assembly side driving member 100, by which the inclination angle (θ_2) is determined (as described hereinbefore regarding the reference attitude D0 of the coupling member 180)
- 15 <operation of coupling member 180 in dismounting process of developing cartridge B1>

[0223] The description will be made as to the operation of the coupling member 180 in the dismounting process of the developing cartridge B1 from the main assembly A1.

- 20 [0224] The operation in the dismounting of the developing cartridge B1 from the main assembly device A1 is the opposite from the in the mounting process.

[0225] First, the user rotates the main assembly cover 94 of the main assembly A1 in the opening direction D1 to expose the inside of the main assembly A1, similarly to the case of the mounting (Figure 18 and 19). At this time, the

- 25 developing cartridge B1 is in the state that the developing roller 13 and the photosensitive drum 10 are in contact with each other by the driving side swing guide 80 and the non-driving side swing guide 81 (unshown).

[0226] The developing cartridge B1 is moved in the dismounting direction along the mounting and dismounting track XH2 of the driving side swing guide 80 and the non-driving side swing guide 81.

[0227] With the movement of the developing cartridge B1, the abutting portion 80y of the driving side swing guide 80 having been in contact with the rotation regulating portion 55y of the coupling lever 55 moves (from the position shown in part (d) of Figure 22 to the position shown in part (c) of Figure 22). With this operation, the coupling lever 55 rotates in the direction of the arrow X11 about the rotational axis L11. When the developing cartridge B1 is further moved, the coupling lever 55 rotates in the direction of the arrow X11, by which the guide portion 55e of the coupling lever 55 is brought into contact to the portion-to-be-guided 180d of the coupling member 180 (the state shown in part (c) of Figure 22). The coupling member 180 receiving the urging forces from the coupling lever 55 and the coupling spring 185 starts to move toward the second inclination attitude D2. Finally, the phase regulation boss 180e of the coupling member 180 is regulated by the guide portion 36kb2a, the guide portion 36kb2b and the guide portion 36kb2c of the driving side developing device bearing 36 so as to engage with the second inclination regulating portion 36kb2. The coupling member 180 is kept in the second inclination attitude D2.

[0228] Thereafter, the developing cartridge B1 is moved in the dismounting direction on the mounting and dismounting track XH1 provided by the driving side guiding member 92 and the non-driving side guiding member 93, and is taken out of the main assembly device A1.

[0229] As described in the foregoing, in this embodiment, the developing cartridge B1 is provided with a movable member (coupling lever 55 and coupling lever spring 56) in the broad sense in order to apply the urging force to the coupling member 180. By this, the coupling member 180 is capable of inclining

to the second inclination attitude D2. That is, the inclining direction of the coupling member 180 caused by the coupling lever 55 can be the direction of the mounting-and-dismounting path X2a of the developing cartridge B1.

Furthermore, the rotation of the coupling lever 55 is interrelated with the

5 mounting and dismounting operation of the developing cartridge B1 by the user.

[0230] As described in the foregoing, in this embodiment, the developing cartridge B1 is provided with the coupling lever 55 and the coupling lever spring 56 to apply the urging force to the coupling member 180. With this structure,

the coupling member 180 is capable of taking the second inclination attitude D2
10 inclined by the urging forces of the coupling lever 55 as the movable member in the narrow sense and the coupling spring 85 as the urging member, and the first inclination attitude D1 inclined only by the urging force of the coupling spring 85 as the urging member. In addition, the coupling member 180 is capable of engaging with the main assembly side driving member 100 in the mounting
15 process of the developing cartridge B1, by making the direction of inclination provided by the urging forces of the coupling lever 55 and the coupling spring 85 the same as the mounting and dismounting direction of the developing cartridge. In addition, the rotation of the coupling lever 55 is interrelated with the developing cartridge B1 mounting and dismounting operation by the user.

20

(7) Contacting and spacing lever as movable member:

[0231] Referring to part (a) of Figure 25, the driving side contacting and spacing lever 70 as the driving side movable member will be described. Part (a) of Figure 25 is a sectional view of the developing cartridge B1 as seen from the
25 driving side, illustrating the driving side contacting and spacing lever 70 and peripheral configuration thereof.

[0232] As shown in part (a) of Figure 25, driving side contacting and spacing

lever 70 comprises a first contact surface 70a, a second contact surface 70b, a third contact surface 70c, a supported portion 70d, a driving side regulating abutment 70e and a first projected portion 70f. The supported portion 70d of the driving side contacting and spacing lever 70 is rotatably supported by a

5 supporting portion 36c of the driving side developing device bearing 36. More particularly, by the engagement between the hole of the supported portion 70d of the driving side contacting and spacing lever 70 with a boss of the supporting portion 36c of the driving side developing device bearing 36, the driving side contacting and spacing lever 70 is rotatably (arrow N9 direction) supported about

10 the boss of the supporting portion 36c. In this embodiment, the supporting portion 36c of the driving side developing device bearing 36 is parallel with a rotational axis L0 of the developing roller 13. The driving side contacting and spacing lever 70 is rotatable in a plane perpendicular to the rotational axis L0 of the developing roller 13.

15 [0233] The driving side contacting and spacing lever 70 contacts one end portion 71d of the driving side development urging spring 71 as a first elastic portion which is a compression spring at a third contact surface 70c. The other end portion 71e of the driving side development urging spring 71 contacts a contact surface 36d of the driving side developing device bearing 36. As a

20 result, the driving side contacting and spacing lever 70 receives the force in the direction of an arrow N16 from the driving side development urging spring 71 at the third contact surface 70c. The urging direction of the driving side development urging spring 71 is such as to urge the first contact surface 70a of the driving side contacting and spacing lever 70 away from the developing roller

25 13 (N16). The spontaneous state of the developing cartridge B1, that is, the state before the developing cartridge B1 is mounted to the main assembly A1, the driving side regulating abutment 70e is in contact with a regulating portion 36b

provided on the driving side developing device bearing 36.

[0234] Referring to part (b) of Figure 25, the 72 as the non-driving side movable member will be described. The non-driving side and the driving side have the similar structures.

5 [0235] Part (b) of Figure 25 is a side view of the developing cartridge B1 as seen from the non-driving side. However, for the convenience of the illustration of the non-driving side contacting and spacing lever 72, some parts are omitted.

[0236] As shown in part (b) of Figure 25, the non-driving side contacting and spacing lever 72 comprises a non-driving side first contact surface 72a, a non-
 10 driving side second contact surface 72b, a non-driving side third contact surface 72c, a supported portion 72d, a non-driving side regulating abutment 72e and a non-driving side first projected portion 72f. By the supporting portion 46f of the non-driving side developing device bearing 46, the supported portion 72d of the non-driving side contacting and spacing lever 72 is supported. More
 15 particularly, by the engagement between the hole of the supported portion 72d of the non-driving side contacting and spacing lever 72 and the boss of the supporting portion 46f of the non-driving side developing device bearing 46, the non-driving side contacting and spacing lever 72 is supported rotatably about the boss of the supporting portion 46f (arrow NH9 direction). In this embodiment,
 20 the supporting portion 46f of the non-driving side developing device bearing 46 is parallel with the rotational axis L0 of the developing roller 13. That is, the non-driving side development contacting and spacing lever 72 is rotatable in a plane perpendicular to the rotational axis L0 of the developing roller 13.

[0237] The non-driving side contacting and spacing lever 72 contacts one end
 25 portion 73e of the non-driving side development urging spring 73 as the second elastic portion which is a compression spring, at the non-driving side third contact surface 72c. The other end portion 73d of the non-driving side

development urging spring 73 contacts a contact surface 46g of the non-driving side developing device bearing 46. As a result, the non-driving side contacting and spacing lever 72 receives the force FH10 in the direction of an arrow NH16 from the non-driving side development urging spring 73 at the non-driving side third contact surface 72c. The direction of the urging force provided by the non-driving side development urging spring 73 is such that the first contact surface 72a of the non-driving side contacting and spacing lever 72 is away from the developing roller 13 (arrow NH16). In the spontaneous state of the developing cartridge B1, that is, before the developing cartridge B1 is mounted to the main assembly A1, the non-driving side regulating abutment 72e is in contact with a regulating portion 46e provided on the non-driving side developing device bearing 46.

[0238] The urging force F10 of the driving side development urging spring 71 and the urging force FH10 of the non-driving side development urging spring 73 are different from each other. The driving side third contact surface 70c and the non-driving side third contact surface 72c are provided at different angles. They may be properly selected in consideration with the properties of the peripheral structures such that an urging force of the developing roller 13 to the photosensitive drum 10 is proper, as will be described hereinafter. In this embodiment, the influence of the moment M6 (part (a) of Figure 29) applied to the developing cartridge 13 when the driving force is received from the main assembly A1 to rotate the developing roller 13 is taken into consideration, and the following is satisfied: $F10 < FH10$.

That is, the urging force in the non-driving side is larger than the urging force in the driving side.

[0239] The driving side contacting and spacing lever 70 is disposed in a side opposite from the side where the photosensitive drum 10 is provided, with respect

to a line Z30 passing through the center 13z of the developing roller 13 in parallel with the mounting direction X2 (Figure 18) of the developing cartridge B1 to the main assembly A1 (lower side in this embodiment). The first projected portion 70f of the driving side contacting and spacing lever 70 is projected beyond outer configurations of the developing container 16, the driving side developing device bearing 36 and the development side cover 34 (Figure 10), as seen in the longitudinal direction. The projecting direction (arrow M2) of the first projected portion 70f crosses with a moving direction (arrows N9, N10) of the driving side contacting and spacing lever 70 and an arrow N6 direction (part (a) of Figure 29) in which the developing cartridge B1 is movable.

[0240] The first projected portion 70f has the first contact surface 70a in the side opposite from the developing roller 13 as seen from the supported portion 70d of the driving side contacting and spacing lever 70. Although the details will be described hereinafter, when the developing roller 13 is to be pressed against the photosensitive drum 10, a second contact surface 150b of the driving side device urging member 150 and the first contact surface 70a of the driving side contacting and spacing lever 70 contact to each other (part (a) of Figure 29).

[0241] The free end of the first projected portion 70f is provided with a spacing force receiving portion 70g projecting toward the developing roller 13 and crossing with the projecting direction (arrow M2) of the first projected portion 70f. The spacing force receiving portion 70g has the second contact surface 70b. Although the details will be described hereinafter, when the developing roller 13 is to be spaced from the photosensitive drum 10 (Figure 30), a first contact surface 150a of the driving side device urging member 150 and the second contact surface 70b of the driving side contacting and spacing lever 70 are contacted to each other.

[0242] Referring to part (b) of Figure 25, the configuration of the non-driving

side contacting and spacing lever 72 will be described in detail. Similarly to the above-described driving side, the non-driving side contacting and spacing lever 72 is provided in a side opposite from the side where the photosensitive drum 10 is provided, with respect to a line Z30 passing through the center 13z of the developing roller 13 and parallel with the mounting direction X2 of the developing cartridge B1 to the main assembly A1 (lower side in this embodiment). A first projected portion 72f of the non-driving side contacting and spacing lever 72 projects beyond the outer configurations of the developing container 16 and the non-driving side developing device bearing 46 as seen in the longitudinal direction. The projecting direction (arrow MH2) of the first projected portion 72f crosses with the moving direction (arrows NH9, NH10) of the non-driving side contacting and spacing lever 72 and an arrow M1 (part (a) of Figure 29) which is a moving direction of the developing cartridge B1.

[0243] The first projected portion 72f has the first contact surface 72a in a side opposite from the developing roller 13 as seen from the supported portion 72d of the non-driving side contacting and spacing lever 72. Although the details will be described hereinafter, when the developing roller 13 is pressed against the photosensitive drum 10, a second contact surface 151b of the non-driving side device urging member 151 and the first contact surface 72a of the non-driving side contacting and spacing lever 72 contact to each other (Figure 31).

[0244] The free end of the first projected portion 72f is provided with a spacing force receiving portion 72g projecting toward the developing roller 13 and crossing with the projecting direction (arrow M3) of the first projected portion 72f from the developing container 16. The spacing force receiving portion 72g has the second contact surface 72b. Although the details will be described hereinafter, when the developing roller 13 is spaced from the photosensitive drum 10 (Figure 31), a first contact surface 151a of the urging member 151 and the

second contact surface 72b of the non-driving side contacting and spacing lever 72 contact to each other.

[0245] Referring to Figure 26, the positions of the driving side contacting and spacing lever 70 and the non-driving side contacting and spacing lever 72 will be described. Figure 26 is a front view of the developing cartridge B1 as seen from the developing roller 13. In this Figure, the parts in the neighborhood of a supporting portion 36a of the driving side developing device bearing 36 supporting a driving side supported portion 13a of the developing roller 13, the supporting portion 46f of the non-driving side developing device bearing 46 supporting a non-driving side supported portion 13c of the developing roller 13 are shown in sectional view. As described in the foregoing, the driving side contacting and spacing lever 70 is provided at the driving side end portion with respect to the longitudinal direction of the developing cartridge B1. The non-driving side contacting and spacing lever 72 is provided at the non-driving side end portion with respect to the longitudinal direction of the developing cartridge B1. The driving side contacting and spacing lever 70 and the non-driving side contacting and spacing lever 72 are rotatable independently from each other (arrows N9 and N10 in part (a) of Figure 25, and arrows NH9 and NH10 in part (b) of Figure 25).

[0246] The driving side supported portion 13a of the developing roller 13 is supported by the supporting portion 36a of the driving side developing device bearing 36 at the position outside a driving side end portion L13bk of the image formation range L13b with respect to the longitudinal direction of the developing roller 13. The non-driving side supported portion 13c of the developing roller 13 is supported by the supporting portion 46f of the non-driving side developing device bearing 46 at the position outside of the non-driving side end portion L13bh of the image formation range L13b, with respect to the longitudinal

direction. The driving side contacting and spacing lever 70 and the non-driving side contacting and spacing lever 72 are at least partly overlapped with a total length L13a of the developing roller 13. Furthermore, they are provided outside the image formation range L13b of the developing roller 13.

5 [0247] In other words, the driving side contacting and spacing lever 70 and the driving side supported portion 13a of the developing roller 13 are at least partly overlapped with an area L14k sandwiched between the driving side end portion L13bk of the image forming region L13b and a driving side end portion L13ak of the total length L13a of the developing roller 13. Therefore, the driving side
10 contacting and spacing lever 70 and the driving side supported portion 13a of the developing roller 13 are placed close to each other in the longitudinal direction.

[0248] In addition, the non-driving side contacting and spacing lever 72 and the driven side supported portion 13c of the developing roller 13 at least partly overlap with an area L14h sandwiched between the non-driving side end portion
15 L13bh of the image forming region L13b and a non-driving side end portion L13ah of the total length L13a of the developing roller 13. Therefore, the non-driving side contacting and spacing lever 72 and the driving side supported portion 13c of the developing roller 13 are placed close to each other in the longitudinal direction of the developing roller 13.

20 [0249] In this embodiment, as the structure for contacting and spacing the developing roller 13, the rotatable lever (70, 72) is used, but this structure is not restricted to the present invention, if it is capable of contacting and spacing the developing roller 13, and it may be a slidable member, for example. In this embodiment, as the structure for contacting and spacing the developing roller 13,
25 the spring (71, 73) is used, but another elastic member such as rubber or the like may be used. In addition, such an elastic member may not be used, if the accuracy relative to the contact spacing mechanism of the main assembly is

assured.

(Contacting and spacing structure)

(Developing device pressing and spacing structure in the main assembly of the apparatus)

5 [0250] The developing device pressing and a spacing structure in the main assembly of the apparatus will be described.

[0251] Part (a) of Figure 27 is an exploded perspective view of the driving-side side plate 90 of the main assembly A1 as seen from the non-driving side, and part (b) of Figure 27 is a side view thereof as seen from the non-driving side. Part
10 (a) of Figure 28 is an exploded perspective view of the non-driving-side side plate 91 of the main assembly A1 as seen from the driving side, and part (b) of Figure 28 is a side view thereof as seen from the driving side.

[0252] As shown in Figure 27, the main assembly A1 includes the driving side guiding member 92 and the driving side swing guide 80 for mounting and
15 dismounting the developing cartridge B1 relative to the main assembly A1. The driving side guiding member 92 and the driving side swing guide 80 guide the driving side portion-to-be-guided 34d of the developing cartridge B1 when the developing cartridge B1 is mounted to the main assembly (Figure 19).

[0253] As shown in part (a) of Figure 27, a positioned portion (portion to be
20 positioned) 92d and a rotation regulated portion (portion to be regulated in rotation) 92e are supported by a positioning portion 90a in the form of a hole provided in the driving-side side plate 90 and a rotation regulating portion 90b, respectively. The driving side guiding member 92 is positioned and fixed relative to the driving-side side plate 90 by fixing means such as a screw
25 (unshown) or the like. In addition, the driving side swing guide 80 is supported by a cylindrical supported projection 80g engaging with a supporting portion 90c in the form of a hole provided in the driving-side side plate 90. Therefore, the

driving side swing guide 80 is supported so as to be rotatable in the direction of an arrow N5 and in the direction of an arrow N6 relative to the driving-side side plate 90.

[0254] In the foregoing description, the supporting portion 90c provided in the driving side plate 90 is in the form of the hole (recess), and correspondingly, the supported projection 80g provided on the driving side swing guide 80 is in the form of a projection, but this is not limiting to the present invention, and the projection and the recess may be interchanged.

[0255] In addition, between a projection 80h of the driving side swing guide 80 and a projection 90d of the driving-side side plate 90, there is provided driving side urging means 76 which is a tension spring. The driving side swing guide 80 is urged by the driving side urging means 76 in the direction of decreasing than the distance between the projection 80h of the driving side swing guide 80 and the projection 90d of the driving-side side plate 90 (arrow N6 direction).

[0256] In addition, the main assembly A1 includes the driving side device urging member 150 for contacting and spacing the developing roller 13 relative to the surface of the photosensitive drum 10. The driving side device urging member 150 is supported by a bottom plate (unshown) so as to be movable in directions indicated by arrow N7 and arrow N8.

[0257] On the other hand, as shown in Figure 28, the main assembly A1 includes the non-driving side guiding member 93 and the non-driving side swing guide 81 for mounting and dismounting the developing cartridge B1 relative to the main assembly A1. The non-driving side guiding member 93 and the non-driving side swing guide 81 guide the non-driving side portion-to-be-guided 46d of the developing cartridge B1 when the developing cartridge B1 is mounted into the main assembly (Figure 19).

[0258] As shown in part (a) of Figure 28, a positioned portion 93d in the form

of a boss projected from the non-driving side guiding member 93 and a rotation regulated portion 93e are supported by a positioning portion 91a in the form of a hole provided in the non-driving-side side plate 91 and a rotation regulating portion 91b, respectively. By the structure, the non-driving side guiding member 93 is supported by the non-driving-side side plate 91. The non-driving side guiding member 93 is positioned and fixed relative to the non-driving-side side plate 91 by fixing means such as a screw (unshown). Furthermore, a cylindrical supported projection 81g of the non-driving side swing guide 81 is engaged with a supporting portion 91c in the form of a hole provided in the non-driving-side side plate 91. By this, the non-driving side swing guide 81 is supported by the non-driving-side side plate 91 rotatably (arrow N5 and arrow N6).

[0259] In the foregoing description, the supporting portion 91c provided on the non-driving-side side plate 91 is in the form of a hole (recess), and the supported projection 81g provided on the non-driving side swing guide 81 is in the form of a projection. However, this recess and projection structure is not limiting, and the recess and the projection may be interchanged.

[0260] Furthermore, a non-driving side urging means 77 in the form of a tension spring is provided between a projection 81h of the non-driving side swing guide 81 and a projection 91d of the non-driving-side side plate 91. The non-driving side swing guide 81 is urged by the non-driving side urging means 77 in the direction of decreasing the distance between the projection 81h of the non-driving side swing guide 81 and the projection 91d of the non-driving side guiding member 91 (arrow N6 direction).

[0261] Similarly to the driving side, the main assembly A1 includes the non-driving side device urging member 151 for contacting and spacing the developing roller 13 relative to the surface of the photosensitive drum 10. The non-driving

side device urging member 151 is supported by the bottom plate (unshown) of the main assembly A so as to be movable in the directions indicated by the arrow N7 and the arrow N8.

5 <Developing device pressing and the spacing relative to the photosensitive drum>

[0262] The pressing and spacing of the developing roller 13 relative to the photosensitive drum 10 will be described.

10 <Pressing mechanism>

[0263] The structure of the developing roller 13 will be described.

[0264] Part (a) of Figure 29 is a side view showing in the state in which the developing roller 13 in the developing cartridge B1 supported by the driving side swing guide 80 is contacted to the photosensitive drum 10. Part (c) of Figure 29
15 is a detailed illustration of the parts around the driving side contacting and spacing lever 70 shown in part (a) of Figure 29, in which the driving side swing guide 80 and the development side cover 34 are omitted for better illustration.

[0265] In this embodiment, a so-called contact-type developing system is employed in which the developing roller 13 carrying the developer t is directly
20 contacted to the photosensitive drum 10 to develop the electrostatic latent image on the photosensitive drum 10.

[0266] The developing roller 13 includes the shaft portion 13e and the rubber portion 13d. The shaft portion 13e is made of electroconductive aluminum or the like and has an elongated cylindrical shape, and the longitudinally central
25 portion is coated with the rubber portion 13d (Figure 6). The rubber portion 13d coats the shaft portion 13e so that the outer configuration thereof is coaxial with the shaft portion 13e. In the cylinder of the shaft portion 13e, the magnet roller

12 is provided. The rubber portion 13d carries the developer t at the peripheral surface thereof, and the shaft portion 13e is supplied with a bias voltage. By contacting the rubber portion 13d carrying the developer t to the surface of the photosensitive drum 10, the electrostatic latent image is developed on the
 5 photosensitive drum 10.

[0267] A mechanism for pressing the developing roller 13 to the photosensitive drum 10 at a predetermined contact pressure will be described.

[0268] As described above, the driving side swing guide 80 is supported swingably relative to the driving-side side plate 90 in the directions of the arrow
 10 N5 and the arrow N6. The non-driving side swing guide 81 is supported swingably relative to the non-driving-side side plate 91 in the directions of the arrow N5 and the arrow N6. As described above, the developing cartridge B1 is positioned relative to the driving side swing guide 80 and the non-driving side swing guide 81. Therefore, the developing cartridge B1 is swingable in the
 15 main assembly A1 in the directions indicated by the arrow N5 and the arrow N6 (Figure 31).

[0269] In such a state, as shown in part (a) of Figure 29 and part (c) of Figure 29, the second contact surface 150b of the urging member 150 and the first contact surface 70a of the driving side contacting and spacing lever 70 contact to
 20 each other. By this, the lever 70 is rotated in the direction of the arrow N9 in part (c) of Figure 29 against the urging force of the driving side development urging spring 71. The third contact surface 70c of the lever 70 compresses a spring 71 and receives an urging force F10a from the spring 71. As a result, the lever 70 is applied by a moment M10 in a direction of an arrow N10. Because
 25 of the contact between the second contact surface 150b of the urging member 150 and the first contact surface 70a of the lever 70, the first contact surface 70a of the lever 70 receive a force F11 from the second contact surface 150b of the

driving side device urging member 150 so that a moment balancing with the moment M10 is applied to the lever 70. Therefore, the developing cartridge B1 receives the external force F11. As described hereinbefore, between the projection 80h of the driving side swing guide 80 and the projection 90d of the driving-side side plate 90, the driving side urging means 76 is provided, and a urging force is applied in a direction of an arrow N12. Therefore, to the developing cartridge B1 positioned by the driving side swing guide 80, the external force F12 in the direction of the arrow N12 is applied.

[0270] That is, the developing cartridge B1 receives the moment M6 in such a direction (arrow N5) that the developing roller 13 approaches to the photosensitive drum 10 by the force F11 imparted by the driving side development urging spring 71 and the force F12 imparted by the driving side urging means 76. By this, the elastic layer 13d of the developing roller 13 is pressed against the photosensitive drum 10 at a predetermined pressure.

[0271] Part (a) of Figure 31 is a side view showing the state in which the developing roller 13 of the developing cartridge B1 supported by the non-driving side swing guide 81 is in contact with the photosensitive drum 10. Part (c) of Figure 31 shows the details of the parts in the neighborhood of the driving side contacting and spacing lever 72 of part (a) of Figure 31, in which the non-driving side swing guide 81 and the non-driving side developing device bearing 46 are partly omitted for better illustration.

[0272] The non-driving side has the structure similar to the driving side, and as shown in part (a) of Figure 31 and part (c) of Figure 31, the developing cartridge B1 receives the external forces FH11 and FH12 by the non-driving side development urging spring 73 and the non-driving side urging means 77. By this, the developing cartridge B1 receives such a moment (M6) that the developing roller 13 approaches to the photosensitive drum 10 (arrow N6). As a

result, the elastic layer 13d of the developing roller 13 can be pressed against the photosensitive drum 10 at a predetermined pressure.

[0273] As shown to part (b) of Figure 29, the third contact surface 70c of the driving side contacting and spacing lever 70 contacted to one end portion 70d of the driving side development urging spring 71 is disposed between the supported portion 70d of the driving side contacting and spacing lever 70 and the first contact surface 70a with respect to a projecting direction M2. That is, the relationship between a distance W10 from the supported portion 70d to the third contact surface 70c and a distance W11 from the supported portion 70d to the first contact surface 70a is as follows:

$$W10 < W11.$$

Therefore, if the movement distance of the first contact surface 70a is W12, a movement distance W13 of the third contact surface 70c satisfies,

$$W13 < W12,$$

where $W13 = W12 \times (W10/W11)$.

[0274] Therefore, if there is an error in the positional accuracy of the driving side device urging member 150, the change in the compression amount of the driving side development urging spring 71 is smaller than the error of the positional accuracy of the driving side device urging member 150. As a result, the accuracy of the urging force for press-contacting the developing roller 13 to the photosensitive drum 10 can be improved. The structures in the non-driving side are similar, and therefore, similar effect can be provided.

[0275] As described hereinbefore, in the longitudinal direction, the driving side contacting and spacing lever 70 and the non-driving side contacting and spacing lever 72 are at least overlapped with the range of the total length L13a of the developing roller 13 (Figure 26). Therefore, the positional difference in the

longitudinal direction between the first contact surfaces 70a and 72a of the driving side contacting and spacing lever 70 receiving the external force F11 (part (a) of Figure 29) and the non-driving side space lever 72 receiving the external force FH11 (Figure 31) and the driving side supported portion 13a and the non-driving side supported portion 13c of the developing roller 13 can be reduced.

As a result, the moment applied to the driving side developing device bearing 36 and the non-driving side developing device bearing 46 can be suppressed.

Therefore, the developing roller 13 can be efficiently press-contacted to the photosensitive drum.

[0276] The rotational motions of the driving side contacting and spacing lever 70 and the non-driving side contacting and spacing lever 72 (arrows N9 and N10 in part (a) of Figure 29, and arrows NH9, NH10 in Figure 31) can be made independently from each other. Therefore, the position of the driving side device urging member 150 in the direction of the arrows N7, N8 and the position of the non-driving side device urging member 151 in the direction of the arrows NH7, NH8 when the developing roller 13 is press-contacted to the photosensitive drum 10 can be independently determined. Furthermore, it is unnecessary that the directions of the rotation of the driving side contacting and spacing lever 70 and the non-driving side contacting and spacing lever 72 (arrows N9, N10 in part (a) of Figure 29, and arrows NH9, NH10 in Figure 31) are the same. As a result, the magnitudes and the directions of the urging forces F11 and FH11 for urging the developing roller 13 to the photosensitive drum 10 in the driving side and the non-driving side can be properly set, respectively. In addition, even when there is a relative error between the positions of the driving side device urging member 150 and the non-driving side device urging member 151, the urging forces F11, FH11 are not influence by that. As a result, the contact pressure between the photosensitive drum 10 and the developing roller 13 can be made precise.

[0277] A position of the developing cartridge B1 with which the developing roller 13 contacts the photosensitive drum 10 and the electrostatic latent image on the photosensitive drum 10 can be developed is called developing position (contacting position). On the other hand, the position of the developing cartridge B1 with which the developing roller 13 is spaced from the photosensitive drum 10 is called retracted position (spacing position). The developing cartridge B1 is capable of selecting the developing position (contacting position) and the retracted position (spacing position), by a mechanism which will be described hereinafter.

<Spacing mechanism>

[0278] Part (a) of Figure 30 is an illustration of the state of the developing cartridge B1 when the developing roller 13 and the photosensitive drum 10 shift from the contact state to the spaced state. Part (c) of Figure 30 is a detailed illustration of the parts around the driving side contacting and spacing lever 70 shown in part (a) of Figure 30, in which the driving side swing guide 80 and the development side cover 34 are omitted for better illustration.

[0279] Part (b) of Figure 30 is an illustration of the spaced state of the developing cartridge B1, in which the photosensitive drum 10 and the developing roller 13 are spaced from each other. Part (c) of Figure 30 is a detailed illustration of the parts around the driving side contacting and spacing lever 70 shown in part (a) of Figure 30, in which the driving side swing guide 80 and the development side cover 34 are omitted for better illustration.

[0280] In the case of a contact-type developing system as in this embodiment, if the developing roller 13 is always in contact with the photosensitive drum 10 (Figure 29), there is a likelihood that the rubber portion 13b of the developing roller 13 deforms. For this reason, it is preferable that the developing roller 13

is kept spaced from the photosensitive drum 10 in the non-development period. Therefore, it is preferable that the state in which the developing roller 13 contact the photosensitive drum 10 as shown in Figure 29, and the state in which the developing roller 13 is spaced from the photosensitive drum 10 as shown in part (b) of Figure 30 can be taken.

[0281] The driving side contacting and spacing lever 70 is provided with a surface-to-be-spaced 70g projecting toward the developing roller 13. The surface-to-be-spaced 70g is engageable with the first 150a provided on a driving side device urging member 82 of the main assembly A1. The driving-side urging member 150 receives a driving force from a motor (unshown) to move in the directions of the arrow N7 and the arrow N8.

[0282] The description will be made as to the operation of shifting to the spaced state in which the developing roller 13 is spaced from the photosensitive drum 10. In the contact state between the developing roller 13 and the photosensitive drum 10 shown in Figure 29, the first 150a and the surface-to-be-spaced 70g are spaced from each other by a gap $\delta 5$.

[0283] On the other hand, part (a) of Figure 30 shows the state in which the driving-side urging member 150 has moved in the direction of the arrow N8 by a distance $\delta 6$, in which the first 70a of the driving side contacting and spacing lever 70 and the second 150b of the driving-side urging member 150 are spaced from each other. At this time, the driving side contacting and spacing lever 70 receives the urging force F10 from the driving side development urging spring 71 and rotates about the supported portion 70d in the direction of the arrow N10, so that a regulating abutment 70e of the driving side contacting and spacing lever 70 and the regulating portion 36b of the driving side bearing member 36 are contacted to each other. By this, the attitude of the driving side contacting and spacing lever 70 is determined definitely.

[0284] Part (b) of Figure 30 shows the state in which the driving-side urging member 150 has moved in the direction of the arrow N8 by a distance $\delta 7$. By the movement of the driving-side urging member 150 in the direction of the arrow N8, the surface-to-be-spaced 70g of the driving side contacting and spacing lever 70 and the first 150a of the driving-side urging member 150 contact to each other. At this time, the regulating abutment 70e of the driving side contacting and spacing lever 70 and the regulating portion 36b of the driving side bearing member 36 contact each other, and therefore, the developing cartridge B1 is moved in the direction of the arrow N8. The position of the developing cartridge B1 is determined by the driving side swing guide 80 supported swingably in the directions of the arrow N5 and the arrow N6. Therefore, by the driving-side urging member 150 moving in the direction of the arrow N8, the developing cartridge B1 is moved in the direction of the arrow N5. At this time, the developing roller 13 is spaced from the photosensitive drum 10 by a gap $\delta 8$.

[0285] The structures in the non-driving side are the same as those described above, and as shown in parts (b) and (d) of Figure 31, the non-driving-side urging member 151 is moved in the direction of the arrow N7 by a distance $\delta h7$ in the state that the non-driving side contacting and spacing lever 72 and the non-driving-side urging member 151 are in contact with each other. By this, the developing cartridge B1 rotates in the direction of the arrow N5 about the supported projection 81g of a swing guide 81. As a result, the developing roller 13 is spaced from the photosensitive drum 10 by the distance $\delta 8$.

[0286] As described above, depending on the positions of the driving-side urging member 150 and the non-driving-side urging member 151 provided in the main assembly A1, the contact state or the spaced state between the photosensitive drum 10 and the developing roller 13, that is, the developing position (contacting position) and the retracted position (spacing position) of the

developing cartridge B1 can be selected as desired.

[0287] When the position changes from the contact state between the developing roller 10 and the photosensitive drum 13 shown in part (a) of Figure 29 to the spaced state between the developing roller 10 and the photosensitive drum 13 shown in part (b) of Figure 30, the driving side swing guide 80 and the developing cartridge B1 integrally rotate. Therefore, the guide portion 55e of the coupling lever 55 is maintained in the retracted state from the portion-to-be-guided 180d of the coupling member 180 (part (b) of Figure 30).

[0288] Furthermore, in this embodiment, as shown in part (b) of Figure 30, when the developing roller 13 is spaced from the photosensitive drum 10, the portion-to-be-guided 180d of the coupling member 180 is out of contact from the lever 55 but is in contact with the guide portion 185d of the coupling spring 185. By this, the coupling member 180 receives the force F1 to take the above-described first inclination attitude D1.

15

<Movement of the coupling member in interrelation with the operation from the contact state to the spaced state>

[0289] Referring to Figure 32 and Figure 33, the description will be made as to the movement of the coupling member 180 in interrelation with the contacting operation and the spacing operation between the photosensitive drum 10 and the developing roller 13.

[0290] First, the release operation between the coupling member 180 and the main assembly side driving member 100 at the time when the developing cartridge B1 (developing roller 13) changes from the spaced state to the contact state will be described.

25

[0291] Figure 32 illustrates an engagement state between the coupling member

180 and the main assembly driving member 100 in a contacted-developing-device-state and a spaced-developing-device-state.

[0292] Figure 33 is an illustration of the engagement states of the coupling member 180 and the main assembly driving member 100 in the contacted-developing-device-state and the spaced-developing-device-state.

[0293] During the image forming operation, the driving side contacting and spacing lever 70 is urged by the urging force F11 by the driving-side urging member 150, as shown in part (a) of Figure 33. The developing roller 13 of the developing cartridge B1 is in the contacted-developing-device-state in which it is in contact with the photosensitive drum 10 at a predetermined pressure. As shown in part (a) of Figure 32, the attitude of the coupling member 180 is the reference attitude D0. At this time, the developing cartridge B1 is in the engaging position in which a rotational force receiving portion 180a of the coupling member 180 is engaged with the rotational force applying portion 100a of the main assembly side driving member 100, and the drive transmission (rotation of the motor (unshown)) from the main assembly side driving member 100 to the coupling member 180 is enabled.

[0294] In addition, the guide portion 55e of the coupling lever 55 is kept completely retracted from the portion-to-be-guided 180d of the coupling member 180 (Figure 11). This is because, as described above, the rotation regulating portion 55y of the coupling lever 55 contacts to the abutting portion 80y of the driving side swing guide 80, and therefore, the rotation in the direction of the arrow X11 about the rotational axis L11 thereof is limited (Figure 11).

[0295] Then, the description will be made as to the attitude of the coupling member 180 in the process of shifting of the developing cartridge B1 from the contacted-developing-device-state to the spaced-developing-device-state.

[0296] As shown in part (b) of Figure 33, when the image forming operation is

completed, the driving-side urging member 150 and the non-driving-side urging member 151 (unshown) move in the direction of the arrow N8. When the driving-side urging member 150 moves in the direction of the arrow N8, the driving side contacting and spacing lever 70 rotates in the direction of the arrow N10 by the urging force of the driving side development urging spring 71 (part (b) of Figure 33). When the driving-side urging member 150 in the direction indicated by the arrow N8 moves further from the state in which the contact regulating portion 70e of the driving side contacting and spacing lever 70 and the positioning portion 36b of the driving side developing device bearing 36 contact to each other, the developing cartridge B1 and the driving side swing guide 80 integrally move in the direction indicated by the arrow N5 about the supported projection 80g of the driving side swing guide 80.

[0297] The above-described description applies to the non-driving side, the this, the developing cartridge B1 and the non-driving side swing guide 81 integrally move in the direction of the arrow N5 about the supported projection 81g of the driving side swing guide 81.

[0298] By this, the spaced-developing-device-state in which the developing roller 13 is spaced from the photosensitive drum 10 is established. The developing cartridge B1 and the driving side swing guide 80 integrally move. Therefore, even in the state shown in part (b) of Figure 33, the guide portion 55e of the coupling lever 55 is kept completely retracted from the portion-to-be-guided 180d of the coupling member 180. This is because, as described above, the abutting portion 80y is integral with the driving side swing guide 80 (Figure 21). And then the hand, the coupling member 180 receives the urging force from the coupling spring 185. Therefore, as shown in part (b) of Figure 32, with the movement of the developing cartridge B1 from the contact state to the spaced state, the axis L2 of the coupling member 180 gradually inclines from the

reference attitude D0 toward the first inclination attitude D1. Then, the developing cartridge B1 further rotates in the direction indicated by the arrow N5, and the inclination movement of the coupling member 180 is completed when the state shown in part (c) of Figure 33 is established. At this time, as described

5 hereinbefore, the phase regulation boss 180e of the coupling member 180 engages with the first inclination regulating portion 36kb1 of the driving side developing device bearing 36 (Figure 11), so that the axis L2 of the coupling member 180 is kept in the first inclination attitude D1. As described in the foregoing, in the first inclination attitude D1 of the coupling member 180, the

10 rotational force receiving portion 180a of the coupling member 180 is directed toward the main assembly side driving member 100 of the main assembly A1. In other words, as seen along the rotational axis of the developing roller 13, the coupling member 180 is inclined toward the developing roller 13. In the state shown in part (c) of Figure 33, the developing cartridge B1 is in the release

15 position for disengaging the rotational force receiving portion 180a from the rotational force applying portion 100a of the main assembly driving member 100. Therefore, the force from the motor (unshown) is not transmitted from the main assembly driving member 100 to the coupling member.

[0299] In this embodiment, the state shown in part (a) of Figure 33 is the

20 attitude of the developing cartridge B1 for the image forming operation. The coupling member 180 is engaged with the main assembly driving member 100, and the driving force can be applied from the main assembly A1. As described hereinbefore, in the process of the movement of the developing cartridge B1 from the position shown in part (a) of Figure 33 than that of the position shown in part

25 (b) of Figure 33 and the position shown in part (c) of Figure 33, the coupling member 180 is disengaged from the main assembly driving member 100. In other words, when the developing cartridge B1 moves from the contact state to

the spaced state, the drive input from the main assembly A1 to the developing cartridge B1 is shut off. While the developing roller 13 of the developing cartridge B1 is spacing from the photosensitive drum 10, the main assembly driving member 100 of the main assembly A1 continues to rotate. Therefore,
5 the developing roller 13 can be spaced from the photosensitive drum 10 while rotating.

<Movement of the coupling member in interrelation with the operation from the spaced state to the contact state>

10 [0300] The description will be made as to an engaging operation between the coupling member 180 and the main assembly side driving member 100 when the developing cartridge B1 (developing roller 13) moves from the contact state to the spaced state.

[0301] The development contacting operation of the developing cartridge B1 is
15 the opposite to the above-described developing device spacing operation. In the state shown in part (b) of Figure 33, the developing cartridge B1 is in the release position in which the rotational force receiving portion 180a as the free end portion of the coupling member 180 is disengaged from the rotational force applying portion 100a of the main assembly driving member 100. In the state
20 shown in part (b) of Figure 33, the driving-side urging member 150 and the non-driving-side urging member 151 have moved in the direction indicated by the arrow N7, from the state shown in part (c) of Figure 33. By the urging force of the above-described driving side urging means 76 (Figure 32 and Figure 33), the developing cartridge B1 and the driving side swing guide 80 integrally rotate in
25 the direction of the arrow N6. The same applies to the non-driving side. By this, the developing cartridge B1 shifts from the spaced state to the contact state. Shown in part (b) of Figure 32 is the state of partway of the movement of the

developing cartridge B1 from the spaced state to the contact state. In addition, the annular portion 180f of the coupling member 180 is in contact with the main assembly side driving member 100. More particularly, the conical portion 180g as the recess provided inside the annular portion 180f of the coupling member 180 contacts the projection 100g provided at the free end of the shaft of the main assembly side driving member 100. From the state shown in part (c) of Figure 32 to the state shown in part (b) of Figure 32, the rotational axis L2 of the coupling member 180 keeps inclined toward the main assembly side driving member 100, and therefore, the coupling member 180 can easily engage with the main assembly side driving shaft 100.

[0302] When the driving-side urging member 150 and the non-driving-side urging member 151 is further moved in the direction of the arrow N7 from the state shown in part (b) of Figure 32, the engagement between the coupling member 180 and the main assembly driving member 100 is completed as shown in part (a) of Figure 32. At this time, the developing cartridge B1 is placed in the engaging position in which the rotational force receiving portions 180a1, 180a2 of the free end portion 180a of the coupling member 180 are engaged with the rotational force applying portions 100a1, 100a2 of the main assembly driving member 100, and the coupling member 180 takes the reference attitude D0. The process of the change of the attitude of the coupling member 180 from the first inclination attitude D1 to the reference attitude D0 is similar to the process of the change of the attitude of the coupling member 180 from the second inclination attitude D2 to the reference attitude D0 at the time when the developing cartridge B1 is mounted to the main assembly A1 (Figure 22).

[0303] In this embodiment, before the state shown in part (b) of Figure 33 at which the engagement between the coupling member 180 and the main assembly driving member 100 starts, the main assembly driving member 100 is started to

rotate by a driving signal of the main assembly A1. By this, in midstream of the movement of the developing cartridge B1 from the state shown in part (c) of Figure 33 to the state shown in part (b) of Figure 33 and part (a) of Figure 33, the coupling member 180 engages with the main assembly driving member 100 to receive the driving force. In other words, partway of the movement of the developing cartridge B1 from the spaced state to the contact state, the driving force is applied to the developing cartridge B1 from the main assembly A1. Before the contact of the developing roller 13 and the photosensitive drum 10 contact to each other, the main assembly driving member 100 of the main assembly A1 has already rotated. As a result, the developing roller 13 which already rotates can be brought into contact to the photosensitive drum 10.

[0304] If only one motor is provided in the main assembly A1, it is necessary for the drive transmission mechanism to be provided with a clutch mechanism for selectively disconnecting the drive transmission for transmitting the rotational force to the developing roller 13 from the motor, in order to disconnect the transmission of the rotational force to the developing roller 13 while transmitting the rotational force to the photosensitive drum 10. However, according to this embodiment, the engagement and the disengagement between the coupling member 180 and the main assembly side driving member 100 are established in the process of the movement of the developing cartridge B1 from the contact state to the spaced state and in the process of the movement from the spaced state to the contact state. For this reason, it is unnecessary to provide a clutch mechanism in the main assembly A1 or the developing cartridge B1, and therefore, the low cost and space saving are accomplished in the developing cartridge B1 and the main assembly A1.

[0305] According to this embodiment, even in the case that the mounting and dismounting directions relative to the main assembly A1 of the

electrophotographic image forming apparatus are different from the development space/space directions, the coupling member is engageable both in the mounting of the developing cartridge B1 and in the contacting operation of the developer carrying member to the photosensitive member in the main assembly A1. Or, 5 the switching of the inclination attitude of the coupling member 180 is interrelated with the mounting and dismounting operation by the user, by which the usability property upon the mounting and dismounting of the developing cartridge B1 is not affected. With such structures, the latitude in the design of the electrophotographic image forming apparatus A1 can be improved, and the 10 structure of the electrophotographic image forming apparatus can be simplified, downsizing and cost-reduced.

[Embodiment 2]

[0306] In Embodiment 1, the developing cartridge B901 and the drum cartridge 15 C901 are respective members, but such a structure is not restrictive to the present invention. For example, the present invention is applicable to a process cartridge P integrally including the developing cartridge B901 and the drum cartridge C901.

[0307] Referring to Figures 34, 35, 36, 37, 38, 39, 40, 41 and 42, the 20 embodiment of the present invention using a process cartridge will be described. With respect to this embodiment, the description will be made as to the structures different from those of the foregoing embodiment, and the detailed description is omitted by using the similar names of parts as in the foregoing embodiment in the case that they have the similar structures and functions. More particularly, in 25 Embodiment 1, the coupling lever 955 and the coupling lever spring 956 are provided on the driving-side side cover 34, but in Embodiment 2, they are provided on the driving side drum bearing 930. In addition, the coupling spring

985 is provided on the driving side developing device bearing 936 similarly to Embodiment 1.

[0308] The details will be described.

[0309] Figure 34 shows the coupling lever 955 and the coupling lever spring 956 provided on the driving side drum bearing 930.

[0310] Figure 35 is a perspective view illustrating assembling of the developing cartridge B901 and the drum cartridge C901 integrally with each other into a process cartridge P.

[0311] Figure 36 is a view illustrating a swing motion of the developing cartridge B901 relative to the drum cartridge C901, as seen from the driving side.

[0312] Figure 37 illustrates attitudes of the coupling lever 955 and the coupling member 980 in the process cartridge P.

[0313] As regards in the developing cartridge B901, the drum cartridge C901 and the electrophotographic image forming process operations are the same as with Embodiment 1, and therefore, the description thereof is omitted.

<Assembling of coupling lever 955 and coupling lever spring 956 on driving side drum bearing 930>

[0314] First, the description will be made as to the structures of the driving side drum bearing 930, the coupling lever 955 and the coupling lever spring 956 provided on the driving side end portion of the drum frame 921.

[0315] As shown in Figure 34, the coupling lever 955 and the coupling lever spring 956 are provided on the inside of the driving side drum bearing 930 with respect to the longitudinal direction of the process cartridge P. More particularly, a lever positioning boss 930m of the driving side drum bearing 930 is engaged with a hole portion 955c of the coupling lever 955, so that the coupling lever 955 is supported by the driving side drum bearing 930 rotatably

about a rotational axis L911. The coupling lever spring 956 is a twisted coil spring and has one end engaged with the coupling lever 955 and the other end engaged with the driving side drum bearing 930. More particularly, an operation arm 956a of the spring 956 is engaged with a spring hook portion 955b of the lever 955. A fixed arm 956c of the spring 956 is engaged with a spring hook portion 930s of the driving side drum bearing 930 (part (c) of Figure 34). [0316] The assembling of the lever 955 and the spring 956 to the driving side drum bearing 930 will be described. First, a positioning portion 956d of the spring 956 is placed coaxially with a cylindrical boss 955a of the lever 955 (part (a) of Figure 34). At this time, the operation arm 956a of the spring 956 is engaged with the spring hook portion 955b of the lever 955. In addition, the fixed arm 956c of the spring 956 is deformed in the direction of an arrow X911 about the rotational axis L911. Then, the hole portion 955c of the lever 955 is fitted around the lever positioning boss 930m of the driving side drum bearing 930 (parts (a) and (b) of Figure 34). In the fitting, a retaining portion 955d of the lever 955 and a portion-to-be-retained 930n of the driving side drum bearing 930 are not interfered with each other by the positions thereof. More particularly, as shown in part (b) of Figure 34, as seen in the longitudinal direction, the retaining portion 955d of the lever 955 and the portion-to-be-retained 930n of the driving side drum bearing 930 are not overlapped with each other.

[0317] In the state shown in part (b) of Figure 34, as described hereinbefore, the fixed arm 956c of the spring 956 is deformed in the direction of the arrow X911. From the state shown in part (b) of Figure 34, the deformation of the fixed arm 956c of the spring 956 is released by which the fixed arm 956c is engaged with the spring hook portion 930s of the driving side drum bearing 930, as shown in part (c) of Figure 34 (parts (c) and (d) of Figure 34) By the foregoing, the

assembling of the lever 955 and the spring 956 to the driving side drum bearing 930 is completed.

[0318] At this time, the retaining portion 955d of the lever 955 is overlapped with the portion-to-be-retained 930n of the driving side drum bearing 930 as seen
5 in the longitudinal direction of the process cartridge P. That is, the lever 955 is prevented in the movement in the longitudinal direction but is permitted in the rotation about the rotational axis X911.

<Unification of the developing cartridge B901 and the drum cartridge C901>

10 [0319] The description will be made as to the unification of the developing cartridge B901 and the drum cartridge C901 into the process cartridge P.

[0320] As shown in Figure 35, the drum cartridge C901 is provided with the photosensitive drum 910, the charging roller 911 and so on, the structures thereof and the supporting structures therefor are the same as with Embodiment 1, and
15 therefore, the description is omitted.

[0321] The driving side end portion of the frame 921 is provided with the driving side drum bearing 930, and the non-driving side end portion thereof is provided with the non-driving side drum bearing 931, these bearings are fixed by a screw, bonding, press-fitting or the like. A supported portion 992f of a driving
20 side flange 992 integrally fixed to the photosensitive drum 910 is supported rotatably by a hole portion 930a of the driving side drum bearing 930, and a supported portion 928f (unshown) of a non-driving side flange 928 is supported by the drum shaft 954 rotatably coaxially with a hole portion 931a of the non-driving side drum bearing 931.

25 [0322] In the developing cartridge B901, a boss 936r provided on the driving side developing device bearing 936 is rotatably supported by a hole 930r provided in the driving side drum bearing 930. In addition, a boss 946r

provided on the non-driving side developing device bearing 946 is rotatably supported by the hole 931r provided in the non-driving side drum bearing 931. By such structures, the developing cartridge B901 is swingable relative to the drum cartridge C901 about the boss 936r of the driving side developing device bearing 936 and the boss 946r of the non-driving side developing device bearing 946 (Figure 36). The developing cartridge B901 in the spontaneous state is always urged to the drum cartridge C901 by an urging member (twisted coil spring, for example) so that the developing roller 913 is urged in the direction of contacting to or being close to the photosensitive drum 910 (unshown). The method for urging the developing cartridge B901 may be such that a spring is provided between the drum cartridge C901 and the developing cartridge B901 or such that the weight of the developing cartridge B901 per se is utilized, but the method is not limited to a particular method.

[0323] On the other hand, in the state of the process cartridge P, a guide portion 955e of the coupling lever 955 is contacted to a portion-to-be-guided 980d of the coupling member 980 by the urging force of the coupling lever spring 956.

With such a structure, in the process cartridge P, similarly to Embodiment 1, the position of the coupling member 980 is determined by contacting to three members, namely, the coupling lever 955, the coupling spring 985 and the phase regulating portion 936kb of the driving side developing device bearing 936 (part (c) and (d) of Figure 37).

[0324] Similarly to Embodiment 1, the attitude of the coupling member 980 is capable of taking three attitudes also in this embodiment.

[0325] In other words, in a reference attitude D900 (drive-transmittable attitude), the rotational axis L2 of the coupling member 980 is coaxial with or in parallel with a rotational axis L3 of the drive input gear 27.

[0326] In a first inclination attitude D901 (at-spaced attitude), the developing

roller 13 is spaced from the photosensitive drum 10 (retracted position (spacing position)) in the state that the process cartridge P is in the main assembly A1, in which the coupling member 180 is directed toward the main assembly side driving member 100 as the main assembly driving shaft (part (a) of Figure 37)

5 [0327] In a second inclination attitude D902 (at-mounting attitude), the rotational force receiving portion 980a and the supported portion 980b of the coupling member 980 are directed toward the main assembly side driving member 100 of the main assembly A91 (part (c) of Figure 37), when the process cartridge P is mounted to the main assembly A91.

10 [0328] The structures and the forces applied to the parts at the time when the coupling member 980 takes the inclination attitudes are the same as with Embodiment 1. Therefore, the detailed description is omitted.

(6) Mounting and dismounting structure of the process cartridge P relative to the
15 main assembly A91:

[0329] Referring to Figure 38, the mounting method of the process cartridge P to the main assembly A91 will be described.

[0330] Figure 38 is a schematic perspective view of the main assembly A91 as seen from the non-driving side, and Figure 39 is a schematic perspective view of
20 the main assembly A91 as seen from the driving side. Figure 40 is an illustration of the process cartridge P when it is being mounted to the main assembly A91. Figure 41 is an illustration of the process cartridge P when the mounting to the main assembly A91 is completed.

[0331] As shown in Figure 38, a non-driving side bearing 931 is provided in the
25 non-driving side of the process cartridge P. The non-driving side drum bearing 931 is provided with a portion-to-be-guided 931d. The portion-to-be-guided 931d includes a positioning portion 931b and a rotation preventing portion 931c.

[0332] As shown in Figure 39 a driving-side drum bearing 930 is provided with a portion-to-be-guided 930d. The portion-to-be-guided 930d includes a positioning portion 930b and a rotation preventing portion 930c.

[0333] On the other hand, as shown in Figures 38 and 39, in the driving side of the main assembly A91, there is provided a driving-side side plate 990 constituting a part of the casing. The driving-side side plate 990 is provided with a driving side guiding member 992. A non-driving-side side plate 991 is provided with a non-driving side guiding member 993. The driving side guiding member 992 includes a guide portion 992c, and the non-driving side guiding member 993 includes a guide portion 993c. The guide portion 992c of the driving side guiding member 992 and the guide portion 993c of the non-driving side guiding member 993 are provided with grooves extending along a mounting-and-dismounting path X903 of the process cartridge P. The driving side guiding member 992 further includes an abutting portion 992y having a function similar to that of the abutting portion 80y of the driving side swing guide 80 in Embodiment 1.

<Mounting of the process cartridge P to the main assembly device A1>

[0334] The mounting method of the process cartridge P to the main assembly A91 will be described. As shown in Figures 38 and 39, an opening and closing main assembly cover 941 provided at an upper portion of the main assembly A91 is rotated in an opening direction D91. By this, the inside of the main assembly A91 is exposed.

[0335] The non-driving side drum bearing 931 is provided in the non-driving side of the process cartridge P. The portion-to-be-guided 931d of the non-driving side drum bearing 931 (Figures 36, 38) is engaged with the guide portion 993c (Figures 36, 39) of the non-driving side guiding member 993 of the main

assembly A91, and the portion-to-be-guided 930d (Figure 39) of the driving side drum bearing 930 of the process cartridge P is engaged with the guide portion 992c (Figure 38) of the driving side guiding member 992 of the main assembly A91. By this, the process cartridge P is inserted into the main assembly A91

5 along a mounting-and-dismounting path X903 provided by the guide portion 992c on the driving side guiding member 992 and the guide portion 993c of the non-driving side guiding member 993. When the process cartridge P is mounted to the main assembly A91, the coupling member 980 is inserted into the main assembly A91 while keeping the second inclination attitude D902, similarly to

10 Embodiments 1. The positioning structure of the process cartridge P relative to the main assembly A91 is fundamentally similar to that of Embodiment 1.

[0336] The detailed descriptions as to the positioning step is omitted because it is similar to that of Embodiment 1, but it is pointed that the positioning portion 930b of the driving side drum bearing 930 receives the urging force from the

15 driving side urging member 982. By this, the positioning portion 930b contacts to a positioning portion 992f of the driving side guiding member 992 (Figure 41). A drive urging member 982 of this embodiment has the structure similar to that of the driving side urging member 82 of Embodiment 1, and the function thereof is similar, too, and therefore, the detailed description is omitted.

20 [0337] In the non-driving side, similarly to the driving side, the non-driving side of the process cartridge P is positioned to the driven side guiding member 993. By this, the driving side drum bearing 930 of the process cartridge P is positioned to the driving side guiding member 992, and the non-driving side drum bearing 931 is positioned to the non-driving side guiding member 993

25 (Figure 41).

<Operation of coupling member 980 in mounting process of process cartridge P>

[0338] The operation of the coupling member 980 in the mounting process of the process cartridge P will be described.

[0339] The operation of the coupling member 980 in the mounting process of the process cartridge P is similar to that of Embodiment 1. Therefore, the
 5 detailed description is omitted, but the brief description will be made.

[0340] In the second inclination attitude D902 of the coupling member 980, the rotational force receiving portion 980a of the coupling member 980 is directed toward the main assembly side driving member 100 of the main assembly A91 (downstream in the mounting direction) (Figure 40) when the process cartridge P
 10 is on the mounting-and-dismounting path X903.

[0341] In the mounting process of the process cartridge P, the coupling member 980 keeps the second inclination attitude D2 by the urging force applied from the coupling lever 956 and the coupling spring 985. When the process cartridge P is inserted in the mounting direction X903 beyond the contact timing between the
 15 annular portion 980f of the coupling member 980 and the main assembly side driving member 100 described in Embodiment 1, the rotation regulating portion 955y of the coupling lever 955 is brought into contact to the abutting portion 992y of the driving side guiding member 992. When the process cartridge P is further inserted in the mounting direction X903, the coupling lever 955 rotates in
 20 a direction of an arrow X912 about the rotation axis X911, so that the guide portion 955e is completely retracted from the portion-to-be-guided 980d of the coupling member 980, similarly to Embodiments 1 (Figures 34 and 40). Then, the coupling member 980 is engaged with the main assembly side driving member 100 and becomes coaxial with a rotational axis of the development input gear 27. In other words, the rotational force receiving portion 980a of the
 25 coupling member 980 and the rotational force applying portion 100a of the main assembly side driving member 100 are engageable with each other. The attitude

of the coupling member 980 at this time is the reference attitude D900. At this time, a phase regulation boss 980e of the coupling member 980 is disengaged from the second inclination regulating portion 936kb2 of the driving side developing device bearing 936, and does not contact any part of the phase regulating portion 936b of the driving side developing device bearing 936 (part (c) of Figure 23 in Embodiment 1).

<Operation of coupling member 980 in the dismounting process of process cartridge P>

[0342] The operation of the coupling member 980 in the dismounting process of the process cartridge P from the main assembly A91 will be described.

[0343] The operation in the dismounting of the process cartridge P from the main assembly device A1 is opposite the above-described mounting process, and the structures are similar to those of Embodiment 1, and therefore, only brief description will be made.

[0344] First, the user rotates the main assembly cover 94 of the main assembly A91 in the opening direction D91 (Figures 38 and 39) to expose the inside of the main assembly A91, similarly to the case of the mounting. At this time, the process cartridge P is maintained in the contact attitude in which the developing roller 13 contacts the photosensitive drum 10 by a structure (unshown).

[0345] The process cartridge P is moved in the dismounting direction along the mounting and dismounting track X903 provided by the driving side guiding member 992 and the non-driving side guiding member 993.

[0346] With the movement of the process cartridge P, the abutting portion 992y of the driving side guiding member 992 contacting the rotation regulating portion 955y of the coupling lever 955 is moved. With this operation, the coupling lever 955 rotates in the direction of the arrow X911 about the rotational axis

X911, so that the guide portion 955e of the coupling lever 955 contacts to the portion-to-be-guided 980d of the coupling member 980. Finally, the phase regulation boss 980e of the coupling member 980 is regulated by the guide portion 936kb2a, the guide portion 936kb2b and the guide portion 936kb2c of the driving side developing device bearing 936 so as to engage with the second inclination regulating portion 936kb2. The coupling member 980 is kept in the second inclination attitude D902.

[0347] Thereafter, the process cartridge P is moved along the X903 until it is taken out of the main assembly device A1.

[0348] As described in the foregoing, in the process cartridge of this embodiment, coupling member 980 can be inclined to the second inclination attitude D902, similarly to Embodiments 1. The effects of Embodiment 1 can also be provided.

<Movement of coupling member in interrelation with the contacting and spacing operation>

[0349] The description will be made as to the movement of the coupling member in interrelation with the development pressing and developing device spacing operations of the developing cartridge B901 relative to the photosensitive drum 10. The development pressing and developing device spacing structures and the development pressing and development spacing mechanisms of the developing roller 13 relative to the photosensitive drum in this embodiment are similar to those of Embodiment 1. Therefore, the description thereof is omitted.

[0350] Figure 42 is a view as seen from the driving side in the development pressing and spacing developing-device-state of the developing cartridge B901 of the process cartridge P relative to the photosensitive drum 10.

[0351] When the contact state between the developing roller 10 and the

photosensitive drum 13 shown in part (a) of Figure 42 changes to the spaced state between the developing roller 10 and the photosensitive drum 13 shown in part (b) of Figure 42, the developing cartridge B901 swings about a boss 930r of the driving side developing device bearing 930 and a boss 946r of the non-driving side developing device bearing 946. At this time, the direction of the spacing operation of the developing cartridge B901 is such that it is away from the guide portion 955e and the coupling lever 955. As described hereinbefore, the driving side drum bearing 930 is positioned in the fixed relative to the driving side guiding member 992. For this reason, in the contacting and spacing operations, the coupling lever 955 maintains the state at the time of completion of the mounting. That is, the contacting and spacing operations of the developing cartridge B901 are carried out while the guide portion 955e of the coupling lever 95 is kept retracted from the coupling member 980.

[0352] When the developing roller 13 is spaced from the photosensitive drum 10 as shown in part (b) of Figure 42, the portion-to-be-guided 980d of the coupling member 980 and the guide portion 185d of the coupling spring 185 are contacted to each other, similarly to Embodiment 1. By this, the coupling member 980 takes the first inclination attitude D901.

[0353] Therefore, also with the structure of this embodiment, the movement of the coupling member 980 in the contacting and spacing operations permits the engagement and disengagement relative to the main assembly side driving member 100 in this embodiment, similarly to Embodiment 1. Therefore, the detailed description is omitted.

[0354] As described in the foregoing, the coupling member is engageable both at the time of the mounting of the process cartridge P and at the time of the movement of the developing roller 13 from the retracted position (spacing position) to the developing position (contacting position) in the main assembly

A91. In addition, the switching of the inclination attitude of the coupling member 980 is interrelated with the mounting and dismounting operation by the user, and therefore, the usability property upon the mounting and dismounting of the process cartridge P is not adversely affected. Furthermore, the latitude in the design of the electrophotographic image forming apparatus A1 is enhanced, and the structure of the electrophotographic image forming apparatus can be simplified, downsized and cost-reduced.

[Embodiment 3]

[0355] In this embodiment, the structure by which the coupling member 180 takes the reference attitude D0, the first inclination attitude D1 (at-spaced attitude) or the second inclination attitude D2 (at-mounting attitude) is different from that of Embodiment 1, as will be described in conjunction with Figure 43 to Figure 47. More particularly, the structures of the development side cover 34, the coupling lever 55, the coupling lever spring 56, the coupling spring 185 and the members concerned with them are different from those of Embodiment 1, as will be described. As regards the other structures of Embodiment 1, they are employed also in this embodiment, and therefore, the detailed description thereof is omitted.

[0356] Figure 43 is a schematic perspective view of a state of a coupling spring 3185 as the urging member (or elastic member), a coupling lever 355 as the movable member (or urging member) and a coupling lever spring 356 as the urging member (or elastic member) for applying an urging force to a lever 355 before being mounted to a development side cover 334. In other words, it is an exploded schematic perspective view of the driving side extreme end of the developing cartridge B1 in this embodiment as seen from the driving side. The movable member in a broad sense includes the lever 355 and the lever spring 356,

similarly to Embodiment 1.

[0357] The side cover 334 includes a projection 334s as a spring mounting portion for mounting one end of the lever spring 356. The side cover 334 also includes a projection 334h as a spring mounting portion for mounting a part of the coupling spring 3185. The side cover 334 includes a supporting portion 334m for movably (rotatably) supporting a supported portion 355c of the lever 355. The supporting portion 334m is a substantially cylindrical surface. The supported portion 355c is a substantially cylindrical surface provided at an outer periphery of one end of the lever 355 and is slidable relative to the supporting portion 334m.

[0358] A guide portion 355a as the movable portion provided at one end of the lever 355 as the movable member is for guiding the coupling member 180 as will be described hereinafter, and includes a narrow portion 355a1 having a relatively small width and a wide portion 355a2 having a relatively large width. The width of the narrow portion 355a1 is small in order to determine an inclining direction of the coupling member 180 with high precision. In other words, the narrow portion 355a1 is capable of functioning as the movable portion for determining the inclining direction of the coupling member 180. The reason why the width increases in the direction from the narrow portion 355a1 to the wide portion 355a2 is that the rotation of the coupling member 180 is not disturbed during the rotation transmission operation. In place of the phase regulating portion 36kb in Embodiment 1, the guide portion 355a may be used as a phase regulating means for the coupling member 180.

[0359] Figure 44 shows the state in which the coupling lever 355, the coupling lever spring 356 and the coupling spring 3185 are mounted to the development side cover 334. Part (a) of Figure 44 is a perspective view as seen from the non-driving side, and part (b) of Figure 44 is a front view as seen from the non-

driving side. Part (c) of Figure 44 is a front view as seen from the driving side.

[0360] As shown in Figure 44, the lever 355 is mounted to the side cover 334 movably (rotatably) in the direction indicated by an arrow. The lever spring 356 is provided between the side cover 334 and the lever 355. As described
 5 hereinbefore, one end of the lever spring 356 is mounted to the projection 334s, and the other end of the spring 356 is mounted to the projection 355t as the spring mounting portion for the lever 355. The lever 355 is urged by the spring 356 in the counterclockwise direction (parts (a) and (b) of Figure 44 (clockwise direction in part (c) of Figure 44)). As a result, the abutting portion 355n of the
 10 lever 355 abuts to the abutting portion 334n of the side cover 334, by which the position of the lever 355 relative to the side cover 334 is determined.

[0361] In addition, the projection 334h of the cover 334 as the spring supporting portion supports a supported portion 3185a of the coupling spring 3185 as the elastic member. One end 3185b of the spring 3185 is locked on the
 15 projection 334b as a locking portion. The spring 3185 includes free end portions (first free end portion 3185c and second free end portion 3185d) as an urging portion or guide portion. The free end portions (first free end portion 3185c and second free end portion 3185d) are swingable relative to the supported portion 3185a by the elastic thereof. The second free end portion 3185d is
 20 provided at a free end side of the first free end portion 3185c and is bent from the first free end portion 3185c.

Figure 45 shows the state in which the developing cartridge B1 is set in the main assembly A1 and is capable of image forming operation. That is, it is the state in which the mounting of the developing cartridge B1 to the main
 25 assembly A1 has been completed. At this time, the coupling member 180 is engaged with the main assembly side driving member 100 and takes the reference attitude D0 (inclination angle of the coupling member 180 $\theta_2=0^\circ$), similarly to

Embodiment 1. At this time, a rotation regulating portion 355y of the coupling lever 355 is urged by the abutting portion 80y of the main assembly A1. The coupling lever 355 is in the position rotated in the counterclockwise direction from the position shown in Figure 47 which will be described hereinafter. As a
 5 result, as seen along the rotational axis of the developing roller, the narrow portion 355a1 is between the rotational axis of the developing roller 13 and the wide portion 355a2 (Figure 45).

[0362] Figure 46 shows the first inclination attitude D1 (at-spaced attitude) of the coupling member 180 in this embodiment. Part (a) of Figure 46 is a front
 10 view as seen from the driving side, and part (b) of Figure 46 is a perspective view as seen from the driving side. In the first inclination attitude D1, the coupling member 180 is inclined toward the main assembly side driving member 100 as the main assembly driving shaft when the developing roller 13 is retracted from the photosensitive drum 10 (retracted position (spacing position) of the
 15 developing cartridge B1) in the main assembly A1. That is, when the developing cartridge B1 (developing roller 13) is in the retracted position (spacing position), a free end portion 180a (rotational force receiving portions 180a1, 180a2) of the coupling member 180 is directed toward the main assembly side driving member 100 of the main assembly A1. In other words, as seen
 20 along the rotational axis of the developing roller 13, the rotational axis of the coupling member 180 is approximately inclined toward the developing roller 13 (photosensitive drum 10) (part (a) of Figure 46). An angular relationship of $\theta 3$ as the developing cartridge B1 is seen from the driving side toward the non-driving side along the rotational axis of the developing roller 13 when the first
 25 inclination attitude D1 is taken in this embodiment is similar to the Embodiment 1. At this time, the coupling member 180 is urged by the second free end portion 3185d as well as by the first free end portion 3185c.

[0363] When the coupling member 180 takes the first inclination attitude D1 (at-spaced attitude), the angle between the rotational axis L2 of the coupling member and the rotational axis of the developing roller 13 (or the rotational axis L3 of the drive input gear 27) is preferably any within the range of approx. 20° to approx. 60°. In this embodiment, the sample is approx. 35°.

Figure 47 shows the state in which the coupling member 180 takes the second inclination attitude D2 (at-mounting attitude). Part (a) of Figure 47 is a front view as seen from the driving side, and part (b) of Figure 47 is a perspective view as seen from the driving side. At this time, the narrow portion 355a1 is downstream of the wide portion 355a2 with respect to the mounting direction. The coupling member 180 is urged by the first free end portion 3185c. By this, the guide portion 180d of the coupling member 180 is positioned by the narrow portion 355a1. As a result, the coupling member 180 is inclined toward the downstream with respect to the mounting direction. In other words, the arm portion 3185c applies the force for inclining the coupling member 180 to the coupling member, and the guide portion 355a determines the inclining direction of the coupling member 180.

[0364] In this embodiment, similarly to Embodiment 1, the rotational axis L2 of the coupling member 180 in the second inclination attitude D2 (at-mounting attitude) is directed substantially opposite to the direction toward the developing blade 15. In this embodiment, the angular relationship of the angle $\theta 4$ as the developing cartridge B1 is seen along the rotational axis of the developing roller 13 in the direction from the driving side toward the non-driving side in the case of the second inclination attitude D1 is the same as in Embodiment 1.

In addition, the angle $\theta 5$ between the rotational axis L2 of the coupling member 180 and a line connecting the rotational axis of the developing roller and the pivoting center of the coupling member 180 as the developing

cartridge B1 is seen along the rotational axis of the developing roller 13 in the direction from the driving side toward the non-driving side is the same as in Embodiment 1.

[0365] In addition, the angle between the rotational axis L2 of the coupling member and the rotational axis of the developing roller 13 (or the rotational axis L3 of the drive input gear 27) at the time of the second inclination attitude D2 is preferably in the range between approx. 20° and approx. 60°, and is approx. 35° in this embodiment, similarly to Embodiment 1.

10 [Embodiment 4]

[0366] In this embodiment, the structure by which the coupling member 180 takes the reference attitude D0, the first inclination attitude D1 (at-spaced attitude) or the second inclination attitude D2 (at-mounting attitude) is different from that of Embodiment 1, as will be described in conjunction with Figure 48 to Figure 52. As regards the other structures of Embodiment 1, they are employed also in this embodiment, and therefore, the detailed description thereof is omitted. In Embodiment 3, the coupling spring 3185 is provided on the development side cover 334, but in this embodiment, a coupling spring 4185 is provided on a coupling lever 455, as is different from Embodiment 3.

20 [0367] Figure 48 is a schematic perspective view of a state of a coupling lever spring 456 as an urging member (or elastic member), the coupling lever 455 as a movable member before being mounted to a development side cover 434, and the state of coupling spring 4185 as the urging member (or elastic member) before being mounted to the coupling lever 455. In other words, it is an exploded schematic perspective view of the driving side extreme end of the developing cartridge B1 in this embodiment as seen from the driving side. The movable member in a broad sense includes the lever 455 and the lever spring 456,

25

similarly to Embodiments 1 and 3.

[0368] The side cover 434 includes a projection 434s as a spring mounting portion for mounting one end of the lever spring 456. The side cover 434 also includes a projection 434h as a spring mounting portion for mounting a part of the coupling spring 4185. The side cover 434 includes a supporting portion 434m for movably (rotatably) supporting a supported portion 455c of the lever 455. The supporting portion 434m is a substantially cylindrical surface. The supported portion 455c is a substantially cylindrical surface provided at an outer periphery of one end of the lever 455 and is slidable relative to the supporting portion 434m.

[0369] A guide portion 455a as a movable portion provided at one end portion of the lever 455 has the same structure as in Embodiment 3. That is, it includes a narrow portion 455a1 and a wide portion 455a2 which function similarly to Embodiment 3. That is, the narrow portion 455a1 functions as the movable portion in the narrow sense.

[0370] Figure 49 shows the state in which the coupling lever 455 and the coupling lever spring 456 are mounted to the development side cover 434, And the coupling spring 4185 is mounted to the coupling lever 455. Part (a) of Figure 49 is a perspective view as seen from the non-driving side, and part (b) of Figure 49 is a front view as seen from the non-driving side. Part (c) of Figure 49 is a front view as seen from the driving side.

As shown in Figure 49 the lever 455 is movably (rotatably) mounted to the side cover 434 similarly to Embodiment 3. The lever spring 456 is provided between the side cover 434 and the lever 455. As described hereinbefore, one end of the lever spring 456 is mounted to the projection 434s, and the other end of the spring 456 is mounted to the projection 455t as the spring mounting portion for the lever 455. The lever 455 is urged by the spring 456 in

the counterclockwise direction (part (a) of Figure 49 (clockwise direction in part (c) of Figure 49). As a result, the abutting portion 455n of the lever 455 abuts to the abutting portion 434n of the side cover 434, by which the position of the lever 455 relative to the side cover 434 is determined.

5 [0371] In addition, the projection 455h of the lever 455 as the spring supporting portion supports the portion 4185 of the coupling spring 4185a as the elastic member. One end 4185b of the spring 4185 is locked on the projection 445b as a locking portion. The spring 4185 includes free end portions (first free end portion 4185c and second free end portion 4185d) as an urging portion or guide
10 portion. The free end portions (first free end portion 4185c and second free end portion 4185d) are swingable relative to the supported portion 4185a by the elastic thereof. The second free end portion 4185d is provided at a free end side of the first free end portion 4185c and is bent from the first free end portion 4185c.

Figure 50 shows the state in which the developing cartridge B1 is set
15 in the main assembly A1 and is capable of image forming operation. That is, it is the state in which the mounting of the developing cartridge B1 to the main assembly A1 has been completed. At this time, the coupling member 180 is engaged with the main assembly side driving member 100 and takes the reference attitude D0 (inclination angle of the coupling member 180 $\theta_2=0^\circ$), similarly to
20 Embodiment 1. At this time, a rotation regulating portion 455y of the coupling lever 455 is urged by the abutting portion 80y of the main assembly A1. The coupling lever 455 is in the position rotated in the counterclockwise direction from the position shown in Figure 52 which will be described hereinafter. As a result, as seen along the rotational axis of the developing roller, the narrow
25 portion 455a1 is between the rotational axis of the developing roller 13 and the wide portion 455a2, similarly to Embodiment 3.

[0372] Figure 51 shows the first inclination attitude D1 (at-spaced attitude) of

the coupling member 180 in this embodiment. Part (a) of Figure 51 is a front view as seen from the driving side, and part (b) of Figure 51 is a perspective view as seen from the driving side. In the first inclination attitude D1, the coupling member 180 is inclined toward the main assembly side driving member 100 as

5 the main assembly driving shaft when the developing roller 13 is retracted from the photosensitive drum 10 (retracted position (spacing position) of the developing cartridge B1) in the main assembly A1. That is, when the developing cartridge B1 (developing roller 13) is in the retracted position (spacing position), a free end portion 180a (rotational force receiving portions

10 180a1, 180a2) of the coupling member 180 is directed toward the main assembly side driving member 100 of the main assembly A1. In other words, as seen along the rotational axis of the developing roller 13, the rotational axis of the coupling member 180 is approximately inclined toward the developing roller 13 (photosensitive drum 10). An angular relationship of θ_3 as the developing

15 cartridge B1 is seen from the driving side toward the non-driving side along the rotational axis of the developing roller 13 when the first inclination attitude D1 is taken in this embodiment is similar to the Embodiment 1. At this time, the coupling member 180 is urged by the second free end portion 4185d and the first free end portion 4185c.

20 [0373] When the coupling member 180 takes the first inclination attitude D1 (at-spaced attitude), the angle between the rotational axis L2 of the coupling member and the rotational axis of the developing roller 13 (or the rotational axis L3 of the drive input gear 27) is preferably any within the range of approx. 20° to approx. 60° . In this embodiment, the sample is approx. 35° .

25 [0374] Figure 52 shows the second inclination attitude D2 (at-mounting attitude) of the coupling member 180 in this embodiment. Part (a) of Figure 52 is a front view as seen from the driving side, and part (b) of Figure 52 is a

perspective view as seen from the driving side. The narrow portion 455a1 is downstream of the wide portion 455a2 with respect to the mounting direction. The coupling member 180 is urged by the first free end portion 4185c. By this, the guide portion 180d of the coupling member 180 is positioned to the narrow
5 portion 455a1. As a result, the coupling member 180 is inclined toward the downstream with respect to the mounting direction. In other words, the arm portion 4185c applies the force for inclining the coupling member 180 to the coupling member, and the guide portion 455a determines the inclining direction of the coupling member 180.

10 [0375] In this embodiment, similarly to Embodiment 1, the rotational axis L2 of the coupling member 180 in the second inclination attitude D2 (at-mounting attitude) is directed substantially opposite to the direction toward the developing blade 15. In this embodiment, the angular relationship of the angle $\theta 4$ as the developing cartridge B1 is seen along the rotational axis of the developing roller
15 13 in the direction from the driving side toward the non-driving side in the case of the second inclination attitude D1 is the same as in Embodiment 1.

[0376] In addition, the angle $\theta 5$ between the rotational axis L2 of the coupling member 180 and a line connecting the rotational axis of the developing roller in the pivoting center of the coupling member 180 as the developing cartridge B1 is
20 seen along the rotational axis of the developing roller 13 in the direction from the driving side toward the non-driving side is the same as in Embodiment 1.

[0377] In addition, the angle between the rotational axis L2 of the coupling member and the rotational axis of the developing roller 13 (or the rotational axis L3 of the drive input gear 27) at the time of the second inclination attitude D2 is
25 preferably in the range between approx. 20° and approx. 60° , and is approx. 35° in this embodiment, similarly to Embodiment 1.

[Embodiment 5]

[0378] In this embodiment, the structure by which the coupling member 180 takes the reference attitude D0, the first inclination attitude D1 (at-spaced attitude) or the second inclination attitude D2 (at-mounting attitude) are different from those in Embodiment 1, as will be described in conjunction with Figure 53 to Figure 57. More particularly, the structures of the development side cover 34, the coupling lever 55, the coupling lever spring 56, the coupling spring 185 and the members concerned with them are different from those of Embodiment 1, as will be described. As regards the other structures of Embodiment 1, they are employed also in this embodiment, and therefore, the detailed description thereof is omitted.

[0379] Figure 53 is a schematic perspective view of a state of a spring 5185 as an urging member (first elastic member) and a spring 555 as a movable member (second elastic member) before being mounted to a development side cover 534. In other words, it is an exploded schematic perspective view of the driving side extreme end of the developing cartridge B1 in this embodiment as seen from the driving side.

[0380] The side cover 534 includes a projection 534m as a supporting portion (spring mounting portion) for mounting the mounting portion 555a of the spring 555. The side cover 534 further includes a projection 534s as a locking portion for locking a portion-to-be-locked 555b of the second spring 555. Furthermore, the side cover 534 includes a projection 534h as the supporting portion (spring mounting portion) for mounting a part of the spring 5185. An arm portion 555c as the movable portion (urging portion) of the spring 555 functions to urge (or guide) the coupling member 180. In other words, the arm portion 555c as the movable portion urges the coupling member 180 against the force by the arm portion 5185d as the urging portion so as to move the coupling member 180

together with the arm portion 5185d. By this, the inclining direction of the coupling member 180 is changed.

[0381] Figure 54 shows the development side cover 534 to which the spring 555 and the spring 5185 are mounted, as seen from the driving side.

5 As shown in Figure 54, the mounting portion 555a is mounted to the development side cover 534 such that the arm portion 555c is movable (rotatable). In addition, the projection 534h of the cover 534 as the spring supporting portion supports the projection 5185a as the mounting portion for the spring 5185. One end portion 5185b of the spring 5185 is locked on the locking portion 534b.

10 The spring 5185 includes free end portions (first free end portion 5185c and second free end portion 5185d) as the urging portion. The free end portion (5185c and 5185d) of the spring 5185 as the urging portion is swingable about the projection 534h. The second free end portion 5185d is provided at a free end side of the first free end portion 5185c and is bent from the first free end portion

15 5185c.

[0382] Figure 55 shows the state in which the developing cartridge B1 is operable for the image forming operation, in the main assembly A1. That is, it is the state in which the mounting of the developing cartridge B1 to the main assembly A1 has been completed. At this time, the coupling member 180 is

20 engaged with the main assembly side driving member 100 and takes the reference attitude D0 (inclination angle of the coupling member 180 $\theta_2=0^\circ$), similarly to Embodiment 1. At this time, a rotation regulating portion 555y of the coupling lever 555 is urged by the abutting portion 80y of the main assembly A1, and by the urging force, the arm portion 555c of the spring 555 is rotated in the

25 counterclockwise direction about the supporting portion 555a together with the arm portion 555d and the rotation regulating portion 555y. As a result, in the completed mounting step, the arm portion 555c is away from the coupling

member 180 as seen along the rotational axis of the developing roller.

Figure 56 shows the first inclination attitude D1 (at-spaced attitude) of the coupling member 180 in this embodiment. Part (a) of Figure 56 is a front view as seen from the driving side, and part (b) of Figure 56 is a perspective view as seen from the driving side. In the first inclination attitude D1, the coupling member 180 is inclined toward the main assembly side driving member 100 as the main assembly driving shaft when the developing roller 13 is retracted from the photosensitive drum 10 (retracted position (spacing position) of the developing cartridge B1) in the main assembly A1. That is, when the developing cartridge B1 (developing roller 13) is in the retracted position (spacing position), a free end portion 180a (rotational force receiving portions 180a1, 180a2) of the coupling member 180 is directed toward the main assembly side driving member 100 of the main assembly A1. In other words, as seen along the rotational axis of the developing roller 13, the rotational axis of the coupling member 180 is inclined substantially toward the developing roller 13 (photosensitive drum 10) in this attitude. An angular relationship of θ_3 as the developing cartridge B1 is seen from the driving side toward the non-driving side along the rotational axis of the developing roller 13 when the first inclination attitude D1 is taken in this embodiment is similar to the Embodiment 1. At this time, the coupling member 180 is urged by the second free end portion 5185d. [0383] When the coupling member 180 takes the first inclination attitude D1 (at-spaced attitude), the angle between the rotational axis L2 of the coupling member and the rotational axis of the developing roller 13 (or the rotational axis L3 of the drive input gear 27) is preferably any within the range of approx. 20° to approx. 60°. In this embodiment, the sample is approx. 35°.

Figure 57 shows the state in which the coupling member 180 takes the second inclination attitude D2 (at-mounting attitude). Part (a) of Figure 57 is a

front view as seen from the driving side, and part (b) of Figure 57 is a perspective view as seen from the driving side. The coupling member 180 is urged by the second free end portion 5185d. The guide portion 180d of the coupling member 180 is positioned by the arm portion 555c. As a result, the coupling member

5 180 is inclined toward the downstream with respect to the mounting direction. In other words, in this embodiment, similarly to Embodiment 1, the rotational axis L2 of the coupling member 180 is directed substantially in the direction away from the developing blade 15. Namely, in this embodiment, the angular relationship of the angle θ_4 as the developing cartridge B1 is seen along the

10 rotational axis of the developing roller 13 in the direction from the driving side toward the non-driving side in the case of the second inclination attitude D1 is the same as in Embodiment 1.

[0384] As shown in Figure 57, in this embodiment, the force applied by the arm portion 555c to the coupling member 180, that is, toward the lower left is made

15 larger than the force applied by the arm portion 5185d to the coupling member, that is, toward the upper right.

In addition, the angle θ_5 between the rotational axis L2 of the coupling member 180 and a line connecting the rotational axis of the developing roller and the pivoting center of the coupling member 180 as the developing

20 cartridge B1 is seen along the rotational axis of the developing roller 13 in the direction from the driving side toward the non-driving side is the same as in Embodiment 1.

[0385] In addition, the angle between the rotational axis L2 of the coupling member and the rotational axis of the developing roller 13 (or the rotational axis

25 L3 of the drive input gear 27) at the time of the second inclination attitude D2 is preferably in the range between approx. 20° and approx. 60° , and is approx. 35° in this embodiment, similarly to Embodiment 1.

[Embodiment 6]

[0386] In this embodiment, the structure by which the coupling member 180 takes the reference attitude D0, the first inclination attitude D1 (at-spaced
5 attitude) or the second inclination attitude D2 (at-mounting attitude) is different from the start of Embodiment 1, as will be described in conjunction with Figure 58 to Figure 62. More particularly, the structures of the development side cover 34, the coupling lever 55, the coupling lever spring 56, the coupling spring 185 and the members concerned with them are different from those of Embodiment 1,
10 as will be described. As regards the other structures of Embodiment 1, they are employed also in this embodiment, and therefore, the detailed description thereof is omitted. In this embodiment, a rotatable member 656 and a spring 655 are used in place of the spring 555 of Embodiment 5.

[0387] Figure 58 is a schematic perspective view of a state of a spring 6185 as
15 an urging member (first elastic member) and a spring 655 as a movable member (second elastic member) before being mounted to a development side cover 634. In other words, it is an exploded schematic perspective view of the driving side extreme end of the developing cartridge B1 in this embodiment as seen from the driving side. The spring 6185 as the urging member (elastic member) illustrated
20 in Figures 60 - 62 is similar to the spring 5185 of Figure 54, and is omitted in Figure 58. The movable member in the broad sense includes the spring 655 and the rotatable member 656.

[0388] A side cover 634 includes a supporting portion 634a for supporting the rotatable member 656 as a supported member. In more detail the supporting
25 portion 634a rotatably supports the supported portion 656a1 provided on the supported member 656. The supporting portion 634a has a substantially cylindrical surface, and the supported portion 656a1 has a substantial cylindrical

surface corresponding to the supporting portion 634a. The rotatable member 656 includes a spring mounting portion 656a2 as a supporting portion for mounting a mounting portion 655a of the spring 655 as the movable member (elastic member). The side cover 634 includes a locking portion 634s for
 5 locking a portion-to-be-locked 655b of the spring 655. In addition, an arm portion 655c as the movable portion (guide portion) of the coupling lever 655 is locked with a locking portion 656b of the rotatable member 656, and urges (or guides) the coupling member 180. In other words, the arm portion 655c as the movable portion urges the coupling member 180 against the force by the arm
 10 portion 6185d as the urging portion so as to move the coupling member 180 together with the arm portion 6185d. By this, the inclining direction of the coupling member 180 is changed.

[0389] Figure 59 shows the spring 655 as the urging member (elastic member), the rotatable member 656 and the spring 6185 as the urging member (elastic
 15 member) which are mounted to the side cover 634, as seen from the non-driving side.

[0390] As shown in Figure 59, the supported member 656 is movably (rotatably) mounted to the side cover 634. A projection 656a as the supporting portion for the rotatable member 656 supports the supported portion 655a of the
 20 spring 655. One end portion 655b of the spring 655 is locked with the locking portion 634s of the development side cover 634. The spring 655 includes a free end portion 655c as the movable portion. The free end portion 655c of the spring 655 is swingable about the projection 656a.

[0391] Figure 60 shows the state in which the developing cartridge B1 is
 25 operable for the image forming operation, in the main assembly A1. That is, it is the state in which the mounting of the developing cartridge B1 to the main assembly A1 has been completed. At this time, the coupling member 180 is

engaged with the main assembly side driving member 100 and takes the reference attitude D0 (inclination angle of the coupling member 180 $\theta_2=0^\circ$), similarly to Embodiment 1. At this time, a rotation regulating portion 656y of the rotatable member 656 is urged by the abutting portion 80y of the main assembly A1, so

5 that the arm portion 655c as the movable portion (urging portion) of the spring 655 and the rotatable member 656 rotate in the counterclockwise direction about the supporting portion 634a. That is, as seen along the rotational axis of the developing roller, the arm portion 655c is spaced from the coupling member 180.

[0392] Figure 61 shows the first inclination attitude D1 (at-spaced attitude) of

10 the coupling member 180 in this embodiment. Part (a) of Figure 61 is a front view as seen from the driving side, and part (b) of Figure 46 is a perspective view as seen from the driving side. In the first inclination attitude D1, the coupling member 180 is inclined toward the main assembly side driving member 100 as the main assembly driving shaft when the developing roller 13 is retracted from

15 the photosensitive drum 10 (retracted position (spacing position) of the developing cartridge B1) in the main assembly A1. That is, when the developing cartridge B1 (developing roller 13) is in the retracted position (spacing position), a free end portion 180a (rotational force receiving portions 180a1, 180a2) of the coupling member 180 is directed toward the main assembly

20 side driving member 100 of the main assembly A1. In other words, as seen along the rotational axis of the developing roller 13, the rotational axis of the coupling member 180 is approximately inclined toward the developing roller 13 (photosensitive drum 10) (part (a) of Figure 61). An angular relationship of θ_3 as the developing cartridge B1 is seen from the driving side toward the non-

25 driving side along the rotational axis of the developing roller 13 when the first inclination attitude D1 is taken in this embodiment is similar to the Embodiment 1. This time, the coupling member 180 is urged by the second free end portion

6185d as the urging portion or the guide portion.

[0393] When the coupling member 180 takes the first inclination attitude D1 (at-spaced attitude), the angle between the rotational axis L2 of the coupling member and the rotational axis of the developing roller 13 (or the rotational axis L3 of the drive input gear 27) is preferably any within the range of approx. 20° to approx. 60°. In this embodiment, the sample is approx. 35°.

[0394] Figure 62 shows the second inclination attitude D2 (at-mounting attitude) of the coupling member 180 in this embodiment. Part (a) of Figure 62 is a front view as seen from the driving side, and part (b) of Figure 62 is a perspective view as seen from the driving side. The coupling member 180 is urged by the second free end portion 6185d as the urging portion (or guide portion). By this, a guide portion 180d of the coupling member 180 is positioned to the arm portion 655c as the urging portion (or guide portion). As a result, the coupling member 180 is inclined toward the downstream with respect to the mounting direction. In other words, in this embodiment, similarly to Embodiment 1, the rotational axis L2 of the coupling member 180 is directed substantially in the direction away from the developing blade 15. In this embodiment, the angular relationship of the angle $\theta 4$ as the developing cartridge B1 is seen along the rotational axis of the developing roller 13 in the direction from the driving side toward the non-driving side in the case of the second inclination attitude D1 is the same as in Embodiment 1.

[0395] In addition, the angle $\theta 5$ between the rotational axis L2 of the coupling member 180 and a line connecting the rotational axis of the developing roller in the pivoting center of the coupling member 180 as the developing cartridge B1 is seen along the rotational axis of the developing roller 13 in the direction from the driving side toward the non-driving side is the same as in Embodiment 1.

[0396] As shown in Figure 62, in this embodiment, too, the force toward the

lower left applied to the coupling member 180 by the arm portion 655c is made larger than the force toward the upper right applied to the coupling member by the arm portion 6185d.

[0397] In addition, the angle between the rotational axis L2 of the coupling member and the rotational axis of the developing roller 13 (or the rotational axis L3 of the drive input gear 27) at the time of the second inclination attitude D2 is preferably in the range between approx. 20° and approx. 60°, and is approx. 35° in this embodiment, similarly to Embodiment 1.

10 [Embodiment 7]

[0398] In this embodiment, the structure by which the coupling member 180 takes the reference attitude D0, the first inclination attitude D1 (at-spaced attitude) or the second inclination attitude D2 (at-mounting attitude) is different from that of Embodiment 1, as will be described in conjunction with Figure 63 to Figure 67. More particularly, the structures of the development side cover 34, the coupling lever 55, the coupling lever spring 56, the coupling spring 185 and the members concerned with them are different from those of Embodiment 1, as will be described. As regards the other structures of Embodiment 1, they are employed also in this embodiment, and therefore, the detailed description thereof is omitted. In Embodiment 1, the lever 55 urges the coupling member 180, but in this embodiment, a lever 755 urges a spring 7185 not the coupling member 180.

[0399] Figure 63 is a schematic perspective view of a coupling spring 7185 as an urging member (or elastic member), a coupling lever 755 as a movable member or urging member (or movable member) and a coupling lever spring 756 as an urging member (or elastic member) for applying an urging force to the lever 755, before being mounted to the development side cover 734. In other words, it is an exploded schematic perspective view of the driving side extreme end of

the developing cartridge B1 as seen from the non-driving side. The movable member in the broad sense includes the lever 755 and the spring 756.

[0400] The side cover 734 includes a supporting portion 734a for supporting the lever 755. More in detail, the supporting portion 734a rotatably supports a supported portion 755a1 provided on the lever 755. The supporting portion 734a is cylindrical, and a supported portion 755a is cylindrical correspondingly to the supporting portion 734a. The lever 755 includes a spring mounting portion 755a2 as a supporting portion for mounting a mounting portion 756a of the spring 756 as the elastic member. The side cover 734 includes a locking portion 734s for locking a portion-to-be-locked 756b of the spring 756. An arm portion 755c as an urging portion (or guide portion) of the lever 755 functions to urge (guide) an arm portion 7185d as an urging portion of the spring 7185. In other words, the arm portion 755c moves the arm portion 7185d to change an inclining direction of the coupling member without contacting the coupling member 180.

[0401] Figure 64 shows the state in which the lever 755, the spring 756 and the spring 7185 have been mounted to the side cover 734, as seen from the non-driving side.

[0402] As shown in Figure 64, to the side cover 734, the lever 755 is movably (rotatable) mounted. A spring supporting portion 755a of the lever 755 supports a supported portion 756a of the coupling lever spring 756 as the elastic member. One end portion 756b of the spring 756 is locked with the locking portion 734b of the development side cover 734. Other end portion 756c of the spring 756 is locked with a locking portion 755b of the lever 755. Therefore, the coupling lever 755 is urged in the clockwise direction by the spring 756.

[0403] Figure 65 shows the state in which the developing cartridge B1 is operable for the image forming operation, in the main assembly A1. That is, it is the state in which the mounting of the developing cartridge B1 to the main

assembly A1 has been completed. At this time, the coupling member 180 is engaged with the main assembly side driving member 100 and takes the reference attitude D0 (inclination angle of the coupling member 180 $\theta_2=0^\circ$), similarly to Embodiment 1. At this time, a rotation regulating portion 755y of the lever 755 is urged by the abutting portion 80y of the main assembly A1, so that the lever 755 (arm portion 755c) rotates in the clockwise direction about a supporting portion 734a. As a result, as seen along a rotational axis of the developing roller, the arm portion 755c is spaced from the spring 7185.

[0404] Figure 66 shows the first inclination attitude D1 of the coupling member 180 (at-spaced attitude) in this embodiment. Part (a) of Figure 66 is a front view as seen from the driving side, and part (b) of Figure 66 is a perspective view as seen from the driving side. In the first inclination attitude D1, the coupling member 180 is inclined toward the main assembly side driving member 100 as the main assembly driving shaft when the developing roller 13 is retracted from the photosensitive drum 10 (retracted position (spacing position) of the developing cartridge B1) in the main assembly A1. That is, when the developing cartridge B1 (developing roller 13) is in the retracted position (spacing position), a free end portion 180a (rotational force receiving portions 180a1, 180a2) of the coupling member 180 is directed toward the main assembly side driving member 100 of the main assembly A1. In other words, as seen along the rotational axis of the developing roller 13, the rotational axis of the coupling member 180 is approximately inclined toward the developing roller 13 (photosensitive drum 10) (part (a) of Figure 66). An angular relationship of θ_3 as the developing cartridge B1 is seen from the driving side toward the non-driving side along the rotational axis of the developing roller 13 when the first inclination attitude D1 is taken in this embodiment is similar to the Embodiment 1. At this time, the coupling member 180 is urged by the second free end

portion 7185d as the urging portion.

[0405] When the coupling member 180 takes the first inclination attitude D1 (at-spaced attitude), the angle between the rotational axis L2 of the coupling member and the rotational axis of the developing roller 13 (or the rotational axis L3 of the drive input gear 27) is preferably any within the range of approx. 20° to approx. 60°. In this embodiment, the sample is approx. 35°.

[0406] Figure 67 shows the second inclination attitude D2 (at-mounting attitude) of the coupling member 180 in this embodiment. Part (a) of Figure 62 is a front view as seen from the driving side, and part (b) of Figure 62 is a perspective view as seen from the driving side. At this time, the second free end portion 7185d as the urging portion is urged by the arm portion 755c as the movable portion. The coupling member 180 is positioned to the second free end portion 7185d urged downwardly to the arm portion 755c by the weight of itself. The guide portion 180d of the coupling member 180 is positioned by the arm portion 7185d. As a result, the coupling member 180 is inclined toward the downstream with respect to the mounting direction. In other words, in this embodiment, similarly to Embodiment 1, the rotational axis L2 of the coupling member 180 is directed substantially in the direction away from the developing blade 15. In this embodiment, the angular relationship of the angle $\theta 4$ as the developing cartridge B1 is seen along the rotational axis of the developing roller 13 in the direction from the driving side toward the non-driving side in the case of the second inclination attitude D1 is the same as in Embodiment 1. In this embodiment, the guide portion 180d of the coupling member 180 in the second inclination attitude D2 is contacted to the second free end portion 7185d, but it may be spaced. In such a case, the attitude of the coupling member 180 in the second inclination attitude D2 is determined by the phase regulation boss 180e and the inclination regulating portion 36kb2b, as with Embodiment 1.

[0407] In addition, the angle θ_5 between the rotational axis L2 of the coupling member 180 and a line connecting the rotational axis of the developing roller and the pivoting center of the coupling member 180 as the developing cartridge B1 is seen along the rotational axis of the developing roller 13 in the direction from the driving side toward the non-driving side is the same as in Embodiment 1.

[0408] In other words, as the developing cartridge B1 is seen along the rotational axis of the developing roller 13 from the driving side toward the non-driving side, the rotational axis L2 of the coupling member 180 is clockwise inclined from the line connecting the rotational axis of the developing roller and the pivoting center of the coupling member 180 by an angle in the range between approx. 35° and approx. 125° . In this embodiment, the angle is substantially 80° .

[0409] In the state shown in Figure 67, the force by the arm portion 755c toward the lower left is larger than the force applied by the arm portion 7185d to the coupling member toward the upper right.

[0410] In addition, the angle between the rotational axis L2 of the coupling member and the rotational axis of the developing roller 13 (or the rotational axis L3 of the drive input gear 27) at the time of the second inclination attitude D2 is preferably in the range between approx. 20° and approx. 60° , and is approx. 35° in this embodiment, similarly to Embodiment 1.

[Embodiment 8]

[0411] In this embodiment, the structure by which the coupling member 180 takes the reference attitude D0, the first inclination attitude D1 (at-spaced attitude) or the second inclination attitude D2 (at-mounting attitude) is different from that of Embodiment 1, as will be described in conjunction with Figure 68 to Figure 72. The structures of the side cover 34, the coupling lever 55, the

coupling lever spring 56, the coupling spring 185 and the members concerned with them of Embodiment 1 are different from those of Embodiment 1, as will be described. More particularly, the spring 7185 is further improved. The other structures of Embodiment 7 are employed in this embodiment, and therefore, the description thereof is omitted.

[0412] Figure 68 is an exploded schematic perspective view of the driving side extreme end of the developing cartridge B1 according to this embodiment, as seen from the driving side. The description will be made as to the portions different from Embodiment 7. More particularly, the description will be made as to the coupling spring 8185 as the urging member (or elastic member). The structure for mounting the spring 8185 to the development side cover 834 is the same, but the structure of the free end portion side of the mounting portion 8185a is different. The spring 8185 includes a first connecting portion 8185c and a second connecting portion 8185d. There is provided a first coupling contact portion 8185e folded back from the second connecting portion 8185d. Furthermore, there is provided a second coupling contact portion 8185f reversely folded from the first coupling contact portion 8185e. The first and second coupling contact portions 8185e and 8185f function as an urging portion for inclining the coupling member 180.

[0413] Figure 69 shows a state in which a lever 855, a lever spring 856 and the coupling spring 8185 are mounted to the development side cover 834, as seen from the driving side. The movable member in the broad sense includes the lever 855 and the spring 856.

[0414] As shown in Figure 69, the lever 855 as the movable member or urging member (or rotatable member) is movably (rotatably) mounted to the side cover 834. A spring supporting portion 855a of the lever 855 supports a supported portion 856a of the lever spring 856 as the elastic member. One end portion

856b of the spring 856 is locked with a locking portion 834b of the side cover 834. Other end portion 856c of the spring 856 is locked with a locking portion 855b of the lever 855. Therefore, the lever 855 is urged counterclockwisely by the spring 856.

5 [0415] Figure 70 shows the state in which the developing cartridge B1 is operable for the image forming operation, in the main assembly A1. That is, it is the state in which the mounting of the developing cartridge B1 to the main assembly A1 has been completed. At this time, the coupling member 180 is engaged with the main assembly side driving member 100 and takes the reference
10 attitude D0 (inclination angle of the coupling member 180 $\theta_2=0^\circ$), similarly to Embodiment 1. At this time, a rotation regulating portion 855y of the lever 855 is urged by the abutting portion 80y of the main assembly A1, so that the lever 855 (arm portion 855c as the movable portion (or urging portion) rotates in the counterclockwise direction about a supporting portion 834a. As a result, as seen
15 along a rotational axis of the developing roller, the arm portion 855c is spaced from the spring 7185.

[0416] Figure 71 shows the first inclination attitude D1 (at-spaced attitude) of the coupling member 180 in this embodiment. Part (a) of Figure 71 is a front view as seen from the driving side, and part (b) of Figure 71 is a perspective view
20 as seen from the driving side. In the first inclination attitude D1, the coupling member 180 is inclined toward the main assembly side driving member 100 as the main assembly driving shaft when the developing roller 13 is retracted from the photosensitive drum 10 (retracted position (spacing position) of the developing cartridge B1) in the main assembly A1. That is, when the
25 developing cartridge B1 (developing roller 13) is in the retracted position (spacing position), a free end portion 180a (rotational force receiving portions 180a1, 180a2) of the coupling member 180 is directed toward the main assembly

side driving member 100 of the main assembly A1. In other words, as seen along the rotational axis of the developing roller 13, the rotational axis of the coupling member 180 is approximately inclined toward the developing roller 13 (photosensitive drum 10) (part (a) of Figure 71). An angular relationship of θ_3 as the developing cartridge B1 is seen from the driving side toward the non-driving side along the rotational axis of the developing roller 13 when the first inclination attitude D1 is taken in this embodiment is similar to the Embodiment 1. At this time, the coupling member 180 is sandwiched between the first coupling contact portion 8185e and the second coupling contact portion 8185f.

[0417] when the coupling member 180 takes the first inclination attitude D1 (at-spaced attitude), the angle between the rotational axis L2 of the coupling member and the rotational axis of the developing roller 13 (or the rotational axis L3 of the drive input gear 27) is preferably any within the range of approx. 20° to approx. 60° . In this embodiment, the sample is approx. 35° .

[0418] Figure 72 shows the second inclination attitude D2 (at-mounting attitude) of the coupling member 180 in this embodiment. Part (a) of Figure 72 is a front view as seen from the driving side, and part (b) of Figure 72 is a perspective view as seen from the driving side. At this time, the second coupling contact portion 8185f is urged by the arm portion 855c as the movable portion. The coupling member 180 is positioned to the first coupling contact portion 8185e by the second coupling contact portion 8185f downwardly urged by the arm portion 855c. The guide portion 180d of the coupling member 180 is positioned by the arm portion 8185d. As a result, the coupling member 180 is inclined toward the downstream with respect to the mounting direction.

[0419] Similarly to Embodiments 1, the rotational axis L2 of the coupling member 180 is directed substantially opposite from the developing blade 15 in this embodiment, too. In this embodiment, the angular relationship of the angle

$\theta 4$ as the developing cartridge B1 is seen along the rotational axis of the developing roller 13 in the direction from the driving side toward the non-driving side in the case of the second inclination attitude D1 is the same as in Embodiment 1.

5 [0420] In addition, the angle $\theta 5$ between the rotational axis L2 of the coupling member 180 and a line connecting the rotational axis of the developing roller and the pivoting center of the coupling member 180 as the developing cartridge B1 is seen along the rotational axis of the developing roller 13 in the direction from the driving side toward the non-driving side is the same as in Embodiment 1.

10 [0421] In addition, the angle between the rotational axis L2 of the coupling member and the rotational axis of the developing roller 13 (or the rotational axis L3 of the drive input gear 27) at the time of the second inclination attitude is preferably in the range between approx. 20° and approx. 60° , and is approx. 35° in this embodiment, similarly to Embodiment 1.

15

[Embodiment 9]

[0422] In this embodiment, the structure for positioning the coupling member 180 in the reference attitude D0, the first inclination attitude D1 (at-spaced attitude) and the second inclination attitude D2 (at-mounting attitude) is different from that of Embodiment 1, as will be described in conjunction with Figure 73. In this embodiment, the configuration of an arm portion 855 of Embodiment 8 is modified so that it is urged to a second connecting portion 9185d not to the contact portion 9185f of the second coupling. Therefore, a first coupling contact portion 9185e and a second coupling contact portion 9185f function as an urging portion full inclining the coupling member 180. An arm portion 955c as the urging portion determines the inclining direction of the coupling 180, similarly to the foregoing embodiment. The other structures are similar to those of

20

25

Embodiment 8, and therefore, the description is omitted.

[Embodiment 10]

[0423] In this embodiment, the structure for positioning the coupling member
5 180 in the reference attitude D0, the first inclination attitude D1 (at-spaced
attitude) and the second inclination attitude D2 (at-mounting attitude) are
different from that of Embodiment 1, as will be described in conjunction with
Figure 74. In the foregoing embodiment, the urging portion and the movable
portion are separate members, but in this embodiment, the urging portion 10185e
10 and the movable portion 10185g are provided as a single part (single spring).
Part (a) of Figure 74 shows a coupling spring 10185 mounted to the development
side cover 1034.

[0424] Part (b) of Figure 74 shows a second inclination attitude D2 of the
coupling member 180. In this state, a movable portion 10185f urges the
15 coupling member 180, but the urging portion 10185e is spaced from the coupling
member 180. However, the urging portion 10185e may also contact the
coupling member 180.

[0425] Part (c) of Figure 74 shows a first inclination attitude D1 of the coupling
member 180. In this state, the urging portion 10185e urges the coupling
20 member 180, but the movable portion 10185f is spaced from the coupling
member 180. However, the movable portion 10185f may also contact the
coupling member 180.

[0426] A mounting portion 10185a, a locking portion 10185b and a connecting
portion 10185d are similar to those of Embodiment 9, and therefore, the
25 description thereof are omitted.

[0427] A connecting portion 10185g connects the force receiving portion
10185h for receiving the force from the main assembly and the movable portion

10185f.

[Embodiment 11]

[0428] In this embodiment, the structure for positioning the coupling member
5 180 in the reference attitude D0, the first inclination attitude D1 (at-spaced
attitude) and the second inclination attitude D2 (at-mounting attitude) are
different from that of Embodiment 1, as will be described in conjunction with
Figure 75. This embodiment is a modification of Embodiment 9. Part (a) of
Figure 75 shows a coupling spring 11185 and a lever 1155 to a development side
10 cover 1134.

[0429] Part (b) of Figure 75 shows a second inclination attitude D2 of the
coupling member 180. In this state, a second movable portion 1155c2 urges the
coupling member 180, but an urging portion 11185d is spaced from the coupling
member 180. At this time, a first movable portion 1155c1 urges the urging
15 portion 11185d. At this time, the urging portion 11185d may contact the
coupling member 180.

[0430] Part (c) of Figure 75 shows a first inclination attitude D1 of the coupling
member 180. In this state, the urging portion 11185d urges the coupling
member 180, but a movable portion 1155c2 is spaced from the coupling member
20 180. However, the second movable portion 1155c2 may also contact the
coupling member 180.

[Embodiment 12]

[0431] In a alternative structure, a movable portion contacts at least one of a
25 coupling member and an urging member when the first inclination attitude D1 is
taken, and it does not contact the coupling member when the second inclination
attitude D2s is taken.

[0432] Part (a) of Figure 76 of Embodiment 12 shows a development side cover 1234, and a lever 1255 as a movable member and a spring 12185 as the urging member which are mounted to the development side cover 1234.

[0433] As shown in part (b) of Figure 76 of Embodiment 12, in the second
 5 inclination attitude D2, the structure is such that a second movable portion 1255c2 as the movable portion of the lever 1255 is not contacted to a lower part of the portion-to-be-guided 180d of the coupling member 180.

At this time, an urging portion 12185c of a spring 121185 as the urging member urges the portion-to-be-guided 180d.

10 [0434] By this, the coupling member 180 takes the second inclination attitude D2.

In other words, in the second inclination attitude D2, only the urging portion 12185c contacts in the portion-to-be-guided 180d, but the second movable portion 1255c2 as the movable portion does not contact the portion-to-
 15 be-guided 180d.

[0435] Part (c) of Figure 76 shows the state in which the force receiving portion 1255y of the levers 1255 has rotated from the position shown in part (b) of Figure 76 counterclockwise by receiving the force from the main assembly of the apparatus.

20 [0436] At this time, a first movable portion 1255c1 urges the urging portion 12185c upwardly, so that the urging portion 12185c is retracted from the portion-to-be-guided 180d.

At this time, the second movable portion 1255c2 urges the portion-to-be-guided 180d.

25 As a result, the coupling member 180 takes the first inclination attitude D1.

[0437] The structures of the mounting portion 12185a of the spring 12185 and

the force receiving portion 1255y for receiving the force from the main assembly and so on are similar to those of the embodiments, and therefore, the description is omitted.

5 [Other the embodiments]

[0438] First, the structures of the Embodiments 3 - 12 are usable with the process cartridge of Embodiment 2.

[0439] In all of the described embodiments, a part of the spring (185, 985, 3185, 4185, 5185, 6185, 7185, 8185, 9185, 10185) has been used as the urging portion.

10 However, as described in the example of the movable member (55+56, 955+956, 355+356, 455+456, 655+656, 755+756, 855+866, 955), the urging portion may be constituted by another member (resin material or the like). For example, a resin material member is fixed to a free end portion of the spring (185, 985, 3185, 4185, 5185, 6185, 7185, 8185, 9185, 10185, 11185, 12185) as the urging member
15 and is used as the urging portion or the guide portion for urging or guiding the coupling member. In addition, as with the lever 656 of Embodiment 6, a base portion is provided with a rotatable member for mounting the spring (185, 985, 3185, 4185, 5185, 6185, 7185, 8185, 9185) as the urging member to the development side cover.

20 [0440] In all of the above-described embodiments, the elastic member has been the twisting spring or the coil spring, but the present invention is not limited to such examples, and the use can be made with a resin material spring, a leaf spring and/or rubber or the like.

[0441] The configuration of the coupling member 180 is not limited to the
25 above-described examples, but may be a barrel configuration not having a thin portion such as the connecting portion 180d. However, using the connecting portion 180d can downsize the cartridge.

[0442] In addition, the coupling member 180 may be made movable in the axial direction of the developing roller 13 in which an elastic member (spring or the like) or the like is provided at the rear side of the coupling member 180. In such a case, the pivoting angle of the coupling member 180 can be reduced.

5 [0443] As shown in part (b) of Figure 11 and part (b) of Figure 12, the two leftwardly projected parts are provided between the guide portion 36kb1b and the guide portion 36kb2b. However, such projections may not be provided, and the portion between the guide portion 36kb1b and the guide portion 36kb2b may be made linear or recessed. In such a case, the boss 180e can easily move between
10 the guide portion 36kb1b and the guide portion 36kb2b. That is, the configuration of the hole portion 36a may be any if it is substantially triangular shape. These modifications are applicable to the other embodiments.

[INDUSTRIAL APPLICABILITY]

15 [0444] According to the present invention, there is provided a cartridge in which a coupling member is engageable with a main assembly driving shaft when the cartridge is mounted to a main assembly and when the developer carrying member is moved from a retracted position to a developing position.

20 [Reference numerals]

A1, A91: main assembly of apparatus

B1, B901: developing cartridge

C, C901: drum cartridge

P: process cartridge

25 1: optical means

2, recording material

3a: sheet feeding roller

	3b: separation pad
	3c: registration roller
	3d: feeding guide
	3e: feeding guide
5	3f: feeding guide
	3g: discharging roller
	3h: discharging portion
	4: sheet feeding tray
	5: fixing means
10	5a: driving roller
	5b: heater
	5c: fixing roller
	6: transfer roller
	6a: transfer nip
15	7: pick-up roller
	8: feeding guide
	9: press-contact member transfer roller
	10: photosensitive drum
	11: charging roller
20	12: magnet roller
	13: developing roller
	13a: driving side end portion
	13c: non-driving side end portion
	15: developing blade
25	15a: supporting member
	15a1: driving side end portion
	15a2: non-driving side end portion

	15b: elastic member
	16: developing container
	16a: developer accommodating portion
	16b: opening
5	16c: developing chamber
	17: developer feeding member
	21: drum frame
	27: drive input gear
	29: developing roller gear
10	34, 934: development side cover
	34a: hole
	36, 936: driving side developing device bearing
	36a: hole
	936r: boss
15	46, 946: non-driving side developing device bearing
	46f: supporting portion
	946r: boss
	51, 52: screw
	70: movable member
20	71: urging member
	80: driving side swing guide
	80y: abutting portion
	81: non-driving side swing guide
	90: driving-side side plate
25	92, 992: driving side guiding member
	992y: abutting portion
	93, 993: non-driving side guiding member

	94: main assembly cover
	100, 900: main assembly side driving member
	150: slider member
	180, 980: coupling member
5	180c1, 980c1: rotational force transmitting portion
	185, 985: coupling spring
	55, 955: coupling lever
	55e, 955e: guide portion
	55b, 955b: spring hook portion
10	55y, 955y: rotation regulating portion
	56, 956: coupling lever spring
	L: laser beam
	Y: recording material
	t: developer
15	X5: rotational moving direction.

CLAIMS

1. A cartridge mountable, along a predetermined mounting path, to a main assembly of an electrophotographic image forming apparatus including a photosensitive member on which a latent image is capable of being formed and including a main assembly driving shaft, wherein said cartridge is movable in the main assembly between a developing position at a terminal end of said mounting path and a retracted position retracted from the developing position in a direction different from the mounting path, said cartridge comprising:

a developer carrying member capable of developing the latent image while being in contact with the photosensitive member when said cartridge is in the developing position; and

a coupling member capable of inclining relative to a rotational axis of said developer carrying member, wherein said coupling member is capable of taking a reference attitude in which a drive transmission is capable from the main assembly driving shaft to said developer carrying member when said cartridge is in the developing position, an at-mounting attitude inclined relative to the rotational axis of said developer carrying member to engage with the main assembly driving shaft when said cartridge moves along the mounting path, and an at-spaced attitude inclined relative to the rotational axis of said developer carrying member in a direction different from that in the at-mounting attitude,

wherein as seen along the axial direction of said developer carrying member, an angle formed between the rotational axis of said coupling member taking the at-spaced attitude and the rotational axis of said coupling member taking the at-mounting attitude is a value in a range of approximately 20° to approximately 150°.

2. A cartridge according to Claim 1, further comprising an urging portion for applying an urging force to incline said coupling member relative to the rotational axis of said developer carrying member.

3. A cartridge according to Claim 2, further comprising a movable portion capable of taking a first movement position for causing said coupling member to take the at-spaced attitude and a second movement position for causing said coupling member to take the at-mounting attitude.

4. A cartridge according to Claim 3, further comprising an urging member including said urging portion.

5. A cartridge according to Claim 4, wherein said movable portion is capable of urging at least one of said coupling member and said urging member at least one of the first movement position and the second movement position.

6. A cartridge according to Claim 5, wherein said movable portion is capable of directly urging at least one of said coupling member and said urging member at least one of the first movement position and the second movement position.

7. A cartridge according to any one of Claims 2 - 6, wherein when said coupling member takes the at-spaced attitude, said urging portion contacts said coupling member, and said movable portion is spaced from said coupling member; and when said coupling member takes the at-mounting attitude, said urging portion and said movable portion both contact said coupling member.

8. A cartridge according to any one of Claims 2 - 6, wherein said urging portion and said movable portion both contact said coupling member when said coupling member takes the at-spaced attitude and when it takes the at-mounting attitude.

9. A cartridge according to any one of Claims 4 - 6, wherein said urging member and a movable member including said movable portion are provided separately so that said urging portion and said movable portion are movable independently from each other.

10. A cartridge according to any one of Claims 4 - 6, wherein said urging member is mounted to a movable member including said movable portion so that said urging portion moves together with said movable portion.

11. A cartridge according to any one of Claims 4 - 6, wherein said movable portion is capable of urging said urging member.

12. A cartridge according to any one of Claims 4 - 6, wherein when said coupling member takes the at-mounting attitude, said movable portion urges said urging member; and when said coupling member takes the at-spaced attitude, said urging portion urges said coupling member, and said movable portion is spaced from said urging member.

13. A cartridge according to any one of Claims 2 - 6, wherein said urging portion and said movable portion constitute a unitary part.

14. A cartridge according to any one of Claims 3 - 6, wherein when said coupling member takes the at-spaced attitude, said urging portion urges said coupling member, and said movable portion is spaced from said coupling member; and when said coupling member takes the at-mounting attitude, said urging portion is spaced from said coupling member, and said movable portion urges said coupling member.

15. A cartridge according to any one of Claims 1 - 14, wherein as seen along an axial direction of said developer carrying member, a rotational axis of said coupling member taking the at-spaced attitude and the rotational axis of said coupling member taking the at-mounting attitude are substantially perpendicular to each other.

16. A cartridge according to any one of Claims 1 - 15, wherein as seen along the axial direction of said developer carrying member, the angle formed between the rotational axis of said coupling member taking the at-spaced attitude and the rotational axis of said coupling member taking the at-mounting attitude is a value in a range of approximately 30° to

approximately 120°.

17. A cartridge according to Claim 16, wherein as seen along the axial direction of said developer carrying member, the angle formed between the rotational axis of said coupling member taking the at-spaced attitude and the rotational axis of said coupling member taking the at-mounting attitude is a value in a range of approximately 75°.

18. A cartridge according to any one of Claims 1 - 17, wherein as seen along the axial direction of said developer carrying member, an angle formed between a line connecting a center of inclination of said coupling member and said developer carrying member and the rotational axis of said coupling member taking the at-spaced attitude is not more than approximately 30°.

19. A cartridge according to Claim 18, wherein as seen along the axial direction of said developer carrying member, the angle formed between a line connecting a center of inclination of said coupling member and said developer carrying member and the rotational axis of said coupling member taking the at-spaced attitude is approximately 5°.

20. A cartridge according to any one of Claims 15 - 19, wherein as seen along the axial direction of said developer carrying member, an angle formed between a line connecting a center of inclination of said coupling member and said developer carrying member and the rotational axis of said coupling member taking the at-mounting attitude is a value in the range of approximately 45° to approximately 95°.

21. A cartridge according to Claim 20, wherein as seen along the axial direction of said developer carrying member, the angle formed between a line connecting a center of inclination of said coupling member and said developer carrying member and the rotational axis of said coupling member taking the at-mounting attitude is approximately 70°.

22. A cartridge according to any one of Claims 15 - 21, wherein an angle formed between the rotational axis of said coupling member taking the at-spaced attitude and the rotational axis of said coupling member taking a reference attitude is a value in the range of approximately 20° to approximately 60°.

23. A cartridge according to any one of Claims 15 - 21, wherein an angle formed between the rotational axis of said coupling member taking the at-mounting attitude and the rotational axis of said coupling member taking a reference attitude is a value in the range of approximately 20° to approximately 60°.

24. A cartridge according to any one of Claims 2 - 6, wherein said urging portion is capable of directly urging said coupling member.

25. A cartridge according to Claim 4, further comprising an urging elastic member.

26. A cartridge according to Claim 25, wherein said urging portion is provided at a part of said urging elastic member.

27. A cartridge according to Claim 25 or 26, wherein said urging elastic member includes a spring.

28. A cartridge according to Claim 27, wherein said spring is a torsion spring.

29. A cartridge according to Claim 27, wherein said spring is a coil spring.

30. A cartridge according to any one of Claims 3 - 6, wherein said movable portion is capable of taking a movement reference position for placing said coupling member in the reference attitude.

31. A cartridge according to Claim 30, wherein for said movable portion, said movement reference position and said second movement position are in the same position.

32. A cartridge according to any one of Claims 3 - 6, 30 and 31, further comprising a movable member including said movable portion.

33. A cartridge according to Claim 32, wherein said movable member includes an elastic member for movement.

34. A cartridge according to Claim 33, wherein said elastic member for movement includes said movable portion.

35. A cartridge according to Claim 33 or 34, wherein said elastic member for movement includes a spring.

36. A cartridge according to Claim 35, wherein said spring is a torsion spring.

37. A cartridge according to Claim 35, wherein said spring is a coil spring.

38. A cartridge according to any one of Claims 32 - 37, wherein said movable member is rotatable.

39. A cartridge according to any one of Claims 32 - 38, wherein said movable member includes a force receiving portion for receiving a force for moving said movable portion from the first movement position to the second movement position.

40. A cartridge according to Claim 39, wherein said movable member is provided with said force receiving portion at one end thereof and said movable portion at the other end thereof.

41. A cartridge according to Claim 39 or 40, wherein as seen along the rotational axis of said developer carrying member, said force receiving portion is disposed substantially in an opposite side from said developer carrying member with respect to a developing blade.

42. A cartridge according to any one of Claims 1 - 41, wherein said coupling member includes a free end portion provided with a rotational force receiving portion for receiving a rotational force from the main assembly driving shaft, a connection end portion provided with a rotational force transmitting portion for transmitting the rotational force to said developer carrying member, and a connecting portion connecting said free end portion and said connection end portion.

43. A cartridge according to Claim 42 wherein said coupling member includes a positioned portion to be positioned relative to said cartridge when taking said at-spaced attitude and/or the at-mounting attitude.

44. A cartridge according to Claim 43, wherein the positioned portion is provided at said connecting portion.

45. A cartridge according to Claim 43, wherein said positioned portion is provided at said connection end portion.

46. A cartridge according to Claim 45, wherein said positioned portion is provided projected from said connection end portion.

47. A cartridge according to any one of Claims 43 - 46, further comprising an at-spaced positioning portion for positioning said positioned portion to cause said coupling member to take the at-spaced attitude.

48. A cartridge according to Claim 47, further comprising a cartridge frame provided with said at-spaced positioning portion.

49. A cartridge according to Claim 48, wherein said cartridge frame provided with said at-spaced positioning portion includes a supporting member for supporting said developer carrying member, and said supporting member includes said at-spaced positioning portion.

50. A cartridge according to any one of Claims 43 - 49, further comprising an at-mounting positioning portion for positioning said positioned portion to cause said coupling member to take the at-mounting attitude.

51. A cartridge according to Claim 50, further comprising a cartridge frame provided with said at-mounting positioning portion.

52. A cartridge according to Claim 51, wherein said cartridge frame provided with

said at-mounting positioning portion includes a second supporting member for supporting said developer carrying member, and said second supporting member includes the at-mounting positioning portion.

53. A cartridge according to any one of Claims 42 - 52, wherein a maximum rotation radius of at least a part of said connecting portion is smaller than a distance between the rotational axis of said developer carrying member and said rotational force receiving portion.

54. A cartridge according to any one of Claims 42 - 53, wherein said urging portion urges said connecting portion.

55. A cartridge according to Claim 1, further comprising a cartridge frame rotatably supporting said developer carrying member, an end member mounted to an end of said cartridge frame, wherein a movable member including said movable portion and an urging member including said urging portion are provided on said end member.

56. A cartridge mountable, along a predetermined mounting path, to a main assembly of an electrophotographic image forming apparatus including a main assembly driving shaft, said cartridge comprising:

a photosensitive member on which a latent image is capable of being formed;
a developer carrying member capable of developing the latent image and the movable between a developing position contacting said photosensitive member to develop the latent image and a retracted position retracted from the contacting position; and

a coupling member capable of inclining relative to a rotational axis of said developer carrying member, wherein said coupling member is capable of taking a reference attitude in which the drive transmission is capable from the main assembly driving shaft to said developer carrying member when said developer carrying member is in the developing position in a state that said cartridge is mounted at a terminal end of the mounting path, an at-mounting attitude inclined relative to the rotational axis of said developer carrying member to engage with the main assembly driving shaft when said cartridge moves along the mounting path, an at-spaced attitude inclined relative to the rotational axis of said developer carrying member in a direction different from that in the at-mounting attitude to engage with the main assembly driving shaft when said developer carrying member moves from the retracted position to the developing position in the state that said cartridge is mounted at the end portion of the mounting path,

wherein as seen along the axial direction of said developer carrying member, the angle formed between the rotational axis of said coupling member taking the at-spaced attitude and the rotational axis of said coupling member taking the at-mounting attitude is a value in a range of approximately 20° to approximately 150°.

57. A cartridge according to Claim 56, further comprising an urging portion for applying an urging force to incline said coupling member relative to the rotational axis of said developer carrying member.

58. A cartridge according to Claim 57, further comprising a movable portion capable of taking a first movement position for causing said coupling member to take the at-spaced attitude and a second movement position for causing said coupling member to take the at-mounting attitude.

59. A cartridge according to Claim 58, further comprising an urging member including said urging portion.

60. A cartridge according to Claim 59, wherein said movable portion is capable of urging at least one of said coupling member and said urging member at least one of the first movement position and the second movement position.

61. A cartridge according to Claim 60, wherein said movable portion is capable of directly urging at least one of said coupling member and said urging member at least one of the first movement position and the second movement position.

62. A cartridge according to any one of Claims 57 - 61, wherein when said coupling member takes the at-spaced attitude, said urging portion contacts said coupling member, and said movable portion is spaced from said coupling member; and when said coupling member takes the at-mounting attitude, said urging portion and said movable portion both contact said coupling member.

63. A cartridge according to any one of Claims 57 - 61, wherein said urging portion and said movable portion both contact said coupling member when said coupling member takes the at-spaced attitude and taking the at-mounting attitude.

64. A cartridge according to any one of Claims 59 - 61, wherein said urging member and a movable member including said movable portion are provided separately so that said urging portion and said movable portion are movable independently from each other.

65. A cartridge according to any one of Claims 59 - 61, wherein said urging member is mounted to a movable member including said movable portion so that said urging portion moves together with said movable portion.

66. A cartridge according to any one of Claims 59 - 61, wherein said movable portion is capable of urging said urging member.

67. A cartridge according to any one of Claims 59 - 61, wherein when said coupling member takes the at-mounting attitude, said movable portion urges said urging member; and when said coupling member takes the at-spaced attitude, said urging portion urges said coupling member, and said movable portion is spaced from said urging member.

68. A cartridge according to any one of Claims 57 - 61, wherein said urging portion and said movable portion constitute a unitary part.

69. A cartridge according to any one of Claims 57 - 61, wherein when said coupling member takes the at-spaced attitude, said urging portion urges said coupling member, and said movable portion is spaced from said coupling member; and when said coupling member takes the at-mounting attitude, said urging portion is spaced from said coupling member, and said movable portion urges said coupling member.

70. A cartridge according to any one of Claims 56 - 69, wherein as seen along an axial direction of said developer carrying member, a rotational axis of said coupling member taking the at-spaced attitude and the rotational axis of said coupling member taking the at-mounting attitude are substantially perpendicular to each other.

71. A cartridge according to any one of Claims 56-70, wherein as seen along the axial direction of said developer carrying member, the angle formed between the rotational axis of said coupling member taking the at-spaced attitude and the rotational axis of said coupling member taking the at-mounting attitude is a value in a range of approximately 30° to approximately 120°.

72. A cartridge according to Claim 71, wherein as seen along the axial direction of said developer carrying member, the angle formed between the rotational axis of said coupling member taking the at-spaced attitude and the rotational axis of said coupling member taking the at-mounting attitude is a value in a range of approximately 75°.

73. A cartridge according to any one of Claims 70 - 72, wherein as seen along the axial direction of said developer carrying member, an angle formed between a line connecting a center of inclination of said coupling member and said developer carrying member and the rotational axis of said coupling member taking the at-spaced attitude is not more than approximately 30°.

74. A cartridge according to Claim 73, wherein as seen along the axial direction of said developer carrying member, the angle formed between a line connecting a center of inclination of said coupling member and said developer carrying member and the rotational axis of said coupling member taking the at-spaced attitude is approximately 5°.

75. A cartridge according to any one of Claims 70 - 74, wherein as seen along the axial direction of said developer carrying member, an angle formed between a line connecting a center of inclination of said coupling member and said developer carrying member and the rotational axis of said coupling member taking the at-mounting attitude is a value in the range of approximately 45° to approximately 95°.

76. A cartridge according to Claim 75, wherein as seen along the axial direction of said developer carrying member, the angle formed between a line connecting a center of inclination of said coupling member and said developer carrying member and the rotational axis of said coupling member taking the at-mounting attitude is approximately 70°.

77. A cartridge according to any one of Claims 70 - 76, wherein an angle formed between the rotational axis of said coupling member taking the at-spaced attitude and the rotational axis of said coupling member taking the reference attitude is a value in the range of approximately 20° to approximately 60°.

78. A cartridge according to any one of Claims 70 - 76, wherein an angle formed between the rotational axis of said coupling member taking the at-mounting attitude and the rotational axis of said coupling member taking the reference attitude is a value in the range of approximately 20° to approximately 60°.

79. A cartridge according to any one of Claims 57 - 61, wherein said urging portion is capable of directly urging said coupling member.

80. A cartridge according to Claim 59, further comprising an urging elastic member.

81. A cartridge according to Claim 80, wherein said urging portion is provided at a part of said urging elastic member.

82. A cartridge according to Claim 80 or 81, wherein said urging elastic member includes a spring.

83. A cartridge according to Claim 82, wherein said spring is a torsion spring.

84. A cartridge according to Claim 82, wherein said spring is a coil spring.

85. A cartridge according to any one of Claims 58 - 61, wherein said movable portion is capable of taking a movement reference position for placing said coupling member in the reference attitude.

86. A cartridge according to Claim 85, wherein for said movable portion, said movement reference position and said second movement position are in the same position.

87. A cartridge according to any one of Claims 58 - 61, 85 and 86, further comprising a movable member including said movable portion.

88. A cartridge according to Claim 87, wherein said movable member includes an elastic member for movement.

89. A cartridge according to Claim 88, wherein said elastic member for movement includes said movable portion.

90. A cartridge according to Claim 88 or 89, wherein said elastic member for movement includes a spring.

91. A cartridge according to Claim 90, wherein said spring is a torsion spring.
92. A cartridge according to Claim 90, wherein said spring is a coil spring.
93. A cartridge according to any one of Claims 87 - 92, wherein said movable member is rotatable.
94. A cartridge according to any one of Claims 87 - 93, wherein said movable member includes a force receiving portion for receiving a force for moving said movable portion from the first movement position to the second movement position.
95. A cartridge according to Claim 94, wherein said movable member is provided with said force receiving portion at one end thereof and said movable portion at the other end thereof.
96. A cartridge according to Claim 94 or 95, wherein as seen along the rotational axis of said developer carrying member, said force receiving portion is disposed substantially in an opposite side from said developer carrying member with respect to a developing blade.
97. A cartridge according to any one of Claims 56 - 96, wherein said coupling member includes a free end portion provided with a rotational force receiving portion for receiving a rotational force from the main assembly driving shaft, a connection end portion provided with a rotational force transmitting portion for transmitting the rotational force to said developer carrying member, and a connecting portion connecting said free end portion and said connection end portion.
98. A cartridge according to Claim 97, wherein said coupling member includes a positioned portion to be positioned relative to said cartridge when taking said at-spaced attitude and/or the at-mounting attitude.
99. A cartridge according to Claim 98, wherein the positioned portion is provided at said connecting portion.
100. A cartridge according to Claim 98, wherein said positioned portion is provided at said connection end portion.
101. A cartridge according to Claim 100, wherein said positioned portion is provided projected from said connection end portion.
102. A cartridge according to any one of Claims 98 - 101, further comprising an at-spaced positioning portion for positioning said positioned portion to cause said coupling member to take the at-spaced attitude.

103. A cartridge according to Claim 102, further comprising a cartridge frame provided with said at-spaced positioning portion.

104. A cartridge according to Claim 103, wherein said cartridge frame provided with said at-spaced positioning portion includes a supporting member for supporting said developer carrying member, and said supporting member includes said at-spaced positioning portion.

105. A cartridge according to any one of Claims 98 - 104, further comprising an at-mounting positioning portion for positioning said positioned portion to cause said coupling member to take the at-mounting attitude.

106. A cartridge according to Claim 105, further comprising a cartridge frame provided with said at-mounting positioning portion.

107. A cartridge according to Claim 106, wherein said cartridge frame provided with said at-mounting positioning portion includes a second supporting member for supporting said developer carrying member, and said second supporting member includes the at-mounting positioning portion.

108. A cartridge according to any one of Claims 97 - 107, wherein a maximum rotation radius of at least a part of said connecting portion is smaller than a distance between the rotational axis of said developer carrying member and said rotational force receiving portion.

109. A cartridge according to any one of Claims 56 - 108, wherein with movement of said developer carrying member from the developing position to the retracted position, said coupling member moves from the at-mounting attitude to the at-spaced attitude.

110. A cartridge according to any one of Claims 56 - 109, wherein said main assembly further includes a second main assembly driving shaft, and said cartridge including a second coupling member capable of transferring the driving force from the second main assembly driving shaft to said photosensitive member.

111. A cartridge according to Claim 56, further comprising a photosensitive member side supporting frame rotatably supporting said photosensitive member, a development side supporting frame rotatably supporting said developer carrying member, wherein a movable member including said movable portion is provided on said photosensitive member side supporting frame, and an urging member including an urging portion is provided on said development side supporting frame.

112. An electrophotographic image forming apparatus for forming an image on a recording material, said apparatus comprising:

- i) a main assembly including a photosensitive member on which a latent image

is capable of being formed, and including a main assembly driving shaft; and

ii) a cartridge mountable, along a predetermined mounting path, to the main assembly, wherein said cartridge is movable in the main assembly between a developing position at a terminal end of said mounting path and a retracted position retracted from the developing position in a direction different from the mounting path, said cartridge including,

ii-i) a developer carrying member capable of developing the latent image while being in contact with the photosensitive member when said cartridge is in the developing position; and

ii-ii) a coupling member capable of inclining relative to a rotational axis of said developer carrying member, wherein said coupling member is capable of taking a reference attitude in which a drive transmission is capable from the main assembly driving shaft to said developer carrying member when said cartridge is in the developing position, an at-mounting attitude inclined relative to the rotational axis of said developer carrying member to engage with the main assembly driving shaft when said cartridge is moved along the mounting path, and an at-spaced attitude inclined relative to the rotational axis of said developer carrying member in a direction different from that in the at-mounting attitude when said cartridge is moved from the retracted position to the developing position,

wherein as seen along the axial direction of said developer carrying member, an angle formed between the rotational axis of said coupling member taking the at-spaced attitude and the rotational axis of said coupling member taking the at-mounting attitude is a value in a range of approximately 20° to approximately 150°.

113. An electrophotographic image forming apparatus for forming an image on a recording material, said apparatus comprising:

i) a main assembly including a main assembly driving shaft; and

ii) a cartridge mountable to the main assembly along a predetermined mounting path;

ii-i) a photosensitive member on which a latent image is capable of being formed;

ii-ii) a developer carrying member capable of developing the latent image and movable between a developing position in which said developer carrying member contacts said photosensitive member to develop the latent image and a retracted position retracted from the contacting position, in a state that said cartridge is mounted to said main assembly; and

ii-iii) a coupling member capable of inclining relative to a rotational axis of said developer carrying member, wherein said coupling member is capable of taking a reference attitude in which a drive transmission is capable from the main assembly driving shaft to said developer carrying member when said developer carrying member is in the developing position, an at-mounting attitude inclined relative to the rotational axis of said developer carrying member to engage with the main assembly driving shaft when said cartridge is moved along the mounting path, and an at-spaced attitude inclined relative to the rotational axis of said developer carrying member in a direction different from that in the at-mounting attitude to engage with the main assembly driving shaft when said developer carrying member is moved from the retracted position to the developing position

wherein as seen along the axial direction of said developer carrying member,

the angle formed between the rotational axis of said coupling member taking the at-spaced attitude and the rotational axis of said coupling member taking the at-mounting attitude is a value in a range of approximately 20° to approximately 150°.

114. A cartridge mountable, along a predetermined mounting path, to a main assembly of the electrophotographic image forming apparatus including a photosensitive member on which a latent image is capable of being formed and including a main assembly driving shaft, wherein said cartridge is movable in the main assembly between a developing position at a terminal end of said mounting path and a retracted position retracted from the developing position in a direction different from the mounting path, said cartridge comprising:

a developer carrying member capable of developing the latent image while being in contact with the photosensitive member when said cartridge is in the developing position; and

a coupling member capable of inclining relative to a rotational axis of said developer carrying member, wherein said coupling member is capable of taking a reference attitude in which a drive transmission is capable from the main assembly driving shaft to said developer carrying member when said cartridge is in the developing position, an at-dismounting attitude inclined relative to the rotational axis of said developer carrying member to disengage from the main assembly side driving shaft when said cartridge is dismounted from the main assembly by being moved along the mounting path from the developing position in the direction opposite from that in the mounting, and at-spaced attitude inclined relative to the rotational axis of said developer carrying member in a direction different from that in the at-dismounting attitude to disengage from the main assembly driving shaft when said cartridge is moved from the developing position to the retracted position,

wherein as seen along the axial direction of said developer carrying member, an angle formed between the rotational axis of said coupling member taking the at-spaced attitude and the rotational axis of said coupling member taking the at-dismounting attitude is a value in a range of approximately 20° to approximately 150°.

115. A cartridge mountable, along a predetermined mounting path, to a main assembly of an electrophotographic image forming apparatus including a main assembly driving shaft, said cartridge comprising:

a photosensitive member on which a latent image is capable of being formed;
a developer carrying member capable of developing the latent image and movable between a developing position contacting said photosensitive member to develop the latent image and a retracted position retracted from the contacting position; and

a coupling member capable of inclining relative to a rotational axis of said developer carrying member, wherein said coupling member is capable of taking a reference attitude in which a drive transmission is capable from the main assembly driving shaft to said developer carrying member when said cartridge is in the developing position in a state that said cartridge is mounted to a terminal end of the mounting path, an at-dismounting attitude inclined relative to the rotational axis of said developer carrying member to disengage from the main assembly side driving shaft when said cartridge is dismounted from the main assembly by being moved along the mounting path from the terminal end in the direction

opposite from that in the mounting, and an at-spaced attitude inclined relative to the rotational axis of said developer carrying member in a direction different from that in the at-dismounting attitude to disengage from the main assembly driving shaft when said developer carrying member is moved from the developing position to the retracted position in the state that said cartridge is mounted to the terminal end,

wherein as seen along the axial direction of said developer carrying member, an angle formed between the rotational axis of said coupling member taking the at-spaced attitude and the rotational axis of said coupling member taking the at-dismounting attitude is a value in a range of approximately 20° to approximately 150°.

116. A cartridge mountable, along a predetermined mounting path, to a main assembly of an electrophotographic image forming apparatus including a photosensitive member on which a latent image is capable of being formed and including a main assembly driving shaft, wherein said cartridge is movable in the main assembly between a developing position at a terminal end of said mounting path and a retracted position retracted from the developing position in a direction different from the mounting path, said cartridge comprising:

a developer carrying member capable of developing the latent image while being in contact with the photosensitive member when said cartridge is in the developing position; and

a coupling member capable of inclining relative to a rotational axis of said developer carrying member, wherein said coupling member is capable of taking a reference attitude in which a drive transmission is capable from the main assembly driving shaft to said developer carrying member when said cartridge is in the developing position, an at-dismounting attitude inclined relative to the rotational axis of said developer carrying member to disengage from the main assembly driving shaft when said cartridge is dismounted from the main assembly by being moved along the mounting path from the developing position in the direction opposite from that in the mounting path, and an at-spaced attitude inclined relative to the rotational axis of said developer carrying member in a direction different from that in the at-dismounting attitude to engage with the main assembly driving shaft when said cartridge is moved from the retracted position to the developing position,

wherein as seen along the axial direction of said developer carrying member, an angle formed between the rotational axis of said coupling member taking the at-spaced attitude and the rotational axis of said coupling member taking the at-dismounting attitude is a value in a range of approximately 20° to approximately 150°.

117. A cartridge mountable, along a predetermined mounting path, to a main assembly of an electrophotographic image forming apparatus including a main assembly driving shaft, said cartridge comprising:

a photosensitive member on which a latent image is capable of being formed;

a developer carrying member capable of developing the latent image and movable between a developing position contacting said photosensitive member to develop the latent image and a retracted position retracted from the contacting position; and

a coupling member capable of inclining relative to a rotational axis of said developer carrying member, wherein said coupling member is capable of taking a reference

attitude in which a drive transmission is capable from the main assembly driving shaft to said developer carrying member when said cartridge is in the developing position in a state that said cartridge is mounted to a terminal end of the mounting path, an at-dismounting attitude inclined relative to the rotational axis of said developer carrying member to disengage from the main assembly side driving shaft when said cartridge is dismounted from the main assembly by being moved along the mounting path from the terminal end in the direction opposite from that in the mounting path, and an at-spaced attitude inclined relative to the rotational axis of said developer carrying member in a direction different from that in the at-dismounting attitude to engage with the main assembly driving shaft when said developer carrying member is moved from the retracted position to the developing position in the state that said cartridge is mounted to the terminal end,

wherein as seen along the axial direction of said developer carrying member, an angle formed between the rotational axis of said coupling member taking the at-spaced attitude and the rotational axis of said coupling member taking the at-dismounting attitude is a value in a range of approximately 20° to approximately 150°.

118. A cartridge according to any one of claims 114 - 117, further comprising an urging portion for urging said coupling member to incline it relative to the rotational axis of said developer carrying member.

119. A cartridge according to Claim 118, further comprising a movable portion capable of taking a first movement position for causing said coupling member to take the at-spaced attitude and a second movement position for causing said coupling member to take the at-mounting attitude.

120. A cartridge according to Claim 119, further comprising an urging member including said urging portion.

121. A cartridge according to Claim 120, wherein said movable portion is capable of urging at least one of said coupling member and said urging member at least one of the first movement position and the second movement position.

122. A cartridge according to Claim 121, wherein said movable portion is capable of directly urging at least one of said coupling member and said urging member at least one of the first movement position and the second movement position.

123. A cartridge according to any one of Claims 119 - 122, wherein when said coupling member takes the at-spaced attitude, said urging portion contacts said coupling, and said movable portion is spaced from said coupling member; and when said coupling member takes the at-dismounting attitude, both of said urging portion and said movable portion contact said coupling member.

124. A cartridge according to any one of Claims 119 - 122, wherein both of said urging portion and said movable portion contact said coupling member when said coupling

member takes the at-spaced attitude and when said coupling member takes the at-dismounting attitude.

125. A cartridge according to any one of Claims 120 - 122, wherein said urging member and a movable member including said movable portion are provided separately so that said urging portion and said movable portion are movable independently from each other.

126. A cartridge according to any one of Claims 120 - 122, wherein said urging member is mounted to a movable member including said movable portion so that said urging portion moves together with said movable portion.

127. A cartridge according to any one of Claims 120 - 122, wherein said movable portion is capable of urging said urging member.

128. A cartridge according to any one of Claims 120 - 122, wherein when said coupling member takes the at-dismounting attitude, said movable portion urges said urging member; and when said coupling member takes the at-spaced attitude, said urging portion urges said coupling member, and said movable portion is spaced from said urging member.

129. A cartridge according to any one of Claims 119 - 122, wherein said urging portion and said movable portion constitute a unitary part.

130. A cartridge according to any one of Claims 119 - 122, wherein when said coupling member takes the at-spaced attitude, said urging portion urges said coupling member, and said movable portion is spaced from said coupling member; and when said coupling member takes the at-dismounting attitude, said urging portion is spaced from said coupling member, and said movable portion urges said coupling member.

131. A cartridge according to any one of claims 114 - 130, wherein as seen along an axial direction of said developer carrying member, the rotational axis of said coupling member taking the at-spaced attitude substantially crosses with the rotational axis of said coupling member taking the at-dismounting attitude.

132. A cartridge according to Claim 131, wherein as seen along the axial direction of said developer carrying member, an angle formed between the rotational axis of said coupling member taking the at-spaced attitude and the rotational axis of said coupling member taking the at-dismounting position is a value in the range of approximately 20° to approximately 150°.

133. A cartridge according to Claim 132, wherein as seen along the axial direction of said developer carrying member, the angle formed between the rotational axis of said coupling member taking the at-spaced attitude and the rotational axis of said coupling member taking the at-dismounting position is a value in the range of approximately 30° to approximately 120°.

134. A cartridge according to Claim 133, wherein as seen along the axial direction of said developer carrying member, the angle formed between the rotational axis of said coupling member taking the at-spaced attitude and the rotational axis of said coupling member taking the at-dismounting position is approximately 75° .

135. A cartridge according to any one of Claims 131 - 134, wherein as seen along the axial direction of said developer carrying member, an angle formed between a line connecting a center of inclination of said coupling member and said developer carrying member and the rotational axis of said coupling member taking the at-spaced attitude is not more than approximately 30° .

136. A cartridge according to Claim 135, wherein as seen along the axial direction of said developer carrying member, the angle formed between a line connecting a center of inclination of said coupling member and said developer carrying member and the rotational axis of said coupling member taking the at-spaced attitude is approximately 5° .

137. A cartridge according to any one of Claims 131 - 136, wherein as seen along the axial direction of said developer carrying member, an angle formed between a line connecting a center of inclination of said coupling member and said developer carrying member and the rotational axis of said coupling member taking the at-dismounting position is a value in the range of approximately 45° to approximately 95° .

138. A cartridge according to Claim 137, wherein as seen along the axial direction of said developer carrying member, the angle formed between a line connecting a center of inclination of said coupling member and said developer carrying member and the rotational axis of said coupling member taking the at-dismounting position is approximately 70° .

139. A cartridge according to any one of Claims 131 - 138, wherein an angle formed between the rotational axis of said coupling member taking the at-spaced attitude and the rotational axis of said coupling member taking the reference attitude is a value in the range of approximately 20° to approximately 60° .

140. A cartridge according to any one of Claims 131 - 138, wherein an angle formed between the rotational axis of said coupling member taking the at-dismounting position and the rotational axis of said coupling member taking the reference attitude is a value in the range of approximately 20° to approximately 60° .

141. A cartridge according to any one of Claims 118 - 122, wherein said urging portion is capable of directly urging said coupling member.

142. A cartridge according to Claim 120, further comprising an urging elastic member.

143. A cartridge according to Claim 142, wherein said urging portion is provided at a part of said urging elastic member.

144. A cartridge according to Claim 142 or 143, wherein said urging elastic member includes a spring.

145. A cartridge according to Claim 144, wherein said spring is a torsion spring.

146. A cartridge according to Claim 144, wherein said spring is a coil spring.

147. A cartridge according to any one of Claims 119 - 122, wherein said movable portion is capable of taking a movement reference position for placing said coupling member in the reference attitude.

148. A cartridge according to Claim 147, wherein for said movable portion, said movement reference position and said second movement position are in the same position.

149. A cartridge according to any one of Claims 119-122, 147 and 148, further comprising a movable member including said movable portion.

150. A cartridge according to Claim 149, wherein said movable member includes an elastic member for movement.

151. A cartridge according to Claim 150, wherein said elastic member for movement includes said movable portion.

152. A cartridge according to Claim 150 or 151, wherein said elastic member for movement includes a spring.

153. A cartridge according to Claim 152, wherein said spring is a torsion spring.

154. A cartridge according to Claim 152, wherein said spring is a coil spring.

155. A cartridge according to any one of Claims 149 - 154, wherein said movable member is rotatable.

156. A cartridge according to any one of claims 149 - 155, wherein said movable member includes a force receiving portion for receiving a force for moving said movable portion from the first movement position to the second movement position.

157. A cartridge according to Claim 156, wherein said movable member is provided with said force receiving portion at one end thereof and said movable portion at the other end thereof.

158. A cartridge according to Claim 156 or 157, wherein as seen along the rotational axis of said developer carrying member, said force receiving portion is disposed substantially in an opposite side from said developer carrying member with respect to a developing blade.

159. A cartridge according to any one of Claims 114 - 158, wherein said coupling member includes a free end portion provided with a rotational force receiving portion for receiving a rotational force from the main assembly driving shaft, a connection end portion provided with a rotational force transmitting portion for transmitting the rotational force to said developer carrying member and a connecting portion connecting said free end portion and said connection end portion.

160. A cartridge according to Claim 159, wherein said coupling member includes a positioned portion for being positioned relative to said cartridge when it takes the at-spaced attitude and/or the at-dismounting attitude.

161. A cartridge according to Claim 160, wherein the positioned portion is provided at said connecting portion.

162. A cartridge according to Claim 160, wherein said positioned portion is provided at said connection end portion.

163. A cartridge according to Claim 162, wherein said positioned portion is provided projected from said connection end portion.

164. A cartridge according to any one of Claims 160 - 163, further comprising an at-spaced positioning portion for positioning said positioned portion to cause said coupling member to take the at-spaced attitude.

165. A cartridge according to Claim 164, further comprising a cartridge frame provided with said at-spaced positioning portion.

166. A cartridge according to Claim 165, wherein said cartridge frame provided with said at-spaced positioning portion includes a supporting member for supporting said developer carrying member, and said supporting member includes said at-spaced positioning portion.

167. A cartridge according to any one of Claims 160 - 166, further comprising an at-dismounting positioning portion for positioning said positioned portion to cause said coupling member to take the at-dismounting attitude.

168. A cartridge according to Claim 167, further comprising a cartridge frame provided with said at-dismounting positioning portion.

169. A cartridge according to Claim 168, wherein said cartridge frame provided with

said at-dismounting positioning portion includes a second supporting member for supporting said developer carrying member, and said second supporting member includes said at-dismounting positioning portion.

170. A cartridge according to any one of Claims 159 - 169, wherein a maximum rotation radius of at least a part of said connecting portion is smaller than a distance between the rotational axis of said developer carrying member and said rotational force receiving portion.

171. A cartridge according to any one of Claims 159 - 170, wherein said urging portion urges said connecting portion.