

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



Amplified copy

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B41J 5/10		A1	(11) International Publication Number: WO 98/16392
			(43) International Publication Date: 23 April 1998 (23.04.98)
(21) International Application Number: PCT/SE97/01685			(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).
(22) International Filing Date: 9 October 1997 (09.10.97)			
(30) Priority Data: 9603787-4 14 October 1996 (14.10.96) SE			
(71) Applicant (for all designated States except US): COMBITECH TRAFFIC SYSTEMS AB [SE/SE]; P.O. Box 1063, S-551 10 Jönköping (SE).			
(72) Inventors; and (75) Inventors/Applicants (for US only): JOHANSSON, Alf [SE/SE]; Skogsvägen 18, S-560 28 Lekeryd (SE), LEJONBERG, Gunnar [SE/SE]; Hunnerydsvägen 13, S-561 46 Huskvarna (SE).			
(74) Agent: LUNDMARK, Jan-Erik; Saab AB, Patent Dept., S-581 88 Linköping (SE).			

Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

In English translation (filed in Swedish).

(54) Title: KEYBOARD IN STATIONARY VEHICLE CONTROL UNITS

(57) Abstract

A keyboard means in stationary control units (23) in a vehicle. The keys (24) thereof are arranged at an outer edge portion of the unit (23), which has the shape of a thin plate (23), which may be embraced in a pinching movement, preferably a pinching movement between the thumb and some finger. The keys may thus be pressed down from one side of the edge portion while supporting it from the opposite side by another finger. This results in very limited free forces against the unit during operation.

