

DESCRIPTION

PRINT MANAGING SERVER, PRINT MANAGING METHOD, PROGRAM, AND
RECORDING MEDIUM

5

TECHNICAL FIELD

The invention relates to control of a print managing server which is connected to a plurality of printers through a network and stores print data which can be printed by the printer in combination with user information.

10

BACKGROUND ART

Hitherto, a print system of what is called "pull print (accumulation print)" in which only the authenticated user makes a print request to print data which has temporarily been accumulated onto a server from a printing apparatus, thereby enabling the print data to be output from the printing apparatus has been proposed. Thus, the print data corresponding to the authenticated user can be output from a desired printing apparatus.

15

20

For example, in Japanese Patent Application Laid-Open No. 2006-99714, there has been disclosed a print system in which an IC card authenticating process is executed by a multi-function apparatus, print data of the authenticated user is specified by a print managing server, and a print command is transmitted to a print server in which the specified print data has been stored, thereby enabling the

25

print data of the authenticated user to be printed by a desired printing apparatus.

However, in the case of using the foregoing prior art by using authenticating means using, for example, contactless type IC card, once an authentication is made, a subsequent process (printing) is executed. Therefore, the IC card is not necessary until the process of a whole sheet responsive to a job to which an execution of the printing has been instructed is completed (or, the IC card is not necessary at all for the subsequent process), so that another printing can be executed by another printer although the printing is being executed (particularly, when a large quantity of printing is being executed, since it takes a long time until a sheet discharge is long, such a situation is liable to occur).

That is, in the related art, there is such a problem that since one user can simultaneously execute the printing by a plurality of printers, a state of a low security occurs.

DISCLOSURE OF THE INVENTION

An object of the present invention is to provide printers with an increased security by allowing only the printer which has sent user identification information to the print managing server to execute printing.

The invention is directed to a print managing server which is connected to a plurality of printers through a network and stores print data in combination with user

identification information. A reception means is provided to receive user identification information from a first one of the plurality of printers. A data transmission means is provided to transmit print data corresponding to the user
5 identification information received by the reception means to the first printer. A control means is provided to control the data transmission means to stop the transmission of the print data to the first printer in accordance with reception of user identification information identical to the user
10 identification information corresponding to the print data from a second one of the plurality of printers, wherein the control means controls the data transmission means to transmit to the second printer the print data which has not been printed due to the stop of the data transmission.

15 According to the present invention, the print managing server allows only the printer which has sent user identification information to the print managing server to execute printing, thereby providing printers with an increased security.

20 Further features of the present invention will become apparent from the following description of exemplary embodiments with reference to the attached drawings.

BRIEF DESCRIPTION OF DRAWINGS

FIG. 1 is a system constructional diagram illustrating an example of a construction of a print system to which a print managing server of the invention can be applied.

FIG. 2 is a block diagram illustrating a hardware construction of an information processing apparatus which can be applied to a print managing server 100, an authenticating server 200, and a client terminal 400 illustrated in FIG. 1.

FIG. 3 is a block diagram illustrating an example of a hardware construction of a controller unit of a printer 300 illustrated in FIG. 1.

FIG. 4 is a flowchart illustrating an example of a first control processing procedure in the invention.

FIG. 5 is a schematic diagram illustrating an example of a form document management database (print management database) in the invention.

FIG. 6 is a schematic diagram illustrating an example of a printer driver related table in the invention.

FIG. 7 is a flowchart illustrating an example of a second control processing procedure in the invention.

5 FIG. 8 is a schematic diagram illustrating an example of a table for authenticating an IC card in the invention.

FIG. 9 is a schematic diagram illustrating an example of a print management table in the invention.

10 FIG. 10 is a schematic diagram illustrating an example of a list of form document data which is displayed to the printer 300 in the invention.

FIG. 11 is a schematic diagram illustrating an example of a table indicative of the presence or absence of a printer display unit in the invention.

15 FIG. 12 is a diagram for describing a memory map in a recording medium (storage medium) for storing various types of data processing programs which can be read out by each of apparatuses constructing the print system according to the invention.

20

BEST MODE FOR CARRYING OUT THE INVENTION

<First embodiment>

An embodiment of the invention will be described in detail hereinbelow with reference to the drawings.

25

FIG. 1 is a system constructional diagram illustrating an example of a construction of a print system to which a print managing server of the invention can be

applied.

As illustrated in FIG. 1, the print system of the embodiment has such a construction that one or a plurality of client terminals 400 (for example, every user), a plurality of printers 300 (printer A 300a, printer B 300b, ...), a print managing server 100, and an authenticating server 200 are connected through a local area network (LAN) 500.

Form document producing software for obtaining form and text data necessary to produce a form document from a server (not shown), executing an overlay, and producing the form document has been installed in the client terminal 400. The form document producing software transmits the produced form document to the print managing server 100 together with a print execution command of the form document and user information by using communication such as SOAP or the like.

A printer driver has been installed in the print managing server 100, the received form document (print data) is accumulated, and the print data is transmitted to the printer 300 through the printer driver according to an output instruction from the printer 300.

The authenticating server 200 stores a table for authenticating an IC card (FIG. 8) and executes an authenticating process by using the IC card authenticating table according to an authenticating request from the printer 300 based on identification information (manufacturing number or the like of the IC card) read out of the IC card.

A hardware construction of an information processing

apparatus which can be applied to the client terminal 400, print managing server 100, and authenticating server 200 illustrated in FIG. 1 will be described hereinbelow by using FIG. 2.

5 FIG. 2 is a block diagram illustrating the hardware construction of the information processing apparatus which can be applied to the print managing server 100, authenticating server 200, and client terminal 400 illustrated in FIG. 1.

10 In FIG. 2, a CPU 201 unitarily controls devices and controllers connected to a system bus 204. A BIOS (Basic Input/Output System) as a control program and an operating system program (hereinbelow, OS) of the CPU 201, various types of programs, which will be described hereinafter, for
15 realizing functions which are executed by each server or each PC, and the like have been stored in a ROM 202 or an external memory 211.

A RAM 203 functions as a main memory, a work area, or the like of the CPU 201. The CPU 201 loads programs and
20 the like necessary for executing processes into the RAM 203 from the ROM 202 or the external memory 211 and executes the loaded programs, thereby realizing various kinds of operations.

An input controller 205 controls an input from a
25 keyboard (KB) 209, a pointing device such as a mouse (not shown), or the like. A video controller 206 controls a display onto a display such as a CRT display (CRT) 210 or

the like. Although the CRT 210 is illustrated in FIG. 2, the display is not limited only to the CRT but may be another display such as a liquid crystal display or the like. They are used by the administrator as necessary.

5 A memory controller 207 controls an access to an external memory 211 such as hard disk (HD), flexible disk (FD), compact flash (registered trademark) memory which is connected to a PCMCIA card slot through an adaptor, or the like in which a boot program, various types of applications,
10 font data, a user file, an edition file, various kinds of data, and the like are stored.

 A communication I/F controller 208 is connected to an external apparatus through a network (for example, LAN 500 illustrated in FIG. 1), communicates with the external
15 apparatus, and executes a communication control process on the network. For example, communication using a TCP/IP or the like can be made.

 The CPU 201 executes, for example, a developing (rasterizing) process of an outline font into an area for
20 display information in the RAM 203, thereby enabling a display to be performed on the CRT 210. The CPU 201 enables the user to make an instruction by using a mouse cursor or the like (not shown) on the CRT 210.

 Various types of programs, which will be described
25 hereinafter, for realizing the invention have been recorded in the external memory 211. Those programs are loaded into the RAM 203 as necessary and executed by the CPU 201. Further,

a definition file, various kinds of information tables, and the like which are used upon execution of the programs have also been stored in the external memory 211 and a detailed description about them will be also made hereinafter.

5 Subsequently, a hardware construction of a controller unit for controlling a printer 300 illustrated in FIG. 1 will be described by using FIG. 3.

FIG. 3 is a block diagram illustrating an example of the hardware construction of the controller unit of the printer 300 illustrated in FIG. 1.

10 In FIG. 3, a controller unit 316 is connected to a scanner unit 314 functioning as an image input device and a printer unit 312 functioning as an image output device and is connected to a LAN (for example, LAN 500 illustrated in FIG. 1) and a public line (WAN) (for example, PSTN, ISDN, or the like), thereby inputting and outputting image data and device information.

15 In the controller unit 316, a CPU 301 is a processor for controlling the whole system. A RAM 302 is a system work memory for allowing the CPU 301 to operate. The RAM 302 is also a program memory for recording the program and an image memory for temporarily recording the image data.

20 The boot program of the system and various types of control programs have been stored in a ROM 303. A hard disk drive (HDD) 304 stores the various types of programs for controlling the system, the image data, and the like.

25 An operation unit interface (operation unit I/F) 307

is an interface unit with an operation unit (UI) 308 and outputs the image data which is displayed onto the operation unit 308 to the operation unit 308. The operation unit I/F 307 plays a role for transferring information (for example, user information and the like) input from the operation unit 308 by the user of the system to the CPU 301. The operation unit 308 has a display unit having a touch panel. The user depresses (touches with a finger or the like) a button displayed on the display unit and can make various kinds of instructions.

A network interface (Network I/F) 305 is connected to the network (LAN) and inputs and outputs data. A modem (MODEM) 306 is connected to the public line and executes input/output of the data such as transmission/reception or the like of FAX.

An external interface (external I/F) 318 is an I/F unit such as USB, IEEE1394, printer port, RS-232C, or the like for receiving an external input. In the embodiment, a card reader 319 for reading an IC card (storage medium) necessary in the authentication is connected to the external I/F unit 318. Through the external I/F 318, the CPU 301 controls the reading of information from the IC card by the card reader 319 and can obtain the information read out of the IC card. The foregoing devices are arranged on a system bus 309.

An image bus interface (IMAGE BUS I/F) 320 is a bus bridge for connecting the system bus 309 to an image bus

315 to transfer the image data at a high speed and converting a data structure.

The image bus 315 is constructed by a PCI bus or IEEE1394. The following devices are arranged on the image
5 bus 315.

A raster image processor (RIP) 310 develops, for example, vector data such as a PDL code or the like into a bit map image. A printer interface (printer I/F) 311 connects the printer unit 312 to the controller unit 316
10 and executes a conversion of a synchronous system/asynchronous system of the image data. A scanner interface (scanner I/F) 313 connects the scanner unit 314 to the controller unit 316 and executes the conversion of the synchronous system/asynchronous system of the image
15 data.

An image processing unit 317 executes a correction, a modification, or an edition to the input image data or executes a correction, a resolution conversion, or the like of the printer to the print output image data. In addition
20 to them, the image processing unit 317 executes a rotation of the image data, executes a compressing/decompressing process of JPEG to multi-value image data, or executes a compressing/decompressing process such as JBIG, MMR, MH, or the like to binary image data.

25 The scanner unit 314 illuminates an image on paper as an original document and scans it by a CCD line sensor, thereby converting it into an electric signal as raster image

data. The sheets for the original are set onto a tray of a document feeder. When the user of the apparatus instructs the reading and activation from the operation unit 308, the CPU 301 instructs the scanner unit 314, the feeder feeds
5 the original sheets one by one, and the reading operation of the original image is executed.

The printer unit 312 is a portion for converting the raster image data into an image on the sheet. As a converting system, there is an electrophotographic system using a
10 photosensitive drum and a photosensitive belt, an ink jet system for discharging ink from a micro-nozzle array and directly printing the image onto the sheet, or the like, and an arbitrary system may be used. The activation of the printing operation is started by an instruction from the
15 CPU 301. The printer unit 312 has: a plurality of sheet feeding stages so that a different sheet size or a different sheet orientation can be selected; and sheet cassettes corresponding to the sheet feeding stages.

The operation unit 308 has an LCD display unit. A
20 touch panel sheet has been adhered onto an LCD. An operation display screen of the system is displayed and when one of displayed keys is pressed, its position information is transferred to the CPU 301 through the operation unit I/F 307. The operation unit 308 has, for example, a start key,
25 a stop key, an ID key, a reset key, and the like as various kinds of operation keys.

The start key in the operation unit 308 is used when

the reading operation of the original image is started or the like. LEDs of two colors of green and red are provided in a center portion of the start key and whether or not the start key is in a usable state is shown by the color. The
 5 stop key in the operation unit 308 functions to stop the operation which is being executed. The ID key in the operation unit 308 is used when a user ID of the user is input. The reset key is used when settings from the operation unit are initialized.

10 The card reader 319 reads the information stored in an IC card (for example, FeliCa (registered trademark) of Sony Corporation) and notifies the CPU 301 of the read information through the external I/F 318 by control from the CPU 301.

15 By the construction as mentioned above, the printer 300 can transmit the image data read out of the scanner unit 314 onto the LAN 500 or allow the print data received from the LAN 500 to be printed and output by the printer unit 312.

20 The image data read out of the scanner unit 314 can be transmitted onto the public line via the FAX by the modem 306 or the image data received from the public line via the FAX can be output by the printer unit 312.

25 A process regarding the accumulation of the form document in the invention will be described hereinbelow with reference to a flowchart of FIG. 4.

FIG. 4 is the flowchart illustrating an example of

a first control processing procedure in the invention and corresponds to the process regarding the accumulation of the form documents in the invention.

5 In the flowchart, S1 corresponds to a step of the client terminal 400 and is realized by a method whereby a CPU of the client terminal 400 executes, on the RAM, a program stored in the external memory.

10 S2 and S3 correspond to steps of the print managing server 100 and are realized by a method whereby a CPU of the print managing server 100 executes, on the RAM, the program stored in the external memory.

15 First, in step S1, the CPU of the client terminal 400 obtains the text data and form data from the server (not shown), executes the overlay, and produces form document data. Further, the CPU of the client terminal 400 transmits the produced form document data to the print managing server 100. When the form document is transmitted, a user name (user information), a document name, and a processing instruction (print command here) are transmitted together
20 with the form document data.

It is also possible to construct so that the form document data is transmitted from a plurality of client terminals 400.

25 In step S2, the CPU of the print managing server 100 executes a receiving process to the form document data transmitted from the client terminal 400.

Subsequently, in step S3, the CPU of the print managing

server 100 accumulates the form document data received in S1 into a form document management database (constructed in the HD of the print managing server 100) in a form as illustrated in FIG. 5.

5 The printer driver has been installed in the print managing server 100. A printer name, an IP address, and a printer driver name are stored and managed in the HD of the print managing server 100 in combination with each other as illustrated in a printer driver related table in FIG.

10 6.

FIG. 5 is a schematic diagram illustrating an example of the form document management database (print management database) in the invention.

As illustrated in FIG. 5, the form document management database (print management database) is constructed by a
15 time stamp 501, a username 502, a document name 503, a printing state 504, and form document data 505.

The time stamp 501 indicates a time/date when the print managing server 100 has received the form document
20 data. The user name 502 and the document name 503 correspond to the user name (user information) and the document name received from the client terminal 400 together with the form document data.

FIG. 6 is a schematic diagram illustrating an example
25 of the printer driver related table in the invention.

As illustrated in FIG. 6, the printer driver related table is constructed by a printer name 601, a printer IP

address 602, and a printer driver name 603.

Processes regarding the printing based on a print instruction from the printer in the invention will be described hereinbelow with reference to a flowchart of FIG. 7.

FIG. 7 is the flowchart illustrating an example of a second control processing procedure in the invention and corresponds to the processes regarding the printing based on the print instruction from the printer in the invention.

In the flowchart, S101 and S102 correspond to steps of the authenticating server 200 and are realized by a method whereby a CPU of the authenticating server 200 executes, on the RAM, the program stored in the external memory.

In the flowchart, S201 to S208 correspond to steps of the printer 300 (although a description will be made here on the assumption that it is the printer A 300a, it may be an arbitrary printer) and are realized by a method whereby the CPU 301 of the printer A 300a executes, on the RAM, the program stored in the ROM 303.

In the flowchart, S301 to S313 correspond to steps of the print managing server 100 and are realized by a method whereby the CPU of the print managing server 100 executes, on the RAM, the program stored in the external memory.

In the flowchart, S401 and S402 correspond to steps of the printer 300 (although a description will be made here on the assumption that it is the printer B 300b, it may be an arbitrary printer so long as it differs from the printer

which executes S201 to S208) and are realized by a method whereby the CPU 301 of the printer B 300b executes the program stored in the ROM 303.

First, in step S201, when it is detected that the
5 IC card has been put over the card reader 319, the CPU 301 of the printer A 300a reads out the detected card manufacturing number (identification information of the IC card) and transmits to the authenticating server 200 (card authentication).

10 In the authenticating server 200, when the identification information of the IC card transmitted from the printer A 300a is received, in step S101, the CPU of the authenticating server 200 authenticates whether or not the user is an authorized user with reference to the received
15 ID number of the IC card and a table for authenticating the IC card (stored in the HD of the authenticating server 200) illustrated in FIG. 8.

FIG. 8 is a schematic diagram illustrating an example of the table for authenticating the IC card in the invention.

20 As illustrated in FIG. 8, the IC card authenticating table is constructed by a card manufacturing number 801, a user name 802, an E-mail address 803, a division ID 804, a division password 805, an administrator's authorization 806, and the like.

25 The description is returned to the description of the flowchart of FIG. 7 hereinbelow.

Subsequently, in step S102, the CPU of the

authenticating server 200 transmits an authentication result of S101 to the printer (printer A 300a) which has requested the authentication. Specifically speaking, if the received card manufacturing number has been registered
5 in the IC card authenticating table, it is determined that the user has been authenticated (normal authentication). The authentication result including the user name 802 in the IC card authenticating table is transmitted to the printer A 300a. If the received card manufacturing number is not
10 registered in the IC card authenticating table, an authentication error is determined and the authentication result including information showing the authentication error is transmitted to the printer A 300a.

Subsequently, in the printer A 300a, when the
15 authentication result transmitted from the authenticating server 200 is received, in step S202, based on the received authentication result, the CPU 301 of the printer A 300a discriminates whether or not the user has been authenticated as a regular user. If it is decided that the user is not
20 authenticated as a regular user (no user information is included in the authentication result), the processing routine is returned to the initial state.

If it is decided in step S202 that the user has normally been authenticated (the user information is included in the
25 authentication result), the CPU 301 of the printer A 300a advances the process to step S203.

Subsequently, in step S203, based on the user name

included in the received authentication result, the CPU 301 of the printer A 300a requests the print managing server 100 to send a list of information of the image data which is not printed yet (list of form document information of the authenticated user) (send an information list transmission request command). The user name and the printer name (it may be an IP address) are also included in the information list transmission request command.

Subsequently, in the print managing server 100, when the information list transmission request command transmitted from the printer A 300a is received, in step S301, the CPU of the print managing server 100 discriminates whether or not the user name included in the received information list transmission request command indicates the user who is in a state where the printing process has already been being executed for another printer (the user name has been stored in a print management table stored in the HD of the print managing server 100 together with the printer name different from the above printer name).

FIG. 9 is a schematic diagram illustrating an example of the print management table in the invention.

As illustrated in FIG. 9, the print management table is constructed by a user name 901, a printer name 902, an IP address 903, and time stamps 904 of the selected form documents (time stamps of the selected number exist).

In this print management table, when the print request command is received from the printer 300, information (the

user name, the printer name, the IP address, the time stamps of the selected form documents (a plurality of time stamps are possible)) corresponding to the print request command is stored. After completion of the printing of all data
5 corresponding to the print request command, the information corresponding to the print request is deleted.

The description is returned to the description of the flowchart of FIG. 7 hereinbelow.

If it is determined in step S301 that the user name
10 included in the received information list transmission request command does not indicate the user who is in the state where the process has already been being executed (the user name and the printer name included in the received information list transmission request command are not stored
15 in the print management table together with the printer name different from the printer name included in the received information list transmission request command), the CPU of the print managing server 100 advances the process to step S305.

20 In step S305, the CPU of the print managing server 100 obtains the non-print form document data corresponding to the user name included in the received information list transmission request command with reference to the form document management database illustrated in FIG. 5.

25 In step S306, the CPU of the print managing server 100 transmits a list of the form document data (form document data list) in the non-printing state corresponding to the

user name included in the received information list
transmission request command obtained in S305 to the printer
300 (printer A 300a here) which has issued the information
list transmission request command. It is now assumed that
5 the document name, user name, and time stamp (it may be an
ID) of the form document are included as information which
is transmitted as a form document data list mentioned above.

Subsequently, in the printer A 300a, when the form
document data list transmitted from the print managing server
10 100 is received, in step S204, the CPU 301 of the printer
A 300a displays the received form document data list onto
the display unit of the operation unit 308.

FIG. 10 is a schematic diagram illustrating an example
of the form document data list which is displayed to the
15 printer 300 in the invention.

In FIG. 10, a form document data selecting area 1001
is shown. The user selects by touching the form document
data to be printed from the form document data selecting
area 1001 (a plurality of form document data can be selected).

20 By touch-instructing a print (Print) button 1002,
the user can request the print managing server 100 to print
the form document data which is in the selecting state in
the form document data selecting area 1001.

The description is returned to the description of
25 the flowchart of FIG. 8 hereinbelow.

When the form document data is selected in the form
document data selecting area 1001 and the print button 1002

is touch-instructed, in step S205, the CPU 301 of the printer A 300a transmits the list of the form documents selected in the form document data selecting area 1001 (information (time stamps) of one or more of the selected form document data) as a print request command to the print managing server 100 together with the user name and the printer name (or IP address).

Subsequently, in the print managing server 100, when the print request command (user name, printer name (or IP address), information (time stamps) of one or a plurality of form documents) transmitted from the printer A 300a is received, in step S307, the CPU of the print managing server 100 obtains (decides) the form document data serving as a print target based on the information (time stamps) of one or a plurality of form documents included in the received print request command. When the print request command is received, the CPU of the print managing server 100 records the information (time stamps) of one or a plurality of form documents included in the received print request command into a print management table illustrated in FIG. 9 together with the user name, the printer name, and the IP address of the printer. Thus, which user prints which form document data by using which printer can be discriminated.

Subsequently, in step S308, the CPU of the print managing server 100 outputs (transmits) the form document data decided in S307 to the printer 300 (printer A 300a here) indicated by the corresponding printer name 902 and IP address

903 in the print management table. In this instance, the printer driver is selected by searching the printer driver related table (FIG. 6) based on the printer name 902 stored in the print management table. The print data of the form document data is output (transmitted) to the printer A through the selected printer driver.

Subsequently, in the printer A 300a, when the print data of the form document data which has been output from the print managing server 100 through the printer driver is received, the CPU 301 of the printer A 300a executes the print output based on the received print data of the form document data in step S206.

When the print output based on the print data of the form document data is completed, in step S207, the CPU 301 of the printer A 300a notifies the print managing server 100 of the print completion. It is assumed that the notification of the print completion is made by using the time stamp of the form document data corresponding to the print data whose printing has been completed. The time stamp is included in the print data (for example, header).

Subsequently, in the print managing server 100, when the notification of the print completion transmitted from the printer A 300a is received, in step S309, the CPU of the print managing server 100 sets the printing state in the form document database of the form document data corresponding to the completion-notified print data into "completion" based on the time stamp which is being processed

at present, and deletes the time stamp of the corresponding form document from the print management table.

Subsequently, in step S309, the CPU of the print managing server 100 discriminates whether or not the printing of all form documents corresponding to the relevant user has been completed (whether or not all of the selected time stamps 904 of the corresponding user in the print management table have been deleted). If it is determined that the printing of all of the form documents is not completed yet, the process is returned to step S307.

If it is determined in step S309 that the printing of all of the form documents corresponding to the relevant user has been completed (all of the selected time stamps 904 of the corresponding user in the print management table have been deleted), the process advances to step S311.

In step S311, the CPU of the print managing server 100 notifies the printer (printer A 300a here) corresponding to the corresponding printer name 902 and IP address 903 in the print management table that the printing has been completed (print completion notification).

Subsequently, in the printer A 300a, when the print completion notification transmitted from the print managing server 100 is received, in step S207, the CPU 301 of the printer A 300a executes a post-process such as cancellation (log off) of the authenticating state, release of the system, or the like.

Subsequently, in step S207, the CPU 301 of the printer

A 300a displays a message indicative of the end of the printing onto the display unit of the operation unit 308 of the printer A 300a in order to notify the user that the printing of all of the selected form document data has been completed.

5 When the completion notification in S311 is finished, in step S312, the CPU of the print managing server 100 deletes the information (record) in the print management table corresponding to the user in which the printing of all of the selected form document data has been completed.

10 If it is decided in step S301 that the user name included in the received information list transmission request command indicates the user who is in the state where the process has already been being executed (the user name and the printer name included in the received information list transmission request command have been stored in the print management table together with the printer name different from the printer name included in the received information list transmission request command), the CPU of the print managing server 100 advances the process to step
15 S302. The case where this process is executed corresponds to the case where, for example, the user authentication has already been made in the printer B 300b and the printing of the form document data corresponding to the user has been executed.

25 In step S302, since it has been decided that the user responsive to the information list transmission request command is in the state where the printing process has already

been being executed by another printer, the CPU of the print managing server 100 decides the processing situation of the print managing server 100 to such another printer that the process has been finished at present point of time.

5 Subsequently, in step S303, the CPU of the print managing server 100 confirms about the presence or absence of the process which has already been being printed by another printer, and starts to prepare for shifting to the cancelling operation of the form document data of the sheet which has
10 already been being discharged as printed matter which needs to be cancelled or the form document data which has been scheduled to be printed. In order to cancel the print reservation of the data whose printing has been reserved for such another printer and to stop a sheet discharging
15 process to the printer with respect to the data of the sheet which is being discharged, the process is advanced to step S303.

 In step S303, the CPU of the print managing server 100 cancel the printing for such another printer (it is
20 assumed to be the printer B 300b here). In detail, if it is determined in step S302 that the printer is not under printing at present but is in a print reservation state, the CPU of the print managing server 100 does not execute anything to the printer B 300b. If it is determined that
25 the printer is in a state where the print data of the sheet which is being discharged has been transmitted to the printer B 300b, a print cancelling instruction is transmitted to

the printer B 300b in order to notify the printer B 300b of the interruption and end of the print data which is being transmitted at present. In this instance, the CPU of the print managing server 100 transmits a message showing that the printing process of the printer B 300b has been cancelled to the printer A 300a. Thus, the printer A 300a which is being used by the user at present can be informed that the printing by the printer B 300b which was authenticated before has been cancelled. Therefore, the user is enabled to recognize until which portion of the data it can be printed by the printer B 300b and from which portion of the data the printer A 300a is allowed to print. It is also possible to construct in such a manner that a list of form documents which could be printed by the printer B 300b is included in the above message, such a list is displayed in another window onto the display unit of the operation unit 308 of the printer A 300a, and the user is allowed to easily discriminate it.

It is also possible to construct in such a manner that when the IC card is inserted into the printer A 300a, a display screen to confirm a status of a job which is being processed in the printer B 300b is displayed onto the operation panel. The user confirms the status of the job which is being processed and subsequently makes a predetermined instruction on the operation panel of the printer A 300a. In response to the predetermined instruction, a command to control the printer B 300b is

transmitted from the printer A 300a to the print managing server 100. When the printer B 300b receives the command from the print managing server 100, the printer B 300b cancels a portion which is not processed yet in the user's job which is being processed. Thus, in the printer A 300a, the user can also select about the cancellation after confirming the status of the job of the printer B 300b.

In the printer B 300b, when the print cancelling instruction transmitted from the print managing server 100 is received, in step S401, the CPU 301 of the printer B 300b interrupts the printing process after the sheet of the print data which is being printed by the printer B 300b was discharged.

Subsequently, in step S402, in order to notify the user that the printing of the printer B 300b has been interrupted (cancelled and finished), the CPU 301 of the printer B 300b displays a message showing that the printing has been cancelled onto the display unit of the operation unit 308 of the printer B 300b.

In the print managing server 100, by executing the processes of S302 and S303, all of the print data of the user which has newly requested is returned to the initial state.

Subsequently, in step S304, the CPU of the print managing server 100 changes the printer name 902 corresponding to the authenticated user name (user name included in the information list transmission request

command) in the print management table to the printer name of the printer name (printer A 300a here) included in the information list transmission request command.

When the process of step S304 is finished, the CPU
5 of the print managing server 100 advances the process to step S305 and obtains information of the non-print form document data corresponding to the authenticated user (user name included in the information list transmission request command). If the processes of steps S302 and S303 have been
10 executed just before S305, the form document data which has already been printed is not handled as non-print form document data because its printing state is "completion".

It is also possible to construct in such a manner that if the form document was produced by the user and the
15 print managing server received and accumulated the form document data while the user is authenticated in the printer A, the new form document data may be included in the list display.

As shown above, according to the embodiment, since
20 the output of the same user is not performed from a plurality of printers, a security of the printer can be raised.

The embodiment has been described with respect to the construction of controlling in such a manner that when the print managing server 100 receives the information list
25 transmission request command including the user information and the print request command including the user information from the printer 300 (for example, printer A 300a), if the

printing process corresponding to the user information included in the command is being executed for such another printer (for example, printer B 300b), the printing process which is being executed is stopped for such another printer
5 (printer B 300b) and the process corresponding to the command is executed. However, it is also possible to use a construction of similarly controlling in such a manner that even in the case of a command other than the information list transmission request command and the print request
10 command, when the print managing server 100 receives an arbitrary command including the user information from the printer 300, if the printing process corresponding to the user information included in the command is being executed for such another printer (for example, printer B 300b), this
15 printing process which is being executed is stopped and the process corresponding to the command is executed.

Since command including the user information which is transmitted from the printer 300 is a command which is issued after completion of the authenticating process in
20 the printer 300, by processing it in a manner similar to the information list transmission request command and the print request command, the security of the printer can be raised.

Although the embodiment has been described with
25 respect to the construction of executing the authenticating process based on the IC card manufacturing number stored in the IC card read out by the card reader equipped for the

printer 300, an arbitrary authenticating method can be used. For example, either an authenticating method by a password or a biological authenticating method may be used.

5 As described above, by not processing the command of the same user received from a plurality of printers, the security of the printer can be raised.

The embodiment has been described with respect to the construction of controlling in such a manner that when the print managing server 100 receives the command including the user information from the printer 300 (for example, printer A 300a), if the printing process corresponding to the user information included in the command is being executed for another printer (for example, printer B 300b), this printing process which is being executed is stopped for another printer and the process corresponding to the command is executed.

However, it is also possible to construct in such a manner that when the print managing server 100 receives the command including the user information from the printer 300 (for example, printer A 300a), if the printing process corresponding to the user information included in the command is being executed for another printer (for example, printer B 300b), the command of the printer A 300a is refused and a message for urging an instruction to the user so as to return to the printer B from the printer A which is executing the printing process is displayed at the printer A.

Owing to such a construction as well, by not processing

the command of the same user received from a plurality of printers, the security of the printer can be raised.

<Second embodiment>

5 The above first embodiment has been described with respect to such a construction that in step S303 in FIG. 7, the CPU of the print managing server 100 cancels the print reservation of the form document data whose printing has been reserved for such another printer.

10 In the embodiment, while the time stamp of the form document data whose printing has been reserved is held as it is in the print management table in step S303 in FIG. 7, the CPU of the print managing server 100 controls so as to change the printer name 902 corresponding to the authenticated user name in the print management table to
15 the printer name of the printer name (printer A 300a here) included in the information list transmission request command in step S304.

By using such a construction, for example, the form document data whose printing has been reserved in the printer
20 B 300b is printed as it is by the printer (printer A 300a) which the user has newly authentication processed.

Therefore, the user does not need to select again the form document data selected by the printer B 300b at the printer A 300a, and a troublesomeness of the selecting operation
25 of the user can be reduced.

<Third embodiment>

Although the first embodiment has been constructed

in such a manner that the list of form documents to be printed (FIG. 10) is displayed onto the display unit of the operation unit 308 of the printer 300, in the third embodiment, processes which are executed when the printer 300 which cannot
5 display the list of form document data (FIG. 10) has been connected to the network will be described.

When the printer 300 does not have the display unit (or, there is not a display unit enough to display the list), the CPU of the print managing server 100 does not transmit
10 the list to the printer 300 but controls so as to obtain all of the corresponding form document data and execute the printing of all of the obtained form document data based on the information of the non-print form documents obtained in step S305.

15 In more detail, based on the user name and the printer name (IP address may be used) included in the information list transmission request command transmitted from the printer 300 in step S205 in FIG. 7, the CPU of the print managing server 100 controls so as to discriminate whether
20 or not the printer 300 for executing the printing has the display unit for displaying the list of form document data in the non-printing state.

FIG. 11 is a schematic diagram illustrating an example of a table indicative of the presence or absence of the printer display unit in the invention. It is assumed that the printer display unit presence/absence table has previously been
25 registered in the HD of the print managing server 100.

If it is determined that the printer 300 has the display unit enough to display the list, in step S306, the CPU of the print managing server 100 transmits a list of form document data in the non-printing state to the printer 300.

5 If it is determined that the printer 300 does not have the display unit enough to display the list, in step S306, the CPU of the print managing server 100 decides the form document data based on the user name and the printing state (not printed) after S305 and advances to step S308.

10 In this case, if the authentication has normally been made, the user does not select the form document but all of the non-print form documents corresponding to the user are print-executed.

 In place of the printer display unit presence/absence table illustrated in FIG. 11, it is also possible to construct

15 in such a manner that the printer 300 side is allowed to discriminate the construction of the display unit equipped for the printer 300 and a request (command) which is transmitted to the print managing server 100 in step S203

20 is changed.

 In this case, the CPU 301 of the print managing server 100 is constructed in such a manner that if the printer 300 does not have the display unit (the list cannot be displayed), a form document data batch transmitting request is

25 transmitted to the print managing server 100, and if the printer 300 has the display unit (the list can be displayed), a list of form document data in the non-printing state is

requested.

The print managing server 100 is constructed in such a manner that a type of received request is discriminated, if it is the list request, the list information is transmitted to the printer 300, and if it is the form document data batch transmitting request, the list information is not transmitted, the form document data is specified from the user name included in the received request, and this form document data is printed by the printer 300 corresponding to the received printer name.

Although the first and second embodiments have been constructed in such a manner that the form document data is provided for the print managing server 100 and the print data of the form document data is output from the print managing server 100 to the authenticated printer 300.

However, it is possible to construct in such a manner that the one or a plurality of print servers are provided, the print data (PDL format) is held in the print server, and management information of the print data held in the print server is managed by the print managing server 100. It is also possible to construct in such a manner that the print managing server 100 instructs the print server in which the print data has been accumulated so that, based on the print instruction from the printer 300, the print server outputs the print data corresponding to the instruction to the instructed printer 300.

In the case of the above construction, the form

document data is produced in the client terminal 400 and this form document data is transmitted as print data to the print server through the printer driver. It is now assumed that the print server holds the print data transmitted from
5 the client terminal 400.

It is assumed that the print managing server 100 holds bibliography information (user name, IP address of the print data stored server, path of a storage destination of the print data, document name, time stamp, etc.) of the print
10 data stored in the print server. By holding the bibliography information, the print managing server 100 can recognize in which print server, the print data designated by the printer 300 exists. The print instruction of the designated print data can be made from the print managing server to
15 the print server which holds the print data.

Although the foregoing first to third embodiments have been described with respect to the construction in which the form document data is held in the print managing server 100, the invention can be also applied to such a construction
20 that general print data is held in the print managing server 100.

The constructions and contents of the foregoing various kinds of data are not limited to those mentioned above but, naturally, they may be replaced by other various
25 types of constructions and contents according to a use and an object.

Although one embodiment has been mentioned above,

the invention can adopt an embodiment as, for example, a system, an apparatus, a method, a program, a recording medium, or the like. Specifically speaking, the invention can be applied to a system constructed by a plurality of apparatuses
5 or may be applied to an apparatus constructed by one device.

A construction of data processing programs which can be read out by each of the apparatuses (print managing server 100, authenticating server 200, printer 300, and a client terminal 400) constructing the print system according to
10 the invention will be described hereinbelow with reference to a memory map illustrated in FIG. 12.

FIG. 12 is a diagram for describing the memory map in a recording medium (storage medium) for storing the various types of data processing programs which can be read out by
15 each of the apparatuses (print managing server 100, authenticating server 200, printer 300, and a client terminal 400) constructing the print system according to the invention.

Although not shown in particular, information for
20 managing the program group stored in the recording medium, for example, version information, implementors, and the like are also stored. There is also a case where information depending on the OS or the like of the program reading side, for example, icons for identifying and displaying the
25 programs and the like are also stored.

Further, data depending on the various programs is also managed in the directory. If the program and data which

are installed have been compressed, there is also a case where a program for decompressing them and the like are also stored.

5 The functions illustrated in FIGS. 4 and 7 of the embodiments may be executed by a host computer based on a program installed from the outside. In such a case, the invention is also applied to the case where an information group including the program is supplied to an output apparatus by a recording medium such as CD-ROM, flash memory, FD, or
10 the like or from an external recording medium through the network.

Naturally, the object of the invention is also accomplished by a method whereby the recording medium in which program codes of software for realizing the functions
15 of the embodiments mentioned above have been recorded is supplied to a system or an apparatus, and a computer (or CPU or MPU) of the system or the apparatus reads out and executes the program codes stored in the recording medium.

In this case, the program codes themselves read out
20 of the recording medium construct the novel functions of the invention. The recording medium in which the program codes have been stored constructs the invention.

As a recording medium for supplying the program codes, for example, a flexible disk, a hard disk, an optical disc, a magneto-optic disc, a CD-ROM, a CD-R, a DVD-ROM, a magnetic
25 tape, a non-volatile memory card, a ROM, an EEPROM, a silicon disk, or the like can be used.

Naturally, the invention incorporates not only the case where the computer executes the read-out program codes, so that the functions of the embodiments mentioned above are realized but also the case where the OS (Operating System) which is operating on the computer executes a part or all of actual processes based on instructions of the program codes, and the functions of the embodiments mentioned above are realized by those processes.

Naturally, the invention incorporates the case where the program codes read out of the recording medium are written into a memory equipped for a function expanding board inserted into the computer or a function expanding unit connected to the computer, thereafter, a CPU or the like equipped for the function expanding board or the function expanding unit executes a part or all of actual processes based on instructions of the program codes, and the functions of the embodiments mentioned above are realized by those processes.

The invention can be applied to a system constructed by a plurality of apparatuses or may be applied to an apparatus constructed by one device. Naturally, the invention can be applied to a case where the above functions are accomplished by supplying the program to the system or apparatus. In such a case, the recording medium in which the program expressed by the software for accomplishing the invention has been stored is read out to the system or the apparatus, so that the system or the apparatus can receive the advantages of the invention.

Further, the program expressed by the software for accomplishing the invention is downloaded and read out from a server, a database, or the like on the network by a communication program, so that the system or the apparatus
5 can receive the advantages of the invention.

All constructions obtained by combining each of the foregoing embodiments and their modifications are also incorporated in the invention.

10

This application claims the benefit of Japanese Patent Application No. 2006-355519, filed December 28, 2006, which is hereby incorporated by reference herein in its entirety.

CLAIMS

1. A print managing server which is connected to a plurality of printers through a network and stores print data in combination with user identification information, the plurality of printers including at least first and second printers, said print managing server comprising:

reception means for receiving user identification information from the first printer;

data transmission means for transmitting print data corresponding to the user identification information received by said reception means to the first printer; and

control means for controlling said data transmission means to stop the transmission of the print data to the first printer in accordance with user identification information identical to the user identification information corresponding to the print data received from the second printer,

wherein said control means controls said data transmission means to transmit to the second printer the print data which has not been printed due to the stop of the data transmission.

2. A print managing server according to claim 1, further comprising message transmission means for transmitting a message indicating that the data transmission to the first printer has been stopped to the second printer, when said control means controls said data transmission means to stop the transmission of the print data to the first

printer.

3. A print managing server according to claim 1, further comprising scheduling means for making a schedule such that the print data corresponding to the user
5 identification information received by said reception means is printed in the first printer, wherein said data transmission means transmits the print data scheduled by said scheduling means to the first printer from among the print data corresponding to the user identification information
10 received by said reception means.

4. A print managing server according to claim 3, wherein said scheduling means stores the user identification information received by said reception means, data identification information identifying the print data
15 transmitted by said data transmission means and printer identification information identifying a printer to which the print data is transmitted in combination with each other, and said scheduling means changes the stored printer identification information to printer identification
20 information identifying the second printer such that the print data which has not been printed due to the stop of the data transmission is transmitted to the second printer.

5. A print managing server according to claim 1, further comprising:
25 management means for managing the print data transmitted by said data transmission means as print data which has been printed; and

list transmission means for transmitting, to the first printer, list information on a list of the print data managed by said management means as print data which has not been printed from among the print data corresponding to the user identification information, in response to the reception of the user identification information from the first printer by said reception means.

10 6. A print managing server according to claim 5, further comprising determination means for determining whether the list information is to be transmitted to a certain printer from which the user identification information is received,

15 wherein said list transmission means transmits the list information to the first printer if said determination means determines that the list information is to be transmitted to the first printer, and wherein said data transmission means transmits the print data corresponding to the user identification information received by said reception means to the first printer without transmission of the list information by said list transmission means if said determination means determines that the list information is not to be transmitted to the first printer.

25 7. A print managing server according to claim 1, further comprising:

canceling means for transmitting a cancel command

requesting a printer which is executing printing to cancel the printing; and

status determination means for determining a print status of the first printer when said control means controls
5 said data transmission means to stop the transmission of the print data to the first printer,

wherein if said status determination means determines that the first printer is executing printing, said canceling means transmits the cancel command to the first printer.

10 8. A print system comprising a plurality of printers and a print managing server which is connected to the plurality of printers through a network and stores print data in combination with user identification information, the plurality of printers including at least first and second
15 printers,

wherein the first or second printer comprises:

acceptance means for accepting input of user identification information of the printer; and

information transmission means for transmitting the
20 user identification information accepted by said acceptance means to said print managing server, and

wherein said print managing server comprises:

reception means for receiving the user identification information from the first printer;

25 data transmission means for transmitting print data corresponding to the user identification information received by said reception means to the first printer; and

control means for controlling said data transmission means to stop the transmission of the print data to the first printer in accordance with user identification information identical to the user identification information corresponding to the print data received from the second printer,

wherein said control means controls said data transmission means to transmit to the second printer the print data which has not been printed due to the stop of the data transmission, and

wherein the first or second printer further comprises print means for printing the print data transmitted by said data transmission means.

9. A method of controlling a print managing server which is connected to a plurality of printers through a network and stores print data in combination with user identification information, the plurality of printers including at least first and second printers, said method comprising:

a reception step of receiving user identification information from the first printer;

a data transmission step of transmitting print data corresponding to the user identification information received in said reception step to the first printer; and

a control step of controlling said data transmission step to stop the transmission of the print data to the first printer in accordance with user identification information identical to the user identification

information corresponding to the print data received from the second printer,

wherein said control step controls said data transmission step to transmit to the second printer the print data which has not been printed due to the stop of the data transmission.

10. A method of controlling a print system comprising a plurality of printers and a print managing server which is connected to the plurality of printers through a network and stores print data in combination with user identification information, the plurality of printers including at least first and second printers, said method comprising:

an acceptance step, carried out in the first or second printer, of accepting input of user identification information of the printer; and

an information transmission step, carried out in the first or second printer, of transmitting the user identification information accepted in said acceptance step to the print managing server;

a reception step, carried out in the print managing server, of receiving the user identification information from the first printer;

a data transmission step, carried out in the print managing server, of transmitting print data corresponding to the user identification information received in said reception step to the first printer;

a control step, carried out in the print managing

server, of controlling said data transmission step to stop
the transmission of the print data to the first printer in
accordance with user identification information identical
to the user identification information corresponding to
5 the print data received from the second printer,

wherein said control step controls said data
transmission step to transmit to the second printer the print
data which has not been printed due to the stop of the data
transmission; and

10 a print step, carried out in the first or second
printer, of printing the print data transmitted in said data
transmission step.

11. A computer program, stored in a
computer-readable storage medium, which causes a computer to
15 execute a method of controlling a print managing server which
is connected to a plurality of printers through a network and
stores print data in combination with user identification
information, the plurality of printers including at least
first and second printers, said method comprising:

20 a reception step of receiving user identification
information from the first printer;

a data transmission step of transmitting print data
corresponding to the user identification information
received in said reception step to the first printer; and

25 a control step of controlling said data transmission
step to stop the transmission of the print data to the first
printer in accordance with user identification

information identical to the user identification information corresponding to the print data received from the second printer,

wherein said control step controls said data transmission step to transmit to the second printer the print data which has not been printed due to the stop of the data transmission.

12. A computer program, stored in a computer-readable storage medium, which causes a computer to execute a method of controlling a print system comprising a plurality of printers and a print managing server which is connected to the plurality of printers through a network and stores print data in combination with user identification information, the plurality of printers including at least first and second printers, said method comprising:

an acceptance step, carried out in the first or second printer, of accepting input of user identification information of the printer; and

an information transmission step, carried out in the first or second printer, of transmitting the user identification information accepted in said acceptance step to the print managing server;

a reception step, carried out in the print managing server, of receiving the user identification information from the first printer;

a data transmission step, carried out in the print managing server, of transmitting print data corresponding to the user identification information received in said

reception step to the first printer;

5 a control step, carried out in the print managing server, of controlling said data transmission step to stop the transmission of the print data to the first printer in accordance with user identification information identical to the user identification information corresponding to the print data received from the second printer,

10 wherein said control step controls said data transmission step to transmit to the second printer the print data which has not been printed due to the stop of the data transmission; and

a print step, carried out in the first or second printer, of printing the print data transmitted in said data transmission step.

15