

FLEXIBLE PIPE

5 The invention relates to a flexible pipe for transporting
abrasive slurry, comprising a tubular body of a flexible polymer,
such as rubber, and a multitude of coaxial, wear-resistant rings
provided in the polymer along the length of the tube, which rings
and which tubular body have substantially the same internal
10 diameter.

Such a pipe is known from GB-A-1,573,189.

While the term "pipes" is used herein, the invention also relates
15 to flexible expansion pieces, bends, reducing pieces and
T-pieces. Many of these products are used as flexible couplings
in pipes through which abrasive slurries are pumped. These
products are used in, for example, the dredging industry, the
sand and gravel extraction industry, the diamond mining industry
20 and the oil-sand industry. Developments in the dredging industry
have been such that increasingly abrasive mixtures are being
pumped.

The invention also relates to new pipes which, before use, have
25 a flexible (rubber) internal lining that covers the
wear-resistant rings, part of which flexible internal lining has
worn away after the pipe has been used for some time, as a result
of which the inner surface of the rings becomes exposed, so that

the internal diameter of the rings and that of the tubular body are only at least substantially the same after some period of usage.

5 Pipes for slurry transportation are generally built up of an interior wearing layer of rubber (or another polymer), one or more inlays, possibly steel vacuum rings or a coil and an outer layer. The wear-resistant rings function to slow down the wearing process, for example by preventing sharp objects in the slurry
10 cutting through the rubber wearing layer over a large distance.

Said rings are usually formed of steel plate, cut, rolled and welded. Common kinds of steel are used, but also high-tensile and wear-resistant kinds, such as CreusabroTM and HardoxTM.

15

The object of the invention is to provide a flexible pipe which is more resistant to wear and damage. The thickness of the rings near their inner circumference is to that end larger than the thickness of the rings near their outer circumference.

20

Various properties of the pipe can be improved by using this configuration of the rings, such as the bending radius, the life and the stiffness. In particular the anchoring of the rings in the pipe is improved in this manner.

25

In a preferred embodiment, the cross-section of the aforesaid part of the rings is substantially trapezoidal.

The rings are preferably made by moulding a heated, flowable metal or a ceramic powder in a mould. Cast iron, cast steel, a cast ceramic material and other materials that can be processed
5 by means of a casting technique or sintering or pressing techniques may be used for this purpose. Such techniques enable a high degree of freedom in moulding this type of rings, such as the various rings discussed in the description.

10 The invention will now be explained in more detail in the following description of embodiments thereof, which are illustrated in the figures, in which:

Figure 1 is a schematic, longitudinal sectional view of a part
15 of a flexible pipe provided with wear-resistant rings in various embodiments thereof;

Figures 2, 3 and 4 are cross-sectional views of various embodiments of a wear-resistant ring;

20

Figure 5 is a schematic, longitudinal sectional view of a bent flexible pipe provided with wear-resistant rings according to one embodiment; and

25 Figure 6 is a schematic, a longitudinal sectional view of a conical, flexible pipe provided with wear-resistant rings.

According to figure 1, a flexible pipe 1 that is used in dredging comprises a rubber tubular part 2, which is provided with wear-resistant rings 3, 4, 5, 6 in various embodiments thereof. Figure 1 is merely a schematic representation, in a practical embodiment identical wear-resistant rings 3, 4, 5, 6 will generally be used. Furthermore, besides the rubber tubular part 2 and the rings 3, 4, 5, 6, a flexible pipe 1 will usually also comprise at least an outer layer arranged around the rubber part 2.

10

The wear-resistant rings 3, 4, 5, 6 are provided in coaxial, regularly spaced-apart relationship in the rubber part 2, with the rings 3, 4, 5, 6 and the rubber part 2 having the same internal diameter, so that a substantially smooth inner surface of the flexible pipe 1 alternately consisting of rubber and a wear-resistant material is obtained. The outer surface of the rubber part 2 only consists of rubber.

15

The wear-resistant ring 3 is of rectangular section. The wear-resistant ring 4 is of trapezoidal section, with the thickness of the ring 4 being smaller near the inner diameter than near the outer diameter. The wear-resistant ring 5 is of trapezoidal section, with the thickness of the ring 4 being larger near the inner diameter than near the outer diameter. The wear-resistant ring 6 has a T-shaped section, with the thickness of the ring 6 being smaller near the inner diameter than near the outer diameter.

20

25

According to figure 2 and figure 3, the rings whose shape corresponds to that of the ring 4 of figure 1, is made of materials

30

having two different hardnesses. The ring of figure 2 consists of a subring 71 of a hard, highly wear-resistant material such as hardfacing steel along the inner circumference, and a subring 72 of a ductile, less breakable material such as mild steel along the outer circumference. The ring of figure 3 consists of a hollow ring 82 of a hard, highly wear-resistant material such as hardfacing steel, the cavity of said ring being filled with a ring 81 of circular section made of a ductile, less breakable material, such as mild steel. In figure 4, too, the ring is built up of subrings 91, 92 of materials having two different hardnesses, similar to the ring of figure 2, with this difference that the ring is of rectangular section.

In figure 5, the bent flexible pipe 11 that is used in dredging comprises a rubber, tubular part 12, which is provided with several wear-resistant rings 13. Figure 5 is merely a schematic representation, besides the rubber tubular part 12 and the rings 13, a practical embodiment of a flexible pipe 11 will usually also comprise at least an outer layer arranged around the rubber part 12.

The wear-resistant rings 13 are provided in coaxial, regularly spaced-apart relationship in the rubber part 12, with the rings 13 and the rubber part 12 having the same internal diameter, so that a substantially smooth inner surface of the flexible pipe 11 alternately consisting of rubber and a wear-resistant material is obtained. The outer surface of the rubber part 12 only consists of rubber.

The thickness of the wear-resistant ring 13 is smaller in the inside bend of the pipe than in the outside bend. As a result, the ring 13 is trapezoidal in section in the outside bend, with the thickness of the rings 13 being smaller near the inner diameter than near the outer diameter. In the inside bend, the ring 13 is trapezoidal in section, with the thickness of the rings 13 being larger near the inner diameter than near the outer diameter.

10 According to figure 6, a flexible reducing piece 21 comprises a rubber tubular part 22, whose inner wall and outer wall extend conically, parallel to each other, with a flange 24, 25 being present at the two ends. Wear-resistant rings 23 are provided in the rubber of the conical tubular part 22. Said wear-resistant
15 rings 23 are likewise conical in shape, so that they have a parallelogram-shaped section, such that the inner walls of the conical rings 23 extend parallel with respect to the inner wall of the conical tubular part 22.

20 It can be seen that in the case of the rings shown in figure 6 the inner walls of the rings 23 do not lie in the same plane as the inner wall of the tubular part 22, but that, on the contrary, the rings 23 are surrounded by rubber. Said rubber can wear away in practice, as a result of which the rings 23 will come to lie
25 at the inner surface of the pipe 22 yet. This aspect may also apply to the embodiments that have been previously discussed.

CLAIMS

1. A flexible pipe for transporting abrasive slurry, comprising
a tubular body of a flexible polymer, such as rubber, and a
5 multitude of coaxial, wear-resistant rings provided in the
polymer along the length of the tube, which rings and which
tubular body have substantially the same internal diameter,
characterised in that the thickness of the rings (5, 13) near
their outer circumference is smaller over at least part of
10 their circumference than the thickness of the rings near their
inner circumference.
2. A flexible pipe according to claim 1, wherein the
cross-section of the aforesaid part of the rings (5, 13) is
15 substantially trapezoidal.
3. A flexible pipe according to claim 1 or 2, wherein the rings
(5, 13) are made of cast iron, hard-faced steel or a ceramic
material.