

PROPULSION SYSTEM

TECHNOLOGICAL FIELD

The presently disclosed subject matter relates to propulsion systems, in particular to propulsion systems for air vehicles, in particular for VTOL type air vehicles.

5 BACKGROUND ART

References considered to be relevant as background to the presently disclosed subject matter are listed below:

- US 8,317,126
- US 8,543,262
- 10 - US 8,640,439
- US 2005/284676
- US 2007/057113
- US 2008/184906
- US 2009/145998
- 15 - US 2012/056040
- US 2012/209456
- US 2013/134264
- US 2013/147204
- GB 2,376,928
- 20 - WO 2010/123601
- WO 2013/186009
- "US Special Ops Wants Hybrid Small UAS", Aviation Week, 24 November 2010

Acknowledgement of the above references herein is not to be inferred as
25 meaning that these are in any way relevant to the patentability of the presently disclosed subject matter.

BACKGROUND

There are at least four main categories of VTOL or V/STOL vehicles: where the vehicle has a single propulsion unit adapted for producing vertical as well as horizontal thrust; where the vehicle has separate propulsion units for producing vertical and horizontal thrust; where the vehicle has a propulsion unit for vertical and horizontal thrust, plus a supplemental propulsion unit for vertical thrust; other configurations.

For air vehicles in the vertical take-off and landing (VTOL) category, the power requirements for vectored flight, including vertical take-off (VTO), vertical landing (VL) and hover, are much higher, for example seven times higher, than the power requirements for aerodynamic flight.

GENERAL DESCRIPTION

According to a first aspect of the presently disclosed subject matter there is provided a propulsion system comprising:

- 15 a first propulsion unit configured for being fixedly mounted to an airframe;
- a second propulsion unit;
- a rotor configured for being pivotably mounted with respect to the first propulsion unit to allow selectively pivoting of the rotor from a horizontal mode to a vertical mode;
- 20 a first coupling for selectively coupling and decoupling the rotor with respect to the first propulsion unit;
- a second coupling for selectively coupling and decoupling the rotor with respect to the second propulsion unit, independently of the first coupling.

For example, the rotor configured for being pivotably mounted to the airframe to allow said selectively pivoting of the rotor from a horizontal mode to a vertical mode.

For example, said first propulsion unit comprises an internal combustion engine.

For example, said second propulsion unit comprises an electric motor.

For example, said second propulsion unit is configured to pivot together with said rotor. For example, the second propulsion unit is mounted to the rotor, such that

irrespective of whether the second propulsion unit is coupled or decoupled from the rotor, the second propulsion unit selectively pivots with the rotor as a unit, between the horizontal mode and the vertical mode.

In at least some examples optionally including the above examples: in vertical
5 mode the rotational axis of the rotor is nominally vertical (i.e., either vertical, or within $\pm 5^\circ$ of vertical, or within $\pm 10^\circ$ of vertical, or within $\pm 15^\circ$ of vertical, or within $\pm 20^\circ$ of vertical; in horizontal mode the rotational axis of the rotor is nominally horizontal (i.e., either horizontal, or within $\pm 5^\circ$ of horizontal, or within $\pm 10^\circ$ of horizontal, or within $\pm 15^\circ$ of horizontal, or within $\pm 20^\circ$ of horizontal).

10 For example, said first propulsion unit is reversibly coupled to a first longitudinal side of the rotor, and wherein said second propulsion unit is reversibly coupled to a second longitudinal side of the rotor.

For example, said rotor comprises any one of: one or more propellers; one or more ducted fans; one or more unducted fans.

15 For example, said first propulsion unit has a first power rating and wherein said second propulsion unit has a second power rating. For example, said first power rating is within $\pm 10\%$ of said second power rating. For example, a power rating ratio between said first power rating and said second power rating is between 0.1 and 10. For example, said power rating ratio is 1.0.

20 For example, the first propulsion unit is reversibly coupled to the rotor via a first driveshaft. For example, said first driveshaft comprises a first portion driven by the first propulsion unit and a second portion for driving the rotor when the first driveshaft is coupled to the rotor via the first coupling, wherein in said vertical mode said first portion is at a first angular disposition with respect to said second portion, wherein in
25 said horizontal mode said first portion is at a second angular disposition with respect to said second portion, and wherein said first angular disposition is less than said second angular disposition. For example, said first angular disposition is about 90° in pitch, and wherein said second angular disposition is about 180° in pitch.

In one example, said first driveshaft comprises a universal joint arrangement to
30 allow said first portion and said second portion to pivot between said first angular

disposition and said second angular disposition while concurrently remaining operatively connected to one another to allow torque to be transmitted between said first portion and said second portion. For example, the propulsion system further comprises a shroud member configured for covering the first driveshaft in any angular disposition
5 between said first angular disposition and said second angular disposition. For example, said shroud member comprises a rigid tubular first shroud portion for covering said first portion, a rigid tubular second shroud portion for covering said second portion, and a flexible tubular shroud joint portion for covering the universal joint arrangement, wherein the first shroud portion, the second shroud portion and said shroud joint portion
10 are contiguous. In another example, said first driveshaft comprises a disconnection arrangement to allow said first portion and said second portion to pivot between said first angular disposition in which said first portion is disconnected with respect to said second portion at said disconnection portion, and said second angular disposition in which said first portion is connected with respect to said second portion at said
15 disconnection portion to thereby allow torque to be transmitted between said first portion and said second portion. For example, said disconnection arrangement comprises a first connector portion provided in said first portion and a second connector portion provided in said second portion, wherein the first connector portion frictionally engages and locks with the second connector portion in the second angular disposition.

20 For example, said first coupling comprises a first electrical clutch configured for selectively engaging and disengaging the first propulsion unit with respect to the rotor.

For example, the second propulsion unit is reversibly coupled to the rotor via a second driveshaft.

For example, said second coupling comprises a second electrical clutch
25 configured for selectively engaging and disengaging the second propulsion unit with respect to the rotor.

For example, the rotor is rotatably mounted to a support bracket, the support bracket being pivotable between the horizontal mode and the vertical mode.

For example, said second propulsion unit is configured for selectively generating
30 electrical power when driven by any one of:

(a) said first propulsion unit;

(b) said rotor, which is in wind milling mode and in turn is aerodynamically driven by an airflow.

According to a second aspect of the presently disclosed subject matter there is
5 provided an air vehicle comprising at least one propulsion system as defined according to the first aspect of the presently disclosed subject matter.

For example, the air vehicle further comprises at least one battery operatively connected to the second propulsion unit.

For example, the air vehicle comprises one said propulsion system and two
10 tiltable vectored thrust propulsion units tiltable at least between respective horizontal mode and vertical mode, wherein said propulsion system and said two vectored thrust propulsion units are in triangle configuration.

In one example, said propulsion system is aft mounted along a longitudinal axis of the air vehicle, and said two vectored thrust propulsion units are forward mounted,
15 each said vectored thrust propulsion unit laterally spaced from the longitudinal axis in opposed directions.

In another example, said propulsion system is forward mounted along a longitudinal axis of the air vehicle, and said two vectored thrust propulsion units are aft mounted, each said vectored thrust propulsion unit laterally spaced from the
20 longitudinal axis in opposed directions.

For example, the air vehicle is configured as a manned air vehicle; alternatively, the air vehicle is configured as an unmanned air vehicle (UAV).

According to a third aspect of the presently disclosed subject matter there is provided a method for operating an air vehicle, comprising:

- 25
- providing the air vehicle as defined an air vehicle as defined according to the second aspect of the presently disclosed subject matter;
 - operating the air vehicle in one or more of vertical configuration and horizontal configuration, wherein in vertical configuration said rotor is in

vertical mode, and wherein in horizontal configuration said rotor is in horizontal mode.

For example, the method comprises setting said rotor in horizontal mode, decoupling said rotor from said first propulsion unit and coupling said rotor to said
5 second propulsion unit.

For example, the method is for use in one or more of:

- enabling the second propulsion unit to exclusively provide propulsion for the air vehicle in aerodynamic flight;
- enabling the air vehicle to cruise unpowered to provide silent gliding;
- 10 - enabling the air vehicle to cruise unpowered and using the airflow over the rotor to drive the second propulsion unit to thereby generate electrical power.

For example, the method comprises setting said rotor in vertical mode, decoupling said rotor from said first propulsion unit and coupling said rotor to said second propulsion unit. For example, the method is for use in enabling the at least one
15 propulsion unit to provide vertical propulsion exclusively from the second propulsion unit thereby providing low-noise VTOL operations.

For example, the method comprises setting said rotor in horizontal mode, coupling said rotor to said first propulsion unit and decoupling said rotor to said second propulsion unit. For example, the method is for use in enabling the first propulsion unit
20 to exclusively provide propulsion for the air vehicle in aerodynamic flight.

For example, the method comprises setting said rotor in vertical mode, coupling said rotor to said first propulsion unit and decoupling said rotor to said second propulsion unit. For example, the method is for use in enabling the at least one propulsion unit to provide vertical propulsion exclusively from the first propulsion unit
25 thereby providing low-noise VTOL operations.

For example, the method comprises setting said rotor in horizontal mode, coupling said rotor to said first propulsion unit and coupling said rotor to said second propulsion unit. For example, the method is for use in one or more of:

- enabling the first propulsion unit and the second propulsion unit to provide augmented propulsion for the air vehicle in any one of: conventional take-off; conventional landing; aerodynamic flight;
- enabling the first propulsion unit to exclusively provide propulsion for the air vehicle and using the first propulsion unit to drive the second propulsion unit to thereby generate electrical power.

For example, the method comprises setting said rotor in vertical mode, coupling said rotor to said first propulsion unit and coupling said rotor to said second propulsion unit. For example, the method is for use in enabling the first propulsion unit and the second propulsion unit to provide augmented vertical propulsion for the air vehicle thereby providing augmented VTOL operations.

A feature of at least one example of the presently disclosed subject matter is that the additional the power requirements for vectored flight is provided by an additional propulsion unit that is electrically powered via a battery.

A feature of at least one example of the presently disclosed subject matter is that the first propulsion unit in the form of an internal combustion engine nominally provides power for aerodynamic flight including cruise. At the same time, the second propulsion unit, in the form of an electrical motor and being less efficient in cruise, can be disengaged from the rotor during cruise, which can reduce power loss which could otherwise result associated with heat generated by the electric motor, and which could otherwise have a negative effect on the performance of the air vehicle.

A feature of at least one example of the presently disclosed subject matter is that by enabling selective coupling and decoupling each one of the first propulsion unit and the second propulsion unit (independently from one another) with respect to the rotor, thrust for vectored flight can be provided by the battery-powered electric motor, while thrust for aerodynamic flight is provided by the internal combustion engine. At the same time, the same rotor can be used for vectored flight and for aerodynamic flight, in at least some cases reducing weight requirements and/or difficult design constraints which would otherwise be required, for example.

A feature of at least one example of the presently disclosed subject matter is that providing a single pivotable rotor selectively coupled/decoupled with respect to

each one of the first propulsion unit and the second propulsion unit can provide significantly greater range or endurance and weight saving as compared with a conventional serial hybrid propulsion system in which the internal combustion engine is connected to an alternator for generating electrical energy to an electric motor that
5 drives a rotor.

A feature of at least one example of the presently disclosed subject matter is that providing a single pivotable rotor selectively coupled/decoupled with respect to each one of the first propulsion unit and the second propulsion unit provides thrust redundancy and high energy efficiency, and provides improved performance and weight
10 saving as compared with a conventional serial hybrid propulsion system in which the internal combustion engine is connected to an alternator for generating electrical energy to an electric motor that drives a rotor.

BRIEF DESCRIPTION OF THE DRAWINGS

15 In order to better understand the subject matter that is disclosed herein and to exemplify how it may be carried out in practice, examples will now be described, by way of non-limiting example only, with reference to the accompanying drawings, in which:

Fig. 1(a) schematically illustrates a propulsion system according to a first
20 example of the presently disclosed subject matter, with the rotor in horizontal mode; **Fig. 1(b)** shows the example of Fig. 1(a) with the rotor in vertical mode.

Fig. 2(a) illustrates in partially fragmented isometric view the example of Fig. 1(a) installed in an airframe of an air vehicle, with the rotor in horizontal mode; **Fig. 2(b)** shows in partially fragmented isometric view the example of Fig. 2(a) with the
25 rotor in vertical mode.

Fig. 3(a) illustrates in partially fragmented side view the example of Fig. 2(a), with the rotor in horizontal mode; **Fig. 3(b)** shows in partially fragmented side view the example of Fig. 3(a) with the rotor in vertical mode.

Fig. 4(a) schematically illustrates a propulsion system according to a second example of the presently disclosed subject matter, with the rotor in horizontal mode; **Fig. 4(b)** shows the example of Fig. 4(a) with the rotor in vertical mode.

Fig. 5(a) illustrates in partially fragmented side view an example of the
5 connector of the example of Figs. 4(a) and 4(b), with the rotor in vertical mode; **Fig. 5(b)** shows in partially fragmented side view the example of Fig. 5(a) with the rotor in horizontal mode prior to connection; **Fig. 5(c)** shows in partially fragmented side view the example of Fig. 5(b) with the rotor in horizontal mode subsequent to connection.

Fig. 6(a) is a front/top/side isometric view of an air vehicle of according to an
10 example of the presently disclosed subject matter, with the rotor in horizontal mode and the air vehicle in aerodynamic flight mode; **Fig. 6(b)** is a front/top/side isometric view of the example of Fig. 6(a), with the rotor in vertical mode and the air vehicle in vectored thrust flight mode.

Fig. 7(a) schematically illustrates a propulsion system according to an
15 alternative variation of the examples of Figs. 1(a) to 4(b), with the rotor in horizontal mode; **Fig. 7(b)** shows the example of Fig. 7(a) with the rotor in vertical mode.

DETAILED DESCRIPTION

Referring to Figs. 1(a) to 3(b), a propulsion system for an air vehicle **1** according
20 to a first example of the presently disclosed subject matter, generally designated **100**, comprises a first propulsion unit **200**, a second propulsion unit **300**, a first coupling **400**, a second coupling **500**, and a rotor **600**.

As will become clearer herein, the first propulsion unit **200** is configured for being fixedly mounted to the airframe **2** of the air vehicle **1**, while the rotor **600** is
25 configured for being pivotably mounted with respect to the first propulsion unit **200** (and thus with respect to the air vehicle **1**) to allow selective pivoting of the rotor **600** between a horizontal mode **HM** (Figs. 1(a), 2(a)), in which the rotor **600** can generate horizontal thrust, and a vertical mode **VM** (Figs. 1(b), 2(b)), in which the rotor **600** can generate vertical thrust. As will also become clearer herein, the first coupling **400** is

configured for selectively coupling or decoupling the rotor **600** with respect to the first propulsion unit **200**, while the second coupling **500** is configured for selectively coupling or decoupling the rotor **600** with respect to the second propulsion unit **300**, wherein the coupling/decoupling operation of the first coupling **400** is independent of
5 the coupling/decoupling operation of the second coupling **500**.

In this example, the first propulsion unit **200** comprises an internal combustion engine, and is configured for developing shaft power. The internal combustion engine in this example can be a piston engine or gas turbine engine, or any other type of liquid fuel or gas-fueled engine configured for generating shaft power, for example. While in
10 this example the first propulsion unit has a first power rating **P1** of (i.e., generates nominal maximum power at) about 500kW, in alternative variations of this example the first propulsion unit **200** can be rated for generating different power levels, for example greater than or less than 500kW. In this example, the first power rating is sufficient to provide at least one of vertical take-off (VTO) capability or vertical landing (VL)
15 capability to the air vehicle **1**, together with additional vectored thrust (VT) propulsion units provided in the air vehicle, as will become clearer herein.

In this example, the second propulsion unit **300** comprises an electric motor, powered by a suitable battery (not shown), which can be accommodated in the airframe **2**, for example. While in this example the second propulsion unit **300** has a second
20 power rating **P2** of (i.e., generates nominal maximum power at) about 500kW, in alternative variations of this example the second propulsion unit **300** can be rated for generating different power levels, for example greater than or less than 500kW. In this example, the second power rating **P2** is also sufficient by itself to provide at least one of VTO capability or VL capability to the air vehicle **1**, together with the additional VT
25 propulsion units provided in the air vehicle, as will become clearer herein.

In this example, the ratio **R** of the first power rating **P1** to the second power rating **P2** is about 1.0, ± 0 to 10% of the second power rating **P2**. However, in alternative variations of this example ratio **R** can be any valued between 0.1 and 10, for example, depending on other factors.

30 In this example, the first propulsion unit **200** is reversibly coupled (via the first coupler **300**) to a first longitudinal side of the rotor **600**, and the second propulsion unit

300 is reversibly coupled (via the second coupler **400**) to the (opposed-facing) second longitudinal side of the rotor **600**. Thus, in horizontal mode HM, the first propulsion unit **200** is reversibly coupled to a forward facing side of the rotor **600**, while the second propulsion unit **300** is reversibly coupled to the aft facing side of the rotor **600**.

5 In this example, the second propulsion unit **300** is mounted to the rotor **600** (in particular to second longitudinal side of the rotor **600**), and thus the second propulsion unit **300** pivots together with the rotor **600** between the horizontal mode HM and the vertical mode VM.

A first driveshaft **220** is provided for turning the rotor **600** when engaged thereto
10 via the first coupling **400**, and thus is configured to transmit the shaft power generated by the first propulsion unit **200** to the rotor **600**, when coupled thereto. Thus, the first propulsion unit **200** is reversibly coupled to the rotor **600** via the first driveshaft **220** and first coupler **400**.

A second driveshaft **320** directly turns the rotor **600** when engaged thereto via
15 the second coupling **500**. Thus, the second propulsion unit **300** is reversibly coupled to the rotor **600** via the second driveshaft **320** and second coupler **500**. In this example, the second coupler **500** is axially located between the rotor **600** and the second propulsion unit **300**.

In this example, the first coupling **400** comprises an electrically controlled clutch
20 enabling the first propulsion unit **200** to be selectively engaged or disengaged with respect to the rotor **600** responsive to electrical, electronic or digital commands received from a controller (not shown). Similarly, in this example, the second coupling **500** comprises another electrically controlled clutch enabling the second propulsion unit **300** to be selectively engaged or disengaged with respect to the rotor **600** (independently of
25 operation of the first coupler **400**) responsive to electrical, electronic or digital commands received from the controller. There are many commercially available electrical clutches that can be used directly or adapted for use as the first coupling **400** or as the second coupling **500**.

Referring in particular to Figs. 3(a) and 3(b), the first driveshaft **220** comprises a
30 propulsion unit end portion **221** connected to and driven by the first propulsion unit **200**,

a rotor end portion **222** connected to and for driving the rotor **600**, and a universal joint arrangement **230** connecting together the propulsion unit end portion **221** and the rotor end portion **222**. While in this example, the first coupling **400** is located in the rotor end portion **222**, in alternative variations of this example the first coupling **400** is located in
5 the propulsion unit end portion **221**.

The rotor **600** comprises any suitable arrangement having aerodynamic elements that collectively and aerodynamically generate a thrust force in response to a torque being applied to the rotor, the torque being provided by the shaft power generated by the first propulsion unit **200** and/or the second propulsion unit **300**, depending on the
10 specific mode of operation, as will become clearer herein. The torque is provided about a rotor axis **RA** about which the rotor **600** rotates responsive to the torque to provide the aforementioned thrust. In at least this and other examples: in vertical mode the rotational axis **RA** of the rotor is nominally vertical (i.e., either vertical, or within $\pm 5^\circ$ of vertical, or within $\pm 10^\circ$ of vertical, or within $\pm 15^\circ$ of vertical, or within $\pm 20^\circ$ of vertical;
15 in horizontal mode the rotational axis **RA** of the rotor **600** is nominally horizontal (i.e., either horizontal, or within $\pm 5^\circ$ of horizontal, or within $\pm 10^\circ$ of horizontal, or within $\pm 15^\circ$ of horizontal, or within $\pm 20^\circ$ of horizontal).

In this example, and referring to Figs. 2(a) and 2(b) in particular, the rotor **600** is in the form of a single stage pusher propeller, comprising a hub **610** and six blades **620**
20 radially projecting therefrom. The rotor end portion **222** of the first driveshaft **220** is thus operatively connected to the hub **610**. In alternative variations of this example, the rotor **600** can have more than six blades or fewer than six blades, and/or can include a plurality of stages (at least some of which can be co-rotating or counter-rotating), and/or can be configured as a puller propeller arrangement, and/or can comprise a ducted fan,
25 and/or can comprise an unducted fan, for example.

Referring again to Figs. 2(a) and 2(b), the rotor **600** is rotatably mounted to a support bracket **650**, comprising a bearing ring **652** onto which the hub **610** is rotatably mounted, and two support arms **660** rigidly connected to the hub **610** at an inner end **662** thereof and radially projecting therefrom. The outer ends **664** of the arms **660** are
30 engaged in a respective curvate slot **670** provided in twin spaced booms **12** in the airframe **2**, on either lateral side of the propulsion system **100**. Each curvate slot **670**

has a uniform curvature having a center of rotation located on a pivot axis PA that is parallel to the pitch axis x of the air vehicle **1**. Each curvate slot **670** also has a first mechanical stop **672** and a second mechanical stop **674**, allowing the outer end **664** of the respective arm **660** to move in the slot between the two mechanical stops, while
5 concurrently the rotor **600** and support bracket **650** correspondingly pivot in pitch about the pivot axis PA. Thus, when the outer ends **664** are abutting the first mechanical stop **672** (see Fig. 2(a)) the rotor **600** is in horizontal mode HM, and when the outer ends **664** are abutting the second mechanical stop **674** (see Fig. 2(a)) the rotor **600** is in vertical mode VM. A suitable actuator (not shown) is operatively connected to at least
10 one of the outer ends **664** and selectively moves the outer ends **664** in the respective slots **670**, thereby selectively pivoting rotor **600** about the pivot axis PA between the horizontal mode HM and the vertical mode VM. Additionally, in this example, the actuator can be operated to provide and maintain any desired pivot angle intermediate between the horizontal mode HM and the vertical mode VM, for example to provide a
15 particular corresponding thrust vector intermediate between horizontal thrust and vertical thrust.

Thus, correspondingly, in the vertical mode VM the propulsion unit end portion **221** is at a first angular disposition $\alpha 1$ (in particular, in pitch) with respect to the rotor end portion **222**, whereas in the horizontal mode HM, the propulsion unit end portion
20 **221** is at a second angular disposition $\alpha 2$ (in particular, in pitch) with respect to the rotor end portion **222** (see Figs. 3(a) and 3(b) in particular). In this example, the first angular disposition $\alpha 1$ is about 90° in pitch (i.e., the propulsion unit end portion **221** is orthogonal to the rotor end portion **222**), and the second angular disposition $\alpha 2$ is 180° in pitch (i.e., the propulsion unit end portion **221** is co-axial to the rotor end portion
25 **222**), and thus the first angular disposition $\alpha 1$ is less than the second angular disposition $\alpha 2$. Furthermore, in this example, the propulsion unit end portion **221** is parallel to the longitudinal axis of the air vehicle **1**. However, in alternative variations of this example, the propulsion unit end portion **221** is at a pitch angle θ to the longitudinal axis of the air vehicle, and thus the first angular disposition $\alpha 1$ is different from 90° , and the
30 second angular disposition $\alpha 2$ is different from 180° ; however, in at least some of these examples, the angular difference between the first angular disposition $\alpha 1$ and the second angular disposition $\alpha 2$ generally remains at 90° .

In this example, the universal joint arrangement **230** allows the propulsion unit end portion **221** and the rotor end portion **222** to pivot with respect to one another between the first angular disposition $\alpha 1$ and the second angular disposition $\alpha 2$, while concurrently remaining operatively connected to one another, thereby allowing torque to be transmitted between the propulsion unit end portion **221** and the rotor end portion **222** for the full range of angular dispositions between $\alpha 1$ and $\alpha 2$. Thus, when the first coupler **400** is in the respective coupled configuration, the first propulsion unit **200** transmits torque to the rotor **600** via the first driveshaft **220** for the full range of angular dispositions between $\alpha 1$ and $\alpha 2$, i.e., during hover, aerodynamic flight, and transitions in-between the two.

Optionally, the universal joint arrangement **230** is configured for varying the total length of the first driveshaft **220** between the vertical mode **VM** and horizontal mode **HM** of the rotor **600**.

There are many commercially available universal joints that can be used directly or adapted for use as the universal joint arrangement **230**. One such commercially available universal joint can include, in at least some examples, the Apex Cornay Universal Joint, provided by Apex Fasteners Inc, USA.

In this example, and referring again in particular to Figs. 3(a) and 3(b), the propulsion system **100** further comprises a shroud member **680** covering the driveshaft **220**. The shroud member **680** is configured for covering the driveshaft **220** for the full range of angular dispositions between $\alpha 1$ and $\alpha 2$, and comprises a rigid or semi rigid, tubular first shroud portion **682** covering at least part of the propulsion unit end portion **221** (i.e., that projects aft from a portion of the airframe **2**), a rigid or semi rigid, tubular second shroud portion **684** covering the a rotor end portion **222**, and a flexible tubular shroud joint portion **686** covering the universal joint arrangement **230**. The first shroud portion **682**, the second shroud portion **684** and the shroud joint portion **686** are contiguous. While in this example the shroud joint portion **686** has an accordion-type form including axially spaced ribs, allowing flexing between the first angular disposition $\alpha 1$ and the second angular disposition $\alpha 2$, in alternative variations of this example the shroud joint portion can have any other suitable form that allows such

flexing to accommodate movement of the universal joint arrangement **230** between the vertical mode **VM** and the horizontal mode **HM**.

The propulsion system **100** has a number of operational modes, including at least the following rotor coupling modes, each rotor coupling mode including the rotor in
5 horizontal mode **HM** or in vertical mode **VM**:

- Rotor coupling mode A: rotor horizontal mode **HM**; rotor vertical mode **VM**.
- Rotor coupling mode B: rotor horizontal mode **HM**; rotor vertical mode **VM**
- Rotor coupling mode C: rotor horizontal mode **HM**; rotor vertical mode **VM**
- Rotor coupling mode D: rotor horizontal mode **HM**; rotor vertical mode **VM**

10

Rotor Coupling Mode A

In Rotor Coupling Mode A, the rotor **600** is decoupled to the first propulsion unit **200** by disengagement via the first coupler **400**, and is concurrently coupled to the second propulsion unit **300** via the second coupler **500**.

15 With the rotor **600** in horizontal mode **HM** the second propulsion unit **300** can be used to drive the rotor **600** when the air vehicle is in aerodynamic flight mode, and for example provides low-noise operation, as compared with driving the rotor **600** using the first propulsion unit **200**. Additionally or alternatively, this coupling mode can be used in emergency situations in which, for example, the first propulsion unit **200** fails or
20 malfunctions and cannot generate any power, or there is a shortage of fuel to run the first propulsion unit, or it is otherwise deemed appropriate to decouple the first propulsion unit **200** from the rotor, and thus the second propulsion unit **300** is used as an emergency propulsion unit for aerodynamic flight.

Alternatively, with the rotor **600** in horizontal mode **HM** the second propulsion
25 unit **300** can be used in windmill mode, in which the rotor **600** drives the second propulsion unit **300** when the air vehicle is in aerodynamic gliding flight mode, and the airstream over the rotor **600** turns the rotor **600**. In this mode of operation, the second propulsion unit **300** operates as an electrical generator (the second propulsion unit **300** being configured for operating as an alternator as well as a motor), and this flight mode
30 can be used for recharging the batteries of the air vehicle, for example.

With the rotor **600** in vertical mode **VM** the second propulsion unit **300** can be used to provide vertical thrust to the air vehicle for hover, VTO and/or VL operations. In addition, such vertical thrust is provided in low-noise operation, as compared with driving the rotor **600** using the first propulsion unit **200**.

5 Rotor Coupling Mode B

In Rotor Coupling Mode B, the rotor **600** is coupled to the first propulsion unit **200** via the first coupler **400**, and is concurrently decoupled from the second propulsion unit **300** by disengagement via the second coupler **500**.

With the rotor **600** in horizontal mode **HM** the first propulsion unit **200** is used
10 to drive the rotor **600** when the air vehicle is in aerodynamic flight mode, and enables efficient and long-range cruising and/or endurance.

With the rotor **600** in vertical mode **VM** the first propulsion unit **200** can be used as an emergency back-up propulsion unit to provide vertical thrust to the air vehicle for hover, VTO and/or VL operations, emergency situations in which, for example, the
15 second propulsion unit **300** fails or malfunctions and cannot generate any power, or it is deemed appropriate to decouple the second propulsion unit **300** from the rotor during vectored thrust flight.

Rotor Coupling Mode C

20 In Rotor Coupling Mode C, the rotor **600** is coupled to the first propulsion unit **200** via the first coupler **400**, and is concurrently coupled to the second propulsion unit **300** via the second coupler **500**.

With the rotor **600** in horizontal mode **HM** the first propulsion unit **200** and the second propulsion unit **300** are both used to drive the rotor **600** when the air vehicle is
25 in aerodynamic flight mode, and provides additional thrust than is required for cruising, for example. This coupling mode can be used for a variety of situations in which additional thrust can be required, for example: high air vehicle weight during conventional lift off or landing; greater altitude and/or airspeed than is possible using only one of the first propulsion unit **200** and the second propulsion unit **300**.

Alternatively, with the rotor **600** in horizontal mode **HM** the first propulsion unit **200** is used to drive the rotor **600**, and the rotor **600** is in turn used to drive the second propulsion unit **300**, which is instead used for generating electrical power, when the air vehicle is in aerodynamic flight mode.

5 With the rotor **600** in vertical mode **VM** the first propulsion unit **200** and the second propulsion unit **300** are both used to drive the rotor **600** when the air vehicle is in vectored flight mode, and provides additional thrust than is required for hovering, VTO and/or VL operations, for example. This coupling mode can be used for a variety of situations in which additional vertical thrust may be required, for example: high air
10 vehicle weight (or operating at high altitude) during VTO, VL or hovering than is possible using only one of the first propulsion unit **200** and the second propulsion unit **300**.

Rotor Coupling Mode D

In Rotor Coupling Mode D, the rotor **600** is decoupled from the first propulsion
15 unit **200** by disengagement via the first coupler **400**, and is concurrently decoupled from the second propulsion unit **300** by disengagement via the second coupler **500**.

With the rotor **600** in horizontal mode **HM** or in vertical mode **VL**, no thrust is generated by the rotor **600**. This coupling mode can be used in extreme situations in which for example the rotor is damaged and if coupled to the first propulsion unit **200**
20 and/or the second propulsion unit **300** could also damage the same as well. For example, other propulsion units in the air vehicle can be used to effect an emergency landing, and/or parachutes or other devices can be used for this purpose.

Referring to Figs. 4(a) and 4(b), a second example of the propulsion system, generally designated **100'**, comprises the elements and feature of the first example
25 and/or alternative variations thereof, with the following differences, *mutatis mutandis*. Thus, propulsion system **100'** also comprises a first propulsion unit **200**, a second propulsion unit **300**, a first coupling **400**, a second coupling **500**, and a rotor **600**, as disclosed for the first example, *mutatis mutandis*.

As with the first example, in the second example a first driveshaft **220'** is
30 provided for turning the rotor **600** when engaged thereto via the first coupling **400**.

Thus, the first propulsion unit **200** is reversibly coupled to the rotor **600** via the first driveshaft **220** and first coupler **400**. However, in contrast to the first example, the first propulsion unit **200** is reversibly coupled to the rotor **600** via the first driveshaft **220'** and first coupler **400** when the rotor **600** is in horizontal mode **HM**, but the first
5 propulsion unit **200** is disengaged from the rotor **600** in vertical mode **VM**, irrespective of operation of the first coupler **400**.

On the other hand, and as with the first example, in the second example the second driveshaft **320** directly turns the rotor **600** when engaged thereto via the second coupling **500**. Thus, the second propulsion unit **300** is reversibly coupled to the rotor
10 **600** via the second driveshaft **320** and second coupler **500**. In the second example, the second coupler **500** is also axially located between the rotor **600** and the second propulsion unit **300**.

Referring in particular to Figs. 4(a) and 4(b), the first driveshaft **220'** comprises a propulsion unit end portion **221'** connected to and driven by the first propulsion unit
15 **200**, a rotor end portion **222'** connected to and for driving the rotor **600**, and a connector arrangement **690**. The connector arrangement **690** is configured for automatically connecting the propulsion unit end portion **221'** with respect to the rotor end portion **222'** when the rotor **600** is in horizontal mode **HM**, and for automatically disconnecting the propulsion unit end portion **221'** from the rotor end portion **222'** when the rotor **600**
20 is in vertical mode **VM**. The connector arrangement **690** comprises a first connector portion **692** provided at the aft end of the propulsion unit end portion **221'**, and a second connector portion provided at the forward end of the rotor end portion **222'**.

An example of the connector arrangement **690** is illustrated in Figs. 5(a), 5(b), 5(c). In this example, the first connector portion **692** comprises a female clutch portion
25 **692A** and a first dog-clutch portion **692B** concentric therewith. The second connector portion **694** comprises a cone-shaped male clutch portion **694A** and a second dog-clutch portion **694B** concentric therewith. The female clutch portion **692A** is in the form of a cone-shaped cavity complementary to the male clutch portion **694A**. When pivoting the rotor **600** from vertical mode **VM** (Fig. 5(a)) to horizontal mode **HM** (Fig. 5(c)), the
30 propulsion system **100'** is configured for first providing a rotation about the pivot axis **PA** followed by a linear displacement. This combination of pivoting and linear

movement can be provided, for example, by suitably contouring the slots **670** to include a linear portion as well as a curvuate portion.

The rotation about the pivot axis **PA** provides the second angular disposition α_2 , in which the propulsion unit end portion **221'** is co-axial to the rotor end portion **222'**,
5 but the first connector portion **692** is axially spaced from the second connector portion **694** (Fig. 5(b)). Once axially aligned, there follows a linear displacement in which the male clutch portion **694A** enters the female clutch portion **692A**; concurrently, the rotor **600** is being turned by second propulsion unit **300**. In this example, the first coupler **400** is provided in the propulsion unit end portion **221'** and initially decouples the female
10 clutch portion **692A** from the first propulsion unit **200** this allows the rotation of the female clutch portion **692A** to be synchronized with the rotation of the male clutch portion **694A** via the frictional frusto-conical facing surfaces of the clutch portions, and once synchronized the first dog-clutch portion **692B** meshes with the second dog-clutch portion **694B** to lock the first connector portion **692** with the second connector portion
15 **694** in rotation. Thereafter the first coupler **400** can couple the rotor with the first propulsion unit **200** whenever desired to allow the first propulsion unit **200** to power the rotor **600**. Operation of the propulsion system **100'** from the horizontal mode **HM** to the vertical mode **VM** is the inverse of the above.

In alternative variations of this example, wherein the coupler **400** is provided in
20 the rotor end portion **222'**, between the rotor **600** and the and initially decouples the female clutch portion **692A** from the first propulsion unit **200** this allows the rotation of the female clutch portion **692A** to be synchronized with the rotation of the male clutch portion **694A** and the second connector portion **694**, the first coupler **400** is also decoupled until the first connector portion **692** and the second connector portion **694** are
25 fully engaged.

While in the second example, the first coupling **400** is located in the rotor end portion **222'**, in alternative variations of this example the first coupling **400** can be located in the propulsion unit end portion **221'**.

The propulsion system **100'** also has a number of operations modes, including at
30 least the following rotor coupling modes, each mode including the rotor in horizontal

mode **HM** or in vertical mode **VM**, in a similar manner as disclosed above for the first example, *mutatis mutandis*:

- Rotor coupling mode A': rotor horizontal mode **HM**; rotor vertical mode **VM**.
- Rotor coupling mode B': rotor horizontal mode **HM**; rotor vertical mode **VM**
- 5 • Rotor coupling mode C': rotor horizontal mode **HM**; rotor vertical mode **VM**
- Rotor coupling mode D': rotor horizontal mode **HM**; rotor vertical mode **VM**

Rotor Coupling Mode A'

In Rotor Coupling Mode A' (corresponding to Rotor Coupling Mode A for the
10 first example), the rotor **600** is decoupled to the first propulsion unit **200** by
disengagement via the first coupler **400**, and is concurrently coupled to the second
propulsion unit **300** via the second coupler **500**, and the propulsion system **100'**
operates in a similar manner to that disclosed for the first example for Rotor Coupling
Mode A, both in vertical mode **VM** and in horizontal mode **HM**, *mutatis mutandis*.

15 **Rotor Coupling Mode B'**

In Rotor Coupling Mode B' (corresponding to Rotor Coupling Mode B for the
first example), the rotor **600** is coupled to the first propulsion unit **200** via the first
coupler **400**, and is concurrently decoupled from the second propulsion unit **300** by
disengagement via the second coupler **500**, and the propulsion system **100'** operates in a
20 similar manner to that disclosed for the first example for Rotor Coupling Mode B in
horizontal mode **HM**, *mutatis mutandis*.

On the other hand, the propulsion system **100'** cannot operate in Rotor Coupling
Mode B' with the rotor **600** in vertical mode **VM**, because in the vertical mode **VM** the
rotor **600** is automatically disconnected from the first propulsion unit **200**. Thus
25 operation Rotor Coupling Mode B' with the rotor **600** in vertical mode **VM** is similar to
operation in Rotor Coupling Mode D' with the rotor **600** in vertical mode **VM** (see
below).

Rotor Coupling Mode C'

In Rotor Coupling Mode C' (corresponding to Rotor Coupling Mode C for the
30 first example), the rotor **600** is coupled to the first propulsion unit **200** via the first
coupler **400**, and is concurrently coupled to the second propulsion unit **300** via the

second coupler **500**, and the propulsion system **100'** operates in a similar manner to that disclosed for the first example for Rotor Coupling Mode C in horizontal mode **HM**, *mutatis mutandis*.

On the other hand, the propulsion system **100'** cannot operate in Rotor Coupling
5 Mode C' with the rotor **600** in vertical mode **VM**, because in the vertical mode **VM** the rotor **600** is automatically disconnected from the first propulsion unit **200**. Thus, operation of Rotor Coupling Mode C' with the rotor **600** in vertical mode **VM** is similar to operation in Rotor Coupling Mode A' with the rotor **600** in vertical mode **VM** (see above).

10 **Rotor Coupling Mode D'**

In Rotor Coupling Mode D' (corresponding to Rotor Coupling Mode D for the first example), the rotor **600** is decoupled from the first propulsion unit **200** by disengagement via the first coupler **400**, and is concurrently decoupled from the second propulsion unit **300** by disengagement via the second coupler **500**, and the propulsion
15 system **100'** operates in a similar manner to that disclosed for the first example for Rotor Coupling Mode D both in vertical mode **VM** and in horizontal mode **HM**, *mutatis mutandis*.

Referring to Figs. 6(a) and 6(b), the air vehicle **1** according to an example of the presently disclosed subject matter, comprises airframe **2** including a main body in the
20 form of fuselage **3**, a wing arrangement **4**, propulsion system **100** and an empennage **5**.

In this example the air vehicle **1** also comprises a suitable undercarriage such as a tricycle undercarriage (not shown), which may be fixed or retractable. In alternative variations of this example, the air vehicle may be provided without an undercarriage and comprises an alternative arrangement for cushioning a landing or is configured for
25 landing onto a suitable cradle or soft cushioning material in VTOL configuration. In alternative variations of this example, the air vehicle may be provided with a different undercarriage arrangement.

The air vehicle **1** has a roll axis **z** aligned with the longitudinal axis **A** of the body or fuselage **3** and the direction of forward flight **F**, pitch axis **x**, and yaw axis **y**.

The air vehicle **1** in this example is configured as a subsonic manned air vehicle, though in alternative variations of this example the air vehicle can be an unmanned air vehicle (UAV), and/or configured as a transonic and/or supersonic air vehicle.

The fuselage **3** comprises a nose and an aft end **6**, and longitudinal axis **A** is
5 generally parallel to the direction of forward flight **F**. The fuselage **3** comprises a generally oblate cross-sectional area taken along transverse planes generally orthogonal to the direction of forward flight **F**. Twin booms **12** extend from the aft end of the fuselage **3**.

Wing arrangement **4** is a fixed wing arrangement, comprising a port wing and a
10 starboard wing, and thus, the port wing and the starboard wing are fixedly connected to the fuselage in a fixed geometrical relationship, at least in aerodynamic flight. It is to be noted that in alternative variations of this example, the port wing and the starboard wing can be pivotably mounted to the fuselage to controllably change the sweep angle of the wings and optimize performance both in the low velocity and high velocity
15 aerodynamic flight regimes (so-called variable geometry wings). In these or other alternative variations of this example, the wings and fuselage may be in the form of a blended wing body (BWB) configuration.

In this example, empennage **5** comprises a pair of laterally spaced empennage booms each having a fin, a port empennage boom **5a** connected to the port wing, and a
20 starboard empennage boom **5b** connected to the starboard wing. Each empennage boom projects in an aft direction from the respective wing. Each fin comprises a control surface at the trailing edge thereof that operates both as a rudder and as a vertical stabilizer in the aerodynamic flight regime of the air vehicle. In alternative variations of this example, any suitable alternative configuration for empennage **5** may be provided,
25 taking into account the structure and function of the propulsion system **100**.

The air vehicle **1** further comprises a pair of forward-mounted vectored thrust propulsion units, in the form of vectored ducted fan units **20a**, **20b**, in addition to the single, aft-mounted, propulsion system **100**, in triangular spatial arrangement in plan-view. The triangular spatial arrangement encloses the center of gravity of the air vehicle
30 in plan view. In alternative variations of this example, the propulsion system **100** can be provided at the front of the air vehicle, or at least forward of the center of gravity CG,

and a pair of vectored thrust propulsion units is provided at the aft end, or at least aft of the center of gravity CG of the air vehicle.

The air vehicle **1** further comprises a suitable control system (not shown) for operating the propulsion system **100** and ducted fan units **20a**, **20b**, in particular the
5 magnitudes of each of the thrusts T_a , T_b , T_c generated by ducted fan units **20a**, **20b**, and the propulsion system **100**, respectively, independently of one another, and the thrust vectors V_a , V_b and V_c of the ducted fan units **20a**, **20b**, and propulsion system **100**, respectively, independently of one another.

In this example, the ducted fan unit **20a**, **20b** each comprises an electric motor
10 for driving the respective fan(s), and each ducted fan unit **20a**, **20b** can have the same power rating as the second propulsion unit **300**, for example.

The forward ducted fan units **20a**, **20b** are rotatably mounted with respect to the fuselage, to enable the ducted fan units **20a**, **20b** to be reversibly tilted about axis X_a with respect to the fuselage **3** about any desired tilt angle α , at least between a tilt angle
15 α of zero degrees and 90 degrees. Tilt angle α of zero degrees corresponds to the general vertical thrust position shown in Fig. 6(b) in which the thrust vector V_{Va} is substantially parallel to the yaw axis y . Tilt angle α of 90 degrees corresponds to the general longitudinal thrust position shown in Fig. 6(a) in which the thrust vector V_{Ha} is substantially parallel to the roll axis z and points in direction F . Axis X_a is substantially
20 parallel to the pitch axis x of the air vehicle **1**.

A suitable drive mechanism (not shown) is provided for independently and controllably driving the tilting of each of the two forward ducted fan units **20a** and **20b** to controllably vary the respective thrust vector, i.e., the angular position of the respective thrust generated by the respective propulsion unit, independently of one
25 another. The drive mechanism is configured for tilting the ducted fan units **20a** and **20b** in a relatively fast manner, and provide very quick and accurate response to tilting commands (in terms of direction and angular displacement) provided by the control system.

In at least this example, the tilt axes X_a , X_b are coaxially aligned.

In alternative variations of this example, the tilt axes X_a , X_b may be each set at a modest angle to the pitch axis x and/or yaw axis y and/or roll axis z so as to provide a desired thrust vector component along one or more of the roll, pitch or yaw axes, respectively. For example, it may be desired to have the thrust vectors V_a and V_b in the
5 vertical thrust position in a mutually converging or diverging relationship when viewed from the front of the air vehicle. Converging thrust vectors may delay the formation of an upwash fountain between the front propulsion units, while diverging thrust vectors may provide natural stability in roll during landing and take-off, for example.

The air vehicle **1** is configured for controllably, selectively and independently
10 varying the thrust vectors V_a and V_b by the changing the respective tilt angles α independently from one another. This feature provides at least differential and selective tilt control for the thrust vectors generated by each one of the forward ducted fan units **20a**, **20b**, independently of the other forward ducted fan unit. Nevertheless, the forward ducted fan units **20a**, **20b** can also be operated to tilt together in the same direction and
15 through the same or different angular displacement one from the other. Furthermore, the air vehicle **1** is configured for controllably and selectively changing the magnitude of the thrust T_a , T_b , T_c generated by each of the ducted fan units **20a**, **20b**, and the propulsion system **100**, respectively, independently of one another. The air vehicle **1** is also configured for controllably and selectively changing the magnitude of the thrust T_a ,
20 T_b , generated by each of the forward ducted fan units **20a**, **20b**, respectively, independently of one another, and also independently of the magnitude of the respective tilt angles α thereof, i.e., of the thrust vectors V_a and V_b , which may also be controllably and selectively varied independently one from the other.

The air vehicle **1** may be operated at least in an aerodynamic flight regime, and
25 in a vectored thrust flight regime, for example as follows. The air vehicle **1** is also configured for performing transition between aerodynamic flight mode and vectored thrust mode.

Aerodynamic Flight Mode

30 In the aerodynamic flight regime, the air vehicle **1** can be operated exclusively in aerodynamic flight mode (also referred to herein as "aerodynamic flight"), in which

the air vehicle has sufficient forward velocity to enable sufficient aerodynamic lift to be generated by the air vehicle, in this example by the wings **4**, and for pitch roll and yaw control to be provided via the air vehicle control surfaces. The two forward mounted ducted fan units **20a**, **20b** are in nominal horizontal or longitudinal mode, with the
5 respective tilt angles α nominally set at **90** degrees, to provide thrust vectors V_{Ha} and V_{Hb} , respectively in the general forward flight direction F , and thrusts T_a and T_b are nominally equal. Concurrently, the rotor **600** is in horizontal mode HM, and the propulsion system **100** can be used in any desired coupling mode, including one or more of Rotor Coupling Modes A, B, C or D, as disclosed above *mutatis mutandis*, as
10 appropriate.

In this flight mode, the air vehicle **1** can operate within its flight envelope in a similar manner to that of conventional fixed-wing aircraft.

For example, in aerodynamic flight - and depending on the speed required -the air vehicle **1** can require on average between 200kW and 400 kW, for an air vehicle in
15 the weight range of between 3 tonne and 4 tonnes.

Vectored Thrust Flight Mode

In the vectored thrust flight regime, the air vehicle **1** may be operated exclusively in vectored thrust flight mode (also referred to herein as "vectored thrust
20 flight", or as "VTOL operations"), in which at least all the lift (and optionally also movement and control) of the air vehicle are provided by the propulsion system **100** and ducted fan units **20a**, **20b**, under the control of the control system.

For VTOL operations, the forward ducted fan units **20a**, **20b** are tilted to the nominal vertical position, in which tilt angles α are set at nominally zero degrees, and
25 ducted fan units **20a**, **20b** and the propulsion system **100** provide vertical thrust. Concurrently, the rotor **600** is in vertical mode VM, and the propulsion system **100** can be used in any desired coupling mode, including Rotor Coupling Modes A, B, C or D, as disclosed above *mutatis mutandis*, as appropriate.

In the illustrated example, the center of gravity CG of the air vehicle is located
30 generally centrally with respect to the ducted fan units **20a**, **20b** and the propulsion

system **100**, and thus the ducted fan units **20a, 20b** and the propulsion system **100** each generate nominally the same thrust levels.

In at least one implementation of the air vehicle **1**, each of the ducted fan units **20a, 20b** and the second propulsion unit of the propulsion system **100** each comprises
5 an electrically powered motor rated at about **500kW**, while the second propulsion unit of the propulsion system **100** comprises an internal combustion engine rated at **500HP** to about **600HP**, which together provide a total power rating of about **2,000kW** or **2,600HP** for the air vehicle **1**, which can have a weight in the **3 tonne** to **3.5 tonne** range, for example.

10 For example, in hover (including VTO, vertical climbing, VL and vertical descent) the air vehicle **1** can require on average about 1,300 kW to be provided by the ducted fan units **20a, 20b** and propulsion system **100**, for an air vehicle in the weight range of between 3 tonne and 4 tonnes.

In alternative variations of this example, where the center of gravity is located
15 closer to or further away from propulsion system **100** than with respect to the forward ducted fan units **20a, 20b**, and the ratio of the thrust provided by the propulsion system **100** relative to the forward ducted fan units **20a, 20b** is correspondingly such as to provide pitch balance to the air vehicle. The relative thrust split between the propulsion system **100** relative to the forward ducted fan units **20a, 20b** can also be controlled to
20 offset a longitudinal shift in the position of the CG, for example related to the location, size or absence of the payload. Additionally or alternatively, the relative thrust split between the two forward ducted fan units **20a, 20b** can also be controlled to offset a lateral shift in the position of the CG that is for example inherent in the air vehicle design or that is related to the location, size or absence of the payload – for example
25 where a stores on one wing is jettisoned while retaining a similar stores on the other wing.

In alternative variations of the above examples, the ducted fan units **20a, 20b**, can be replaced with any other suitable vectored thrust propulsion unit configurations, for example pivotable unducted fans, pivotable propellers, etc.

In another example of the air vehicle **1**, the propulsion unit **100** is replaced with propulsion unit **100'** and thus operates in a similar manner to that disclosed above for air vehicle **1** in aerodynamic flight mode and in vectored thrust flight mode, *mutatis mutandis*, with the main difference that correspondingly the propulsion unit **100'** operates in its corresponding coupling mode, including Rotor Coupling Modes A', B', C' or D', as disclosed above *mutatis mutandis*, as appropriate.

Thus, in the above examples, the propulsion system **100** or the propulsion system **100'** each operates as a hybrid propulsion system at times driven by fuel energy and electrical energy, at other times by fuel energy only, and at other times by electrical energy only.

In the above examples, the propulsion system **100** or the propulsion system **100'** each operates to pivot the respective rotor between vertical mode **VM** and horizontal mode **HM** while the second propulsion unit **300** is connected thereto, and thus the second propulsion unit **300** concurrently pivots with the rotor between vertical mode **VM** and horizontal mode **HM**. However, in alternative variations of these examples, the second propulsion unit **300** does not pivot with the rotor when the rotor pivots between vertical mode **VM** and horizontal mode **HM**. For example, referring to Figs. 7(a) and 7(b), the second propulsion unit **300** is fixedly mounted to the airframe in a similar manner to the first propulsion unit **200**, but the respective second driveshaft **320A** comprises a universal joint arrangement **325A** that enables the second propulsion unit **200** to be driven by or to drive the rotor **600**, both in vertical mode **VM**, horizontal mode **HM** and in transition therebetween. Thus, in the examples illustrated in Figs. 7(a) and 7(b), only the rotor **600** pivots between vertical mode **VM** and horizontal mode **HM**.

While in the above examples, the propulsion system **100** or the propulsion system **100'** each has the second propulsion unit **300** on the opposed longitudinal side of the rotor with respect to the first propulsion unit **200**, in alternative variations of these examples, both the first propulsion unit **200** and the second propulsion unit **300** can be on the same longitudinal side of the rotor.

While in the above examples the air vehicle has a single propulsion system **100** or **100'**, in alternative variations of these examples, the air vehicle can have two or more

propulsion system **100** or **100'**, and optionally no additional vectored thrust propulsion units, or one or more than one additional vectored thrust propulsion units.

In the method claims that follow, alphanumeric characters and Roman numerals used to designate claim steps are provided for convenience only and do not imply any
5 particular order of performing the steps.

Finally, it should be noted that the word “comprising” as used throughout the appended claims is to be interpreted to mean “including but not limited to”.

While there has been shown and disclosed examples in accordance with the presently disclosed subject matter, it will be appreciated that many changes may be made
10 therein without departing from the spirit of the presently disclosed subject matter.

CLAIMS:

1. A propulsion system comprising:
 - a first propulsion unit configured for being fixedly mounted to an airframe;
 - a second propulsion unit;
 - 5 a rotor configured for being pivotably mounted with respect to the first propulsion unit to allow selectively pivoting of the rotor from a horizontal mode to a vertical mode;
 - a first coupling for selectively coupling and decoupling the rotor with respect to the first propulsion unit;
 - 10 a second coupling for selectively coupling and decoupling the rotor with respect to the second propulsion unit, independently of the first coupling.
2. The propulsion system according to claim 1, wherein said first propulsion unit comprises an internal combustion engine.
3. The propulsion system according to claim 1 or claim 2, wherein said second
15 propulsion unit comprises an electric motor.
4. The propulsion system according to any one of claims 1 to 3, wherein said second propulsion unit is configured to pivot together with said rotor.
5. The propulsion system according to any one of claims 1 to 4, wherein said first propulsion unit is reversibly coupled to a first longitudinal side of the rotor, and wherein
20 said second propulsion unit is reversibly coupled to a second longitudinal side of the rotor.
6. The propulsion system according to any one of claims 1 to 5, wherein said rotor comprises any one of: one or more propellers; one or more ducted fans; one or more unducted fans.
- 25 7. The propulsion system according to any one of claims 1 to 6, wherein said first propulsion unit has a first power rating and wherein said second propulsion unit has a second power rating.
8. The propulsion system according to claim 7, wherein said first power rating is within $\pm 10\%$ of said second power rating.
- 30 9. The propulsion system according to claim 7, wherein a power rating ratio between said first power rating and said second power rating is between 0.1 and 10.

10. The propulsion system according to any one of claims 7 to 9, wherein said power rating ratio is 1.0.
11. The propulsion system according to any one of claims 1 to 10, wherein the first propulsion unit is reversibly coupled to the rotor via a first driveshaft.
- 5 12. The propulsion system according to claim 11, wherein said first driveshaft comprises a first portion driven by the first propulsion unit and a second portion for driving the rotor when the first driveshaft is coupled to the rotor via the first coupling, wherein in said vertical mode said first portion is at a first angular disposition with respect to said second portion, wherein in said horizontal mode said first portion is at a
10 second angular disposition with respect to said second portion, and wherein said first angular disposition is less than said second angular disposition.
13. The propulsion system according to claim 12, wherein said first angular disposition is about 90° in pitch, and wherein said second angular disposition is about 180° in pitch.
- 15 14. The propulsion system according to any one of claims 11 to 13, wherein said first driveshaft comprises a universal joint arrangement to allow said first portion and said second portion to pivot between said first angular disposition and said second angular disposition while concurrently remaining operatively connected to one another to allow torque to be transmitted between said first portion and said second portion.
- 20 15. The propulsion system according to claim 14, further comprising a shroud member configured for covering the first driveshaft in any angular disposition between said first angular disposition and said second angular disposition.
16. The propulsion system according to claim 15, wherein said shroud member comprises a rigid tubular first shroud portion for covering said first portion, a rigid
25 tubular second shroud portion for covering said second portion, and a flexible tubular shroud joint portion for covering the universal joint arrangement, wherein the first shroud portion, the second shroud portion and said shroud joint portion are contiguous.
17. The propulsion system according to any one of claims 11 to 13, wherein said first driveshaft comprises a disconnection arrangement to allow said first portion and
30 said second portion to pivot between said first angular disposition in which said first portion is disconnected with respect to said second portion at said disconnection portion, and said second angular disposition in which said first portion is connected

with respect to said second portion at said disconnection portion to thereby allow torque to be transmitted between said first portion and said second portion.

18. The propulsion system according to claim 17, wherein said disconnection arrangement comprises a first connector portion provided in said first portion and a
5 second connector portion provided in said second portion, wherein the first connector portion frictionally engages and locks with the second connector portion in the second angular disposition.

19. The propulsion system according to any one of claims 1 to 18, wherein said first coupling comprises a first electrical clutch configured for selectively engaging and
10 disengaging the first propulsion unit with respect to the rotor.

20. The propulsion system according to any one of claims 1 to 19, wherein the second propulsion unit is reversibly coupled to the rotor via a second driveshaft.

21. The propulsion system according to any one of claims 1 to 20, wherein said second coupling comprises a second electrical clutch configured for selectively
15 engaging and disengaging the second propulsion unit with respect to the rotor.

22. The propulsion system according to any one of claims 1 to 21, wherein the rotor is rotatably mounted to a support bracket, the support bracket being pivotable between the horizontal mode and the vertical mode.

23. The propulsion system according to any one of claims 1 to 22, wherein said
20 second propulsion unit is configured for selectively generating electrical power when driven by any one of:

- (a) said first propulsion unit;
- (b) said rotor, which is in wind milling mode and in turn is aerodynamically driven by an airflow.

25 **24.** An air vehicle comprising at least one propulsion system as defined in any one of claims 1 to 23

25. The air vehicle according to claim 24, further comprising at least one battery operatively connected to the second propulsion unit.

26. The air vehicle according to any one of claims 24 and 25, comprising one said
30 propulsion system and two tiltable vectored thrust propulsion units tiltable at least between respective horizontal mode and vertical mode, wherein said propulsion system and said two vectored thrust propulsion units are in triangle configuration.

27. The air vehicle according to claim 26, wherein said propulsion system is aft mounted along a longitudinal axis of the air vehicle, and said two vectored thrust propulsion units are forward mounted, each said vectored thrust propulsion unit laterally spaced from the longitudinal axis in opposed directions.
- 5 28. The air vehicle according to claim 26, wherein said propulsion system is forward mounted along a longitudinal axis of the air vehicle, and said two vectored thrust propulsion units are aft mounted, each said vectored thrust propulsion unit laterally spaced from the longitudinal axis in opposed directions.
29. The air vehicle according to any one of claims 24 to 28, wherein the air vehicle
10 is configured as an unmanned air vehicle (UAV).
30. The air vehicle according to any one of claims 24 to 28, wherein the air vehicle is configured as a manned air vehicle.
31. A method for operating an air vehicle, comprising:
15 - providing the air vehicle as defined in any one of claims 24 to 30;
- operating the air vehicle in one or more of vertical configuration and horizontal configuration, wherein in vertical configuration said rotor is in vertical mode, and wherein in horizontal configuration said rotor is in horizontal mode.
20
32. The method according to claim 31, comprising setting said rotor in horizontal mode, decoupling said rotor from said first propulsion unit and coupling said rotor to said second propulsion unit.
- 25 33. The method according to claim 32, for use in one or more of:
- enabling the second propulsion unit to exclusively provide propulsion for the air vehicle in aerodynamic flight;
- enabling the air vehicle to cruise unpowered to provide silent gliding;
- enabling the air vehicle to cruise unpowered and using the airflow over the
30 rotor to drive the second propulsion unit to thereby generate electrical power.

34. The method according to claim 31, comprising setting said rotor in vertical mode, decoupling said rotor from said first propulsion unit and coupling said rotor to said second propulsion unit.
- 5 35. The method according to claim 34, for use in enabling the at least one propulsion unit to provide vertical propulsion exclusively from the second propulsion unit thereby providing low-noise VTOL operations.
36. The method according to claim 31, comprising setting said rotor in horizontal
10 mode, coupling said rotor to said first propulsion unit and decoupling said rotor to said second propulsion unit.
37. The method according to claim 36, for use in enabling the first propulsion unit to exclusively provide propulsion for the air vehicle in aerodynamic flight.
- 15 38. The method according to claim 31, comprising setting said rotor in vertical mode, coupling said rotor to said first propulsion unit and decoupling said rotor to said second propulsion unit.
- 20 39. The method according to claim 38, for use in enabling the at least one propulsion unit to provide vertical propulsion exclusively from the first propulsion unit thereby providing low-noise VTOL operations.
40. The method according to claim 31, comprising setting said rotor in horizontal
25 mode, coupling said rotor to said first propulsion unit and coupling said rotor to said second propulsion unit.
41. The method according to claim 40, for use in one or more of:
- enabling the first propulsion unit and the second propulsion unit to provide
30 augmented propulsion for the air vehicle in any one of: conventional take-off; conventional landing; aerodynamic flight;

- enabling the first propulsion unit to exclusively provide propulsion for the air vehicle and using the first propulsion unit to drive the second propulsion unit to thereby generate electrical power.

5 **42.** The method according to claim 41, comprising setting said rotor in vertical mode, coupling said rotor to said first propulsion unit and coupling said rotor to said second propulsion unit.

10 **43.** The method according to claim 42, for use in enabling the first propulsion unit and the second propulsion unit to provide augmented vertical propulsion for the air vehicle thereby providing augmented VTOL operations.