

considered. A surveillance robot that covers an area by pointing a camera at a location from any of a near infinite number of vantage points will require different planning techniques than a vacuuming robot which covers an area by simply traveling over it.

Brief Summary of the Invention

- [0006a] According to an aspect of the present invention, there is provided a method of performing surface processing on a three dimensional object using a robotic manipulator, with a stationary or mobile base, in a work environment comprising the steps of: obtaining a base model of said three dimensional object; generating a surface model from said base model by performing a surface scan of said three dimensional object and augmenting said base model with range data and surface property data obtained from said scan; planning a temporal sequence of states of said robotic manipulator to maximize processing of said surface of said three dimensional object; placing said robotic manipulator in each state in said sequence of states, and, for each state: scanning said surface of said three dimensional object before said surface is processed to control or modulate a processing tool connected to said robotic manipulator; processing said surface with said processing tool; scanning said surface of said three dimensional object after said surface has been processed and updating said surface model with new surface property data; adjusting said temporal sequence of states for said robotic manipulator based on said updated surface model; and continuing processing of said surface and said updating of said surface model until said surface reaches a desired state.
- [0006b] Disclosed herein is a system for performing surface processing on a three dimensional object in a work environment comprising: one or more robotic manipulators, each of said robotic manipulators including an end effector having a surface processing tool, a ranging sensor and one or more surface property sensors attached thereto; a computer running software for controlling said one or more robotic manipulators, said software comprising:

a surface property analyzer, for processing surface properties sensor data before and after the processing point of said surface processing tool to classify the current state of said surface; a surface model for storage of the geometry of said surface and said current state of said surface; a surface process planner for planning a sequence of processing actions to be carried out by said processing tool based on an observed state of said surface stored in said surface model; a surface process modulator for modifying said planned sequence of processing actions based on real-time feedback from said ranging sensor and said one or more surface property sensors; and a surface coverage planner, for planning movements and poses of said one or more robotic manipulators to maximize coverage of said surface.

[0007] The system disclosed herein precisely maneuvers one or more machine vision components and/or one or more surface processing devices over the surface of a three-dimensional object. The vision systems gather data about the surface that are used to inform the surface process. These data include both intrinsic properties of the surface, such as color, texture or abstract classification results, along with precise estimates of the distance and orientation of the surface relative to the processing point. These data are used to accurately plan for and modulate the surface process to efficiently generate high-quality results. In the preferred embodiment of the invention, the machine vision components are comprised of multi-spectral cameras with corresponding illumination sources that can discriminate between various layers of paint and underlying substrates, and the surface processing device is a high-power laser scanner, originally designed for laser welding, which is used to remove coatings from aeronautical surfaces.

Description of the Drawings

[0008] Figure 1: Core Operational Principles. The symmetry of the Surface Property Analyzers allows surface classification data to be generated both immediately before and immediately after processing.

Claims

1. A method of performing surface processing on a three dimensional object using a robotic manipulator, with a stationary or mobile base, in a work environment comprising the steps of:
 - obtaining a base model of said three dimensional object;
 - generating a surface model from said base model by performing a surface scan of said three dimensional object and augmenting said base model with range data and surface property data obtained from said scan;
 - planning a temporal sequence of states of said robotic manipulator to maximize processing of said surface of said three dimensional object;
 - placing said robotic manipulator in each state in said sequence of states, and, for each state:
 - scanning said surface of said three dimensional object before said surface is processed to control or modulate a processing tool connected to said robotic manipulator;
 - processing said surface with said processing tool ; and
 - scanning said surface of said three dimensional object after said surface has been processed and updating said surface model with new surface property data;
 - adjusting said temporal sequence of states for said robotic manipulator based on said updated surface model; and
 - continuing processing of said surface and said updating of said surface model until said surface reaches a desired state.
2. The method of claim 1 further comprising the steps of:
 - refining the position of said surface model with respect to said work environment; and
 - refining the position of said robotic manipulator with respect to said work environment.
3. The method of claim 2 wherein said robotic manipulator is mounted on a mobile base which is capable of moving with respect to said work environment.

4. The method of claim 3 wherein said robotic manipulator is mounted on a rail base capable of moving said robotic manipulator along a rail.
5. The method of claim 1, wherein said base model is obtained from a pre-existing 3-D model with subsurface properties.
6. The method of claim 1, wherein said base model is generated by scanning said three dimensional object using an optical sensor capable of capturing the shape of said three dimensional object.
7. The method of claim 1 further comprising the step of augmenting said base model with processing policies regarding the processing of said surface.
8. The method of claim 7 further comprising the step of allowing user interaction with said surface model.
9. The method of claim 8 wherein said user interaction includes allowing the specification of masks which preclude portions of said surface from being processed.
10. The method of claim 8 wherein said user interaction includes allowing the specification of keep out areas or volumes which prevents the positioning of said robotic manipulator over said specified area or inside said specified volume.
11. The method of claim 8 wherein said user interaction includes allowing the marking of an area that needs further processing
12. The method of claim 8 wherein said user interaction allows the overriding of said processing policies.
13. The method of claim 1 wherein said robotic manipulator includes a LIDAR device and further wherein said range data is generated by said LIDAR device.

14. The method of claim 1 wherein said robotic manipulator includes one or more sensors, and further wherein said surface property data is generated by said one or more sensors.
15. The method of claim 14 wherein said one or more sensors is selected from a group comprising multi-spectral cameras, color cameras, monochrome cameras and cameras with specific wavelength sensitivities.
16. The method of claim 14 wherein said one or more sensors is selected from a group comprising inspection sensors, including non-destructive inspection sensors, ultrasonic sensors, and eddy current based crack detection sensors.
17. The method of claim 1 wherein said temporal sequence of states of said robotic manipulator comprises a set of positions with respect to said work environment and poses.
18. The method of claim 1 wherein said step of planning a temporal sequence of states of said robotic manipulator includes maximizing the processing of said surface while avoiding a collision between said three-dimensional object and other objects in said work environment.
19. The method of claim 1 wherein said step of planning a temporal sequence of states of said robotic manipulator precludes processing the same area of said surface more than once within a predetermined minimum period of time.
20. The method of claim 1 wherein said surface model consists of a set of two dimensional manifolds, each of said manifolds composed of a plurality of cells, each of said cells representing a physical unit of surface area and each of said cells having a set of properties associated therewith.
21. The method of claim 20 where said properties associated with each of said cells includes the type of material and coating properties.

22. The method of claim 1 wherein said processing tool is a laser capable of ablating paint from said surface.

23. The method of claim 1 further comprising the steps of:
 querying the most recently observed state of said surface along a trajectory of said processing tool; and
 planning a sequence of processing actions and parameters to be carried out by said processing tool based on said observed state.

24. The method of claim 1 further comprising the step of analyzing a processed surface to determine if further processing is necessary for any portion of said surface.

25. The method of claim 1 wherein said robotic manipulator includes an end effector, further comprising the step of measuring the 3-D position and orientation of said end effector relative to a work area using an optical positioning camera viewing fiducials in said work area, said optical positioning camera being mounted close to said end effector to minimize pose error due to relative motion between optical based positioning and said robotic manipulator.

26. The method of claim 1 wherein said robotic manipulator includes an end effector, further comprising the step of measuring the 3-D position and orientation of said end effector using an optical positioning camera sighting said surface to measure relative motion between said end effector and said surface, as said processing tool is processing said surface.