

VIRTUAL SERVICE PROVIDER ZONES

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application claims priority to co-pending U.S. Patent Application Nos. 13/932,824 and 13/932,872, both filed on July 1, 2013, the contents of which are incorporated herein by reference in their entireties. This application incorporates by reference for all purposes the full disclosure of U.S. Patent No. 8,416,709, issued on April 9, 2013, entitled "NETWORK DATA TRANSMISSION ANALYSIS MANAGEMENT," U.S. Patent Application No. 13/491,403, filed on June 7, 2012, entitled "FLEXIBLY CONFIGURABLE DATA MODIFICATION SERVICES," U.S. Patent Application No. 13/764,963, filed on February 12, 2013, entitled "DATA SECURITY SERVICE," and U.S. Patent Application No. 13/932,872, filed on July 1, 2013, entitled "DATA LOSS PREVENTION TECHNIQUES" (Attorney Docket No. 0097749-051US0).

BACKGROUND

[0002] The security of computing resources and associated data is of high importance in many contexts. As an example, organizations often utilize networks of computing devices to provide a robust set of services to their users. Networks often span multiple geographic boundaries and often connect with other networks. An organization, for example, may support its operations using both internal networks of computing resources and computing resources managed by others. Computers of the organization, for instance, may communicate with computers of other organizations to access and/or provide data while using services of another organization. Organizations may utilize complex data storage systems to efficiently and cost effectively store data. In many instances, organizations configure and utilize data storage systems hosted and managed by other organizations, thereby reducing infrastructure costs and achieving other advantages. These data storage systems and other services may operate under multiple different jurisdictions, each with their own rules and regulations. With such complex use of computing resources to manage, ensuring that access to the data is authorized and generally that the data is secure can be challenging, especially as the size and complexity of such configurations grow.

BRIEF DESCRIPTION OF THE DRAWINGS

[0003] Various embodiments in accordance with the present disclosure will be described with reference to the drawings, in which:

5 [0004] FIG. 1 shows an illustrative example of an environment in which various embodiments may be practiced;

[0005] FIG. 2 shows an illustrative example of an environment in which various embodiments may be practiced;

[0006] FIG. 3 shows an illustrative example of an environment in which various embodiments may be practiced;

10 [0007] FIG. 4 shows an illustrative example of another environment in which various embodiments may be practiced;

[0008] FIG. 5 shows an illustrative example of a cryptography service in accordance with at least one embodiment;

15 [0009] FIG. 6 shows an illustrative example of a process for processing a request for a data key in accordance with at least one embodiment;

[0010] FIG. 7 shows an illustrative example of a process for processing a request to decrypt a data key in accordance with at least one embodiment;

[0011] FIG. 8 shows an illustrative example of a process for processing a request to store data in accordance with at least one embodiment;

20 [0012] FIG. 9 shows an illustrative example of a process for processing a request to retrieve data in accordance with at least one embodiment;

[0013] FIG. 10 shows an illustrative example of a database table transformation in accordance with at least one embodiment;

25 [0014] FIG. 11 shows an illustrative example of a process for processing a database query in accordance with at least one embodiment;

[0015] FIG. 12 shows an illustrative example of an environment in which various embodiments may be practiced;

[0016] FIG. 13 shows an illustrative example of a process for storing customer data in accordance with at least one embodiment;

[0017] FIG. 14 shows an illustrative example of a process for applying one or more data loss prevention techniques in accordance with at least one embodiment; and

[0018] FIG. 15 illustrates an environment in which various embodiments can be implemented.

5

DETAILED DESCRIPTION

[0019] In the following description, various embodiments will be described. For purposes of explanation, specific configurations and details are set forth in order to provide a thorough understanding of the embodiments. However, it will also be apparent to one skilled in the art
10 that the embodiments may be practiced without the specific details. Furthermore, well-known features may be omitted or simplified in order not to obscure the embodiment being described.

[0020] Techniques described and suggested herein provide the ability to offer various computing resource services, such as data storage services, in various zones without the need
15 to build full infrastructures in those zones. In some examples, the zones correspond to facilities in different geopolitical boundaries. Various geographic regions may have their own rules, laws and/or regulations with respect to the handling of other people's data. For instance, one regulation may require that certain types of data remain in country. Similar regulations may be in force in multiple geographic regions. At the same time, many
20 organizations find it advantageous to utilize various computing resource services. Such services may not be available in all jurisdictions or better and/or more economical services may be provided in other regions.

[0021] In many instances, compliance with such regulations may be achieved by encrypting data before the data leaves a regulated jurisdiction. Techniques of the present
25 disclosure, accordingly, allow various data-related services to be provided to multiple geographic regions while maintaining compliance with the differing rules, laws and/or regulations. Generally, the techniques described and suggested herein allow for the providing of services in multiple zones, where the zones may, but do not necessarily, correspond to different sovereign entities. For instance, different zones may be different computer
30 networks governed by different entities, whether those entities be governmental agencies of a

sovereign entity, corporations, organizations, divisions within an organization, individuals and/or others. Other example zones are discussed in more detail below.

[0022] In various embodiments, a service interface, such as a web service interface, is provided in one zone. In some examples, the service operates in an Internet Point of Presence (PoP). The service interface may operate as a virtual application programming interface (API) endpoint for a service whose supporting infrastructure is in another zone (e.g., under another political (legal) jurisdiction). Accordingly, the service interface may operate to receive and respond to requests submitted to the service interface while fulfillment of some or even all the requests, may require the use of the infrastructure in the other zone. In this manner, customers may utilize the service interface to utilize a service as if the customers were utilizing a service with fully supporting infrastructure in the zone. In other words, from the perspective of the customers, a computing resource provides instances of a service in multiple zones, but behind the scenes, the processing of a request for a particular zone may occur, at least in part, using the instance of a service of another zone. For example, a web service request to store data may be fulfilled by the service interface by transmitting the data for persistent storage to the service in the other zone. Similarly, a data retrieval request may be fulfilled by retrieving data persistently stored in the infrastructure of the service in the other zone. In this manner, a full infrastructure does not need to be constructed and maintained for every zone wherein there may be legal restrictions on the export of certain types of information.

[0023] To comply with various rules, laws, regulations and/or preferences, some or even all data passing through the service interface to a service in another zone may be encrypted using cryptographic keys that are maintained within the zone of the service interface and/or generally in a zone that is outside of the zone of the supporting service infrastructure. In this manner, while in the zone of the supporting service infrastructure, the data is secure and inaccessible without access to appropriate cryptographic keys in another zone. The data that is encrypted may be generally or selectively encrypted. The data which is encrypted may also be configurable by a customer on behalf of whom the data is stored. In addition, the data that is encrypted and whether the data is encrypted may be determined in accordance with one or more data loss prevention (DLP) policies. In addition, while various illustrative embodiments of the present disclosure utilize encryption for the purpose of illustration, various other techniques may also be used. For example, the various techniques described

herein include various manipulation (mangling) of data, where the type of mangling to be applied may be customer configurable.

[0024] Returning to the illustrative examples of encryption of data, in some embodiments, the service interface operating as an API proxy utilizes a cryptography service within the same zone. The cryptography service may securely manage cryptographic keys used for encrypting and decrypting and possibly for performing other cryptographic operations, such as message signing. When data is to be encrypted, the service interface may utilize the cryptography service to encrypt the data before the data is transmitted to the other service in the other zone. Similarly, when data is to be decrypted, the service interface may utilize the cryptography service to decrypt the data. Illustrative manners in which the cryptography service may be utilized appear below. An example cryptography service can be found in U.S. Patent Application No. 13/764,963, filed on February 12, 2013, entitled "DATA SECURITY SERVICE," which is incorporated herein by reference.

[0025] The instances of a service type of a service provider may be utilized by a customer to restrict access to certain data by certain individuals, such as to comply with one or more regulations. As an example, the set of operators (e.g., individuals with authority to make requests to a service of the computing resource service provider on behalf of a customer) may have different vetting properties or qualifications than another set of operators for another service. For example, as noted above and discussed in more detail below, a service provider, may operate a first service in a first region and a second service in a second region (e.g., in a different legal jurisdiction than the first region) where, for at least some requests to the first service, the first service acts as a proxy for the second service. The operators of the first service may be required to have certain qualifications which are different than the qualifications (if any) required for utilizing the second service. Example qualifications include, but are not limited to: having passed a background investigation; having a particular nationality or location; being subject to certain nondisclosure obligations; having a certain security clearance level; having a certain job title (e.g., attorney); and the like. To enable enforcement of such restrictions, the service provider can require different authentication credentials for one service than for another service. As an example, a signing key used to sign requests to the first service may not be usable for the second service. In this manner, distribution of signing keys to individuals with the appropriate qualifications can be used to

ensure that data access is in compliance with various regulations despite the data passing from one region to another.

[0026] FIG. 1 shows an illustrative example of an environment 100 in which various embodiments may be practiced. In the environment illustrated in FIG. 1 a virtual service 102 is provided. The virtual service 102 may be configured to provide a service interface, such as a web service interface, usable by customers 104 for the purposes of utilizing various computing resource services. In some embodiments the virtual service 102 operates as a proxy for a backing service 106. As discussed in more detail below, the virtual service 102 and the backing service 106 may be separate instances of the same overall service type (e.g., a data storage service with network endpoints in different geographical regions). For example, the backing service 106 may be a collection of computing resources such as servers, data storage devices, and networking equipment configured to enable the operation of the computing resources in a network. The backing service 106 may provide the infrastructure needed to process requests submitted to the virtual 102. For example, the virtual service 102 may lack sufficient storage capacity to provide a data storage service. In other words, while the virtual service 102 may include data storage devices, the amount of storage maintained in the virtual service 102 may be insufficient for processing the requests it receives without use of the backing service 106. Customers 104, nevertheless, can utilize the virtual service 102 for the purpose of utilizing data storage services.

[0027] As illustrated in FIG. 1, for example, the customer 104 may transmit data to the virtual service 102, such as through a web service API call to the virtual service 102. The data may be transferred, for instance, in connection with a request to store the data. The virtual service 102 may process the request to store data as if the request had been submitted to the backing service 106. For example, despite the virtual service 102 lacking sufficient storage capacity to provide a data storage service to customers 104, data provided to the virtual service 102 may nevertheless be stored utilizing the infrastructure of the backing service 106. As noted above, various jurisdictional considerations may come into play when utilizing a data storage service. Accordingly, as illustrated in FIG. 1 the virtual service 102 and the backing service 106 in some embodiments are implemented using physical infrastructure such as one or more data center facilities and/or collections of servers, networking equipment, data storage, and the like. In the example illustrated in FIG. 1, the

virtual service 102 and backing service 106 are in different countries, although different jurisdictional entities are also considered as being within the scope of the present disclosure.

[0028] In order to prevent data that is transmitted to the virtual service 102 from being stored in plaintext form in the backing service 106 which may violate one or more rules,
5 laws, regulations and/or preferences, data from the customer transmitted from the virtual service 102 to the backing service 106 may be encrypted. In various embodiments, the data is encrypted using a cryptographic key that is never provided (without the consent and/or instruction of the customer 104) to a computing device in the jurisdiction in which the backing service 106 is located. For example, in some embodiments, the key used to encrypt
10 the data is maintained securely within the jurisdiction in which the virtual 102 is located. As discussed in more detail below, some data may be provided from the virtual service 102 to the backing service 106 in plaintext (cleartext) form while other data may be encrypted. Further, some data provided to the virtual service 102 may not be transmitted to the backing service 106, such as when such a transfer of information would violate one or more DLP
15 policies.

[0029] It should be noted that while FIG. 1 illustrates data being transmitted to the virtual service 102 by the customer 104 other ways in which the virtual service 102 may obtain data that is transmitted to the backing service 106 may be provided. For example, in some embodiments customers of the customer 104 utilize services of the customer 104 that are
20 implemented using computing resources of a computing resource service provider. Data may be transmitted to the virtual service 102 directly from these customers of the customer 104. As another example, customer data transmitted to the virtual service 102 may be transmitted from a computing device that is physically hosted by a computing resource service provider that operates the virtual service 102. For instance, the customer 104 may provide the virtual
25 service 102 data from a virtual machine instance implemented by the computing resource service provider utilizing a virtual computer system service such as described below.

[0030] In addition, while FIG. 1 illustrates data from the customer 104 traveling to the virtual service 102 from outside the jurisdiction in which the virtual service 102 sits, the data may be provided from within that jurisdiction or from a different jurisdiction such as the
30 jurisdiction in which the backing service 106 is located. It should be further be noted that, while the present disclosure discusses various communications and transmissions as coming from a customer 104 or other entity, unless otherwise clear from context, it should be

understood that such communications are initiated by one or more computing devices of the customer 104, which may be operating pursuant to synchronous user input and/or in accordance with automated processes. In other words, while the customer 104 may refer to an entity such as an organization when data is described as traveling from the customer 104, unless otherwise clear from context, the data is being provided from a computing device of the customer 104 or a computing device operating on behalf of the customer 104. Other variations and additional features are discussed in more detail below.

[0031] FIG. 2 shows an illustrated example of an environment 200 in which various embodiments of the present disclosure may be practiced. In the environment 200, a computing resource service provider 202 may provide a variety of services to a customer 204. The customer 204 may be an organization that may utilize the various services provided by the computing resource service provider 202 to maintain and deliver information to its employees, which may be located in various geographical locations. Additionally, the customer 204 may be an individual that could utilize the various services to deliver content to a working group located remotely. As illustrated in FIG. 2, the customer 204 may communicate with the computing resource service provider 202 through one or more communications networks 206, such as the Internet. Some communications from the customer 204 to the computing resource service provider 202 may cause the computing resource service provider 202 to operate in accordance with various techniques described herein or variations thereof.

[0032] As noted above, a computing resource service provider 202 may provide various computing resource services to its customers. The services provided by the computing resource service provider, in this example, include a virtual computer system service 208, a block-level data storage service 210, a cryptography service 212 (also referred to as a key management service), a data storage service 214 and one or more other services 216, although not all embodiments of the present disclosure will include all such services and additional services may be provided in addition to or as an alternative to services explicitly described herein. Each of the services may include one or more web service interfaces that enable the customer 204 to submit appropriately configured API calls to the various services through web service requests. In addition, each of the services may include one or more service interfaces that enable the services to access each other (e.g., to enable a virtual computer system of the virtual computer system service 208 to store data in or retrieve data

from the data storage service and/or to access one or more block-level data storage devices provided by the block data storage service).

[0033] The virtual computer system service 208 may be a collection of computing resources configured to instantiate virtual machine instances onto virtual computing systems on behalf of the customers 204 of the computing resource service provider 202. Customers 204 of the computing resource service provider 202 may interact with the virtual computer systems' service (via appropriately configured and authenticated API calls) to provision and operate virtual computer systems that are instantiated on physical computing devices hosted and operated by the computing resource service provider 202. The virtual computer systems may be used for various purposes, such as to operate as servers supporting a website, to operate business applications or, generally, to serve as computing power for the customer. Other applications for the virtual computer systems may be to support database applications, electronic commerce applications, business applications and/or other applications.

[0034] The block-level data storage service 210 may comprise a collection of computing resources that collectively operate to store data for a customer 204 using block-level storage devices (and/or virtualizations thereof). The block-level storage devices of the block-level data storage service 210 may, for instance, be operationally attached to virtual computer systems provided by the virtual computer system service 208 to serve as logical units (e.g., virtual drives) for the computer systems. A block-level storage device may enable the persistent storage of data used/generated by a corresponding virtual computer system where the virtual computer system service 208 may only provide ephemeral data storage.

[0035] As illustrated in FIG. 2, the computing resource service provider 202 may operate a cryptography service, which is described in more detail below in connection with FIG. 3. Generally, the cryptography service may be a collection of computing resources collectively configured to manage and use cryptographic keys for customers of the computing resource service provider. Keys used by the cryptography service 212 may have associated identifiers that the customers can reference when submitting requests to perform cryptographic operations (such as encryption, decryption and message signing) and/or other operations, such as key rotation. The cryptography service may securely maintain the cryptographic keys to avoid access by unauthorized parties.

[0036] As noted, the computing resource service provider 202 may also include one or more data storage services 214 which may include an on-demand data storage service and/or

an archival data storage service. As on-demand data storage service may be a collection of computing resources configured to synchronously process requests to store and/or access data. The on-demand data storage service may operate using computing resources (e.g., databases) that enable the on-demand data storage service 208 to locate and retrieve data quickly, so as to allow data to be provided in responses to requests for the data. For example, the on-demand data storage service may maintain stored data in a manner such that, when a request for a data object is retrieved, the data object can be provided (or streaming of the data object can be initiated) in a response to the request. As noted, data stored in the on-demand data storage service may be organized into data objects. The data objects may have arbitrary sizes except, perhaps, for certain constraints on size. Thus, the on-demand data storage service may store numerous data objects of varying sizes. The on-demand data storage service may operate as a key value store that associates data objects with identifiers of the data objects which may be used by the customer 204 to retrieve or perform other operations in connection with the data objects stored by the on-demand data storage service 210. The on-demand data storage service may also be accessible to the cryptography service 212. For instance, in some embodiments, the cryptography service utilizes the on-demand data storage service to store keys of the customers in encrypted form, where keys usable to decrypt the customer keys are accessible only to particular devices of the cryptography service 212. Access to the data storage service by a customer, another service, or other entity may be through appropriately configured API calls.

[0037] An archival storage system may operate differently than an on-demand data storage service. For instance, an archival storage system may be configured to store data in a manner that reduces the costs of storage at the expense of performance in connection with data access. As one illustrative example, the archival storage system may be configured to perform data operations (i.e., store and retrieve data) asynchronously to take advantage of cost savings afforded by batch processing and parallelism. For instance, a client of the archival storage system may receive requests to access data objects stored in the archival storage system, aggregate the requests, process the requests in batches and make the requested data available for retrieval using additional requests. Due to the asynchronous processing, the archival storage system may require another request to retrieve a data object once the data object has been made ready for retrieval, such as by reading the data object

from one or more archival data storage devices and writing the data to one or more staging data storage devices from which the data object is available.

[0038] The on-demand storage system, on the other hand, may be configured to provide better performance with respect to data access. For example, the on-demand storage system may be configured to synchronously process requests to store and/or access data. To enable better performance relative to the archival storage system, the on-demand storage system may operate using additional computing resources (e.g., databases) that enable the on-demand storage system to locate and retrieve data quickly relative to the archival storage system. The on-demand storage system may provide synchronous data access. For example, the on-demand storage system may maintain stored data in a manner such that, when a request for a data object is retrieved, the data object can be provided (or streaming of the data object can be initiated) in a response to the request.

[0039] In the environment illustrated in FIG. 2, a notification service 216 is included. The notification service 216 may comprise a collection of computing resources collectively configured to provide a web service or other interface and browser-based management console that can be used to create topics customers want to notify applications (or people) about, subscribe clients to these topics, publish messages, and have these messages delivered over clients' protocol of choice (i.e., HTTP, email, SMS, etc.). The notification service may provide notifications to clients using a "push" mechanism without the need to periodically check or "poll" for new information and updates. The notification service may be used for various purposes such as monitoring applications executing in the virtual computer system service, workflow systems, time-sensitive information updates, mobile applications, and many others.

[0040] The computing resource service provider 202 may additionally maintain one or more other services 218 based on the needs of its customers 204. For instance, the computing resource service provider 202 may maintain a database service for its customers 204. A database service may be a collection of computing resources that collectively operate to run one or more databases for one or more customers 204. Customers 204 of the computing resource service provider 202 may operate and manage a database from the database service by utilizing appropriately configured API calls. This, in turn, may allow a customer 204 to maintain and potentially scale the operations in the database. Other services include, but are

not limited to, object-level archival data storage services, services that manage and/or monitor other services and/or other services.

[0041] As illustrated in FIG. 2, the computing resource service provider 202, in various embodiments, includes an authentication system 220 and a policy management service 222.

5 The authentication system, in an embodiment, is a computer system (i.e., collection of computing resources) configured to perform operations involved in authentication of users of the customer. For instance, one of the services may provide information from the users to the authentication service to receive information in return that indicates whether or not the user requests are authentic. Determining whether user requests are authentic may be performed in
10 any suitable manner and the manner in which authentication is performed may vary among the various embodiments. For example, in some embodiments, users electronically sign messages (i.e., computer systems operated by the users electronically sign messages) that are transmitted to a service. Electronic signatures may be generated using secret information (e.g., a private key of a key pair associated with a user) that is available to both an
15 authenticating entity (e.g., user) and the authentication system. The request and signatures for the request may be provided to the authentication system which may, using the secret information, compute a reference signature for comparison with the received signature to determine whether the request is authentic.

[0042] If the request is authentic, the authentication service may provide information to the
20 service that the service can use to determine whether to fulfill a pending request and/or to perform other actions, such as prove to other services, such as the cryptography service, that the request is authentic, thereby enabling the other services to operate accordingly. For example, the authentication service may provide a token that another service can analyze to verify the authenticity of the request. Electronic signatures and/or tokens may have validity
25 that is limited in various ways. For example, electronic signatures and/or tokens may be valid for certain amounts of time. In one example, electronic signatures and/or tokens are generated based at least in part on a function (e.g., a Hash-based Message Authentication Code) that takes as input a timestamp, which is included with the electronic signatures and/or tokens for verification. An entity verifying a submitted electronic signature and/or token may
30 check that a received timestamp is sufficiently current (e.g., within a predetermined amount of time from a current time) and generate a reference signature/token using for the received timestamp. If the timestamp used to generate the submitted electronic signature/token is not

sufficiently current and/or the submitted signature/token and reference signature/token do not match, authentication may fail. In this manner, if an electronic signature is compromised, it would only be valid for a short amount of time, thereby limiting potential harm caused by the compromise. It should be noted that other ways of verifying authenticity are also considered
5 as being within the scope of the present disclosure.

[0043] The policy management service 222, in an embodiment, is a computer system configured to manage policies on behalf of customers of the computing resource service provider. The policy management service 222 may include an interface that enables customers to submit requests related to the management of policy. Such requests may, for
10 instance, be requests to add, delete, change or otherwise modify policy for the customer or for other administrative actions, such as providing an inventory of existing policies and the like. The policy management service 222 may also interface with other services to enable the services to determine whether the fulfillment of a pending request is allowable according to policy corresponding to the customer for which the request was made. For example, when a
15 service receives a request, the service (if it has not locally cached such information) may transmit information about the request (and/or the request itself) to the policy management system which may analyze policies for the customer to determine whether existing policy of the customer allows fulfillment of the request and provide information to the service according to the determination.

20 [0044] FIG. 3 shows an illustrative example of an environment 300 in which various embodiments may be practiced. As illustrated in FIG. 3, the environment 300 includes three zones, a customer premise 302, a virtual zone 304, and a backing zone 306. Referring to FIG. 1, the customer premises 302 may include facilities operated by and/or on behalf of the customer 104 described above. Similarly, the virtual zone 304 may correspond to facilities
25 operated by a computing resource service provider in a jurisdiction (e.g., political (legal) jurisdiction) different than to which the backing zone 306 corresponds. In other words, the customer premises 302 may correspond to the customer 104, the virtual zone 304 may correspond to the virtual service 102, and the backing zone 306 may correspond to the backing service 106. As noted above however, the zones do not necessarily correspond to
30 differing geopolitical boundaries, but may correspond to other types of administrative control. For example, the customer premises 302 may correspond to a network of computing resources under administrative control of a customer 308, which may be the customer 104

described above in connection with FIG. 1. Similarly, the virtual zone 304 may correspond to a network of computing resources under the administrative control of a computing resource service provider 304.

[0045] The backing zone 306 may correspond to a network of computing resources under the administrative control of the computing resource service provider or another computing resource service provider. The virtual zone 304 may be implemented in a variety of ways and, generally, as discussed below, the virtual zone 304 is implemented to operate such that, from the perspective of a customer, the virtual zone 304 operates as if it is a fully facilitated backing zone that is independently capable of processing requests without use of the backing zone 306. In other words, despite use of the backing zone 306, the virtual zone 304 is able to receive and cause the processing of requests as if the requests were submitted directly to the backing zone (except for certain manipulations of data, such as encryption that would not otherwise occur if the request were submitted directly to the backing zone 306). For example, as noted above, in some instances the virtual zone 304 may be implemented as an internet PoP in a particular political jurisdiction. The backing zone 306 may correspond to one or more data center facilities having infrastructure capable of providing one or more computing resource services such as described above in connection with FIG. 2.

[0046] Turning to the virtual zone 304, as noted above, the virtual zone 304 may include a storage service proxy 310 and a cryptography service 312. As described in more detail below, the storage service proxy 310 may provide a service interface to which the customer 308 can submit requests. The service interface may be accessible at one or more public network addresses, such as one or more public IP addresses. The storage service proxy 310 may utilize the cryptography service 312 to ensure sure that data sent to a storage service 314 of the backing zone 306 is encrypted. The storage service 314 may also provide its own storage interface which may be directly accessible by the customer 308 and/or other customers. The backing zone 306 may also include an authentication service 316. The authentication service 316 may be a collection of computing resources such as described above that serve to enable the storage service proxy 310, cryptograph service 312, and storage service 314 to determine whether to fulfill requests submitted by the customer 308 or by another component of the environment 300.

[0047] It should be noted that the storage service proxy 310 and the storage service 314 may correspond to a data storage service of one or more computing resource service

providers. For example, the storage service 314 may be an on-demand storage service, an archival data storage service, a block level data storage service, a database service such as a relational data base service, a noSQL database storage service, or a data warehouse data storage service. Generally any service that operates to store data on behalf of one or more customers may be utilized in the environment 300. It should also be noted that while storage services are used for the purpose of illustration, the virtual zone 304 and backing zone 306 may include computing resources for other types of services such as virtual computer system services, computing resource management service, and/or generally any computing resource service that may be provided by a computing resource provider and which may involve access to customer or other sensitive data. Accordingly, the backing zone 306 may include facilities to implement such a service and the virtual zone 304 may include a corresponding service interface that operates as an API proxy for that service. In addition, the virtual zone 304 may also include multiple different services, each with a corresponding service proxy in the virtual zone 304. As noted above, a virtual zone may be provided in various ways and the ways in which a virtual zone may be provided are not limited to that which is illustrated in FIG. 1 and described above.

[0048] FIG. 4 accordingly shows an illustrative example of an environment 400 in which various embodiments may be practiced. For example, as illustrated in FIG. 4, the environment 400 includes customer premises 402, a virtual zone 404, and a backing zone 406 such as described above in connection with the FIG. 3. For example, the customer premises 402 may include one or more facilities with computing resources of a customer 408 or that is utilized on behalf of the customer 408. As illustrated in FIG. 4, the virtual zone 404 may be a zone located on the customer premises 402. For example, a computing device of a network of the customer premises 402 may provide a web service interface to which requests may be submitted. In some embodiments, the web service interface is accessible at one or more private network addresses, such as one or more private IP addresses. Customer computing devices or, in some embodiments, any computing devices may submit requests to the interface for the virtual zone 404 in order to have the requests processed which may include use of facilities of the backing zone 406.

[0049] As illustrated in FIG. 4, the virtual zone 404, as described above in connection with FIG. 3 includes a storage service proxy 410 and a cryptography service. As noted above, the storage service proxy 410 may include a storage service interface serving as an API proxy for

a storage service 414 located in the backing zone 406. As with the storage service proxy 410, requests may be submitted by the customer 408 to the storage service proxy 410 and fulfillment of their requests may utilize the storage service 414. The cryptography service 412 may be utilized by the storage service proxy 410 to ensure that data transmitted to the storage service 414 by the storage service proxy 410 is encrypted when appropriate in accordance with the various embodiments. Similarly, an authentication service 416 in the backing zone 406 may be utilized by the storage service proxy cryptography service 412 and storage service 414 to enable determinations of whether requests are authentically submitted and therefore fulfillable, if otherwise fulfillable (e.g., where fulfillment would be in accordance any applicable policy.

[0050] It should be noted that as with all environments described here in variations are considered as being within the scope of the present disclosure. For example, FIG. 4 shows a cryptography service 412 inside of the virtual zone 404. The cryptography service may be operated, for example, as a hardware security module (HSM) or other computing device that manages cryptographic keys on behalf of the customer 408. It should be noted, however, the cryptography service may be located in other zones such as the backing zone 406 or another virtual zone which is not illustrated in the figure. For instance, the cryptography service may be in a virtual zone such as described above in connection with FIG. 3. Generally, the cryptography service may be a service exclusively dedicated to the customer 408 or may be a multitenant service that manages cryptographic keys on behalf of multiple customers of a computing resource service provider as appropriate. It should be also noted that FIG. 4 shows a customer premises having a single virtual zone 404, however, a customer premise may include multiple virtual zones which may be utilized for various purposes. For example, the customer 408 may be an organization and different virtual zones may be used by different administrative entities within the organization. In this manner, data mingling and other issues which may be of concern to the customer 408 may be managed through the use of multiple virtual zones. Similarly, while a storage service 414 and a storage service proxy 410 are utilized for the purpose of illustration, one or more virtual zones of the customer premises 402 may include multiple service proxies to multiple corresponding services. Generally, the techniques described and suggested herein may be used to enable use of multiple services each with a corresponding proxy.

[0051] Further, as noted above, various service proxies may be accessible via public network addresses, such as IP addresses. In some embodiments, a service proxy has a corresponding uniform resource locator (URL) that is different than a URL used for the corresponding backing service. For instance, in the example of a proxy and service being in different geographic jurisdictions, a proxy may have a URL in the form of storageservice<dot>country1<dot>serviceprovider<dot>com while the backing service may have a URL of the form storageservice<dot>country2<dot>serviceprovider<dot>com, where <dot> represents the character in the brackets used for delimiting domains and sub-domains. In other examples, the proxy and the storage service may have the same URL but different public IP addresses. Distributed DNS servers may be configured to resolve the URL to an IP address for the proxy or backing service that is geographically closest. As yet another example of a variation considered as being within the scope of the present disclosure, a backing service may be configured to reroute requests through the proxy so that the backing service receives data in encrypted form, where appropriate. Other variations are also considered as being within the scope of the present disclosure.

[0052] FIG. 5 shows an illustrative example of a cryptography service which may be used to implement various embodiments of the present disclosure. The cryptography service 500 illustrated in FIG. 5 may be used, for example, as the cryptography service described above in connection with FIGS. 2, 3 and 4. In an embodiment the cryptography service 500 includes various subsystems which enable the cryptography service 500 to perform cryptographic operations using cryptographic keys securely managed by the cryptography service 500. For example, as illustrated in FIG. 5 the cryptography service 500 includes a request processing subsystem 502. The request processing subsystem 502 may include one or more web servers and one or more application servers that collectively operate to receive and process requests submitted to the request processing subsystem 502.

[0053] In an embodiment the request processing subsystem 502 includes one or more web servers that provide a web service interface to the cryptography service 500 such that web service calls (from a customer or other service) may be made to the request processing subsystem 502 via the web service interface in order to cause the performance of various cryptographic operations. As noted above the cryptography service 500 may securely manage cryptographic keys. Accordingly, various components of the cryptography service 500 may enable such secure management. In an embodiment the cryptography service 500

includes a plurality of cryptographic modules 504 and customer key storage 506. Each cryptographic module 504 may be a subsystem of the cryptography service 500 that securely manages cryptographic keys which may be referred to as domain keys. In an embodiment the cryptographic modules 504 each store a set of one or more domain keys that is common to all
5 of the cryptographic modules 504. In other words each of the cryptographic modules 504 may store one of more of the same domain keys. Storage of the domain keys may be performed so that the domain keys never leave the cryptographic modules 504 and generally are inaccessible to any subsystems of the cryptography service 500 or other systems.

[0054] In an embodiment, for example, the cryptographic modules are security modules,
10 which may be hardware security modules (HSMs). The hardware security modules may be configured with computing resources such as processors and memory storing executable instructions that enable the cryptographic modules to perform cryptographic operations. The cryptographic modules may be configured to be tamper-proof such that if intrusion into the interior of the cryptographic modules 504 is detected, domain keys stored within the
15 cryptographic module may be erased, thereby preventing access to the domain keys by way of physical intrusion into a cryptographic module 504. As noted above, in an embodiment the cryptography service 500 includes a repository for customer keys, which is illustrated in FIG. 5 as the customer key storage 506. In alternate embodiments, however, one or more security modules store the customer keys without the use of external customer key storage
20 506. In such embodiments, the customer keys may be accessed from memory and there may not be a need to decrypt using a domain key.

[0055] Returning to the embodiment illustrated, each customer key corresponds to a corresponding customer of the cryptography service 500, where one customer may have multiple corresponding customer keys but where keys are not shared among customers. As
25 such the cryptography service 500 may store customer keys in the customer key storage 506 for multiple customers. Similarly, the cryptography service 500 may perform various cryptographic operations through the cryptographic modules 504 for multiple customers. As illustrated in FIG. 5, customer keys stored in the customer key storage 506 are encrypted under a domain key stored by the cryptographic modules 504. It should be noted that the
30 brackets around the customer key with the domain key annotating the right-hand brackets is provided as notation indicating encryption of the customer key under the domain key. In this manner customer keys stored in the customer key storage 506 are stored in a manner that

requires access to a domain key in order to access the customer key. Thus access to data in the customer key storage 506 does not by itself provide access to data encrypted under a customer key. Therefore, customer keys for multiple customers may be stored external to the cryptographic modules 504, therefore providing scalability without requiring the security modules 504 to store all keys which they may use to perform cryptographic operations.

[0056] The cryptographic modules may be configured to, upon a request to perform cryptographic operation, using a specified customer key, access the encrypted specified customer key from the customer key store 506, use a domain key to decrypt the customer key and use the decrypted customer key to perform the cryptographic operations as discussed in more detail below. It should be noted that while the customer key storage 506 is illustrated as being within the cryptography service 500, the customer key storage may be located in another system such as a data storage service which may be in the same or in a different zone than the cryptography service 500.

[0057] FIG. 6 is an illustrated example of a process 600 which may be performed to encrypt a data key used to encrypt data. The process 600 may be performed by any suitable system such as by the cryptography service 500 discussed above in connection with FIG. 5. In an embodiment the process 600 includes receiving 602 a request for a data key. The request 602 may be in the form of an appropriately configured API call such as a web service call with various parameters that enable the system performing the process 600 to select a customer key to be used as described in more detail below to provide a data key. For example, the API call may include a parameter having a value that specifies an identifier for a customer key. It should be noted that the customer key may be implicitly determined. For instance, the request coming from a particular customer may enable the cryptography service to associate the customer key with the customer and determine which customer key to use. In an embodiment the process 600 includes determining 604 whether the request is authentic.

[0058] Determination 604 whether the request is authentic may be performed in any suitable manner. For example, in some embodiments the request may be electronically (digitally) signed in a manner that is verifiable by the system performing the process 600 or another system in which the system performing the process 600 communicates. Referring to FIG. 3 the request may be signed using a secret key shared between the customer 308 and the authentication service 316. The cryptography service, if performing the process 600, may provide the request and the signature for the request to the authentication service 316 which

may generate a reference signature based on the request and its own copy of the secret key to determine whether the digital signature that was received with the request matches. If the signature generated by the authentication service matches, the authentication service 316 may provide a communication to the cryptography service 312 that the request is authentic,
5 thereby enabling the cryptography service 312 to determine that the request should be fulfilled. A similar process may be performed in connection with FIG. 4.

[0059] It should be noted that while not illustrated in the figure, additional determinations regarding whether the request should be processed may be made. For example, process 600 may include determining whether policy allows the request to be fulfilled. The request may
10 be a policy on a key to be used on one of more principals such as a user that submitted the request or otherwise. Such additional operations may also be performed as part of other processes, including those described below. If it is determined 606 that the request is authentic, the process 600 may include generating 606 a data key. A data key may be a
15 cryptographic key to be used to encrypt data, such as data of a request to store the data in a storage service. The data key may be randomly, pseudo-randomly or otherwise generated. In addition, while the process 600 illustrates generation 606 of the data key, a data key may be pre-generated and accessed from memory.

[0060] In an embodiment, the process 600 includes accessing 608 an encrypted customer key. Referring to FIG. 5, for example, a cryptographic module 504 of the cryptography
20 service 500 may submit a request to the customer key storage 506 for the encrypted customer key, which may be encrypted under a domain key. The request to the customer key storage 506 may include an identifier of the customer key to be obtained. Once the encrypted customer key has been accessed 608 the process 600 may include using 610 the domain key to decrypt the customer key. The decrypted customer key may then be used 612 to encrypt
25 the data key. The data key and the encrypted data key may then be provided 614 in response to the request, thereby enabling the requester to utilize the data key for the encrypted of data as discussed in more detail below.

[0061] Returning to the determination 604 whether the request is authentic, if it is determined 604 that the request is not authentic, such as if an authentication service indicates
30 that the request is not authentic, the process 600 may include denying 616 the request. Denying 616 the request may be performed in various ways in accordance with various embodiments. Denying the request may be performed, for example, by responding the

request with an indication that the request was denied and/or one of more reasons for the denial. Denying the request may also include simply inaction such as not responding to the request. Generally any suitable way in which a request may be denied may be used. It should be noted that FIG. 6 and generally all processes described herein show a particular order or operations, although the scope of the present disclosure is not necessarily limited to the order or operations performed therein. For example, FIG. 6 shows generating 606 a data key occurring before access 608 of an encrypted customer key. Further, operations may be performed in a different order or in parallel. Similarly, using 601 the domain key to decrypt a customer key may be performed before generation 606 of the data key or otherwise obtaining the data key. Other variations are also considered as being within the scope of the present disclosure.

[0062] FIG. 7 shows an illustrative example of a process 700 which may be used to decrypt a data key, such as a data key that was used to decrypt data and persisted in encrypted form for later retrieval of the data. The data key may be encrypted in any suitable manner, such as by performance of the process 600 discussed above in connection with FIG. 6. Further, the process 700 may be performed by any suitable system such as the same system that performed the process 600 discussed above in connection with FIG. 6 or another system. In an embodiment the process 700 includes receiving 702 a request to decrypt a data key. The request may be an appropriately configured API call such as described above. The request may originate, for example, from a service proxy such as described above. A determination may be made 704 whether the request is authentic, such as by communicating with an authentication service that analyzes an electronic signature and provides an indication whether the signature is authentic. Further, as discussed above in connection with FIG. 6, other operations may be performed in determining whether to fulfill a request, such as operations in connection with policy enforcement.

[0063] Returning to the embodiment illustrated in the figure, if it is determined 704 that the request is authentic, the process 700 may include accessing 706 an encrypted customer key such as described above. The access customer key may then be used 710 to decrypt the data key. The data key may then be provided 712 in response to the request. In this manner a computer system that submitted the request may use the decrypted data key to perform one of more cryptographic operations such as decryption of data that was encrypted under the data key. Returning to the determination 704 whether the request is authentic, the process 700

may include denying 714 the request if determined 704 that the request is not authentic or otherwise upon determining that the request should not be fulfilled.

[0064] FIG. 8 shows an illustrative example of a process 800 which may be used to store data in a data storage service. The process 800 may be performed by any suitable system
5 such as a service proxy described above. In an embodiment the process 800 includes receiving 802 a request to store data. The request may be in the form of an appropriately configured API call such as a web service call that includes values for parameters that enable the request to be fulfilled and that enable determination of whether the request should be fulfilled. The request may originate from any suitable computer system such as a customer
10 computer system such as described above. Upon receipt 802 of the request, a determination may be made 804 whether the request is authentic. The determination 804 whether the request is authentic may be made in any suitable way such as described above in connection with the processes 600 and 700 described in connection with FIGS. 6 and 7, respectively. For example, a service proxy may communicate with an authentication service in order to
15 receive a decision from the authentication service whether the request is authentic. As with the processes described above, additional operations such as checks whether fulfillment of the request is in compliance with policy may also be performed.

[0065] If it is determined 804 that the request is authentic and/or generally that the request should be fulfilled, the process 800 may include requesting 806 a data key from a local
20 cryptography service. The local cryptography service may be a cryptography service such as described above that is in the same zone as the system performing the process 800. For instance, referring to FIG. 3, the cryptography service may be the cryptography service 312. Referring to FIG. 4, the cryptography service may be the cryptography service 412. It should be noted that, as with all processes described herein, variations are considered as being within
25 the scope of the present disclosure and the cryptography service is not necessarily a local cryptography service but it may be a cryptography service that is in a zone that is different from a zone in which a data storage service in which the data is to be ultimately stored is located. In this manner the cryptography service is not necessarily local but in a zone that is different from the zone where the data will be stored. Further the keys required for accessing
30 the data are stored in a different zone than the encrypted data itself.

[0066] As illustrated in FIG. 8 a response to the request for the data key from the local cryptography service may be provided, and an encrypted data key may be received 808 from

the cryptography service. The data key may be encrypted by a customer key, which may have been implicitly determined by the cryptography service or which may have been specified in the request to the local cryptography service. The received data key may then be used 810 to encrypt the data. Once the data has been encrypted 810 the process 800 may
5 include generating 812 a data object that comprises the encrypted data and the encrypted data key. The data object that was generated 812 may be transmitted 814 to a backing storage service in another zone. Referring to FIG. 3, for example, the storage service proxy 310 may transmit the data object to the storage service 314 via an appropriately configured API call such as a web service call to the storage service 314. Referring to FIG. 4, the storage service
10 proxy 410 may transmit the data object to the storage service 414 via an appropriately configured API call.

[0067] Once the data key is no longer needed by the system performing the process 800, the process 800 may include destroying the unencrypted data key. Destroying 816 the unencrypted data key may be performed in any suitable manner and generally in any manner
15 in which access to the data key is lost by the system performing the process 800. As one example, the data key in unencrypted form may be managed by the system performing the process 800 such that the data key is only stored in volatile memory such as random access memory (RAM) or a central processing unit (CPU) register. In this manner, when power is cut to the volatile memory, the access to the stored unencrypted data key is lost, or if power is
20 never cut the memory locations in which the data key is stored will eventually be overwritten as the system performing the process 800 continues to operate such as by performing the process 800 additional times as future requests are received. As another example, the data key may be destroyed by overriding any memory locations in which the data key is stored, whether volatile or non-volatile memory with other data, which may be a sequence of 0 bits,
25 a sequence of 1 bits, a sequence of random bits, or a sequence of bits that does not contain sensitive information. Generally, any manner of causing a loss of access to the data key may be used. In addition, as noted above, destruction 818 of the unencrypted data key may be performed synchronously in performance of the process 800 and not necessarily as an operation in the order illustrated in FIG. 8, or may be performed asynchronously, such as part
30 of a process that operates to eventually destroy data keys or allow data keys to be overwritten with other data.

[0068] Returning to the determination 804 whether the request is authentic, if it is determined 804 that the request is not authentic or otherwise that the request should not be fulfilled, the process 800 may include denying 818 the request such as described above. As with all processes discussed herein, variations are considered as being within the scope of the present disclosure. For example, as illustrated in FIG. 8, a request for a data key is submitted to a cryptography service that generates or otherwise obtains a data key and provides in response the data key in plaintext and cypher text form. As an alternative a system performing the process 800 may generate or obtain a data key itself and provide the data key to the cryptography service for encryption. The cryptography service may then provide the encrypted data key back and not necessarily provide the data key back since the system performing the process 800 may already have access to the data key. Also as noted above, the request to store data that is received 802 is described as being received from a customer computing system such as described above. In various embodiments, the request does not necessarily originate from a customer computer system but may originate from another computer system despite the data ultimately being stored as a service for the customer.

[0069] In addition, as another example of a variation, a request to store data may not be received externally from another system. Performance of the process 800 may, for example, include generation of the data, and upon generation of the data and performing operations that result in the data being encrypted and transmitted to a data storage service such as described above. Further, the process 800, as illustrated in FIG. 8, includes generation 812 of a data object that comprises an encrypted data and the encrypted data key. As an example, the encrypted data and encrypted data key may be concatenated together to form the data object. In this manner the encrypted data key and the encrypted data object are persisted together for later access such as described below. However, in various embodiments, the encrypted data key and encrypted data are not necessarily persisted together but may be persisted in different logical data containers of a data storage service in different storage services or in other ways. For instance, the encrypted data key may be stored locally while the encrypted data is transmitted to a storage service in accordance with techniques described above. Metadata maintained may persist an association between the encrypted data key and the data encrypted under the key. Other variations are also considered as being within the scope of the present disclosure.

[0070] FIG. 9 illustrates an illustrative example of a process 900 which may be performed to retrieve data from a data storage service where the data may have been stored by the data storage service in accordance with the process 800 described above in connection with FIG. 8. The process 900 may be performed by any suitable system such as by the system that performed the process 800 discussed above in connection with FIG. 8 or by another system, such as another system in a zone that is different from the zone in which the data storage service is located. As illustrated in FIG. 9, the process 900 includes receiving 902 a request to retrieve data, where the request to retrieve data may be in the form of an appropriately configured API call such as described above. A determination may be made 904 whether the request is authentic, such as described above, and if determined 904 that the request is authentic, the process 900 may include obtaining 906 encrypted data and an encrypted data key from a backend storage service. For example, referring to FIG. 3, the storage service proxy 310 may submit a request to the storage service 314 to retrieve a data object that comprises the encrypted data key in the encrypted data. The storage service 314 may provide the data object that comprises the encrypted data and the encrypted data key in response. Referring to FIG. 4, for example, the storage service proxy 410 may submit a request to the storage service 414 for a data object that comprises the encrypted data and the encrypted data key, and the storage service 414 may provide, in response, the data object that comprises the encrypted data and encrypted data key. As noted above, however, the encrypted data and encrypted data key are not necessarily persisted together and performance of the process 900 may include obtaining the encrypted and including the encrypted data key in various ways and in accordance with various embodiments, such as by retrieving the encrypted data from a system that stores the encrypted data and retrieving the encrypted data key from another system that stores the encrypted data key.

[0071] Once the encrypted data and encrypted data key have been obtained 906, the process 900 may include requesting 908 decryption of the data key from a cryptography service which may be a local cryptography service such as described above or any suitable cryptography service such as a cryptography service in a zone that is different from a zone the data storage service is located. In response to the request 908 for decryption of the data key from the cryptography service, the decrypted data key may be received 910 from the cryptography service to which the request was submitted. The decrypted data key may then be used to decrypt the encrypted data, and the decrypted data may then be provided 914 in

response to the request to retrieve the data. Returning to the determination 904 whether the request is authentic, if it is determined 904 that the request is not authentic or otherwise that the request should not be fulfilled, the process 900 may include denying 916 the request. In addition, while not illustrated in the figure, the process 900 may include destroying the unencrypted data key such as described above. The unencrypted data key may be destroyed, for example, in instances where the data is to remain stored by a storage service in encrypted form and therefore in a manner such that unauthorized access to the data key could be problematic.

[0072] As noted above, the types of services which may utilize the various techniques described herein may vary in accordance with the various embodiments. In some examples, for instance, a service proxy for a database service may be located in one zone where the service proxy services as an API proxy to a database service in another zone. Referring to FIG. 3, for example, the storage service proxy 310 may be a service proxy for a database service which may be the storage service 314. Similarly referring to FIG. 4, the storage service 414 may be a database service to which the storage service proxy 410 acts as an API proxy. As noted above, some, but not all, data sent from a service proxy to a backing service may be encrypted. FIG. 10 accordingly shows an illustrative example of data which may be stored by a database service. In particular, FIG. 10 shows an illustrative diagram of data organized into a relational table 1002 stored by a virtual data base service which may be, for instance, a service proxy such as described above. As illustrated in FIG. 10, the data base table 1002 comprises various data which may be, for instance, data about sales transactions, although the scope of the present disclosure is not limited to the specific types of data mentioned herein. In this particular example, each column of the table 1002 corresponds to a different type of information. The first column shown, for instance, may correspond to first names, the second column may correspond to last names, the third illustrated column may correspond to transaction amounts, and the last column may correspond to dates on which the corresponding transaction occurred. A row in the table 1002 may, for instance, identify the person who made a transaction, the transaction, and the date on which the transaction occurred. As indicated by the ellipses, other information may be included as well, such as an identifier for an item purchased, a payment method (credit card, e.g.) and other types of data. Some of the data in the table 1002 may be considered sensitive. For instance, the first and last name which may be names of customers may be considered sensitive data and may be

subject to various privacy laws, rules, regulations, or general preferences. Some of the data may not be considered sensitive such as the amounts of the transactions and the dates of which they occurred.

[0073] Accordingly, performance of the various techniques described above may include encrypting some, but not all, of the data in the table 1002 before it is sent to a backing database service. FIG. 10 shows an illustrative example of a table 1004 illustrating how the same data may be organized at the backing database service. In particular, as indicated by the arrow transitioning between the virtual database service and the backing database service, data in the table 1002 transformed, resulting in the table 1004 where the first two columns corresponding to first and last names respectively, and possibly other columns, are encrypted. The values in the tables corresponding to the amounts, however, are left unencrypted. In this manner, as discussed in more detail below, the backing database service may be able to provide at least some functionality with respect to the unencrypted data, such as by processing queries using the unencrypted data. While the encrypted columns of the relational database table are consecutive, the columns that are encrypted are not necessarily consecutive. Further, while FIG. 10 shows illustrative examples of a relational database table, the scope of the present disclosure is not limited to relational databases and related organizations of data sets, but also extends to other types of databases and generally any types of data storage services that store data in a structured manner. Generally, any type of database that is able to process queries may be used in accordance with the various embodiments.

[0074] When a database of a computing resource provider stores some but not all data that is encrypted, such as in accordance with the techniques described above, processing of database queries may occur across different zones. In other words, some processing may occur in one zone and other processing may occur in other zones. FIG. 11 accordingly shows an illustrative example of a process 1100 which may be used to process a database query. The process 1100 may be performed by any suitable system such as by a service proxy described above. For example, a service proxy may perform the process 1100 in order to process queries that it receives despite the actual data being stored by a backing service in another zone. In an embodiment, the process 1100 includes receiving 1102 a query for a database. The query may be received encoded in an appropriately configured API call to the system performing the process 1100. The query may then be parsed 1104 or otherwise

analyzed in order to generate a sensitive query and a non-sensitive query, where the sensitive query and the non-sensitive query are configured such that sequential execution of the non-sensitive query then the sensitive query, with some intermediate data modification on a result of the non-sensitive query as described in more detail below, provides the same result as
5 executing the query.

[0075] Parsing the query may be performed in any suitable manner. For example, in some embodiments, columns of a database table are tagged in a manner indicating whether the columns contain sensitive data. Referring to FIG. 10, for example, the first two columns
10 illustrated may be tagged as sensitive where as other columns may be tagged as non-sensitive where tagging as sensitive or non-sensitive may be implicit by the absence of a tag. The tags may enable a storage proxy to determine which data to encrypt before transmitting data to a backing service. The service proxy may, for instance, be configured to receive data through its API interface, identify which columns in a database the data affects, determine which, if any, columns are tagged as sensitive, and encrypt the data for the identified columns before
15 transmitting to the backing service. Parsing the query may be performed by identifying portions of the query that require a search of columns tagged as sensitive, or generally a search of data tagged as sensitive. Similarly, parsing the query may be performed by identifying of the query requiring a search of data tagged as non-sensitive. Turning to the illustrative example of FIG. 10, for instance, a query may be configured to identify data in a
20 relational database that satisfies one or more conditions on a last name as well as one or more conditions on a transaction amount. As noted above, a column for last names may be tagged as sensitive whereas a column of transactions amounts may be tagged as non-sensitive. In this manner, parsing such a query may be performed by extracting from the query a sub-query for identifying data that satisfies the one or more conditions on the transaction amount.
25 Some of the data identified may not satisfy the one or more conditions on the last name. In this manner a sub-query configured to identify data that satisfies the one or more conditions on the last name may be identified as the sensitive query.

[0076] Returning to FIG. 11, the non-sensitive query may be forwarded 1106 to a backing database service such as in the form of an appropriately configured API call to the backing
30 database service. The backing database service may receive the non-sensitive query and process the non-sensitive query on a database the backing database services maintains on behalf of a customer for which the query was received 1102. The backing database service

may then generate a preliminary response and provide that generated preliminary response which, as noted above, may be over-inclusive as it may include data that does not satisfy the sensitive query that was generated 1104. Accordingly, the process 1100 includes receiving 1108 the preliminary response from the backing database service. The preliminary
5 response may be received, for example, as a response to the API call that was made to the backing database service.

[0077] Once the preliminary response was received 1108 from the backing database service, the process 1100 may include obtaining 1110 an encrypted data key. Obtaining 1110 the encrypted data key may be performed in any suitable manner. For example, the
10 encrypted data key may be included with the preliminary response. And as another example, the encrypted data key may be locally stored in another storage service which may be in the same or in a different zone as the zone in which the system performing the process 1100 is located. Once the encrypted data key has been obtained 1110 the process 1100 may include requesting 1112 decryption of the data key from a cryptography service such as described
15 above. The decrypted data key may be, therefore, received 1114 from the cryptography service and the data key may be used 1116 to decrypt 1116 encrypted portions of the preliminary result that was received from the backing database service.

[0078] It should be noted that encryption, and therefore decryption, may be performed in various ways in accordance with the various embodiments. For example, each entry in a
20 database table that is encrypted may be encrypted separately. In this manner, the data that is returned in the preliminary result is decryptable regardless of whether the preliminary result includes all the data that was encrypted. Further, as noted, a single data key may be used to decrypt all the data that is encrypted in the preliminary result. Accordingly, depending on a cryptographic cypher that is used, each entry in the database that is encrypted may be
25 encrypted using a different initialization vector (nonce). Numerous variations are considered as being within the scope of the present disclosure, such as encrypting each entry with a different data key, encrypting each column with a different data key, and generally performing encryption in various ways.

[0079] Returning to FIG. 11, once the data key has been used 1116 to decrypt the encrypted
30 portions of the preliminary result, the process 1100 may include executing 1118 the sensitive query on the decrypted preliminary result to obtain a query result. The query result may then be provided 1120 in response to the query that was received 1102. In this manner, various

technical advantages are achieved. For example, as noted above, a service proxy, which also may be referred to as a virtual database service, may include limited infrastructure. A database service, on the other hand, may include much greater infrastructure in order to handle large amounts of data. The virtual database service may, for example, lack the
5 infrastructure that would enable the virtual database service to handle the amounts of data that the backing database service handles. In this manner, the vast infrastructure of the backing database service may be used to perform the initial processing of the non-sensitive query in a zone where some of the data is encrypted for various reasons discussed above. The much more limited infrastructure of the virtual database service may be used to finish
10 processing of the query. In this manner, despite the presence of data considered sensitive, the infrastructure of the database service is able to be utilized.

[0080] In addition, while FIG. 11 shows a process where a query is received to a service proxy and the service proxy generates two queries, one for the backing service to execute and the other for the service proxy to execute, the process 1100 may be adapted to operate in
15 different ways. For instance, in some embodiments, the complete query may be forwarded to the backing service which may itself generate two queries and pass at least one to the service proxy with the preliminary result. As another example, the backing service may process the complete query while ignoring any conditions involving subsets of data tagged as sensitive (or ignoring particular conditions, e.g. conditions required to be satisfied). The proxy may
20 also process the whole query on the preliminary result. Other variations, including adaptations for other types of databases, may be used.

[0081] As noted above, various embodiments of the present disclosure may utilize numerous zones, numerous service proxies, and numerous backing zones. In some instances, a service proxy may selectively provide data to different backing zones. For example, a
25 storage service may have different advantages in different zones. A data storage service in one zone, for example, may be cheaper than the same or a similar data storage service in another zone. As another example, a data storage service in one zone may be better for latency reasons than the same or similar data storage service in another zone. Despite the advantages of one zone over another, as noted above, various concerns may result in a
30 requirement or preference that data be stored in one zone or another zone. Different jurisdictions may have different regulations regarding various types of data, for instance. Thus, in order to achieve some advantages and/or generally comply with various regulations,

some data may be stored in one zone and other data may be stored in another zone in order to comply with various requirements and/or preferences. [0082] Accordingly, a storage service proxy (or proxy for another service) may actively make decisions where to store data based at least in part on various factors. For example, some customers may request through
5 an account configuration or as a parameter in an API call, that their data be stored in a particular zone. As another example, some types of data may be stored for the same customer in one zone while other types of data may be stored in another zone due to varying regulatory requirements. As yet another example, a customer may configure computing resources of a computing resource service provider so that the service proxy applies one or
10 more DLP policies so that some data is sent to one zone and other data is sent to another zone. FIG 12 accordingly shows an illustrative example of an environment 1200 in which various embodiments that utilize selection from multiple zones may be practiced.

[0083] As illustrated in FIG. 12, the environment 1200 includes customer premises 1202, a virtual zone 1204, and one or more backing zones 1206. In this particular example, FIG. 12
15 illustrates n backing zones where n is a positive integer. It should be noted that while the virtual zone 1204 relative to the customer premises 1202 are illustrated as with FIG. 3, variations such as those shown in FIG. 4 are considered as being within the scope of the present disclosure. As illustrated in FIG. 12, a customer 1208 submits requests and receives responses from a storage service proxy 1210 or other service proxy and a photography
20 service 1212. Each of the backing zones 1206 may include a backing service and an authentication service such as described above, although such services are not illustrated in FIG. 12 for the purpose of simplification. In an embodiment, the customer 1208 submits requests to the storage service proxy 1210 which then may select and submit corresponding requests to one of the backing zones 1206 as appropriate. Appropriateness may be
25 determined in accordance with DLP policy, customer preferences, account configuration, API call parameters and the like.

[0084] FIG. 13 shows an illustrative example of a process 1300 which may be used to utilize various backing services, such as illustrated in FIG. 12, in accordance with various embodiments. As illustrated in FIG. 13, the process 1300 includes obtaining 1302 customer
30 data. Customer data may be obtained, for example, from the customer's computer systems themselves or from other computer systems on behalf of the customer, such as when the customer utilizes a computer resource service provider to provide a service to various

members of the public or generally to other customers of the customer. When the customer data is obtained 1302 the process 1300 may include determining 1304 a backing zone for the customer data. Determining 1304 the backing zone can be performed in various ways in accordance with variance embodiments. For example, as noted above, account configuration
5 for a customer may indicate which backing zone is to be used. As another example, the nature of the data itself may be used to determine which backing zone to use. For instance, if data is organized according to a schema, the data's location according to the schema may be used to determine which backing zone to use. As yet another example, a source (network address, user identity, political jurisdiction, etc.) of the customer data may be used to
10 determine the backing zone. Generally, any way in which a backing zone may be determined may be used.

[0085] Upon determining 1304, the backing zone for the customer data the process 1300 may include requesting 1306 a data key from a local cryptography service such as described above, or generally from another suitable cryptography service such as described above.

15 Accordingly, a data key and encrypted data key may be received 1308 from the cryptography service to which the request for the data key was submitted. The data key may then be used 1310 to encrypt the customer data and a data object comprising the encrypted customer data and the encrypted data key may be generated 1312. The data object may then be transmitted 1314 to a backing storage service in the determined backing zone. The
20 unencrypted data key may then be destroyed 1316 such as described above.

[0086] It should be noted that variations of the process 1300 are considered as being within the scope of the present disclosure including variations of the various processes described above for transmitting data to a backing service. FIG. 14 shows an illustrative example of a process 1400 for selectively encrypting data and providing the data to a backing service in
25 accordance with an embodiment. In particular, the process 1400 utilizes various data loss prevention techniques such as those described in U.S. Pat. No. 8,416,709, which is incorporated herein by reference. The process 1400 of FIG. 14 may be performed by any suitable system, such as by a service proxy such as described above. The traffic may include, for example, one or more data packets such as IP or transmission control protocol (TCP)
30 packets, handshake requests, such as a portion of the three part TCP handshake or an SSL handshake, or other appropriate data packets. The network traffic may be received from a customer such as described above or another entity associated with the customer such as

described above. In some embodiments, the traffic is received through an application programming interface (e.g., web service interface) of a system performing the process 1400. The network traffic may be analyzed 1404 with respect to one or more DLP policy criteria. DLP policy criteria may include those discussed in U.S. Pat No. 8,416,709, noted above. For
5 example, data in IP or TCP packets may be inspected for data of certain data types, such as credit card numbers, social security numbers, and/or any other types of data that may be considered sensitive or otherwise for which modification is desired.

[0087] A determination may be made 1406 whether the DLP's criteria are satisfied. If it is determined 1406 that the DLP criteria are satisfied, the process 1400 may include
10 encrypting 1408 the network traffic that was received, and transmitting 1410 the network to the backing service. If, however, it is determined 1406 that the DLP criteria are not satisfied, then the network traffic may be transmitted 1410 to the backing service without being encrypted.

[0088] As discussed above, various variations are considered as being within the scope of
15 the present disclosure, including decrypting some but not all of the data when DLP criteria are satisfied. In addition, additional actions may be taken in addition to or as an alternative to encryption of the data. Sample actions include, but are not limited to snapshotting, i.e., copying, the network traffic that was received and persisting the snapshot in a data storage service such as the backing service or another data storage service performing packet tracing,
20 performing a quarantine of the network traffic that was received, initiating enhanced logging of network traffic, and/or denial of the action. Generally, any type of action configured to address DLP concerns may be used. In addition, the actions that are taken when a DLP or other policy criteria are satisfied may be configurable by a customer. Generally, data may be manipulated in accordance with customer specifications utilizing techniques such as those
25 described in U.S. Patent Application No. 13/491,403, filed on June 7, 2012, entitled "FLEXIBLY CONFIGURABLE DATA MODIFICATION SERVICES," which is incorporated herein by reference.

[0089] In particular, a customer may specify certain rules by which various types of data, inbound and/or outbound from customer devices or other devices, may be modified, upon
30 which various components of the distributed computing system are utilized to implement the rules, e.g., using packet mangling techniques. For example, the customer may specify that data through a service proxy to specific external device types or locales must conform to a

customer-provided specification (e.g., for regulatory compliance and/or performance optimization), upon which the distributed computing system determines the necessary alterations and data patterns (or other markers) to which they apply. Thereafter, in the example given, the implementation may include redirection of some or all of the network traffic between the customer and the external device in question to a component of the distributed computing system, such as a backing service. Upon processing in the determined manner, the redirected data may be relayed to the original destination. As will be contemplated, a similar process may be utilized for inbound network traffic.

[0090] In another example, the data alteration service may be effective to modify data transiting, through the service proxy, between two virtualized instances of the distributed computing system, one of which is controlled by a customer requesting the service, while the other is controlled by a different customer. A separate virtualized instance of the distributed computing system implemented in the service proxy may be invoked to implement the customer-requested rules, or in some embodiments, the same instance from whence (or to which) the data desired to be modified may perform the actual modification, e.g., in a quarantine or “sandbox.” It is contemplated that data transiting to or from any device or component controlled by a service-requesting customer, whether physical, virtual, aggregated or otherwise, to a device not under control by the customer (without regard to its nature), may be subject to packet mangling by the service. The service may, in some embodiments, be granularly controllable based on a number of criteria, including customer or external device type, geographic location, and the like.

[0091] An example implementation of such a data alteration service may include the generation of one or more policies that apply to some or all components involved in a given data transaction type. The policies, in some embodiments, are generated by the distributed computing system upon receipt of customer-defined rules, and may take into account data type, connected device type, customer characteristics, network topology, or any other characteristics relevant to the generation of an effective policy. Such policies, when broadcasted to the relevant devices, can ensure that all controlled devices (or a desired subset thereof) act to implement the associated customer-defined rules in a unified, predictable fashion. In embodiments where a customer controls a significant plurality of devices at varying levels of abstraction and/or access, such policies may also ensure that, e.g., mission-critical or strict rules take effect across all affected devices.

[0092] Further, additional operations may be performed in connection with the process 1400. For example, the analysis 1404 of the network traffic may inform the performance of one or more other operations. In some embodiments, for instance, a cryptographic key may be determined based at least in part on the analysis. Some types of data may, for example, 5 may require (e.g., in accordance with one or more regulations and/or preferences) stronger encryption than other types of data. If the analysis finds one type of data, the data may be encrypted using a key that is smaller than another type of data that could be determined by the analysis. A first type of data, for instance, may require encryption using a 128-bit key whereas another type of data may require encryption using a 256-bit key. The key, 10 accordingly, may be determined (e.g., generated or obtained from data storage) based on the analysis.

[0093] Embodiments of the disclosure can be described in view of the following clauses:

1. A system, comprising:

a first data storage service comprising a plurality of data storage devices and a first 15 web service interface configured to receive web service requests transmitted to the first web service interface, the first data storage service being configured to process the web service requests transmitted to the first web service interface using the plurality of data storage devices;

a second data storage service comprising a second web service interface, the second 20 data storage service configured to operate as a proxy to the first data storage service by at least:

receiving, to the second web service interface, a request from a requestor to store data;

encrypting the data using a cryptographic key inaccessible to the first data 25 storage service;

transmitting the encrypted data to the first data storage service for persistent storage on behalf of the requestor; and

maintain access to the cryptographic key while preventing access to the cryptographic key by the first data storage service.

30 2. The system of clause 1, wherein:

the first data storage service is implemented with computing resources in a first set of one or more facilities; and

the second data storage service is implemented with computing resources in a second set of one or more facilities that is disjoint from the first set of one or more facilities.

5

3. The system of clause 1 or 2, wherein both the first web service interface and the second web service interface are each publicly addressable interfaces in a public communications network.

10 4. The system of any one of the preceding clauses, wherein the second data storage service is configured to encrypt the data without requiring the requestor to specify that the data should be encrypted.

15 5. The system of any one of the preceding clauses, wherein the second data storage service is further configured to:

receive, to the second web service interface, a request to retrieve the data;
obtain the encrypted data from the first data storage service;
use the key to decrypt the encrypted data; and
provide the decrypted data.

20

6. The system of any one of the preceding clauses, wherein the first data storage service and second data storage service are implemented in different legal jurisdictions.

25 7. The system of any one of the preceding clauses, wherein the first data storage service is configured to operate in accordance with a first set of regulations and the second data storage service is configured to operate in accordance with a second set of regulations that is different from the first set of regulations.

30 8. A system, comprising:
one or more processors; and
memory comprising computer executable instructions that, when executed by the one or more processors, cause the system to:

operate an application programming interface to which requests are submittable over a network;

for each first request of at least a plurality of requests submitted to the application programming interface, process the first request by at least:

5 using a key to perform one or more cryptographic operations on data involved in processing the first request; and

transmitting, across a network, a second request to a service that causes the service to perform one or more operations on the data in encrypted form, the service lacking access to the key and being configured to be independently capable of processing the first request.

10

9. The system of clause 8, wherein:

the system is operated as part of a first instance of a service type provided by a service provider; and

the service is operated as part of a second instance of the service type provided by

15

the service provider.

10. The system of clause 8 or 9, wherein the application programming interface is a web service interface.

20

11. The system of any one of clauses 8 to 10, wherein:

at least some of the plurality of requests are transmitted by different entities; and each different entity corresponds to an account of the service.

12. The system of any one of clauses 8 to 11, wherein:

25

the executable instructions further cause the system to selectively determine whether to perform the one or more cryptographic operations when processing requests; and the plurality of requests are a subset of a set of requests processed by the system, the subset consisting of requests for which the system has selectively determined to perform the one or more cryptographic operations.

30

13. The system of any one of clauses 8 to 12, wherein the executable instructions further cause the system to select the service from a plurality of services capable of being used in processing the first request.

14. The system of any one of clauses 8 to 13, wherein:

the second request to the service causes the service to perform one or more operations on unencrypted data and provide, to the system, a result of performance of the one or more operations and the data in encrypted form;

using the key to perform the one or more cryptographic operations includes decrypting the data in encrypted form; and

the executable instructions further cause the system to perform one or more operations on a collection of data comprising the unencrypted data and the decrypted data.

15. The system of any one of clauses 8 to 14, wherein the service is operated by a first organizational entity that is different from a second organizational entity that operates the system.

16. A computer-implemented method, comprising:

under the control of one or more computer systems configured with executable instructions,

receiving, from a requestor at a network address of the one or more computer systems, an application programming interface request to perform one or more operations;

and

processing the application programming interface request by at least:

transmitting, over a network, a request to a service that is configured to be independently capable of performing the one or more operations, the request being configured to causes the service to perform one or more service operations on encrypted data, the encrypted data being encrypted under a key that is inaccessible to the service; and

using the key to perform one or more cryptographic operations in connection with the encrypted data.

17. The computer-implemented method of clause 16, wherein:

the one or more cryptographic operations include encryption of data to obtain the encrypted data; and

the one or more service operations include persistent storage of the encrypted data.

18. The computer-implemented method of clause 16 or 17, wherein the network address is a public Internet protocol address.

19. The computer-implemented method of any one of clauses 16 to 18, wherein the
5 method further comprises selecting the service from a plurality of services each independently capable of performing the one or more operations.

20. The computer-implemented method of any one of clauses 16 to 19, wherein
10 performing the one or more cryptographic operations includes transmitting, over the network to a cryptography service, a request that causes the cryptography service to perform one or more other cryptographic operations using cryptographic information that is inaccessible to both the one or more computer systems and the service.

21. The computer-implemented method of any one of clauses 16 to 20, wherein the
15 network address is associated with a string that is usable for obtaining the network address from a domain name service, the string being unassociated with a network address for the service by any domain name service.

22. One or more computer-readable storage media having collectively stored therein
20 computer executable instructions that, when executed by one or more processors of a computer system, cause the computer system to:

provide an application programming interface accessible at a network address;

receive, at the application programming interface, an application programming
interface request to perform one or more operations on a set of data;

25 fulfill the received request by, at least in part:

causing at least a subset of the set of data to be encrypted under a key kept
inaccessible to a remote service;

utilizing the remote service to perform at least a subset of the one or more
operations on the set of data such that, for the subset of the set of data, the remote service has
30 access to the subset of the set of data only in encrypted form.

23. The one or more computer-readable storage media of clause 22, wherein:
the network address is a public Internet protocol address; and

utilizing the remote service includes transmitting a request to the remote service addressed to a public Internet protocol address of the remote service.

24. The one or more computer-readable storage media of clause 22 or 23, wherein:

5 the application programming interface request is a request, from a requestor, to perform a requested operation; and

the remote service is independently capable of performing the requested operation for the requestor.

10 25. The one or more computer-readable storage media of any one of clauses 22 to 24, wherein:

the computer executable instructions further cause the computer system to analyze the application programming interface request to determine whether to restrict access by the remote service to the subset of the data in encrypted form; and

15 the remote service only having access to the subset of the data in encrypted form as a result of determining to restrict access by the remote service to the subset of the data in encrypted form.

26. The one or more computer-readable storage media of clause 25, wherein:

20 as a result of determining to restrict access by the remote service to the subset, the instructions further cause the computer system to determine, based at least in part on the analysis, an encryption key;

restricting access by the remote service includes encrypting at least a portion of the subset using the determined encryption key.

25

27. The one or more computer-readable storage media of any one of clauses 22 to 26, wherein:

the application programming interface request is from a requestor;

a plurality of services that include the remote service are capable of being utilized

30 by the computer system for fulfilling the application programming interface request; and

the computer executable instructions further cause the computer system to select, from the plurality of services, the remote service based at least in part on a configuration setting specific to the requestor.

28. The one or more computer-readable storage media of any one of clauses 22 to 27, wherein:

the computer executable instructions further cause the computer system to encrypt
5 the subset of the set of data using the key; and
utilizing the remote service to perform one or more operations includes submitting a storage request to the remote service to store the set of data.

29. A system, comprising:

10 a first data storage service comprising a plurality of data storage devices and a first web service interface configured to receive web service requests transmitted to the first web service interface, the first data storage service being configured to process the web service requests transmitted to the first web service interface using the plurality of data storage devices;

15 a second data storage service comprising a second web service interface, the second data storage service configured to operate as a proxy to the first data storage service by at least:

receiving data in connection with a request, submitted to the second web service interface from a requestor, to store data;

20 analyzing the received data to generate a determination whether the received data satisfies one or more criteria of one or more data loss prevention policies;

processing the received request in accordance with the generated determination, wherein:

25 when the determination indicates that the received data satisfies the one or more criteria of the one or more data loss prevention policies, processing the received request includes:

using a key maintained inaccessible to the first data storage service to encrypt the received data; and

30 transmitting the encrypted received data to the second data storage service by submitting a second request to the first web service interface.

30. The system of clause 29, wherein, when the determination indicates that the one or more criteria of the one or more data loss prevention policies are unsatisfied by the received

data, processing the received request includes submitting a third request to web service interface that causes the received data to be persistently stored by the first data storage service such that the data is retrievable, from the first data storage service in unencrypted form.

5

31. The system of clause 29 or 30, wherein the one or more data loss prevention policies are configurable via the second web service interface.

32. The system of any one of clauses 29 to 31, wherein the first web service interface
10 has at least one public Internet protocol address.

33. The system of any one of clauses 29 to 32, further comprising a cryptography service configured to maintain the key in a political jurisdiction outside of another legal jurisdiction in which the first data storage service is located.

15

34. The system of any one of clauses 29 to 33, wherein the second storage service is further configured to:

receive, to the second web service interface, a third request to retrieve the data;

and

20 process the third request by at least:

obtain the encrypted data from the first data storage service by submitting a fourth request to the first web service interface;

using the key to decrypt the obtained encrypted data; and

providing the decrypted obtained encrypted data.

25

35. A system, comprising:

one or more processors; and

memory including computer executable instructions that, when executed by the one or more processors, cause the system to:

30 provide an application programming interface accessible at a network address;

receive data in connection with requests to perform one or more operations submitted to the application programming interface;

analyze the data to identify a subset of the data meeting one or more criteria of one or more data policies;

modifying the subset of data in accordance with the one or more data policies;

and

5 transmit the modified subset of data to a remote service that is independently capable of processing requests to perform the one or more operations.

36. The system of clause 35, wherein the instructions further cause the system to perform at least one of: providing one or more notifications corresponding to meeting the
10 one or more criteria; or performing enhanced logging for the identified subset.

37. The system of clause 35 or 36, wherein modifying the subset of data includes encrypting the subset of data.

15 38. The system of any one of clauses 35 to 37, wherein the computer executable instructions further cause the system to:
 receive, through the application programming interface, user-defined rules for modifying data; and
 modifying the data is performed in accordance with the user-defined rules.

20

39. The system of any one of clauses 35 to 38, wherein:
 analyzing the data includes detecting, in the data, one or more instances of a data type specified as sensitive; and
 the subset of the data includes the detected one or more instances of the data type
25 specified as sensitive.

40. The system of any one of clauses 35 to 39, wherein the computer executable instructions further cause the computer system to transmit a second subset of the received data to the remote service without modifying the second subset.

30

41. The system of any one of clauses 35 to 40, wherein the computer executable instructions further cause the computer system to:

receive a second request whose fulfillment includes retrieval of the subset of the data;

obtain the modified subset from the remote service; and

reverse modifying the modified subset to regenerate the subset; and

5 fulfill the second request using the regenerated subset.

42. A computer-implemented method, comprising:

under the control of one or more computer systems configured with executable instructions,

10 receiving, at an application programming interface proxy to a remote service, a request to process data whose fulfillment involves utilization of the remote service;

analyzing the data to generate a determination whether the data implicates one or more data policies; and

processing the data in accordance with the generated determination, wherein

15 processing the data includes modifying the data according to one or more implicated data policies of the one or more data policies prior to utilization of the remote service.

43. The computer-implemented method of clause 42, wherein modifying the data includes encrypting the data.

20

44. The computer-implemented method of clause 42 or 43, wherein the request is received at a private Internet protocol address of the application programming interface proxy.

25 45. The computer-implemented method of any one of clauses 42 to 44, wherein the request to process the data is a request to store the data.

46. The computer-implemented method of any one of clauses 42 to 45, further comprising:

30 receiving, at the application programming interface proxy, one or more user-defined criteria for the one or more data policies; and

generating the determination is based at least in part on the user-defined criteria.

47. The computer-implemented method of any one of clauses 42 to 46, further comprising:

receiving, at the application programming interface, a second request to process second data whose fulfillment involves utilization of the remote service; and

5 preventing the second data from being transmitted to the remote service as a result of the second data satisfying one or more criteria of the one or more data policies.

48. One or more computer-readable storage media having collectively stored thereon executable instructions that, when executed by one or more processors of a system, cause the
10 system to:

provide an application programming interface proxy to a remote service;

cause enforcement of one or more data loss prevention policies on data received through the provided application programming interface proxy to the remote service, the enforcement including at least:

15 identifying a subset of the received data that satisfies one or more data loss prevention criteria of the one or more data loss prevention policies; and

performing one or more actions on the identified subset in accordance with the one or more data loss prevention criteria the one or more actions including modifying data in the identified subset and transmitting the modified data to the remote service.

20

49. The one or more computer-readable storage media of clause 48, wherein:

the system is operated by a computing resource service provider; and

the application programming interface proxy is available to multiple customers of the computing resource service provider at one or more public network addresses.

25

50. The one or more computer-readable storage media of clause 48 or 49, wherein the application programming interface proxy and remote service are implemented in separate facilities.

30 51. The one or more computer-readable storage media of any one of clauses 48 to 50, wherein the one or more data loss prevention policies are programmatically configurable through the application programming interface proxy.

52. The one or more computer-readable storage media of any one of clauses 48 to 51, wherein the application programming interface proxy and the remote service are accessible by different uniform resource locators.

5 53. The one or more computer-readable storage media of any one of clauses 48 to 52, wherein modifying the data includes encrypting the data prior to transmission to the remote service.

[0094] FIG. 15 illustrates aspects of an example environment 1500 for implementing
10 aspects in accordance with various embodiments. As will be appreciated, although a web-based environment is used for purposes of explanation, different environments may be used, as appropriate, to implement various embodiments. The environment includes an electronic client device 1502, which can include any appropriate device operable to send and receive requests, messages or information over an appropriate network 1504 and convey information
15 back to a user of the device. Examples of such client devices include personal computers, cell phones, handheld messaging devices, laptop computers, tablet computers, set-top boxes, personal data assistants, embedded computer systems, electronic book readers and the like. The network can include any appropriate network, including an intranet, the Internet, a cellular network, a local area network or any other such network or combination thereof.
20 Components used for such a system can depend at least in part upon the type of network and/or environment selected. Protocols and components for communicating via such a network are well known and will not be discussed herein in detail. Communication over the network can be enabled by wired or wireless connections and combinations thereof. In this example, the network includes the Internet, as the environment includes a web server 1506
25 for receiving requests and serving content in response thereto, although for other networks an alternative device serving a similar purpose could be used as would be apparent to one of ordinary skill in the art.

[0095] The illustrative environment includes at least one application server 1508 and a data store 1510. It should be understood that there can be several application servers, layers or
30 other elements, processes or components, which may be chained or otherwise configured, which can interact to perform tasks such as obtaining data from an appropriate data store. Servers, as used herein, may be implemented in various ways, such as hardware devices or

virtual computer systems. In some contexts, servers may refer to a programming module being executed on a computer system. As used herein the term “data store” refers to any device or combination of devices capable of storing, accessing and retrieving data, which may include any combination and number of data servers, databases, data storage devices and data storage media, in any standard, distributed or clustered environment. The application server can include any appropriate hardware and software for integrating with the data store as needed to execute aspects of one or more applications for the client device, handling some (even a majority) of the data access and business logic for an application. The application server may provide access control services in cooperation with the data store and is able to generate content such as text, graphics, audio and/or video to be transferred to the user, which may be served to the user by the web server in the form of HyperText Markup Language (“HTML”), Extensible Markup Language (“XML”) or another appropriate structured language in this example. The handling of all requests and responses, as well as the delivery of content between the client device 1502 and the application server 1508, can be handled by the web server. It should be understood that the web and application servers are not required and are merely example components, as structured code discussed herein can be executed on any appropriate device or host machine as discussed elsewhere herein. Further, operations described herein as being performed by a single device may, unless otherwise clear from context, be performed collectively by multiple devices, which may form a distributed system.

[0096] The data store 1510 can include several separate data tables, databases or other data storage mechanisms and media for storing data relating to a particular aspect of the present disclosure. For example, the data store illustrated may include mechanisms for storing production data 1512 and user information 1516, which can be used to serve content for the production side. The data store also is shown to include a mechanism for storing log data 1514, which can be used for reporting, analysis or other such purposes. It should be understood that there can be many other aspects that may need to be stored in the data store, such as for page image information and to access right information, which can be stored in any of the above listed mechanisms as appropriate or in additional mechanisms in the data store 1510. The data store 1510 is operable, through logic associated therewith, to receive instructions from the application server 1508 and obtain, update or otherwise process data in response thereto. In one example, a user, through a device operated by the user, might submit a search request for a certain type of item. In this case, the data store might access the user

information to verify the identity of the user and can access the catalog detail information to obtain information about items of that type. The information then can be returned to the user, such as in a results listing on a web page that the user is able to view via a browser on the user device 1502. Information for a particular item of interest can be viewed in a dedicated
5 page or window of the browser. It should be noted, however, that embodiments of the present disclosure are not necessarily limited to the context of web pages, but may be more generally applicable to processing requests in general, where the requests are not necessarily requests for content.

[0097] Each server typically will include an operating system that provides executable
10 program instructions for the general administration and operation of that server and typically will include a computer-readable storage medium (e.g., a hard disk, random access memory, read only memory, etc.) storing instructions that, when executed by a processor of the server, allow the server to perform its intended functions. Suitable implementations for the operating system and general functionality of the servers are known or commercially available and are
15 readily implemented by persons having ordinary skill in the art, particularly in light of the disclosure herein.

[0098] The environment in one embodiment is a distributed computing environment utilizing several computer systems and components that are interconnected via communication links, using one or more computer networks or direct connections. However,
20 it will be appreciated by those of ordinary skill in the art that such a system could operate equally well in a system having fewer or a greater number of components than are illustrated in FIG. 15. Thus, the depiction of the system 1500 in FIG. 15 should be taken as being illustrative in nature and not limiting to the scope of the disclosure.

[0099] The various embodiments further can be implemented in a wide variety of operating
25 environments, which in some cases can include one or more user computers, computing devices or processing devices which can be used to operate any of a number of applications. User or client devices can include any of a number of general purpose personal computers, such as desktop, laptop or tablet computers running a standard operating system, as well as cellular, wireless and handheld devices running mobile software and capable of supporting a
30 number of networking and messaging protocols. Such a system also can include a number of workstations running any of a variety of commercially-available operating systems and other known applications for purposes such as development and database management. These

devices also can include other electronic devices, such as dummy terminals, thin-clients, gaming systems and other devices capable of communicating via a network.

[0100] Various embodiments of the present disclosure utilize at least one network that would be familiar to those skilled in the art for supporting communications using any of a variety of commercially-available protocols, such as Transmission Control Protocol/Internet Protocol (“TCP/IP”), protocols operating in various layers of the Open System Interconnection (“OSI”) model, File Transfer Protocol (“FTP”), Universal Plug and Play (“UpnP”), Network File System (“NFS”), Common Internet File System (“CIFS”) and AppleTalk. The network can be, for example, a local area network, a wide-area network, a virtual private network, the Internet, an intranet, an extranet, a public switched telephone network, an infrared network, a wireless network and any combination thereof.

[0101] In embodiments utilizing a web server, the web server can run any of a variety of server or mid-tier applications, including Hypertext Transfer Protocol (“HTTP”) servers, FTP servers, Common Gateway Interface (“CGI”) servers, data servers, Java servers and business application servers. The server(s) also may be capable of executing programs or scripts in response requests from user devices, such as by executing one or more web applications that may be implemented as one or more scripts or programs written in any programming language, such as Java[®], C, C# or C++, or any scripting language, such as Perl, Python or TCL, as well as combinations thereof. The server(s) may also include database servers, including without limitation those commercially available from Oracle[®], Microsoft[®], Sybase[®] and IBM[®].

[0102] The environment can include a variety of data stores and other memory and storage media as discussed above. These can reside in a variety of locations, such as on a storage medium local to (and/or resident in) one or more of the computers or remote from any or all of the computers across the network. In a particular set of embodiments, the information may reside in a storage-area network (“SAN”) familiar to those skilled in the art. Similarly, any necessary files for performing the functions attributed to the computers, servers or other network devices may be stored locally and/or remotely, as appropriate. Where a system includes computerized devices, each such device can include hardware elements that may be electrically coupled via a bus, the elements including, for example, at least one central processing unit (“CPU” or “processor”), at least one input device (e.g., a mouse, keyboard, controller, touch screen or keypad) and at least one output device (e.g., a display device,

printer or speaker). Such a system may also include one or more storage devices, such as disk drives, optical storage devices and solid-state storage devices such as random access memory (“RAM”) or read-only memory (“ROM”), as well as removable media devices, memory cards, flash cards, etc.

5 [0103] Such devices also can include a computer-readable storage media reader, a communications device (e.g., a modem, a network card (wireless or wired), an infrared communication device, etc.) and working memory as described above. The computer-readable storage media reader can be connected with, or configured to receive, a computer-readable storage medium, representing remote, local, fixed and/or removable storage devices
10 as well as storage media for temporarily and/or more permanently containing, storing, transmitting and retrieving computer-readable information. The system and various devices also typically will include a number of software applications, modules, services or other elements located within at least one working memory device, including an operating system and application programs, such as a client application or web browser. It should be
15 appreciated that alternate embodiments may have numerous variations from that described above. For example, customized hardware might also be used and/or particular elements might be implemented in hardware, software (including portable software, such as applets) or both. Further, connection to other computing devices such as network input/output devices may be employed.

20 [0104] Storage media and computer readable media for containing code, or portions of code, can include any appropriate media known or used in the art, including storage media and communication media, such as, but not limited to, volatile and non-volatile, removable and non-removable media implemented in any method or technology for storage and/or transmission of information such as computer readable instructions, data structures, program
25 modules or other data, including RAM, ROM, Electrically Erasable Programmable Read-Only Memory (“EEPROM”), flash memory or other memory technology, Compact Disc Read-Only Memory (“CD-ROM”), digital versatile disk (DVD) or other optical storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices or any other medium which can be used to store the desired information and which can be
30 accessed by the system device. Based on the disclosure and teachings provided herein, a person of ordinary skill in the art will appreciate other ways and/or methods to implement the various embodiments.

[0105] The specification and drawings are, accordingly, to be regarded in an illustrative rather than a restrictive sense. It will, however, be evident that various modifications and changes may be made thereunto without departing from the broader spirit and scope of the invention as set forth in the claims.

5 [0106] Other variations are within the spirit of the present disclosure. Thus, while the disclosed techniques are susceptible to various modifications and alternative constructions, certain illustrated embodiments thereof are shown in the drawings and have been described above in detail. It should be understood, however, that there is no intention to limit the invention to the specific form or forms disclosed, but on the contrary, the intention is to cover
10 all modifications, alternative constructions and equivalents falling within the spirit and scope of the invention, as defined in the appended claims.

[0107] The use of the terms “a” and “an” and “the” and similar referents in the context of describing the disclosed embodiments (especially in the context of the following claims) are to be construed to cover both the singular and the plural, unless otherwise indicated herein or
15 clearly contradicted by context. The terms “comprising,” “having,” “including” and “containing” are to be construed as open-ended terms (i.e., meaning “including, but not limited to,”) unless otherwise noted. The term “connected,” when unmodified and referring to physical connections, is to be construed as partly or wholly contained within, attached to or joined together, even if there is something intervening. Recitation of ranges of values herein
20 are merely intended to serve as a shorthand method of referring individually to each separate value falling within the range, unless otherwise indicated herein and each separate value is incorporated into the specification as if it were individually recited herein. The use of the term “set” (e.g., “a set of items”) or “subset” unless otherwise noted or contradicted by context, is to be construed as a nonempty collection comprising one or more members.
25 Further, unless otherwise noted or contradicted by context, the term “subset” of a corresponding set does not necessarily denote a proper subset of the corresponding set, but the subset and the corresponding set may be equal.

[0108] Conjunctive language, such as phrases of the form “at least one of A, B, and C,” or “at least one of A, B and C,” unless specifically stated otherwise or otherwise clearly
30 contradicted by context, is otherwise understood with the context as used in general to present that an item, term, etc., may be either A or B or C, or any nonempty subset of the set of A and B and C. For instance, in the illustrative example of a set having three members

used in the above conjunctive phrase, “at least one of A, B, and C” and “at least one of A, B and C” refers to any of the following sets: {A}, {B}, {C}, {A, B}, {A, C}, {B, C}, {A, B, C}. Thus, such conjunctive language is not generally intended to imply that certain embodiments require at least one of A, at least one of B and at least one of C to each be present.

[0109] Operations of processes described herein can be performed in any suitable order unless otherwise indicated herein or otherwise clearly contradicted by context. Processes described herein (or variations and/or combinations thereof) may be performed under the control of one or more computer systems configured with executable instructions and may be implemented as code (e.g., executable instructions, one or more computer programs or one or more applications) executing collectively on one or more processors, by hardware or combinations thereof. The code may be stored on a computer-readable storage medium, for example, in the form of a computer program comprising a plurality of instructions executable by one or more processors. The computer-readable storage medium may be non-transitory.

[0110] The use of any and all examples, or exemplary language (e.g., “such as”) provided herein, is intended merely to better illuminate embodiments of the invention and does not pose a limitation on the scope of the invention unless otherwise claimed. No language in the specification should be construed as indicating any non-claimed element as essential to the practice of the invention.

[0111] Preferred embodiments of this disclosure are described herein, including the best mode known to the inventors for carrying out the invention. Variations of those preferred embodiments may become apparent to those of ordinary skill in the art upon reading the foregoing description. The inventors expect skilled artisans to employ such variations as appropriate and the inventors intend for embodiments of the present disclosure to be practiced otherwise than as specifically described herein. Accordingly, the scope of the present disclosure includes all modifications and equivalents of the subject matter recited in the claims appended hereto as permitted by applicable law. Moreover, any combination of the above-described elements in all possible variations thereof is encompassed by the scope of the present disclosure unless otherwise indicated herein or otherwise clearly contradicted by context.

[0112] All references, including publications, patent applications and patents, cited herein are hereby incorporated by reference to the same extent as if each reference were individually

and specifically indicated to be incorporated by reference and were set forth in its entirety herein.

CLAIMS

WHAT IS CLAIMED IS:

- 5 1. A system, comprising:
- one or more processors; and
- memory comprising computer executable instructions that, when executed
- by the one or more processors, cause the system to:
- operate, by a service provider, an application programming interface to
- 10 which requests are submittable over a network, the request originating from
- a network not operated by the service provider; and
- for each first request of at least a plurality of requests submitted to the
- application programming interface, process the first request by at least:
- using a key to perform one or more cryptographic operations on data
- 15 involved in processing the first request; and
- transmitting, across a network, a second request to a service utilizing
- separate computing resources than the application programming
- interface that causes the service to perform one or more operations on
- the data in encrypted form wherein the separate computing resources
- 20 are located in a first location governed by different regulations than a
- second location where the application programming interface is located,
- the service lacking access to the key and being configured to be
- independently configured to process the first request;

wherein the executable instructions further cause the system to restrict access by the service to the data in encrypted form based at least in part on an analysis of the application programming interface request.

5 2. A system, comprising:

one or more processors; and

memory including computer executable instructions that, when executed by the one or more processors, cause the system to:

10 provide an application programming interface accessible at a network address;

receive data in connection with a request to perform one or more operations submitted to the application programming interface;

analyze the data to identify a subset of data that meets one or more criteria of one or more data policies;

15 modify the subset of data in accordance with the one or more data policies by at least encrypting the subset of data using a cryptographic key inaccessible to a remote service that is independently capable of processing the request to perform the one or more operations, to form a modified subset of data, wherein the cryptographic key is determined based at least in part
20 on a type of the subset of data; and

provide the modified subset of data to the remote service.

3. The system of claim 2, wherein the computer executable instructions further cause the system to at least:
provide one or more notifications corresponding to meeting the one or more criteria, or
5 perform enhanced logging for the subset identified.
4. The system of claim 2, wherein the computer executable instructions further include computer executable instructions that cause the system to:
obtain an encrypted cryptographic key;
10 decrypt the encrypted cryptographic key to form the cryptographic key; and
as a result of transmission of the modified subset of data to the remote service, destroy the cryptographic key.
5. The system of claim 2, wherein:
15 the computer executable instructions further cause the system to receive, through the application programming interface, user-defined rules for modifying data; and
the computer executable instructions that cause the system to modify the subset of data cause the system to modify the data in accordance with the
20 user-defined rules.

6. The system of claim 2, wherein:
the computer executable instructions that cause the system to analyze the data includes computer executable instructions that cause the system to detect, in the data, one or more instances of a data type specified as sensitive; and
5 the subset of data includes the one or more instances of the data type specified as sensitive.
7. The system of claim 2, wherein the computer executable instructions further
10 cause the system to provide a second subset of the data received to the remote service without modifying the second subset.
8. The system of claim 2, wherein the computer executable instructions further cause the system to:
15 receive a second request whose fulfilment includes retrieval of the subset of data;
obtain the modified subset of data from the remote service;
reverse modification of the modified subset of data to form a regenerated subset of data; and
20 fulfill the second request using the regenerated subset of data.
9. The system of claim 2, wherein the data is received from a requestor that is different from the system.

10. A computer-implemented method, comprising:

under the control of one or more computer systems having one or more hardware processors and memory including executable instructions,

5 receiving at an application programming interface proxy to a remote service, a request to process data whose fulfillment involves utilization of the remote service;

analysing the data to make a determination whether the data implicates one or more data policies;

10 processing the data in accordance with the determination at least in part by modifying the data according to the one or more data policies implicated prior to utilization of the remote service, by at least encrypting the data to form encrypted data; and

utilizing the remote service that is independently capable to process the
15 request, the remote service lacking a cryptographic key usable to decrypt the encrypted data, wherein the cryptographic key is determined based at least in part on a type of a subset of data.

11. The computer-implemented method of claim 10, comprising:

20 obtaining an encrypted data key;
decrypting the encrypted data key to form the cryptographic key; and
as a result of the remote service to process the request, destroy the cryptographic key.

12. The computer-implemented method of claim 10, wherein the request is received at a private Internet protocol address of the application programming interface proxy.

5

13. The computer-implemented method of claim 10, wherein the request to process the data is a request to store the data.

14. The computer-implemented method of claim 10, further comprising:

10 receiving, at the application programming interface proxy, one or more user-defined criteria for the one or more data policies; and
generating the determination is based at least in part on the one or more user-defined criteria.

15 15. The computer-implemented method of claim 10, further comprising:

receiving, at the application programming interface, a second request to process second data whose fulfillment involves utilization of the remote service; and
preventing the second data from being transmitted to the remote service as
20 a result of the second data satisfying one or more criteria of the one or more data policies.

16. One or more non-transitory computer-readable storage media having collectively stored thereon executable instructions that, when executed by one or more processors of a system, cause the system to:

provide an application programming interface proxy to a remote service;

5 cause one or more data loss prevention policies on data received through the application programming interface proxy to be enforced at the remote service by at least:

identifying a subset of the data received that satisfies one or more data loss prevention criteria of the one or more data loss prevention

10 policies; and

performing one or more actions on the subset identified in accordance with the one or more data loss prevention criteria, the one or more actions including:

modifying data in the subset, at least by encrypting the data

15 in the subset, to form modified data; and

providing the modified data to the remote service that is independently capable to process a request and lacks access to a cryptographic key usable to decrypt the modified data, wherein the cryptographic key is determined based at least in part on a type of

20 the subset of data.

17. The one or more non-transitory computer-readable storage media of claim 16, wherein:

the system is operated by a computing resource service provider; and
the application programming interface proxy is available to multiple
customers of the computing resource service provider at one or more public
network addresses.

5

18. The one or more non-transitory computer-readable storage media of claim
16, wherein the application programming interface proxy and remote service
are implemented in separate facilities.

10 19. The one or more non-transitory computer-readable storage media of claim
16, wherein the one or more data loss prevention policies are
programmatically configurable through the application programming
interface proxy.

15 20. The one or more non-transitory computer-readable storage media of claim
16, wherein the application programming interface proxy and the remote
service are accessible by different uniform resource locators.

21. The one or more non-transitory computer-readable storage media of claim
20 16, wherein performing the one or more actions further includes:
encrypting the cryptographic key to form an encrypted data key; and
providing the encrypted data key to the remote service, wherein the remote
service is unable to decrypt the encrypted data key.

22. A system, comprising:

one or more computer-readable storage mediums having stored thereon a set of computer executable instructions, which if performed by one or more

5 processors, cause the system to:

operate an application programming interface to which requests are submittable over a network;

for each first request of at least a plurality of requests submitted to the application programming interface, process the first request by at least:

10 using a key to perform one or more cryptographic operations on data involved in processing the first request; and

transmitting, across a network, a second request to a service that causes the service to perform one or more operations on the data in encrypted form, the service lacking access to the key and being

15 configured to be independently capable of processing the first request;

wherein the executable instructions further cause the system to selectively determine whether to perform the one or more cryptographic operations when processing requests, wherein the plurality of requests are a subset of a set of requests processed by the system, the subset including requests for which the
20 system has selectively determined to perform the one or more cryptographic operations.

23. The system of claim 22, wherein:

the system is operated as part of a first instance of a service type provided by the service provider; and
the service is operated as part of a second instance of the service type provided by the service provider.

5

24. The system of claim 22 or claim 23, wherein the application programming interface is a web service interface.

25. The system of any one of claims 22, 23 or 24, wherein:

10 at least some of the plurality of requests are transmitted by different entities;
and
each different entity corresponds to an account of the service.

26. The system of any one of claims 22 to 25, wherein the executable

15 instructions further cause the system to select the service from a plurality of services capable of being used in processing the first request.

27. The system of any one of claims 22 to 26, wherein:

the second request to the service causes the service to perform one or more
20 operations on unencrypted data and provide, to the system, a result of performing the one or more operations and the data in encrypted form;
wherein using the key to perform the one or more cryptographic operations includes decrypting the data in encrypted form; and

the executable instructions further cause the system to perform one or more operations on a collection of data comprising the unencrypted data and the decrypted data.

- 5 28. The system of any of claims 22 to 27, wherein the service is operated by a first organizational entity that is different from a second organizational entity that operates the system.

29. The system of any of claims 22 to 28, wherein the executable instructions
10 further cause the system to restrict access by the service to the data in encrypted form based at least in part on an analysis of the application programming interface request.

30. A computer-implemented method, comprising:
15 receiving, from a requestor at a network address of one or more computer systems configured with executable instructions, a plurality of requests submitted to an application programming interface to perform one or more operations; and

- processing a first request of the plurality of requests submitted to the
20 application programming interface request by at least:
transmitting, over a network, a second request to a service that is configured to be independently capable of performing the one or more operations, the second request being configured to cause the service to

perform one or more service operations on encrypted data, the encrypted data being encrypted under a key that is inaccessible to the service; and
using the key to perform one or more cryptographic operations in connection with the encrypted data, and

5 wherein the executable instructions further cause the one or more computer systems to selectively determine whether to perform the one or more cryptographic operations when processing requests; and

the plurality of requests are a subset of a set of requests processed by the one or more computer systems, the subset including requests for which the one
10 or more computer systems has selectively determined to perform the one or more cryptographic operations.

31. The computer-implemented method of claim 30, wherein:

the one or more cryptographic operations include encryption of data to
15 obtain the encrypted data; and

the one or more service operations include persistent storage of the encrypted data.

32. The computer-implemented method of claim 30 or claim 31, wherein the
20 network address is a public Internet protocol address.

33. The computer-implemented method of any one of claims 30, 31 or 32, wherein the method further comprises selecting the service from a plurality

of services each independently capable of performing the one or more operations.

34. The computer-implemented method of any one of claims 30 to 33, wherein
5 performing the one or more cryptographic operations includes transmitting,
over the network to a cryptography service, a request that causes the
cryptography service to perform one or more other cryptographic operations
using cryptographic information that is inaccessible to both the one or more
computer systems and the service.

10

35. The computer-implemented method of any one of claims 30 to 34, wherein
the network address is associated with a string that is usable for obtaining
the network address from a domain name service, the string being
unassociated with a network address for the service by any domain name
15 service.