


**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B65B 21/14, 21/22, 43/26	A1	(11) International Publication Number: WO 96/32322 (43) International Publication Date: 17 October 1996 (17.10.96)
(21) International Application Number: PCT/US96/05267 (22) International Filing Date: 15 April 1996 (15.04.96) (30) Priority Data: 08/421,113 13 April 1995 (13.04.95) US 08/450,323 25 May 1995 (25.05.95) US (71) Applicant (for all designated States except US): THE MEAD CORPORATION [US/US]; Courthouse Plaza, Northeast, Dayton, OH 45463 (US). (72) Inventors; and (75) Inventors/Applicants (for US only): ROBINSON, Glenn [US/US]; 662 Longleaf Drive, Atlanta, GA 30342 (US). CULPEPPER, Will, L. [US/US]; 6147 Turner Lake Road, Covington, GA 30209 (US). (74) Agents: DREW, Michael, V. et al.; The Mead Corporation, 4850D North Church Lane, Smyrna, GA 30080 (US).	(81) Designated States: AU, BG, BR, CA, CN, CZ, FI, HU, JP, KR, MX, NO, NZ, PL, RO, RU, SG, SK, TR, US, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	

(54) Title: APPARATUS FOR LOADING BOTTOM-LOADING BASKET-STYLE CARRIER



(57) Abstract

An apparatus (10) for loading containers into basket-style bottom-loading carriers (3) has a container infeed mechanism; a carrier infeed supplier (30); a carrier feeder mechanism (50) for removing carriers from the carrier infeed supplier; a carrier timer-transport assembly (60 or 260) for receiving carriers (3) from the carrier infeed supplier and initiating transport of the carriers in synchronous parallel motion above the containers; a gripper (82) assembly for opening the carriers (3); a declination belt assembly (90) forming a pathway for receiving transversely extending bottom panels of said carriers and transporting said carriers downwardly over the groupings of containers; a seating assembling (120) for engaging tops of handles of carriers such that as the seating members rotate the bottommost seating member engages the respective tops of the handles of the carriers; and bottom-panel closure mechanisms (130, 140, 182) for placing the bottom panels together in locking relationship with respect to one another.