



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04R 7/06, 29/00	A1	(11) International Publication Number: WO 99/56497 (43) International Publication Date: 4 November 1999 (04.11.99)
(21) International Application Number: PCT/GB99/01101 (22) International Filing Date: 26 April 1999 (26.04.99) (30) Priority Data: 9808962.6 28 April 1998 (28.04.98) GB 9811959.7 4 June 1998 (04.06.98) GB (71) Applicant (for all designated States except US): NEW TRANSDUCERS LIMITED [GB/GB]; Ixworth House, 37 Ixworth Place, London SW3 3QH (GB). (72) Inventors; and (75) Inventors/Applicants (for US only): AZIMA, Henry [CA/GB]; 3 Southacre Close, Chaucer Road, Cambridge CB2 2TT (GB). HILL, Nicholas, Patrick, Roland [GB/GB]; The Flat, 206 Cherry Hinton Road, Cambridge CB1 4AW (GB). HARRIS, Neil [GB/GB]; 9 Davey Crescent, Great Shelford, Cambridge CB2 5JF (GB). COLLOMS, Martin [GB/GB]; 22 Burgess Hill, London NW2 2DA (GB). DJAHANSOUZI, Bijan [GB/GB]; 101 Pier House, Cheyne Walk, London SW3 5HN (GB). (74) Agent: MAGUIRE BOSS; 5 Crown Street, St. Ives, Cambridgeshire PE17 4EB (GB).		
(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>		
(54) Title: METHOD AND APPARATUS FOR LOCATING BENDING WAVE TRANSDUCER MEANS (57) Abstract Method and apparatus for determining beneficial site(s) for locating bending wave transducer means in operative association with member(s) relying for acoustic operation on resonant modes of bending wave action in such member(s). The method comprises investigative excitation of acoustically relevant bending wave action in a said member; and systematic assessment of measurable effect(s) related to such excited bending wave action and corresponding said acoustic action, which effects vary according to bending wave transducer location areally of said member concerned. Investigative excitation is by application of acoustic energy to said member concerned so as to induce said acoustically relevant bending wave action with bending wave transducer means selectively operatively associatable areally locally of said member to respond to its bending wave action and said measurable effect(s) being of signals from said transducer means, or by bending wave transducer means selectively operatively associatable areally locally of said member concerned so as to induce said acoustically relevant bending wave action.		