



- (51) **International Patent Classification:**
E21B 19/06 (2006.01) *E21B 19/07* (2006.01)
- (21) **International Application Number:**
PCT/EP2019/080086
- (22) **International Filing Date:**
04 November 2019 (04.11.2019)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**
62/756,421 06 November 2018 (06.11.2018) US
- (71) **Applicant:** NABORS LUX 2 SARL [LU/LU]; 8-10 Avenue de la Gare, L-1610 LUXEMBOURG (LU).
- (72) **Inventors:** FRIESTAD, Jan; Verdalsveien 41, NO-4352 KLEPPE (NO). MIKALSEN, Kenneth; Alexander Kielandsgate 16A, NO-4319 SANDNES (NO). LARSEN, Ørjan H.; Postveien 4A, NO-4319 SANDNES (NO). LINGJERDE, Bjørnar; Eikelia 30, NO-4325 SANDNES (NO).
- (74) **Agent:** SAVOCA, Agatino et al.; c/o JACOBACCI & PARTNERS S.p.A., corso Emilia 8, 10152 TORINO (IT).
- (81) **Designated States** (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

- (84) **Designated States** (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))
- of inventorship (Rule 4.17(iv))

(54) **Title:** ELEVATOR WITH A TILTABLE HOUSING FOR LIFTING TUBULARS OF VARIOUS SIZES




FIG. 2

(57) **Abstract:** A system including an elevator (100) to move a tubular (38), the elevator (100) including two or more remotely operable latches (110-140) that can configure the elevator to handle various tubular diameters. A portion of the latches can be laterally offset from each other and another portion can overlap adjacent latches. The elevator can be ATEX certified or IECEx certified according to EX Zone 1 requirements with an electronics enclosure contained within a sealed chamber (454). The elevator can be rotated greater than 90 degrees relative to a pair of links (44) that support the elevator. The elevator can use rotary actuators (210) to operate the latches (110-140) and rotate the housing (102) of the elevator (100).

Published:

- *with international search report (Art. 21(3))*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))*