

PACKAGE DISPENSER FOR ONE OR MORE CONDOMS

Field of the Invention

The present invention relates to a package dispenser for one or more elastic expandable garments, such as latex gloves or condoms. More particularly, the invention relates to a garment shaped package dispenser, wherein a user dons one or more garments sequentially from a garment-shaped container. For example the present invention may relate to a package dispenser for one or more condoms, wherein a user dons a condom from a container in the shape of a partially rolled condom. Each condom may be nested with one or more interleaved separators which form a hermetic seal around each condom.

Background of the Invention

Among background art includes U.S. patent no. 4,840,187 of Brazier which describes a rigid, cylindrical tubular container to dispense rigid male urine collection sleeve, not a flattened closed container openable by pressing upon the side edges corresponding to the major axis of the open end of the container, as noted in the present invention.

The use of the flattened, openable container in the present invention would be discouraged, if not clearly taught away from the rigid cylindrical tubular container of Brazier 1187.

Brazier '187 discloses a sheath applicator for directing a stream of urine. Thus the single sheath is open at the distal end

This Sheet Has Been Replaced



and not closed as in a condom. In addition, the tubular casing does not conform to the shape of a condom, has a flexible liner casing which is exposed by side openings to permit adjustment of the flexible liner casing on the penis. Strip 12 therein is designed to expose an adhesive so when the sheath is rolled over the penis, the end of the sheath can be cemented to the base of the penis.

U. S. Patent no. 4,696,095 of Elenteny has peel away multi-layered gloves which are peeled away one at a time. This arrangement is not suitable for use as a condom, as it lacks the leak proof layers in between the various layers of gloves.

Various devices have been made for releasing a single glove from a vacuum chamber. U.S. Patent no. 5,269,405 of the Applicant describes a package for dispensing one or more gloves from a nested plurality of gloves, wherein a pump creates a vacuum to inflate the gloves in an open expanded state.

Applicant's U.S. Patent No. 5,269,405 also discloses a container for sequentially dispensing a single glove from a plurality of gloves placed inside each other, wherein a vacuum holds the plurality of gloves intact in an open position for insertion of a hand therein.

Wood '405 discloses a dispenser for gloves which are stored in a layered condition within a container and a vacuum is applied. Each glove can be removed without disturbing the vacuum. Each glove has the open end pulled around the outside of the container with each succeeding glove layered on top of the preceding one.



Adhesive is employed to maintain a seal. To remove a glove the open edge of the glove is pulled away thereby relieving the vacuum surrounding the glove. The glove is pulled away thereby relieving the vacuum surrounding the glove to be removed, thus easing the removal of the glove. This is a far different arrangement from the present invention.

Applicant's U. S., patent no. 5,456,354 describes a package dispenser for garments such as one or more gloves or condoms, from a dispenser which is shaped like the garment to be dispensed. Among other patents are U.S. Patent Nos. 3,695,493 of Karr, disclosing an apparatus for alternately donning and removing a single glove within a vacuum chamber 4,069,913 of Harrigan for a package for donning a single surgical glove, and 4,889,266 of Wight for an apparatus which removes a single glove from a disposable single use package.

Other related patents include U.S. Patent No. 685,574 of Conboie which shows a hand-shaped case, but for an unrelated use in mortuaries. The U. S. patent no. 1,938,685 to Breulis shows a somewhat bulb-shaped cavity for applying a surgical glove. The cuff of the glove is stretched over the opening of the cavity. The U. S. patent no. 2,741,410 to Violette shows a rack for removing gloves that may be wall mounted.

The U. S. patent no. 2,886,824 to Smith shows a rubber glove having a tapered wrist shape. The U. S. patent no. 3,852,826 to Schindler shows a surgical glove which is sterilized using radiation. The U. S. patent no. 4,186,445 to Stager shows a glove




having a mylar outer coating and a polymer foam inner coating. The U. S. patent no. 4,310,928 to Joung and U. S. patent no. 4,851,266 to Momose show talc free surgical gloves. The U. S. patent no. 4,696,065 to Elenteny shows a single peel-away multi-layer glove. No powder is used between the layers. This glove has a slight taper at the wrist portion.

The U. S. patent to Richardson, 5,224,221 describes a single glove which is two layers, one inside the other, with the space between them evacuated.

Various devices have been made for packaging condoms. U.S. patent no. 5,269,405 of the Applicant herein describes a package for a plurality of condoms, wherein the condoms are nested within a tubular package having an open end and a closed end, wherein a pump creates a vacuum to inflate the condoms in an open inflated state. Applicant's U. S. patent no. 5,456,354, noted above, describes a package for a plurality of condoms which specifically describes a removable layer between each of the condoms, to maintain each of the condoms sanitary before use.

Among prior art patents related to condom manufacturing are U.S. patent no. 5,136,825 of White for an apparatus and method for compacting condoms in a pleated package and U.S. patent no. 4,867,176 of Lash for a vacuum formed package for a female condom, as shown in Fig. 16 therein.

U. S. Patent no. 4,638,790 of Conway describes a rolled condom which is adhesively adhered to the skin of a male user.



U. S. Patent no. 5,316,019 of Jones described an annular applicator which functions as a package for a condom.

U. S. Patent no. 5,267,575 of Hrisko describes a dispenser for an individual condom, wherein the condom is inflated before each use by blowing air through the dispenser to inflate the condom before donning. However, Hrisko 1575 only describes an applicator for single condom, which must be inflated by the user blowing air into the dispenser before each use.

U. S. Patent no. 4,987,905 of Broad describes a "no hands" application for a condom, wherein a pair of strips are moved to release the condom.

However, none of the above patents for donning condoms disclose an apparatus for donning one of a plurality of hermetically sealed condoms within a condom shaped chamber. As defined in the Academic Press Dictionary of Science and Technology, Publishers, ed. C. Morris, 1992 edition, at page 1015, a "hermetic seal, is defined as a seal that is impervious to air and other fluids, i.e. made airtight.

The United States Department of Health, Food and Drug Administration (FDA) mandates that condoms be manufactured to prevent pregnancy and to prevent the transmission of sexually transmitted diseases (STD's), from the mixture of bodily fluids between sexually active persons.

Pursuant to Title 21 U. S. Code, Section 360 (c) (a) (1) FDA regulations classify medical devices in a hierarchy of classification standards, namely, Class I for medical devices which



require general controls in manufacturing, Class II for medical devices which also require performance tests, and Class III, for medical devices which require FDA premarket approval.

The FDA has classified the condom as a Class II device under 21 CFR 884.5300. The condom must be subject to rigorous performance tests, such as air burst tests, to certify that the condoms are sealed from leakage.

The FDA utilizes the manufacturer's standards of the American Society for Testing Materials (ASTM) entitled "Standard Specification for Rubber Contraceptives (Condoms)" Designation: D 3492-83 for quality control of leakage defects, wherein the acceptable quality level for leakage is 0.4 percent, that is, not to exceed 4 leaking condoms per 1000 tested. The FDA's sampling inspections, pursuant to 21 CFR 800.20, are based on the tables of MIL - STD - 105 E which is the military sampling standards in "Sampling Procedure and Tables for Inspection by Attributes", dated May 10, 1989.

Among the tests for condoms include the Air Inflation Test, adopted in 1994 by U. S. inspectors, which includes inflating condoms, checking their elasticity, whereby experts determine the quality that keeps a condom intact during intercourse.

As noted in "How Reliable Are Condoms?" Consumer Reports, May 1995, pp 320 - 324, latex condoms are produced by dipping a cylindrical form in liquid latex and heating it. Machines shape and trim the condoms ring; then new condoms are washed and aged for a number of days, during a "curing" that lets the rubber complete the



chemical actions that strengthen the latex. The final steps are rolling and wrapping individual condoms.

Industry standards require a width of no greater than 54 millimeters, - about 2-1/8 inches, to prevent slippage. The minimum length is 160 mm, roughly 6-1/3 inches.

Since 1987, the U.S. Food and Drug Administration has allowed condom boxes to list all the diseases condoms help avert. More recently, the FDA advised a condom manufacturing company that because the disease-prevention message is so important, manufacturers should also print a disease prevention message on the wrappers of individual condoms.

Therefore, both manufacturers and the FDA take steps to catch the flawed condoms before they can leave the factory.

Objects of the Invention

It is an object of the present invention to provide a disposable dispenser for a single use condom.

It is another object of the present invention to provide a garment package dispenser which has an inner shape which constricts the palm and forces the fingers of the garment to expand and conform to the proper position to allow easy donning.

It is therefore a further object of the present invention to provide a package dispenser for dispensing one or more garments sequentially from a glove-shaped vacuum container.

It is yet another object of the present invention to provide a garment dispenser that allows powderless gloves to be easily donned.



It is a further object to provide a garment-shaped package with a releasing means including a thin continuous ribbon.

It is a still further object to provide a garment-shaped package with a releasing means including a thin ribbon for each garment.

It is yet another object to provide a garment package with an annular releasing means.

It is yet another object to provide a garment package with a releasing means including a tubular plastic cover which has a wasted area line cut spiraling around it so when the tab is removed it resembles a spiral shape.

It is yet another object to provide a container with a neck opening of a garment package which is tapered inward so that when the plastic is pulled off, the cuff of the garment easily rolls off the package and onto the hand.


It is a further object to provide a garment package dispenser in the shape of a large hand for a glove.

It is yet another object of the present invention to provide a glove dispenser for powder free gloves.

It is another object to provide a surgical glove package dispenser which provides a fast method of donning surgical gloves.

It is a further object to provide a surgical glove dispenser with a single wall container shaped like a large glove.

It is yet another object to provide a single or double walled glove package container with the inside shaped like a large glove and the outside having a box-like shape.



It is a further object to provide a glove package dispenser with a regular box-like shaped exterior and a flexible non-elastic large glove shape inside.

It is a further object to provide a glove package dispenser which is flattened for convenient storage and has a flexible non-elastic large glove shape inside.

It is yet another object to provide a glove package wherein the gloves in the package are stored in a relaxed shape, so that when the package is opened for use, the vacuum in the hollow tip causes a plurality of gloves to expand into the proper shape.


It is yet another object to provide a glove dispenser wherein an inner glove component which has holes in it to release trapped air.

It is yet another object to provide a garment dispenser which includes a flexible non-elastic garment shape on the inside of the plurality of garments which is sealed within package in order to provide a leak-proof, air free area for increased shelf-life or storage life of the garments.

It is yet another object to provide a leak-proof layer in between each garment.

It is yet another object to provide a plurality of garments wherein there is provided an outermost garment shape which constitutes a leak-proof layer, for the purpose of shaping all the garments.

This Sheet Has Been Replaced



It is yet another object to provide a garment package with an opening which is flared out to prevent unwanted releasing of the garments.

It is yet another object to provide a garment dispenser package with an opening which is tapered in to aid in the releasing of each garment.

It is yet another object to provide a garment package with a mechanical attachment for pulling a release tab, to allow for hands-free or automatic releasing of the garments.

It is an object of the present invention to provide a condom or condom package dispenser which has an inner shape which forces a condom to expand and conform to the proper position to allow easy donning.

It is also an object of the present invention to provide a dispenser for dispensing one or more condoms, or packages of condoms, sequentially from a container.


It is a further object to provide a condom shaped package dispenser with a releasing means.

It is a still further object to provide a condom-shaped package dispenser with a hermetically sealed layer between each condom.

It is another object to provide a dispenser which permits a conveniently hands-free method of donning condoms.

It is a further object to provide a condom package dispenser which is flattened for convenient storage.

It is yet another object to provide a condom package



dispenser wherein the condoms in the package are stored in a relaxed shape, so that when the dispenser is opened-for use, the partial vacuum in the hollow tip causes the plurality of condoms to expand into the proper shape.

It is yet another object to provide a dispenser with a neck opening which is flattened so that when the neck opening is squeezed, a partial vacuum is formed by the increase of volume within the closed interior of the condom shaped dispenser.

It is yet another object to provide a condom package dispenser with a leak-proof layer in between each condom.


It is also an object of the present invention to improve over the disadvantages of the prior art.

Summary of the Invention

In keeping with these objects and others which will become apparent, the present invention includes a garment-shaped container package dispenser for sequentially dispensing at least one elastic expandable garment, such as a single condom or a plurality of condoms.

In the preferred embodiment, a package dispenses one or more condoms directly on a penis. The package includes a flexible pouch container having the general configuration of a penis. An optional interior plate, within the container prevents the condom from shrinking away from the outside walls of the container.

In another embodiment for gloves, such as latex surgical gloves or the like, the gloves are maintained in an open, expanded state,



wherein the user loosely inserts a hand into the innermost glove, breaks the air seal by pulling a tab or similar device, thus allowing air to leak in around the innermost glove, so that the glove snaps over the hand of the user in a tight fitting manner.

The remaining gloves stay in an expanded state, so that if the user desires to wear two or more gloves, the user then releases a tab to break the seal against the next, exposed, innermost glove, whereupon the next innermost glove snaps into place over the previous first innermost glove upon the hand of the user.

The inside of the package dispenser container of another embodiment for dispensing gloves is glove-shaped, so that the gloves may be expanded in the proper state and condition. Otherwise, in a nondescript tubular or box-like package, the finger portions will not expand or they will become distorted when forced to expand and will not be held in a useful shape, thus necessitating the use of powder to lubricate the finger portions.

In comparison, the glove-shaped package dispenser of the present invention permits proper expansion of all surfaces of the glove, including the fingers, thus obviating the need for powder as a lubricant.

To release a garment, such as a glove or a condom, the releasing means may be a thin continuous ribbon made out of latex or plastic, wherein the user pulls a predetermined length of the tab to release the glove or condom. Alternatively, the releasing means may be a tubular plastic cover, with a wasted line cut in an annular fashion, or spiraling around the cover, so that as it is removed the



releasing means resembles a large spring or spiral shape. In one embodiment, the neck of the hand-shaped glove package is tapered inward, so that when the plastic releasing means is pulled off, the cuff end of the innermost glove is separated from the package and onto the hand of the user.

With respect to the glove-shape of the glove package dispenser, several variations are described herein. For example, the inside and/or the outside of the package may be in the shape of a large glove.

Moreover, a conventional tubular or box-like package dispenser container may be used, wherein the inner glove-shape is achieved by having an outermost glove shape layer, made of a non-elastic plastic hand-shaped material, such as 'Mylar®'.

The glove-shaped package dispenser container also allows the user to quickly put on the gloves in exigent circumstances, such as in an ambulance or for police use.

The glove-shaped package dispenser container, or similar modifications, obviates the need for powder to slide the glove on the hand of the user. The powder, which is presently used on latex gloves, causes problems, such as irritation of the eyes and skin. The powder may also cause allergic respiratory ailments. Moreover, hand perspiration causes the powder to become caked on, making it difficult to wash off. In addition, powder can contaminate surgical incisions, so a surgeon must carefully remove the powder with a sterile towel before surgery, which is a time consuming step.




In order to easily don gloves without powder, the glove shape of the package dispenser constricts the palm portion of the glove and forces the fingers of the glove to expand and conform to the proper position to allow easy donning.

To release any trapped air, the inner glove shape mentioned in the above designs may have holes in it.

It is anticipated that the gloves are to be dispensed in disposable or refillable cartridges of a number of gloves, such as, for example, two dozen. The cartridges are held in a mounting means, such as upon a wall.

In order to hold the glove cartridge firmly in the holder the glove cartridge may have one or more female snaps on the top or one side of it which mate with male snaps on the inside of the glove cartridge holder. This allows for the recognition of different glove sizes and prevents the glove cartridges from being installed in a wrong location, thus, in turn, preventing the donning of the wrong sized glove upon the hand of the user.

In another embodiment for dispensing elastic expandable garments from a package, the package dispenser container of the present invention may also be used for donning condoms from a condom-shaped package which folds flat for storage. In the case of the condom package, where the garments would not be used up as fast as gloves, there may be a special leakproof layer in between each condom. This would also provide extra cleanliness for the inside of the innermost condom that would otherwise be exposed to the outside air.



For non-surgical, non-elastic gloves, the gloves may be stacked and packaged without a vacuum if they are designed with a tapered shape so that the innermost glove(s) do not get crushed. These gloves have no air in between the layers. The wrist part of these gloves is the largest part, tapering down to the fingertips, wherein the gloves have an integral release tab which gets exposed only when the innermost glove inside of it has been removed.

In summary, the present invention relates to a package dispenser for one or more garments such as a condom or a surgical glove. More particularly, the present invention relates to a garment-shaped package dispenser, wherein a user dons one or more garments sequentially from a vacuum packed garment-shaped container. In a preferred embodiment, the shape of the package allows even powder free gloves to be donned quickly and easily, because the inner hand shape constricts the palm of the glove and forces the fingers to expand and conform to the proper position within the package interior.

The present invention also includes a condom-shaped package dispenser for sequentially dispensing at least one elastic expandable condom, from a dispenser package.

In the preferred embodiment, the condom is preferably nested within the package and is maintained in the package in a flattened, partially unrolled state. The user squeezes the flattened package to open the openable end, breaks an air tight seal by pulling a tab or similar device, thus releasing an air tight layer from around the condom, so that the condom is opened for donning when the condom



dispenser is inserted over the skin of the male for use. One advantage of this embodiment is that the user is not able to mistakingly don the condom inside out.

In another embodiment, one condom is dispensed from a plurality of condoms and the remaining condoms remain in an open state, so that when the user desires to use a condom at a later time, the user then releases a tab to release a next innermost seal from against the next innermost condom, whereupon the next innermost condom is available for use.

The inside of the condom package dispenser of the preferred embodiment is condom-shaped, so that the condom may be expanded in the proper state and condition.

Another embodiment provides a plurality of individually sealed single condom packages in a partially unrolled state to facilitate donning, which packages are removable from each other by a tear seal.

In summary, the inside of the package dispenser for dispensing one or more condoms is condom-shaped. The package dispenser folds flat for storage. There may be a hermetically sealed leak-proof layer in between each condom. This provides extra cleanliness for the inside of the innermost condom that would otherwise be exposed to the outside air. The user dons one or more condoms sequentially from the condom-shaped container. The shape of the dispenser allows condoms to be donned quickly and easily, because the condom shape, when squeezed at the open neck end, forces the condoms to expand and conform to the proper position within the interior of the dispenser.



Description of the Drawings

The invention can best be understood from the specification and drawings, in which:

FIG. 1 is a perspective view of one embodiment of the glove package dispenser of the present invention.

FIG. 2 is a blown-up cross-sectional view of the glove package dispenser as in FIG. 1, taken along line 2-2 of FIG. 1.

FIG. 3 is a blown-up cross-sectional view of the glove package dispenser as in FIG. 1, taken along line 3-3 of FIG. 1.

FIG. 4 is a perspective view of another embodiment of a glove package dispenser, wherein the inside surfaces of the package are a mirror image of a glove.

FIG. 5 is a blown-up cross-sectional view of the glove package dispenser as in FIG. 4, taken along lines 5-5 of FIG. 4.

FIG. 6 is a side-sectional view of a third embodiment of a glove package dispenser.

FIG. 7 is a blown-up sectional view of the glove package dispenser as in FIG. 6.

FIG. 7A is a blown-up sectional view of an alternate embodiment of the glove dispenser package.

FIG. 8 is a perspective view of a fourth embodiment of a glove package dispenser, shown in a closed position.

FIG. 9 is a blown-up cross-sectional view of the glove package dispenser as in FIG. 8, taken along lines 9-9 of FIG. 8.



FIG. 10 is a blown-up cross-sectional side elevational view of the glove package dispenser as in FIG. 8, shown in an open position.

FIG. 11 is a blown-up sectional view of one embodiment for a release tab portion of the glove package dispenser.

FIG. 12 is a blown-up perspective view of another embodiment for a release tab portion of the glove package dispenser.

FIG. 13 is a blown-up cross-sectional view of the release tab as in FIG. 12, taken along lines 13-13 of FIG. 12.

FIG. 14 is a perspective view of a condom dispenser embodiment of the present invention, shown in a closed position.

FIG. 15 is a blown-up cross-sectional view of the condom dispenser embodiment as in FIG. 14, taken along lines 15-15 of FIG. 14.

FIG. 16 is a perspective view of the condom dispenser embodiment as shown in FIG. 14, shown in an open position.

FIG. 17 is a perspective view of an alternate embodiment of a condom dispenser, shown in a closed position.

FIG. 18 is a perspective view of a condom within the condom dispenser as in FIG. 17.

FIG. 19 is a perspective view of a tapered multi-condom package.

FIG. 20 is a perspective view of the condom package as in Fig. 19.

FIG. 21 is a cross-sectional side view of a typical preformed separator of the condom package as in Fig. 19.

FIG. 22 is a closeup cross-sectional side view of lip portion of package as in Fig. 19.

FIG. 23 is a side elevational view of a condom integrity testing procedure for the condom package as in Fig. 19.

FIG. 24 is a perspective view of an alternate package dispenser for condoms.

FIG. 25 is a side cross-sectional view of the dispenser as in Fig. 24.

FIG. 26 is a closeup cross-sectional view of the condom as in Fig. 24.

FIG. 27 is a closeup cross-sectional view of the seal chamber detail of a further alternate embodiment of a condom dispenser.

FIG. 28 is a closeup view of a further alternate condom dispenser.

FIG. 29 is an exploded perspective of a further embodiment for a condom dispenser including a cap closure having a projecting condom holding plate insertable within the condom within the dispenser;

FIG. 30 is a cross sectional end view of the dispenser as in Fig. 29.

FIG. 31 is a left side elevational view in cross section of the dispenser as in Fig. 29, shown in a closed position;

FIG. 32 is a left side elevational view in cross section of the dispenser as in Fig. 29, shown in an open position;

This Sheet Has Been Replaced



FIG. 33 is a left side elevational view in cross section of a condom shown mounted upon the condom holding plate of the dispenser as in Fig. 29;

FIG. 34 is a left side elevational view in cross section of the pouch portion of the dispenser as in Fig. 29 shown open and empty.;

FIGS. 35 and 35C are respective front views of a further embodiment for an openable pouch package for a condom, wherein the package is shown closed and open;

FIG. 35A is a side elevational view in cross section of the pouch package as in FIG. 35;

FIG. 35B is a top plan view thereof;


FIGS. 36, 36A, 36B and 36C show the pouch package of FIGS. 35, 35A, 35B and 35C with a condom therein;

FIG. 36D shows the pouch package within a sealed, openable outer envelope container.

FIGS. 37 and 38 are close-up views of the condom support members upon the pouch package as in FIGS. 35, 35A, 35B, 35C, 36, 36A, 36B, 36C and 36D.

Detailed Description of the Preferred Embodiments

As shown in FIGS. 1-3, there is provided a package dispenser 1 for a plurality of elastic expandable garments such as glove 2, for donning upon a hand of a person, wherein package dispenser 1 comprises a glove shaped inner cavity 11 within a housing 13 shown in phantom wherein a user inserts a hand and dons at least one glove 2 of a plurality of gloves 2a, 2b, 2c, 2d, ... 2z etc. sequentially



from a vacuum packed accumulation of garments 2, which is subject to a vacuum pressure V, within the dispenser such as drawn by a pump 3 in the manufacturing process for loading package dispenser 1 with gloves 2a, 2b, 2c, 2d, . . . 2z etc. The vacuum pressure V within the dispenser unit 1 is sufficient to open fully and expand uniformly each of the gloves in the glove-shaped cavity 11 within the dispenser 1.

In a one embodiment, the glove shape of package dispenser 1 eliminates the need for powder on gloves 2, such as, for example, latex surgical gloves. Vacuum V is drawn away from external outermost glove 2z and remaining gloves 2a, 2b, 2c etc., thus expanding gloves 2a, 2b, 2c, 2d... 2z in an open position.

Glove package dispenser 1 operates to release innermost single glove 2a from the application of vacuum V within package dispenser 1, which package dispenser 1 functions as an apparatus for sequentially donning one or more glove upon a body part such as a hand 4 from a plurality of gloves 2a, 2b, etc.

Glove package dispenser 1 enables the user to sequentially don gloves 2a, 2b, .2z etc. from the plurality of gloves 2 placed inside each other, wherein vacuum V holds the plurality of gloves 2 within the cavity 11 intact in an open position for insertion of the user's hand 4 therein.

Glove-shaped package 1, includes palm portion 10 and individual finger portions 5, 6, 7, 8, 9 to maintain equal expansion of all surfaces of glove 2, so that, for example, five finger portions 5a, 6a, 7a, 8a, 9a of glove 2a are held in the proper expanded open



position, thereby obviating the need for powder to lubricate gloves 2a, 2b, 2c etc.

The cuffs of the gloves 2a, 2b, 2c, 2d. . . 2z etc. are stretched over the collar portion 16 of the open end of the inner cavity 11 of the glove package dispenser 1 by virtue of which the open end of the gloves 2a, 2b, 2c ... 2z etc. are maintained in an open, expanded state, permitting the user to insert a hand 4 into innermost glove 2a.

As shown in FIG. 11, after insertion of a hand 4, the user breaks a seal by pulling a first portion 17a of seal tab 17 or similar device, such as a thin continuous ribbon made out of latex or plastic. The user pulls first portion 17a of a predetermined length of tab 17 to relieve innermost glove 2a from vacuum V. so that glove 2a is released from the next, subsequent innermost glove 2b, and glove 2a then snaps over the hand 4 of the user in an air tight manner.

Remaining gloves 2b, 2c, 2d... 2z etc. stay in an expanded state, so that if the user desires to wear two or more gloves 2 on one hand, the user then releases a further portion 17b of seal tab 17 from the next, exposed, innermost glove 2b, whereupon the next innermost glove 2b snaps into place over the previous first innermost glove 2a upon the hand 4 of the user. Ultimately, the user dons the remaining outermost glove 2z by pulling the last remaining portion 17z of release pull tab 17, to release outermost glove 2z from its open expanded state under the influence of vacuum V.



In contrast to the release tab embodiment shown in FIG. 11, alternatively, as shown in FIGS. 12 and 13, the releasing means may be a tubular plastic cover 18, with a wasted linear area cut spiraling around the cover so that as it is removed, releasing portion 18a of release cover 18 resembles a large spring. or spiral shape.

Glove package dispensing container 1 of the present invention is glove-shaped, to maintain equal expansion of all of the surfaces of gloves 2. Otherwise, in a nondescript tubular or box-like package, equal expansion is not maintained in the crevices and undulating finger portions 5, 6, 7, 8, 9 of glove 2, thus necessitating the use of powder to lubricate the finger portions and allow donning.

The glove-shaped dispenser package 1 of the present invention, as indicated, permits an equal expansion of all surfaces of glove 2, including palm portion 10 and finger portions 5, 6, 7, 8, 9, thus obviating the need for powder to lubricate the glove 2, to allow the user's hand to be readily inserted within the latex glove.

In one embodiment, collar neck 16 of the open end of the glove-shaped package dispenser 1 may be tapered inward, so that when the plastic releasing means 17 or 18 is pulled off, the cuff end of the innermost glove 2a is separated from the package 1 and onto the hand 4 of the user.

With respect to the glove-shape feature of the glove package dispenser, several variations are described herein. For example, as shown in FIGS. 4 and 5, the inside 21 of a package 20 may be solid



surrounding the shape of a large glove shaped cavity 11 with adequate means therein for drawing a vacuum.

Moreover, as shown in FIGS. 6 and 7, a conventional hollow container 30 may be used, such as a tubular container or a box-like container, wherein the glove-shape cavity 11 is achieved by having an outermost inelastic glove-like layer 31 positioned adjacent to and about outermost glove 2z' of gloves 2a', 2b' ... 2z', wherein inelastic layer 31 is made of an inelastic gas impermeable plastic hand-shaped material, such as non-elastic Mylar(D.

Therefore, gloves 2a', 2b' ... 2z' will expand equally inside of each other in an expanded state against inelastic glove-like layer 31, due to the effect of vacuum V initiated by pump 3 (not shown) when gloves 2a', 2b, 2c' ... etc. 2z' are installed in an expanded state against inelastic gas impermeable layer 31 within container 30.

As shown in FIG. 7, if there is a significant time delay before innermost glove 2a, is used, a special preferably gas impermeable protective layer 32 is provided inside of innermost glove 2a'-

As shown in FIG. 7A an innermost protective layer 33 is provided inside innermost glove 2a'. Thereafter internal protective layers 33 preferably gas impermeable are provided between each glove of gloves 2a', 2b' ... 2z' until outermost glove shield layer 31 such as Mylar@.

In order to easily don gloves without powder, the glove-shape of the package 1 constricts palm portion 10 of each glove 2 and forces fingers 5, 6, 7, 8 and 9 of glove 2 to expand and conform



to the proper position to allow easy donning upon the hand 4 of the user.

To release any trapped air, the inner glove shape mentioned in the above designs may have holes in it.

The gloves 2 are dispensed in disposable or refillable glove-shaped cartridges 1 including therein a plurality of gloves 2, such as two dozen. In use package dispenser cartridges 1 are held in a mounting means, such as upon a wall.

In order to hold glove cartridge package dispenser 1 firmly in a holder the glove dispenser cartridge 1 may have one or more female snaps located on the top or one side of the package dispenser which mate with male snaps on the inside of the glove cartridge holder. This allows for the recognition of different glove sizes and prevents the glove dispenser cartridges from being installed incorrectly.

As shown in FIGS. 8-10, in an alternate embodiment of a package dispenser 40 for gloves 2a", 2b", 2c", 2d", etc., the gloves may be stacked and packaged within the dispenser package without a vacuum if they are designed with a tapered shape so that innermost gloves 2a", 2b", etc. do' not get crushed. These gloves 2a", 2b", etc. have no air in between the layers. The wrist part 41 of these gloves 2a", 2b", etc. is the largest part, tapering down to the fingertips 42, wherein the gloves 2a", 2b", etc. have an integral release tab which is exposed only when the innermost glove inside of it has been removed.

This Sheet Has Been Replaced



Therefore, glove shaped package dispenser 1 allows a user to don one or more gloves sequentially from a vacuum packed hand-shaped container. In a preferred embodiment, the shape of the container will obviate the need for powder on latex gloves.

As shown in FIGS. 14-16, in another embodiment of the package dispenser for elastic, expandable garments, the container of the present invention may also be used for donning elastic, expandable condoms from a condom-shaped package 50, which folds flat for storage. In the case of condom package 50, where condoms 52a, 52b ... 52z etc. would not be used up as fast as gloves, there may be provided a special protective leak-proof layer 53a, 53b ... 53z inside of innermost condom 52a, and subsequent protective layers 53b ... 53z in between each of the condoms 52b ... 52z etc. This feature provides extra cleanliness for the inside of each condom 52a, 52b ... 52z etc. One advantage of this embodiment is that the user is not able to mistakingly don the condom inside out because it is partially unrolled in the correct position for donning.

For added convenience, as shown in FIGS. 17-18, condom package 50 may be short. In this case it would be used to dispense a rolled or folded condom 52a which would be unrolled or unfolded as needed.

In other respects, this further embodiment of the present invention for condoms differs only in that condom shaped package dispenser 50 is used, with or without a partially elongated receptacle tip end 55, depending upon the shape of each of condoms 52a, 52b ... 52z etc. Therefore, when condom package dispenser 50



is opened as shown in FIG. 16, condom package dispenser 50 maintains equal expansion of all surfaces of each of condoms 52a, 52b ... 52z etc, including partially elongated receptacle tips 56a, 56b... 56z etc, so that innermost condom 52a can be held in the proper position for placement. The proximal open end portions 54 of the plurality of condoms 52a, 52b... 52z are stretched over a collar portion 57 of condom package dispenser 50, and condoms 52a, 52b ... 52z etc. are maintained in an expanded state, wherein the user first removes innermost protective leak-proof layer 53a, thereby exposing innermost condom 52a, and inserts the penis into innermost condom 52a, and a release tab is pulled, so that condom 52a deflates over the skin in a tight fitting manner, leaving next a leak-proof layer 53b inside next innermost condom 52b.

Moreover, the inside shape of condom dispensing package 50 may be condom shaped, or the plurality of condoms may be inserted in an outermost condom shaped layer made of a nonelastic material, such as Mylar similar to the glove embodiment described in FIGS. 6 and 7.

A compact condom dispenser package 60 as shown in Fig. 19 contains a number of condoms 62 nested with interleaved separators 63 which form a hermetic seal around each condom 62.

Quantities such as one to twelve condoms 62 can be packaged in this manner.

The length of package dispenser 60 is reduced by packaging condoms 62 in a partially rolled-up configuration. Condoms 62 are contained in a tapered plastic outer shell 64 with the partially rolled open ends folded over the lip 65 of outer shell 64. Outer



shell 64 folds fairly flat as shown with the proximal end 66 in a flattened oval configuration. Distal end 61 is closed. A molded flange 67 encircling outer shell 64 near proximal open end 66 forms a convenient surface for attaching separators 63 thereto and providing a sealed surface 70 thereat. Separators 63 can be heat sealed, adhesively bonded, ultrasonically bonded or otherwise attached to each other and to flange 67 in such a manner as to achieve a hermetic seal. A tear strip 68 is provided with an end tab 69 and is torn open to remove innermost separator layer 63 and to expose both the inner condom surface of condom 62 as well as the rolled open condom end 71 on the lip 65 of package shell 64. As shown in Fig. 20, by pressing in on the edges 72, 73 forming the major axis of the oval opening 66 shown in Fig. 19, the package dispenser 60 assumes the open shape shown in Fig. 20. Package dispenser 60 is now ready for donning. This is easily accomplished by placing package dispenser 60 over the front portion of the erect penis and sliding rolled condom end 71 off the package dispenser lip 65 and onto the penis. The donning process is completed by further rolling of the condom 62 down the shaft of the penis.

Fig. 21 shows a side view cross-section of a typical preformed separator layer 63 as used between condoms 62. Separator layer 63 can be of a variety of materials that are impermeable to air. They do not have to be elastomeric, but they do have to be somewhat flexible so as to go from the flattened configuration as in Fig. 19 to the round crosssection configuration of Fig. 20.

This Sheet Has Been Replaced



Materials that can be used for separator layer 63 include a wide variety such as Mylar- or Aclar, a very low permeability material. Laminates may also be used for this application. One example is a low density polyethylene (LDPE) substrate laminated to an aluminum foil layer as a permeability barrier. The LDPE substrate also serves as the heat bonding agent. The preforms are preferably vacuum formed, pressure formed or injection molded as appropriate to the particular material. Tear strip 68 is integrated into separators 63 in the general location region shown. Tear strip region 74 ends cantilevered in spaced relation above body portion 75 of separator layer 63, so that a clearance recess 76 is formed between body portion 75 and tear strip region 74, which has extending therefrom a flared attachment surface 77 for the next subsequent separator 63. The recesses 76 have clearances which are more understandable in Fig. 22.

A smaller recess 78 is provided between an open end 79 of separator 63 and tear strip region 74 to provide clearance for insertion of package shell 64 therein. The length of the package shell recess 78 as well as the rolled condom recess 76 will depend on the particular location of the separator 63 and the number of condoms 62 in the package dispenser 60.

The tapered form of outer shell 64 as well as separators 63, facilitates simple automated loading and assembly by using a tapered cylindrical mandrel. The shape also enhances the separability of condoms 62 from the package dispenser during donning. Each condom 62 is placed on the mandrel "M", and then a



separator 63 is placed on the mandrel "M". The condom 62 is held on the mandrel "MI, by rolls "RII or other means. Then the mandrel "M" is inserted in the pack with the exception of rolled edge 71 of condom 62, which rolls down the tapered end of the mandrel "M", and the rolled edge 71 is stopped by flange 67 of the package dispenser 60.

Then the separator 63 is placed on the mandrel "M", which is bonded to shell 64. Separators 63 are bonded to shell 64 sequentially, or using other packaging machinery. All condoms 62 can be assembled on the mandrel "MI, and separator layers 63 can be bonded in one final step.

Figures 21A, 21B, 21C, 21D and 21E illustrate a sequential method that can be used to assemble the multicondom package 60. Fig. 21A shows tapered cylindrical mandrel , ,m,, with the first condom 62, placed over it and an array of rollers "RII (two shown) around the circumference of the condom lip moving to the left, urging the condom 62 to unroll to the proper length. Alternate structures such as pliable fingers or bristles from a circular brush structure can be used instead of the rollers "RII. The condom rollers "R,, are spread away f rom the surf ace and moved further to the left beyond the condom rolled edge (not shown).

Then the package shell 64 is placed over the condom 62 on the mandrel "MI, and the rollers "RII are then moved to the right urging the condom edge over the lip of the package shell 64 toward the sealing flange, as shown in Fig. 21B. After this step, the condom/shell 62, 64 is withdrawn off the mandrel "M" preferably with



the help of a blast of compressed air through a hole or holes in the mandrel (not shown).

The first separator 63 is placed over the mandrel "M" as shown in Fig. 21C. Then the condom-shell assembly 62, 64 is placed over the separator 63, which had been placed over the mandrel "M" as shown in Fig. 21D. At this point, a heat seal ring "S" is moved to the right so as to contact the edge of the first separator 63 and apply heat and pressure to hermetically seal it to the sealing flange 67 of the package shell 64.

Now the sealed subassembly (separator/condom/shell) is removed from the mandrel (not shown) . For the rest of the condom package assembly, the steps discussed are essentially repeated with Fig. 21E showing the unrolling of 'a second condom.

Figure 22 is a detail of the lip portion of the package dispenser 60 in cross-section, with the package shell 64 shown with sealing flange 67. Also shown is each layer of condom 62, 62a, 62c, etc. Separators 63, 63a, 63b, etc. are shown with the sealed ends 631 63a', 63b', 63c' at sealing flange 6.7. While Fig. 22 shows a four condom package, it is merely illustrative, as the amount of condoms 62 and separators 63 may be varied.

As shown in Fig. 23, through the use of conductive polymers such as those recently developed for the electronics industry, or laminates with conductive surfaces for separators 63, 63a, 63b, 63c, etc. some condom integrity testing of condoms 62, 62a, 62b, 62c, etc. can be performed after insertion in package dispenser 601, but prior to sealing of the separator ends 63, 63a, 63b, 63c, etc.. This



operation can be automated with ohmmeter 80 connected by leads 81, 82 connected to respective conductive layers 63a, 63a' attached to separators 63, 63b. The operation simply tests the continuity or resistance between two consecutive separator layers 63, 63a, etc. to assess the integrity of the condom 62 in between. Condom 62, an insulator, preferably results in an infinite, or very high, resistance reading. For a dry condom, this reading may not pick up small flaws such as pinholes because the thickness of the condom material may keep the separator layers 63, 63a apart. However, if condom 62 is lubricated and/or contains spermicide on its outer surface, the jelly material "J" may be made somewhat conductive. The jelly material used may tend to leak through small openings "O" in the wall of condom 62 as shown in Fig. 23.

In this case, the electrical integrity testing may be far more robust, showing minor flaws that would escape in a dry condom test. The test of the final condom in the stack shown in Fig. 22, is preferably between conductive layer 63c" of last separator 63c and conductive inner surface 6411 of outer plastic shell 64.

Fig. 24 shows a separable package dispenser 160 for six condom subpackages 162, 162a, 162b, 162c, 162d, 162e, with as few as one packaged condom 62, or larger packages having up to perhaps a dozen or more condoms 62, 62a, 62b, etc. Package dispenser 160 can be used in much the same manner as the tapered multi-condom package if the condoms 62, 62a, 62b, etc. are just used sequentially as purchased.

However, alternately as shown in Fig. 24 - 27, these



separable packages 160 can be separated into multiple sub-packages of one or more condoms.

Although basically a flattened oval tapered packaging concept like the multi condom version, one major difference with package dispenser 160 is the absence of a thick plastic outer shell. The role of this shell is assumed by multiple semi-rigid impervious plastic or laminated separators 163, 163a, 163b, 163c, etc. which have the dual role of being inter-condom separators as well as being support vehicles for condoms 62, 62a, 62b, etc. To use a condom 62, the pull tab 169 as shown in Fig. 24, nearest the closed distal end 161 is pulled to operate the tear strip 168 which then reveals the rolled condom end on the separator rim. Fig. 25 shows a side view cross-section of a semi-rigid separator 163 with an annular seal chamber wall flange 167. The portion in front of the seal chamber wall flange 167 is an extension 167 with an annular bermed condom rim 16711 retainer to support the rolled open end of condom 62.

Fig. 26 is a detail illustration of the last three seal chambers 162e, 162d, 162c near the edge of opening 166 of package dispenser 160. Condoms 62 are sealed between two adjacent separators 163b, 163c or between the end seal 163 and an adjacent separator 163a. A small gas space 190 is permitted between the outer wall of the condom 62 and the inner edge of the next separator 163a. A small amount of air or dry nitrogen may be admitted at assembly so that donning would become a more automatic procedure. With a small amount of gas in the space 190, when the package dispenser 160 is urged into a shape having a round cross-section by



applying pressure on the sides edges 172, 173 and the tip of the erect penis is inserted in the opening 166, the increased gas pressure between condom 62 wall and separator 163a causes the rolled end of the condom 62 to expand off separator lip automatically onto the penile shaft. The use of nitrogen instead of air reduces the chance of latex oxidation.

Each condom 62 is covered by chamber caps 190, 191, 192, etc., which are rings of impermeable plastic that are sealed to the seal chamber walls 190a, 191a, 192a of separators 163a, 163b, 163c or the end seal 163. Caps 190, 191, 192, etc. have molded-in notches 1901, 1911, 1921 which act as tear strips revealing the condom edge when removed. A subpackage 162 may be separated at any location by removing the associated tear strip 168, to separate subpackage 162 into two sections, a front and a back section.

While the rear section is still hermetically sealed, the end condom 62 on the front section has an inner surface and edge that is exposed to the ambient air. If it is to be used in the immediate future, there is no problem. However, if it is carried or stored for a long time, it may get contaminated or deteriorate through oxidation. Fig. 27 shows the addition of a thin barrier film 195 to mitigate these problems. While not offering a true hermetic seal to the inner surface and edge as thin films are somewhat permeable, the protective layer helps. Film 195 is removed prior to donning by grasping the end thereof and peeling it off the wall wherein pressure sensitive adhesive with limited peel strength is used.



Fig. 28 shows yet another embodiment for a separable package 260. Another embodiment provides a plurality of individually sealed single condom packages in a partially unrolled state to facilitate donning, which packages are removeable from each other by a tear seal. Accordingly, the user can carry a single condom package 260 if they so wish.

This embodiment 260 uses double layer separators 263a, or 263b, 263c, between adjacent condoms 62. one separator is shaped exactly as shown in Fig. 25 without the condom support portion. These separators 262a, 262b, etc. may be somewhat thinner than the single versions. A cap 291 is used to form a hermetic seal encasing a condom 62 between a "short" separator 263a and a "full" separator 263a'. Each sealed condom subassembly 262 nests with the next one 262a forming a complete multi-condom separable package by "spot" bonding between subassemblies 262, 262a with a low strength adhesive. To separate a package into a smaller one, it is just physically separated by breaking apart and the tear strip is not used. In this manner, all condoms 62 remain hermetically sealed until used even if the large package is separated into smaller units. Even a single condom can be separated and remains sealed.

In a further embodiment shown in Figs. 29 - 34, a package 300 dispenses a single condom 301 directly on a penis. The package 300 includes a container 302 having the elongated shape of a condom 301 closed at one end 302a and open at another end 302b- The container 302 has outside wall 304 and is made of a flexible material permitting the container 302 to be flattened. The container 302



includes a flattened closure cap 300 insertable over the open end 305 of the container 302. Projecting from the inside of the closure cap 303 is a condom holder plate 305 insertable within the condom.

As shown in Figs. 31 and 32, the closure cap 305 includes an annular ring member 306 which includes a snap hinge 307 to enable the closure cap 305 to spring open as in Fig. 32.

The container 302 has a lip forming the open end 302b thereof and a flange encircling the container 302 adjacent to the open end 302b.

While the package 300 can be made without separator seals, preferably as in the embodiments shown in Figures 19-23, a first separator (not shown in Figures 29-34) conforms to and lines the inside of the container 302 with the separator having an open end and stretched over a flange for achieving a hermetic seal within the container 302. The first separator has a tear strip on the outside adjacent the flange for providing tearing of the first separator.

A single 301 condom within the container 302 lines the inside of the first separator, with the open end of the condom 301 rolled over the first separator and the flange leaves the tear strip exposed.

A second separator (not shown in Figs. 29-34) lines the inside wall of the condom 301 with the open end of the second separator rolled over the condom and the separator on the flange to achieve hermetic sealing of the condom 301, so that removal of the second separator permits the penis to be inserted into the condom 301 and pulling of the tear strip unseals the condom 301 from the



first separator, resulting in the condom 301 being released so that the penis can withdraw from the container 302 and the first separator with the condom 301 on the penis.

The container 302 with the condom 301 and separators therein is normally flattened for convenient storage and is enlargeable to the shape of a penis when said condom 301 is to be dispensed on a penis by applying force on the edges of the container 302, wherein the edges conform to the major axis of the open end of the container 302.

The dispenser may be foreshortened so that the condom therein is partially unrolled on the outside of the container, thus achieving a compact dispenser.

In another embodiment, the dispenser shown in Figs. 29 34 can be used for a plurality of condoms.

A first condom is located within the container lining the inside of the first separator, with the open end of the first condom rolled over the first separator and the flange leaving said first tear strip means exposed.

A second condom is also located within the container lining the inside of the second separator, with the open end of the second condom rolled over the first separator, the first condom, and the second separator leaving the first and second tear strip means exposed.

A third separator lines the inside wall of the second condom with the open end of the third separator rolled over the first and second condoms and the separators on the flange, achieving



hermetic sealing of the second condom and leaving the tear strip means exposed, so that removal of the third separator permits the penis to be inserted into the second condom and pulling of the second tear strip unseals the second condom from the second separator, resulting in the condom being released so that the penis can withdraw with the second condom on the penis.

The container with the interleaved condoms and the separators therein is normally flattened for convenient storage and enlargeable to the shape of a penis when the condoms are to be dispensed.

As shown in FIGS. 35, 35A, 35B, 35C, 36, 36A, 36B and 36C a further embodiment includes pouch package 401 in the shape of a hollow container, having hollow interior 402, for insertion of a condom 403 partially unrolled therein.

In that manner, when pouch package 401 is removed from sealed, openable outer envelope container 404 (shown in FIG. 36D) by tearing or otherwise, open end 401a of pouch package 401 exposes rolled open end 403a of condom 403 for donning upon a penis.

Closed end 403b of condom 403 nests within pouch package 401. However, the unrolled portion 403c of condom 403 is long enough for insertion of the tip of the penis therein.

When in place upon the tip of the penis, rolled open end 403a of condom 403 is then unrolled off of pouch package 401 and down onto the shaft of the penis.

Pouch package 401 includes condom retaining means 401b, such as a peripherally extending lip thereat, for wrapping of the open end 403a of condom 403 therearound.



Pouch package 401 comprises two convex arcuate walls 401c, and 401d', each partially co-joined at corner joints 401c, 401d of pouch package 401, when viewed in an end view as in FIGS. 35 and 36. Corner joints 401c and 401d extend along the closed periphery of pouch package 401, except at open end 401a thereof.

Thereafter, elongated opening 401a becomes rounder by mutually pinching joints 401c and 401d toward each other, resulting in the rounder open position of walls 401c1 and 401d' of pouch package 401, as shown in FIGS. 35C and 36C. Arrows I-I in FIG. 35 indicate the direction of pinching of joints 401c, 401d. Arrows II-II in FIGS. 35C and 36C indicate the expansion movement of walls 401c1 and 401d' of pouch package 401 at mid point 401e thereof.

As further shown in FIGS. 35B, 36B, 37 and 38, one or more supports 401f, such as axially extending ridges or otherwise, release trapped air caused by containment of the partially rolled portion 403a of latex condom 403 over lip edge 401b of pouch package 401. These supports 401f are preferred but optional.

In summary, FIGS 35, 35A, 35B and 35C all disclose a preferred embodiment for a package 401 for accommodating a condom 403 therein in an open position for donning upon a penis.

It is further noted that other modifications may be made to the present invention, without departing from the spirit and scope of the present invention, as noted in the appended claims.

This Sheet Has Been Replaced



CLAIMS



WHAT IS CLAIMED IS:

1. A package dispenser for the dispensing of garments made of elastic, expandable material for wear upon a body part, each of said garments having a distal closed end and a collar at an open end for insertion of the body part therein, wherein a vacuum is drawn from the elastic expandable material around the body part in order to expand the elastic expandable material in an open position for insertion of the body part therein to obtain an external protection over the body part, said package dispenser comprising:

a container having a housing, said housing having a cavity therein, said cavity of said container having therein a plurality of the said garments, all but the outermost garment being fitted inside of another of said plurality of garments;

said container having an open end, each collar of each of said garments being wrapped around said open end of said container, said plurality of garments covering said open end of said container;

This Sheet Has Been Replaced





said plurality of garments being wrapped in a predetermined pattern so that the innermost garment is exposed to said open end of said container, and the next subsequent garments of said plurality of garments being wrapped around said innermost garment;

said outermost garment covering said next subsequent garments and said innermost garment; and

said container having an outside layer and an inelastic, gas-impermeable inside layer, said inelastic, gas-impermeable inside layer having a geometric shape conforming to a geometric shape of said outermost garment, wherein a vacuum is applied between said outermost garment and said inelastic gas-impermeable inside layer of said container for expansion of said plurality of garments in an open position against said inelastic, gas-impermeable inner layer in an expanded position for insertion of the body

part therein upon release of the vacuum against said innermost garment, said innermost garment being collapsible onto the body part.

2. A package dispenser for the dispensing of garments made of an elastic, expandable material for wear upon a body part,





each of said garments having a distal closed end and a collar at an open end for insertion of the body part therein, to obtain external protection over the body part, said package dispenser comprising:

a container having a cavity, said cavity having therein a plurality of said garments, all but an outermost garment thereof being fitted inside of another of remaining garments of said plurality of garments;

said container having an open end, each collar of each of said garments being wrapped around said open end of said container, said plurality of garments covering said open end of said container;

said plurality of garments being wrapped in a predetermined pattern so that an innermost garment thereof is exposed to said open end of said container, and next subsequent garments of said plurality of garments are wrapped around said innermost garment;

said outermost garment covering said innermost garment and each of said next subsequent garments; and said container having a geometric shape conforming to a geometric shape of said outermost garment, said innermost garment being collapsible onto the body part.





3. A package dispenser according to claim 2, wherein said container has an outside layer and an inelastic gas-impermeable inside layer, said inelastic gas-impermeable layer having a geometric shape conforming to a geometric shape of said outermost garment, and/or further comprising vacuum means, said vacuum means drawing a vacuum from said elastic, expandable material of said innermost garment,
- said vacuum of said vacuum means is applied between said outermost garment and said inelastic gasimpermeable inside layer in an expanded position for insertion of the body part therein, upon release of said vacuum of said vacuum means against said innermost garment.
4. A package dispenser according to claim 3, wherein said garments (such as gloves, preferably latex gloves) are stored in a relaxed shape, so that when said container is opened for use, said vacuum applied in said package causes said garments to expand, and wherein said garments are tapered from each said open end of each of said garments toward each said distal closed end of each of said garments.
5. A package dispenser according to any of claims 2 to 4, wherein said container is in the shape of a glove, and where said package is such that a user dons said garment





sequentially from said container having said vacuum means therein, said container having a means for constricting a palm portion of said innermost garment and for forcing finger portions of said innermost garment to expand and conform to a proper position to allow easy donning.

6. A package dispenser according to claim 4, for sequentially dispensing an innermost glove upon a hand of a user from a plurality of gloves placed inside each other, each of said gloves having five finger portions wherein said vacuum holds said innermost glove of said plurality of gloves intact in an open expanded position for insertion of a hand therein, said package comprising a glove-shaped container, said container having a plurality of individual finger portions so that said five finger portions of said innermost glove can remain expanded to allow a hand of a user to be loosely inserted therein, said innermost glove

stretchable over an open end of said container, said innermost glove being inside another next subsequent glove of said plurality of gloves, wherein a releasing means is provided for producing a space between said innermost glove and said another next subsequent glove.

7. A package dispenser according to claim 4, wherein said garments are condoms, and said container is in the shape of





a condom and further comprising at least one leak-proof layer positioned in between two adjacent condoms of each of said condoms of said plurality of condoms, and where said condoms are preferably latex condoms.

8. A package dispenser according to any of claims 2 to 7, which is mountable upon a wall, said package dispenser having a mateable fastener mateable with a mounting means to mount said container upon the wall.
9. A package dispenser according to any of claims 1 to 8, wherein said container has two accesses, one access in said open end of said container for an insertion of the body part therein and another access in said distal closed end for evacuation of said therefrom, and/or wherein said container has a movable releasing means for producing displacement of said innermost garment from said container.
10. A package dispenser according to claim 9, wherein said releasing means comprises a thin continuous ribbon, and/or is annular and includes a tubular plastics cover having a waisted area line cut spiralling around said container.
11. A package dispenser according to any of claims 1 to 10, further comprising a neck collar at said open end of said





container, said collar being tapered inward or flared outward.

12. A package dispenser according to any of c 3ms 1 to 11, wherein said inelastic, gas-impermeable inner layer of said container is in the shape of a glove, said package dispenser being preferably such that a user dons said garment sequentially from a vacuum packed container, said container having a means for constricting a palm portion of said innermost garment and for forcing finger portions of said innermost garment to expand and conform to the proper position to allow easy donning.
13. A package dispenser according to any of claims 1 to 11, wherein said garments are condoms, and said inelastic, gas-impermeable inner-layer of said container is in the shape of a condom.
14. A package dispenser according to any of claims 1 to 13, wherein said container includes an inside portion shaped like a large glove and an outside portion having a predetermined shape and/or wherein said package dispenser has an exterior portion (preferably flattened) in a predetermined shape of, and an interior portion in a shape of, a flexible non-elastic large glove.





15. A package dispenser according to claim 1, wherein said garments are stored in a relaxed shape, so that when said container is opened for use, said vacuum applied in said package dispenser causes said garments to expand and further comprising at least one leak-proof layer positioned in between two adjacent garments of each of said garments of said plurality of garments in which said leak proof layer is preferably a hermetic seal.
16. A package dispenser for the dispensing of condoms made of an elastic, expandable material for wear upon a body part, said condoms having a distal closed end and an open end for insertion of the body part therein, said package dispenser
- a container, said container having a cavity therein, said cavity of said container having therein a plurality of condoms with respective condoms of said plurality being fitted inside of each other of said condoms; said container having an open end, said open end of each of said condoms being rolled around said open end of said container, said condoms covering said open end of said container located at an opposite end of said container from said distal closed end of said container; said condoms being wrapped in a predetermined pattern wherein an innermost condom is exposed to said open end of said container, and next

This Sheet Has Been Replaced





subsequent condoms of said plurality of condoms are wrapped around said innermost condom;

said plurality of condoms including an outermost condom enclosing said next subsequent condoms and said innermost condom, said innermost condom having an outer hermetically sealed separator layer between said open end of said container and said innermost condom; each said condom of subsequent condoms of said plurality of condoms having a further hermetically sealed separator layer; and

said further hermetically sealed separator layer having a geometric shape generally conforming to a geometric shape of said outermost condom.

17. A package dispenser according to claim 16, wherein said container is responsive to opening by application of force against an edge of said open end of said container, for expansion of said condoms and said container in an open position and in an expanded position, for insertion of the body part therein, and wherein said container has a movable releasing means for producing the displacement of said at least one innermost condom from said condoms.

18. A package dispenser according to claim 17, wherein said separator layer comprises an annular flange near an open end of said separator layer (said separator layers being preferably hermetically sealed to said annular flange).





19. A package dispenser according to claim 18, wherein at least one of said separator layers is heat sealed and/or adhesively bonded and/or ultrasonically bonded to said annular flange (typically by a combination of at least two seals selected from a heat seal, an adhesive bond and an ultrasonic bond).
20. A package dispenser according to claim 19, wherein each of said separator layers comprises an impermeable barrier material, and/or a low density polyethylene, and/or a conductive material; and/or wherein each of said separator layers further comprises a separate attachment region spaced apart from a body portion of each said separator layer.
21. A package dispenser according to claim 16 or 17, wherein said container comprises a flexible outer shell, wherein further said condoms are nested with said separator layers within said container; and/or wherein the container is preferably flattened and operable to an expendable position, and wherein said condoms are partially rolled over an open edge of said container.
22. A package dispenser according to claim 21, in which further said container has an annular flange encircling said





container, said separator layers being attachable to said annular flange for providing a sealed surface thereat.

18. A package dispenser according to claim 17, wherein said separator layer comprises an annular flange near an open end of said separator layer (said separator layers being preferably hermetically sealed to said annular flange).
19. A package dispenser according to claim 18, wherein at least one of said separator layers is heat sealed and/or adhesively bonded and/or ultrasonically bonded to said annular flange (typically by a combination of at least two seals selected from a heat seal, an adhesive bond and an ultrasonic bond).
20. A package dispenser according to claim 19, wherein each of said separator layers comprises an impermeable barrier material, and/or a low density polyethylene, and/or a conductive material; and/or wherein each of said separator layers further comprises a separate attachment region spaced apart from a body portion of each said separator layer.
21. A package dispenser according to claim 16 or 17, wherein said container comprises a flexible outer shell, wherein further said condoms are nested with said separator layers





within said container; and/or wherein the container is preferably flattened and operable to an expendable position, and wherein said condoms are partially rolled over an open edge of said container.

22. A package dispenser according to claim 21, in which further said container has an annular flange encircling said container, said separator layers being attachable to said annular flange for providing a sealed surface thereat.
23. A package dispenser for sequentially dispensing an innermost condom package from a plurality of condom packages placed inside each other for insertion of a body part within a condom within said innermost condom package, said package dispenser having a shape of a condom so that an innermost condom of said innermost package can expand to allow a penis of a user to be inserted therein, said innermost condom having a rolled edge, said rolled edge of said innermost condom being stretchable over an open end of said at least one condom package, said innermost condom package being inside a subsequent condom package of said plurality of condom packages, wherein a releasing means is provided for producing a space between said innermost condom package and said subsequent condom package.

This Sheet Has Been Replaced





24. A package dispenser according to claim 23, wherein said container is flattened and openable to an expandable position; and/or wherein said releasing means is annular and/or includes a tear strip, and wherein said separator layer further comprises an annular flange near an open end of said layer.

25. A package dispenser for dispensing of condoms for wear upon a body part, said condoms having a distal closed end and an open end for insertion of the body part therein, said package dispenser comprising:

a container having an inner cavity, said inner cavity having inside therein a plurality of the condoms, each respective condom of said plurality of condoms wrapped inside of another condom of said plurality of condoms, each condom of said condoms having a predetermined geometric shape;

said plurality of condoms including an innermost condom located within respective subsequent condoms of said plurality of condoms;

- said container having a plurality of hermetically sealed separator layers conforming to said predetermined geometric shape of each of said condoms; said condoms





being placed in a predetermined pattern wherein an innermost condom is exposed; a first hermetically sealed separator layer being provided between said innermost condom and said open end of said container, and subsequent condoms of said plurality of condoms being rolled around said innermost condom; and a release tab responsive to releasing each condom from said plurality of condoms upon release of said tab.

26. A package dispenser for dispensing at least one condom for wear upon a body part, said at least one condom having a distal closed end and an open end for insertion of the body part therein, said package dispenser comprising:

a container having an inner cavity having said at least one condom located inside said inner cavity;

said container having an openable open end and a closable or closed end;

said openable end having a major axis between respective side edges of said container;

said container having a flattened closed position and an expandable open position;





wherein in the flattened closed position said container has respective upper and lower surfaces being broader than a predetermined height of the container at respective side edges thereof;

wherein in the open position said open end of said container has a height greater than a predetermined height of said container in a closed position;

wherein said container is openable by pressing on said respective side edges corresponding to said major axis of said openable end of said container when in a closed position;

wherein said container is opened to expose said at least

said at least one condom having a pre in ric shape;

said container having at least one sealed separator layer placed between said at least one condom and said open end of said container; and

said container having at least one release tab for releasing said at least one sealed separator layer from between said at least one condom and said open end of said container and for exposing said at least one condom to said open end of said container for insertion of the body part therein.





27. A package dispenser for dispensing of a condom directly on a penis comprising:

a hollow container having an elongated shape of a condom, said hollow container being closed at one end and open at another end, said container being made of a flexible material;

said hollow container having an inside wall configuration conforming substantially to an exterior shape of a condom, wherein said container is adapted to nest a condom in an open position therein,

said hollow container having a condom retaining means at said open end of said container.

28. A package dispenser for dispensing a plurality of condoms, said plurality of condoms including an innermost condom, an outermost condom and at least one next subsequent condom located between said innermost condom and said outermost condom of the plurality of condoms;

said package dispenser comprising a container having an openable open end and a closable or closed end;





said container having a flattened closed position and an expandable open position,

said openable end having a major axis between respective side edges of said container;

wherein in the flattened closed position said container has respective upper and lower surfaces said respective upper and lower surfaces being broader than a predetermined height of the container at respective side edges thereof; wherein in the open position said open end of said container has a height greater than the predetermined height of the container in a closed position; wherein said container is opened by pressing on said respective side edges corresponding to said major axis of said openable end of said container when in a closed position;

wherein said container is opened to expose said at least one innermost condom of said plurality of condoms; wherein said container includes a plurality of sealed separator layers including an innermost sealed separator layer, an outermost separator layer and at least one next subsequent sealed separator layer between said innermost sealed separator layer and said outermost separator layer of said plurality of layers;

wherein said innermost sealed separator layer is located between said open end of said container; wherein said at





least one further sealed separator layer is located between said next subsequent condom and said outermost condom.

29. A package dispenser for dispensing at least one condom for wear upon a body part, said at least one condom having a predetermined geometric shape with a distal closed end and an open end for insertion of the body part therein, said package dispenser comprising:

a container having an inner cavity, said inner cavity having said at least one condom located inside said inner cavity,

said container having an openable open end and a closable or closed end;

said container having a flattened closed position and an

said openable end having a major a een resp ive side edges of said container;

wherein in said flattened closed position said container has respective upper and lower surfaces being broader than a predetermined height of said container at respective side edges thereof;

wherein in said open position, said open end of said container has a height greater than the predetermined height of the container in a closed position; wherein said





container is opened by pressing on said respective side edges corresponding to said major axis of said openable end of said container when in a closed position;
wherein said container is opened to expose said at least one condom.

30. A package dispenser for dispensing a plurality of condoms, said plurality of condoms including an innermost condom, an outermost condom and at least one next subsequent condom located between said innermost condom and said outermost condom of the plurality of condoms;

said package dispenser comprising a container having an openable open end and a closable or closed end;

said container having a flattened closed position and an expandable open position;

said openable end having a major axis between respective side edges of said container;

wherein in said flattened closed position said container has respective upper and lower surfaces being broader than a predetermined height of said container at respective side edges thereof;

This Sheet Has Been Replaced





wherein in said open position said open end of said container has a height greater than the predetermined height of said container in a closed position;

wherein said container is opened by pressing on said respective side edges corresponding to said major axis of said openable container end of said container when in a closed position;

wherein said container is opened to expose said innermost condom of said plurality of condoms.

31. A package dispenser for dispensing a condom directly on a penis comprising:

a container having the elongated shape of a condom closed at one end and open at another end, said container being made of a flexible material permitting said container to be flattened;

said container having a lip forming said open end thereof and a flange encircling said container adjacent said open end;

said container having a first separator layer conforming to and lining an inside of said container, with said separator





layer having an open end stretched over said flange for achieving a hermetic seal within said container, said first separator layer having a tear strip on an outside adjacent said flange for providing tearing of said first separator layer;

a condom located within said container lining an inside of said first separator layer, with an open end of said condom being rolled over said first separator layer and said flange, leaving said tear strip exposed;

a second separator layer lining an inside wall of said condom, with an open end of said second separator layer rolled over said condom and said first separator layer, on said flange, to achieve hermetic sealing of said condom, so that removal of said second separator layer permits a penis to be inserted into said condom and pulling of said tear strip unseals said condom from said first separator layer, resulting in said condom being released so that the penis can withdraw from said container and first separator layer with said condom on the penis;

said container with said condom and said separator layers therein normally being flattened for convenient storage and being enlargeable to the shape of the penis when said





wherein said container is opened to expose said innermost condom of said plurality of condoms.

31. A package dispenser for dispensing a condom directly on a penis comprising:

a container having the elongated shape of a condom closed at one end and open at another end, said container being made of a flexible material permitting said container to be flattened;

said container having a lip forming said open end thereof and a flange encircling said container adjacent said open end;

said container having a first separator layer conforming to and lining an inside of said container, with said separator layer having an open end stretched over said flange for achieving a hermetic seal within said container, said first separator layer having a tear strip on an outside adjacent said flange for providing tearing of said first separator layer;

a condom located within said container lining an inside of said first separator layer, with an open end of said condom





being rolled over said first separator layer and said flange, leaving said tear strip exposed;

a second separator layer lining an inside wall of said condom, with an open end of said second separator layer rolled over said condom and said first separator layer, on said flange, to achieve hermetic sealing of said condom, so that removal of said second separator layer permits a penis to be inserted into said condom and pulling of said tear strip unseals said condom from said first separator layer, resulting in said condom being released so that the penis can withdraw from said container and first separator layer with said condom on the penis;

said container with said condom and said separator layers therein normally being flattened for convenient storage and being enlargeable to the shape of the penis when said

32. A package dispenser for dispensing condoms directly on a penis comprising:

a container having the elongated shape of a condom closed at one end and open at another end, said container being made of a flexible material permitting said container to be flattened;





said package dispenser having a plurality of condoms therein,

said container having a lip surrounding said open end thereof and a flange encircling said container adjacent said open end;

a first separator layer conforming to and lining an inside of said container, with said first separator layer having an open end stretched over said flange for achieving hermetic sealing of an inside of said container, said first separator layer having a first tear strip means on an outside adjacent said flange for unsealing said inside of said container;

a first condom of said plurality of condoms within said container lining the inside of said first separator layer, with an open end of said first condom rolled over said first separator layer and said flange leaving said first tear strip means exposed;

a second separator layer lining an inside wall of said first condom with an open end of said second separator layer rolled over said first condom and said first separator layer on said flange, thereby achieving hermetic sealing of said first condom,





said second separator layer having a second tear strip means on the outside adjacent said flange and said first tear strip means for tearing said second separator layer; a second condom of said plurality of condoms within said container lining an inside of said second separator layer, with an open end of said second condom rolled over said first separator layer, said first condom, and said second separator layer, leaving said first and second tear strip

a third separator layer lining an inside wall of said second condom, with an open end of said third separator layer rolled over said first and second condoms and separator layers on said flange, thereby achieving hermetic sealing of said second condom and leaving said tear strip means exposed, wherein removal of said third separator layer permits a penis to be inserted into said second condom and pulling of said second tear strip means unseals said second condom from said second separator layer, resulting in said second condom being released so that the penis can withdraw with said second condom on said penis, providing access to said container for the penis to be inserted for later withdrawal of a subsequent condom thereon;

wherein said condoms and said separator layers are interleaved,





said container with said interleaved condoms and separator layers so therein normally being flattened for convenient storage and being enlargeable to a shape of a penis when each condom of said plurality of condoms is to be dispensed.

33. A package dispenser according to claim 31 or 32, wherein said container is foreshortened so that said condoms therein are partially unrolled on the outside of said container.
34. A condom dispensing package comprising:
a container having a circumferential wall; and
a condom having a circumferential end secured to said wall in the vicinity of said opening, said condom extending into said container;
said circumferential wall flexing between a first and a second configuration, said container being relatively flat in said first configuration so that said container can be stored;
said circumferential wall defining in said second configuration an opening for receiving a penis, said container and said condom cooperating to don said condom on the penis as said penis is inserted into said opening.

This Sheet Has Been Replaced





35. The package of claim 34 wherein said circumferential end cooperates with said circumferential wall to secure said condom within said container.
36. The package of claim 34 wherein said circumferential wall is formed with a lip, said circumferential end being mounted on said lip to secure said condom.
37. The package of claim 34 wherein said circumferential end is formed with a lip, and said circumferential end has a dimension smaller than said lip and is extended over said lip to form a resilient interference fit.
38. The package of claim 34 wherein said container has a longitudinal length and wherein said condom has a condom length longer than said longitudinal length.
39. The package of claim 39 wherein said condom is rolled within said container.
40. The package of claim 39 wherein said container is shaped to receive the head of said penis as said penis is inserted into said opening to allow said condom to be unrolled onto said penis.

This Sheet Has Been Replaced





41. A method of donning a condom from a condom package, said package including container with a circumferential wall with an opening and a condom extending into said container and having a condom end secured to said circumferential wall, comprising the steps of:

inserting the head of the penis into said opening to force said condom to be deposited onto said penis; and
after said condom is substantially deposited onto said penis, separating said container from said condom.

The method of claim 40 wherein said container has a longitudinal length shorter than the length of said condom so that the penis is inserted into the opening as the condom is deposited onto the penis, it is automatically separated from the container in a single motion.

42. A package for dispensing of a condom directly on a penis comprising:

a container having the elongated shape of a condom closed at one end and open at another end, said container being made of a flexible material permitting said container to be flattened;

said container having a lip forming the open end thereof;
said container having a closure cap covering said open end of said container with said closure cap having a condom holder plate extending therefrom and insertable within said condom within said container, said closure cap having a





snap hinge on the outside thereof for opening said closure cap.

43. The package for dispensing a condom directly on a penis as in Claim 42, further comprising:
- a first separator conforming to and lining the inside of said container with said separator having an open end stretched over a flange thereof, for achieving a hermetic seal within said container, said first separator having a tear strip on the outside adjacent said flange for providing tearing of said first separator,
- said condom within said container lining the inside of said first separator, with the open end of said condom rolled over said first separator and said flange leaving said tear strip exposed;
- a second separator lining the inside wall of said condom with the open end of said second separator rolled over said condom and first separator on said flange to achieve hermetic sealing of said condom, so that removal of said second separator permits the penis to be inserted into said condom and pulling of said tear strip unseals said condom from said first separator resulting in said condom being released so that the penis can withdraw from said container and first separator with said condom on the penis;
- said container with the condom and separators therein normally being flattened for convenient storage and being





enlargeable to the shape of a penis when said condom is to be dispensed on a penis.

44. The package of Claim 42 in which said container is foreshortened so that the condom therein is partially unrolled on the outside of said container.

45. The package for dispensing condoms as in Claim 2 further comprising:

a second condom within said container lining the inside of said second separator, with the open end of said condom rolled over said first separator, said first condom and said second separator leaving said first and second tear strip means exposed;

a third separator lining the inside wall of said second condom with the open end of said third separator rolled over said first and second condoms and separators on said flange achieving hermetic sealing of said second condom and leaving said tear strip means exposed, so that removal of said third separator permits the penis to be inserted into said second condom and pulling of said second tear strip means unseals said second condom from said second separator resulting in said condom being released so that the penis can withdraw with said second condom on said penis, providing access to said container for a second penis to be





inserted for later withdrawal with said second condom on said second penis;

said container with the interleaved condoms and separator so therein normally being flattened for convenient storage and enlargeable to the shape of a penis when said condoms are to be dispensed.

46. The package of Claim 45, in which said container is forshortened so that the condoms therein are partially unrolled on the outside of said container.
47. A package for dispensing of a condom directly on a penis comprising:
a container having the elongated shape of a condom closed at one end and open at another end, said container being made of a flexible material permitting said container to be flattened,
said container having a lip forming the open end thereof,
said container having a closure cap covering said open end of said container,
said closure cap having a snap hinge on the outside thereof for opening said closure cap.
48. A pouch package for dispensing of a condom directly on a penis comprising:





a hollow container having the elongated shape of a condom, said hollow container being closed at one end and open at another end, said container being made of a flexible material;

said hollow container having an inside wall configuration conforming to an exterior shape of a condom, wherein said closed end of said container is adapted to nest a closed portion of a condom therein,

said hollow container having a condom retaining means thereat.

49. The pouch package for dispensing of a condom directly upon a penis wherein said condom retaining means comprises a lip edge around a periphery of said open end of said hollow container.

50. The pouch package for dispensing a condom directly on a penis as in Claim 8, further comprising:
a condom within said hollow container, said condom lining said hollow interior of said container, with an open end of said condom rolled over said lip edge, leaving a rolled up portion of said condom exposed;
said container with said condom therein normally being flattened for convenient storage and being enlargeable to the shape of a penis when said condom is to be dispensed on a penis.

This Sheet Has Been Replaced





51. The package as in Claim 50 wherein said container is enlargeable to the shape of a penis by pinching of co-joined edges thereof toward a mid point of two partially conjoined walls of said container.
52. The package of Claim 48 in which said container is foreshortened so that the condom therein is partially unrolled on the outside of said container.

This Sheet Has Been Replaced

