200007260-3

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 :
G01P 3/489, G01R 31/34, G01L 3/00

A1

(11) International Publication Number: WO 99/66335

(43) International Publication Date: 23 December 1999 (23.12.99)

(21) International Application Number: PCT/IL99/00290

(22) International Filing Date: 1 June 1999 (01.06.99)

(30) Priority Data:
124932 16 June 1998 (16.06.98) IL

(71) Applicant *(for all designated States except US)*: M.E.A. MOTOR INSPECTION LTD. [IL/IL]; Poleg Industrial Park, Netanya-South, P.O. Box 8027, 42101 Netanya (IL).

(72) Inventors; and
(75) Inventors/Applicants *(for US only)*: COHEN, Menachem [IL/IL]; Yeari Street 9/30, 93843 Jerusalem (IL). COHEN, Eyal [IL/IL]; Daniel Moritz Street 56/4, 69345 Tel Aviv (IL).


(74) Agent: REINHOLD COHN AND PARTNERS; P.O Box 4060, 61040 Tel Aviv (IL).

(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published
With international search report.
With amended claims.

1 PD.
1 appln.
2 Invs.
IPC : G01P 3/489
IPER 16/12/99.

(54) Title: METHOD AND SYSTEM FOR PERFORMANCE TESTING OF ROTATING MACHINES



(57) Abstract

A method for measuring an angular rotation of a rotating shaft, comprising the steps of attaching to the shaft a digital rotary encoder which generates successive HIGH and LOW logic levels during respective successive time intervals. The shaft is rotated and the respective time periods of each successive logic level generated by the digital rotary encoder are accumulated so as to allow derivation of the angular rotation or a function thereof of the shaft. Such a method produces accurate results regardless of tolerance errors in the duty cycle of the encoder. This may be used for testing a performance of a rotating machine or of a component thereof in order to derive a speed-time characteristic of the rotating machine or a function thereof. Owing to the inherent high measurement resolution of the invention, dynamic performance may be determined accurately as well as steady-state performance without the need to slow down the machines speed of rotation by use of a flywheel.