



- (51) International Patent Classification:
E21B 33/06 (2006.01) *E21B 33/08* (2006.01)
- (21) International Application Number:
PCT/GB2012/050615
- (22) International Filing Date:
21 March 2012 (21.03.2012)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
1104885.7 23 March 2011 (23.03.2011) GB
- (71) Applicant (for all designated States except US): **MAN-AGED PRESSURE OPERATIONS PTE. LTD.** [SG/SG]; 1 Maritime Square, #12-04A, Harbour Front Centre, 099253 (SG).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **LEUCHTENBERG, Christian** [DE/SG]; Apt 06#103, Block 42A, Caribbean Apartments Keppel Bay Drive, 098656 (SG). **MAC-**

GREGOR, Alexander John [GB/SG]; 33 Jurong West St 41, #09-54 The Lakeshore, Singapore 649413 (SG).


(74) Agent: **FORRESTERS KETLEY & CO**; Chamberlain House, Paradise Place, Birmingham, West Midlands B3 3HP (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE,

[Continued on next page]

(54) Title: BLOW OUT PREVENTER



(57) Abstract: A blow out preventer (BOP), in particular a new configuration of BOP which may have a smaller outer diameter for a given operating force than conventional BOPs comprises a housing which has a longitudinal axis and which is divided in a first housing part (14a) and a second housing part (14b), movement of the first housing part relative to the second housing part being prevented by fasteners (16), each fastener including a shaft which extends through a fastener receiving passage provided in the first housing part into a fastener receiving passage provided in the second housing part, the housing being further provided with fluid flow passages (44) which extend from the first part of the housing to the second part of the housing, the fluid flow passages being interspersed between fastener receiving passages. In one embodiment of the invention, three annular BOPs according to this design are integrated to form a stack. A seal assembly is mounted in a central bore of the bore, the lowermost end of the seal assembly being supported on a locking dog (56) which extends from the BOP housing into the central bore. The locking dog is movable, for example using hydraulic actuation means, and can be retracted into the wall of the BOP housing.



DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT,
LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE,
SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— *before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments (Rule 48.2(h))*

Published:

— *with international search report (Art. 21(3))*

(88) Date of publication of the international search report:

30 May 2013