

**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶: H04L 12/56	A1	(11) International Publication Number: WO 97/17787 (43) International Publication Date: 15 May 1997 (15.05.97)
(21) International Application Number: PCT/SE96/01413 ✓ (22) International Filing Date: 4 November 1996 (04.11.96) ✓ (30) Priority Data: 9503967-3 ✓ 9 November 1995 (09.11.95) SE (71) Applicant (for all designated States except US): TELEFON- AKTIEBOLAGET LM ERICSSON (publ) [SE/SE]; S-126 25 Stockholm (SE). (72) Inventor; and (75) Inventor/Applicant (for US only): HÖRLIN, Dan [SE/SE]; Hemskogsvägen 212, S-122 64 Enskede (SE). (74) Agents: BERGENTALL, Annika et al.; Göteborgs Patentbyrå AB, P.O. Box 5005, S-402 21 Göteborg (SE).	(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, <u>SG</u> , SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>	
(54) Title: ARRANGEMENT AND METHOD RELATING TO PACKET FLOW CONTROL (57) Abstract The present invention relates to an arrangement and a method for controlling the flow of signals comprising a number of information packets in a communications network, e.g. an ATM-network. The arrangement comprises means for separating the signals in first traffic signals and second traffic signals. The first traffic signals are signals that have a higher proportion of guaranteed resources, i.e. bandwidth, than the second traffic signals. The first traffic signals are also given a lower priority than the second traffic signals. The first and second traffic signals are handled separately.		