


PCTORGANISATION MONDIALE DE LA PROPRIÉTÉ INTELLECTUELLE
Bureau international

DEMANDE INTERNATIONALE PUBLIÉE EN VERTU DU TRAITE DE COOPERATION EN MATIÈRE DE BREVETS (PCT)

(51) Classification internationale des brevets ⁷ : A61J 1/00	A1	(11) Numéro de publication internationale: WO 00/47159 (43) Date de publication internationale: 17 août 2000 (17.08.00)
(21) Numéro de la demande internationale: PCT/FR00/00315 (22) Date de dépôt international: 9 février 2000 (09.02.00) (30) Données relatives à la priorité: 99/01755 10 février 1999 (10.02.99) FR (71) Déposant (pour tous les Etats désignés sauf US): BIODOME [FR/FR]; Parc Technologique de la Béchade, Z.I. de Lavaur, F-63500 Issoire (FR). (72) Inventeur; et (75) Inventeur/Déposant (US seulement): ANEAS, Antoine [FR/FR]; 7, Impasse Voltaire, F-63200 Menetrol (FR). (74) Mandataires: MYON, Gérard etc.; Cabinet Lavoix Lyon, 62, rue de Bonnel, F-69448 Lyon Cedex 03 (FR).		(81) Etats désignés: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, brevet ARIPO (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), brevet eurasien (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), brevet européen (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), brevet OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Publiée <i>Avec rapport de recherche internationale.</i>
(54) Title: CONNECTING DEVICE BETWEEN A CONTAINER AND ITS CONTENTS AND READY-TO-USE ASSEMBLY COMPRISING SAME		
(54) Titre: DISPOSITIF DE CONNEXION ENTRE UN RECIPIENT ET UN CONTENANT ET ENSEMBLE PRET A L'EMPLOI COMPRENANT UN TEL DISPOSITIF		
(57) Abstract <p>The invention concerns a device comprising a base plate (10) mounted on the container (2) and a sleeve (14) forming an inner bore (A), and a plunger capable of sliding in said bore (A), between a first released position relatively to the cap (5) of the container (2) and a second position called transfer position, wherein a hollow needle (21) borne by the plunger (20) passes through the cap (5). The base plate (10) is provided with at least an elastic spout (15) retaining the plunger (20) in transfer position, said spout projecting, from the sleeve (14), towards the bore (A) inside and capable of co-operating with an outer radial flap (24) of the plunger (20).</p> <p>(57) Abrégé Ce dispositif comprend une embase (10), montée sur le récipient (2) et une douille (14) formant un alésage interne (A), et un piston (20) apte à coulisser dans cet alésage (A), entre une première position dégagée par rapport au bouchon (5) du récipient (2) et une seconde position dite de transfert, dans laquelle une aiguille creuse (21) portée par le piston (20) traverse le bouchon (5). L'embase (10) est pourvue d'au moins un bec élastique (15) de retenue du piston (20) en position de transfert, ce bec faisant saillie, à partir de la douille (14), vers l'intérieur de l'alésage (A) et étant apte à coopérer avec une patte radiale externe (24) du piston (20).</p>		



UNIQUEMENT A TITRE D'INFORMATION

Codes utilisés pour identifier les Etats parties au PCT, sur les pages de couverture des brochures publiant des demandes internationales en vertu du PCT.

AL	Albanie	ES	Espagne	LS	Lesotho	SI	Slovénie
AM	Arménie	FI	Finlande	LT	Lituanie	SK	Slovaquie
AT	Autriche	FR	France	LU	Luxembourg	SN	Sénégal
AU	Australie	GA	Gabon	LV	Lettonie	SZ	Swaziland
AZ	Azerbaïdjan	GB	Royaume-Uni	MC	Monaco	TD	Tchad
BA	Bosnie-Herzégovine	GE	Géorgie	MD	République de Moldova	TG	Togo
BB	Barbade	GH	Ghana	MG	Madagascar	TJ	Tadjikistan
BE	Belgique	GN	Guinée	MK	Ex-République yougoslave de Macédoine	TM	Turkménistan
BF	Burkina Faso	GR	Grèce	ML	Mali	TR	Turquie
BG	Bulgarie	HU	Hongrie	MN	Mongolie	TT	Trinité-et-Tobago
BJ	Bénin	IE	Irlande	MR	Mauritanie	UA	Ukraine
BR	Brésil	IL	Israël	MW	Malawi	UG	Ouganda
BY	Bélarus	IS	Islande	MX	Mexique	US	Etats-Unis d'Amérique
CA	Canada	IT	Italie	NE	Niger	UZ	Ouzbékistan
CF	République centrafricaine	JP	Japon	NL	Pays-Bas	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norvège	YU	Yougoslavie
CH	Suisse	KG	Kirghizistan	NZ	Nouvelle-Zélande	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	République populaire démocratique de Corée	PL	Pologne		
CM	Cameroun	KR	République de Corée	PT	Portugal		
CN	Chine	KZ	Kazakhstan	RO	Roumanie		
CU	Cuba	LC	Sainte-Lucie	RU	Fédération de Russie		
CZ	République tchèque	LI	Liechtenstein	SD	Soudan		
DE	Allemagne	LK	Sri Lanka	SE	Suède		
DK	Danemark	LR	Libéria	SG	Singapour		
EE	Estonie						

DEVICE FOR CONNECTION BETWEEN A RECIPIENT AND A CONTAINER AND
READY-TO-USE ASSEMBLY COMPRISING SUCH A DEVICE

5 The present invention relates to a device for connection between a closed recipient and a container. The invention also relates to a ready-to-use assembly comprising, inter alia, a closed recipient and a connection device of the afore-mentioned type.

10 In the domain of packaging medicines, it is known to store one component of a pharmaceutical preparation, such as for example its active ingredient, in a recipient closed by a relatively non-rigid material, for example made of elastomer. A liquid may be introduced into this recipient, after perforation of the stopper, in order to place the component contained in the recipient in solution or in suspension, so as to obtain a preparation, in particular a medicament or vaccine, in liquid form ready to be administered to the patients.

15 Documents WO-A-90/03536 and WO-A-97/10156 disclose connection devices, each comprising a base adapted to cover the neck of a recipient and extended by a flange or sleeve forming an inner bore, while a plunger is mounted to slide in this bore. The plunger is provided to be pushed towards a transfer position in which a hollow needle borne by the plunger passes through the stopper of the recipient. These known devices allow axial movements of the plunger when it has been displaced up to transfer position, which might lead to leakages and does not efficiently control the lost volume of the recipient, i.e. the quantity of liquid which cannot be drawn off therefrom.

20 Document WO-A-98/13006 discloses a device adapted, in particular, for connection between a recipient with a stopper which is adapted to be perforated and a syringe, in which teeth are distributed about the axis of the plunger and provided to be returned centrifugally or centripetally in order to cooperate with a stop element provided on a base. This device allows

a locking of the plunger as long as the effort of displacement to which it is subjected is not too great. However, under certain conditions, the teeth might be deformed plastically, which might allow the plunger to tear in a direction of extraction.

Document WO-A-98/32411 discloses a connection device in which a plunger fast with a needle is provided with a flap intended to be engaged in a reinforcement made in the thickness of a base. The ring which borders this reinforcement is deformed essentially parallel to the direction of displacement of the plunger and by a small width in a radial direction, which does not make it possible to ensure an efficient hold of the plunger in position of transfer.

It is a particular object of the present invention to overcome these drawbacks, by proposing an improved connection device in which a particularly efficient locking of the plunger in transfer position is obtained

To that end, the invention relates to a device of the type mentioned above, in which the base is provided with at least one elastic catch for retaining the plunger in transfer position, this catch projecting, from the bush, towards the interior of the bore being adapted to cooperate with an outer radial tab of the plunger.

Thanks to the invention, the elastic catch guarantees a efficient locking of the plunger in transfer position. Such locking is all the more efficient as a plurality of catches are advantageously provided, which catches may be regularly distributed about the central axis of the device.

According to a first advantageous aspect of the invention, the catch is provided on an outer radial face, with a heel adapted to cooperate with a ring for locking the plunger in position of retention, this ring being adapted to slide about the bush. This ring gives the retaining catch a sufficient rigidity to efficiently resist an effort of displacement of the plunger from the transfer position. This ring is advantageously provided with an outer radial flange for locking in translation in a position of cooperation with the catch.

According to another advantageous aspect of the invention, the device comprises means for locking in rotation the plunger and/or the locking ring. These means advantageously comprise longitudinal ribs made on the inner face and/or the outer face of the bush and adapted to cooperate with corresponding elements in relief provided on the outer radial surface of the plunger and/or on the inner radial surface of the ring.

According to another advantageous aspect of the invention, in disengaged position with respect to the stopper, the plunger is fast with the bush by at least one breakable tongue. In addition, the base and the plunger are advantageously formed in one piece by injection of plastics material. This facilitates positioning of the plunger with respect to the base, insofar as this positioning results directly from the method of manufacture and as it is not necessary to provide an assembly step corresponding to the insertion of the plunger in the base. Moreover, the one-piece nature of the base and plunger guarantees that the plunger does not risk sliding in the bore, particularly under the effect of vibrations or sudden accelerations during transport of the device. In this way, the tip of a needle borne by the plunger is held for certain inside the bore, with the result that it does not risk projecting beyond the base to the point of marking or perforating a stopper when the device is positioned on the recipient. With the known devices, such a risk could not be completely eliminated, including when using beads for holding the plunger.

According to another advantageous aspect of the invention, a cap for protecting the bore and the plunger is provided, on an inner face, with a member for transmission of a thrust effort for the displacement of the plunger from the first position towards the second position. In this way, the protecting cap serves as member for manoeuvring the plunger.

According to another advantageous aspect of the invention, the bush comprises, near its free edge, means for blocking the container by cooperation of shapes, in particular bayonet-type locking slots adapted to cooperate with at least one tab of the container.

According to another advantageous aspect, the base comprises a cylindrical surface defining a skirt which extends around the neck of the recipient and bears hooking teeth, this skirt comprising at least one opening for access to the catch and/or to certain hooking teeth from the outside. These openings are particularly useful for efficiently moulding the catch or catches and the corresponding teeth.

The invention also relates to a ready-to-use assembly comprising a closed recipient containing a product, in particular a pharmaceutical preparation, this recipient being provided with a neck whose opening is obdurate by a stopper, and a connection device as described herein above, mounted on the recipient. Such an assembly enables a component of a medicine or a vaccine, in particular its active ingredient, to be kept sterile and to be prepared when necessary by mixture with a liquid, while its plunger is efficiently held in position. The invention will be more readily understood and other advantages thereof will appear more clearly on reading the following description of an embodiment of a connection device in accordance with its principle, given solely by way of example, with reference to the accompanying drawings, in which:

Figure 1 is an exploded side view of a ready-to-use assembly according to the invention.

Figure 2 is a transverse section along line II-II of Figure 1.

Figure 3 is a broken section along line III-III in Figure 2, the plane of section of Figure 2 being indicated at II-II.

Figure 4 is a section similar to Figure 3 during a first step of using the device, and

Figure 5 is a section similar to Figure 3 during a second step of using the device.

The device 1 according to the invention has a dual function. On the one hand, it guarantees the tamper-proof nature of a recipient 2, for example a glass bottle containing a product (not shown) and previously closed or stopped. This product may be a powder intended to form a drinkable vaccine. It may be question of any other type of pharmaceutical preparation, in particular any type of medicine. On the other hand, the device 1 ensures or establishes a tight connection between the interior of the recipient 2 and the interior of another container 3, such as a syringe containing a liquid intended to place the product contained in the recipient 2 in solution or in suspension.

Instead of a syringe, the container 3 might be formed by a supple bag or another glass bottle.

The recipient 2 comprises a neck 4, whose opening 4a is tightly obturated by a stopper 5 made of a relatively non-rigid material, for example elastomer and, in particular, rubber. The neck 4 comprises an outer annular bead 4b on which is crimped a capsule 6 which also covers a peripheral part of the stopper 5 and which is provided with a central opening 6a through which it is possible to perforate the stopper 5. The stopper 5 comprises a substantially cylindrical central part 5a, adapted for supple and tight fit inside the opening 4a, and a flattened outer part 5b, shouldered by the bead 4a, and covered by the capsule 6.

The device 1 is essentially formed by two parts made by injection of plastics material, for example polyethylene, polypropylene, polyamide or ABS (polyacrylonitrile/butadiene/styrene), namely a base element 10 intended to be mounted around elements 3 to 6, and a cap 30.

The base element 10 comprises a plurality of hooking teeth 11 provided to be arranged around the bead 4b, in the manner shown in Figure 3. These teeth are defined in the lower part of a cylindrical skirt 12 surrounding the neck 4. The element 10 comprises a wall 13 for abutment on the upper part of the capsule 6, this wall being provided with a central recess 13a bordered by a cylindrical sleeve 14, concentric to the skirt 12 and extending opposite the wall 13 with respect to said skirt.

XX' denotes the central axis of the device 1 which is, in particular, the axis of the skirt 12 and of the sleeve 14. The sleeve 14 extends up to contact with the capsule 6 and defines a bore A centred on axis XX'.

In its part 14a closest to the stopper 5, the sleeve 14 is equipped with two spouts 15 and 15' projecting radially towards the interior of the bore A. Taking into account the plastic material used for moulding element 10, these spouts are supple enough to be elastically deformed,

as represented by arrow F in Figure 3.

As is clearly visible in Figure 2, the spouts 15 and 15' are diametrically opposite. However, other distributions, as well as a different number of retaining spouts, may be
5 envisaged.

Inside bore A is disposed a plunger 20 forming a hollow needle 21 adapted to perforate the stopper 5 in its central part. Plunger 20 is connected to the sleeve 14 by tongues 22 which are three in number and regularly distributed on the periphery of the plunger 20. In this way, the plunger 20 is in one-piece with the base 10 until the tongues 22 are broken.

10 Plunger 20 also forms a sleeve 23 for receiving the nose 3a of the syringe 3. The inner diameter of the sleeve 23 is chosen to be sufficiently small for only those syringes that may be introduced into said sleeve to correspond to a special manufacture intended for this use.

Plunger 20 bears two flaps 24 extending radially outwardly at the level of the transition zone 25 between the needle 21 and the sleeve 23.

15 On its inner radial surface, the sleeve 14 bears three longitudinal ribs 16 which cooperate with the sides of the flaps 24 to avoid a rotation of the plunger 20 about axis XX'.

The cap 30 is formed by a removable part 31, surrounding the free edge 14b of the sleeve 14, and by a ring 32 disposed around the sleeve 14, parts 31 and 32 being connected by a breakable zone 33.

20 Near its free edge 14b, the sleeve 14 is provided with an outer ring 14c provided to penetrate in an inner peripheral groove 32c of the ring 32. These outer ring and groove make it possible to maintain the cap 30 in position with respect to the element 10 in the storage position of Figures 1 to 3. The device 1 may be maintained in position on bottle 2 for several months, before use.

25 On its inner face 31a, part 31 is equipped with an extension 34 whose shape is adapted to be able to engage partially in the sleeve 23. In cross-section, this extension is

in the form of a cross, as it is formed by two substantially orthogonal ribs 34a and 34b intersecting at the level of axis XX'. In the position of Figure 3, the positioning of extension 34, and in particular its depth of penetration in sleeve 23, is determined by the cooperation of the ring 14c and the groove 32c.

When it is necessary to mix the contents of syringe 23 and of recipient 2, an effort, represented by arrow E in Figure 3, is exerted on part 31 of the cap 30, which has the effect of bearing the shoulders 34c of the ribs 34a and 34b against the free edge of the sleeve 23, while driving groove 32c with respect to ring 14c. Ring 32 then moves along the sleeve 14 in the direction of wall 13. The effort transmitted by the extension 34 to the sleeve 23 has the effect of cutting the tongues 22 and of pushing the plunger 20 towards the central opening 6a of the capsule 6, with the result that the sharp tip 21a of the needle 21 penetrates in the bottle 2 through the stopper 5. Effort E is maintained until the ring 32 is received in an annular space 17 defined between the upper part of the skirt 12 and the lower part 14a of the sleeve 14. Such displacement of the ring 32 corresponds to a displacement of the plunger 20 such that the transition zone 25 between the needle 21 and the sleeve 23 is disposed in the immediate vicinity of the upper surface of the capsule 6.

Such displacement of the plunger 20 has the effect of engaging the flaps 24 and 24' respectively to the rear of the spouts 15 and 15', these spouts being driven radially, outwardly of the sleeve 14, by flaps 24 and 24' during the movement of advance of the plunger 20. This is possible, as the front face 15a of the spout 15 visible in Figures 3 to 5 is inclined with respect to axis XX'. In that case, one is in the position of Figure 4 where the ring 32 exerts on a heel 15b located on a rear or outer radial surface 15c of the spout 15, a centripetal effort which maintains the spout 15 in an efficient locking position of the flap 24. Spout 15', which is identical, functions in the same way.

In order to guarantee a constant positioning of the ring 32

inside the volume 17, this ring is provided with an outer flange 32d adapted to engage beneath an upper re-entrant edge 12a of the skirt 12 provided on an angular sector at the level of spout 15. A similar re-entrant edge 12'a is provided at the level of spout 15'.

5 In this way, the ring 32 is firmly maintained in a position such that it prevents an elastic deformation of the spout 15 which might allow a movement of the flaps 24 in a direction moving away with respect to the stopper 5. Functioning is similar at the level of spout 15'.

10 At the level of its part 14a, the sleeve 14 is provided with outer ribs 14e provided to engage in corresponding notches 32e made on the inner radial surface of the ring 32. In this way, in the position of Figure 4, the ring 32 is immobilized in rotation about axis XX'. It is then possible to exert on part 31 of the cap 30 a couple C allowing the breakable part 33 to be broken so as to withdraw this part 31, while the ring 32 remains in position of locking of the spouts 15 and 15'.

15 The nose 3a of the syringe 3 is then introduced in the sleeve 23, as shown in Figure 5, using one or more flaps 3b provided at the level of a base sleeve 3c of the syringe 3 in order each to penetrate in a bayonet-type locking slot 14f provided near the free edge 14b of the sleeve 14. This particular construction allows an efficient locking of the syringe 3 with respect to the device 1 during the operations of transit of the liquid from the syringe towards the bottle
20 and of recovery of the preparation in the syringe.

The sleeve 12 is provided, at the level of spout 15, with an opening 18 which allows a mobile slide to form the rear part of the spout 15 and the re-entrant edge 12a of the skirt 12 during moulding. The teeth 11 may be obtained during moulding of the element 10 by slides penetrating to the bottom of the skirt 12 through the openings 13b provided in the wall 13.

25 Taking into account the geometry and location of the spouts 15, this is not possible for the teeth 11 located in the same angular sector as the spouts 15 and 15'. An opening

19 is provided in the skirt 12, below the opening 18, to allow the passage of a mobile slide for forming the corresponding tooth 11 during moulding of the device 1. Corresponding openings are, of course, provided in the angular sector corresponding to spout 15'.

5 The particular structure of the spouts 15 and 15' and their cooperation with the ring 32 guarantee an efficient locking of the plunger 20 in the transfer position of Figures 4 and 5. It will be readily understood that the number and distribution of the spouts 15, 15' or equivalent depend on a choice of design within the scope of the person skilled in the art, as a function of the desired force of locking and of the rigidity of the materials used.

10 The invention presents the particular advantage that it is adaptable to bottles packaged conventionally with a stopper and a crimped capsule 6, which allows it to be used after packaging of part of the medicines on a conventional chain.

15 The invention is applicable independently of the mode of fixing the base element 10 on the recipient 2 and, in general, it can be used in any connection device comprising a plunger mobile inside a bore of a base mounted on a recipient.

CLAIMS

1. A device for connection between a closed recipient and a container, said closed recipient comprising a neck whose opening is obdured by a stopper, said connection device comprising:

- a base adapted to be mounted on said recipient and comprising a bush forming an inner bore,

- a plunger adapted to slide in said bore, between a first position disengaged with respect to said stopper and a second, position, in which a hollow needle borne by said plunger traverses said stopper,

wherein said base is provided with at least one elastic catch deformable outward of said bush, said catch projecting from said bush towards the interior of the bore for retaining the plunger in the second position and being adapted to be driven radially outwardly of said bush and substantially external of the bore by an outer radial tab of said plunger, during the movement of said plunger between the first position and the second position, and to lock said tab and said plunger in said second position.

2. The device of Claim 1, wherein said catch is provided, on an outer radial face, with a heel adapted to cooperate with a ring for locking said plunger in position of retention, said ring being adapted to slide around said bush.

3. The device of Claim 2, wherein said ring is provided with an outer radial flange for locking in translation in a position of cooperation with said catch.

4. The device according to one of the preceding Claims, wherein the device comprises means for locking said plunger in rotation about a central axis of said bore.

5. The device according to Claim 4, wherein said means for locking in rotation comprise longitudinal ribs made on at least one of the inner face

and of the outer face of said bush and adapted to cooperate with corresponding elements in relief provided on the outer radial surface of said plunger or on the inner radial surface of a ring.

6. The device according to one of the preceding Claims, wherein, in said disengaged position with respect to said stopper, said plunger is connected with said bush by at least one breakable tongue.

7. The device according to one of the preceding Claims, wherein said base and said plunger are formed in one piece by injection of plastics material.

8. The device according to one of the preceding Claims, wherein the device comprises a cap for protecting said bore and said plunger, said cap being provided, on an inner face, with a member for transmitting a thrust effort for the displacement of said plunger from said first position towards said second position.

9. The device according to one of the preceding Claims, wherein said bush comprises, near its free edge, means for locking said container with bayonet-type locking slots adapted to cooperate with at least one tab of said container.

10. The device according to one of the preceding Claims, wherein said base comprises a skirt which extends around said neck of said recipient and bears hooking teeth, said skirt comprising at least one opening for access to at least of one said catch or to at least one hooking teeth from the outside.

11. A ready-to-use assembly comprising a closed recipient containing a product, in particular a pharmaceutical preparation, said recipient being provided with a neck whose opening is obdured by a stopper, and the connection device according to one of the preceding Claims, mounted on said recipient.

12. The device according to any one of the preceding Claims, wherein the device comprises means for locking a ring with respect to the bush in rotation about a central axis of said bore.

13. The device of Claim 12, wherein said means for locking in rotation comprise longitudinal ribs made on at least one of the inner face and outer face of said bush and adapted to cooperate with corresponding elements in relief provided on the outer radial surface of said plunger or on the inner radial surface of said ring.

DEVICE FOR CONNECTION BETWEEN A RECIPIENT
AND A CONTAINER AND READY-TO-USE ASSEMBLY
COMPRISING SUCH A DEVICE

- 5 The invention concerns a device comprising a base plate (10) mounted on the container (2) and a sleeve (14) forming an inner bore (A), and a plunger capable of sliding in said bore (A), between a first released position relatively to the cap (5) of the container (2) and a second position called transfer position, wherein a hollow needle (21) borne by the plunger (20) passes through the cap (5). The base plate (10) is provided with at least an elastic spout
- 10 (15) retaining the plunger (20) in transfer position, said spout projecting, from the sleeve (14), towards the bore (A) inside and capable of co-operating with an outer radial flap (24) of the plunger (20).