

BLOCKCHAIN-BASED PRIVACY TRANSACTION AND BLOCKCHAIN-BASED PRIVACY TRANSACTION APPLICATION METHODS AND APPARATUSES

TECHNICAL FIELD

5 **[0001]** The present specification relates to the field of data processing technologies, and in particular, to blockchain-based privacy transactions and blockchain-based privacy transaction application methods and apparatuses.

BACKGROUND

10 **[0002]** The blockchain technology, also referred to as the distributed ledger technology, is an emerging technology that several computing devices participate in "bookkeeping" to jointly maintain a complete distributed database. The blockchain technology has been widely used in many fields because the blockchain technology has features of decentralization and transparency, each computing device can participate in database recording, and data can be quickly synchronized between the
15 computing devices.

[0003] However, in a current mainstream blockchain architecture, all nodes store the same data. In some actual scenarios, a blockchain node participant does not want its data to be obtained by another node.

SUMMARY

20 **[0004]** For the previously described situation and problem in a blockchain data processing procedure, according to a first aspect of some embodiments of the present specification, a blockchain-based privacy transaction method is provided and is applied to a node device of a trusted user. The trusted user is determined by a trust setting transaction stored in a distributed database of a blockchain, and the trust
25 setting transaction includes identifiers of all trusted users corresponding to a blockchain user of the blockchain. The method includes the following: the first message sent by the blockchain user is received, where the first message includes privacy-unprotected first data information; and privacy-protected second data

information; the privacy-unprotected first data information is converted into the privacy-protected second data information; the first data information is stored in a local database of the node device of the trusted user; and a second transaction is sent to the blockchain, where the second transaction includes the second data information, so that the second transaction is recorded in the distributed database of the blockchain after being verified.

[0005] According to a second aspect of some embodiments of the present specification, a blockchain-based privacy transaction application method is provided, including the following: a second transaction sent by a node device of a trusted user is obtained from a distributed database of the blockchain, the second transaction includes privacy-protected second data information, where the trusted user is determined by a trust setting transaction stored in the distributed database of the blockchain, and the trust setting transaction includes identifiers of all trusted users corresponding to a blockchain user; privacy-unprotected first data information sent by the node device of the trusted user is received, where the first data information is stored in a local database of the node device of the trusted user; and whether the privacy-protected second data information is converted from the privacy-unprotected first data information is verified, and if yes, application logic is executed on the second transaction.

[0006] According to a third aspect of some embodiments of the present specification, a blockchain-based privacy transaction apparatus is provided and is applied to a node device of a trusted user, where the trusted user is determined by a trust setting transaction stored in a distributed database of the blockchain, and the trust setting transaction includes identifiers of all trusted users corresponding to a blockchain user. The apparatus includes: a receiving unit, configured to receive a first message sent by the blockchain user, where the first message includes privacy-unprotected first data information; a conversion unit, configured to convert the privacy-unprotected first data information into privacy-protected second data information; a storage unit, configured to store the first data information in a local database of the node device of the trusted user; and a sending unit, configured to send a second transaction to the blockchain, where the second transaction includes the second data information, so that the second transaction is recorded in the distributed database of the blockchain after being verified.

[0007] According to a fourth aspect of some embodiments of the present specification, a blockchain-based privacy transaction application apparatus is provided, including: an obtaining unit, configured to obtain a second transaction sent by a node device of a trusted user from a distributed database of the blockchain, the
5 second transaction includes privacy-protected second data information, where the trusted user is determined by a trust setting transaction stored in the distributed database of the blockchain, and the trust setting transaction includes identifiers of all trusted users corresponding to a blockchain user; a receiving unit, configured to receive privacy-unprotected first data information sent by the node device of the
10 trusted user, where the first data information is stored in a local database of the node device of the trusted user; a verification unit, configured to verify whether the privacy-protected second data information is converted from the privacy-unprotected first data information; and an application unit, configured to execute application logic on the second transaction.

15 [0008] The present specification further provides a computer device, including a memory and a processor, where the memory stores a computer program that can be run by the processor, and when the processor runs the computer program, executing the above steps of the blockchain-based privacy transaction method.

[0009] The present specification further provides a computer device, including a
20 memory and a processor, where the memory stores a computer program that can be run by the processor, and when the processor runs the computer program, executing the above steps of the blockchain-based privacy transaction application method.

[0010] It can be seen from the previous technical solutions that in the blockchain-based privacy transaction methods and apparatuses, a user sets the trusted
25 user on the blockchain using the trust setting transaction, and publishes to the trusted user the first data information whose privacy the user wants to protect, and the trusted user uploads the privacy-protected second data information converted from the first data information to the distributed database of the blockchain, so that consensus verification is performed on the privacy-protected second data information on the
30 blockchain. The application of the privacy transaction methods provided in the present specification can not only protect the privacy of the first data information whose privacy was not protected by the user, and prevent any other nodes on the blockchain from obtaining the first data information, but also store and protect on the blockchain the second data information converted from the first data information data.

When any node needs to use or verify the second data information in the future, the node can obtain the first data information from the trusted node set by the user, and verify a mapping relationship between the first data information and the second data information. Therefore, not only the second data information stored in the blockchain is verified, but also the original of the first data information can be obtained and be used.

[0011] In the previous technical solutions provided in the present specification, based on a distributed database storage mechanism of the blockchain technology, the second data information of the user is recorded in all nodes in a decentralized way, jointly maintained by nodes of all participants, and is synchronized in real time. All records are traceable. In addition, based on a consensus protocol of the blockchain, the second data information provided by each user cannot be tampered after being provided, thereby ensuring authenticity and security of the second data information of the user. Based on trust of the trusted user, when the first data information corresponding to the second data information is used, the trusted user provides the original of the first data information, thereby ensuring authenticity, security, and accuracy of the first data information.

BRIEF DESCRIPTION OF DRAWINGS

[0012] FIG. 1 is a flowchart illustrating a blockchain-based privacy transaction method performed by a node device of a trusted user, according to some example embodiments of the present specification;

[0013] FIG. 2 is a flowchart illustrating transmission of a privacy-unprotected message by a node device of a trusted user to a node device of another trusted user, according to some example embodiments of the present specification;

[0014] FIG. 3 is a flowchart illustrating a privacy-protected transaction application method performed by any node device on a blockchain, according to some example embodiments of the present specification;

[0015] FIG. 4 is a flowchart illustrating a blockchain-based privacy transaction method and a privacy-protected transaction application method, according to other embodiments of the present specification;

[0016] FIG. 5 is a schematic diagram illustrating a blockchain-based privacy transaction apparatus, according to some embodiments of the present specification;

[0017] FIG. 6 is a schematic diagram illustrating a blockchain-based privacy transaction application apparatus, according to some embodiments of the present specification; and

[0018] FIG. 7 is a structural diagram of hardware running some embodiments of a blockchain-based privacy transaction apparatus or a privacy transaction application apparatus, according to the present specification.

DESCRIPTION OF IMPLEMENTATIONS

[0019] Example embodiments are described in detail here, and the example embodiments are presented in the accompanying drawings. When the following description relates to the accompanying drawings, unless specified otherwise, same numbers in different accompanying drawings represent same or similar elements. Implementations described in the following example embodiments do not represent all implementations consistent with one or more embodiments of the present specification. On the contrary, the implementations are only examples of apparatus and methods that are described in the appended claims in detail and consistent with some aspects of one or more embodiments of the present specification.

[0020] It is worthwhile to note that steps of a corresponding method are not necessarily performed in a sequence shown and described in the present specification in another embodiment. In some other embodiments, the method can include steps more or less than those described in the present specification. In addition, a single step described in the present specification can be divided into a plurality of steps in another embodiment for description. However, the plurality of steps described in the present specification can also be combined into a single step for description in another embodiment.

[0021] As shown in FIG. 1, an example embodiment of the present specification provides a blockchain-based privacy transaction method. The blockchain described in some embodiments can be a P2P network system that has a distributed data storage structure and that is formed by all node devices using a consensus protocol. Data in the blockchain is distributed in a time-connected "block". A later block includes a data digest of a previous block, and replicates of all the data of all or some of the node devices are based on a specific consensus protocol (for example, PoW, PoS, DPOS, or PBFT, etc.). A person skilled in the art knows that because a blockchain system runs

under a corresponding consensus protocol, data recorded in a blockchain database is difficult to be tampered with by any node device. For example, a blockchain using PoW consensus protocol requires a network-wide attack to have computational power of at least 51 percent of the hash rate of the blockchain in order for the attack to tamper with existing data of the blockchain. Therefore, a blockchain system has features that other centralized database systems cannot achieve: data security assurance, and attack and tampering prevention.

[0022] A transaction described in the present specification is a piece of data that is created by a user using a node device on a blockchain and that is ultimately needed to be published to a distributed database of the blockchain. Transactions in the blockchain are divided into a transaction in a narrow sense and a transfer in a broad sense. A transaction in a narrow sense is a value transfer published by a user to the blockchain. For example, in a traditional bitcoin blockchain network, a transaction can be a fund transfer initiated by the user in the blockchain. The transaction in a broad sense is any piece of data published by the user to the blockchain: For example, an operator can establish a consortium blockchain based on actual service needs, and deploy, based on the consortium blockchain, some other types of online services (for example, a house renting service, a vehicle scheduling service, an insurance claim service, a credit service, and a medical service) that are unrelated to a value transfer. In such a consortium blockchain, the transaction can be a service message or a service request that is published by the user in the consortium blockchain and that has a service intention. As another example, in a ledger-type blockchain, the transaction can be data (such as an account balance) sent by the user to the blockchain to change an account status of the user. Therefore, any data published by the user to the distributed database of the blockchain, regardless of whether the data is stored in a block body, a block header, or another location in a block, shall belong to the "transaction" described in the present invention.

[0023] In addition, it is worthwhile to note that the node device described in the present specification can include not only a full node device that stores all the data in the distributed database of the blockchain, but also a light node device that stores part of the data in the distributed database of the blockchain, and other terminal devices or client devices. This is not limited in the present specification.

[0024] The blockchain-based privacy transaction method shown in FIG. 1 is applied to a node device of a trusted user. The trusted user is determined by a trust

setting transaction stored in the distributed database of the blockchain, and the trust setting transaction includes identifiers of all trusted users determined by a blockchain user, such as an account address of the trusted user, a public key of the trusted user, or an account name of the trusted user, etc, that can uniquely determine information about the trusted user. The blockchain user can select and set a trusted user corresponding to the blockchain user based on trust of the blockchain user to another user, for example, can select a financial institution with a relatively high credit, an authentication institution, a supervisor institution user, or another institution. The trust setting transaction can be directly published by the blockchain user to the blockchain, or can be published by having the blockchain user invoke a smart contract declaring logic that sets the trusted user. This is not limited here.

[0025] The method shown in FIG. 1 includes: Step 102: Receive a first message sent by the blockchain user, where the first message includes privacy-unprotected first data information.

[0026] The first message sent by the blockchain user in step 102 is received by the node device of the trusted user that communicates with the blockchain user through an off-chain channel. The off-chain channel means that a transaction is not sent to the distributed database of the blockchain, but a network communication method such as private point-to-point communication or a method using other relay nodes. It is worthwhile to note that the first message can have a same data content format as that of the transaction published to the blockchain, and is referred to here as "message" instead of "transaction" because the first message is not sent to the distributed database of the blockchain, but sent through the off-chain channel. The privacy-unprotected first data information means that the first data information is the original whose privacy is not protected or encrypted.

[0027] Step 104: Convert the privacy-unprotected first data information into privacy-protected second data information.

[0028] The privacy-protected second data information is converted from the privacy-unprotected first data information. A specific data conversion rule can be set by the underlying protocol of the blockchain, or can be set by the trusted user. The conversion process can be encrypting or performing coding operation on the first data information to obtain the second data information. In some illustrated implementations, the second data information can be a hash digest of the first data

information to ensure that the second data information can uniquely correspond to the first data information.

[0029] Step 106: Store the first data information in a local database of the node device of the trusted user.

5 **[0030]** The local database of the node device of the trusted user is different from the distributed database of the node device of the trusted user on the blockchain. The first data information stored in the local database of the node device cannot be obtained by another node device on the blockchain, thereby ensuring privacy of the first data information.

10 **[0031]** In another illustrated embodiment, a verification rule can be further predetermined to ensure validity of content included in the first message, so that the node device of the trusted user verifies the first message, and stores the first data information in the local database of the node device of the trusted user after verification specified in the predetermined verification rule succeeds. For example,
15 when the first message includes a first digital signature made by the blockchain user at least for the privacy-unprotected first data information, the predetermined verification rule can at least include: verifying that the first digital signature is made by the blockchain user at least for the privacy-unprotected first data information, so as to prevent another user from impersonating the blockchain user to tamper with the
20 first data information.

[0032] Step 108: Send a second transaction to the blockchain, where the second transaction includes the second data information, so that the second transaction is recorded in the distributed database of the blockchain after being verified by a node device having consensus authority on the blockchain.

25 **[0033]** Any node device on the blockchain can obtain the second data information in the second transaction by accessing the distributed database of the blockchain. Because the second data information is in a privacy protection state, except the blockchain user sending the first message and the trusted user trusted by the blockchain user, no other user on the blockchain can obtain the first data information
30 corresponding to the second data information, thereby effectively protecting privacy of the first data information.

[0034] A detailed process of recording the second transaction in the distributed database of the blockchain can be specifically set based on the consensus protocol of the blockchain and the verification rule. In some illustrated implementations, a

specific step of recording the second transaction in the distributed database of the blockchain can include the following steps:

[0035] A node device having bookkeeping authority on the blockchain adds the second transaction to a candidate block.

5 **[0036]** A consensus node device having bookkeeping authority satisfying the blockchain consensus mechanism is determined from the node device having bookkeeping authority.

[0037] The consensus node device having bookkeeping authority broadcasts the candidate block to the node device of the blockchain.

10 **[0038]** The candidate block is considered as the latest block and added to the distributed database of the blockchain after the candidate block is verified and approved by a predetermined quantity of node devices on the blockchain.

[0039] In the previous embodiments, the node device having bookkeeping authority is a node device having authority to generate the candidate block, and can
15 include a node device having users with a relatively high credit and other node devices on the blockchain. The consensus node device having bookkeeping authority can be determined from the node devices having bookkeeping authority on the candidate block based on the consensus protocol of the blockchain. The consensus protocol can include the Proof of Work protocol (PoW), the Proof of Stake protocol
20 (PoS), the delegated proof of stake protocol (DPoS), or PBFT usually used by the consortium blockchain, etc.

[0040] Verification of the second transaction can usually include verification of a data content format of the second transaction, verification of all or a part of content of the second transaction, or verification of a digital signature included in the second
25 transaction, etc. In some illustrated embodiments, to ensure that the node device of the trusted user sending the second transaction belongs to the trusted user set by the blockchain user, the node device on the blockchain should verify whether an identifier of the trusted user is included in the trust setting transaction initiated by the blockchain user; if yes, it indicates that an initiating user of the second transaction is a
30 valid initiating user.

[0041] In other illustrated embodiments, to prevent any other node device from initiating the second transaction by impersonating the node device of the trusted user, the second transaction further includes a second digital signature made by the trusted user at least for the privacy-protected second data information. To reflect and prove

that the second data information included in the second transaction is originally generated by the node device of the blockchain user, the second transaction can further include the first digital signature that is included in the first message and that is made by the blockchain user at least for the privacy-unprotected first data information. Correspondingly, verification of the second transaction by the node device on the blockchain should include at least verification of the second digital signature based on the public key of the trusted user, so as to record the second transaction in the distributed database of the blockchain after the verification succeeds.

10 **[0042]** The blockchain user can set a plurality of trusted users when setting the trusted user. The blockchain user can select a trusted user from the plurality of trusted users and send the first message to the trusted user. Correspondingly, in addition to completing the blockchain-based privacy transaction method described in steps 102 to 108 in the previous embodiments, the trusted user should further transmit the first message sent by the blockchain user to node devices of other trusted users, so that the other trusted users store the privacy-unprotected first data information included in the first message in local databases of the node devices of the other trusted users. Specifically, as shown in FIG. 2, the step of transmitting the first message sent by the blockchain user to the node devices of other trusted users can include the following steps:

20 **[0043]** Step 202: Obtain the trust setting transaction from the distributed database of the blockchain.

[0044] Step 204: Determine other trusted users trusted by the blockchain user based on the trust setting transaction.

25 **[0045]** Step 206: Transmit, using an off-chain method, the privacy-unprotected first data information and the privacy-protected second data information to the node devices of the other trusted users trusted by the user, so that the first data information is stored in the local databases of the node devices of the other trusted users after it is verified that the first data information is converted from the second data information.

30 **[0046]** As described in the previous embodiments, the trust setting transaction includes identifiers of all trusted users determined by the blockchain user, such as account addresses of the trusted users, public keys of the trusted users, or account names of the trusted users that can uniquely determine information about the trusted

users. Therefore, all the other trusted users can be determined based on the trust setting transaction.

[0047] To prevent the first data information from losing privacy after being obtained by any node device on the blockchain, the node device of the trusted user
5 transmits the first data information obtained by the node device to the node devices of the other trusted users through off-chain channels. To help other trusted users verify whether the second data information corresponds to the first data information, the node device of the trusted user should also transmit, through off-chain channels, the second data information converted by the trusted user to the node devices of the other
10 trusted users. The off-chain transmission method includes but is not limited to a form of off-chain point-to-point communication, broadcast, etc.

[0048] Likewise, the node device of the another trusted user can also verify the first data information based on a predetermined verification rule, so as to store the first data information in a local database of the node device of the another trusted user
15 after the verification succeeds. The predetermined verification rule includes verifying that the privacy-protected second data information is converted from the privacy-unprotected first data information. When the trusted user further sends the first digital signature or the second digital signature described in the previous embodiment to other trusted users using an off-chain method, the other trusted users
20 should verify that the first digital signature is made by the blockchain user at least for the privacy-unprotected first data information, or verify that the second digital signature is made by the trusted user at least for the privacy-protected second data information, etc. Details are omitted here for simplicity.

[0049] It is worthwhile to note that after node devices of other trusted users
25 receive the first data information and the second data information, the node devices of the other trusted users can transmit, to the trusted user, a reply such as "information receiving completion", "verification succeeds", or "agree to store the first data information". In other illustrated implementations, the node devices of other trusted users send to the trusted user respective digital signatures made by the other trusted
30 users at least for the privacy-protected second data information. The respective digital signatures can be used to provide to the trusted user, an indication indicating that respective verification of the first message by the node device of each of the other trusted users succeeds, or a prompt indicating that the first data information is stored in the respective node device of the respective trusted user of the other trusted users.

In addition, the node device of the trusted user can further record all the digital signatures in the second transaction published by the node device of the trusted user to the distributed database of the blockchain. These digital signatures recorded in the second transaction can be used, together with a fourth digital signature made by the node device of the trusted user, to support validity verification of the second data information included in the second transaction by any other node devices on the blockchain.

[0050] The previous embodiments provided in the present specification provides the blockchain-based privacy transaction method executed by the node device of the trusted user. By storing the privacy-unprotected first data information in the local database of the node device of the trusted user, the node device of the trusted user sends the privacy-protected second data information to the distributed database of the blockchain, so that the node devices of the blockchain can store the privacy-protected second data information, thereby protecting privacy of the first data information.

[0051] Correspondingly, the present specification further provides a blockchain-based privacy transaction application method. As shown in FIG. 3, any node device on the blockchain can perform the following steps when the node device needs to apply the second transaction.

[0052] Step 302: Obtain a second transaction sent by a node device of a trusted user from a distributed database of the blockchain, the second transaction includes privacy-protected second data information, where the trusted user is determined by a trust setting transaction stored in the distributed database of the blockchain, and the trust setting transaction includes identifiers of all the trusted users corresponding to a blockchain user.

[0053] Step 304: Receive privacy-unprotected first data information sent by the node device of the trusted user, where the first data information is stored in a local database of the node device of the trusted user. Any node device on the blockchain can obtain, through off-chain communication with the node device of the trusted user sending the second transaction, the first data information stored in the local database by the node device of the trusted user.

[0054] Step 306: Verify whether the privacy-protected second data information is converted from the privacy-unprotected first data information.

[0055] If yes,

[0056] Step 308: Execute application logic on the second transaction.

[0057] The method for setting the trust setting transaction, the rule or method for conversion between the first data information and the second data information, the method for selecting the trusted user, etc. are described in the plurality of embodiments of the blockchain-based privacy transaction method. Details are omitted
5 here for simplicity. The application logic on the second transaction includes obtaining privacy-unprotected first data information corresponding to the privacy-protected second data information in the second transaction, or a data application or service application developed based on the first data information. The application can include a data application off the blockchain, or can include a data application on the
10 blockchain, for example, publishing a transaction based on the first data information. This is not limited in the present specification.

[0058] Compared with a general transaction of setting parameter state or publishing privacy-protected data information, a transfer transaction in the blockchain includes some special steps because it involves changes associated with account
15 balance statuses of at least two users. The following describes in detail the privacy transaction method provided in the present specification using an example that blockchain user A sends a transfer transaction to blockchain user B. Considering privacy security of an account of blockchain user A, blockchain user A coordinates with its trusted user SA to set a balance (assume that the balance is 100) in its account
20 status to a privacy-protected state (for example, a hash digest value (100) corresponding to the balance 100) using the method described in some previous embodiments.

[0059] As shown in FIG. 4, a process of setting the balance 100 in the account status of blockchain user A to hash (100) can include the following steps:

25 **[0060]** Step 401: A node device of blockchain user A sends a trust setting transaction to a distributed database of a blockchain, and sets user SA as a trusted user of blockchain user A.

[0061] Step 402: The node device of blockchain user A sends a first message to a node device of trusted user SA through an off-chain channel, where the first message
30 can include first data information—balance 100, and a digital signature Sign 1 made by user A for the first data information.

[0062] Step 403: A node device of trusted user SA converts the first data information—balance 100 into second data information—privacy-protected balance hash (100) based on a data conversion rule, and verifies Sign 1.

[0063] Step 404: After the verification described in step 403 succeeds, the node device of trusted user SA stores the first data information—balance 100 included in the first message in a local database. Optionally, the node device of trusted user SA can set a mapping table in the local database to record the first data information and the
5 second data information.

[0064] Step 405: The node device of trusted user SA makes a digital signature Sign 2 on the verified second data information.

[0065] Step 406: The node device of trusted user SA sends a second transaction to the blockchain, where the second transaction includes the second data information—
10 protected balance hash (100), the digital signature Sign1 made by user A for the first data information, and the digital signature Sign 2 made by user SA for the second data information.

[0066] Step 407: A consensus node on the blockchain verify the second transaction based on a consensus protocol of the blockchain, where the verification
15 includes verifying whether user SA belongs to a trusted user determined by user A using the trust setting transaction, and verifying that digital signatures included in the second transaction are respectively made by user A and trusted user SA determined by user A.

[0067] Step 408: After the verification described in step 407 succeeds, the
20 consensus node (a node having consensus authority) on the blockchain records a block including the second transaction in the distributed database of the blockchain, and all nodes on the blockchain update a balance status of user A to hash (100) in their databases.

[0068] Likewise, user B can also protect balance status privacy in an account of
25 user B. A specific method can be similar to steps 401 to 408, and details are omitted here for simplicity.

[0069] It is worthwhile to note that when the privacy transaction method provided in the present specification is a privacy transfer transaction, to ensure that an account balance of a transferor and an account balance of a transferee can be verified by the
30 node device of the trusted user, and a corresponding balance correspondingly changes, the transferor and the transferee should trust at least one trusted user trusted by both the transferor and the transferee, that is, the trust setting transaction sent by the transferor and the trust setting transaction sent by the transferee should include at least one identifier of at least one trusted user trusted by both the transferor and the

transferee. In some embodiments, trusted user SA is both a trusted user of user A and a trusted user of user B.

[0070] A process that user A completes a transfer to user B can specifically include the following steps:

5 **[0071]** Step 409: The node device of user A sends, to the node device of trusted user SA trusted by both user A and user B, a transaction message Txab indicating a transfer from user A to user B. The transaction message Txab includes account identifiers (account addresses or public keys) of user A and user B, a transfer amount 10, and a digital signature Sign (10) made by user A for the transfer amount 10.

10 **[0072]** Step 410: The node device of trusted user SA converts the transfer amount 10 into a hash digest hash (10) based on a data conversion rule, verify whether an account balance 100 of user A is sufficient to pay the current transfer, and verify Sign (10).

[0073] Step 411: After the verification described in step 410 succeeds, the node
15 device of trusted user SA stores the transfer amount 10 in the transfer message in the local database. Based on the current transfer, the node device of trusted user SA should further change the account balances of user A and user B in the local database.

[0074] Step 412: The node device of trusted user SA makes a digital signature Sign 2 (hash (10)) for the verified privacy-protected transfer amount hash (10), makes
20 digital signatures Sign (hash (account A)) and Sign (hash (account B)) for hash digests hash (account A) and hash (account B) generated for the account balances of user A and user B after the transfer is completed.

[0075] Step 413: The node device of trusted user SA sends the second transaction to the blockchain, where the second transaction includes the privacy-protected transfer
25 amount hash (10), the new hash digests hash (account A) and hash (account B) generated for the account balances of user A and user B after the transfer is completed, the digital signature Sign 1 (10) made by user A for the transfer amount 10, and the digital signature Sign 2 (hash (10)), Sign (hash (account A)), and Sign (hash (account B)) of user SA.

30 **[0076]** Step 414: The consensus node on the blockchain verifies the second transaction based on the consensus protocol of the blockchain. The verification includes verifying whether user SA is a trusted user determined by user A and user B using the trust setting transaction, verifying that the digital signature Sign 2 (hash (10)) included in the second transaction is a hash digest hash (10) made by trusted user SA

determined by user A for the hash digest hash (10) of the transfer amount, and the digital signatures Sign (hash (account A)) and Sign (hash (account B)) of user SA are the hash digests hash (account A) and hash (account B) respectively made by the user SA for the new account balances of user A and user B.

5 **[0077]** Step 415: After the verification described in step 414 succeeds, the consensus node (a node having consensus authority) on the blockchain records a block including the second transaction in the distributed database of the blockchain, and all nodes on the blockchain update a balance status of user A to hash (account A) and a balance status of user B to hash (account B) in their databases.

10 **[0078]** Optionally, to ensure that update made by the node device of trusted user SA to the account balances of the user A and the user B after the transfer is performed is approved by user A and user B, user A and user B can separately send their updated account balances and the digital signature based on the updated account balances to the node device of trusted user SA. The previous specific process is similar to a
15 process in some embodiments of the present specification that the trusted user selected by the user stores the privacy-protected second data information of the user in the distributed database of the blockchain, and details are omitted here for simplicity.

[0079] To correspond to the previous process, some embodiments of the present specification further provide a blockchain-based privacy transaction apparatus and a
20 blockchain-based privacy transaction application apparatus. The apparatus can be implemented using software, or can be implemented using hardware or a combination of software and hardware. A software implementation is used as an example. As a logical apparatus, a corresponding computer program instruction is read into a memory for running using a central processing unit (CPU) of a device the apparatus is
25 in. In terms of hardware, in addition to the CPU, the memory, and the storage shown in FIG. 7, a device that a network risk service implementation apparatus is in usually further includes other hardware such as a chip used to receive and send a wireless signal, and/or other hardware such as a board used to implement a network communication function.

30 **[0080]** FIG. 5 is a blockchain-based privacy transaction apparatus 50, applied to a node device of a trusted user. The trusted user is determined by a trust setting transaction stored in a distributed database of the blockchain, and the trust setting transaction includes identifiers of all trusted users corresponding to a blockchain user. The apparatus 50 includes:

a receiving unit 502, configured to receive a first message sent by the blockchain user, where the first message includes privacy-unprotected first data information;
a conversion unit 504, configured to convert the privacy-unprotected first data information into privacy-protected second data information;
5 a storage unit 506, configured to store the first data information in a local database of the node device of the trusted user; and
a sending unit 508, configured to send a second transaction to the blockchain, where the second transaction includes the second data information, so that the second transaction is recorded in the distributed database of the blockchain after being
10 verified.

[0081] In other implementations, the first message includes a first digital signature made by the blockchain user at least for the privacy-unprotected first data information.

[0082] The apparatus 50 further includes a verification unit 510, configured to
15 verify the first message based on a predetermined verification rule so as to store the first data information in the local database of the node device of the trusted user after the verification succeeds, where the predetermined verification rule further includes verifying that the first digital signature is made by the blockchain user at least for the privacy-unprotected first data information.

20 **[0083]** In other implementations, the second transaction further includes a second digital signature made by the trusted user at least for the privacy-protected second data information and the first digital signature made by the blockchain user at least for the privacy-unprotected first data information.

[0084] In other shown implementations, the apparatus 50 further includes:
25 an obtaining unit 512, configured to obtain the trust setting transaction from the distributed database of the blockchain;
a determining unit 514, configured to determine other trusted users trusted by the blockchain user based on the trust setting transaction; and
a transmission unit 516, configured to transmit, in an off-chain method, the
30 privacy-unprotected first data information and the privacy-protected second data information to node devices of the other trusted users trusted by the blockchain user, so that the first data information is stored in the local databases of the node devices of the other trusted users after it is verified that the first data information is converted from the second data information.

[0085] In other shown implementations, the receiving unit 502 is configured to receive a digital signature made by the another trusted user at least based on the second data information.

[0086] The second transaction further includes the digital signature made by the another trusted user at least based on the second data information.

[0087] In other shown implementations, the privacy-protected second data information is a data digest of the privacy-unprotected first data information.

[0088] In other shown implementations, the first message includes a transfer amount of the blockchain user to another blockchain user, and the second transaction includes the privacy-protected transfer amount and privacy-protected account balances of the blockchain user and the another blockchain user.

[0089] The trusted user is also a trusted user corresponding to the another blockchain user in the trust setting transaction.

[0090] FIG. 6 shows an application apparatus 60 for a blockchain-based privacy transaction, according to the present specification, including:

an obtaining unit 602, configured to obtain a second transaction sent by a node device of a trusted user from a distributed database of the blockchain, the second transaction includes privacy-protected second data information, where the trusted user is determined by a trust setting transaction stored in the distributed database of the blockchain, and the trust setting transaction includes identifiers of all trusted users corresponding to a blockchain user;

a receiving unit 604, configured to receive privacy-unprotected first data information sent by the node device of the trusted user, where the first data information is stored in a local database of the node device of the trusted user;

a verification unit 606, configured to verify whether the privacy-protected second data information is converted from the privacy-unprotected first data information; and

an application unit 608, configured to execute application logic on the second transaction.

[0091] For an implementation process of functions and roles of each unit in the apparatus, references can be made to an implementation process of corresponding steps in the previous method. For related parts, reference can be made to partial descriptions in the method embodiments. Details are omitted here.

[0092] The previously described apparatus embodiments are merely examples. The units described as separate parts can or cannot be physically separate, and parts

displayed as units can or cannot be physical modules, can be located in one position, or can be distributed on a plurality of network modules. Some or all of the units or modules can be selected based on actual needs to achieve the objectives of the solutions of the present specification. A person of ordinary skill in the art can
5 understand and implement some embodiments of the present specification without creative efforts.

[0093] The apparatus, unit, or module illustrated in the previous embodiments can be implemented using a computer chip or an entity, or can be implemented using a product having a certain function. A typical implementation device is a computer,
10 and the computer can be a personal computer, a laptop computer, a cellular phone, a camera phone, a smartphone, a personal digital assistant, a media player, a navigation device, an email receiving and sending device, a game console, a tablet computer, a wearable device, or any combination of these devices.

[0094] Corresponding to the previous method embodiments, some embodiments
15 of the present specification further provide a computer device, and the computer device includes a memory and a processor. The memory stores a computer program that can be run by the processor. The processor performs steps of the blockchain-based privacy transaction method in some embodiments of the present specification when running the stored computer program. For detailed descriptions of
20 the steps of the blockchain-based privacy transaction method, reference can be made to the previous content. Details are not described here.

[0095] Corresponding to the previous method embodiments, some embodiments of the present specification further provide a computer device, and the computer device includes a memory and a processor. The memory stores a computer program
25 that can be run by the processor. The processor performs steps of the blockchain-based privacy transaction application method in some embodiments of the present specification when running the stored computer program. For detailed descriptions of the steps of the blockchain-based privacy transaction application method, reference can be made to the previous content. Details are not described here.

[0096] The previous descriptions are merely preferred embodiments of the
30 present specification, but are not intended to limit the present specification. Any modification, equivalent replacement, or improvement made without departing from the spirit and principle of the present specification shall fall within the protection scope of the present specification.

[0097] In a typical configuration, a computing device includes one or more processors (CPU), an input/output interface, a network interface, and a memory.

[0098] The memory can include a non-persistent memory, a random access memory (RAM), a non-volatile memory, and/or another form that are in a computer readable medium, for example, a read-only memory (ROM) or a flash memory (flash RAM). The memory is an example of the computer readable medium.

[0099] The computer readable medium includes permanent, non-permanent, movable, and unmovable media that can store information using any method or technology. The information can be a computer readable instruction, a data structure, a program module, or other data.

[0100] Examples of the computer storage medium include but are not limited to a phase change random access memory (PRAM), a static random access memory (SRAM), a dynamic random access memory (DRAM), a random access memory of another type (RAM), a read-only memory (ROM), an electrically erasable programmable read-only memory (EEPROM), a flash memory or another memory technology, a compact disc read-only memory (CD-ROM), a digital versatile disc (DVD) or another optical storage, a cassette, a cassette magnetic disk storage or another magnetic storage device, or any other non-transmission medium. The computer storage medium can be configured to store information that can be accessed by a computing device. Based on the definition in the present specification, the computer readable medium does not include transitory media such as a modulated data signal and carrier.

[0101] It is worthwhile to further note that, the terms "include", "contain", or their any other variants are intended to cover a non-exclusive inclusion, so that a process, a method, a product, or a device that includes a list of elements not only includes those elements but also includes other elements not expressly listed, or further includes elements inherent to such process, method, product or device. Without more constraints, an element preceded by "includes a ..." does not preclude the existence of additional identical elements in the process, method, product or device that includes the element.

[0102] A person skilled in the art should understand that an embodiment of the present specification can be provided as a method, a system, or a computer program product. Therefore, some embodiments of the present specification can use a form of hardware only embodiments, software only embodiments, or embodiments with a

combination of software and hardware. Moreover, some embodiments of the present specification can use a form of a computer program product that is implemented on one or more computer-usable storage media (including but not limited to a disk memory, a CD-ROM, an optical memory, etc.) that include computer-usable program

5 code.

CLAIMS

What is claimed is:

1. A blockchain-based privacy transaction method, applied to a node device of a trusted user, wherein the trusted user is determined by a trust setting transaction stored in a distributed database of the blockchain, and the trust setting transaction comprises
5 identifiers of all trusted users corresponding to a blockchain user; and the method comprises:

receiving a first message sent by the blockchain user, wherein the first message comprises privacy-unprotected first data information;

10 converting the privacy-unprotected first data information into privacy-protected second data information;

storing the first data information in a local database of the node device of the trusted user; and

15 sending a second transaction to the blockchain, wherein the second transaction comprises the second data information, so that the second transaction is recorded in the distributed database of the blockchain after being verified.

2. The method according to claim 1, wherein the first message comprises a first digital signature made by the blockchain user at least for the privacy-unprotected first data information; and

20 the method further comprises:

verifying the first message based on a predetermined verification rule so as to store the first data information in the local database of the node device of the trusted user after the verification succeeds, wherein the predetermined verification rule further comprises verifying that the first digital signature is made by the blockchain
25 user at least for the privacy-unprotected first data information.

3. The method according to claim 2, wherein the second transaction further comprises a second digital signature made by the trusted user at least for the privacy-protected second data information and the first digital signature made by the blockchain user at least for the privacy-unprotected first data information.

30 4. The method according to any one of claims 1 to 3, further comprising:

obtaining the trust setting transaction from the distributed database of the blockchain; and

determining another trusted user trusted by the user based on the trust setting transaction; and

transmitting, in an off-chain method, the privacy-unprotected first data information and the privacy-protected second data information to a node device of the another trusted user trusted by the user, so that the first data information is stored in a local database of the node device of the another trusted user after it is verified that the first data information is converted from the second data information.

5. The method according to claim 4, further comprising:

receiving a digital signature made by the another trusted user at least based on the second data information; wherein

the second transaction further comprises the digital signature made by the another trusted user at least based on the second data information.

6. The method according to claim 1, wherein the privacy-protected second data information is a data digest of the privacy-unprotected first data information.

7. The method according to claim 1, wherein the first message comprises a transfer amount of the blockchain user to another blockchain user, and the second transaction comprises the privacy-protected transfer amount and privacy-protected account balances of the blockchain user and the another blockchain user; and

the trusted user is also a trusted user corresponding to the another blockchain user in the trust setting transaction.

8. A blockchain-based privacy transaction application method, comprising:

obtaining a second transaction sent by a node device of a trusted user from a distributed database of the blockchain, wherein the second transaction comprises privacy-protected second data information, the trusted user is determined by a trust setting transaction stored in the distributed database of the blockchain, and the trust setting transaction comprises identifiers of all trusted users corresponding to a blockchain user;

receiving privacy-unprotected first data information sent by the node device of the trusted user, wherein the first data information is stored in a local database of the node device of the trusted user; and

verifying whether the privacy-protected second data information is converted from the privacy-unprotected first data information, and if yes, executing application logic on the second transaction.

9. A blockchain-based privacy transaction apparatus, applied to a node device of a trusted user, wherein the trusted user is determined by a trust setting transaction stored in a distributed database of the blockchain, and the trust setting transaction comprises identifiers of all trusted users corresponding to a blockchain user; and the apparatus comprises:

a receiving unit, configured to receive a first message sent by the blockchain user, wherein the first message comprises privacy-unprotected first data information;

a conversion unit, configured to convert the privacy-unprotected first data information into privacy-protected second data information;

10 a storage unit, configured to store the first data information in a local database of the node device of the trusted user; and

a sending unit, configured to send a second transaction to the blockchain, wherein the second transaction comprises the second data information, so that the second transaction is recorded in the distributed database of the blockchain after being verified.

15 10. The apparatus according to claim 9, wherein the first message comprises a first digital signature made by the blockchain user at least for the privacy-unprotected first data information; and

the apparatus further comprises a verification unit, configured to verify the first message based on a predetermined verification rule so as to store the first data information in the local database of the node device of the trusted user after the verification succeeds, wherein the predetermined verification rule further comprises verifying that the first digital signature is made by the blockchain user at least for the privacy-unprotected first data information.

25 11. The apparatus according to claim 10, wherein the second transaction further comprises a second digital signature made by the trusted user at least for the privacy-protected second data information and the first digital signature made by the blockchain user at least for the privacy-unprotected first data information.

12. The apparatus according to any one of claims 9 to 11, further comprising:

30 an obtaining unit, configured to obtain the trust setting transaction from the distributed database of the blockchain;

a determining unit, configured to determine another trusted user trusted by the user based on the trust setting transaction; and

a transmission unit, configured to transmit, in an off-chain method, the privacy-unprotected first data information and the privacy-protected second data information to a node device of the another trusted user trusted by the user, so that the first data information is stored in a local database of the node device of the another trusted user after it is verified that the first data information is converted from the second data information.

13. The apparatus according to claim 12, wherein
the receiving unit is configured to receive a digital signature made by the another trusted user at least based on the second data information; and
10 the second transaction further comprises the digital signature made by the another trusted user at least based on the second data information.

14. The apparatus according to claim 9, wherein the privacy-protected second data information is a data digest of the privacy-unprotected first data information.

15 15. The apparatus according to claim 9, wherein the first message comprises a transfer amount of the blockchain user to another blockchain user, and the second transaction comprises the privacy-protected transfer amount and privacy-protected account balances of the blockchain user and the another blockchain user; and
the trusted user is also a trusted user corresponding to the another blockchain user in the trust setting transaction.

20 16. A blockchain-based privacy transaction application apparatus, comprising:
an obtaining unit, configured to obtain a second transaction sent by a node device of a trusted user from a distributed database of the blockchain, wherein the second transaction comprises privacy-protected second data information, the trusted user is determined by a trust setting transaction stored in the distributed database of the blockchain, and the trust setting transaction comprises identifiers of all trusted users
25 corresponding to a blockchain user;

a receiving unit, configured to receive privacy-unprotected first data information sent by the node device of the trusted user, wherein the first data information is stored in a local database of the node device of the trusted user;

30 a verification unit, configured to verify whether the privacy-protected second data information is converted from the privacy-unprotected first data information; and
an application unit, configured to execute application logic on the second transaction.

17. A computer device, comprising a memory and a processor, wherein the memory stores a computer program that can be run by the processor, and the processor performs the method according to any one of claims 1 to 7 when running the computer program.

- 5 18. A computer device, comprising a memory and a processor, wherein the memory stores a computer program that can be run by the processor, and the processor performs the method according to claim 8 when running the computer program.