

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
28 April 2005 (28.04.2005)

PCT

(10) International Publication Number
WO 2005/038189 A1

(51) International Patent Classification⁷: **E21B 7/18**,
10/60, B24C 1/04, 5/04, E21B 41/00

(72) Inventor; and

(75) Inventor/Applicant (for US only): **BLANGÉ, Jan-Jette**
[NL/NL]; Kesslerpark 1, NL-2288 GS Rijswijk (NL).

(21) International Application Number:
PCT/EP2004/052593

(22) International Filing Date: 20 October 2004 (20.10.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
03103883.9 21 October 2003 (21.10.2003) EP
PCT/EP04/051407 8 July 2004 (08.07.2004) EP

(71) Applicant (for all designated States except CA,
US): **SHELL INTERNATIONALE RESEARCH
MAATSCHAPPIJ B.V.** [NL/NL]; Carel van Bylandtlaan
30, NL-2596 HR The Hague (NL).


(71) Applicant (for CA only): **SHELL CANADA LIMITED**
[CA/CA]; 400 - 4th Avenue S.W., Calgary, Alberta T2P
2H5 (CA).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

[Continued on next page]

(54) Title: NOZZLE UNIT AND METHOD FOR EXCAVATING A HOLE IN AN OBJECT



(57) Abstract: Nozzle unit (1) for generating an abrasive jet, which nozzle unit (1) comprises: a first nozzle (3) connected to a pressurized carrier fluid supply (2); a mixing chamber (5) in which the first nozzle (3) discharges; a second nozzle (6) connected to the mixing chamber (5); and an abrasive particle inlet (4) discharging in the mixing chamber (5); wherein the proportion of the cross sectional area of the first nozzle opening (A_1) and the cross sectional area of the second nozzle opening (A_2) is in a range of 0.50-1.0.



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*