

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
27 May 2004 (27.05.2004)

PCT

(10) International Publication Number
WO 2004/043674 A2

(51) International Patent Classification⁷: **B29C 45/36**

[US/US]; 17194 Toronto Avenue SE, Prior Lake, MN 55372 (US). **KRANTZ, Bradley** [US/US]; 7885 Hyacinth, Victoria, MN 55386 (US).

(21) International Application Number:
PCT/US2003/035927

(22) International Filing Date:
12 November 2003 (12.11.2003)

(74) Agents: **CHRISTENSEN, Douglas, J.** et al.; Patterson, Thunte, Skaar & Christensen, P.A., 4800 IDS Center, 80 South Eight Street, Minneapolis, MN 55402-2100 (US).

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/425,458 12 November 2002 (12.11.2002) US

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(71) Applicant (*for all designated States except US*): **ENTEGRIS, INC.** [US/US]; 3500 Lyman Boulevard, Chaska, MN 55318 (US).


(84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **STOCK, Michael**

[Continued on next page]

(54) Title: PROCESS AND APPARATUS FOR MOLDING POLYMER FITTINGS



(57) Abstract: A method and apparatus for producing molded fluoropolymer sweep elbows with straight ends while minimizing distortion of the fitting. The invention includes a mold for creating the sweep fittings of the invention. The mold includes a mold cavity block and internal coring. The internal coring includes two symmetrical cores that shut off at a 45° miter. Each of the symmetrical cores is divided into two parts, an outside sweep core and an inside sweep core. The outside sweep core and the inside sweep core are divided on a straight plane running the length of the core. The outside sweep core molds half of the straight lumen and the greater curvature at the outside sweep surface of the bend. The inside sweep core molds the other half of the straight bore and the lesser curvature of the inside or undercut portion of the bend.



European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *without international search report and to be republished upon receipt of that report*