

METHOD AND APPARATUS FOR CHANNEL RESOURCE MAPPING IN CARRIER AGGREGATION

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the benefit of U.S. provisional application Nos. 61/293,540 filed January 8, 2010 and 61/307,721 filed February 24, 2010, the contents of which are hereby incorporated by reference herein.

FIELD OF THE INVENTION

[0002] This application is related to wireless communications.

BACKGROUND

[0003] In Long Term Evolution (LTE) Release 8 (R8), a base station may configure a wireless transmit/receive unit (WTRU) with downlink (DL) and uplink (UL) resources on a single DL carrier and a single UL carrier, respectively. In LTE R8, the uplink (UL) Hybrid Automatic Repeat Request (HARQ) mechanism may perform retransmissions of missing or erroneous data packets transmitted by the WTRU. The UL HARQ functionality may span across both the physical (PHY) layer and the Medium Access Control (MAC) layer. The WTRU receives acknowledgments/negative acknowledgments (ACK/NACKs) on the physical HARQ indicator channel (PHICH). That is, the PHICH may be used by a base station for transmission of HARQ feedback, (ACK or NACK), in response to Uplink Shared Channel (UL-SCH) transmissions.

[0004] User multiplexing in LTE R8 may be performed by mapping multiple PHICHs on the same set of resource elements (REs) which constitute a PHICH group. PHICHs within the same PHICH group are separated through different orthogonal Walsh sequences. In order to lower the control signalling overhead, the PHICH index pair may be implicitly associated with the index of the lowest uplink resource block used for the corresponding physical uplink shared channel (PUSCH) transmission and the cyclic shift of

the corresponding uplink demodulation reference signal. The association of PHICH resources and the cyclic shifts enable the allocation of the same time and frequency resource to several WTRUs in support of uplink Multi-User Multiple Input Multiple Output (MU-MIMO). In LTE R8, there are no ambiguities or PHICH collisions, (as a result of using the same RBs), since the downlink (DL) and uplink (UL) resources are associated with a single DL carrier and a single UL carrier, respectively.

[0005] In multi-carrier wireless systems, the WTRU may be assigned or configured with multiple component carriers (CCs), such as for example, with at least one DL component carrier and at least one UL component carrier. The WTRU may be configured to aggregate a different number of CCs of possibly different bandwidths in the UL and the DL. A one-to-one relationship between the DL CC and the UL CC may not exist in multi-carrier wireless systems. In fact, multi-carrier wireless systems may use cross-carrier scheduling, where for example, a DL CC may carry information pertinent to multiple UL CCs.

[0006] Cross-carrier scheduling may include cross-carrier PHICH resource allocation. In these systems, a PHICH may be transmitted on one DL CC that may be associated with multiple UL CCs. If the PHICH is linked to two or more PUSCHs, then application of the LTE R8 PHICH parameter selection for resources may lead to ambiguities and collisions.

[0007] PHICH collisions may also occur with respect to spatial multiplexing. In spatial multiplexing, multiple transport blocks may be transmitted using multiple antennas using an identical first physical resource block (PRB) index. In other words, multiple layers of signaling or multiple streams may be transmitted over multiple antennas using the same PRB index. Therefore, given that each stream needs a corresponding ACK/NACK, the issues related to PHICH collisions stated above with respect to multiple CCs are applicable to spatial multiplexing.

SUMMARY

[0008] Methods and apparatus for preventing physical hybrid automatic repeat request (HARQ) indicator channel (PHICH) ambiguities or collisions, for example, in a multi-carrier system or when transmitting multiple streams over multiple antennas, are described. Methods may include dividing resources or groups among multiple component carriers (CCs), using and assigning unused or vacant resources to CCs, forcing usage of adaptive HARQ processes in specified scenarios, setting a value for the cyclic shift of the corresponding uplink demodulation reference signals (DMRS) to a previous value for semi-persistent scheduling, and assigning a different first resource block for semi-persistent scheduling uplink resources and random access response grants for multiple CCs.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] A more detailed understanding may be had from the following description, given by way of example in conjunction with the accompanying drawings wherein:

[0010] FIG. 1A is a system diagram of an example communications system in which one or more disclosed embodiments may be implemented;

[0011] FIG. 1B is a system diagram of an example wireless transmit/receive unit (WTRU) that may be used within the communications system illustrated in FIG. 1A;

[0012] FIG. 1C is a system diagram of an example radio access network and an example core network that may be used within the communications system illustrated in FIG. 1A.

[0013] FIGs. 2(A), 2(B) and 2(C) illustrate three different configurations for carrier aggregation;

[0014] FIG. 3 is a flowchart for an example method where physical hybrid automatic repeat request (HARQ) indicator channel (PHICH) resources or groups are divided and associated with component carriers;

[0015] FIG. 4 is a flowchart for non-adaptive HARQ procedures at the WTRU;

[0016] FIG. 5 is an example diagram of both contiguous and non-contiguous resource allocations for two users with two uplink component carriers;

[0017] FIG. 6 is a flowchart illustrating HARQ procedures at the base station; and

[0018] FIG. 7 is a flowchart illustrating HARQ procedures at the WTRU.

DETAILED DESCRIPTION

[0019] FIG. 1A is a diagram of an example communications system 100 in which one or more disclosed embodiments may be implemented. The communications system 100 may be a multiple access system that provides content, such as voice, data, video, messaging, broadcast, etc., to multiple wireless users. The communications system 100 may enable multiple wireless users to access such content through the sharing of system resources, including wireless bandwidth. For example, the communications systems 100 may employ one or more channel access methods, such as code division multiple access (CDMA), time division multiple access (TDMA), frequency division multiple access (FDMA), orthogonal FDMA (OFDMA), single-carrier FDMA (SC-FDMA), and the like.

[0020] As shown in FIG. 1A, the communications system 100 may include wireless transmit/receive units (WTRUs) 102a, 102b, 102c, 102d, a radio access network (RAN) 104, a core network 106, a public switched telephone network (PSTN) 108, the Internet 110, and other networks 112, though it will be appreciated that the disclosed embodiments contemplate any number of WTRUs, base stations, networks, and/or network elements. Each of the WTRUs 102a, 102b, 102c, 102d may be any type of device configured to operate and/or communicate in a wireless environment. By way of example, the WTRUs 102a, 102b, 102c, 102d may be configured to transmit and/or

receive wireless signals and may include user equipment (UE), a mobile station, a fixed or mobile subscriber unit, a pager, a cellular telephone, a personal digital assistant (PDA), a smartphone, a laptop, a netbook, a personal computer, a touchpad, a wireless sensor, consumer electronics, and the like.

[0021] The communications systems 100 may also include a base station 114a and a base station 114b. Each of the base stations 114a, 114b may be any type of device configured to wirelessly interface with at least one of the WTRUs 102a, 102b, 102c, 102d to facilitate access to one or more communication networks, such as the core network 106, the Internet 110, and/or the networks 112. By way of example, the base stations 114a, 114b may be a base transceiver station (BTS), a Node-B, an eNode B, a Home Node B, a Home eNode B, a site controller, an access point (AP), a wireless router, and the like. While the base stations 114a, 114b are each depicted as a single element, it will be appreciated that the base stations 114a, 114b may include any number of interconnected base stations and/or network elements.

[0022] The base station 114a may be part of the RAN 104, which may also include other base stations and/or network elements (not shown), such as a base station controller (BSC), a radio network controller (RNC), relay nodes, etc. The base station 114a and/or the base station 114b may be configured to transmit and/or receive wireless signals within a particular region, which may be referred to as a cell (not shown). The cell may further be divided into cell sectors. For example, the cell associated with the base station 114a may be divided into three sectors. Thus, in one embodiment, the base station 114a may include three transceivers, i.e., one for each sector of the cell. In another embodiment, the base station 114a may employ multiple-input multiple output (MIMO) technology and, therefore, may utilize multiple transceivers for each sector of the cell.

[0023] The base stations 114a, 114b may communicate with one or more of the WTRUs 102a, 102b, 102c, 102d over air interface(s) 116, which may be any suitable wireless communication link (e.g., radio frequency (RF)),

microwave, infrared (IR), ultraviolet (UV), visible light, etc.). The air interface 116 may be established using any suitable radio access technology (RAT).

[0024] More specifically, as noted above, the communications system 100 may be a multiple access system and may employ one or more channel access schemes, such as CDMA, TDMA, FDMA, OFDMA, SC-FDMA, and the like. For example, the base station 114a in the RAN 104 and the WTRUs 102a, 102b, 102c may implement a radio technology such as Universal Mobile Telecommunications System (UMTS) Terrestrial Radio Access (UTRA), which may establish the air interface 116 using wideband CDMA (WCDMA). WCDMA may include communication protocols such as High-Speed Packet Access (HSPA) and/or Evolved HSPA (HSPA+). HSPA may include High-Speed Downlink Packet Access (HSDPA) and/or High-Speed Uplink Packet Access (HSUPA).

[0025] In another embodiment, the base station 114a and the WTRUs 102a, 102b, 102c may implement a radio technology such as Evolved UMTS Terrestrial Radio Access (E-UTRA), which may establish the air interface 116 using Long Term Evolution (LTE) and/or LTE-Advanced (LTE-A).

[0026] In other embodiments, the base station 114a and the WTRUs 102a, 102b, 102c may implement radio technologies such as IEEE 802.16 (i.e., Worldwide Interoperability for Microwave Access (WiMAX)), CDMA2000, CDMA2000 1X, CDMA2000 EV-DO, Interim Standard 2000 (IS-2000), Interim Standard 95 (IS-95), Interim Standard 856 (IS-856), Global System for Mobile communications (GSM), Enhanced Data rates for GSM Evolution (EDGE), GSM EDGE (GERAN), and the like.

[0027] In other embodiments, the base station 114a and the WTRUs 102a, 102b, 102c may implement any combination of the aforementioned radio technologies. For example, the base station 114a and the WTRUs 102a, 102b, 102c may each implement dual radio technologies such as UTRA and E-UTRA, which may concurrently establish one air interface using WCDMA and one air interface using LTE-A respectively.

[0028] The base station 114b in FIG. 1A may be a wireless router, Home Node B, Home eNode B, or access point, for example, and may utilize any suitable RAT for facilitating wireless connectivity in a localized area, such as a place of business, a home, a vehicle, a campus, and the like. In one embodiment, the base station 114b and the WTRUs 102c, 102d may implement a radio technology such as IEEE 802.11 to establish a wireless local area network (WLAN). In another embodiment, the base station 114b and the WTRUs 102c, 102d may implement a radio technology such as IEEE 802.15 to establish a wireless personal area network (WPAN). In yet another embodiment, the base station 114b and the WTRUs 102c, 102d may utilize a cellular-based RAT (e.g., WCDMA, CDMA2000, GSM, LTE, LTE-A, etc.) to establish a picocell or femtocell. As shown in FIG. 1A, the base station 114b may have a direct connection to the Internet 110. Thus, the base station 114b may not be required to access the Internet 110 via the core network 106.

[0029] The RAN 104 may be in communication with the core network 106, which may be any type of network configured to provide voice, data, applications, and/or voice over internet protocol (VoIP) services to one or more of the WTRUs 102a, 102b, 102c, 102d. For example, the core network 106 may provide call control, billing services, mobile location-based services, pre-paid calling, Internet connectivity, video distribution, etc., and/or perform high-level security functions, such as user authentication. Although not shown in FIG. 1A, it will be appreciated that the RAN 104 and/or the core network 106 may be in direct or indirect communication with other RANs that employ the same RAT as the RAN 104 or a different RAT. For example, in addition to being connected to the RAN 104, which may be utilizing an E-UTRA radio technology, the core network 106 may also be in communication with another RAN (not shown) employing a GSM radio technology.

[0030] The core network 106 may also serve as a gateway for the WTRUs 102a, 102b, 102c, 102d to access the PSTN 108, the Internet 110, and/or other networks 112. The PSTN 108 may include circuit-switched telephone networks that provide plain old telephone service (POTS). The

Internet 110 may include a global system of interconnected computer networks and devices that use common communication protocols, such as the transmission control protocol (TCP), user datagram protocol (UDP) and the internet protocol (IP) in the TCP/IP internet protocol suite. The networks 112 may include wired or wireless communications networks owned and/or operated by other service providers. For example, the networks 112 may include another core network connected to one or more RANs, which may employ the same RAT as the RAN 104 or a different RAT.

[0031] Some or all of the WTRUs 102a, 102b, 102c, 102d in the communications system 100 may include multi-mode capabilities, i.e., the WTRUs 102a, 102b, 102c, 102d may include multiple transceivers for communicating with different wireless networks over different wireless links. For example, the WTRU 102c shown in FIG. 1A may be configured to communicate with the base station 114a, which may employ a cellular-based radio technology, and with the base station 114b, which may employ an IEEE 802 radio technology.

[0032] FIG. 1B is a system diagram of an example WTRU 102. As shown in FIG. 1B, the WTRU 102 may include a processor 118, a transceiver 120, a transmit/receive element 122, a speaker/microphone 124, a keypad 126, a display/touchpad 128, non-removable memory 130, removable memory 132, a power source 134, a global positioning system (GPS) chipset 136, and other peripherals 138. It will be appreciated that the WTRU 102 may include any sub-combination of the foregoing elements while remaining consistent with an embodiment.

[0033] The processor 118 may be a general purpose processor, a special purpose processor, a conventional processor, a digital signal processor (DSP), a plurality of microprocessors, one or more microprocessors in association with a DSP core, a controller, a microcontroller, Application Specific Integrated Circuits (ASICs), Field Programmable Gate Array (FPGAs) circuits, any other type of integrated circuit (IC), a state machine, and the like. The processor 118 may perform signal coding, data processing, power control, input/output

processing, and/or any other functionality that enables the WTRU 102 to operate in a wireless environment. The processor 118 may be coupled to the transceiver 120, which may be coupled to the transmit/receive element 122. While FIG. 1B depicts the processor 118 and the transceiver 120 as separate components, it will be appreciated that the processor 118 and the transceiver 120 may be integrated together in an electronic package or chip.

[0034] The transmit/receive element 122 may be configured to transmit signals to, or receive signals from, a base station (e.g., the base station 114a) over the air interface 116. For example, in one embodiment, the transmit/receive element 122 may be an antenna configured to transmit and/or receive RF signals. In another embodiment, the transmit/receive element 122 may be an emitter/detector configured to transmit and/or receive IR, UV, or visible light signals, for example. In yet another embodiment, the transmit/receive element 122 may be configured to transmit and receive both RF and light signals. It will be appreciated that the transmit/receive element 122 may be configured to transmit and/or receive any combination of wireless signals.

[0035] In addition, although the transmit/receive element 122 is depicted in FIG. 1B as a single element, the WTRU 102 may include any number of transmit/receive elements 122. More specifically, the WTRU 102 may employ MIMO technology. Thus, in one embodiment, the WTRU 102 may include two or more transmit/receive elements 122, e.g., multiple antennas, for transmitting and receiving wireless signals over the air interface 116.

[0036] The transceiver 120 may be configured to modulate the signals that are to be transmitted by the transmit/receive element 122 and to demodulate the signals that are received by the transmit/receive element 122. As noted above, the WTRU 102 may have multi-mode capabilities. Thus, the transceiver 120 may include multiple transceivers for enabling the WTRU 102 to communicate via multiple RATs, such as UTRA and IEEE 802.11, for example.

[0037] The processor 118 of the WTRU 102 may be coupled to, and may receive user input data from, the speaker/microphone 124, the keypad 126, and/or the display/touchpad 128, (e.g., a liquid crystal display (LCD), display unit or organic light-emitting diode (OLED) display unit). The processor 118 may also output user data to the speaker/microphone 124, the keypad 126, and/or the display/touchpad 128. In addition, the processor 118 may access information from, and store data in, any type of suitable memory, such as the non-removable memory 130 and/or the removable memory 132. The non-removable memory 130 may include random-access memory (RAM), read-only memory (ROM), a hard disk, or any other type of memory storage device. The removable memory 132 may include a subscriber identity module (SIM) card, a memory stick, a secure digital (SD) memory card, and the like. In other embodiments, the processor 118 may access information from, and store data in, memory that is not physically located on the WTRU 102, such as on a server or a home computer (not shown).

[0038] The processor 118 may receive power from the power source 134, and may be configured to distribute and/or control the power to the other components in the WTRU 102. The power source 134 may be any suitable device for powering the WTRU 102. For example, the power source 134 may include one or more dry cell batteries (e.g., nickel-cadmium (NiCd), nickel-zinc (NiZn), nickel metal hydride (NiMH), lithium-ion (Li-ion), etc.), solar cells, fuel cells, and the like.

[0039] The processor 118 may also be coupled to the GPS chipset 136, which may be configured to provide location information (e.g., longitude and latitude) regarding the current location of the WTRU 102. In addition to, or in lieu of, the information from the GPS chipset 136, the WTRU 102 may receive location information over the air interface 116 from a base station (e.g., base stations 114a, 114b) and/or determine its location based on the timing of the signals being received from two or more nearby base stations. It will be appreciated that the WTRU 102 may acquire location information by way of

any suitable location-determination method while remaining consistent with an embodiment.

[0040] The processor 118 may further be coupled to other peripherals 138, which may include one or more software and/or hardware modules that provide additional features, functionality and/or wired or wireless connectivity. For example, the peripherals 138 may include an accelerometer, an e-compass, a satellite transceiver, a digital camera (for photographs or video), a universal serial bus (USB) port, a vibration device, a television transceiver, a hands free headset, a Bluetooth® module, a frequency modulated (FM) radio unit, a digital music player, a media player, a video game player module, an Internet browser, and the like.

[0041] FIG. 1C is a system diagram of the RAN 104 and the core network 106 according to an embodiment. As noted above, the RAN 104 may employ an E-UTRA radio technology to communicate with the WTRUs 102a, 102b, and 102c over the air interface 116. The RAN 104 may also be in communication with the core network 106.

[0042] The RAN 104 may include eNode-Bs 140a, 140b, 140c, though it will be appreciated that the RAN 104 may include any number of eNode-Bs while remaining consistent with an embodiment. The eNode-Bs 140a, 140b, 140c may each include one or more transceivers for communicating with the WTRUs 102a, 102b, 102c over the air interface 116. In one embodiment, the eNode-Bs 140a, 140b, 140c may implement MIMO technology. Thus, the eNode-B 140a, for example, may use multiple antennas to transmit wireless signals to, and receive wireless signals from, the WTRU 102a.

[0043] Each of the eNode-Bs 140a, 140b, 140c may be associated with one or more cells (not shown), each possibly on different carrier frequencies, and may be configured to handle radio resource management decisions, handover decisions, scheduling of users in the uplink and/or downlink, and the like. As shown in FIG. 1C, the eNode-Bs 140a, 140b, 140c may communicate with one another over an X2 interface.

[0044] The core network 106 shown in FIG. 1C may include a mobility management gateway (MME) 142, a serving gateway 144, and a packet data network (PDN) gateway 146. While each of the foregoing elements are depicted as part of the core network 106, it will be appreciated that any one of these elements may be owned and/or operated by an entity other than the core network operator.

[0045] The MME 142 may be connected to each of the eNode-Bs 142a, 142b, 142c in the RAN 104 via an S1 interface and may serve as a control node. For example, the MME 142 may be responsible for authenticating users of the WTRUs 102a, 102b, 102c, bearer setup/configuration/release, selecting a particular serving gateway during an initial attach of the WTRUs 102a, 102b, 102c, and the like. The MME 142 may also provide a control plane function for switching between the RAN 104 and other RANs (not shown) that employ other radio technologies, such as GSM or WCDMA.

[0046] The serving gateway 144 may be connected to each of the eNode Bs 140a, 140b, 140c in the RAN 104 via the S1 interface. The serving gateway 144 may generally route and forward user data packets to/from the WTRUs 102a, 102b, 102c. The serving gateway 144 may also perform other functions, such as anchoring user planes during inter-eNode B handovers, triggering paging when downlink data is available for the WTRUs 102a, 102b, 102c, managing and storing contexts of the WTRUs 102a, 102b, 102c, and the like.

[0047] The serving gateway 144 may also be connected to the PDN gateway 146, which may provide the WTRUs 102a, 102b, 102c with access to packet-switched networks, such as the Internet 110, to facilitate communications between the WTRUs 102a, 102b, 102c and IP-enabled devices.

[0048] The core network 106 may facilitate communications with other networks. For example, the core network 106 may provide the WTRUs 102a, 102b, 102c with access to circuit-switched networks, such as the PSTN 108, to facilitate communications between the WTRUs 102a, 102b, 102c and traditional land-line communications devices. For example, the core network

106 may include, or may communicate with, an IP gateway (e.g., an IP multimedia subsystem (IMS) server) that serves as an interface between the core network 106 and the PSTN 108. In addition, the core network 106 may provide the WTRUs 102a, 102b, 102c with access to the networks 112, which may include other wired or wireless networks that are owned and/or operated by other service providers.

[0049] When referred to hereafter, the term “Component Carrier (CC)” includes, without loss of generality, a frequency on which the WTRU operates. For example, a WTRU may receive transmissions on a downlink CC (hereafter “DL CC”). A DL CC may include a number of DL physical channels including, but not limited to, the Physical Control Format Indicator Channel (PCFICH), the Physical Hybrid Automatic Repeat Request Indicator Channel (PHICH), the Physical Downlink Control Channel (PDCCH), the physical multicast data channel (PMCH) and the physical downlink shared channel (PDSCH). On the PCFICH, the WTRU receives control data indicating the size of the control region of the DL CC. On the PHICH, the WTRU may receive control data indicating hybrid automatic repeat request (HARQ) acknowledgement/negative acknowledgement (ACK/NACK) feedback for a previous uplink transmission. On the PDCCH, the WTRU receives downlink control information (DCI) messages that may be used for scheduling downlink and uplink resources. On the PDSCH, the WTRU may receive user and/or control data.

[0050] In another example, a WTRU may transmit on an uplink CC (hereafter “UL CC”). An UL CC may include a number of UL physical channels including, but not limited to, the physical uplink control channel (PUCCH) and the physical uplink shared channel (PUSCH). On the PUSCH, the WTRU may transmit user and/or control data. On the PUCCH, and in some cases on the PUSCH, the WTRU may transmit uplink control information, (such as channel quality indicator/precoding matrix index/rank indication (CQI/PMI/RI) or scheduling request (SR)), and/or HARQ

ACK/NACK feedback. On a UL CC, the WTRU may also be allocated dedicated resources for transmission of Sounding Reference Signals (SRS).

[0051] A DL CC may be linked to a UL CC based on the system information (SI) received by the WTRU either broadcasted on the DL CC or possibly using dedicated configuration signaling from the network. For example, when broadcasted on the DL CC, the WTRU may receive the uplink frequency and bandwidth of the linked UL CC as part of the SystemInformationBlockType2 (SIB2) information element.

[0052] When referred to hereafter, a primary CC may be a CC operating in the primary frequency in which the WTRU either performs the initial connection establishment procedure or initiates the connection re-establishment procedure, or the CC indicated as the primary CC in a handover procedure. The WTRU may use the primary CC to derive the parameters for the security functions and for upper layer system information such as NAS mobility information. Other functions that may be supported by a primary DL CC may include SI acquisition and change monitoring procedures on the broadcast channel (BCCH), and paging. A primary UL CC may correspond to the CC whose PUCCH resources are configured to carry all HARQ ACK/NACK feedback for a given WTRU. When referred to hereafter, a secondary CC may be a CC operating on a secondary frequency which may be configured once an radio resource control (RRC) connection is established and which may be used to provide additional radio resources.

[0053] In LTE Release 8 (R8), the uplink (UL) Hybrid Automatic Repeat Request (HARQ) mechanism may be used to perform retransmissions of missing or erroneous data packets transmitted by the WTRU. The UL HARQ functionality may span across both the physical (PHY) layer and the Medium Access Control (MAC) layer and operates as described herein. The WTRU may perform what the PDCCH requests, i.e., perform a transmission or a retransmission (referred to as adaptive retransmission) when a PDCCH addressed to a Cell Radio Network Temporary Identifier (C-RNTI) of the WTRU is correctly received, regardless of the content of the HARQ feedback,

(ACK or NACK). When no PDCCH addressed to the C-RNTI of the WTRU is detected, the HARQ feedback may dictate how the WTRU performs retransmissions. For a NACK, the WTRU may perform a non-adaptive retransmission, i.e., a retransmission on the same UL resource as previously used by the same process. For an ACK, the WTRU may not perform any UL transmission or retransmission and keep the data in the HARQ buffer. A PDCCH may then be required to perform a retransmission, i.e., a non-adaptive retransmission may not follow.

[0054] In summary, the uplink HARQ protocol in LTE R8 may support either adaptive or non-adaptive transmissions or retransmissions. The non-adaptive HARQ may be considered the basic mode of operation in the UL. The UL HARQ operation in LTE R8 is summarized in Table 1, which shows behavior based on HARQ feedback sent on the PHICH.

HARQ feedback sent on the PHICH and seen by the WTRU	PDCCH seen by the WTRU	WTRU behavior
ACK or NACK	New Transmission	New transmission according to PDCCH
ACK or NACK	Retransmission	Retransmission according to PDCCH (adaptive retransmission)
ACK	None	No transmission or retransmission, keep data in HARQ buffer and a PDDCH is required to resume retransmissions
NACK	None	Non-adaptive retransmission

Table 1

[0055] From the WTRU's perspective, the PHY layer in the WTRU may deliver an ACK/NACK that was received on the PHICH and assigned to the WTRU, to the higher layers of the WTRU as described herein. For a downlink subframe i , if a transport block is transmitted in the associated PUSCH subframe, then an ACK may be delivered to the higher layers if the ACK is

decoded on the PHICH in subframe i . Otherwise, a NACK may be delivered to the higher layers.

[0056] In LTE R8, as described herein above, the PHICH may be used for transmission of HARQ feedback, (ACK or NACK), in response to an Uplink Shared Channel (UL-SCH) transmission. User multiplexing in LTE R8 may be performed by mapping multiple PHICHs on the same set of resource elements (REs) which may constitute a PHICH group. The PHICHs within the same PHICH group may be separated through different orthogonal Walsh sequences. The number of PHICH groups may be a function of DL bandwidth (BW) and may be determined by:

$$N_{\text{PHICH}}^{\text{group}} = \begin{cases} \left\lceil N_g (N_{\text{RB}}^{\text{DL}} / 8) \right\rceil & \text{for normal cyclic prefix} \\ 2 \cdot \left\lceil N_g (N_{\text{RB}}^{\text{DL}} / 8) \right\rceil & \text{for extended cyclic prefix} \end{cases}$$

Equation (1)

where $N_g \in \{1/6, 1/2, 1, 2\}$ may be provided by higher layers and $N_{\text{RB}}^{\text{DL}}$ may be the number of DL resource blocks (RBs). The term N_g is a scaling factor that indicates the number of resources that may be allocated. For example, if N_g is equal to two, then it signifies the maximum allowable resources that maybe configured for the system given the bandwidth. The scaling factor is nominally set by, for example, the base station using higher layer signaling. Accordingly, the maximum number of PHICH resources for normal cyclic prefix (CP) and extended CP may be calculated as shown in Table 2 and Table 3, respectively. In particular, Table 2 shows the number of PHICH groups as a function of DL BW and N_g for normal CP, and Table 3 shows the number of PHICH groups as a function of DL BW and N_g for extended CP.

	6 RBs	15 RBs	25 RBs	50 RBs	75 RBs	100 RBs
$N_g=1/6$	1	1	1	2	2	3
$N_g=1/2$	1	1	2	4	5	7
$N_g=1$	1	2	4	7	10	13
$N_g=2$	2	4	7	13	19	25

Table 2

	6 RBs	15 RBs	25 RBs	50 RBs	75 RBs	100 RBs
Ng=1/6	2	2	2	4	4	6
Ng=1/2	2	2	4	8	10	14
Ng=1	2	4	8	14	20	26
Ng=2	4	8	14	26	38	50

Table 3

[0057] A PHICH resource may be implicitly identified by the index pair $(n_{PHICH}^{group}, n_{PHICH}^{seq})$, where n_{PHICH}^{group} may be the PHICH group number and n_{PHICH}^{seq} may be the orthogonal sequence index within the group.

[0058] In order to decrease the control signaling overhead, the PHICH index pair may be implicitly associated with the index of the lowest uplink resource block used for the corresponding PUSCH transmission and the cyclic shift of the corresponding UL demodulation reference signals (DMRS) as follows:

$$n_{PHICH}^{group} = (I_{PRB_RA}^{lowest_index} + n_{DMRS}) \bmod N_{PHICH}^{group} + I_{PHICH} N_{PHICH}^{group}$$

$$n_{PHICH}^{seq} = (\lfloor I_{PRB_RA}^{lowest_index} / N_{PHICH}^{group} \rfloor + n_{DMRS}) \bmod 2N_{SF}^{PHICH}$$

Equation (2)

where the parameters are defined as follows:

n_{DMRS} is mapped from the cyclic shift in the DMRS field in the most recent downlink control information (DCI) format 0 for the transport block associated with the corresponding PUSCH transmission. It may be a three bit field and for a single user configuration, n_{DMRS} may be set to zero. For a semi-persistently configured PUSCH transmission on subframe n in the absence of a corresponding PDCCH with a DCI Format 0 in subframe $n - k_{PUSCH}$ or a PUSCH transmission associated with a random access response grant, n_{DMRS} is set to zero where $k_{PUSCH} = 4$ for FDD transmissions;

N_{SF}^{PHICH} is the spreading factor size used for PHICH modulation defined as a function of cyclic prefix;

$I_{PRB_RA}^{lowest_index}$ is the lowest physical RB index in the first slot of the corresponding PUSCH transmission;

N_{PHICH}^{group} is the number of PHICH groups configured by higher layers; and

$$I_{PHICH} = \begin{cases} 1 & \text{for TDD UL/DL configuration 0 with PUSCH transmission in subframe } n = 4 \text{ or } 9 \\ 0 & \text{otherwise} \end{cases}$$

[0059] The association of PHICH resources and the cyclic shifts may enable the allocation of the same time and frequency resource to several WTRUs in support of uplink Multi-User Multiple Input Multiple Output (MU-MIMO).

[0060] In LTE-Advanced (LTE-A), carrier aggregation may be used. The WTRU may be configured to aggregate a different number of CCs of possibly different bandwidths in the UL and the DL. Three example configurations for LTE-A carrier aggregation are illustrated in FIGs. 2(A), 2(B) and 2(C). FIG. 2(A) illustrates a symmetric carrier aggregation, FIG. 2(B) illustrates multiple DL CCs with one UL CC, and FIG. 2(C) illustrates one DL CC with multiple UL CCs. In these multi-carrier systems, a PDCCH on a CC may assign PDSCH or PUSCH resources in one of multiple CCs using a carrier indicator field (CIF). The latter may be realized by extending DCI formats with a 3-bit CIF. As for the HARQ feedback transmission, it may be assumed that PHICH is transmitted on the DL CC that is used to transmit the UL grant.

[0061] In LTE-A, cross-carrier scheduling may be used and may include cross-carrier PHICH resource allocation. In these systems, a PHICH may be transmitted on a DL CC that may be associated with multiple UL CCs. If the PHICH is linked to two or more PUSCHs, then application of the LTE R8 PHICH parameter selection for resources may lead to ambiguities and collisions. For example, UL transmissions on two or more CCs may be scheduled by the same DL CC. In this example, if the PUSCH transmissions on two or more CCs use the same lowest PRB index, $I_{PRB_RA}^{lowest_index}$, the association of a PHICH resource in the DL, and the lowest PRB index used for PUSCH transmission in the UL in accordance with LTE R8 may not be unique and a PHICH resource collision may occur. In fact, assuming a non-adaptive HARQ operation, multiple HARQ processes at the base station may attempt to

transmit their corresponding feedback information on the same PHICH resource which may result in PHICH resource collisions.

[0062] Several solutions offered to address the problem are insufficient. For example, one solution may semi-statically configure UL carrier-specific PHICH resource offsets. However, this alternative requires a large number of PHICH resources, e.g., one set per UL carrier. Another solution may be based on a system-wide indexing of PRB and PHICH resources, starting from WTRUs and continuing for LTE-A WTRUs. The shortcoming of this alternative is that the solution is not backward compatible and hence LTE R8 and LTE Release 10 (R10) or LTE-A WTRUs cannot coexist. Further, it has been suggested that where some UL CC transmissions use the same first PRB index, the collision may be avoided by using different DMRS cyclic shifts as in LTE R8. However, this approach may limit the UL MU-MIMO capabilities of LTE-A as compared to that of LTE R8. In fact, in LTE-A, the cyclic shifts may be consumed by configuring MU-MIMO transmissions, hence using cyclic shifts to avoid PHICH collisions may result in UL system throughput loss.

[0063] The following embodiments identify solutions, some of which may involve implicit PHICH mapping schemes, to address channel resource mapping and the PHICH mapping ambiguity issue. The solutions may be applicable to assigning radio resources generally, to Frequency Division Duplex (FDD) or to Time Division Duplex (TDD) modes of operation in LTE-A, or to any combination of radio resource technologies.

[0064] Any or all of the methods and embodiments outlined below may be supported by the WTRU to address the identified problems. The methods and embodiments may also be supported by the base station in addition to those identified as applicable to the WTRU.

[0065] In an example method, the existing PHICH resource groups may be divided, and assigned to different UL CCs by the scheduler at, for example, the base station. For illustrative purposes only, a PHICH mapping rule may be determined by

$$n_{PHICH,n_{CI}}^{group} = (I_{PRB_RA}^{lowest_index} + n_{DMRS}) \bmod \left(\left\lfloor N_{PHICH}^{group} / N_{CC} \right\rfloor \right) + n_{CI} \left(\left\lfloor N_{PHICH}^{group} / N_{CC} \right\rfloor \right)$$

$$n_{PHICH}^{seq} = \left(\left\lfloor I_{PRB_RA}^{lowest_index} / \left\lfloor N_{PHICH}^{group} / N_{CC} \right\rfloor \right\rfloor + n_{DMRS} \right) \bmod 2N_{SF}^{PHICH}$$

Equation (3)

where the parameters above are defined as follows:

$n_{PHICH,n_{CI}}^{group}$ may be the number of the PHICH groups assigned to the n_{CI} th UL CC;

n_{PHICH}^{seq} may be the orthogonal sequence index within the group;

n_{CI} may be the index of the UL CC used for transmission of the corresponding PUSCH;

n_{DMRS} may be mapped from the cyclic shift in DMRS field in the most recent DCI format 0 for the transport block associated with the corresponding PUSCH transmission;

N_{SF}^{PHICH} may be the spreading factor size used for PHICH modulation defined as a function of cyclic prefix;

$I_{PRB_RA}^{lowest_index}$ may be the lowest physical RB index in the first slot of the corresponding PUSCH transmission;

N_{PHICH}^{group} may be the number of PHICH groups configured by higher layers; and

N_{CC} may denote the number of UL CCs linked to a single DL CC.

[0066] Three of the above described parameters, namely $n_{PHICH,n_{CI}}^{group}$, n_{PHICH}^{seq} , and n_{CI} , may be determined by decoding the PDCCH on the associated DL CC using the WTRU specific C-RNTI to read the DCI format 0 granting the PUSCH transmission, (assuming that a CIF exists).

[0067] In this method, an assumption may be that $N_g = 2$, so as to maximize the number of available PHICH groups. Other values may be possible depending on the number of aggregated UL CCs. As shown in Table 2, the number of PHICH groups may also be a function of the DL BW. Accordingly, the maximum number of aggregated CCs that may be supported

when the DL bandwidth is 6 RBs and 12 RBs may be two and four, respectively.

[0068] In a variation of the example method, an assumption may be that $N_g = 1/4$, such that there may only be one PHICH group available for BWs up to 25 RBs. Thus, the PHICH groups may not be divided and dedicated to different carriers. However, this may be resolved by dividing the total PHICH resources or PHICH channels instead of PHICH groups. For example, the total number of PHICH channels for $N_g = 1/4$ may be eight. Eight PHICH channels may be divided into several divisions, each of which may then be associated with a CC. Moreover, for some other configurations such as $N_g = 1/2$ or $N_g = 1$, the number of PHICH groups may be two and four respectively, thus the maximum number of carriers which may be supported is limited to two and four carriers, respectively. Again, this may be resolved by dividing the total number of PHICH resources or channels instead of PHICH groups. Table 4 shows the number of PHICH groups and number of PHICH channels that may be divided among carriers with different N_g configurations for a 5MHz bandwidth.

	$N_g=1/4$	$N_g=1/2$	$N_g=1$	$N_g=2$
Number of PHICH groups	1	2	4	7
Number of PHICH channels	8	16	32	56

Table 4

[0069] This example method may include any possible division of channel resources, PHICH resources, channels, groups, or combination thereof. Each division may be configured for, or assigned to, a particular CC.

[0070] FIG. 3 shows a flowchart 300 illustrating the example method. A WTRU decodes a PDCCH on an associated DL CC using, for example, a WTRU specific C-RNTI for a UL CC that may be assigned to the WTRU for UL transmission (305). The WTRU then determines a set of dynamic parameters, for example, $I_{PRB_RA}^{lowest_index}$, n_{DMRS} and n_{CI} (310). Using a set of semi-

static parameters configured by higher layers, such as for example, N_{CC} and N_{SF}^{PHICH} (320), and the dynamic parameters, the WTRU distributes the resources, groups or a combination thereof proportionately among the UL CCs (315). This may be evenly or unevenly proportioned among the UL CCs. In particular, the WTRU may determine the number of the PHICH group assigned to a UL CC and the sequence index number with the group, e.g., $n_{PHICH}^{group}, n_{PHICH}^{seq}$, in accordance with, for example, the mapping rule of Equation (3).

[0071] In another method, it is assumed that in order to increase the user capacity under carrier aggregation, a WTRU may be allocated more than one RB on a given CC. However, there may still be a one-to-one mapping between each PHICH resource and the PRB index used for a PUSCH transmission. Thus, there may be unused PHICH resources available that are not assigned for HARQ feedback transmissions. These spare or vacant PHICH resources may be utilized for PHICH resource collision avoidance. Thus, in this example method, a basic assumption may be made that each user's assignment on each UL CC in terms of the number of RBs may be greater than or equal to the number of aggregated UL CCs or the number of transport blocks. Stated differently, $L_{RBs} \geq N_{CC}$, where N_{CC} may denote the number of aggregated UL CCs linked to a single DL CC and L_{RBs} may be the length of contiguously or non-contiguously allocated RBs to a WTRU per CC.

[0072] The WTRU may use the following mapping formula by replacing the $I_{PRB_RA}^{lowest_index}$ parameter in Equation (2) with $(I_{PRB_RA}^{lowest_index} + \Delta_i)$, thereby resulting in the following equation:

$$n_{PHICH,i}^{group} = ((I_{PRB_RA}^{lowest_index} + \Delta_i) + n_{DMRS}) \bmod N_{PHICH}^{group} + I_{PHICH} N_{PHICH}^{group}$$

$$n_{PHICH,i}^{seq} = ((I_{PRB_RA}^{lowest_index} + \Delta_i) / N_{PHICH}^{group} \lfloor + n_{DMRS} \rfloor) \bmod 2N_{SF}^{PHICH}$$

Equation (4)

where the additional parameters above are defined as follows:

$I_{PRB_RA}^{lowest_index}$ may be the lowest PRB index in the first slot of the corresponding PUSCH transmission; and

Δ_i may be a CC dependent offset or an offset associated with the index of the transport block which may be applied to $I_{PRB_RA}^{lowest_index}$, and may be identified as the collision avoidance parameter. The Δ_i parameter may be used to uniquely link a PRB index within the contiguously or non-contiguously allocated RBs of a WTRU to a different CC in order to avoid PHICH resource collision. For example, the Δ_i points to the extra or vacant resources in the primary CC. For a system with N_{RB} RBs, the parameter Δ_i may take the following values:

$$\Delta_i \in \{0, 1, \dots, N_{RB} - 1\}.$$

[0073] The parameter Δ_i may either be configured and communicated to the WTRU through higher layer signaling or identified by the WTRU according to a pre-specified mapping rule based on its PRB allocations. To realize the latter, one possible mapping rule may be to sequentially associate the PRB indices within an allocated UL grant on one of the UL CCs to a sequence of PHICH resources and then transmit the HARQ feedbacks corresponding to multiple UL CCs using these PHICH resources. For instance, the PHICH resource associated with the PUSCH transmission on UL CC₀ may be linked to the lowest PRB index from the set of PRBs allocated to the WTRU (i.e., $I_{PRB_RA}^{lowest_index}$), the PHICH resource associated with the PUSCH transmission on UL CC₁ may be linked to the second lowest PRB index from the set of PRBs allocated to the WTRU, and so on, (such that the assignments may incrementally continue for all UL CCs).

[0074] FIG. 4 is a flowchart 400 for the non-adaptive HARQ procedures at the WTRU based on the example method associated with Equation (4). The method starts with the WTRU decoding a PDCCH on a DL CC that may contain resource information for the CCs (405). The allocated UL PRBs for the multiple CCs are then identified (410). The WTRU then determines if the lowest PRB indices of the PRB allocations among the multiple CCs are the same (415). If there are no collisions (420), then the WTRU identifies the assigned PHICH resources in accordance with the LTE R8 method described herein (425). If there are potential collisions, then the WTRU determines if

the number of RBs is greater than or equal to the number of CCs (430). If there are more CCs than RBs, then the method associated with Equation (4) is inapplicable (440). In this case, other methods described herein may be used. If the number of RBs is greater than or equal to the number of CCs, then the WTRU determines the collision avoidance factor Δ_i for each CC or transport block with respect to the primary UL CC (445). The PHICH group number for each UL CC and the orthogonal sequence index within the PHICH group are then determined by the WTRU in accordance with Equation (4) (450) and the method completes (455).

[0075] FIG. 5 illustrates an example using the method illustrated in FIG. 4. As shown in FIG. 5, two users, WTRU₀ and WTRU₁, may be allocated two RBs on each CC in a system having two aggregated UL CCs, CC₀ and CC₁. Both users may be allocated two non-contiguous RBs on CC₀ and two contiguous RBs on CC₁. In other words, each user, WTRU₀ and WTRU₁, may be configured to transmit two transport blocks, one on CC₀ and CC₁. Each user is therefore expecting to receive feedback information related to the transmitted transport blocks on a PHICH carried by a DL CC. Application of LTE R8 processing would lead to a PHICH resource collision as the WTRUs are expecting ACK/NACKs for each transport block transmission. For example, RB₀ would be used for sending an ACK/NACK for transport block 1 and transport block 2 for WTRU₀ and RB₁ would be used for sending an ACK/NACK for transport block 1 and transport block 2 for WTRU₁. However, using the method of FIG. 4 and given the above PHICH collision, each WTRU determines if the number of allocated resources is greater than or equal to the number of CCs. In this example, this is true for each WTRU. Each WTRU would then calculate a collision avoidance factor for the number of CCs, with respect to the primary UL CC, which in this example is CC₀. In this example, WTRU₀ may then expect to receive its HARQ feedbacks on PHICH resources that are linked to RB₀ and RB₂ for the two transport blocks that are transmitted on CC₀ and CC₁, respectively, (i.e., WTRU₀ may determine $\Delta_i \in \{0,2\}$). As for WTRU₁, it may expect to receive its HARQ feedbacks on

PHICH resources that are linked to RB_1 and RB_3 for the two transport blocks that are transmitted on CC_0 and CC_1 , respectively, (i.e., $WTRU_1$ may determine $\Delta_i \in \{1,3\}$).

[0076] Another method for PHICH resource collision avoidance may be based on a network-configured solution. More specifically, in the case of PHICH resource collisions, the base station may force all HARQ feedback corresponding to all UL CCs except for one to be transmitted on the PDCCH. A result of this approach may be that an adaptive mode of operation is dictated to a number of the HARQ processes while only one of the HARQ processes may be based on the non-adaptive HARQ process. For purposes of backward compatibility, in the event that the PHICH resources are shared by both LTE R8 and LTE-A WTRUs, the available PHICH resource may be assigned to the LTE R8 WTRU. This method uses non-adaptive HARQ processing and adaptive HARQ processing in a complementary manner to implement PHICH resource collision avoidance.

[0077] FIG. 6 is a flowchart 600 for HARQ procedures at the base station based on the network-configured method. Initially, the base station may allocate UL PRBs on multiple CCs configured at the WTRU (605). The base station then determines whether the lowest PRB indices of the PRB allocations among the multiple CCs are the same (610). If the lowest indices of the PRB allocations are not the same among the multiple CCs (615), then the base station may follow the LTE R8 HARQ transmission method described herein (620). If the lowest PRB indices of the PRB allocations are the same, then the base station triggers an adaptive HARQ process for each CC that has the possibility of a PHICH collision (625). The base station may transmit the appropriate feedbacks, ACK/NACKs, for adaptive HARQ processes on the PDCCH and for non-adaptive HARQ processes on the PHICH (630).

[0078] Before reviewing the network-configured method from perspective of the WTRU, note that in LTE R8 there is one HARQ entity that maintains a number of parallel HARQ processes at the WTRU. In order to

support carrier aggregation in LTE-A, it may be assumed that a HARQ process may be dedicated to each UL CC.

[0079] The behavior at the WTRU and in particular at the MAC layer is now described. At a transmission time interval (TTI) for which the HARQ entity at the WTRU may expect to receive feedback transmissions, (ACK/NACK information), corresponding to any UL CC, the WTRU may first conduct a search for the PDCCH DCI format 0/0x on the DL CC on which an initial UL grant has been transmitted. Note that DCI Format 0x represents the UL grant for single user (SU)-MIMO (SU-MIMO) transmission mode. If a UL grant addressed to the C-RNTI (or Semi-Persistent Scheduling C-RNTI) of the WTRU is detected for a CC, the HARQ entity may identify the corresponding HARQ process for which a transmission has taken place and then route the received ACK/NACK information to the appropriate HARQ process. When no PDCCH DCI format 0/0x addressed to the C-RNTI of the WTRU is detected for a given CC, the HARQ entity may attempt to obtain the feedback information transmitted in the PHICH and then route the content of the HARQ feedback, (ACK or NACK), to the appropriate HARQ process. With respect to PHICH, the PHY layer in the WTRU may deliver certain information to the higher layers.

[0080] In particular, for downlink subframe *i*, if a transport block was transmitted in the associated PUSCH subframe then an ACK may be delivered to the higher layers if ACK is decoded on the PHICH in subframe *i*. Otherwise, a NACK may be delivered to the higher layers if a NACK is decoded on the PHICH in subframe *i*. If, no PHICH is detected in subframe *i*, a WTRU may indicate the absence of PHICH to the higher layers. This is summarized in Table 5.

For downlink subframe i , if a transport block was transmitted in the associated PUSCH subframe then:

- *if ACK is decoded on the PHICH in subframe i ,*
 - o *ACK shall be delivered to the higher layers;*
- *else, if NACK is decoded on the PHICH in subframe i ,*
 - o *NACK shall be delivered to the higher layers;*
- *else, no PHICH was detected in subframe i ,*
 - o *UE shall indicate the absence of PHICH to the higher layers.*

Table 5

[0081] A result of the network-configured method may be the increased control channel overhead due to the additional PDCCH transmissions which may be the direct consequence of forced adaptive HARQ transmissions for some of the feedback transmissions. However, the probability of having PHICH collisions may be relatively low for an appropriately designed DL scheduler at the base station. Hence, it may not be expected for the base station to be forced to initiate many adaptive HARQ retransmissions at a given TTI. This method may in fact minimize the impact on standardization efforts as it may only require insertion of the procedures in the R8 HARQ processes.

[0082] FIG. 7 is a flowchart 700 for WTRU behavior in accordance with the network-configured method. Initially, the HARQ entity at the WTRU determines the TTI for which it expects to receive feedback information (705). The WTRU then initiates a search for the PDCCH DCI format 0/0x on the CC that the initial UL grants have been transmitted on (710). The WTRU then attempts to detect the UL grants for each CC as addressed by the WTRU's C-RNTI (715). If no PDCCH DCI format 0/0x addressed to the C-RNTI of the WTRU is detected for a given CC (720), the WTRU may attempt to obtain the feedback information transmitted in the PHICH (725). The HARQ entity may then route the content of the HARQ feedback, (ACK or NACK), to the appropriate HARQ process for each CC (730). The process then completes (740). If a UL grant addressed to the C-RNTI (or Semi-Persistent Scheduling

C-RNTI) of the WTRU is detected for a CC, the HARQ entity may identify the corresponding HARQ process for which a transmission has taken place and then route the received ACK/NACK information to the appropriate HARQ process (735). The process then completes (740).

[0083] Described now is a method that addresses the problems associated with the cyclic shift based approach to avoid PHICH collisions. The method addresses the issue when two or more users may be semi-persistently configured on multiple UL component carriers or assigned random access response grants on multiple UL component carriers.

[0084] In particular, for a semi-persistently configured PUSCH transmission in the absence of a corresponding PDCCH with a DCI Format 0 or for a PUSCH transmission associated with a random access response grant, the variable n_{DMRS} is set to zero. This may imply that if two or more semi-persistently co-scheduled users share the same lower resource block on UL component carriers that receive their grants from the same DL component carrier for their PUSCH transmissions, then all these co-scheduled users may be assigned the same cyclic shift for their UL DMRS, (i.e., $n_{DMRS} = 0$). Accordingly, by relying on a cyclic-shift-based solution, the PHICH collisions may be inevitable.

[0085] In the case of a semi-persistently configured PUSCH transmission on subframe n in the absence of a corresponding PDCCH with a DCI Format 0 in subframe $n - k_{PUSCH}$, the WTRU may determine its n_{DMRS} based on the information in the most recent grant that assigns the semi-persistent resource allocation. With respect to the base station, the scheduler may schedule such that co-scheduled WTRUs on multiple UL CCs are assigned different first resource blocks as part of their initial semi-persistently scheduled PUSCH.

[0086] In the case of a PUSCH transmission associated with a random access response grant, the scheduler may configure co-scheduled WTRUs on multiple UL CCs such that the WTRUs are assigned different first resource

blocks as part of their random access response grant. This may lead to different PHICH resources and thus avoids collisions of PHICH resources originating from different UL CCs.

[0087] Embodiments:

[0088] 1. A method implemented at a base station for performing feedback channel resource mapping, comprising dividing at least one of allocated feedback channel resources or feedback channel groups.

[0089] 2. The method of embodiment 1, further comprising assigning divided feedback channel resources or feedback channel groups to uplink component carriers.

[0090] 3. The method as in any of the preceding embodiments, wherein an implicit mapping rule uses a feedback channel group number and a sequence index number to associate the divided feedback channel resources or feedback channel groups with the uplink component carriers.

[0091] 4. A method implemented at a wireless transmit/receive unit (WTRU) for performing feedback channel resource mapping, comprising decoding a downlink control channel associated with uplink resource grant.

[0092] 5. The method as in embodiment 4, further comprising determining a set of dynamic parameters from a decoded downlink control channel.

[0093] 6. The method as in any of the embodiments 4-5, further comprising receiving a set of semi-static parameters.

[0094] 7. The method as in any of the embodiments 4-6, further comprising distributing at least one of allocated feedback channel resources or feedback channel groups to uplink component carriers based on the set of dynamic parameters and semi-static parameters.

[0095] 8. The method as in any of the embodiments 4-7, further comprising determining a feedback channel group number from the set of dynamic parameters and semi-static parameters.

[0096] 9. The method as in any of the embodiments 4-8, further comprising determining a sequence index number from the set of dynamic parameters and semi-static parameters.

[0097] 10. The method as in any of the embodiments 4-9, further comprising associating the at least one of allocated feedback channel resources or feedback channel groups with the uplink component carriers using the feedback channel group number and the sequence index number.

[0098] 11. A method implemented at a wireless transmit/receive unit (WTRU) for performing feedback channel resource mapping, comprising determining a feedback channel resource collision.

[0099] 12. The method as in embodiment 11, further comprising determining a collision avoidance index on occurrence of a feedback channel resource collision, wherein the collision avoidance index points to unused allocated resources and links the unused allocated resources to uplink component carriers or transport blocks.

[00100] 13. The method as in any of the embodiments 11-12, wherein feedback channel resource collision determination checks sameness of lowest resources allocated among the uplink component carriers.

[00101] 14. The method as in any of the embodiments 11-13, further comprising checking that a quantity of unused allocated resources is greater than or equal to the uplink component carriers or transport blocks.

[00102] 15. The method as in any of the embodiments 11-14, further comprising determining a feedback channel group number from at least the collision avoidance index.

[00103] 16. The method as in any of the embodiments 11-15, further comprising determining a sequence index number from at least the collision avoidance index.

[00104] 17. The method as in any of the embodiments 11-16, further comprising associating the unused allocated resources with the uplink component carriers or transport block using the feedback channel group number and the sequence index number.

[00105] 18. The method as in any of the embodiments 11-17, wherein the collision avoid index is configured and communicated to the WTRU through higher layer signaling.

[00106]

[00107] 19. The method as in any of the embodiments 11-18, wherein the collision avoid index is identified by the WTRU using a predetermined mapping rule based on resource allocations.

[00108] 20. A method implemented at a base station for avoiding feedback channel resource collision, comprising determining a feedback channel resource collision.

[00109] 21. The method as in embodiment 20, further comprising forcing an adaptive feedback channel process for each uplink component carrier having a feedback channel resource collision.

[00110] 22. The method as in any of the embodiments 20-21, wherein feedback channel resource collision determination checks sameness of lowest resources allocated among an uplink component carriers.

[00111] 23. The method as in any of the embodiments 20-22, wherein a non-adaptive feedback channel process is used for one uplink component carrier having a feedback channel resource collision.

[00112] 24. A method implemented at a wireless transmit/receive unit (WTRU) for avoiding feedback channel resource collision, comprising at an expected feedback information reception time, searching for downlink control information on a downlink control channel associated with an uplink resource grant.

[00113] 25. The method as in embodiment 24, further comprising routing the feedback information to an identified feedback process for each component carrier upon detection of an uplink grant for a component carrier that is addressed to the WTRU.

[00114] 26. The method as in any of the embodiments 24-25, further comprising routing the feedback information obtained from a feedback

channel to an applicable feedback process for each component carrier upon failure to detect an uplink grant.

[00115] 27. A method for avoiding feedback channel resource collision for co-scheduled wireless transmit/receive units (WTRUs), comprising semi-persistently configuring each WTRU with an uplink transmission in a subframe.

[00116] 28. The method as in embodiment 27, further comprising for each WTRU, determining a value for a parameter from a grant assigning a semi-persistent resource allocation on a condition that a downlink control channel is absent in a previous subframe, wherein the parameter is mapped to a cyclic shift of a corresponding uplink demodulation reference signal (DMRS).

[00117] 29. The method as in embodiment 24, wherein each WTRU has a different first resource block for a semi-persistently configured uplink transmission.

[00118] 30. A method for avoiding feedback channel resource collision for co-scheduled users wireless transmit/receive units (WTRUs), comprising scheduling random access response grants to the WTRUs on multiple component carriers.

[00119] 31. The method as in embodiment 30, further comprising assigning different first resource blocks to each of the WTRUs for their respective random access response grants.

[00120] 32. A method for performing channel resource mapping for carrier aggregation, the method comprising dividing existing channel resource groups.

[00121] 33. The method as in embodiment 32, further comprising assigning existing channel resource groups to different uplink (UL) component carriers (CCs).

[00122] 34. The method as in any of the embodiments 32-33, further comprising applying Physical Hybrid ARQ Indicator Channel (PHICH) resource mapping for carrier aggregation.

[00123] 35. The method as in any of the embodiments 32-34, wherein an implicit Physical Hybrid ARQ Indicator Channel (PHICH) mapping scheme addresses a PHICH mapping ambiguity.

[00124] 36. The method as in any of the embodiments 32-35, wherein the method is applicable to Frequency Division Duplex (FDD).

[00125] 37. The method as in any of the embodiments 32-36, wherein the method is applicable to FDD or Time Division Duplex (TDD), or both, modes of operation.

[00126] 38. The method as in any of the embodiments 32-37, wherein the method is applicable to Long Term Evolution-Advanced (LTE-A).

[00127] 39. The method as in any of the embodiments 32-38, further comprising dividing existing Physical Hybrid ARQ Indicator Channel (PHICH) resource groups.

[00128] 40. The method as in any of the embodiments 32-39, further comprising assigning existing Physical Hybrid ARQ Indicator Channel (PHICH) resource groups to different UL component carriers (CCs).

[00129] 41. The method as in any of the embodiments 32-40, wherein the method is performed by a scheduler.

[00130] 42. The method as in any of the embodiments 32-41, further comprising implementing a Physical Hybrid ARQ Indicator Channel (PHICH) mapping rule.

[00131] 43. The method as in any of the embodiments 32-42, wherein the PHICH mapping rule is:

$$n_{PHICH, n_{CI}}^{group} = (I_{PRB_RA}^{lowest_index} + n_{DMRS}) \bmod \left(\left\lfloor \frac{N_{PHICH}^{group}}{N_{CC}} \right\rfloor \right) + n_{CI} \left(\left\lfloor \frac{N_{PHICH}^{group}}{N_{CC}} \right\rfloor \right)$$

$$n_{PHICH}^{seq} = \left(\left\lfloor \frac{I_{PRB_RA}^{lowest_index}}{\left\lfloor \frac{N_{PHICH}^{group}}{N_{CC}} \right\rfloor} \right\rfloor + n_{DMRS} \right) \bmod 2N_{SF}^{PHICH}.$$

[00133] 44. The method as in any of the embodiments 32-43, wherein $n_{PHICH, n_{CI}}^{group}$ is the number of the PHICH group assigned to the n_{CI} th UL component carrier (CC).

[00134] 45. The method as in any of the embodiments 32-44, wherein n_{PHICH}^{seq} is the orthogonal sequence index within the group, n_{CI} is the index of

the UL CC used for transmission of the corresponding Physical Uplink Shared Channel (PUSCH).

[00135] 46. The method as in any of the embodiments 32-45, wherein n_{DMRS} is mapped from the cyclic shift for Demodulation Reference Signal (DMRS) field in the most recent Downlink Control Information (DCI) format 0 for the transport block associated with the corresponding Physical Uplink Shared Channel (PUSCH) transmission.

[00136] 47. The method as in any of the embodiments 32-46, wherein N_{SF}^{PHICH} is the spreading factor size used for PHICH modulation defined as a function of cyclic prefix.

[00137] 48. The method as in any of the embodiments 32-47, wherein $I_{PRB_RA}^{lowest_index}$ is the lowest physical resource block (RB) index in the first slot of the corresponding PUSCH transmission.

[00138] 49. The method as in any of the embodiments 32-48, wherein N_{PHICH}^{group} is the number of PHICH groups configured by higher layers.

[00139] 50. The method as in any of the embodiments 32-49, wherein N_{CC} denotes the number of UL CCs linked to a single downlink (DL) CC.

[00140] 51. The method as in any of the embodiments 32-50, wherein one or a combination of n_{PHICH}^{group} , n_{PHICH}^{seq} , or n_{CI} are determined by decoding the Physical Downlink Control Channel (PDCCH) on an associated DL CC using a wireless transmit/receive unit (WTRU) specific Cell Radio Network Temporary Identifier (C-RNTI) to read Downlink Control Information (DCI) format 0 granting the Physical Uplink Shared Channel (PUSCH) transmission.

[00141] 52. The method as in any of the embodiments 32-51, wherein a PHICH arrangement parameter $N_g = 2$.

[00142] 53. The method as in any of the embodiments 32-52, wherein the value of a PHICH arrangement parameter N_g depends upon the amount of aggregated UL CCs.

[00143] 54. The method as in any of the embodiments 32-53, wherein the number of Physical Hybrid ARQ Indicator Channel (PHICH) groups is a function of the DL bandwidth.

[00144] 55. The method as in any of the embodiments 32-54, wherein a maximum number of aggregated component carriers (CCs) that can be supported when the DL bandwidth is 6 resource blocks (RBs) is 2.

[00145] 56. The method as in any of the embodiments 32-55, wherein a maximum number of aggregated component carriers (CCs) that can be supported when the DL bandwidth is 12 resource blocks (RBs) is 4.

[00146] 57. The method as in any of the embodiments 32-56, wherein a PHICH arrangement parameter $N_g = 1/4$.

[00147] 58. The method as in any of the embodiments 32-57, wherein one PHICH group is available for bandwidths (BWs) up to 25 RBs and the PHICH group cannot be divided or dedicated to different carriers.

[00148] 59. The method as in any of the embodiments 32-58, further comprising dividing the total Physical Hybrid ARQ Indicator Channel (PHICH) resources.

[00149] 60. The method as in any of the embodiments 32-59, further comprising dividing Physical Hybrid ARQ Indicator Channel (PHICH) channels into at least one division.

[00150] 61. The method as in any of the embodiments 32-60, wherein each of the at least one divisions is dedicated to a component carrier (CC).

[00151] 62. The method as in any of the embodiments 32-61, wherein the bandwidth is 5MHz.

[00152] 63. The method as in any of the embodiments 32-62, wherein a division includes dividing or combining divisions of Physical Hybrid ARQ Indicator Channel (PHICH) resources, channels, groups, or any combination thereof.

[00153] 64. The method as in any of the embodiments 32-63, wherein each division may be configured for, or assigned to, a particular carrier.

[00154] 65. The method as in any of the embodiments 32-64, wherein a wireless transmit/receive unit (WTRU) is allocated more than one resource block (RB) per component carrier (CC).

[00155] 66. The method as in any of the embodiments 32-65, further comprising a one-to-one mapping between each Physical Hybrid ARQ Indicator Channel (PHICH) resource and the physical RB (PRB) index used for each Physical Uplink Shared Channel (PUSCH) transmission.

[00156] 67. The method as in any of the embodiments 32-66, wherein on a condition that a Physical Hybrid ARQ Indicator Channel (PHICH) resource collision occurs, unused PHICH resources available in the system are utilized via modifications to the current PHICH mapping schemes.

[00157] 68. The method as in any of the embodiments 32-67, wherein the method is applied in LTE.

[00158] 69. The method as in any of the embodiments 32-68, wherein each user's assignment on each UL component carrier (CC), in terms of number of resource blocks (RBs), is greater than or equal to the number of aggregated UL CCs.

[00159] 70. The method as in any of the embodiments 32-69, wherein $L_{RBs} \geq N_{CC}$, where:

N_{CC} denotes the number of aggregated UL CCs linked to a single DL CC and

L_{RBs} is the length of contiguously or non-contiguously allocated resource blocks to a WTRU per CC.

[00160] 71. The method as in any of the embodiments 32-70, further comprising a mapping formula.

[00161] 72. The method as in any of the embodiments 32-71, wherein the mapping formula uses the following equation:

$$\begin{aligned} n_{PHICH,i}^{group} &= \left(\left(I_{PRB_RA}^{lowest_index} + \Delta_i \right) + n_{DMRS} \right) \bmod N_{PHICH}^{group} + I_{PHICH} N_{PHICH}^{group} \\ n_{PHICH,i}^{seq} &= \left(\left\lfloor \left(I_{PRB_RA}^{lowest_index} + \Delta_i \right) / N_{PHICH}^{group} \right\rfloor + n_{DMRS} \right) \bmod 2 N_{SF}^{PHICH} \end{aligned}$$

[00162] 73. The method as in any of the embodiments 32-72, wherein $I_{PRB_RA}^{lowest_index}$ is the lowest physical resource block (PRB) index in the first slot of the corresponding Physical Uplink Shared Channel (PUSCH) transmission.

[00163] 74. The method as in any of the embodiments 32-73, wherein Δ_i is a component carrier (CC) dependent offset which is applied to $I_{PRB_RA}^{lowest_index}$.

[00164] 75. The method as in any of the embodiments 32-74, further comprising linking a physical resource block (PRB) index within contiguously or non-contiguously allocated resource blocks of a wireless transmit/receive unit (WTRU) to a different component carrier (CC) in order to avoid Physical Hybrid ARQ Indicator Channel (PHICH) resource collision.

[00165] 76. The method as in any of the embodiments 32-75, wherein the linking of a PRB index within contiguously allocated resource blocks of a WTRU to a different CC is performed uniquely.

[00166] 77. The method as in any of the embodiments 32-76, wherein a parameter Δ_i takes the values $\Delta_i \in \{0, 1, \dots, N_{RB} - 1\}$.

[00167] 78. The method as in any of the embodiments 32-77, wherein a parameter Δ_i is configured and communicated to a wireless transmit/receive unit (WTRU) through higher layer signaling.

[00168] 79. The method as in any of the embodiments 32-78, wherein a parameter Δ_i is identified by a wireless transmit/receive unit (WTRU) according to a pre-determined mapping rule based on its physical resource block (PRB) allocations.

[00169] 80. The method as in any of the embodiments 32-79, wherein the mapping rule further comprises sequentially associating the PRB indices within an allocated UL grant on one of the UL component carriers (CCs) to a sequence of Physical Hybrid ARQ Indicator Channel (PHICH) resources and then transmitting the Hybrid Automatic Repeat Request (HARQ) feedbacks corresponding to multiple UL CCs using the PHICH resources.

[00170] 81. The method as in any of the embodiments 32-80, further comprising linking the PHICH resource associated with a PUSCH transmission on a UL CC to the lowest PRB index from a set of PRBs allocated to the WTRU.

[00171] 82. The method as in any of the embodiments 32-81, wherein a plurality of users are allocated a plurality of resource blocks (RBs) on each component carrier (CC) in a system with a plurality of aggregated UL CCs.

[00172] 83. The method as in any of the embodiments 32-82, wherein the users are allocated a plurality of non-contiguous RBs on a first CC and a plurality of contiguous RBs on a second CC.

[00173] 84. The method as in any of the embodiments 32-83, wherein a wireless transmit/receive unit (WTRU) receives Hybrid Automatic Repeat Request (HARQ) feedback on Physical Hybrid ARQ Indicator Channel (PHICH) resources that are linked to a first RB and a second RB for the two transport blocks that are transmitted on two specific CCs.

[00174] 85. The method as in any of the embodiments 32-84, further comprising basing the method on a network-configured solution that avoids Physical Hybrid ARQ Indicator Channel (PHICH) resource collision.

[00175] 86. The method as in any of the embodiments 32-85, wherein on a condition that Physical Hybrid ARQ Indicator Channel (PHICH) resource collisions occur, a wireless transmit/receive unit (WTRU) receives Hybrid Automatic Repeat Request (HARQ) feedback corresponding to all UL CCs except for one to be transmitted on Physical Downlink Control Channel (PDCCH).

[00176] 87. The method as in any of the embodiments 32-86, wherein an adaptive mode of operation is dictated to a number of HARQ processes while only one of the HARQ processes can be based on a non-adaptive mode of operation.

[00177] 88. The method as in any of the embodiments 32-87, wherein on a condition that PHICH resources are shared by both LTE and LTE-A WTRUs, the only available PHICH resource is assigned to the LTE WTRU.

[00178] 89. The method as in any of the embodiments 32-88, wherein a wireless transmit/receive unit (WTRU) contains one Hybrid Automatic Repeat Request (HARQ) entity which maintains a number of parallel HARQ processes.

[00179] 90. The method as in any of the embodiments 32-89, one Hybrid Automatic Repeat Request (HARQ) process is dedicated to each UL component carrier (CC).

[00180] 91. The method as in any of the embodiments 32-90, wherein the wireless transmit/receive unit (WTRU) first conducts a search for Physical Downlink Control Channel (PDCCH) Downlink Control Information (DCI) format 0/0x on the DL component carrier (CC) that initial uplink grant has been transmitted at a predetermined Transmission Time Interval (TTI) for which the Hybrid Automatic Repeat Request (HARQ) entity at the WTRU expects to receive feedback corresponding to any UL CC.

[00181] 92. The method as in any of the embodiments 32-91, wherein on a condition that UL grant addressed to the Cell Radio Network Temporary Identifier (C-RNTI) of the wireless transmit/receive unit (WTRU) is detected for a component carrier (CC), the Hybrid Automatic Repeat Request (HARQ) entity identifies a corresponding HARQ process for which a transmission has taken place and then routes the received acknowledgement (ACK)/negative acknowledgement (NACK) information to the appropriate HARQ process.

[00182] 93. The method as in any of the embodiments 32-92, wherein on a condition that no Physical Downlink Control Channel (PDCCH) Downlink Control Information (DCI) format 0/0x addressed to the Cell Radio Network Temporary Identifier (C-RNTI) of the wireless transmit/receive unit (WTRU) is detected for a given component carrier (CC), the Hybrid Automatic Repeat Request (HARQ) entity performs the method further comprising attempting to obtain feedback information transmitted in the Physical Hybrid ARQ Indicator Channel (PHICH).

[00183] 94. The method as in any of the embodiments 32-93, further comprising routing HARQ feedback to the appropriate HARQ process.

[00184] 95. The method as in any of the embodiments 32-94, wherein the C-RNTI is a Semi-Persistent Scheduling C-RNTI.

[00185] 96. The method as in any of the embodiments 32-95, wherein on a condition that for a downlink subframe, a transport block was transmitted in an associated Physical Uplink Shared Channel (PUSCH) subframe, the method further comprising delivering ACK to the higher layers on a condition that ACK is decoded on the Physical Hybrid ARQ Indicator Channel (PHICH) in the subframe.

[00186] 97. The method as in any of the embodiments 32-96, further comprising delivering NACK to the higher layers on a condition that NACK is decoded on the PHICH in the subframe.

[00187] 98. The method as in any of the embodiments 32-97, further comprising delivering an indication of the absence of PHICH to the higher layers on a condition that no PHICH was detected in the subframe.

[00188] 99. The method as in any of the embodiments 32-98, wherein wireless transmit/receive unit (WTRU) and evolved Node-B (eNB) procedures are included in Hybrid Automatic Repeat Request (HARQ) operations.

[00189] 100. The method as in any of the embodiments 32-99, further comprising the WTRU determining a n_{DMRS} parameter based on information in a most recent grant, wherein the grant comprises an assignment of a semi-persistent resource allocation.

[00190] 101. The method as in any of the embodiments 32-100, further comprising a scheduler determining that co-scheduled WTRUs on multiple UL CCs are assigned different first resource blocks as part of an initial semi-persistently scheduled PUSCH.

[00191] 102. The method as in any of the embodiments 32-101, further comprising, for a PUSCH transmission associated with a random access response grant, the scheduler configuring co-scheduled WTRUs on multiple UL CCs such that the WTRUs are assigned different first resource blocks as part of a random access response grant.

[00192] 103. A wireless transmit receive unit (WTRU) configured to perform at least part of a method of any one of the preceding embodiments.

[00193] 104. An eNodeB (eNB) configured to perform at least part of a method of any of the embodiments 1-102.

[00194] 105. An integrated circuit (IC) configured to perform at least part of a method of any of the embodiments 1-102.

[00195] Although features and elements are described above in particular combinations, one of ordinary skill in the art will appreciate that each feature or element can be used alone or in any combination with the other features and elements. In addition, the methods described herein may be implemented in a computer program, software, or firmware incorporated in a computer-readable medium for execution by a computer or processor. Examples of computer-readable media include electronic signals (transmitted over wired or wireless connections) and computer-readable storage media. Examples of computer-readable storage media include, but are not limited to, a read only memory (ROM), a random access memory (RAM), a register, cache memory, semiconductor memory devices, magnetic media such as internal hard disks and removable disks, magneto-optical media, and optical media such as CD-ROM disks, and digital versatile disks (DVDs). A processor in association with software may be used to implement a radio frequency transceiver for use in a WTRU, UE, terminal, base station, RNC, or any host computer.

*

*

*

CLAIMS

What is claimed is:

1. A method implemented at a base station for performing feedback channel resource mapping, comprising:

dividing at least one of allocated feedback channel resources or feedback channel groups; and

assigning divided feedback channel resources or feedback channel groups to uplink component carriers.

2. The method of claim 1, wherein an implicit mapping rule uses a feedback channel group number and a sequence index number to associate the divided feedback channel resources or feedback channel groups with the uplink component carriers.

3. A method implemented at a wireless transmit/receive unit (WTRU) for performing feedback channel resource mapping, comprising:

decoding a downlink control channel associated with uplink resource grant;

determining a set of dynamic parameters from a decoded downlink control channel;

receiving a set of semi-static parameters; and

distributing at least one of allocated feedback channel resources or feedback channel groups to uplink component carriers based on the set of dynamic parameters and semi-static parameters.

4. The method of claim 3, further comprising:

determining a feedback channel group number from the set of dynamic parameters and semi-static parameters;

determining a sequence index number from the set of dynamic parameters and semi-static parameters; and

associating the at least one of allocated feedback channel resources or feedback channel groups with the uplink component carriers using the feedback channel group number and the sequence index number.

5. A method implemented at a wireless transmit/receive unit (WTRU) for performing feedback channel resource mapping, comprising:

determining a feedback channel resource collision; and

determining a collision avoidance index on occurrence of a feedback channel resource collision, wherein the collision avoidance index points to unused allocated resources and links the unused allocated resources to uplink component carriers or transport blocks.

6. The method of claim 5, wherein feedback channel resource collision determination checks sameness of lowest resources allocated among the uplink component carriers.

7. The method of claim 5, further comprising:

checking that a quantity of unused allocated resources is greater than or equal to the uplink component carriers or transport blocks.

8. The method of claim 5, further comprising:

determining a feedback channel group number from at least the collision avoidance index;

determining a sequence index number from at least the collision avoidance index; and

associating the unused allocated resources with the uplink component carriers or transport block using the feedback channel group number and the sequence index number.

9. The method of claim 5, wherein the collision avoid index is configured and communicated to the WTRU through higher layer signaling.

10. The method of claim 5, wherein the collision avoid index is identified by the WTRU using a predetermined mapping rule based on resource allocations.

11. A method implemented at a base station for avoiding feedback channel resource collision, comprising:

determining a feedback channel resource collision; and

forcing an adaptive feedback channel process for each uplink component carrier having a feedback channel resource collision.

12. The method of claim 11, wherein feedback channel resource collision determination checks sameness of lowest resources allocated among an uplink component carriers.

13. The method of claim 11, wherein a non-adaptive feedback channel process is used for one uplink component carrier having a feedback channel resource collision.

14. A method implemented at a wireless transmit/receive unit (WTRU) for avoiding feedback channel resource collision, comprising:

at an expected feedback information reception time, searching for downlink control information on a downlink control channel associated with an uplink resource grant;

routing the feedback information to an identified feedback process for each component carrier upon detection of an uplink grant for a component carrier that is addressed to the WTRU; and

routing the feedback information obtained from a feedback channel to an applicable feedback process for each component carrier upon failure to detect an uplink grant.

15. A method for avoiding feedback channel resource collision for co-scheduled wireless transmit/receive units (WTRUs), comprising:

semi-persistently configuring each WTRU with an uplink transmission in a subframe; and

for each WTRU, determining a value for a parameter from a grant assigning a semi-persistent resource allocation on a condition that a downlink control channel is absent in a previous subframe, wherein the parameter is mapped to a cyclic shift of a corresponding uplink demodulation reference signal (DMRS).

16. The method of claim 15, wherein each WTRU has a different first resource block for a semi-persistently configured uplink transmission.

17. A method for avoiding feedback channel resource collision for co-scheduled users wireless transmit/receive units (WTRUs), comprising:

scheduling random access response grants to the WTRUs on multiple component carriers; and

assigning different first resource blocks to each of the WTRUs for their respective random access response grants.

18. A wireless transmit/receive unit (WTRU) configured to perform feedback channel resource mapping, comprising:

a processor configured to decode a downlink control channel associated with uplink resource grant;

the processor configured to determine a set of dynamic parameters from a decoded downlink control channel;

a receiver configured to receive a set of semi-static parameters, the processor in communication with the receiver; and

the processor configured to distribute at least one of allocated feedback channel resources or feedback channel groups to uplink component carriers based on the set of dynamic parameters and semi-static parameters.

19. A wireless transmit/receive unit (WTRU) configured to perform feedback channel resource mapping, comprising:

a processor configured to determine a feedback channel resource collision; and

the processor configured to determine a collision avoidance index on occurrence of a feedback channel resource collision, wherein the collision avoidance index points to unused allocated resources and links the unused allocated resources to uplink component carriers or transport blocks.

20. The WTRU of claim 19, wherein the processor is further configured to check that a quantity of unused allocated resources is greater than or equal to the uplink component carriers or transport blocks.