




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04N 5/455, 5/44, 7/015	A1	(11) International Publication Number: WO 95/26101 (43) International Publication Date: 28 September 1995 (28.09.95)
(21) International Application Number: PCT/US95/03155 (22) International Filing Date: 13 March 1995 (13.03.95) (30) Priority Data: 9405487.1 21 March 1994 (21.03.94) GB (71) Applicant (for all designated States except US): RCA THOMSON LICENSING CORPORATION [US/US]; Two Independence Way, Princeton, NJ 08540 (US). (72) Inventors; and (75) Inventors/Applicants (for US only): STROLLE, Christopher, Hugh [US/US]; 275 Bickley Road, Glenside, PA 19038 (US). JAFFE, Steven, Todd [US/US]; 90 Eaglenest Road, Freehold, NJ 07729 (US). (74) Agents: TRIPOLI, Joseph, S. et al.; GE & RCA Licensing Management Operation, Inc., CN 5312, Princeton, NJ 08540 (US).	(81) Designated States: BR, CN, JP, KR, MX, SG US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published With international search report. RTMP AI	

(54) Title: CARRIER RECOVERY SYSTEM FOR A VESTIGIAL SIDEBAND SIGNAL



(57) Abstract

A television signal receiver for processing an HDTV signal transmitted in a vestigial sideband (VSB) format includes input complex filters shared by a timing recovery network (30) and a carrier recovery network (50). The filter network includes a pair of upper and lower band edge filters (20, 22) mirror imaged around the upper and lower band edges of the VSB signal for producing suppressed subcarrier AM output signals. The timing recovery network includes a phase detector (28, 38, 62) and responds to an AM signal derived from the two filters (via 26) for synchronizing a system clock (CLK). The carrier recovery network (50) also includes a phase detector (54, 60, 62, 64), and responds to outputs from one or both of the filters for producing an output error signal (Δ) representing a phase/frequency offset of the VSB signal. The error signal is used to reduce or eliminate the offset to produce a recovered baseband or near baseband signal. A subsequent equalizer eliminates any residual phase offsets in the recovered signal.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

96 11389-9