

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
27 March 2003 (27.03.2003)

PCT

(10) International Publication Number
WO 03/026370 A1

(51) International Patent Classification⁷: **H05K 3/34**

CORPORATION, 3-1, Nichiden, Minakuchi-cho,
Koka-gun, Shiga 528-0034 (JP).

(21) International Application Number: PCT/JP02/09389

(22) International Filing Date:
12 September 2002 (12 09 2002)

(74) Agents: **FUKAMI, Hisao** et al., Fukami Patent Office,
Mitsui Sumitomo Bank Minamimorimachi Bldg, 1-29,
Minamimorimachi 2-chome, Kita-ku, Osaka-shi, Osaka
530-0054 (JP)

(25) Filing Language: English

(81) Designated States (*national*): CN, KR, SG, US

(26) Publication Language: English

(84) Designated States (*regional*): European patent (AT, BE,
BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT,
LU, MC, NL, PT, SE, SK, TR).

(30) Priority Data:
2001-280654 14 September 2001 (14.09.2001) JP

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(71) Applicant (*for all designated States except US*): **NEC SCHOTT COMPONENTS CORPORATION** [JP/JP],
3-1, Nichiden, Minakuchi-cho, Koka-gun, Shiga 528-0034 (JP)


(72) Inventor; and

(75) Inventor/Applicant (*for US only*): **FUKUSHIMA, Daisuke** [JP/JP], c/o NEC SCHOTT COMPONENTS

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette

162162

(54) Title: SURFACE MOUNTING PACKAGE



(57) Abstract: A surface mounting package includes a metal base (1) with a lower surface having a through hole, a metal lead (2) arranged to be inserted into the through hole, an insulating material (3) filling in an internal space defined by the metal base (1), a cap (30) covering the metal base (1) as a lid, and an electronic part component arranged at a surface (2i) on the internal space side of the metal lead (2). The internal space is held at an air-tight atmosphere. The metal base (1) has a lower surface positioned on the same plane as a lower surface of the metal lead (2) or the insulating material (3), the same plane (P) forming a plane to be attached to a mounting board.

WO 03/026370 A1