

Description

FIELD OF THE INVENTION

The present invention relates to an optical system for splitting a light beam into two orthogonally polarized subbeams and for combining said subbeams.

The invention also relates to an illumination system for an LCD projection display system comprising a light source, means for collecting the light of said light source into a beam and the said optical system.

BACKGROUND OF THE INVENTION

In illumination systems for an LCD projection display device linearly polarized light is derived from a non-polarized light source and is typically filtered to yield a linearly polarized beam. This polarized beam is directed to the light modulation device. Due to this filtering, at best, only half the light output of the light source is utilized. However, projection display systems are progressing toward systems of greater and greater brightness so as to be usable in a normally lit room. Clearly, systems that permit half of the output of the light source to go unused are inefficient.

An example of an LCD display system in which only one of the orthogonal beams is utilized is shown in the design proposed by Seiko Epson Corp. which is described in the May 12, 1986 issue of "Electronics" at page 47. This system uses an absorption polarizer which absorbs the beam of the unwanted polarization and which transmits typically only 40% of the light provided by the source.

One approach for utilizing all of the light of the light source is described in U.S. Patent No. 4,127,322 which is directed to an LCD projection television system. The system utilizes six electron beam addressed LCDS. Three LCDS are used for each beam of polarized light from a polarizing beamsplitter. The usefulness of such a system is accordingly limited by its expense and complexity.

Another approach for utilizing all of the light of the illumination system in an LCD projection television system is shown in Japanese Patent Application No. 61-122626 in which the light of the desired polarization direction is passed to the light modulating LCD. The light component of the other polarization direction is reflected by an additional mirror back towards the light source and is reflected again by the source's reflector. The returned light passes through a quarterwave plate twice so that its polarization direction is rotated 90° and thus has the same polarization of the main beam. The converted beam is thereafter passed to the light modulating LCD. However, this approach suffers from the fact

that light must pass through many air-glass interfaces and reflectors which results in an inefficient system.

SUMMARY OF THE INVENTION

The present invention is directed to an illumination system for an LCD projection display system in which the light from the undesired polarization state is converted to the desired polarization state and combined therewith in an efficient manner with a minimal number of air-glass interfaces and reflecting surfaces.

The invention provides an optical system according to the opening paragraph which is characterized by:

first means directing said first subbeam towards said second face of said prism means such that said first subbeam undergoes total internal reflection from said second face and is directed towards said third face of said prism means where it exists said prism means, and by second means directing said second subbeam through said polarization rotating means towards said second face of said prism means such that said second subbeam is refracted into said prism means and is directed toward said third face where it exits said prism means.

The present system minimizes the number of air-glass interfaces and the number of reflecting surfaces to provide a highly efficient system.

According to a second aspect the present invention relates to a new and improved illumination system which is characterized by an optical system as hereinbefore defined.

BRIEF DESCRIPTION OF THE DRAWINGS

For a better understanding of the invention reference is made to the following drawings which are to be taken in conjunction with the detailed description of the invention, in which:

Fig. 1 illustrates the geometry of the prism used to combine a first light beam with a second light beam whose polarization has been converted to the direction of the first beam;

Fig. 2 illustrates the combining prism in conjunction with the polarizing beam splitter and the reflectors forming the illumination system for an LCD projection television system; and

Fig. 3 illustrates a second embodiment of the illumination system in which the light splitting, reflection and combination elements are combined into two adjoining prisms to maximize the efficiency of the system.

DESCRIPTION OF EMBODIMENTS

An ordinary prism may be used to combine two beams which originate from one source or from different sources. Figure 1 shows an ordinary prism 10 labeled with faces A, B, and C and angles ω_A , ω_B , ω_C . If a beam of light (beam 1) is incident at Face A with an angle θ_A , it will refract into the prism with an angle θ'_A given by Snell's Law. The beam will be incident at Face B at an angle θ'_B given by

$$\theta'_B = \omega_C + \theta'_A. \quad (1)$$

If θ'_B is greater or equal to the critical angle of the prism, the beam will undergo total internal reflection (TIR) at Face B. The critical angle is defined as the smallest angle with the normal at which the beam will be totally internally reflected from a surface on which it is incident. If the beam undergoes TIR, it will be incident at Face C at an angle θ'_C given by

$$\theta'_C = \omega_A - \theta'_B \quad (2)$$

and will be refracted out of the prism with an angle θ_C which may be calculated using Snell's Law.

If a second beam of light (beam 2) is incident at Face B at an angle ϕ_B , it will refract into the prism with an angle ϕ'_B given by Snell's Law. This beam will be incident at Face C at an angle given by

$$\phi'_C = \omega_A - \phi'_B \quad (3)$$

The beam will refract out of the prism with an angle ϕ_C that also may be calculated using Snell's Law.

Polarized beams are conventionally referred to as being "S-polarized" and "P-polarized" with the P-polarized beam defined as polarized in a direction parallel to the plane of incidence and the S beam defined as polarized perpendicular the plane of incidence. The divergence δ of the two beams after exiting the prism is given by $\phi_C - \theta_C$. In most applications, δ should be minimized so that the beams are nearly collinear. In order to minimize δ , ϕ_B should be as large as possible, θ'_B should be equal to the critical angle of the prism, and ω_A should equal $(\theta'_B + \phi'_B)/2$ so that $\theta_C = -\phi_C$. If the refractive index of the prism is 1.52 and if beam 2 is p-polarized, the reflection losses at face B will be relatively small for incident angles up to 73° . If $\phi_B = 73^\circ$ and $\theta'_B = 41^\circ$ (the critical angle for $n=1.52$) then $\delta = 3.0^\circ$. By separating the centers of beams 1 and 2 at face B, the beams can be made to coincide at Face C or at any plane parallel to Face C.

Figure 2 illustrates the use of the combining prism 10 in the inventive illumination system for an LCD television projection system. Non-polarized light derived from a light source 20 is collimated by any suitable means such as a condensor lens 22 and the non-polarized beam of light 24 is directed to a polarizing beam splitter 26. The action of polarizing beam splitter 26 is to split beam 24 into a first beam 28 of the P-polarization direction which passes through beam splitter 26 and a second beam 30 of the S-polarization direction which is reflected from beam splitter 26. First beam 28 is polarized in the P direction which is the direction to be utilized by the LCD light modulation system and is directed towards prism 10 by a reflector 32. Beam 28 enters prism 10 through face A and because it impinges on face B at greater than the critical angle of prism 10 it will undergo TIR and be reflected out of prism 10 through face C.

Second beam 30 is polarized in the S direction and is reflected off polarizing beam splitter 26 towards a reflector 34. Beam 30 is polarized in the direction which is orthogonal to the direction required by the light modulating LCD. Accordingly, in order to convert S polarized beam 30 to the desired polarization direction (P direction) there is disposed between reflector 34 and prism 10 a polarization rotator 36 which rotates the polarization of beam 30 90° so that it becomes a P-polarized beam. Beam 30 is directed towards the underside of face B of prism 10 and it is refracted into prism 10 towards face C. Thus, it is seen that beams 28 and 30 exit face C of prism 10 and have the same direction of polarization. The beams may pass to further optics 38 for passage to a light modulating LCD 40 which modulates the light to form the desired image. Alternatively, light modulating LCD 40 may be disposed at the intersection of beams 28 and 30.

Polarizing beam splitter 26 may be any of the known devices. It may be, for example, composed of a dielectric thin film stack disposed on a suitable substrate. The stack may consist of alternating layers of high and low refractive index films each with a quarterwave optical thickness. At each film/film interface, light is incident at Brewster's angle which transmits P-polarized light and reflects S-polarized light. Similarly, reflectors 32, 34 may be any suitable reflecting device. However, the greater the efficiency of the reflecting device, such as by the use of metallized front surface mirrors, the greater the efficiency of the illumination system as a whole. Polarization rotation device 36 may be a number of devices known to rotate polarized light 90° . Such devices are for example, a halfwave achromatic waveplate, two quarterwave plates or a twisted nematic liquid crystal cell which rotates the plane of polarization of light passing therethrough.

Polarization rotation device 36 may be disposed at any point along the path of the beam before the prism i.e. either before or after reflector 34. Furthermore, prism 10 may alternatively be manufactured from optical quality plastic rather than glass or a liquid filled prism. Finally, if S-polarized light is desired at the output, polarization rotation 36 device can be positioned in beam 28 rather than beam 30.

Figure 3 illustrates an alternative embodiment of the projection LCD television illumination system which replaces reflectors 32 and 34 with prism faces that utilize TIR to direct beams 28 and 30 and which also utilizes one of the prisms to combine the beams. The embodiment of Figure 3 includes a prism 50 having faces D, E, F and G for directing the P-polarized beam and a prism 52 having faces H, I, J, K for directing the S-polarized beam. Disposed between face F of prism 50 and face H of prism 52 is a polarizing beam splitter 56 which may be constructed from a series of thin film quarterwave layers as described above. As can be seen from Figure 3, prism 50 replaces both mirror 32 and combining prism 10. Prism 52 replaces mirror 34 and provides a surface (face K) for mounting polarization rotator 36.

In Figure 3 the same reference numerals are used to depict the same elements as illustrated in Figure 2. Incident beam of non-polarized light 24 is directed to face I of prism 52 and is split into two orthogonally disposed polarized beams 28 and 30 by beam splitter 56. Beam 28 which is polarized in the P direction undergoes TIR at face D of prism 50 and is reflected towards face F where it again undergoes TIR and emerges out of face G of prism 50. The S-polarized beam 30 reflects off polarizing beam splitter 56 toward face J of prism 52 where it undergoes TIR and is directed toward face K of prism 52 on which polarization rotator 36 is mounted. The direction of polarization of beam 30 is rotated from S-polarization to P-polarization by rotator 36 and is directed towards face F of prism 50. Beam 30 impinges on face F of prism 50 and it refracts into prism 50 and is directed towards face G where it exits at an angle of divergence δ with beam 28 as shown in Figure 3. Thereafter the recombined beams are directed to optics 38 and LCD 40.

The embodiment of Figure 3 provides a number of advantages over the embodiment of Figure 2. Firstly, because mirrors 32 and 34 are replaced with prism surfaces which totally internally reflect light beams 30, 28 there is 100% efficiency in directing the light beams. In contrast, the reflectivity of a typical mirror is only 94%. Accordingly, the efficiency of the entire illumination system is improved. Secondly, a further improvement in efficiency results because an air/glass interface for

each of the two light beams is eliminated. Finally, any possibility of misalignment between polarizing beam splitter 26, mirrors 32, 34 and combining prism 10 is eliminated as the surfaces are defined by the fixed geometry of prisms 50, 52. Accordingly, the configuration of Figure 3 provides maximum brightness to the LCD illumination system.

Although the present invention has been described in conjunction with preferred embodiments, it is to be understood that modifications and variations may be resorted to without departing from the scope of the invention, as those skilled in the art would readily understand and which modifications and variations are considered to be within the purview and scope of the invention and the appended claims.

Claims

1. An optical system for splitting a beam of light (24) into two orthogonally polarized subbeams (28, 30) and for combining said subbeams (28, 30) comprising:
 - a) means (26) for obtaining from said beam of light (24) first and second subbeams (28, 30), each being linearly polarized, the direction of polarization of said subbeams (28, 30) being orthogonal to each other, and
 - b) means (36) for rotating the direction of polarization of one of said subbeams (30) over 90°,
 - c) prism means (10), said prism means (10) including at least first, second and third faces (A; B; C); and
 - d) first and second means (32; 34) for directing said first and second polarized subbeams (28, 30) towards said prism means (10), characterised by said first means (32) is directing said first subbeam (28) towards said second face (B) of said prism means (10) such that said first subbeam (28) undergoes total internal reflection from said second face (B) and is directed towards said third face (C) of said prism means (10) where it exits said prism means (10), and by said second means (34) directing said second subbeam (30) through said polarization rotating means (36) towards said second face (B) of said prism means (10) such that said second subbeam (30) is refracted into said prism means (10) and is directed toward said third face (C) where it exits said prism means (10).
2. An optical system as claimed in Claim 1, wherein said first and second directing means (32; 34) comprise faces (D; J) of prisms (50; 52).



Polarization rotation device 36 may be disposed at any point along the path of the beam before the prism i.e. either before or after reflector 34. Furthermore, prism 10 may alternatively be manufactured from optical quality plastic rather than glass or a liquid filled prism. Finally, if S-polarized light is desired at the output, polarization rotation 36 device can be positioned in beam 28 rather than beam 30.

Figure 3 illustrates an alternative embodiment of the projection LCD television illumination system which replaces reflectors 32 and 34 with prism faces that utilize TIR to direct beams 28 and 30 and which also utilizes one of the prisms to combine the beams. The embodiment of Figure 3 includes a prism 50 having faces D, E, F and G for directing the P-polarized beam and a prism 52 having faces H, I, J, K for directing the S-polarized beam. Disposed between face F of prism 50 and face H of prism 52 is a polarizing beam splitter 56 which may be constructed from a series of thin film quarterwave layers as described above. As can be seen from Figure 3, prism 50 replaces both mirror 32 and combining prism 10. Prism 52 replaces mirror 34 and provides a surface (face K) for mounting polarization rotator 36.

In Figure 3 the same reference numerals are used to depict the same elements as illustrated in Figure 2. Incident beam of non-polarized light 24 is directed to face I of prism 52 and is split into two orthogonally disposed polarized beams 28 and 30 by beam splitter 56. Beam 28 which is polarized in the P direction undergoes TIR at face D of prism 50 and is reflected towards face F where it again undergoes TIR and emerges out of face G of prism 50. The S-polarized beam 30 reflects off polarizing beam splitter 56 toward face J of prism 52 where it undergoes TIR and is directed toward face K of prism 52 on which polarization rotator 36 is mounted. The direction of polarization of beam 30 is rotated from S-polarization to P-polarization by rotator 36 and is directed towards face F of prism 50. Beam 30 impinges on face F of prism 50 and it refracts into prism 50 and is directed towards face G where it exits at an angle of divergence δ with beam 28 as shown in Figure 3. Thereafter the recombined beams are directed to optics 38 and LCD 40.

The embodiment of Figure 3 provides a number of advantages over the embodiment of Figure 2. Firstly, because mirrors 32 and 34 are replaced with prism surfaces which totally internally reflect light beams 30, 28 there is 100% efficiency in directing the light beams. In contrast, the reflectivity of a typical mirror is only 94%. Accordingly, the efficiency of the entire illumination system is improved. Secondly, a further improvement in efficiency results because an air/glass interface for

each of the two light beams is eliminated. Finally, any possibility of misalignment between polarizing beam splitter 26, mirrors 32, 34 and combining prism 10 is eliminated as the surfaces are defined by the fixed geometry of prisms 50, 52. Accordingly, the configuration of Figure 3 provides maximum brightness to the LCD illumination system.

Although the present invention has been described in conjunction with preferred embodiments, it is to be understood that modifications and variations may be resorted to without departing from the scope of the invention, as those skilled in the art would readily understand and which modifications and variations are considered to be within the purview and scope of the invention and the appended claims.

Claims

1. An optical system for splitting a beam of light (24) into two orthogonally polarized subbeams (28, 30) and for combining said subbeams (28, 30) comprising:
 - a) means (26) for obtaining from said beam of light (24) first and second subbeams (28, 30), each being linearly polarized, the direction of polarization of said subbeams (28, 30) being orthogonal to each other, and
 - b) means (36) for rotating the direction of polarization of one of said subbeams (30) over 90° ,
 - c) prism means (10), said prism means (10) including at least first, second and third faces (A; B; C); and
 - d) first and second means (32; 34) for directing said first and second polarized subbeams (28, 30) towards said prism means (10), characterised by said first means (32) is directing said first subbeam (28) towards said second face (B) of said prism means (10) such that said first subbeam (28) undergoes total internal reflection from said second face (B) and is directed towards said third face (C) of said prism means (10) where it exits said prism means (10), and by said second means (34) directing said second subbeam (30) through said polarization rotating means (36) towards said second face (B) of said prism means (10) such that said second subbeam (30) is refracted into said prism means (10) and is directed toward said third face (C) where it exits said prism means (10).
2. An optical system as claimed in Claim 1, wherein said first and second directing means (32; 34) comprise faces (D; J) of prisms (50; 52).



3. An optical system as claimed in Claim 1, wherein said first and second directing means (32; 34) comprise mirrors.
4. An optical system as claimed in Claim 1 wherein said first directing means (D) and said prism means (50) comprise a single prism (50).
5. An optical system as claimed in Claim 1 wherein said second directing means comprises a prism (52) having at least first and second faces (J; K), and said first face (J) of said prism functioning as said second directing means.
6. An optical system as claimed in Claim 5 wherein said second face (K) of said prism (52) mounts said polarization rotating means (36).
7. An optical system as claimed in Claim 1 wherein said means for obtaining said first and second subbeams (28, 30) comprises a polarizing beam splitter (26, 56).
8. An optical system as claimed in Claim 1 wherein said means (36) for rotating said polarization comprise a halfwave plate.
9. An optical system as claimed in Claim 1 wherein said means (36) for rotating said polarization of said second subbeam (30) comprise a twisted nematic liquid crystal cell.
10. An optical system as claimed in Claim 1, wherein said first and second directing means comprises first and second prism means (50, 52) and said means (56) for obtaining said first and second subbeams are disposed between said first and second prism means (50, 52).
11. An illumination system for an LCD projection display system comprising:
 - a) a light source (20), and
 - b) means (22) for collecting the light of said light source (20) into a beam (24);
 characterized by the optical system as claimed in Claims 1, 2, 3, 4, 5, 6, 7, 8, 9 or 10 for splitting and combining said beam (24) into said two orthogonally polarized subbeams (28, 30) and combining said subbeams into a composed beam directed at an LCD display (40).

Patentansprüche

1. Optisches System zur Aufteilung eines Lichtstrahlenbündels (24) in zwei orthogonal zuein-

ander polarisierte Teilbündel (28, 30) und zur Zusammenführung der Teilbündel (28, 30) mit

- a) Mitteln (26), um aus dem Lichtstrahlenbündel (24) erste und zweite Teilbündel (28, 30) zu erhalten, die jeweils linear polarisiert sind, wobei die Teilbündel orthogonal zueinander angeordnete Polarisationsrichtungen haben, und
 - b) Mitteln (36) zur Drehung der Polarisationsrichtung von einem der Teilbündel (30) um 90°,
 - c) Prismamitteln (10), die mindestens erste, zweite und dritte Flächen (A, B, C) umfassen, und
 - d) ersten und zweiten Mitteln (32, 34) zur Leitung des ersten und zweiten polarisierten Teilbündels (28, 30) in Richtung auf die Prismamittel (10), dadurch gekennzeichnet, daß die ersten Mittel (32) das erste Teilbündel (28) in Richtung auf die zweite Fläche (B) der Prismamittel (10) leiten, so daß das erste Teilbündel (28) der Totalreflexion an der zweiten Fläche (B) unterliegt und in Richtung auf die dritte Fläche (C) der Prismamittel (10) geleitet wird, wo es aus den Prismamitteln (10) austritt, und daß die zweiten Mittel (34) das zweite Strahlenbündel (30) durch die polarisationsdrehenden Mittel (36) in Richtung auf die zweite Fläche (B) der Prismamittel (10) leiten, so daß das zweite Strahlenbündel (30) in das Innere der Prismamittel (10) gebrochen und in Richtung auf die dritte Fläche (C) geleitet wird, wo es aus den Prismamitteln (10) austritt.
2. Optisches System nach Anspruch 1, wobei die ersten und zweiten leitenden Mittel (32, 34) Flächen (D, J) von Prismen (50, 52) umfassen.
 3. Optisches System nach Anspruch 1, wobei die ersten und zweiten leitenden Mittel (32, 34) Spiegel umfassen.
 4. Optisches System nach Anspruch 1, wobei die ersten leitenden Mittel (D) und Prismamittel (50) ein einzelnes Prisma (50) umfassen.
 5. Optisches System nach Anspruch 1, wobei die zweiten leitenden Mittel ein Prisma (52) mit mindestens ersten und zweiten Flächen (J, K) umfassen und wobei die erste Fläche (J) des Prismas die Funktion der zweiten leitenden Mittel übernimmt.
 6. Optisches System nach Anspruch 5, wobei die zweite Fläche (K) des Prismas (52) die polarisationsdrehenden Mittel (36) aufnimmt.



7. Optisches System nach Anspruch 1, wobei die Mittel zum Erhalt des ersten und zweiten Teilbündels (28, 30) einen polarisierenden Strahlenbündelteiler (26, 56) umfassen.

8. Optisches System nach Anspruch 1, wobei die Mittel (36) zur Drehung der Polarisation eine Halbwellenplatte umfassen.

9. Optisches System nach Anspruch 1, wobei die Mittel (36) zur Drehung der Polarisation des zweiten Teilbündels (30) eine verdrehte nematische Flüssigkristallzelle umfassen.

10. Optisches System nach Anspruch 1, wobei die ersten und zweiten leitenden Mittel erste und zweite Prismamittel (50, 52) umfassen und wobei die Mittel (56) zum Erhalt der ersten und zweiten Teilbündel zwischen den ersten und zweiten Prismamitteln (50, 52) angeordnet sind.

11. Beleuchtungssystem für ein LCD-Projektionswiedergabesystem mit

- a) einer Lichtquelle (20) und
- b) Mitteln (22) zur Sammlung des Lichts der Lichtquelle (20) in einem Strahlenbündel (24), dadurch gekennzeichnet, daß das optische System zur Aufteilung und Zusammenführung der Teilbündel nach einem der Ansprüche 1, 2, 3, 4, 5, 6, 7, 8, 9 oder 10 das Strahlenbündel (24) in zwei orthogonal polarisierte Teilbündel (28, 30) aufteilt und die Teilbündel zu einem zusammengesetzten und auf eine Flüssigkristallanzeige (40) gerichteten Strahlenbündel zusammenführt.

Revendications

1. Système optique permettant de scinder un faisceau de lumière (24) en deux sous-faisceaux (28, 30) polarisés dans des directions orthogonales et de combiner lesdits sous-faisceaux (28, 30), comprenant :

- a) un moyen (26) pour obtenir à partir dudit faisceau de lumière (24) un premier et un deuxième sous-faisceau (28, 30), chacun d'eux ayant une polarisation linéaire, les directions de polarisation desdits sous-faisceaux (28, 30) étant mutuellement orthogonales;
- b) un moyen (36) pour faire tourner la direction de polarisation de l'un desdits sous-faisceaux (30) de 90°;
- c) un moyen à prisme (10), ce moyen à prisme (10) comprenant au moins une première, une deuxième et une troisième face (A; B; C), et

d) un premier et un deuxième moyen (32; 34) pour diriger lesdits premier et deuxième sous-faisceaux polarisés (28, 30) vers ledit moyen à prisme (10), caractérisé en ce que ledit premier moyen (32) dirige ledit premier sous-faisceau (20) vers ladite deuxième face (B) dudit moyen à prisme (10), de telle sorte que ledit premier sous-faisceau (28) subisse une réflexion interne totale sur ladite deuxième face (B) et soit dirigé vers ladite troisième face (C) dudit moyen à prisme (10) d'où il sort dudit moyen à prisme (10), et ledit deuxième moyen (34) dirige ledit deuxième sous-faisceau (30) à travers ledit moyen de rotation de polarisation (36) vers ladite deuxième face (B) dudit moyen à prisme (10), de telle sorte que ledit deuxième sous-faisceau (30) soit réfracté dans ledit moyen à prisme (10) et soit dirigé vers ladite troisième face (C) d'où il sort dudit moyen à prisme (10).

2. Système optique selon la revendication 1, dans lequel lesdits premier et deuxième moyens directeurs (32; 34) sont constitués par des faces (D; J) de prismes (50; 52).

3. Système optique selon la revendication 1, dans lequel lesdits premier et deuxième moyens directeurs (32; 34) sont constitués de miroirs.

4. Système optique selon la revendication 1, dans lequel ledit premier moyen directeur (D) et ledit moyen à prisme (50) constituent un seul prisme (50).

5. Système optique selon la revendication 1, dans lequel ledit deuxième moyen directeur comprend un prisme (52) ayant au moins une première et une deuxième faces (J; K) et ladite première face (J) dudit prisme jouant le rôle dudit deuxième moyen directeur.

6. Système optique selon la revendication 5, dans lequel ladite deuxième face (K) dudit prisme (52) porte ledit moyen de rotation de polarisation (36).

7. Système optique selon la revendication 1, dans lequel ledit moyen permettant d'obtenir ledit premier et ledit deuxième sous-faisceau (28, 30) comprend un diviseur de faisceau de polarisation (26, 56).

8. Système optique selon la revendication 1, dans lequel ledit moyen (36) pour faire tourner ladite polarisation comprend une lame demi-



onde.

9. Système optique selon la revendication 1, dans lequel ledit moyen (36) pour faire tourner ladite polarisation dudit deuxième sous-faisceau (30) comprend une cellule à cristal liquide nématique en hélice. 5
10. Système optique selon la revendication 1, dans lequel lesdits premier et deuxième moyens directeurs comprennent un premier et un deuxième moyen à prisme (50, 52) et lesdits moyens (56) pour obtenir lesdits premier et deuxième sous-faisceaux sont disposés entre lesdits premier et deuxième moyens à prisme (50, 52). 10 15
11. Système d'illumination pour système d'affichage à projection LCD comprenant :
 - a) une source lumineuse (20), et 20
 - b) des moyens (22) pour recueillir la lumière de ladite source lumineuse (20) sous la forme d'un faisceau (24),
 caractérisé par le système optique selon l'une quelconque des revendications 1, 2, 3, 4, 5, 6, 7, 8, 9 ou 10 pour scinder et combiner ledit faisceau (24) en lesdits sous-faisceaux (28, 30) polarisés dans des directions orthogonales et pour combiner lesdits sous-faisceaux sous la forme d'un faisceau composé dirigé sur un affichage LCD (40). 25 30

35

40

45

50

55

7