



(51) International Patent Classification:

C10M 169/04 (2006.01) *C10N 30/06* (2006.01)
C10N 30/02 (2006.01)

(21) International Application Number:

PCT/US2012/044280

(22) International Filing Date:

27 June 2012 (27.06.2012)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/503,012 30 June 2011 (30.06.2011) US

(71) Applicant (for all designated States except US): **EXXON-MOBIL RESEARCH AND ENGINEERING COMPANY** [US/US]; 1545 Route 22 East, P.O. Box 900, Annandale, NJ 08801-0900 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **HABEEB, Jacob, Joseph** [US/US]; 102 East Dudley Avenue, Westfield, NJ 07090 (US). **MAZZONE, Dominick, Nicholas** [US/US]; 10 North Monroe Avenue, Wenonah, NJ 08090-1734 (US).

(74) Agents: **PURWIN, Paul, E.** et al.; Exxonmobil Research And Engineering Company, 1545 Route 22 East, P.O. Box 900, Annandale, NJ 08801-0900 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: METHOD OF IMPROVING POUR POINT OF LUBRICATING COMPOSITIONS CONTAINING POLYALKYLENE GLYCOL MONO ETHERS

(57) Abstract: Provided is a method of improving the pour point of lubricating compositions comprising in admixture a base stock selected from the group consisting of Group I, Group II, Group III, Group IV and Group V base stocks, or any combination thereof, one or more polyalkylene glycol mono ethers and one or more pour point depressant by premixing at least one polyalkylene glycol mono ether with at least one pour point depressant prior to blending the premixed polyalkylene glycol mono ethers and pour point depressant with the base stock.

