

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization

International Bureau

(43) International Publication Date
25 November 2021 (25.11.2021)



(10) International Publication Number
WO 2021/235994 A1

(51) International Patent Classification:

C09K 5/10 (2006.01) C09K 3/18 (2006.01)

(21) International Application Number:

PCT/SE2021/050462

(22) International Filing Date:

14 May 2021 (14.05.2021)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

2050574-9 17 May 2020 (17.05.2020) SE

(71) Applicant: **CFLIQUIDS AB** [SE/SE]; Götlundagatan 3,
124 71 BANDHAGEN (SE).

(72) Inventor: **WIKLUND, Per**; Marieviksgatan 45, 117 60
STOCKHOLM (SE).

(74) Agent: **NOVITAS PATENT AB**; P.O. Box 55557, 102 04
Stockholm (SE).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, IT, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, WS, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: HEAT TRANSFER FLUID

(57) Abstract: The invention relates to a fluid comprising or consisting of glycerol and potassium acetate in a weight ratio interval of 3:2 to 1:6 with a water content of 55-80 w%, wherein the combined weight of glycerol and potassium acetate constitutes 20-45 w%, up to a maximum or total of 100 w%. The inventive fluid is useful as a heat transfer fluid, a deicing fluid or a windscreen washing fluid. A method for producing the inventive fluid is also provided.



WO 2021/235994 A1