

Surface traversing vehicle

The invention is a vehicle for traversing a surface such as for carrying out an inspection, survey or maintenance operation upon that surface. For
5 example, vehicles of this type may be used to traverse a flat surface, or a space between two such surfaces, or to traverse internally or externally the length of a generally tubular conduit such as a pipe, shaft, tunnel, drain, chimney or the like, in a horizontal,
10 vertical or intermediate direction.

Vehicles and similar tools for use in carrying out operations such as inspection and maintenance of the interior of tubular conduits are known and used. Many such vehicles can be used only in conduits which
15 are horizontal or do not depart greatly from the horizontal; many of these rely upon the conduit being more-or-less uniform in cross-section throughout its length.

If a vehicle is to traverse the length of a
20 generally vertical or steeply-inclined surface, then

- 2 -

the vehicle must be able to grip the face of the surface sufficiently well to support itself, and any equipment which it is required to carry or move, against the effects of gravity, friction and any other resistance. Thus vertically-traversing vehicles are more difficult to devise and such vehicles as are available for this purpose are usually suitable for use only in tubular conduits of uniform cross-section and having diameters of a specific value or lying within a narrowly-defined range.

Few, if any, prior vehicles are suitable for carrying out exploratory or other operations other than over the interior surfaces of such uniform tubular conduits. Such vehicles are not able satisfactorily to carry out such operations even in tubular conduits of varying cross-sectional size or shape, whether or not those conduits are generally horizontal. They are also usually unsuitable for use when the inner surface of a tubular conduit has irregularities such as hollows or localised projections.

Against this background, it is an object of the present invention to provide a surface traversing vehicle which is suitable for use upon a wide variety of smooth and/or irregular surfaces, including those

- 3 -

of a wide range of generally tubular conduits of uniform or irregular cross-sectional size and/or shape and also generally planar surfaces of uniform or irregular shape, any of which surfaces may be horizontal, vertical or intermediate these directions.

The surface traversing vehicle according to the present invention comprises two bodies interconnected by means to move the bodies towards and away from each other, each said body being supported upon a multiplicity of resilient bristles extending from it. It has unexpectedly been found that alternate moving of the bodies towards and away from each other causes the vehicle to move in successive steps along a generally linear path over the surface upon which the vehicle is supported. For example, when the vehicle is placed within a tubular conduit having an average inside diameter a little less than the maximum overall dimension of the bristles measured in that diametrical direction, the vehicle traverses the length of the conduit in this way.

Subject to the foregoing features, the particular detailed form of the surface traversing vehicle according to the present invention will depend upon the general nature of the surface to be traversed. For example, the shape of the bristle-carrying bodies

- 4 -

may be generally flat when the vehicle is to be used to traverse a generally planar surface or when it is to traverse a space between two adjacent generally planar, generally parallel surfaces. For use upon or
5 within tubular conduits they may be elongate in the direction of the length of the vehicle or relatively short in that direction and are preferably rotationally symmetrical about that direction. Thus, for example, they may be generally cylindrical in
10 shape. However, they may also be non-symmetrical or irregular in shape, in order to correspond to the cross-sectional shape of the conduit upon or within which they are intended to be used.

The bristles extending from these bodies are
15 resilient and are directed generally towards the surface which is to be traversed. For example, if that surface is a single generally flat surface, then the bristles may extend generally parallel to each other in a single direction away from each of the
20 bodies. If the surface is one of a pair of such surfaces, then the bristles will normally extend in two opposite directions. When the vehicle is intended for use within a generally tubular conduit, the bristles are directed outwardly from the bodies.
25 However, the bodies may alternatively be of generally

- 5 -

annular cross-section, with the bristles directed inwardly, for use to traverse the outside of a chimney, post, cable or the like.

The bristles upon which the bodies are supported
5 may extend, when in an unstressed state, in a direction which is generally perpendicular to the surface of the body, for example radially outwardly or inwardly in the case of a generally cylindrical (including annular) body. Alternatively, the
10 bristles may be slightly inclined to that direction. They may all be mounted in mutual parallel or they may be off-set from parallel, for example in pairs of mutually inclined bristles.

When the vehicle according to the present
15 invention is in use, it is necessary for the bristles to be diverted to a greater or lesser extent from their unstressed orientation. The required resiliency of the bristles enables them to return, or to tend to return, to that unstressed orientation and
20 then, if the vehicle is to be reversed, to be diverted beyond that orientation into a new inclination in an opposite direction. The bristles may be natural bristles or may be of any other material having the desired resiliency, for example a synthetic polymeric
25 material or a metal. The material ideally displays a

- 6 -

relatively high stiffness coupled with a high rate of elasticity. When the vehicle is used to carry a relatively light load, for example a camera to inspect the surface in question, then synthetic polymeric material bristles, for example of nylon, are suitable. When better traction is required, for example when the vehicle is to tow behind it a relatively heavy load, then metal bristles, for example of steel, are preferred. Mixtures of bristles of different materials and/or of different lengths may also be used.

If, having performed the desired function, the vehicle is required to move in the reverse direction, for example to enable it to be retrieved or because it has encountered an obstruction, it is necessary for the inclination of the bristles to be reversed. This result may be achieved in any of a number of different ways. Since movement of the vehicle over a surface requires one of the bodies to remain stationary while the other moves towards or away from it, the main requirement is to reverse the inclination of the bristles on a first body, preferably that one which is rearmost during the initial forward movement of the vehicle. The vehicle may therefore be constructed with, for example, shorter bristles on the first unit, to enable more

- 7 -

ready reversal of the bristles.

As another approach to aiding reversal of the vehicle, one or more of the bodies may be constructed with retractable bristles and/or a mechanism may be provided specifically for the purpose of reversing the inclination of the bristles. As a further alternative, the vehicle may be reversed simply by pulling the whole vehicle, or just the rearmost body, backwards by a distance sufficient to cause the bristles to move to the oppositely-inclined position. This may be achieved by pulling manually upon a line attached to the vehicle, or by, say, operating a pneumatic or hydraulic cylinder included in such a line.

When, as is most operating situations, the vehicle is required to change from forward motion to rearward motion within a limited space, for example within a tubular conduit, the movement of the bristles within that space may be aided by providing means to rotate one or more of the bodies about its axis.

In one form of the present invention, the vehicle is required to traverse a single flat surface. To that end, the vehicle may be retained in contact with that surface simply by gravity. However one preferred alternative, which may then allow the

vehicle to traverse an inclined or even a vertical surface, is to provide means whereby to retain the vehicle against the surface magnetically, for example using a permanent magnet or electromagnetically.

5 The means for moving the bristle-carrying bodies towards and away from each other may take any desired form, being chosen to reflect various factors including the circumstances and/or conditions in which the vehicle is to be used. For example the means may
10 be electrically-powered by a direct electrical line or by a battery, preferably a rechargeable battery. In one preferred form of the invention, the means is a pneumatic or hydraulic cylinder, by means of which the bodies may be moved apart when operating fluid is
15 supplied to the cylinder and moved towards each other when the fluid flow is reversed.

 The linking together of the bristle-carrying bodies may be rigid or relatively so, especially when the vehicle comprises only two such bodies. However,
20 in general it is preferred that the bodies be flexibly interconnected, in particular to enable the vehicle to traverse non-linear, for example curved or angled, conduits.

 While the bodies are supported upon the bristles
25 which extend from them, some of the weight of the vehicle may be carried by one or more wheels, for

example in pairs, located upon the bodies themselves and/or upon the links, for example pneumatic cylinders, disposed between adjacent bodies. Such wheels also may provide stability to the linear movement of the vehicle, which might otherwise jack-knife in some circumstances.

The vehicle may comprise only two bristle-carrying bodies or may comprise three or more such bodies. In the latter case, it is preferred that the mutual approaching and moving apart of adjacent bodies be phased so as to lead to a sequence of such movements along the length of the vehicle, thereby smoothing out the progression of the vehicle along the conduit. However in one alternative arrangement, the bodies may be coupled together in pairs, the two bodies in each pair being coupled at a fixed distance apart, to enable the effective length of each body to be increased.

The operation of a vehicle according to the invention comprising three or more of the bristle-carrying bodies, by bringing about the relative movement of adjacent bodies in a pre-determined sequence, may be effected automatically by means of a suitable controller, which may be located upon the vehicle or remote from it; in the latter case, an electrical link from the remote location to the

- 10 -

vehicle may be by means of a direct electrical line -
or a radio link may be provided for the purpose.

When the vehicle is designed to be operated
pneumatically, an air line may be provided from a
5 remote source of compressed air to the pneumatic
cylinders. That line may be combined with an
electrical line, in the form of an umbilical linking
the remote control position to the vehicle. The
umbilical may in turn be dragged behind the vehicle by
10 means of a similar towing vehicle specifically
provided for that purpose. As the vehicle proper
moves further from the control position, supplementary
such umbilical tugs may be added. Sensors in the
line may monitor tension in the umbilical and in turn
15 prompt an umbilical tug to respond by accelerating
or decelerating briefly.

The vehicle according to the invention may be
used for a wide range of purposes in a wide number of
situations. It will most usually carry or convey a
20 tool to apply some treatment to the interior surface
of a tubular conduit, for example to clear debris or
growth therefrom, or some form of monitoring device or
instrument, for example to survey or explore the shape
or condition of such a conduit. Thus it may be used
25 in mine shafts, in chimneys, in tunnels and in pipes

- 11 -

conveying utility services such as water, electrical and gas pipelines, telecommunication lines and sewers. In other forms, it may be used to traverse the space between parallel surfaces, for example between the
5 hulls of a twin-hulled tanker or other sea-going vessel, or to survey or treat a single planar surface.

The vehicle is particularly suitable for use in hazardous environments, for example where there may be a risk of fire and/or explosion, because it does not
10 require to have any electrical or electronic components.

The invention is further described and illustrated with reference to the accompanying drawings, which illustrate, by way of example only,
15 one simple embodiment of the vehicle according to the present invention and wherein:

Fig. 1 is an elevation of the vehicle; and

Figs. 2 to 4 show, to a smaller
20 scale, three successive positions of the vehicle in use within a pipe.

The illustrated vehicle comprises two short generally cylindrical bodies 10, 11, linked together by a pneumatic cylinder 12, to which the two bodies
25 are pivotally coupled at 13 and 14 respectively.

- 12 -

Each of the bodies has a substantial number of resilient bristles 15 extending radially outwardly from around its curved surface.

5 Figs. 2 to 4 show how the vehicle is able to progress, from right to left as illustrated, along a pipe 16, only a short part of the length of which is illustrated. The vehicle is introduced to the pipe at its right-hand end 17 and, since the inside diameter of the pipe 16 is somewhat less than the
10 maximum overall lateral diameter of the vehicle between the ends of the bristles 15, the bristles adopt a position in which they are curved and inclined towards the right, at an average angle of the order of between 15 and 45 degrees.

15 In order to advance the vehicle along the pipe in the direction of the arrow 18, air is introduced into the cylinder 12 and the bodies 10, 11 are thereby urged apart. The orientation of the bristles on the body 11 resists rearward movement of that body and the
20 body 10 is therefore thrust forwards, the rearwardly-directed bristles thereon offering less resistance to that motion, so that the bodies adopt the positions shown in Fig. 3. Upon subsequent evacuation of the cylinder 12 (Fig. 4), the body 11 is drawn forwards
25 towards the body 10 until the cylinder is fully

retracted as shown. As will readily be understood,
alternate extension and retraction of the cylinder
thus causes the vehicle to advance, progressively and
stepwise, through the pipe 16 in the direction of the
5 arrow 18.

In experimental use, the illustrated vehicle has
been shown to be able to advance vertically,
horizontally and at intermediate inclinations along a
tubular conduit and to take with it loads
10 substantially greater than its own weight.



WO 97/11307

PCT/GB96/02307

- 14 -

CLAIMS

1. A surface traversing vehicle characterised in that it comprises two bodies (10, 11) interconnected by means to move the bodies towards and away from
5 each other, each said body being supported upon a multiplicity of resilient bristles (15) extending from it.
2. A surface traversing vehicle according to Claim 1, characterised in that each body is generally flat.
- 10 3. A surface traversing vehicle according to Claim 2, characterised in that the bristles (15) extend from a single flat face of each body.
4. A surface traversing vehicle according to Claim 3, characterised by means to retain the vehicle against
15 a surface magnetically.
5. A surface traversing vehicle according to Claim 2, characterised in that the bristles (15) extend in opposite directions from opposite flat faces of each body.
- 20 6. A surface traversing vehicle according to Claim 1, characterised in that each body (10, 11) is rotationally symmetrical about the length of the vehicle.



WO 97/11307

PCT/GB96/02307

- 15 -

7. A surface traversing vehicle according to Claim 6, characterised in that each body (10, 11) is generally cylindrical and the bristles (15) extend outwardly from the bodies.

5 8. A surface traversing vehicle according to Claim 6, characterised in that each body (10, 11) is of generally annular cross-section and the bristles (15) extend inwardly from the bodies.

9. A surface traversing vehicle according to any
10 of the preceding claims, characterised in that the bristles (15) extend generally perpendicular to the surface of the body (10, 11), or slightly inclined to that direction.

10. A surface traversing vehicle according to any
15 of the preceding claims, characterised in that the bristles (15) are mounted off-set from mutual parallel.

11. A surface traversing vehicle according to any
of the preceding claims, characterised in that the bristles (15) are natural bristles or of a synthetic
20 polymeric material or a metal.

12. A surface traversing vehicle according to Claim 11, characterised in that the bristles (15) are of nylon or steel.



WO 97/11307

PCT/GB96/02307

- 16 -

13. A surface traversing vehicle according to any of the preceding claims, characterised in that the bristles (15) are of different materials and/or of different lengths.
- 5 14. A surface traversing vehicle according to any of the preceding claims, characterised by retractable bristles and/or a mechanism for reversing the inclination of the bristles.
- 10 15. A surface traversing vehicle according to any of Claims 1 to 13, characterised by a line which includes a pneumatic or hydraulic cylinder to enable movement of the vehicle to be reversed.
- 15 16. A surface traversing vehicle according to any of the preceding claims, characterised by means to rotate one or more of the bodies (10, 11) about its axis.
- 20 17. A surface traversing vehicle according to any of the preceding claims, characterised in that the means to move the bodies towards and away from each other is electrically powered.
18. A surface traversing vehicle according to any of Claims 1 to 16, characterised in that the means (12) to move the bodies towards and away from each other is a pneumatic or hydraulic cylinder.



WO 97/11307

PCT/GB96/02307

- 17 -

19. A surface traversing vehicle according to any of the preceding claims, characterised in that the bodies are flexibly interconnected (13, 14).

20. A surface traversing vehicle according to any
5 of the preceding claims, characterised by having one or more wheels located upon the bodies and/or upon the links between adjacent bodies.

21. A surface traversing vehicle according to any of the preceding claims, characterised in that it
10 comprises more than two said bodies (10, 11), coupled together in pairs at a fixed distance apart.

22. A surface traversing vehicle according to any of Claims 1 to 20, characterised in that it comprises three or more said bodies (10, 11), each interconnected
15 (12, 13, 14) for movement towards and away from the adjacent body or bodies.

23. A surface traversing vehicle according to Claim 22, characterised in that relative movement of adjacent bodies (10, 11) is effected automatically by means
20 of a controller.

24. A surface traversing vehicle according to any of the preceding claims, characterised by an umbilical linking the vehicle to a remote control position.



WO 97/11307

PCT/GB96/02307

- 18 -

25. A surface traversing vehicle according to Claim 24, characterised by having a similar vehicle for towing the umbilical.

26. A surface traversing vehicle according to Claim 5 25, characterised by having one or more sensors to monitor tension in the umbilical.