



(43) International Publication Date
25 April 2013 (25.04.2013)

(10) International Publication Number
WO 2013/058709 A2

(51) International Patent Classification:
B32B 3/30 (2006.01)

(21) International Application Number:
PCT/SG2012/000385

(22) International Filing Date:
15 October 2012 (15.10.2012)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
201107612-2 18 October 2011 (18.10.2011) SG

(72) Inventor; and

(71) Applicant : CHEW, Yi Xin [SG/SG]; 3A, Siglap Terrace,
Singapore 455829 (SG).

(74) Agent: CHONG, Y F; P. O. Box 0399, PSA Building,
Singapore 911144 (SG).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,
BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,

HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP,
KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD,
ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI,
NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU,
RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ,
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA,
ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ,
UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).


Declarations under Rule 4.17:

— of inventorship (Rule 4.17(iv))

Published:

— without international search report and to be republished
upon receipt of that report (Rule 48.2(g))

(54) Title: PACKAGING MATERIAL, PACKAGE PRODUCED THEREFROM AND METHOD FOR CONSTRUCTING THE PACKAGE



(57) Abstract: The present invention provides packaging material for making packages, comprising a breakable film; and a substrate on which the breakable film is positioned, wherein the substrate comprises a chemically resistant and non-heat sealable (NHS) layer having a first surface and a second surface, and a heat sealable (HS) layer bonded to the first surface of the NHS layer, and the breakable film is laminated onto the second surface of the NHS layer, and wherein at least one die cut line to define a preformed hole is formed through the NHS and HS layers. The invention also provides a package produced therefrom and a method for constructing the package.



WO 2013/058709 A2