

Description

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a tubular protective device or condom-like device for protection against the transfer of infectious matter during sexual intercourse. Specifically, the invention relates to a thin-walled tubular protective device having a closed end and an open end wherein the open end has an outwardly extending portion with means for keeping the open end radially stretched.

2. Description of the Background Art

Condoms, besides being contraceptives, offer protection during sexual intercourse against the transfer of infectious matter such as bacterial and viral microbes that cause venereal diseases. After the appearance of AIDS great efforts have been made by various health authorities to impel people to increase the use of condoms during sexual intercourse in order to prevent the spread of this fatal disease.

Condoms comprise a thin tubular casing, that is typically manufactured from latex and that has an open end and a closed end. Condoms are drawn over the penis before coitus. The casing has an inner diameter that is adapted to allow the condom to fit tightly on the penis. At the open end of a condom an elastic, flexible ring or rolled portion of latex is usually provided. This ring portion is the same diameter as the tubular casing of the condom. This elastic ring portion serves primarily to secure the condom on the penis and to prevent leakage of semen from the interior of the condom. Such elastic ring portions contract the open end of a condom onto the penis and do not radially extend the open end of the condom.

It is generally accepted that the AIDS virus can only be transferred through contact with the carrier's blood or blood plasma. During sexual intercourse such a transfer of the AIDS virus occurs when lesions of the carrier contact the mucous membrane or skin of the carrier's partner. Such a transfer of the AIDS virus is especially likely to occur around the root or base of the penis and the vulva. There is a risk that lesions in these areas can be caused to bleed during sexual intercourse. When using a standard condom, these areas are unprotected or unshielded by the condom and consequently a condom does not offer full protection against the transfer of infectious matter such as the AIDS virus.

Numerous attempts have been made to design a condom or condom-like device that provides

effective contraception and/or more protection against the transfer of infectious matter than the standard condom. A sampling of these attempts are described below.

U.S. Patent Number 4,004,591 to Freemark discloses a birth control device. This birth control device is a female condom made of a strong rubber, plastic, or other similar material. This condom has a rigid, ring-like rim that is bent or scalloped. This rim can be a wire. The rim is not adapted to radially extend the open end of this device because this device is a hard molded material and not flexible. The cross-sectional dimensions of this condom are disclosed as being sufficiently large to easily accommodate the average male width with some additional clearance space. The primary function of this device is to prevent unwanted pregnancy. This device is useful in preventing the spread of venereal disease. This device provides no means to prevent an exchange between partners of secreted fluids that may contain venereal disease. Additionally, this birth control device is intended for use by females, but includes no means to secure or maintain the device in the vagina.

U.S. Patent Number 4,630,602 to Strickman et al. discloses a disposable contraceptive cervical barrier. The cervical barrier of this invention is similar to standard diaphragms in size and design. This cervical barrier contains various "cavities for cells" that can hold spermicidal lubricants. These spermicidal lubricants can also be placed in numerous grooves within the body of the cervical barrier. Urethane polymers are used to make the device. The cervical barrier of this invention, unlike a condom, has no tubular side walls to prevent the exchange between partners or secretions that can contain a venereal disease.

U.S. Patent Number 3,536,066 to Ludwig discloses a human birth control appliance. The appliance of this patent protects both partners from any dermic contact. This device is large and awkward to use.

U.S. Design Patent Number 254,808 to Meldahl discloses a design for a male contraceptive. This contraceptive appears to be larger in diameter than the average condom, but this contraceptive has no means at its open end to aid in the prevention of the spread of venereal disease.

DE-C-210413 discloses a tubular protective device for the transfer of infectious matter during sexual intercourse, comprising a flexible thin-walled tube (b) said flexible thin-walled tube having a closed end and an open end with the open end having a means (a) for radially extending the open end.

The industry is lacking a simple, easy-to-use device that provides protection against the transfer

of body fluids between partners during sexual intercourse, especially between the base of the penis and the vulva.

SUMMARY OF THE INVENTION

A tubular protective device as set forth with reference to DE-C-210413 is characterised in that the thin-walled tube (1) has a sufficiently large diameter to permit movement of a penis within the tube during coitus and a means for retaining (5) is provided at the closed end of the flexible thin-walled tube said means for retaining, maintaining said closed end in a vagina of a user.

Thus by providing a thin-walled flexible tube with means for retaining the position of the tube at both ends relative to the vagina, the diameter of the tube can be chosen so as to permit movement of a penis with in said tube during coitus, the tube being properly retained in place.

The various preferred embodiments of the invention may be as set forth in the sub-claims.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a three dimensional view of the protective device of this invention.

Figure 2a is a three dimensional front view of the invention that is adapted to function as a female condom-like or protective device.

Figure 2b is a three dimensional side view of the protective device of Figure 2a.

Figure 3 is a top plan view of a closed end or internal ring for use with the protective device of Figure 1.

Figure 4a is a three dimensional front view of the protective device of Figure 1 with the closed end or internal ring of Figure 3 inserted therein.

Figure 4b is a three dimensional side view of the protective device of Figure 1 with the closed end or internal ring of Figure 3 inserted therein.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

The invention is a tubular protective device for protection against a transfer of infectious matter during sexual intercourse. The device comprises a flexible, thin-walled tube closed at one end and open at a second end. The open end has a collar-shaped, outwardly extending portion and a means for radially stretching the collar-shaped portion or open end. The device has an inner diameter of sufficiently large dimension to permit movement of a penis with respect to the protective device during sexual intercourse. Besides protecting against a transfer of infectious matter, the protective device is a contraceptive and, due to the presence of the

collar-shaped portion of the device, the contraceptive effect is even more efficient than that obtained with standard condoms because of the additional protection provided around the vulva.

The invention is based on the discovery that a particularly good protection against the transfer of infectious matter, and especially the AIDS virus, is obtained if a condom-like or tubular protective device is used during sexual intercourse that has at its open end an outwardly extending collar that is connected to a rigid ring-like means. The ring-like means is adapted to maintain the collar of the device in a radially extended or stretched condition. The collar is preferably of a dimension that covers the vulva completely. The tubular protective device desirably has a sufficiently large inner diameter to allow movement of a penis with respect to the walls of the tubular device. The walls of the tubular device are held in a relatively immovable state or condition against the vaginal wall. The collar covering the vulva is, also, essentially immovable with respect to the vulva during coitus.

The flexible, thin-walled tube of the invention is desirably cylindrical in shape and has an open end and a closed end. The tube is preferably made from a natural or synthetic polymer material. Desirable polymer materials are members selected from the group consisting of latex, polyethylenes, polyurethanes, and derivatives based upon these polymers. The preferred material is a polyether polyurethane that has a soft, nonadhesive "hand feel". Other polymers or plastics such as polyolefins can be used to manufacture the tube of this device.

The tube of this device can be manufactured by numerous methods that are standard within the industry that fabricates items from polymer materials. The particular method chosen to manufacture the device of this invention varies with the particular polymer material chosen. An acceptable method of manufacturing the device can include curing a polymer material, such as latex, on a mold that has been dipped into a container of heated, liquified polymer material. Other methods can include either vacuum forming or blow molding a sheet of heated polymer material into or onto a mold. Vacuum forming and blow molding are desirable with synthetic polymer materials such as polyurethanes.

The preferred method for manufacturing the device, when it is made of a synthetic polymer such as polyurethane, is to heat seal two layered sheets of the polymer material together to form the desired shape of the device. Heat sealing methods can be undesirable if caution is not exercised during the process. This is because these methods can leave hardened seams that can potentially irritate skin and mucous membrane surfaces. Addi-

tionally, the seams are subject to leakage and tearing if the heat sealing method is performed at an undesirably high temperature. Heat sealing methods, however, are desirable because the sheets of polymer material is not stretched during the manufacturing of the device and a consistent wall thickness for the device can be obtained.

The wall thickness of the condom-like device can vary greatly. Typically, thinner wall thicknesses for the device allow more sensitivity during coitus. Wall thicknesses can be varied depending upon the strength of the polymer material that is chosen for the device. Preferably, a wall thickness for the device is between 20 and 60 microns (μm) for synthetic materials such as polyurethanes and 30 to 90 microns for natural materials such as latex. A wall thickness, regardless of the material from which the device is manufactured, must provide a tensile strength of at least 17 MPa when tested less than 12 months after manufacture and at least 15 MPa when tested 12 months or more after manufacture in order to comply with the standards of the American Society for Testing and Materials.

The internal or inner diameter of the tubular protective device in its unstretched state is desirably of a sufficiently large dimension to permit movement of a penis with respect to the protective device during sexual intercourse. The invention can have an inner diameter that causes the condom to be form fitting, but form fitting condom devices do not permit adequate sensitivity for the male during sexual intercourse. This is because a form fitting condom moves with the penis and prevents direct contact between the vaginal wall and the glans area during intercourse. This undesirable effect of form fitting condoms discourages their use by many members of the public. A condom-like device having a large inner diameter merely functions as a barrier for the vaginal wall. In this situation the device is relatively stationary to the vaginal wall and the glans is in direct contact with the surface against which it is moving. This structural arrangement, wherein the inner diameter of the condom-like device is larger than a penis, provides greater sensitivity for both partners.

Desirably any diameter of the tube below the outwardly extending collar-shaped means for radially stretching the open end or such as an elastic ring is smaller than a second diameter of the means for radially stretching the open end and the first diameter is sufficiently large to permit movement of a penis within the tube during sexual intercourse.

Standards within the industry for condoms, typically, do not define the inner diameter of a condom, but define the acceptable width of the condom when it is laid flat on a surface. A condom having a width of about 47 millimeters to about 51

millimeters is considered, within the industry, to be form fitting. Contoured or loose fitting condoms have a width of about 50 millimeters to about 54 millimeters. For this invention an acceptable width is at least about 50 millimeters in an unstretched state along the entire length of the tube. A desirable range for the width of the condom-like device of this invention is between about 55 millimeters and about 85 millimeters.

The collar-shaped, outwardly extending portion of the protective device has a means for radially stretching or extending the collar, such as a ring. Furthermore, the ring serves to prevent the open end of the tubular protective device from being pushed into the vagina during sexual intercourse.

The means for extending the collar is desirably a semirigid ring or ring-like member. In the most desirable embodiments of the invention, the ring is manufactured from a suitable plastic as a separate part. The invention can be made wherein the means for extending the collar is integrally formed from the same material from which the walls of the device are formed. Such a structure can be formed by rolling the polymer material that forms the walls of the device from the open end of the tube so as to form a ring of material. This ring of material can be maintained by heating the ring or using an adhesive to maintain the ring and prevent it from unrolling.

The diameter of the means for radially stretching the collar is desirably large enough to prevent the exchange of secretions between partners during sexual intercourse. The diameter of the means for radially stretching the collar is desirably large enough such that the vulva and the base of the penis are covered by the extended collar. The preferred embodiments of the invention have a first diameter for the tube of the device and a second diameter for the means for radially stretching the collar such as an elastic ring wherein the second diameter is larger than the first diameter. Acceptable diameters for the means for radially stretching the collar of the device are at least about 50 millimeters and desirably between about 60 and about 75 millimeters. Preferably, the collar is conically shaped and when a tubular protective device having an inner diameter of approximately 50 millimeters is used, the collar, supported by the means for radially stretching, preferably has an inner diameter of approximately 75 millimeters.

Insertion into the vagina of the tubular device of the invention can be done by either the man or the woman. The device can be inserted in the traditional manner by the male partner placing the device over the penis before coitus. The female partner can insert the device with a finger or by means of a insertion probe or applicator.

In order to prevent the tubular protective device from unintentionally slipping out of the vagina once inserted by the female partner has occurred, a means for retaining the device in the vagina such as a circular elastic member or an elastic ring can be used. This member or ring can be connected to the internal or external wall at or near the closed end of the device. After being placed correctly in the vicinity of the uterus, the circular elastic member or an elastic ring is maintained within the vagina in the same manner as a diaphragm.

In order to facilitate insertion of the tubular protective device into the vagina, the closed end of the device can be enclosed by a sheathing which is axially movable relative to the protective device. During the insertion of the protective device into the vagina, the sheathing is moved backwards and, thus it opens for insertion of the closed end of the protective device. Such a sheathing is not typically present if a means for retaining the device in the vagina such as an elastic ring is present.

Prior to or in connection with the insertion of the tubular protective device, a lubricant is preferably applied to at least the inner side of the device to reduce friction during contact with the penis. If desired, a lubricant can also be applied to the exterior side of the device. Application of a lubricant to the inner side of the tubular protective device can facilitate the insertion of the device into the vagina. Selection of a desirable lubricant can vary greatly. The selection of a lubricant depends in part upon the compatibility of the lubricant with the polymer material used to manufacture the device. Desirable lubricants can include ointments, creams, or water-based mucilages or mucilage-like substances such as cellulose-based lubricants.

The invention is described in more detail with reference to the figures which show desirable embodiments of both the male and female tubular protective devices according to the invention.

Figure 1 discloses a thin-walled tubular device 1 having a closed end 2 that is rounded. At the end of the thin-walled tubular device 1 that is opposite to the closed end 2, the thin-walled tubular device 1 continues into a conically-shaped collar 3 ending in an elastic ring 4. The composition and dimensions of the elastic ring 4 are adapted such that the collar 3 is stretched and maintained in a stretched condition. The flexible material used to form the thin-walled tubular device 1 of this embodiment overlaps or encapsulates the elastic ring 4. The thin-walled tubular device of this figure functions as a male condom-like device.

Figure 2a discloses a front view of a thin-walled tubular device 1 having a closed end 2, that is rounded, and a collar 3 that is stretched by an

elastic ring 4. At the rounded end 2 the thin-walled tubular device 1 a second elastic ring 5 is located and held in position by a means for affixing the ring 6. In this figure the means for affixing the ring is a small square of flexible material that is affixed on two of its edges to the thin-walled tubular device 1. In this manner the small square of flexible material is adapted to allow the second elastic ring 5 to pass freely through an open passage between the center of the square of flexible material and the thin-walled tubular device 1 that is covered by the square of flexible material 6. The means for affixing the ring serves to maintain the thin-walled tubular device 1 in the vagina. The thin-walled tubular device of this figure functions as a female condom-like device.

In Figure 2a the tubular element 1 can be enclosed at the closed end by a thin cylindrical sheathing (not shown) which is axially movable in relation to the tubular element 1. However, the tubular protective device does not ordinarily have both a sheathing and a second elastic ring 5 at the same time.

Figure 2b discloses a side view of the thin-walled tubular device 1 of Figure 2a. In this figure the structural and spatial arrangement at the closed end 2 of the second ring 5 and the square of flexible material 6 is depicted so as to illustrate the passage through which the second ring 5 is free to move. The second ring 5 in this embodiment is not in a planar position that is parallel to the planar position of the first ring 4. This planar position of the second ring 5 is at an acute angle to the planar position of the first ring 4 in this embodiment because the opening of the uterus is positioned at a similar angle to the vulva.

The diameter of the internal or second ring 5 is typically smaller than the diameter of the first ring 4. The diameter of the second ring 5 can vary to include any size that can adequately maintain the closed end 2 in the vagina. In this manner the female condom-like device can be inserted into the vagina and worn for a significant period of time before coitus. Desirable outer diameters for the second ring 5 are those typically used for diaphragms which are between about 65 millimeters and 80 millimeters.

Figure 3 is a top plan view of the internal of second ring 5 of Figure 2b. In desirable embodiments of the invention the second ring 5 is not attached to the flexible wall of the thin-walled tubular device 1. In such embodiments the thin-walled tubular device of Figure 1 can be provided with, but separately from, the second ring 5. In this manner the invention can be adapted for use either as a male or female condom-like device after its purchase. The thin-walled tubular device 1 can be used as a male condom-like device without a

second ring 5. The thin-walled tubular device 1 can be adapted for use as a female condom-like device by inserting the second ring 5 into the closed end 2 of the thin-walled tubular device 1.

Figure 4a depicts a front view of the thin-walled tubular device 1 of Figure 1 with the internal or second ring 5 of Figure 3 inserted into the closed end 2. This represents the preferred embodiment of the invention. The second ring 5 is inserted into the closed end 2 by squeezing it to form an oval shape and then inserting the second ring 5 into the thin-walled tubular device 1. When the second ring 5 is released, it regains its circular shape. When the second ring 5 is in place, the thin-walled tubular device 1 can be inserted into the vagina by using the second ring 5 to function in a manner similar to a diaphragm.

Figure 4b depicts a side view of the thin-walled tubular device 1 of Figure 1 with the internal second ring 5 of Figure 3 inserted into the closed end 2.

Claims

1. A tubular protective device for protection against the transfer of infectious matter during sexual intercourse, comprising a flexible thin-walled tube (1) which has a closed end and an open end with the open end having a means (4) for radially extending the open end, characterised in that the thin-walled tube (1) has a sufficiently large diameter to permit movement of a penis within the tube during coitus and a means for retaining (5) is provided at the closed end of the flexible thin-walled tube, said means for retaining, maintaining said closed end in a vagina of a user.
2. A tubular protective device according to Claim 1, characterised in that the open end is conically shaped.
3. A tubular protective device according to Claim 1 or Claim 2 characterised in that the flexible thin-walled tube is a polymer material, for example, latex, polyethylenes, polyurethanes and derivatives thereof.
4. A tubular protective device according to any one of Claims 1 to 3, characterised in that the means (4) for radially extending the open end is an elastic ring integrally connected with the said open end.
5. A tubular protective device as claimed in any one of Claims 1 to 4, characterised in that the closed end is enclosed by a sheathing which is axially movable relative to the protective device.
6. A tubular protective device according to any one of the preceding Claims, characterised in that the means for retaining (5) is an outwardly extending planar ring-shaped means.
7. A tubular protective device according to Claim 6, characterised in that the means for retaining (5) is an elastic ring, the elastic ring being removably insertable into said closed end.
8. A tubular protective device according to Claim 1, characterised in that the open end has a collar-shaped, outwardly extending portion and the means (4) for radially extending the said open end comprises means for radially stretching the collar-shaped portion having a second diameter larger than the said first diameter.
9. A tubular protective device according to Claim 8, characterised in that the means for radially stretching said open end is an elastic ring (4).
10. A tubular protective device according to Claim 8 or Claim 9, characterised in that the means for retaining (5) is an outwardly extending planar ring-shaped means.
11. A tubular protective device according to Claim 10, characterised in that the means for retaining (5) is an inner elastic ring, said inner elastic ring being removably insertable into the closed end.
12. A tubular protective device according to Claim 10, characterised in that there is provided a means (6) for affixing said means for retaining (5) to said flexible, thin-walled tube.
13. A tubular protective device as claimed in Claim 8, characterised in that the tube has a first diameter, the means for radially stretching (4) has a second diameter wherein said first diameter of the tube is smaller than the second diameter of the means for radially stretching and the first diameter is sufficiently large to permit movement of a penis within the tube during coitus.
14. A tubular protective device according to Claim 13, characterised in that the means for radially stretching the open end is an elastic ring (4).
15. A tubular protective device of Claim 14, characterised in that the outwardly extending planar ring-shaped means is a second elastic



second ring 5. The thin-walled tubular device 1 can be adapted for use as a female condom-like device by inserting the second ring 5 into the closed end 2 of the thin-walled tubular device 1.

Figure 4a depicts a front view of the thin-walled tubular device 1 of Figure 1 with the internal or second ring 5 of Figure 3 inserted into the closed end 2. This represents the preferred embodiment of the invention. The second ring 5 is inserted into the closed end 2 by squeezing it to form an oval shape and then inserting the second ring 5 into the thin-walled tubular device 1. When the second ring 5 is released, it regains its circular shape. When the second ring 5 is in place, the thin-walled tubular device 1 can be inserted into the vagina by using the second ring 5 to function in a manner similar to a diaphragm.

Figure 4b depicts a side view of the thin-walled tubular device 1 of Figure 1 with the internal second ring 5 of Figure 3 inserted into the closed end 2.

Claims

1. A tubular protective device for protection against the transfer of infectious matter during sexual intercourse, comprising a flexible thin-walled tube (1) which has a closed end and an open end with the open end having a means (4) for radially extending the open end, characterised in that the thin-walled tube (1) has a sufficiently large diameter to permit movement of a penis within the tube during coitus and a means for retaining (5) is provided at the closed end of the flexible thin-walled tube, said means for retaining, maintaining said closed end in a vagina of a user.

A tubular protective device according to Claim 1, characterised in that the open end is conically shaped.

3. A tubular protective device according to Claim 1 or Claim 2 characterised in that the flexible thin-walled tube is a polymer material, for example, latex, polyethylenes, polyurethanes and derivatives thereof.

4. A tubular protective device according to any one of Claims 1 to 3, characterised in that the means (4) for radially extending the open end is an elastic ring integrally connected with the said open end.

5. A tubular protective device as claimed in any one of Claims 1 to 4, characterised in that the closed end is enclosed by a sheathing which is axially movable relative to the protective de-

vice.

6. A tubular protective device according to any one of the preceding Claims, characterised in that the means for retaining (5) is an outwardly extending planar ring-shaped means.

7. A tubular protective device according to Claim 6, characterised in that the means for retaining (5) is an elastic ring, the elastic ring being removably insertable into said closed end.

8. A tubular protective device according to Claim 1, characterised in that the open end has a collar-shaped, outwardly extending portion and the means (4) for radially extending the said open end comprises means for radially stretching the collar-shaped portion having a second diameter larger than the said first diameter.

9. A tubular protective device according to Claim 8, characterised in that the means for radially stretching said open end is an elastic ring (4).

10. A tubular protective device according to Claim 8 or Claim 9, characterised in that the means for retaining (5) is an outwardly extending planar ring-shaped means.

11. A tubular protective device according to Claim 10, characterised in that the means for retaining (5) is an inner elastic ring, said inner elastic ring being removably insertable into the closed end.

12. A tubular protective device according to Claim 10, characterised in that there is provided a means (6) for affixing said means for retaining (5) to said flexible, thin-walled tube.

13. A tubular protective device as claimed in Claim 8, characterised in that the tube has a first diameter, the means for radially stretching (4) has a second diameter wherein said first diameter of the tube is smaller than the second diameter of the means for radially stretching and the first diameter is sufficiently large to permit movement of a penis within the tube during coitus.

14. A tubular protective device according to Claim 13, characterised in that the means for radially stretching the open end is an elastic ring (4).

15. A tubular protective device of Claim 14, characterised in that the outwardly extending planar ring-shaped means is a second elastic



ring, said second elastic ring being removably insertable into the closed end.

16. A tubular protective device according to Claim 15, wherein the second ring is affixed (6) to said flexible, thin-walled tube.
17. A tubular protective device according to Claim 13, wherein said ring-shaped means is adapted for radially stretching said closed end, whereby to retain the closed end in a vagina during coitus.
18. A tubular protective device according to Claim 16, characterised in that there is further provided a means for affixing the ring-shaped means to the said flexible thin-walled tube.

Patentansprüche

1. Schlauchförmige Schutzvorrichtung zum Schutz vor Übertragung von infektiösen Stoffen beim Geschlechtsverkehr, welche einen flexiblen, dünnwandigen Schlauch (1) aufweist, der ein geschlossenes Ende und ein offenes Ende hat, wobei das offene Ende eine Einrichtung (4) zur radialen Erweiterung des offenen Endes hat, **dadurch gekennzeichnet**, daß der dünnwandige Schlauch (1) einen so ausreichend großen Durchmesser hat, daß eine Bewegung eines Penis in dem Schlauch während des Geschlechtsverkehrs möglich ist, und daß eine Halteeinrichtung (5) an dem geschlossenen Ende des flexiblen, dünnwandigen Schlauches vorgesehen ist, wobei diese Einrichtung das geschlossene Ende in einer Vagina eines Benutzers festlegt und festhält.
2. Schlauchförmige Schutzvorrichtung nach Anspruch 1, **dadurch gekennzeichnet**, daß das offene Ende konisch ausgebildet ist.
3. Schlauchförmige Schutzvorrichtung nach Anspruch 1 oder Anspruch 2, **dadurch gekennzeichnet**, daß der flexible, dünnwandige Schlauch aus einem Polymermaterial, wie beispielsweise Latex, Polyethylen, Polyurethan und Derivate hiervon, hergestellt ist.
4. Schlauchförmige Schutzvorrichtung nach einem der Ansprüche 1 bis 3, **dadurch gekennzeichnet**, daß die Einrichtung (4) zum radialen Erweitern des offenen Endes ein elastischer Ring ist, welcher einteilig mit dem offenen Ende verbunden ist.
5. Schlauchförmige Schutzvorrichtung nach einem der Ansprüche 1 bis 4, **dadurch ge-**

kennzeichnet, daß das geschlossene Ende von einer Umhüllung umgeben ist, welche relativ zu der Schutzvorrichtung axial beweglich ist.

6. Schlauchförmige Schutzvorrichtung nach einem der vorangehenden Ansprüche, **dadurch gekennzeichnet**, daß die Halteeinrichtung (5) eine nach außen verlaufende, planare, ringförmige Einrichtung ist.
7. Schlauchförmige Schutzvorrichtung nach Anspruch 6, **dadurch gekennzeichnet**, daß die Halteeinrichtung (5) ein elastischer Ring ist, und der elastische Ring lösbar in das geschlossene Ende einführbar ist.
8. Schlauchförmige Schutzvorrichtung nach Anspruch 1, **dadurch gekennzeichnet**, daß das offene Ende ein bundförmiges, nach außen verlaufendes Teil hat, und daß die Einrichtung (4), welche das offene Ende radial erweitert, eine Einrichtung zum radialen Strecken des bundförmigen Teils aufweist, welches einen zweiten Durchmesser hat, der größer als der erste Durchmesser ist.
9. Schlauchförmige Schutzvorrichtung nach Anspruch 8, **dadurch gekennzeichnet**, daß die Einrichtung zum radialen Strecken des offenen Endes ein elastischer Ring (4) ist.
10. Schlauchförmige Schutzvorrichtung nach Anspruch 8 oder Anspruch 9, **dadurch gekennzeichnet**, daß die Halteeinrichtung (5) eine nach außen verlaufende, planare, ringförmige Einrichtung ist.
11. Schlauchförmige Schutzvorrichtung nach Anspruch 10, **dadurch gekennzeichnet**, daß die Halteeinrichtung (5) ein innerer, elastischer Ring ist, und daß der innere elastische Ring lösbar in das geschlossene Ende einführbar ist.
12. Schlauchförmige Schutzvorrichtung nach Anspruch 10, **dadurch gekennzeichnet**, daß eine Einrichtung (6) zum Festlegen der Halteeinrichtung (5) an dem flexiblen, dünnwandigen Schlauch vorgesehen ist.
13. Schlauchförmige Schutzvorrichtung nach Anspruch 8, **dadurch gekennzeichnet**, daß der Schlauch einen ersten Durchmesser hat, die Einrichtung (4) zum radialen Strecken einen zweiten Durchmesser hat, der erste Durchmesser des Schlauches kleiner als der zweite Durchmesser der Einrichtung zum radialen



Strecken ist, und der erste Durchmesser so ausreichend groß bemessen ist, daß eine Bewegung eines Penis in dem Schlauch während des Geschlechtsverkehrs möglich ist.

14. Schlauchförmige Schutzvorrichtung nach Anspruch 13, **dadurch gekennzeichnet**, daß die Einrichtung zum radialen Strecken des offenen Endes ein elastischer Ring (4) ist.

15. Schlauchförmige Schutzvorrichtung nach Anspruch 14, **dadurch gekennzeichnet**, daß die nach außen verlaufende, planare, ringförmige Einrichtung ein zweiter, elastischer Ring ist, und der zweite elastische Ring lösbar in das geschlossene Ende einführbar ist.

16. Schlauchförmige Schutzvorrichtung nach Anspruch 15, bei der der zweite Ring an dem flexiblen, dünnwandigen Schlauch (bei 6) festgelegt ist.

17. Schlauchförmige Schutzvorrichtung nach Anspruch 13, bei der die ringförmige Einrichtung derart beschaffen und ausgelegt ist, daß sie das geschlossene Ende radial streckt, wodurch das geschlossene Ende während des Geschlechtsverkehrs in einer Vagina festgehalten ist.

18. Schlauchförmige Schutzvorrichtung nach Anspruch 16, **dadurch gekennzeichnet**, daß ferner eine Einrichtung zum Festlegen der ringförmigen Einrichtung an dem flexiblen, dünnwandigen Schlauch vorgesehen ist.

Revendications

Dispositif protecteur tubulaire pour la protection contre le transfert d'une matière infectieuse pendant un rapport sexuel, comprenant un tube à paroi mince flexible (1), ayant une extrémité fermée et une extrémité ouverte, ladite extrémité ouverte ayant un moyen (4) pour étirer radialement ladite extrémité ouverte, caractérisé en ce que le tube à paroi mince possède un diamètre suffisamment grand pour permettre le mouvement d'un pénis dans le tube pendant le coït et un moyen de retenue (5) est prévu à l'extrémité fermée du tube à paroi mince flexible, ledit moyen de retenue maintenant ladite extrémité fermée dans le vagin d'une utilisatrice.

2. Dispositif protecteur tubulaire selon la revendication 1, caractérisé en ce que l'extrémité ouverte est de forme conique.

3. Dispositif protecteur tubulaire selon la revendication 1 ou la revendication 2, caractérisé en ce que le tube à paroi mince flexible est en un matériau polymère, par exemple en latex, polyéthylènes, polyuréthanes et dérivés de ceux-ci.

4. Dispositif protecteur tubulaire selon l'une quelconque des revendications 1 à 3, caractérisé en ce que le moyen (4) d'étirage radial de l'extrémité ouverte est un anneau élastique solidarisé avec ladite extrémité ouverte.

5. Dispositif protecteur tubulaire selon l'une quelconque des revendications 1 à 4, caractérisé en ce que l'extrémité fermée est entourée par une enveloppe qui est mobile axialement par rapport au dispositif protecteur.

6. Dispositif protecteur tubulaire selon l'une quelconque des revendications précédentes, caractérisé en ce que le moyen de retenue (5) est un moyen annulaire plan s'étendant vers l'extérieur.

7. Dispositif protecteur tubulaire selon la revendication 6, caractérisé en ce que le moyen de retenue (5) est élastique, l'anneau élastique étant insérable de manière amovible dans ladite extrémité fermée.

8. Dispositif protecteur tubulaire selon la revendication 1, caractérisé en ce que l'extrémité ouverte possède une partie en forme de col s'étendant vers l'extérieur, et le moyen (4) pour étirer radialement l'extrémité ouverte comporte un moyen pour étirer radialement la partie en forme de col possédant un second diamètre plus grand que ledit premier diamètre.

9. Dispositif protecteur tubulaire selon la revendication 8, caractérisé en ce que ledit moyen pour étirer radialement ladite extrémité ouverte est un anneau élastique (4).

10. Dispositif protecteur tubulaire selon la revendication 8 ou la revendication 9, caractérisé en ce que le moyen de retenue (5) est un moyen annulaire plan s'étendant vers l'extérieur.

11. Dispositif protecteur tubulaire selon la revendication 10, caractérisé en ce que le moyen de retenue (5) est un anneau élastique intérieur, ledit anneau élastique intérieur étant insérable de manière amovible dans l'extrémité fermée.



12. Dispositif protecteur tubulaire selon la revendication 10, caractérisé en ce qu'il est prévu en outre un moyen (6) pour attacher ledit moyen de retenue (5) audit tube à paroi mince, flexible. 5
13. Dispositif protecteur tubulaire selon la revendication 8, caractérisé en ce que le tube possède un premier diamètre, le moyen d'étirage radial (4) possède un second diamètre, ledit premier diamètre du tube étant plus petit que ledit second diamètre du moyen d'étirage radial, et le premier diamètre est suffisamment grand pour permettre le mouvement d'un pénis à l'intérieur dudit tube pendant le coït. 10 15
14. Dispositif protecteur tubulaire selon la revendication 13, caractérisé en ce que le moyen pour étirer radialement l'extrémité ouverte est un anneau élastique (4). 20
15. Dispositif protecteur tubulaire selon la revendication 14, caractérisé en ce que le moyen annulaire plan s'étendant vers l'extérieur est un second anneau élastique, ledit second anneau élastique étant insérable de manière amovible dans l'extrémité fermée. 25
16. Dispositif protecteur tubulaire selon la revendication 15, caractérisé en ce que le second anneau est attaché (6) audit tube à paroi mince, flexible. 30
17. Dispositif protecteur tubulaire selon la revendication 13, caractérisé en ce que ledit moyen annulaire est adapté pour étirer radialement ladite extrémité fermée pour retenir l'extrémité fermée dans un vagin pendant le coït. 35
18. Dispositif protecteur tubulaire selon la revendication 16, caractérisé en ce qu'il comprend en outre un moyen pour attacher le moyen annulaire audit tube à paroi mince flexible. 40

45

50

55