WELLHEAD SYSTEM COMPRISING A SLIDING SLEEVE SEAL

Field of the Invention

This invention relates to sealing of the annulus between a tubing hanger and a surrounding spool such as an xmas tree, in a wellhead assembly having a laterally extending fluid conduit. For example, the laterally extending conduit may comprise the production outlet of a horizontal xmas tree.

Background of the Invention

There is a trend towards subsea completions incorporating increasingly large bores. Current subsea xmas tree system configurations (both parallel and concentric) can be inefficient in terms of space usage within the tubing hanger assembly. For large bore systems it would be advantageous to reconfigure the subsea xmas tree system whilst maintaining a large number of down-hole lines through the tubing hanger. A solution for releasing additional radial space to facilitate larger bores would be to reduce the size of the mechanism for sealing off the annulus void.

The design of large bore subsea xmas trees and completions is constrained due to requirements of utilising existing standard BOP configurations. Therefore in order to run larger completion tubing, space must be saved elsewhere to permit using existing BOP's. Additionally, particularly in the case of deepwater developments, significant cost savings can be achieved by using smaller standard BOP and casing programs while still maintaining - or increasing - the radial space available for the completion tubing. In this way vessel selection is made easier, and hence costs decreased, due to smaller handling requirements associated with the smaller BOP size.

The problematic situation of a drive toward larger bore completions coupled with potentially utilising smaller BOP stacks makes the radial space taken within the well system for annular packoffs of prime importance. Any space saved here can have a direct impact on the size of the completion tubing that can be accommodated.

Essentially, the sealing requirement for a slick bore tubing hanger is to seal the annulus between the tubing hanger and spool (wellhead, xmas tree or tubing spool), maintaining a

clearance while running in the hanger, and once the hanger is in position, setting the seal to a sealed condition. In the particular case of horizontal production outlet tubing hangers, it is usual to seal the annulus above and below the horizontal outlet. In the case of conventional tubing hangers (or casing hangers), only one seal barrier is required to seal off the annulus.

Summary of the Invention

The present invention aims to release additional space in a tubing hanger and wellhead system incorporating a lateral wellbore fluid conduit, by improving the mechanism for sealing off the annulus void. In this way, larger bore completion tubing can be accommodated. Accordingly the present invention provides a wellhead system comprising a wellbore fluid conduit extending laterally between a tubing hanger and a surrounding spool in use, the system comprising a sleeve slideable axially of the wellbore fluid conduit from a position in which it is clear of the tubing hanger / spool interface to a position in which it seals across the tubing hanger / spool interface. Therefore, with the sleeve positioned clear of the tubing hanger / spool interface, the tubing hanger and attached completion tubing may be run or retrieved. As it is capable of sealing across this interface, the sleeve eliminates the need for the relatively bulky annulus seals and their energizing mechanisms above and below the laterally extending wellbore fluid conduit.

This provides the dual benefits of releasing radial space while also making the completion system and in particular its seal forming surfaces or areas less susceptible to damage. Preferably, the spool is provided with recessed sealing profiles affording protection to the seal areas during drilling operations.

The laterally extending wellbore fluid conduit may be used to contain any fluid that is conventionally conveyed to or from the wellbore via the tubing hanger. Most often in production mode this will be production fluid, but the fluid could also be for example lift gas, injection water or other fluids such as glycol for chemical injection, or fluids for pressure and circulation testing.

The wellhead sealing system of the present invention may provide some or all of the following additional benefits:

1. Reliability under cyclical loading.
2. It can be remotely operated using simple tooling.
3. Ability to accommodate 10,000 psi (69 MNm^{-2}) nominal maximum working pressure as a base case. However a family of such sealing systems may be produced, also including, for example, members for 5,000 psi (35 MNm^{-2}), 15,000 psi (104 MNm^{-2}) and other duties as required.
4. Minimum temperature range of 0 to 250°F (-17.8°C to 121°C) and preferably beyond at either end.

In accordance with a first aspect of the invention, there is provided wellhead system comprising a wellbore fluid conduit extending laterally between a tubing hanger and a surrounding spool in use, the system comprising a sleeve slideable axially of the wellbore fluid conduit from a position in which it is clear of the tubing hanger / spool interface to a position in which it seals across the tubing hanger / spool interface.

Further preferred features of the invention are in the dependent claims and in the following description of illustrative embodiments, made with reference to the drawings.

Brief Description of the Drawings

Figure 1 is a diagrammatic illustration of a prior art sealing arrangement between a horizontal xmas tree and a tubing hanger landed in it;

Figure 2 is a diagram of a first embodiment of the invention, showing the tubing hanger just prior to landing in the spool;

Figure 2a is a half section through parts of the spool, tubing hanger and sleeve, showing details of possible sealing arrangements;

Figure 3 corresponds to Figure 2 but shows the tubing hanger landed, locked down and sealed to the spool;

Figure 4 corresponds to Figure 2 but shows a second embodiment of the invention, and

Figure 5 corresponds to Figure 3 and shows the second embodiment.

For horizontal xmas trees, it is conventional to isolate the annulus 12

surrounding the tubing hanger 10, using annular seals 14, 16 installed between the tubing hanger 10 and the surrounding tree block 18 above and below the production outlet 20 as shown in Figure 1. The lower seal 16 isolates fluid in the production bore 22 and production outlet 20 from the well annulus 24 below. Similarly the upper seal 14 isolates the outlet 20 and bore 22 from the annulus 26 above.

The illustrated embodiments of the invention seek to eliminate one of these annular seals (either the top or the bottom seal can be eliminated, although for brevity Figures 2 – 5 only show elimination of the top seal). Elimination of a seal set will free radial space, while making the completion less susceptible to damage during drilling.

Two embodiments are described, one having the sealing sleeve located or stowed within the xmas tree or spool while running (Figures 2 and 3; suitable more for surface applications) and one with the seal sleeve located within the tubing hanger (Figures 4 and 5; more suitable for subsea applications).

Figure 2 shows the tubing hanger 10 being run into the xmas tree or spool 18. The sealing sleeve 28 is axially slideable in a lateral production fluid outlet conduit 20 comprising parts 20a and 20b extending through the spool 18 and tubing hanger 10 respectively. These parts are aligned when the tubing hanger is properly landed in the spool (Figure 3). To allow the tubing hanger 10 to be run or retrieved, the sleeve 28 is withdrawn fully into the conduit part 20a in the spool 18 body (Figure 2), clear of the spool / tubing hanger interface. Figure 3 shows the sealing sleeve 28 stroked so as to extend into the landed and locked tubing hanger 10.

The lower annular seal 16 (or a corresponding upper seal, not shown) may be run and set in known manner. For example, it may be run on the tubing hanger 10 and set prior to stroking the sleeve 28 to its sealed position.

The sleeve 28 is required to form a seal with an annular area or surface 30 of the conduit part 20b in the tubing hanger 10. It is likewise required to make an annular seal with the conduit part 20a in the spool 18. Conventionally, it is preferred that metal seals are used in the production bore. Therefore self-energizing metal seals as shown in Figure 2a may be used between the sleeve 28 and the conduit parts 20a, 20b. The sleeve 28 may incorporate annular seal bumps 34, 36 which are transited from a clearance condition in the respective conduit parts 20b, 20a, to an interference fit in respective cylindrical seal areas 30, 32 by respective ramp surfaces 38, 40, as the sleeve 28 is moved to the left. For clarity, the slope of the ramp surfaces 38, 40 is shown somewhat exaggerated. Such a

sealing arrangement is a development of the applicants' SBMS (straight bore metal seal) concept: see US patent no. 4471965.

The nature of SBMS type seals dictates that surface finishes should be tightly controlled, and more significantly, concentricity of seals and bores should also be strictly controlled. In the Figure 2 embodiment the tubing hanger must therefore be located accurately in altitude and rotation to allow the seal sleeve to locate correctly. This magnitude of installation accuracy is achievable, for example already being routine in relation to the use of horizontal penetrators. Elastomeric and other seal types may also be used to provide the annular seals between the sleeve 28 and the conduit parts 20a, 20b.

The sleeve 28 can be stroked between its retracted and extended positions by any suitable mechanical, electrical and/or hydraulic means, well known to those familiar with valve and /or oilfield technology. Because the sleeve 28 extends from the spool body 10, which in turn is accessible exteriorly (e.g. for manual actuation of the sleeve), the embodiment shown in figures 2 and 3 is best suited for surface use. The relatively long conduit part 20a accommodates a relatively long sleeve 28 and sleeve operating stroke.

In the embodiment shown in Figure 4, the sleeve 28 is held within the conduit part 20b in the tubing hanger body 10, for running and retrieval of the tubing hanger and completion. Figure 5 shows the sleeve 28 stroked outwardly into the conduit part 20a in the spool.

In this embodiment the tubing hanger 10 must again be located accurately vertically and in rotation to allow the sealing sleeve 28 to locate correctly. However, in this case it may be possible to utilize the sleeve to "fine align" the tubing hanger prior to lockdown. For this purpose, the sleeve 28 and/or the conduit part 20a may have suitable tapering guide surfaces at their mating ends. The same fine alignment technique can be used in relation to a variant of the Figures 2 and 3 embodiment, provided that the hanger is locked down and the annular seal is set between it and the spool after such alignment. For example, the tubing hanger/spool annular seal may be installed above the lateral conduit 20.

The sleeve 28 of Figures 4 and 5 can again be stroked into position by any suitable mechanical, electrical or hydraulic actuating means. As such actuating means are

contained in the tubing hanger and/or the tubing hanger running tool, this embodiment is more suitable for subsea use. In other respects, the embodiment of Figures 4 and 5 is similar to the embodiment of Figures 2 and 3.

CLAIMS

1. A wellhead system comprising a wellbore fluid conduit extending laterally between a tubing hanger and a surrounding spool in use, the system comprising a sleeve slideable axially of the wellbore fluid conduit from a position in which it is clear of the tubing hanger / spool interface to a position in which it seals across the tubing hanger / spool interface.

2. A wellhead system as defined in claim 1 comprising recessed sealing profiles provided in the spool, with which the sleeve co-operates to form the interface seal.

3. A wellhead system as defined in claim 1 or 2 in which the sleeve is stowed in the spool for running or retrieval of the tubing hanger.

4. A wellhead system as defined in claim 1 or 2 in which the sleeve is stowed in the tubing hanger for running or retrieval of the tubing hanger.

5. A wellhead system as defined in any preceding claim comprising a single annular seal between the tubing hanger and the spool.

6. A wellhead system as defined in any preceding claim comprising an SBMS-type seal between the sleeve and the spool and/or tubing hanger.

7. A wellhead system as defined in any preceding claim comprising an elastomeric seal between the sleeve and the spool and/or tubing hanger.

8. A wellhead system substantially as described with reference to or as shown in Figures 2 and 3 or Figures 4 and 5.

Abstract

[Fig. 2]

SLIDING SLEEVE SEALS

For horizontal completions the present invention permits the use of one annulus sealing element 16 as opposed to the conventional two (one above and one below the production outlet in the well system). This provides the dual benefits of releasing radial space while making the completion system less susceptable to damage. A sealing sleeve 28 is slidable between a retracted position as shown, for running and retrieval of a tubing hanger 10, and an extended position (Fig. 3, not shown), for sealing between respective lateral conduit parts 20a, 20b, in a spool 18 and the tubing hanger 10.