



(51) International Patent Classification:
E05B 47/06 (2006.01) *E05B 71/00* (2006.01)
B62H 5/00 (2006.01)

(74) Agent: **FASKEN MARTINEAU DuMOULIN LLP**;
Stock Exchange Tower, P.O. Box 242, 800, Square Vic-
toria, Bureau 3700, Montreal, Québec H4Z 1E9 (CA).

(21) International Application Number:
PCT/CA2009/000539

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ,
CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ,
EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN,
HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR,
KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME,
MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO,
NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG,
SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, ZA, ZM, ZW.

(22) International Filing Date:
22 April 2009 (22.04.2009)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
61/047,162 23 April 2008 (23.04.2008) US
12/417,108 2 April 2009 (02.04.2009) US
09157502.7 7 April 2009 (07.04.2009) EP

(71) Applicant (for all designated States except US): **SOCI-
ETE DE VELO EN LIBRE-SERVICE** [CA/CA]; 704
St-Jacques Street, Montreal, Québec H3C 1E9 (CA).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **KHAIRALLAH,**
Charles Ibrahim [CA/CA]; 1650 Lincoln Street, Suite
1203, Montreal, Québec H3H 1H1 (CA). **DALLAIRE,**
Michel [CA/CA]; 4062 Wilson Avenue, Montreal,
Québec H4A 2T9 (CA).

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ,
TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR),
OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML,
MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: METHOD AND APPARATUS FOR SECURING A MOVABLE ITEM TO A STRUCTURE




FIG.1

(57) Abstract: An electronic lock for re-
movably securing a movable item to a
structure, the electronic lock comprising
first and second complementary cooperat-
ing connecting members, each being fixed-
ly mounted to a respective one of the mov-
able item and the structure and being en-
gageable together in a lockable position;
and a securing assembly for securing the
first and second connecting members to-
gether when engaged in the lockable posi-
tion, the securing assembly comprising a
movable locking member operatively asso-
ciated to the first connecting member, a
locking aperture defined in the second con-
necting member, the locking aperture being
adapted for receiving the movable locking
member when the connecting members are
engaged together in the lockable position;
an actuator operatively coupled to the mov-
able locking member for actuating the mov-
able locking member between an unlocked
position enabling disengagement of the first
and second connecting members and a
locked position wherein the movable lock-
ing member engages the locking aperture,

and electronic control means for controlling selective actuation of the movable locking member.