

(19) World Intellectual Property Organization
International Bureau



G00002



(43) International Publication Date
23 May 2002 (23.05.2002)

PCT

(10) International Publication Number
WO 02/40425 A1

(51) International Patent Classification⁷: C04B 41/63

(21) International Application Number: PCT/EP01/12411

(22) International Filing Date: 25 October 2001 (25 10.2001)

(25) Filing Language: English

(26) **Publication Language:** English

(30) **Priority Data:**
PD2000A000259

17 November 2000 (17.11.2000) IT

(71) Applicant (for all designated States except US): ISOL-CEM ITALIA S.R.L. [IT/IT], Via dell'Artigianato, 13, I-35010 Loreggia (IT).

(72) Inventor; and

(75) Inventor/Applicant (for US only): MASON, Maurizio [IT/IT]; Via dell' Artigianato, 13, I-35010 Loreggia (IT).

(74) Agents: ROBBA, Pierpaolo et al, Interpatent, Via Caboto, 35, I-10129 Torino (IT).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette

(54) Title: WATERPROOFING PASTE



(57) Abstract: The paste is based on air-polymerisable resins (6), generally acrylic resins with an aqueous vehicle, loaded with plastic grains (7). The paste is to be spread in particular on wall surfaces (1) of foundations, to form a waterproofing, protecting and shock-resistant resilient sheath (2) The paste can be applied to certain thickness to get consistency and to undergo no trickling The paste does not contain any kind of solvent, apart from water, and thus it is ecological.