COVER LETTER

IPOS COPY 9802361-7

PCT WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : F17C 13/04 — A1

(11) International Publication Number: WO 97/13998

(43) International Publication Date: 17 April 1997 (17.04.97)

(21) International Application Number: PCT/NL96/00392

(22) International Filing Date: 7 October 1996 (07.10.96)

(30) Priority Data:
1001379 9 October 1995 (09.10.95) NL

(71) Applicant *(for all designated States except US)*: BENTFIELD EUROPE B.V. [NL/NL]; Postbus 23, NL-2150 AA Nieuw-Vennep (NL).

(72) Inventor; and
(75) Inventor/Applicant *(for US only)*: GANZEBOOM, Wilhelmus, Everhardus [NL/NL]; Zonnelaan 4, NL-2012 TC Haarlem (NL).

(74) Agent: DE BRUIJN, Leendert, C.; Nederlandsch Octrooibureau, Scheveningseweg 82, P.O. Box 29720, NL-2502 LS The Hague (NL).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published
With international search report.

(54) Title: RAPID CONNECTING ASSEMBLY

(57) Abstract

Rapid connecting assembly for an aerosol can and a dispensing device. The rapid connecting assembly consists of a first part which is to be connected to the aerosol can and is supplied together with the aerosol can. The second part of the rapid connecting assembly is connected to the dispensing device. A tubular holder is present in this second part, for receiving the tubular part projecting from the aerosol can when the dispensing device and the aerosol can are being connected to each other. For simple connection of the two parts, one of the parts is provided with a lug and the other part is provided with a peripheral edge. The peripheral edge is provided with a flattened part for receiving the lug.

