

FETCHING METHOD, FETCHING APPARATUS, BAG OPENING APPARATUS, AND FETCHING SYSTEM

CROSS-REFERENCE TO RELATED PATENT APPLICATION

5 This application claims the benefit of priority to Taiwan Patent Application
No. 109141227 filed on November 25, 2020, and to the U.S. Provisional Patent
Application Ser. No. 63/057,558 filed on July 28, 2020. The entire content of
each of the above identified applications is incorporated herein by reference.

Some references, which may include patents, patent applications and
10 various publications, may be cited and discussed in the description of this
disclosure. The citation and/or discussion of such references is provided merely
to clarify the description of the present disclosure and is not an admission that
any such reference is “prior art” to the disclosure described herein. All
references cited and discussed in this specification are incorporated herein by
15 reference in their entireties and to the same extent as if each reference was
individually incorporated by reference.

FIELD OF THE DISCLOSURE

The present disclosure relates to a fetching method, a fetching apparatus, a
20 bag opening apparatus, and a fetching system, and more particularly to a
fetching method, a fetching apparatus, a bag opening apparatus, and a fetching
system for opening a protective bag of a semiconductor material and taking out
an accommodating box disposed in the protective bag.

25 **BACKGROUND OF THE DISCLOSURE**

Generally, when a wafer box (e.g., a front opening unified pod) carrying a wafer is transferred, a dust protection bag or an antistatic bag is used to cover an outer periphery of the wafer box, so as to prevent dust from settling on the wafer box or to prevent the wafer in the wafer box from being affected by external static electricity. The dust protection bag or the antistatic bag covering the outer periphery of the wafer box is generally fixed by components such as tape.

In a conventional application, when the outer periphery of the wafer box is covered by the dust protection bag or the antistatic bag, and a wafer carried by such a wafer box enters a related working station for processing, the tape first needs to be cut off, and then the dust protection bag or the antistatic bag is opened manually. Finally, the wafer box is manually taken out from the protective bag or the antistatic bag. In this way, the efficiency is low and excessive human power is required. In addition, when technical personnel cannot go to work due to various unavoidable circumstances (such as the government announcing office closure), the overall wafer manufacturing process may be put to halt, thereby causing huge losses.

SUMMARY OF THE DISCLOSURE

In response to the above-referenced technical inadequacies, the present disclosure provides a fetching method, a fetching apparatus, a bag opening apparatus, and a fetching system primarily configured to improve the issues associated with a conventional fetching method (i.e., manually opening a protective bag of a semiconductor material and manually taking out an accommodating box in the protective bag). The conventional fetching method

requires excessive human power, and is of low efficiency. Further, when relevant technical personnel cannot go to work, the overall manufacturing process may be put to halt.

In one aspect, the present disclosure provides a fetching method configured
5 to take out an accommodating box in a protective bag of a semiconductor material. The protective bag has an accommodating space and an opening, the accommodating box is disposed in the accommodating space through the opening, the protective bag is configured to have a packaging portion and a non-packaging portion, the packaging portion covers an outer periphery of the
10 accommodating box, the non-packaging portion is folded into a tail structure, a tape is adhered to the packaging portion and the tail structure, and the tape is configured to fix the tail structure to the packaging portion. The fetching method includes a positioning step, a cutting step, a stretching step, and a taking out step. The positioning step is implemented by fixing the semiconductor
15 material. The cutting step is implemented by controlling one or more knife machines to sequentially cut off the tape and the tail structure, so that the packaging portion forms a fetching opening and the accommodating box is exposed through the fetching opening. The stretching step is implemented by controlling a bag stretching machine to stretch the packaging portion. The
20 taking out step is implemented by controlling a fetching device to enter into the packaging portion, hold the accommodating box, and take out the accommodating box from the packaging portion.

In another aspect, the present disclosure provides a fetching apparatus configured to take out an accommodating box in a protective bag of a
25 semiconductor material. The protective bag has an accommodating space and

an opening, the accommodating box is disposed in the accommodating space through the opening, the protective bag is configured to have a packaging portion and a non-packaging portion, the packaging portion covers an outer periphery of the accommodating box, the non-packaging portion is folded into a tail structure, a tape is adhered to the packaging portion and the tail structure, and the tape is configured to fix the tail structure to the packaging portion. The fetching apparatus includes a processing device, a fixing machine, one or more knife machines, a bag stretching machine, and a fetching device. The fixing machine is electrically connected to the processing device. The processing device is configured to control the fixing machine to fix the semiconductor material. The one or more knife machines are electrically connected to the processing device and configured to cut off the tape and the tail structure. The bag stretching machine is electrically connected to the processing device and configured to stretch the packaging portion. The fetching device is electrically connected to the processing device and configured to take out the accommodating box disposed in the packaging portion from the packaging portion. The processing device controls the fixing machine to fix the semiconductor material, and then the processing device controls the one or more knife machines to cut off the tape and the tail structure, so that the packaging portion forms a fetching opening and the accommodating box is exposed through the fetching opening. After the accommodating box is exposed through the fetching opening, the processing device sequentially controls the bag stretching machine to stretch the packaging portion and controls the fetching device to enter into the packaging portion to take out the accommodating box.

In yet another aspect, the present disclosure provides a bag opening apparatus configured to take out an accommodating box in a protective bag of a semiconductor material. The protective bag has an accommodating space and an opening, the accommodating box is disposed in the accommodating space through the opening, the protective bag is configured to have a packaging portion and a non-packaging portion, the packaging portion covers an outer periphery of the accommodating box, the non-packaging portion is folded into a tail structure, a tape is adhered to the packaging portion and the tail structure, and the tape is configured to fix the tail structure to the packaging portion. The bag opening apparatus includes a processing device, a fixing machine, one or more knife machines, and a bag stretching machine. The processing device is configured to be communicatively connected to a fetching device. The fixing machine is electrically connected to the processing device. The processing device is configured to control the fixing machine to fix the semiconductor material. The one or more knife machines are electrically connected to the processing device and configured to cut off the tape and the tail structure. The bag stretching machine is electrically connected to the processing device and configured to stretch the packaging portion. The processing device controls the fixing machine to fix the semiconductor material, and then the processing device controls the one or more knife machines to cut off the tape and the tail structure, so that the packaging portion forms a fetching opening and the accommodating box is exposed through the fetching opening. After the accommodating box is exposed through the fetching opening, the processing device sequentially controls the bag stretching machine to stretch the packaging portion. When the bag stretching machine stretches the packaging portion, the

processing device is configured to transmit a signal to the fetching device, so that the fetching device takes out the accommodating box from the packaging portion.

5 In still yet another aspect, the present disclosure provides a fetching system including a fetching apparatus, a central control apparatus, and a bag recycling apparatus. The central control apparatus is electrically connected to the fetching apparatus and the bag recycling apparatus. The central control apparatus is configured to control the fetching apparatus to cut off the tail structure of the semiconductor material and take out the accommodating box in
10 the packaging portion, and then the central control apparatus controls the bag recycling apparatus to fold and recycle the packaging portion.

Therefore, the fetching method, the fetching apparatus, the bag opening apparatus, and the fetching system of the present disclosure can automatically cut off the tape and the tail structure to open the protective bag, and then take
15 out the accommodating box disposed in the protective bag. During the overall process, human operation is basically not required, thereby significantly reducing the need for human power and effectively increasing the overall efficiency.

These and other aspects of the present disclosure will become apparent
20 from the following description of the embodiment taken in conjunction with the following drawings and their captions, although variations and modifications therein may be affected without departing from the spirit and scope of the novel concepts of the disclosure.

25

BRIEF DESCRIPTION OF THE DRAWINGS

The described embodiments may be better understood by reference to the following description and the accompanying drawings, in which:

FIG. 1 is a schematic view of a bag opening apparatus of the present disclosure;

5 FIG. 2 is a schematic view of a semiconductor material;

FIG. 3 is a schematic view of a protective bag and an accommodating box;

FIG. 4 and FIG. 5 are schematic views of the protective bag in different states;

FIG. 6 is a schematic view of a fixing machine of the bag opening
10 apparatus of the present disclosure;

FIG. 7 is a schematic view showing the fixing machine of the bag opening apparatus holding the semiconductor material according to the present disclosure;

FIG. 8 to FIG. 12 and FIG. 14 are schematic operational views showing the
15 bag opening apparatus cutting off two tapes of the semiconductor material and holding a tail structure according to the present disclosure;

FIG. 13 is a schematic view of a clamping device of a pulling machine of the bag opening apparatus of the present disclosure;

FIG. 15 to FIG. 18 are schematic operational views of the bag opening
20 apparatus cutting off the tail structure of the semiconductor material according to the present disclosure;

FIG. 19 is a schematic view of a bag stretching machine, the pulling machine, and a transferring machine of the bag opening apparatus of the present disclosure;

25 FIG. 20 is a schematic view of the bag stretching machine of the bag

opening apparatus of the present disclosure;

FIG. 21 is a schematic view of two flipping devices, the transferring machine, and the semiconductor material of the bag opening apparatus of the present disclosure;

5 FIG. 22 and FIG. 23 are schematic operational views showing the flipping devices of the bag opening apparatus opening an opening of a packaging portion according to the present disclosure;

FIG. 24 and FIG. 25 are schematic operational views showing the bag stretching machine of the bag opening apparatus stretching the packaging
10 portion according to the present disclosure;

FIG. 26 is a schematic view of a bag opening system of the present disclosure;

FIG. 27 is a schematic view of a bag recycling apparatus of the bag opening system and the packaging portion of the protective bag according to the
15 present disclosure;

FIG. 28 is a schematic view showing a clamping module of the bag recycling apparatus of the bag opening system entering into the packaging portion of the protective bag according to the present disclosure;

FIG. 29 is a schematic view showing the protective bag being disposed
20 onto a platform by the bag recycling apparatus of the bag opening system of the present disclosure;

FIG. 30 is a flowchart of a bag opening method of the present disclosure;
and

FIG. 31 is another flowchart of the bag opening method of the present
25 disclosure.

DETAILED DESCRIPTION OF THE EXEMPLARY EMBODIMENTS

The present disclosure is more particularly described in the following examples that are intended as illustrative only since numerous modifications
5 and variations therein will be apparent to those skilled in the art. Like numbers in the drawings indicate like components throughout the views. As used in the description herein and throughout the claims that follow, unless the context clearly dictates otherwise, the meaning of “a”, “an”, and “the” includes plural reference, and the meaning of “in” includes “in” and “on”. Titles or subtitles
10 can be used herein for the convenience of a reader, which shall have no influence on the scope of the present disclosure.

The terms used herein generally have their ordinary meanings in the art. In the case of conflict, the present document, including any definitions given herein, will prevail. The same thing can be expressed in more than one way.
15 Alternative language and synonyms can be used for any term(s) discussed herein, and no special significance is to be placed upon whether a term is elaborated or discussed herein. A recital of one or more synonyms does not exclude the use of other synonyms. The use of examples anywhere in this specification including examples of any terms is illustrative only, and in no way
20 limits the scope and meaning of the present disclosure or of any exemplified term. Likewise, the present disclosure is not limited to various embodiments given herein. Numbering terms such as “first”, “second” or “third” can be used to describe various components, signals or the like, which are for distinguishing one component/signal from another one only, and are not intended to, nor
25 should be construed to impose any substantive limitations on the components,

signals or the like.

Referring to FIG. 1 to FIG. 3, a bag opening apparatus S1 of the present disclosure is configured to open a protective bag A1 of a semiconductor material A, so that an accommodating box A2 arranged in the protective bag A1 is exposed. Accordingly, the accommodating box A2 can be conveniently taken out from the protective bag A1 by other fetching devices (e.g., a robotic arm). The bag opening apparatus S1 includes a processing device 1, a fixing machine 2, a first knife machine 3, a pulling machine 4, a second knife machine 5, a transferring machine 6, and a bag stretching machine 7. In the present embodiment, the bag opening apparatus S1 includes two knife machines, but the quantity of the knife machines included by the bag opening apparatus S1 is not limited thereto. In other embodiments, the quantity of the knife machines included by the bag opening apparatus S1 can be one. In addition, in other embodiments, the bag opening apparatus S1 can be provided to not include at least one of the fixing machine 2 and the pulling machine 4.

The processing device 1 is electrically connected to the fixing machine 2, the first knife machine 3, the pulling machine 4, the second knife machine 5, the transferring machine 6, and the bag stretching machine 7. The processing device 1 can be, for example, various types of computers or servers. The fixing machine 2 is configured to hold the semiconductor material A. The first knife machine 3, the pulling machine 4, and the second knife machine 5 can be used in cooperation with each other, so as to open the protective bag A1 of the semiconductor material A that is held by the fixing machine 2. The transferring machine 6 can cooperate with the fixing machine 2, so that the semiconductor material A that is held can be transferred among the first knife machine 3, the

second knife machine 5, and the bag stretching machine 7. The bag stretching machine 7 is configured to stretch the protective bag A1 of the semiconductor material A that has been opened, so as to facilitate the fetching device to take out an accommodating box A2 disposed in the protective bag A1. To clearly
5 show the components included by the bag opening system S1, a supporting frame for supporting the processing device 1, the first knife machine 3, the second knife machine 5, and the bag stretching machine 7 is omitted from the drawings of the present disclosure.

Referring to FIG 2 to FIG. 5, the semiconductor material A includes the
10 protective bag A1, the accommodating box A2, and two tapes A3. The protective bag A1 has an accommodating space A11 and an opening A12, and the accommodating box A2 is disposed in the accommodating space A11 through the opening A12. In a practical application, the accommodating box A2 can be, for example, various types of front opening unified pods (i.e., FOUP),
15 and the protective bag A1 can be various types of tin foil bags or anti-static bags. Referring to FIG.3 and FIG. 4, after the accommodating box A2 is disposed in the protective bag A1, a portion of the protective bag A1 covers an outer periphery of the accommodating box A2, and said portion of the protective bag A1 is defined as a packaging portion A13. The remaining
20 portion of the protective bag A1 is defined as a non-packaging portion A14. Referring to FIG. 2 and FIG. 5, a side of the non-packaging portion A14 that has the opening A12 can be operated by a technical personnel or a related machine, so that the side of the non-packaging portion A14 is repeatedly folded in a direction toward the packaging portion A13 to form a tail structure A15.
25 The tail structure A15 is fixed to the packaging portion A13 by the two tapes

A3. After the tail structure A15 is fixed to a top surface of the packaging portion A13 by the two tapes A3, the protective bag A1, the accommodating box A2 disposed in the protective bag A1, and the two tapes A3 jointly define the semiconductor material A.

5 Referring to FIG. 1, FIG. 6, and FIG. 7, the transferring machine 6 can include a rail 61 and a carrying platform 62, and the carrying platform 62 is slidably disposed on the rail 61. The processing device 1 is electrically connected to the transferring machine 6, and the carrying platform 62 is controllable by the processing device 1 to move along the rail 61. The carrying
10 platform 62 is configured to carry the semiconductor material A, the fixing machine 2 is disposed on the carrying platform 62, and the fixing machine 2 is configured to hold the semiconductor material A that is disposed on the carrying platform 62. The processing device 1 is configured to control the carrying platform 62 to slide on the rail 61, so that the semiconductor material A
15 disposed on the carrying platform 62 moves from a position near the first knife machine 3 to a position near the second knife machine 5.

The fixing machine 2 can include four pushing devices 21 and two abutting devices 22. Each of the pushing devices 21 can include a driver 211 and a pushing member 212. In each of the pushing devices 21, the driver 211 is
20 electrically connected to the processing device 1, and the pushing member 212 is connected to the driver 211. In each of the pushing devices 21, the processing device 1 is configured to control the driver 211 to be operated so that the pushing member 212 moves toward the carrying platform 62 to push against a side of the semiconductor material A disposed on the carrying platform 62, or
25 to control the driver 211 to be operated so that the pushing member 211 moves

away from the carrying platform 62 to no longer push against the side of the semiconductor material A. For example, each of the drivers 211 can include a pneumatic cylinder (or a hydraulic cylinder) and a plurality of pushing rods. The processing device 1 can control the pneumatic cylinder, so that the pushing rods and the pushing member 212 connected thereto move toward or away from the carrying platform 62.

When the semiconductor material A is disposed on the carrying platform 62, the processing device 1 controls the four pushing devices 21, so that the four pushing members 212 push against four side surfaces of the semiconductor material A. In a practical application, at least one detector can be disposed on the carrying platform 62, the detector is configured to detect whether the carrying platform 62 has the semiconductor material A disposed thereon, and the processing device 1 determines whether the carrying platform 62 has the semiconductor material A disposed thereon according to a detection result of the detector. When the processing device 1 determines that the carrying platform 62 has the semiconductor material A disposed thereon according to the detection result, the processing device 1 can control the four pushing devices 21 to be operated, so that the four pushing devices 21 push against the four side surfaces of the semiconductor material A to hold the semiconductor material A.

In a practical application, when the semiconductor material A is disposed on the carrying platform 62, the processing device 1 can control the four pushing devices 21 to be operated at the same time, so that the four pushing members 212 push against the four side surfaces of the semiconductor material A at the same time. In this way, even if placement of the semiconductor material A on the carrying platform 62 slightly deviates from a correct position

on the carrying platform 62, the semiconductor material A can eventually move to the correct position through being pushed by the four pushing members 212. In other words, the four pushing devices 21 can not only hold the semiconductor material A disposed on the carrying platform 62, but also allow
5 the semiconductor material A to be correctly disposed on the carrying platform 62 (i.e., allow the semiconductor material A to return to the correct position on the carrying platform 62).

Each of the abutting devices 22 includes a driver 221 and an abutting member 222. In each of the abutting devices 22, the driver 221 is electrically
10 connected to the processing device 1, and the abutting member 222 is connected to the driver 221. The processing device 1 can control the two drivers 221 of the two abutting devices 22, so that the two abutting members 222 abut against the packaging portion A13. In a practical application, each of the drivers 221 can include a pneumatic cylinder and a plurality of pushing rods. The
15 processing device 1 can control each of the drivers 221 to be operated, so that the pushing rods extend or retract to drive the abutting members 222 to abut against or no longer abut against the packaging portion A13 of the semiconductor material A.

The two abutting devices 22 can be disposed near the two pushing devices
20 21. Before the processing device 1 controls the pulling machine 4 to hold the tail structure A15, the processing device 1 can control the two abutting devices 21 to be operated, so that the two abutting members 212 no longer abut against the semiconductor material A. Then, the processing device 1 controls the two abutting devices 22 to be operated, so that the two abutting members 222 abut
25 against a bottom portion A131 (as shown in FIG. 2) of the packaging portion

A13. In a practical application, each of the abutting devices 22 is disposed near one of the pushing devices 21, but each of the abutting devices 22 is not limited to being disposed near one of the pushing devices 21.

Referring to FIG. 8 and FIG. 9, the first knife machine 3 can include a first
5 knife 31, a vertical movement module 32, and a horizontal movement module 33. The first knife 31 is connected to the vertical movement module 32, and the vertical movement module 32 is connected to the horizontal movement module 33. The processing device 1 is electrically connected to the vertical movement module 32 and the horizontal movement module 33. The processing device 1 is
10 configured to control the vertical movement module 32 to be operated, so that the first knife 31 moves in a vertical direction (e.g., vertical to the ground) toward or away from the semiconductor material A disposed on the carrying platform 62. The processing device 1 is configured to control the horizontal movement module 33 to be operated, so that the first knife 31 moves in a
15 horizontal direction (e.g., perpendicular to the vertical direction) toward or away from the semiconductor material A disposed on the carrying platform 62. The first knife 31 can include a main body 311, the main body 311 has at least two blades 312 respectively disposed on at least two sections of a side of the main body 311, and no blade 312 is disposed on the remaining sections of the
20 side of the main body 311.

In a practical application, the vertical movement module 32 of the first knife machine 3 can have a slide 321 and a slider 322, the slider 322 is controllable to slide on the slide 321, the horizontal movement module 33 of the first knife machine 3 can have a slide 331 and a slider 332, and the slider 332 is
25 controllable to slide on the slide 331. The first knife 31 is connected to the

slider 322 of the vertical movement module 32, and the slider 321 of the vertical movement module 32 is connected to the slider 332 of the horizontal movement module 33.

In a practical application, the transferring machine 6 is configured to move the semiconductor material A along an X-axis direction, the horizontal movement module 33 of the first knife machine 3 is configured to move the first knife 31 along a Y-axis direction, and the vertical movement module 32 of the first knife machine 3 is configured to move the first knife 31 along a Z-axis direction.

Referring to FIG. 1, the pulling machine 4 of the bag opening apparatus S1 can include a flipping device 41, an auxiliary abutting device 42, a movement device 43, and a clamping device 44. The flipping device 41 and the auxiliary abutting device 42 are disposed near the first knife machine 3, the movement device 43 is configured to move from a position near the first knife machine 3 to a position near the second knife machine 5, the clamping device 44 is connected to the movement device 43, the clamping device 44 is configured to clamp the tail structure A15, and the clamping device 44 can follow the movement device 43 to move from the position near the first knife machine 3 to the position near the second knife machine 5.

It is worth mentioning that, the pulling machine 4 is primarily configured to allow the tail structure A15 of the semiconductor material A to be vertically disposed relative to the packaging portion A13. In the present embodiment, the pulling machine 4 includes the flipping device 41, the auxiliary abutting device 42, the movement device 43, and the clamping device 44, but the components included by the pulling machine 4 are not limited thereto.

Referring to FIG. 8, the flipping device 41 can include a movement module 411, a rotatable module 412, a supporting structure 413, and a plurality of suction assemblies 414. The movement module 411 and the rotatable module 412 are electrically connected to the processing device 1, the movement module 411 is connected to the rotatable module 412, and the supporting structure 413 is connected to the rotatable module 412. The suction assemblies 414 are spaced apart from each other and disposed on the supporting structure 413. Each of the suction assemblies 414 is connected to an air suction device, and the processing device 1 can control the air suction device so that each of the suction assemblies 414 has a suction force, or control the air suction device so that each of the suction assemblies 414 no longer has the suction force.

The auxiliary abutting device 42 can include a vertical movement module 421, a horizontal movement module 422, and an auxiliary abutting member 423. The vertical movement module 421 is connected to the auxiliary abutting member 423, and the vertical movement module 421 is connected to the vertical movement module 422. The processing device 1 is electrically connected to the vertical movement module 421 and the horizontal movement module 422 of the auxiliary abutting device 42. The processing device 1 can control the vertical movement module 421 of the auxiliary abutting device 42 to be operated, so that the auxiliary abutting member 423 moves along a vertical direction (e.g., vertical to the ground, as the Z-axis direction shown in FIG. 9) toward or away from the semiconductor material A. The processing device 1 can control the horizontal movement module 422 of the auxiliary abutting device 42 to be operated, so that the auxiliary abutting member 243 moves along a horizontal direction (e.g., perpendicular to the vertical direction, as the Y-axis direction

shown in FIG. 9) toward or away from the semiconductor material A.

The processing device 1 can control the movement module 411 to be operated, so that the rotatable module 412, the supporting structure 413, and the suction assemblies 414 move along a horizontal direction (e.g., parallel to the ground, as the Y-axis direction shown in FIG. 9) toward or away from the semiconductor material A disposed on the carrying platform 62. The processing device 1 can control the rotatable module 412 to be operated, so that the supporting structure 413 rotates (e.g., taking the X-axis shown in FIG. 9 as a central axis for rotation) to change a direction of the suction assemblies 414.

The movement module 411 can include a driver 4111, a plurality of pushing rods 4112, and a connection member 4113. Two ends of each of the pushing rods 4112 are respectively connected to the driver 4111 and the connection member 4113, and the processing device 1 can control the driver 4111 to allow the pushing rods 4112 to move the connection member 4113 in a direction toward or away from the driver 4111. Accordingly, the rotatable module 412, the supporting structure 413, and the suction assemblies 414 are driven to move along the horizontal direction.

Reference is made to FIG. 8 to FIG. 12 and FIG. 14, which are schematic operational views showing the bag opening apparatus cutting off the two tapes A3 of the semiconductor material A disposed on the carrying platform 62 and holding the tail structure A15 according to the present disclosure. As shown in FIG. 8 to FIG. 10, when the carrying platform 62 has the semiconductor material A disposed thereon, the processing device 1 can control the auxiliary abutting device 42 to be operated, so that the auxiliary abutting member 423 moves to a position near the tail structure A15 of the semiconductor material A

and the auxiliary abutting member 423 abuts against the top surface of the packaging portion A13 of the semiconductor material A. Afterwards, the processing device 1 controls the first knife machine 3 to be operated, so that the two blades 312 of the first knife 31 cut off the two tapes A3 of the semiconductor material A.

Referring to FIG. 9 and FIG. 10, it is worth mentioning that the main body 311 of the first knife 31 can further include a protrusion structure 313 arranged between the two blades 312, and the protrusion structure 313 is configured to push against the tail structure A15. A distance between a side of the protrusion structure 313 and another side of the main body 311 (i.e., a side of the main body 311 that is away from the protrusion structure 313) is greater than a distance between a side of each of the blades 312 and said side of the main body 311.

Referring to FIG. 10, after the first knife 31 cuts off the two tapes A3, the processing device 1 can control the first knife 31 to move continuously, so that the first knife 31 enters between the tail structure A15 and the non-packaging portion A14 to push against the non-packaging portion A14 through the protrusion structure 313. Therefore, the tail structure A15 flips relative to the packaging portion A13, and an inner side A151 of the flipped tail structure A15 is exposed. In a process where the first knife 31 pushes the tail structure A15, the auxiliary abutting member 423 can still abut against the top surface of the packaging portion A13, but the present disclosure is not limited thereto. In this process, the auxiliary abutting member 423 can also not abut against the packaging portion A13.

Referring to FIG. 11 and FIG. 12, when the two tapes A3 are cut off, and

the tail structure A15 is pushed by the first knife 31 such that the inner side A151 of the tail structure A15 is exposed, the processing device 1 controls the flipping device 41 to be operated, so that the supporting structure 413 and the suction assemblies 414 disposed on the supporting structure 413 move onto the tail structure A15. At this time, the processing device 1 controls the air suction device to be operated, so that the suction assemblies 414 generate a suction force to suck onto the tail structure A15. After the suction assemblies 414 suck onto the tail structure A15, the processing device 1 controls the rotatable module 412 to be operated, so that the supporting structure 413 and the suction assemblies 414 disposed thereon rotate 90 degrees (the angle is not limited thereto). In this way, the tail structure A15 sucked by the suction assemblies 414 are vertically disposed relative to the packaging portion A13.

Referring to FIG. 13, the clamping device 44 can include a movement module 441, a connection arm 442, and a clamper 443. The connection arm 442 is connected to the movement module 441, and the clamper 443 is connected to the connection arm 442. The processing device 1 is electrically connected to the movement module 441, and the processing device 1 can control the movement module 441 to be operated, so that the connection arm 442 and the clamper 443 move from a position near the first knife machine 3 to a position near the second knife machine 5. The movement module 441 can include a slide 4411 and a slider 4412, the slider 4412 is connected to the connection arm 442, and the processing device 1 can control the slider 4412 to slide on the slide 4411. The clamper 443 can include a driver 4431 and two clamping arms 4432, the two clamping arms 4432 are connected to the driver 4431, and the processing device 1 can control the driver 4431 to allow the two

clamping arms 4432 to rotate toward or away from each other with respect to the driver 4431, so that the two clamping arms 4432 clamp or no longer clamp the tail structure A15.

Referring to FIG. 1, FIG. 14, and FIG. 15, when the suction assemblies 414
5 suck onto the tail structure A15 and the tail structure A15 is vertically disposed relative to the packaging portion A13, the processing device 1 controls the clamping device 44 to be operated, so that the connection arm 442 and the clamper 443 move to a position above the tail structure A15. Then, the processing device 1 controls the clamper 443 to clamp the tail structure A15.
10 After the clamper 443 clamps the tail structure A15, the processing device 1 controls the flipping structure 41 to be operated, so that the suction assemblies 414 no longer suck onto the tail structure A15. Further, the processing device 1 controls the clamping device 44 and the carrying platform 62 to be operated at the same time, so that the clamping device 44 and the semiconductor material A
15 move together to a position near the second knife machine 5.

Referring to FIG. 15 to FIG. 18, the second knife machine 5 is electrically connected to the processing device 1, and the processing device 1 can control the second knife machine 5 to cut off the tail structure A15, so that the tail structure A15 and the packaging portion A13 are separated from each other.
20 More specifically, the second knife machine 5 can include an abutting device 51 and a knife device 52 that face toward each other. The abutting device 51 can include a driver 511 and an abutting board 512 that are connected to each other. The processing device 1 is electrically connected to the driver 511, and the processing device 1 can control the driver 511 to be operated, so that the
25 abutting board 512 moves toward or away from the knife device 52.

Referring to FIG. 15 and 16, the knife device 52 can include a movement module 521, a shell 522, a second knife 523, and an extendable machine 524. The movement module 521 includes two drivers 5211 and a connection board 5212. The two drivers 5211 are electrically connected to the processing device 1, the connection board 5212 is connected to the two drivers 5211, and the processing device 1 can control the two drivers 5211 to be operated, so that the connection board 5212 moves toward or away from the abutting device 51. The connection board 5212 is connected to the shell 522, the second knife 523 is disposed in the shell 522, the shell 522 has a thru-hole, the extendable machine 524 is disposed in the shell 522, and the extendable machine 524 is connected to the second knife 523. The processing device 1 is electrically connected to the extendable machine 524, and the processing device 1 can control the extendable machine 524 to be operated, so that a portion of the second knife 523 protrudes from the shell 522 through the thru-hole 5221. Or, the processing device 1 can control the extendable machine 524 to be operated, so that the second knife 523 protruding from the shell 522 returns to the shell 522.

Referring to FIG. 16 to FIG. 18, when the two clamping arms 4432 of the clamper 443 of the clamping device 44 clamp the tail structure A15, and the tail structure A15 is correspondingly arranged between the abutting device 51 and the knife device 52, the processing device 1 controls the abutting device 51 and the two drivers 5211 of the movement module 521 of the second knife device 52 to be operated, so that the abutting board 512 and the connection board 5212 jointly hold the tail structure A15. When the abutting board 512 and the connection board 5212 jointly hold the tail structure A15, the processing device controls the extendable machine 524 to be operated, so that the second knife

523 protrudes from the thru-hole and cuts off the tail structure A15.

It is worth mentioning that as shown in FIG. 6, FIG. 15, and FIG. 16, in an exemplary embodiment, before the processing device 1 controls the second knife machine 5 to be operated, the processing device 1 can control the two abutting devices 22 to be operated, so that the two abutting members 222 abut against the bottom portion A131 of the protective bag A1. When the two abutting members 222 abut against the bottom portion A131 of the protective bag A1, the processing device 1 controls the clamping device 44 to be operated, so that the clasper 443 moves in a direction away from the carrying platform 62. At this time, the tail structure A15 is clamped by the clasper 443, and a portion of the tail structure A15 connected to the packaging portion A13 is in a relative tight state. When the tail structure A15 clamped by the clasper 443 is in the relatively tight state, the processing device 1 continues to control the second knife machine 5 to be operated, so that the second knife 523 cuts off the tail structure A15 when the abutting board 512 and the connection board 5212 jointly hold the tail structure A15. Since the portion of the tail structure A15 connected to the packaging portion A13 is in the relatively tight state when the tail structure A15 is clamped by the clasper 443, and then the second knife 523 cuts off the tail structure A15, it can be ensured that the second knife 523 smoothly cuts off the connection between the tail structure A15 and the packaging portion A13.

It is worth mentioning that in an embodiment of the present disclosure, the accommodating box A2 is a front opening unified pod and the protective bag A1 is an aluminum foil bag or an anti-static bag. Since the first knife 31 and the second knife 523 are respectively used to cut off the tapes A3 of the

semiconductor material A and the tail structure A15, it can be ensured that the first knife 31 and the second knife 523 can successfully and respectively cut off the tapes A3 and the tail structure A15. In addition, it can be ensured that a glue of the tapes A3 remained on the first knife 31 does not adhere to the front opening unified pod. In a practical application, the blade of the first knife 31 can be in a flat shape, and the blade of the second knife 523 can be in a jagged shape. In this way, the first knife 31 and the second knife 523 can successfully and respectively cut off the tapes A3 and the tail structure A15. If a knife having a blade that is in a jagged shape is used to sequentially cut off the tapes A3 and the tail structure A15, a substantial amount of the glue of the tapes A3 can remain on the blade after the knife is used to cut off the tapes A3 (as shown in FIG. 2). In this way, the blade of the knife loses its sharpness, and the glue may adhere to the front opening unified pod.

Referring to FIG. 17 and FIG. 18, after the second knife 523 cuts off the tail structure A15, the processing device 1 controls the abutting device 51 and the knife device 52 to be operated, so that the abutting board 512 and the connection board 5212 no longer hold the tail structure A15. Afterwards, the processing device 1 can control the carrying platform 62 to move on the slide 61, so that the semiconductor material A disposed on the carrying platform 62 leaves the second knife structure 5. After the second knife 523 cuts off the tail structure A15, the processing device 1 can control the clamping device 44 to be operated, so that the clamping device 44 moves to a particular position. After the clamping device 44 moves to the particular position, the processing device 1 controls the two clamping arms 4432 of the clamper 443 to no longer clamp the tail structure A15, and the tail structure A15 is released to the particular

position. After the tail structure A15 is cut off and is separated from the packaging portion A13, the packaging portion A13 forms a fetching opening A5, and the accommodating box A2 is exposed from the fetching opening A5.

Referring to FIG. 1 and FIG. 18 to FIG. 20, when the tail structure A15 of the semiconductor material A is cut off, the processing device 1 controls the carrying platform 62 to move along the rail 61, so that the packaging portion A13 forming the fetching opening A5 and the accommodating box A2 disposed therein move to the bag stretching machine 7. The bag stretching machine 7 is configured to stretch the fetching opening A5 of the packaging portion A13. After the fetching opening A5 is stretched, the processing device 1 can transmit a signal to a fetching device (not shown), and after the fetching device receives the signal, the fetching device takes out the accommodating box A2 from the packaging portion A13. In a practical application, the fetching device can include a robotic arm, but the present disclosure is not limited thereto. Any machine that is configured to take out the accommodating box A2 from the packaging portion A13 falls within the applicable scope of the fetching device.

Referring to FIG. 19 and FIG. 20, the bag fetching machine 7 can include two supporting structures 71, a lift module 72, four movement modules 73, four rod bodies 74, two auxiliary movement modules 75, two auxiliary boards 76, and two flipping devices 77. The two supporting structures 71 can be major supporting structures (not shown) for fixing the fetching apparatus S2, and the two supporting structures 71 face toward each other. The lift module 72 can include four lift assemblies 721, two ends of each of the supporting structures 71 are connected to two of the lift assemblies 721, and each of the lift assemblies 721 can include a driver 7211 and a plurality of pushing rods 7212.

The processing device 1 is electrically connected to the lift module 72, and the processing device 1 can control the lift module 72 to allow the driver 7211 of each of the lift assemblies 7211 to be operated, so that the pushing rods 7212 stretch relative to the drivers 7211, and the two supporting structures 71 accordingly move upward or downward relative to the carrying platform 62. The formation and the quantity of the components included by the lift module 72 are not limited to above description. In other embodiments, each of the supporting structures 71 can include one or at least three lift assemblies 721.

Each of the supporting structures 71 has two of the movement modules 73 disposed thereon, the two movement modules 73 are respectively disposed near two ends of one of the supporting structures 71, and each of the movement modules 73 is connected to one of the rod bodies 74. The processing device 1 is electrically connected to each of the movement modules 73, and the processing device 1 can control each of the movement modules 73, so that the rod bodies 74 move in a direction away from the supporting structures 71 or move in a direction toward the supporting structures 71. In a practical application, each of the movement modules 73 can include a driver 731, a plurality of pushing rods 732, and a connection member 733. The pushing rods 732 are connected to the driver 731, the connection member 733 is connected to a plurality of ends of the pushing rods 732, and the connection member 733 are configured to allow the rod bodies 74 and the pushing rods 732 to be connected to each other. In a practical application, each of the rod bodies 74 can be substantially in a columnar shape, and each of the rod bodies 74 connected to the movement module 73 can be substantially vertically disposed (i.e., perpendicular to a horizontal line).

Each of the auxiliary movement modules 75 is disposed on one of the supporting structures 71, and each of the auxiliary movement modules 75 is arranged between two adjacent ones of the movement modules 73. Each of the auxiliary movement modules 75 can include a driver 751, a plurality of pushing rods 752, and a connection member 753. The pushing rods 752 are connected to the driver 751, the connection member 753 is fixed to a plurality of ends of the pushing rods 752, and each of the connection members 753 is connected to one of the auxiliary boards 76. The processing device 1 is electrically connected to the auxiliary movement modules 75. The processing device 1 can control the drivers 751 to be operated, so that the pushing rods 752 move relative to the drivers 751, thereby allowing each of the auxiliary boards 76 to move in a direction toward the supporting structures 71 or in a direction away from the supporting structures 71.

It is worth mentioning that the two supporting structures 71 are arranged in a same plane, and the four movement modules 73 and the two auxiliary movement modules 75 can respectively allow the four rod bodies 74 and the two auxiliary boards 76 to substantially move in the same plane. In a practical application, the processing device 1 can simultaneously move the four movement modules 73 and the two auxiliary movement modules 75, but the present disclosure is not limited thereto. The processing device 1 can also independently control any one of the movement modules 73 or any one of the auxiliary movement modules 75 to be operated according to practical requirements.

Referring to FIG. 19 and FIG. 21, the two flipping devices 77 are disposed near the two supporting structures 71. Each of the flipping devices 77 can be a

major supporting structure (not shown) for fixing the bag opening apparatus. Each of the flipping devices 77 can include a movement module 771, a rotatable module 772, a supporting structure 773, and a plurality of suction assemblies 774. Each of the movement module 771 and the rotatable module 772 is electrically connected to the processing device 1, and the movement module 771 and the rotatable module 772 are connected to each other. Each of the supporting structures 773 is connected to one of the rotatable modules 772, and the rotatable module 772 is controllable to rotate one of the supporting structures 773. The suction assemblies 774 are spaced apart from each other and disposed on the supporting structures 773. Each of the suction assemblies 774 is connected to an air suction device, and the processing device 1 can control the air suction device so that each of the suction assemblies 774 has a suction force, or control the air suction device so that each of the suction assemblies 774 no longer has the suction force.

The processing device 1 can control the movement modules 771 to be operated, so that the rotatable modules 772, the supporting structures 773, and the suction assemblies 774 move along a horizontal direction (e.g., parallel to the ground, as a Y-axis direction shown in FIG. 21) toward or away from the semiconductor material A disposed on the carrying platform 62. The processing device 1 can control the rotatable modules 772 to rotate the supporting structures 773 (e.g., taking the X-axis shown in FIG. 9 as a central axis for rotation) to change the directions of the suction assemblies 774. Each of the movement modules 771 can include a driver 7711 and a plurality of pushing rods 7712. In each of the movement modules 771, the processing device 1 can control the driver 7711 to allow the pushing rods 7712 to extend or retract, and

the pushing rods 7712 are connected to one of the rotatable modules 772. Naturally, the components included by each of the movement modules 771 are not limited to the above description.

Referring to FIG. 22 to FIG. 24, an operational process of the bag stretching machine 7 stretching the packaging portion A13 can be described as follows. When the processing device 1 controls the carrying platform 62 to move along the rail 61 to a position below the bag stretching machine 7, the processing device 1 controls the two movement modules 771 of the two flipping devices 77, so that the two supporting structures 773 and the suction assemblies 774 connected thereto move to positions near the packaging portion A13. The processing device 1 then controls the two rotatable modules 772 to be operated, so that the supporting structures 773 and the suction assemblies 774 disposed thereon turn toward the packaging portion A13. Finally, the processing device 1 controls the air suction device to be operated, so that the suction assemblies A13 suck onto the packaging portion A13.

When the suction assemblies 774 of the two flipping devices 77 suck onto the packaging portion A13, the processing device 1 controls the two rotatable modules 772 to be operated, so that the two supporting structures 773 rotate away from the carrying platform 62. In this way, the packaging portion A13 sucked by the suction assemblies A13 is rotated away from the accommodating box A2, and the fetching opening A5 of the packaging portion A13 is stretched to a greater extent. In the present embodiment, each of the rotatable modules 772 allows the corresponding supporting structure 773 to rotate by 90 degrees, but the present disclosure is not limited thereto. The angle that the rotatable module 772 rotates the supporting structure 773 connected thereto can be

changed according to practical requirements.

It is worth mentioning that to facilitate the suction assemblies 774 of the two flipping devices 77 to suck onto the packaging portion A13 and to facilitate the packaging portion A13 to rotate away from the accommodating box A2, before the processing device 1 controls the two flipping devices 77 to be operated, the processing device 1 can control the two abutting devices 22 (as shown in FIG. 6 and FIG. 7) to be operated, so that the two abutting members 222 abut against the bottom portion A131 of the packaging portion A13.

Referring to FIG. 20, FIG. 23, and FIG. 24, after the suction assemblies 774 of the two flipping devices 77 suck onto the packaging portion A13 and rotate 90 degrees, the processing device 1 can control the four movement modules 771 and the two auxiliary movement modules 75 to be operated, so that the four rod bodies 74 and the two auxiliary boards 76 move toward each other (as shown in FIG. 20). Afterwards, the processing device 1 controls the lift module 72 to be operated, so that the two supporting structures 71 move toward the carrying platform 62, thereby allowing the four rod bodies 74 and the two auxiliary boards 76 to enter into the packaging portion A13 (as shown in FIG. 24) through the fetching opening A5. In a process where the four rod bodies 74 and the two auxiliary boards 76 enter into the packaging portion A13 through the fetching opening A5, the processing device 1 can control the two flipping devices 77 to be operated, so that the suction assemblies 774 no longer suck onto the packaging portion A13.

Referring to FIG. 24 and FIG. 25, when the four rod bodies 74 and the two auxiliary boards 76 are arranged in the packaging portion A13, the processing device 1 controls the four movement modules 73 and the two auxiliary

movement modules 75 to be operated, so that the four rod bodies 74 and the two auxiliary boards 76 move away from each other, thereby allowing the fetching opening A5 to be stretched to a maximum state (i.e., the packaging portion A13 is substantially in a tight state). In a practical application, when the rod bodies
5 74 stretch the fetching opening A5, the four rod bodies 74 can be substantially arranged at four corners of the packaging portion A13, and the two auxiliary boards 76 can be substantially arranged at two side surfaces of the packaging portion A13 that face toward each other.

When the four rod bodies 74 and the two auxiliary boards 76 stretch the
10 packaging portion A13 and the packaging portion A13 is substantially in the tight state, the processing device 1 can control the fetching device (e.g., various types of robotic arms) to take out the accommodating box A2 arranged in the packaging portion A13. The fetching device can be disposed near the bag stretching machine 7, but the present disclosure is not limited thereto.

15 In other embodiments, when the bag stretching machine 7 stretches the fetching opening A5 through the four rod bodies 74 and the two auxiliary boards 76, the processing device 1 can also control a related warning device (e.g., various types of lamps or speakers) to be operated, so as to notify a technical personnel through light or sound generated by the warning device to
20 take out the accommodating box A2 in the packaging portion A13. In a practical application, when the accommodating box A2 is taken out manually or taken out by the fetching device from the packaging portion A13, the bag stretching machine 7 can continuously stretch the fetching opening A5 of the packaging portion A13, but the present disclosure is not limited thereto.

25 The above-mentioned bag opening apparatus S1 of the present disclosure

can also not include the fetching device, and the bag opening apparatus S1 can be independently operated, manufactured, or sold. In addition, the processing device 1, the fixing machine 2, the first knife machine 3, the second knife machine 5, and the bag stretching machine 7 included by the above-mentioned bag opening apparatus S1 of the present disclosure and the fetching device can be jointly defined as a fetching apparatus. In other words, the components included by the above-mentioned bag opening apparatus S1 and the fetching device can be jointly operated, manufactured, and sold.

According to the above, the bag opening apparatus S1 and the fetching apparatus of the present disclosure can automatically cut off the tail structure A15 of the semiconductor material A, and then stretch the fetching opening A5 of the packaging portion A13 through the bag stretching machine 7. Finally, the technical personnel or the fetching device can easily and conveniently take out the accommodating box A2 from the packaging portion A13. Essentially, the process in which the bag opening apparatus S1 and the fetching apparatus of the present disclosure cut off the tail structure A15 and stretch the packaging portion A13 can be carried out automatically with no human power involved. In this way, an issue of the semiconductor material A being damaged due to inappropriate manual operation can be effectively prevented.

Conventionally, the tail structure A15 is manually cut off, and the opening of the packaging portion A13 is manually stretched. Such an operation not only wastes time and human power, but may also cause damage to the accommodating box A2 due to inappropriate manual operation or even damage to a wafer in the accommodating box A2. In addition, since this operation is carried out manually, when the technique personnel cannot go to work due to

unavoidable circumstances (e.g., the government imposing a lockdown), no operation can be carried out.

Referring to FIG. 26 to FIG. 29, FIG. 26 is a schematic view of a bag opening system of the present disclosure, FIG. 27 is a schematic view of a bag recycling apparatus of the bag opening system and the packaging portion of the protective bag according to the present disclosure, FIG. 28 is a schematic view showing a clamping module of the bag recycling apparatus of the bag opening system enters into the packaging portion of the protective bag according to the present disclosure, and FIG. 29 is a schematic view showing the protective bag being disposed onto a platform by the bag recycling apparatus of the bag opening system of the present disclosure. The bag opening system S of the present disclosure includes a fetching apparatus S2, a central control apparatus S3, and a bag recycling apparatus S4. The fetching apparatus S2 includes the bag opening apparatus S1 mentioned above and a fetching device 8. The fetching device 8 can be various types of robotic arms. The bag opening apparatus S1 is as described above, and will not be reiterated herein. The fetching device 8 is configured to take out the accommodating box A2 (as shown in FIG. 3) disposed in the packaging portion A13 (as shown in FIG. 3).

The central control apparatus S3 is electrically connected to the fetching apparatus S2 and the bag recycling apparatus S4. The central control apparatus S3 can control the fetching apparatus S2 to cut off the tail structure A15 of the semiconductor material A and take out the accommodating box A2 disposed in the packaging portion A13, and the central control apparatus S3 can then control the bag recycling apparatus S4 to fold and recycle the packaging portion A13. The central control apparatus S3 can be various types of computers or

servers. The central control apparatus S3 mentioned herein can be the processing device 1 mentioned above, or the central control apparatus S3 can be an apparatus independent from the processing device 1.

The bag recycling apparatus S4 can include a vertical movement module S41, a horizontal movement module S42, a clamping module S43, a platform S44, and a guiding structure S45. In the present embodiment, the bag recycling apparatus S4 includes two movement modules (i.e., the vertical movement module S41 and the horizontal movement module S42), but the quantity and the formation of the movement modules included by the bag recycling apparatus S4 are not limited thereto.

The vertical movement module S41 is connected to the clamping module S43, and the horizontal movement module S42 is connected to the vertical movement module S41. The central control apparatus S3 is electrically connected to the vertical movement module S41 and the horizontal movement module S42. The central control apparatus S3 can control the vertical movement module S41 to be operated, so that the clamping module S43 moves along a vertical direction (e.g., a direction perpendicular to the ground, such as the Z-axis direction shown in FIG. 22) toward or away from the packaging portion A13. The central control apparatus S3 can control the horizontal movement module S42 to be operated, so that the clamping module S42 moves along a horizontal direction (e.g., a direction perpendicular to the vertical direction, such as the Y-axis direction shown in FIG. 22) toward or away from the packaging portion A13.

The central control apparatus S3 is electrically connected to the clamping module S43, and the central control apparatus S43 can control the clamping

module S43 to be operated, so that the clamping module S43 clamps the packaging portion A13. The clamping module S43 can include a driving assembly S431, two clamping arms S432, and an entering member S433. The two clamping arms S432 are connected to the driving assembly S431, and the entering member S433 is arranged between the two clamping arms S432. The central control apparatus S3 is electrically connected to the driving assembly S431, and the central control apparatus S3 can control the driving assembly S431 to be operated, so that the two clamping arms S432 move in a direction toward or in a direction away from the entering member S433. The driving assembly S431 can include a rail and a related driver, and the two clamping arms S432 can be slidably disposed on the rail of the driving assembly S431.

The entering member S433 has two end surfaces that are opposite to each other and defined as two first abutting surfaces S4331, each of the clamping arms S432 has a second abutting surface S4321, and each of the second abutting surfaces S4321 faces toward one of the first abutting surfaces S4331. The first abutting surfaces S4331 and the second surfaces S4321 facing toward each other can jointly hold the packaging portion A13. In a practical application, the first abutting surfaces S4331 and the second abutting surfaces S4321 can be rectangular surfaces having a substantially uniform structure and a substantially uniform dimension. Naturally, the structure and the dimension of the first abutting surfaces S4331 and the second abutting surfaces S4321 are not limited to those shown in FIG. 22. As long as the first abutting surfaces S4331 and the second abutting surfaces S4321 facing toward each other can jointly hold the packaging portion A13, the structure and the dimensions of the first abutting surfaces S4331 and the second abutting surfaces S4321 can be changed

according to practical requirements.

The platform S44 is disposed at a side of the rail 61 of the transferring machine 6, the guiding structure S45 is disposed at one end of the platform S44, the platform S44 is disposed near the horizontal movement module S42, and the
5 horizontal movement module S42 of the bag recycling apparatus S4 can move the clamping module S43 to a position above the platform S44.

A process in which the bag recycling apparatus S4 recycles the packaging portion A13 can be described as follows. As shown in FIG. 27, when the accommodating box A2 (as shown in FIG. 3) disposed in the packaging portion
10 A13 is taken out, and the carrying platform 62 moves to a position below the bag recycling apparatus S4, the central control apparatus S3 can control the two abutting devices 22 of the fixing machine 2 to be operated, so that the two abutting members 222 abut against the bottom portion A131 of the packaging portion A13. Afterwards, the central control apparatus S3 controls the
15 horizontal movement module S42, so that the clamping module S43 moves to a position above the fetching opening A5 of the packaging portion A13. As shown in FIG. 28, the central control apparatus S3 then controls the vertical movement module S41 to be operated, so that the entering member S433 enters into the packaging portion A13 through the fetching opening A5 of the
20 packaging portion A13, and the two clamping arms S432 are correspondingly arranged outside the packaging portion A13.

As shown in FIG. 28, when the entering member S433 is arranged inside the packaging portion A13, and the two clamping arms S432 are arranged outside the packaging portion A13, the central control apparatus S3 controls the
25 driving assembly S431 to be operated, so that each of the clamping arms S432

moves toward the entering member S433. In this way, each of the clamping arms S432 and the entering member S433 jointly hold the packaging portion A13, and the packaging portion A13 jointly held by the two clamping arms S432 and the entering member S433 folds along a plurality of creases A4 at two
5 sides of the packaging portion A13.

After the two clamping arms S432 and the entering member S433 jointly hold the packaging portion A13, the central control apparatus S3 controls the vertical movement module S41 to move in a direction away from the packaging portion A13. At this time, the two abutting members 222 of the two abutting
10 devices 22 still abut against the bottom portion A131 of the packaging portion A13. In this way, the packaging portion A13 is substantially in a flattened state.

After the packaging portion A13 is substantially in the flattened state, the central control apparatus S3 controls the two abutting devices 22 to no longer abut against the bottom portion A131 of the packaging portion A13.
15 Afterwards, the central control apparatus S3 controls the horizontal movement module S42 to be operated, so that the packaging portion A13 clamped by the clamping module S43 moves toward the platform S44. When the clamping module S43 moves, the packaging portion A13 is guided by the guiding structure S45 and falls toward the platform S44. As shown in FIG. 29, after the
20 packaging portion A13 falls toward the platform S44, the central control apparatus S3 controls the clamping module S43 to no longer clamp the packaging portion A13, and the folded packaging portion A13 is placed on the platform S44. In a practical application, when the central control apparatus S3 controls the clamping module S43 to no longer clamp the packaging portion
25 A13, the central control apparatus S3 can further control the vertical movement

module S41 to be operated, so that the entering member S433 abuts against the packaging portion A13 lying flat on the platform S44.

In other embodiments, the platform S44 can be connected to a movement module S46, the central control apparatus S3 is electrically connected to the movement module S46, and the central control apparatus S3 can control the movement module S46 to be operated, so that the platform S44 moves toward the carrying platform 62. In a process where the central control apparatus S3 controls the horizontal movement module S42 to allow the packaging portion A13 clamped by the clamping module S43 to move toward the platform S44, the central control apparatus S3 can further control the movement module S46 to be operated at the same time, so that the movement module S46 moves toward the carrying platform 62 and the platform S44 pushes the packaging portion A13 clamped by the clamping module S43. In this way, the packaging portion A13 can easily lie flat on the platform S44.

Referring to FIG. 2, FIG. 3, and FIG. 30, the fetching method of the present disclosure is configured to take out the accommodating box A2 in the protective bag A1 of the semiconductor material A. The fetching method includes a positioning step A11, a cutting step S12, a stretching step S13, and a taking out step S14.

The positioning step S11 is implemented by fixing the semiconductor material. The cutting step S12 is implemented by controlling at least one knife machine to sequentially cut off the tape and the tail structure, so that the packaging portion forms a fetching opening and the accommodating box is exposed from the fetching opening. The stretching step S13 is implemented by controlling a bag stretching machine to stretch the packaging portion. The

taking out step S14 is implemented by controlling a fetching device to enter into the packaging portion, hold the accommodating box, and take out the accommodating box from the packaging portion.

5 The fetching method of the present disclosure can be implemented by the fetching apparatus mentioned above, but the present disclosure is not limited thereto. Referring to FIG. 8, FIG. 12, and FIG. 17, in an embodiment of the present disclosure, the fetching apparatus mentioned above is used to implement the fetching method of the present disclosure. In the cutting step S2, after the first knife machine 3 is controlled to cut off the tapes A3, the tail
10 structure A15 is in a movable state. Then, the second knife machine 5 is controlled to cut off the tail structure A15, so that the packaging portion A13 forms the fetching opening A5.

Referring to FIG. 19, FIG. 21 to FIG. 24, and FIG. 31, FIG. 31 is another flowchart of the bag opening method of the present disclosure. The fetching
15 method of the present embodiment includes a positioning step S21, a cutting step S22, a bag opening step S23, a stretching step S24, and a taking out step S25. The cutting step S22 and the taking out step S25 of the present embodiment are respectively the same as the cutting step S12 and the taking out step S14 of the previous embodiment, and will not be reiterated herein.

20 Referring to FIG. 6 and FIG. 7, the positioning step S21 of the present embodiment is implemented by controlling the drivers 211 of the four pushing devices 21 of the fixing machine 2 so that the four pushing members 212 respectively push against four side surfaces of the semiconductor material A, and controlling the drivers 221 of the two abutting devices 22 so that the two
25 abutting members 222 abut against the packaging portion A13. Accordingly,

the semiconductor material A disposed on a carrying platform 62 is fixed.

The bag opening step S23 is implemented by controlling the suction assemblies 774 (as shown in FIG. 23) to suck onto an outer surface of the packaging portion A13 and flipping the suction assemblies 774 away from the accommodating box A2 (as shown in FIG. 3). Through the design of the bag opening step S23, a diameter of the fetching opening A5 (as shown in FIG. 23) can be enlarged.

The difference between the stretching step S24 of the present embodiment and the stretching step S13 mentioned above is as follows. After the four rod bodies 74 of the bag stretching machine 7 (as shown in FIG. 7) enter into the packaging portion, at least one of the movement modules 73 (as shown in FIG. 20) is controlled to be operated, so that the four rod bodies 74 (as shown in FIG. 20) move away from the accommodating box A2 (as shown in FIG. 3) to stretch the packaging portion A13 (as shown in FIG. 25).

In the above description, the related components of the above-mentioned bag opening apparatus provided by the present disclosure are used for clarification purposes, and the structure of each of the components in the present embodiment is not limited to the structure of the bag opening apparatus mentioned above.

20

[Beneficial Effects of the Embodiments]

In conclusion, the fetching method, the fetching apparatus, and the bag opening apparatus of the present disclosure can automatically and swiftly cut off the tail structure of the semiconductor material, so that the packaging portion of the semiconductor material is in an opened state, and the

25

accommodating box is eventually taken out from the packaging portion by the fetching device. Essentially, no human power is involved in the bag opening process. In this way, the need for human power can be effectively reduced. In a conventional application, the tape and the tail structure are manually cut off.

5 Therefore, excessive human power is required and the efficiency is low. Moreover, the wafer stored in the accommodating box is very expensive. When the packaging portion of the semiconductor is manually opened and the accommodating box is manually taken out, there is also a possibility of the technical personnel damaging the wafer in the accommodating box due to
10 various reasons.

The foregoing description of the exemplary embodiments of the disclosure has been presented only for the purposes of illustration and description and is not intended to be exhaustive or to limit the disclosure to the precise forms disclosed. Many modifications and variations are possible in light of the above
15 teaching.

The embodiments were chosen and described in order to explain the principles of the disclosure and their practical application so as to enable others skilled in the art to utilize the disclosure and various embodiments and with various modifications as are suited to the particular use contemplated.
20 Alternative embodiments will become apparent to those skilled in the art to which the present disclosure pertains without departing from its spirit and scope.

CLAIMS

What is claimed is:

1. A fetching method configured to take out an accommodating box in a protective bag of a semiconductor material, wherein the protective bag has an accommodating space and an opening, the accommodating box is disposed in the accommodating space through the opening, the protective bag is configured to have a packaging portion and a non-packaging portion, the packaging portion covers an outer periphery of the accommodating box, the non-packaging portion is folded into a tail structure, a tape is adhered to the packaging portion and the tail structure, and the tape is configured to fix the tail structure to the packaging portion, the fetching method comprising:
 - a positioning step implemented by fixing the semiconductor material;
 - a cutting step implemented by controlling one or more knife machines to sequentially cut off the tape and the tail structure, so that the packaging portion forms a fetching opening and the accommodating box is exposed through the fetching opening;
 - a stretching step implemented by controlling a bag stretching machine to stretch the packaging portion; and
 - a taking out step implemented by controlling a fetching device to enter into the packaging portion, hold the accommodating box, and take out the accommodating box from the packaging portion.
2. The fetching method according to claim 1, wherein, in the cutting step, two of the one or more knife machines are sequentially controlled, and the two

knife machines are respectively defined as a first knife machine and a second knife machine, and wherein, in the cutting step, the first knife machine is controlled to cut off the tape, so that the tail structure is in a movable state, and then the second knife machine is controlled to cut off the tail structure, so that the packaging portion forms the fetching opening.

3. The fetching method according to claim 2, further comprising a bag opening step between the cutting step and the stretching step, wherein the bag opening step is implemented by controlling a plurality of suction assemblies to suck onto an outer side of the packaging portion and flipping the suction assemblies in a direction away from the accommodating box.
4. The fetching method according to claim 2, wherein, in the stretching step, four rod bodies of the bag stretching machine are controlled to enter into the packaging portion, and then at least one movement module is controlled to allow the four rod bodies to move away from the accommodating box, so as to stretch the packaging portion.
5. The fetching method according to claim 1, wherein, in the positioning step, four pushing devices of a holding machine are controlled to respectively push against four side surfaces of the semiconductor material, and two abutting devices are controlled to abut against the packaging portion to fix the semiconductor material that is disposed on a carrying platform, wherein each of the pushing devices includes one of a plurality of drivers and one of a plurality of pushing members, and in the positioning step, the four drivers are controlled, so that the four pushing members push against the packaging

portion and the accommodating box, and wherein each of the abutting devices includes one of a plurality of drivers and one of a plurality of abutting members, and in the positioning step, the two drivers of the two abutting devices are controlled, so that the two abutting members of the two abutting devices only abut against the packaging portion.

6. A fetching apparatus configured to take out an accommodating box in a protective bag of a semiconductor material, wherein the protective bag has an accommodating space and an opening, the accommodating box is disposed in the accommodating space through the opening, the protective bag is configured to have a packaging portion and a non-packaging portion, the packaging portion covers an outer periphery of the accommodating box, the non-packaging portion is folded into a tail structure, a tape is adhered to the packaging portion and the tail structure, and the tape is configured to fix the tail structure to the packaging portion, the fetching apparatus comprising:

- a processing device;

- a fixing machine electrically connected to the processing device, wherein the processing device is configured to control the fixing machine to fix the semiconductor material;

- one or more knife machines electrically connected to the processing device and configured to cut off the tape and the tail structure;

- a bag stretching machine electrically connected to the processing device and configured to stretch the packaging portion; and

- a fetching device electrically connected to the processing device and

configured to take out the accommodating box disposed in the packaging portion from the packaging portion,

wherein, the processing device controls the fixing machine to fix the semiconductor material, and then the processing device controls the one or more knife machines to cut off the tape and the tail structure, so that the packaging portion forms a fetching opening and the accommodating box is exposed through the fetching opening, and wherein, after the accommodating box is exposed through the fetching opening, the processing device sequentially controls the bag stretching machine to stretch the packaging portion and controls the fetching device to enter into the packaging portion, so as to take out the accommodating box.

7. The fetching apparatus according to claim 6, wherein the fetching apparatus includes two of the one or more knife machines that are respectively defined as a first knife machine and a second knife machine, the first knife machine includes a first knife and a first knife driver, the second knife machine includes a second knife and a second knife driver, the processing device is electrically connected to the first knife driver and the second knife driver, the first knife is connected to the first knife driver, and the second knife is connected to the second knife driver, and wherein the processing device is configured to control the first knife driver to drive the first knife to cut off the tape, and the processing device is configured to control the second knife driver to drive the second knife to cut off the tail structure.
8. The fetching apparatus according to claim 6, further comprising a transferring machine, wherein the transferring machine includes a rail and a

carrying platform, the carrying platform is controllable to move along the rail, the fixing machine is disposed on the carrying platform, the fixing machine includes four pushing devices, and each of the pushing devices includes a driver and a pushing member, wherein in each of the pushing devices, the driver is electrically connected to the processing device, and the pushing member is connected to the driver, and wherein, when the processing device is disposed on the carrying platform, the processing device controls the four pushing devices, so that four pushing members push against the packaging portion and the accommodating box.

9. The fetching apparatus according to claim 6, further comprising two abutting devices, wherein each of the abutting devices includes one of a plurality of drivers and one of a plurality of abutting members, wherein in each of the abutting devices, the driver is electrically connected to the processing device, and the abutting member is connected to the driver, and wherein the processing device is configured to control the two drivers, so that the two abutting members only abut against the packaging portion.
10. The fetching apparatus according to claim 6, wherein the bag stretching machine includes a lift module, two supporting structures, four rod bodies, and four movement modules, the lift module is electrically connected to the processing device, the two supporting structures are connected to the lift module, each of the supporting structures has two of the movement modules disposed thereon, and each of the rod bodies is connected to one of the movement modules, wherein the processing device is electrically connected to the lift module and the four movement modules, and the

processing device is configured to control the lift module, so that the four rod bodies enter into the packaging portion through the fetching opening, and wherein the processing device is configured to control the four movement modules, so that the four rod bodies in the packaging portion move away from the accommodating box to stretch the packaging portion.

11. The fetching apparatus according to claim 10, wherein the fetching machine further includes two auxiliary movement modules and two auxiliary boards, the two auxiliary movement modules are disposed on the two supporting structures, each of the auxiliary boards is connected to one of the auxiliary movement modules, and the processing device is configured to control the lift module, so that the two auxiliary boards enter into the packaging portion, and wherein the processing device is configured to control the two auxiliary movement modules, so that the auxiliary boards move away from the accommodating box to stretch the packaging portion.
12. The fetching apparatus according to claim 6, further comprising two flipping devices, wherein each of the flipping devices includes a movement module, a rotatable module, a supporting structure, and a plurality of suction assemblies, wherein in each of the flipping devices, the movement module and the rotatable module are electrically connected to the processing device, the movement module is connected to the rotatable module, the supporting structure is connected to the rotatable module, the rotatable module is controllable to rotate the supporting structure, and the suction assemblies are fixed to the supporting structure, and wherein the processing device controls the suction assemblies to suck onto an outer side

of the packaging portion, and then the processing device is configured to control the two rotatable modules to flip the two supporting structures, so that the suction assemblies flip the packaging portion away from the accommodating box.

13. A bag opening apparatus configured to take out an accommodating box in a protective bag of a semiconductor material, wherein the protective bag has an accommodating space and an opening, the accommodating box is disposed in the accommodating space through the opening, the protective bag is configured to have a packaging portion and a non-packaging portion, the packaging portion covers an outer periphery of the accommodating box, the non-packaging portion is folded into a tail structure, a tape is adhered to the packaging portion and the tail structure, and the tape is configured to fix the tail structure to the packaging portion, the bag opening apparatus comprising:

- a processing device configured to be communicatively connected to a fetching device;

- a fixing machine electrically connected to the processing device, wherein the processing device is configured to control the fixing machine to fix the semiconductor material;

- one or more knife machines electrically connected to the processing device and configured to cut off the tape and the tail structure; and

- a bag stretching machine electrically connected to the processing device and configured to stretch the packaging portion,

- wherein the processing device controls the fixing machine to fix the semiconductor material, and then the processing device controls the one or

more knife machines to cut off the tape and the tail structure, so that the packaging portion forms a fetching opening and the accommodating box is exposed through the fetching opening, wherein, after the accommodating box is exposed through the fetching opening, the processing device sequentially controls the bag stretching machine to stretch the packaging portion, and wherein, when the bag stretching machine stretches the packaging portion, the processing device is configured to transmit a signal to the fetching device, so that the fetching device takes out the accommodating box from the packaging portion.

14. A fetching system, comprising the fetching apparatus as claimed in any one of claims 6 to 12, a central control apparatus, and a bag recycling apparatus, wherein the central control apparatus is electrically connected to the fetching apparatus and the bag recycling apparatus, and wherein the central control apparatus is configured to control the fetching apparatus to cut off the tail structure of the semiconductor material and take out the accommodating box in the packaging portion, and then the central control apparatus controls the bag recycling apparatus to fold and recycle the packaging portion.

15. The fetching system according to claim 14, wherein the bag recycling apparatus includes at least one movement module, a clamping module, and a platform, the at least one movement module is connected to the clamping module, the clamping module includes two clamping arms and an entering member, the entering member is arranged between the two clamping arms, each of the clamping arms faces toward the entering member, and each of

the clamping arms is controllable to move in a direction toward the entering member or move in a direction away from the entering member, so as to clamp the packaging portion or no longer clamp the packaging portion, wherein the central control apparatus is electrically connected to the bag recycling apparatus, and wherein the central control apparatus is configured to control the clamping module and the at least one movement module to clamp and move the packaging portion to the platform.