(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
12 August 2004 (12.08.2004)

PCT

(10) International Publication Number
WO 2004/067883 A3

(51) International Patent Classification[7]: E21B 7/12

(21) International Application Number:
PCT/US2004/002053

(22) International Filing Date: 26 January 2004 (26.01.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

60/442,939	27 January 2003 (27.01.2003)	US
10/764,199	23 January 2004 (23.01.2004)	US

(71) Applicant *(for all designated States except US)*: **DRIL-QUIP, INC.** [US/US]; 13550 Hempstead Highway, Houston, TX 77040 (US).

(72) Inventor; and

(75) Inventor/Applicant *(for US only)*: **REIMERT, Larry, E.**; 6 Winners Circle, Houston, TX 77024 (US).


(74) Agent: **HELMREICH, Loren, G.**; Browning Bushman P.C., 5718 Westheimer, Suite 1800, Houston, TX 77057 (US).

(81) Designated States *(unless otherwise indicated, for every kind of national protection available)*: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States *(unless otherwise indicated, for every kind of regional protection available)*: ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,

[Continued on next page]

(54) Title: CONTROL POD LATCHDOWN MECHANISM



(57) Abstract: A latchdown mechanism 11 latches a control pod 10 to a lower mounting plate 14 of a subsea tree. A receptacle housing 12 secured to subsea tree receives the control pod therein and has an interior latching surface 13 at an upper end of the receptacle housing. A latchdown actuator 15 is supported on the control pod, and moves a plurality of gripping arms 22 for engagement and disengagement with the latching surface to selectively connect and disconnect the control pod 12 to the structure in response to the latchdown actuator.

WO 2004/067883 A3

GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report*
— *with amended claims*

(88) Date of publication of the international search report: 3 February 2005

Date of publication of the amended claims: 24 March 2005

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.