

## DESCRIPTION

INSPECTION SYSTEM FOR INSPECTING DISCRETE WIRING  
PATTERNS FORMED ON A CONTINUOUS SUBSTRATE SHEET OF  
A FLEXIBLE MATERIAL

5

## TECHNICAL FIELD

The present invention is directed to an inspection system for  
inspecting discrete wiring patterns formed on a continuous substrate  
sheet of a flexible material, and more particularly to such inspection  
10 system capable of feeding the wiring patterns for inspection by use of  
the substrate sheet as a feeding carrier or conveyer.

## BACKGROUND ART

In the manufacture of the printed boards, it has been a quite common  
to form a number of identical wiring patterns on a continuous substrate  
15 sheet of a relatively flexible material and then to cut the substrates into  
the discrete circuit boards each having the wiring pattern for an end use.  
For inspection of the wiring patterns of the circuit boards, it has been  
proposed to place the discrete circuit boards one by one on a suitable  
conveyer for feeding the boards into an inspection zone where they are  
20 successively scanned for inspection of the wiring pattern. However,  
this inspection system suffers from a problem in that the boards must be  
accurately located on the conveyer for exact registration with the camera  
in the inspection zone, and that the system necessitates the conveyer.

## 25 SUMMARY OF THE INVENTION

The present invention has been achieved in view of the above  
problem and provides an advantageous system for inspecting discrete

wiring patterns on a continuous substrate sheet of a flexible material by making the use of the substrate sheet as a feeding carrier. Therefore, a main object of the present invention is to provide the inspection system capable of using the substrate sheet as the feeding carrier and of assuring  
5 accurate positioning of the wiring patterns for reliable inspection even with the use of the flexible substrate sheet as the sole feeding carrier.

The inspection system in accordance with the present invention includes an inspection zone provided with camera means for inspecting the individual wiring patterns and detecting a position of said wiring pattern  
10 on the substrate sheet. A draw-in roller is provided to introduce the substrate into the inspection zone. Associated with the draw-in roller is a draw-out roller which draws out the substrate sheet from the inspection zone and is positioned to define the inspection zone between the draw-in roller and the draw-out roller as well as to give a tension to the substrate  
15 sheet for extending the substrate sheet straight through the inspection zone. A control means is provided to control a position of the substrate sheet passing through the inspection zone based upon a position signal detected by the camera means as indicative of the position of the individual wiring patterns on the substrate sheet within the inspection  
20 zone. Thus, the wiring pattern can be exactly positioned within the inspection zone relative to the camera means for reliable inspection thereby.

Since the wiring patterns can be formed on the substrate sheet at a regular precise interval, the exact positioning of the wiring pattern in the  
25 inspection zone is made to compensate for a possible lateral shift of the substrate sheet being fed and for a possible angular directional divergence of the substrate sheet from an intended feed direction. In

order to compensate for such undesired erroneous movement of the substrate sheet during the feed, the present invention is contemplated to utilize a feeder of feeding the substrate sheet into the inspection zone and a collector of collecting the substrate sheet as constituting an exact  
5 positioning mechanism. The mechanism allows the draw-in roller as well as the draw-out roller to shift in a direction transverse to the feeding direction. The control means operates, in response to the position signal, to shift at least one of the draw-in roller and the draw-out roller for correct positioning of the wiring pattern within the inspection zone.

10 The present invention discloses various modes of feeding the substrate sheet for reliable inspection of the wiring patterns, and specific features in association with the individual modes. For all modes, the camera means is composed of an inspection camera means and a position camera means. The inspection camera means provides a scanned image  
15 of the wiring pattern to an image inspector where the scanned image is compared with a reference image for determination of a defect in the wiring pattern. The position camera means detects marks on the substrate sheet to acknowledge a pre-inspection position of the wiring pattern which is just before being inspected by the inspection camera and  
20 provides the position signal indicative of the pre-inspection position.

In a first mode, the substrate sheet is fed at a uniform speed and the inspection camera means is composed of an array of inspection cameras arranged in a direction transverse to a feeding direction of the substrate sheet in such a manner to cover a whole width of the wiring patterns.  
25 A speed sensor is provided to detect the feeding speed of the substrate sheet and to provide a speed signal indicative of the feeding speed. The control means is responsive to the speed signal to feed the substrate

sheet at the uniform speed. Further, based upon the position signal as well as the speed signal, the control means activates the inspection camera means for scanning the image of the wiring pattern in synchronism with the position of the wiring pattern.

5 In a second mode, the inspection camera means comprises an array of inspection cameras arranged in an array direction transverse to a feeding direction of the substrate sheet so as to cover the whole width of the wiring pattern when the array is shifted between a first position and a second position in the array direction. The control means operates to  
10 feed the substrate sheet forwardly along the feeding direction by one forward step during which the inspection camera means at the first position completes scanning of a portion of the wiring pattern, and subsequently to feed the substrate sheet reversely by one reverse step during which the inspection camera means at the second position  
15 completes scanning of the rest of the wiring pattern.

In a third mode, the control means operates to feed the substrate sheet intermittently such that the wiring pattern is held stationary at an inspection position for a predetermined period during which the inspection camera means is controlled to move relative to the wiring  
20 pattern for inspection of the wiring pattern.

In a fourth mode, the inspection camera means comprises an array of inspection cameras arranged in a direction parallel to a feeding direction of the substrate sheet so as to cover the whole width of the wiring pattern when the array reciprocates by one cycle along a  
25 transverse direction perpendicular to the feeding direction. The control means operates to hold the substrate sheet at a first inspection position where the inspection camera means is shifted by half of the one cycle in

the transverse direction in order to scan a portion of the wiring pattern, and subsequently feed the substrate sheet by one step to a second inspection position where the inspection camera is shifted by the remaining half of the one cycle in the transverse direction in order to scan the rest of the wiring pattern. In this way, the control means operate to feed the substrate sheet intermittently so that the wiring pattern is held stationary at the first and second inspection positions at which the inspection camera means is controlled to move relative to the wiring pattern for inspection of the wiring pattern.

For the second, third, and fourth modes where the substrate sheet is held stationary or fed stepwise during the inspection of the wiring pattern by the inspection camera means, it is advantageous to provide a suction table behind the substrate sheet so as to hold the substrate sheet flat on the suction table for facilitating the inspection. The suction table may be movable in synchronism with the substrate sheet being fed step-wise during the inspection. Further, the suction table may be utilized to effect correct positioning of the wiring pattern in relation to the inspection camera means based on the position signal from the position camera means. For this purpose, the suction table is disposed to have its feed axis extending along a feeding direction of the substrate sheet and is capable of swinging around a vertical axis perpendicular to a plane of the substrate sheet so as to adjust an angle of the feed axis with respect to the feeding direction, thereby compensating for an angular divergence of the substrate from an intended feed direction.

These and still other objects and advantageous features of the present invention will become more apparent from the following description of the preferred embodiments when taken in conjunction

with the attached drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of an inspection system in accordance with  
5 a first embodiment of the present invention;

FIG. 2 is a block diagram of the inspection system;

FIG. 3 is a sectional view of a substrate sheet on which a number of  
wiring patterns are formed;

FIG. 4 is a plan view of the substrate sheet with the wiring patterns to be  
10 inspected;

FIG. 5 is a schematic top view of the system;

FIG. 6 is a partial view of the substrate for explaining an operation of  
correcting the position of the wiring pattern;

FIGS. 7A to 7E are views for explaining the operation of an inspection  
15 system in accordance with a second embodiment of the present  
invention;

FIGS. 8A and 8B are schematic views for explaining an operation of a  
suction table applicable to the above embodiment;

FIG. 9A and 9B are schematic views for explaining an operation of  
20 another suction table also applicable to the above embodiment;

FIG. 10 is a schematic view of an inspection system in accordance with a  
third embodiment of the present invention;

FIGS. 11A to 11E are views for explaining the operation of an  
inspection system in accordance with a fourth embodiment of the present  
25 invention;

FIG. 12 is a schematic view of a modification of the fourth embodiment;  
and

FIG. 13 is a schematic view of an inspection system in accordance with a fifth embodiment of the present invention.

## DETAILED DESCRIPTION OF THE EMBODIMENTS

### 5 First Embodiment <FIGS. 1 to 6>

Referring now to FIG. 1, there is shown an inspection system in accordance with a first embodiment of the present invention. The system is provided to inspect discrete wiring patterns formed on a continuous substrate sheet of a flexible material. For example, as  
10 shown in FIG. 3, the substrate sheet **10** is a laminate composed of a 0.04 mm to 0.2 mm thick resin-impregnated glass-sheet **11** and two outer 35  $\mu$ m thick copper layers **12**. The wiring patterns **14** are formed on the upper copper layer **12** by etching. The wiring patterns to be inspected by the present system may be otherwise those of a resist material  
15 deposited on the copper layer. The substrate sheet **10** are formed adjacent to the individual wiring patterns **14** with plural sets of position markings **16**, each set having two dot markings **16** arranged transversely of a length of the substrate sheet **10**, as shown in FIG. 4. The markings **16** are printed together with the wiring patterns **14** on the substrate **10** at  
20 precise locations and can be therefore utilized as calibrations for the substrate sheet.

The system includes a feeder **20**, a collector **40**, and an inspection zone **30** provided therebetween. The feeder **20** includes a unwinder **21** of unwinding a roll of the substrate sheet **10**, feed rollers **22**, **23**, **24**, and  
25 a dancer roller **25**. A recovery roller **26** is provided adjacent to the unwinder **21** to recover a protective film **18** from the underside of the substrate sheet **10**. The substrate sheet **10** from the feeder **20** is

introduced into the inspection zone **30** by means of a draw-in roller composed of a driving roller **31** and a pinch roller **32**, and is guided into the collector **40** by a draw-out roller composed of a driving roller **33** and a pinch roller **34**. The collector **40** includes a winder **41** of winding the  
5 substrate sheet, feed rollers **42**, **43**, **44**, and a dancer roller **45**. A supply roller **46** is provided adjacent to the winder **41** to supply a like protective film on the underside of the substrate being wound on the winder **41**. The draw-in roller and the draw-out roller are so positioned to define therebetween the inspection zone **30** and to give a tension of  
10 extending the substrate sheet **10** horizontally in the inspection zone **30**. A guide table **36** is juxtaposed below the substrate sheet **10** in the inspection zone for guiding the substrate sheet flat on the table **35**. The feeder **20** as well as the collector **40** are both made movable in a direction transverse to the feeding direction of the substrate sheet in  
15 order to make a fine adjustment of a transverse position of the substrate sheet as well as a feeding direction. For this purpose, the feeder **20** is carried by a frame **28** which is movably supported to a fixed base **29** to allow the transverse movement of the feeder **20**. Likewise, the collector **40** is carried by a frame **48** which is movably supported to a  
20 fixed base **49** to allow the transverse movement of the collector **40**.

The inspection zone **30** is provided with a pair of position cameras **51** for monitoring the position markings **16** and an inspection camera **54** for scanning the wiring patterns **14**. The inspection camera **54** includes an array of camera units **55** arranged closely in a transverse array  
25 perpendicular to the feeding direction of the substrate sheet **10** in such a manner that the entire wiring pattern **14** is scanned while the substrate sheet **10** is fed in the forward direction with the camera units being held

stationary. The cameras **51** and **54** are connected to a controller **60** for controlled operations of detecting the position of the wiring patterns and scanning the same. The controller **60** also controls the speed of feeding the substrate sheet **10**, i.e., the rotating speed of the drive rollers **31** and **33**, in addition to the operations of the feeder **20** and the collector **40** including the transverse movement thereof. In this embodiment, the controller **60** acts to feed the substrate sheet **10** at a uniform speed through the inspection zone **30**. A rotary encoder **35** is provided on a shaft of the pinch roller **32** to detect the speed which is acknowledged by the controller **60** for a feed back control of maintaining the feed speed constant. For these purposes, the controller **60** includes, as shown in FIG. 2, a position detector **61** connected to receive the monitored data from the position camera **51**, a pattern inspector **64** connected to receive the scanned image of the wiring pattern **14** from the inspection camera **54**, a speed detector **62** for detection of the feeding speed. An output of the speed detector **62** is fed to processor **63** which in turn activates a speed controller **65** for controlling the speeds of the unwinder **21**, drive rollers **31** and **33**, and winder **41** in order to keep the feed speed constant. The pattern inspector **64** compares the scanned image of the wiring pattern with a reference image representative of a correct wiring pattern to determine whether the wiring pattern being scanned is defective or not. If the wiring pattern is determined defective, the pattern inspector **64** stores an identification number assigned to this particular wiring pattern into a memory **66** such that the defective wiring pattern could be re-examined or rejected thereafter by reference to the identification number. The identification number may be printed on the substrate sheet so as to be acknowledged by the image inspector or may be acknowledged by

counting the individual wiring patterns being inspected.

The position camera **51** detects a pre-inspection position of the wiring pattern **14** which is just before being inspected by the inspection camera **54** and provides a position signal indicative of the pre-inspection position to the position detector **61** where it is analyzed to give an error with respect to a correct feeding axis. The error includes a transverse displacement error and an angular divergence error of the wiring pattern in the pre-inspection position in relation the correct feeding axis. Such error is evaluated in the processor **63** to give a compensation signal to a position controller **67** which responds to make the transverse movement of the feeder **20** and/or the collector **40** in such a manner as to eliminate the error, thereby placing the wiring pattern into a correct position for inspection by the array of the inspection camera **54**. Details of the operation are explained with reference to FIG. 6. Each of the position cameras **51** has a field of view **52** with center X-axis and Y-axis. When the wiring pattern **14** in the pre-inspection position is inclined with respect to the correct feeding axis, as shown in the figure, or shifted laterally, the corresponding markings **16** captured respectively in the field of views **52** of the individual position cameras **51** show deviations  $\Delta X$  and/or  $\Delta Y$  with reference to the center X-axis and Y-axis. Such deviations represent the angular divergence error or the transverse displacement error of the wiring pattern. FIG. 6 demonstrates undesired angular divergence  $\theta$  of the wiring pattern **14** with respect to the feeding axis FX. Based upon  $\Delta X$  and  $\Delta Y$  being obtained, the processor **63** generates the compensation signal for eliminating the error before the wiring pattern **14** is fed into a position of being inspected the inspection camera **54**.

## Second Embodiment &lt;FIGS. 7A to 7E&gt;

FIGS. 7A to 7E illustrates an inspection system in accordance with a second embodiment of the present invention which is similar in construction with the first embodiment except that an inspection camera

5 **54A** is composed of separate camera units **55A** spaced along the transverse direction of the substrate sheet **10** and is movable in the transverse direction between a first position of FIGS. 7A to 7C and a second position of FIGS. 7D and 7E. Like parts are designated by like numerals with a suffix letter of 'A'. The camera units **55A** are spaced

10 by a fixed distance such that the entire width of the wiring pattern **14** is covered when the units are shifted by the distance between the first and second positions. With the use of the inspection camera **54A** of this structure, a control is made to feed the substrate sheet **10** in forward and reverse directions. Operation of the system is now discussed. As

15 shown in FIG. 7A, when the wiring pattern **14** proceeds to a pre-inspection position where the corresponding position markings **16** are captured by the position cameras **51A**, the controller operates to feed the substrate sheet **10** at a relatively high speed to a first inspection position of FIG. 7B where the leading edge of the wiring pattern **14** is aligned

20 with the inspection camera **54A**. Then, the controller feeds the substrate sheet **10** at a relatively low speed by one forward step to a second inspection position of FIG. 7C with the inspection camera **54A** held at the first position, during which a half area of the wiring pattern (as indicated by hatched lines) is scanned. Then, the inspection camera

25 **54A** is moved in the transverse direction to the second position, as shown in FIG. 7D. Subsequently, the substrate sheet **10** is fed by one reverse step at the relatively low speed to a position of FIG. 7E, during

which the remainder half of the wiring pattern **14** is scanned. Thus, the entire area of the wiring pattern is scanned by feeding the substrate sheet **10** forwardly and then reversely by the same step. Thereafter, the substrate sheet **10** is fed forwardly at the high speed to a position of FIG. 7A for inspection of the next wiring pattern.

It is noted that the position cameras **51A** act also in this embodiment to detect the pre-inspection position of the wiring pattern **14** using the position markings **16** in order to achieve correct positioning of the wiring pattern at the first inspection position of FIG. 7B in the same manner as made in the first embodiment. Further, it is noted in this connection that the controller acknowledges the pre-inspection position of the wiring pattern **14** when the position markings **16** come into the fields of the view of the corresponding position cameras **51A** even if each marking **16** is not strictly coincident with the longitudinal center of the field of view of the camera, i.e., the Y-axis as shown in FIG. 6. Then, the controller operates to feed the substrate sheet **10** by a fixed distance at a rapid speed and to feed it by a suitable distance at a low speed for effecting a fine adjustment of the wiring pattern to the correct position of FIG. 7B in consideration of the deviation  $\Delta X$ . With this scheme, it is possible to make a reliable inspection of each wiring pattern while reducing a run time of consecutively inspecting the individual wiring patterns.

As shown in FIGS. 8A and 8B, it is preferred in this embodiment to dispose a suction table **70** behind the substrate sheet **10** in the inspection zone for holding the substrate sheet by a suction force while the wiring pattern is scanned by the inspection camera **54A**. In order to assist holding the substrate sheet **10** flat against the suction table **70**, there may

be utilized press-rollers **71** which are controlled to press the sheet against the table **70** when the wiring pattern comes into the position of being scanned, after which the sheet is held by the suction force on the table for reliable scanning of the wiring pattern. The table **70** is  
5 supported on a base frame **72** to be movable for a limited length along the feeding direction so that the substrate sheet **10** can move for inspection by the inspection camera, i.e., between the positions of FIGS. **7B** to **7E**, while being held against the table **70**. Further, as shown in FIGS. **9A** and **9B**, a vertically movable suction table **70A** may be  
10 utilized for holding the substrate sheet thereon when the wiring pattern is in the position of being scanned and for releasing the substrate sheet while the sheet is fed from the pre-inspection position to the inspection position. The suction table **70A** is pivotally supported to a base frame **72A** through a cylinder **73** so as to be pivotable about a vertical axis of  
15 the cylinder. With this pivotable structure, the table **70A** can act to compensate for the angular divergence error detected by the position camera for correct positioning of the wiring pattern in relation to the inspection camera. The table **70A** is also movable along the feeding direction of the substrate sheet with the base frame **72A** supported  
20 movably on a guide rail **74**, in order to follow the movement of the substrate sheet during the inspection of the wiring pattern. In this connection, the table **70A** as well as table **70** of FIG. **8A** may be movable in the transverse direction in order to compensate for the transverse displacement error based upon the position signal from the  
25 position camera, as discussed with reference to the first embodiment.

#### Third Embodiment <FIG. 10>

Referring to FIG. 10, there is shown an inspection system in

accordance with a third embodiment of the present invention which is similar to the first embodiment except that an inspection camera **54B** extends along the feeding direction of the substrate sheet **10** and is movable in the transverse direction. Like parts are designated by the like reference numerals with a suffix letter of 'B'. The inspection camera **54B** is composed of an array of camera units arranged closely along the feeding direction such that the entire area of the wiring pattern can be scanned when the inspection camera is shifted in the transverse direction with the substrate sheet being kept stationary. With the use of the inspection camera **54B** of this structure, a controller **60B** operates to feed the substrate sheet **10** intermittently for providing a standstill period during which the wiring pattern is scanned for inspection. Also in this embodiment, a like position camera **51B** provides a position signal indicative of the error of the above kind for the wiring pattern at the pre-inspection position so that the controller responds to compensate for the error when the wiring pattern is fed to the inspection position of being scanned by the inspection camera, by shifting the feeder **20A** and/or the collector **40A**. A like suction table **70B** as utilized in the second embodiment is provided for stably holding the substrate sheet while the wiring pattern is scanned as well as for correct positioning of the wiring pattern in relation to the inspection camera **54B**.

#### Fourth Embodiment <FIGS. 11A to 11E>

FIGS. 11A to 11E illustrates an inspection system in accordance with a fourth embodiment of the present invention which is similar to the third embodiment except that an inspection camera **54C** is composed of separate camera units **55C** spaced along the feeding direction of the substrate sheet **10** and is movable in the transverse direction between a

first position of FIG. 11A and a second position of FIG. 11C. Like parts are designated by like numerals with a suffix letter of 'C'. The camera units **55C** are spaced by a fixed distance such that the entire length of the wiring pattern **14** is covered when the wiring pattern **14** are  
5 shifted by that distance in the forward direction. With the use of the inspection camera **54C** of this structure, a control is made to feed the substrate sheet **10** by a forward step while reciprocating the inspection camera **54C** by one cycle along the transverse direction between the first and second positions. Operation of the system is now discussed. As  
10 shown in FIG. 11A, when the wiring pattern **14** proceeds to a pre-inspection position where the corresponding position markings **16** are captured by the position cameras **51C**, the controller operates to feed the substrate sheet **10** at a relatively high speed to a first inspection position of FIG. 11B where the leading edge of the wiring pattern **14** is aligned  
15 with the forward most inspection camera unit **55C**. Then, the inspection camera **54C** is caused to shift in the transverse direction by a half-cycle to the position of FIG. 11C with the substrate sheet **10** held stationary for scanning a half area of the wiring pattern (as indicated by hatched lines). Then, the substrate sheet **10** is fed forward by a short  
20 distance corresponding the spacing between the adjacent camera units **55C** to bring the wiring pattern **14** at a second inspection position of FIG. 11D. Subsequently, the inspect camera **54C** is shifted in the reverse direction by the remaining half-cycle to the position of FIG. 11E, thereby completing to scan the whole area of the wiring pattern **14**. It  
25 is noted that the substrate sheet is fed at a relatively high speed to proceed the wiring pattern **14** from the pre-inspection position of FIG. 11A to the first inspection position of FIG. 11B, while it is fed at a

relatively low speed to proceed the wiring pattern from the first inspection position of FIG. 11C to the second inspection position of FIG. 11D, in order to reduce a total inspection time of consecutively inspecting the discrete wiring patterns while assuring a reliable inspection of the individual wiring patterns. Also in this embodiment, the position camera **51C** serves to realize a correct positioning of the wiring pattern 14 when it comes to the first inspection position with the control of shifting the feeder and/or the collector in the transverse direction as discussed in the first embodiment. The suction table as discussed with reference to FIGS. 8A and 9A may be applicable to the present system for the same purpose of assuring the reliable inspection.

FIG. 12 illustrates a modification of the third embodiment in which the inspection camera 54D is composed of an array of closely arranged camera units 55D to cover a half length of the wiring pattern 14. The scanning of the wiring pattern 14 can be made by the same sequence as discussed with reference to FIGS. 11A to 11E of the third embodiment.

#### Fifth embodiment <FIG. 13>

Referring to FIG. 13, there is shown an inspection system in accordance with a fifth embodiment of the present invention. The inspection system includes a display **80** for re-inspection by human eyes of the wiring pattern determined to be defective by the image processing as explained with the previous embodiments. The system further includes a backup table **90** which passes the substrate sheet **10** thereon and serves as a supporting desk when a personnel requires to apply a force to the wiring pattern being monitored by the display in order to, for example, mend a defective portion with a hand-tool. The basic structure of the system comprises a feeder **20E** of feeding the substrate

sheet **10** from an unwinder **21E** to an inspection zone **30E** and a collector **40E** of collecting the substrate sheet on a winder **41E**. A tension is given to the substrate sheet **10** between a draw-in roller set and a draw-out roller so as to extend the substrate sheet **10** horizontally in the inspection zone **30E**. The draw-in roller set is composed of a drive roller **31E** and a pinch roller **32E**, while the draw-out roller set is likewise composed of a drive roller **33E** and a pinch roller **34E**.

Disposed between the draw-in roller set and the draw-out roller set is a pair of vertically spaced guide rollers **27** by which the feeding direction is reversed. The guide rollers **27** are supported to the backup table **90** and are so positioned to introduce the substrate sheet **10** through an inlet **91** near the bottom of the table and emerge the substrate sheet on top of the table **90** through an outlet **92** at one longitudinal end of the table.

Disposed between the table **90** and the draw-out roller set **33E** and **34E** is a riser roller **93** which is vertically movable in order to lift the substrate sheet **10** up away from the table **90** while feeding the sheet.

When the substrate sheet **10** is stopped for inspection of the wiring pattern, the riser roller **93** is lowered to land the sheet on the table **90** for reliable recognition of the defective pattern as well as for facilitating to handle the wiring pattern by the personnel, if needed.

A controller **60E** includes a retrieval section which derives from the output of the image processing as made in the previous embodiments that which one or ones of the wiring pattern are determined defective. That is, the identification number assigned to the defective wiring pattern is transmitted to the controller **60E** which responds to feed that wiring pattern on the table **90** while passing the non-defective wiring pattern. Local information as to the location of a particular defect

found within the area of the wiring pattern is also obtained at the image processing and is fed together with the identification number to the controller **60E** such that a television camera **54E** is controlled to move to the particular location for giving a magnified image of the defect to the display **80** for easy recognition by the personnel. If the defect is judged to be easily mended, the personnel can make the use of the table **90** as a mending desk to mend the defect with a suitable hand tool.

Like position cameras **51E** as utilized in the previous embodiments is mounted to watch the position markings on the substrate sheet **10** and detect a pre-inspection position of the wiring pattern immediately before being inspected by the camera **54E**. Based upon the information about the pre-inspection position, the controller **60E** instructs to feed the wiring pattern to a correct inspection position, while making suitable correction for possible errors of the lateral shift, directional divergence by moving at least one of the feeder **20E**, collector **40E**, and table **90** in the transverse direction in the like manner as discussed with reference to the previous embodiments. In this connection, the table **90** is mounted on a foot **94** to be rotatably about a vertical axis of a cylinder **95** such that the table **90** can adjust its orientation in order to compensate for the angular directional divergence of the substrate sheet from an intended feed direction.

Although the position markings are printed separately from the wiring pattern in the aforementioned embodiments, they may be printed within the area of the wiring pattern. Further, the relative position of the separate printed markings to the wiring pattern may be suitably selected in consideration of the particular arrangement of the inspection camera and the other configuration of the system.

## Claims

1. An inspection system for inspecting discrete wiring patterns (14) formed integrally on a continuous substrate sheet (10) of a flexible material, said  
5 system comprising:

an inspection zone (30) provided with camera means (51, 54) for inspecting the individual wiring patterns and detecting a position of said wiring pattern on said substrate sheet;

draw-in roller means (31, 32) for introducing the substrate sheet into  
10 said inspection zone;

draw-out roller means (33, 34) for drawing out said substrate sheet from said inspection zone, said draw-out roller means being positioned to define said inspection zone between said draw-in roller means and said draw-out roller means and to give a tension to said substrate sheet  
15 for extending said substrate sheet straight within said inspection zone;

control means (60) which controls a position of said substrate sheet passing through said inspection zone based upon a position signal detected by said camera means as indicative of said position of said  
20 individual wiring patterns on said substrate sheet within said inspection zone.

19a

a feeder (20) for feeding said substrate sheet towards said draw-in roller means from a first stock (21) of said substrate sheet;

a collector (40) for collecting said substrate sheet past through said draw-out roller means into a second stock (41) of said substrate sheet;  
and

a dancer roller (35, 45) being provided at least one of two locations, one between said feeder and said draw-in roller means, and the other between said draw-out roller means and said collector.

2. The system as set forth in claim 1, further including

a feeder (20) for feeding said substrate sheet through said draw-in roller means into said inspection zone,

a collector (40) for collecting said substrate sheet past through said

draw-out roller means from said inspection zone,

said feeder and said collector being movable in a transverse direction generally perpendicular to a feeding direction of said substrate sheet through said inspection zone,

5        said control means (60) comprises a mechanism of shifting at least one of said feeder and said collector in said transverse direction, in response to said position signal, for correct positioning of said wiring pattern in said inspection zone .

10

3. The system as set forth in claim 1, wherein

each of said draw-in and draw-out roller means comprises a driving roller (31, 33) and a pinch roller (32, 34), said driving roller being controlled by said control means to rotate, and said pinch roller pressing  
15    said substrate sheet against said driving roller to feed said substrate sheet.

4. The system as set forth in claim 1, wherein

20        said camera means comprises an inspection camera means (54) and a position camera means (51),

said inspection camera means (54) providing an image of said wiring pattern to an image inspector (64) where said image is compared with a reference image for determination of a defect in said wiring  
25    pattern,

said inspection camera means (54) comprising an array of inspection cameras arranged in a direction transverse to a feeding

direction of said substrate sheet in such a manner to cover a whole width of said wiring patterns,

said position camera means (51) detecting marks (16) on said substrate sheet to acknowledge a pre-inspection position of said wiring pattern which is just before being inspected by said inspection camera and providing said position signal indicative of said pre-inspection position,

a speed sensor (35) detecting the feeding speed of said substrate sheet and providing a speed signal indicative of said feeding speed,

said control means controlling to feed said substrate through said inspection zone at a uniform speed based upon said speed signal,

said control means being responsive to said position signal and said speed signal to activate said inspection camera means (54) for scanning the image of said wiring pattern in synchronism with the position of the wiring patterns.

5. The system as set forth in claim 1, wherein

said camera means comprises an inspection camera means (54A) and a position camera means (51A),

said inspection camera means (54A) providing an image of said wiring pattern to an image inspector (64) where said image is compared with a reference image for determination of a defect in said wiring pattern,

said position camera means (51A) detecting marks (16) on said substrate sheet (10) to acknowledge a pre-inspection position of said

wiring pattern which is just before being inspected by said inspection camera and providing said position signal indicative of said pre-inspection position,

said inspection camera means (54A) comprises an array of  
5 inspection cameras (55A) arranged in an array direction transverse to a feeding direction of said substrate sheet so as to cover the whole width of said wiring pattern when said array is shifted between a first position and a second position in said array direction,

said control means operating to feed said substrate sheet forwardly  
10 along said feeding direction by one forward step during which said inspection camera means at said first position completes scanning of a portion of said wiring pattern, and subsequently to feed said substrate sheet reversely by one reverse step during which said inspection camera means at said second position completes scanning of the rest of said  
15 wiring pattern.

6. The system as set forth in claim 1, wherein

20 said camera means comprises an inspection camera means (54B) and a position camera means (51B),

said inspection camera means (54B) providing an image of said wiring pattern to an image inspector where said image is compared with a reference image for determination of a defect in said wiring pattern,

25 said position camera means (51B) detecting marks (16) on said substrate sheet to acknowledge a pre-inspection position of said wiring pattern which is just before being inspected by said inspection camera

and providing said position signal indicative of said pre-inspection position,

said control means operating to intermittently feed said substrate sheet so that said wiring pattern is held stationary at an inspection  
5 position for a predetermined period during which said inspection camera means is controlled to move relative to said wiring pattern for inspection of the wiring pattern.

10

7. The system as set forth in claim 1, wherein

said camera means comprises an inspection camera means (54C) and a position camera means (51C),

said inspection camera means providing an image of said wiring  
15 pattern to an image inspector where said image is compared with a reference image for determination of a defect in said wiring pattern,

said position camera means detecting marks (16) on said substrate sheet to acknowledge a pre-inspection position of said wiring pattern which is just before being inspected by said inspection camera and  
20 providing said position signal indicative of said pre-inspection position,

said inspection camera means (54C) comprising an array of inspection cameras (55C) arranged in a direction parallel to a feeding direction of said substrate sheet so as to cover the whole width of said wiring pattern when said array reciprocates by one cycle along a  
25 transverse direction perpendicular to said feeding direction,

said control means operating to hold said substrate sheet at a first inspection position where said inspection camera means is shifted by

half of said one cycle in said transverse direction to scan a portion of said wiring pattern, and subsequently feed said substrate sheet by one step to a second inspection position where said inspection camera is shifted by the remaining half of said one cycle in said transverse  
5 direction to scan the rest of said wiring pattern.

said control means operating to intermittently feed said substrate sheet so that said wiring pattern is held stationary at said first and second inspection positions at which said inspection camera means is controlled to move relative to said wiring pattern for inspection of the wiring  
10 pattern.

25 8. The system as set forth in any one of claims 4 to 7, wherein  
said inspection zone is provided with a suction table (70) which is positioned behind said substrate sheet to hold said substrate sheet flat on

said suction table by a suction force, said suction table being controlled by said control means to hold said substrate sheet while said wiring pattern is being scanned by said inspection camera means and to release said substrate sheet after said wiring pattern is inspected .

5

9. The system as set forth in claim 8, wherein  
said suction table (70A) has a feed axis extending along a feeding  
10 direction of said substrate sheet and is capable of swinging around a  
vertical axis perpendicular to a plane of said substrate sheet to adjust an  
angle of said feed axis with respect to said feeding direction for correct  
positioning of said wiring pattern in relation to said inspection camera  
means.

15

10. The system as set forth in claim 8, wherein  
said suction table (70) is movable in synchronism with said  
20 substrate sheet being fed through said inspection zone.

11. The system as set forth in claim 1, wherein  
said camera means comprises a view camera (54E) which gives a  
25 selected area of said wiring pattern on a display (80) for inspection by  
human eyes,  
said inspection zone being provided with a backup table (90) upon

which said substrate sheet being fed.

## ABSTRACT

An inspection system for inspecting discrete wiring patterns on a continuous substrate sheet of a flexible material by making the use of the substrate sheet as a feeding carrier. The system is capable of assuring accurate positioning of the wiring patterns (14) for reliable inspection even with the use of the flexible substrate sheet (10) as the sole feeding carrier. The inspection system includes an inspection zone (30) provided with camera means (51, 54) for inspecting the individual wiring patterns (14) and detecting a position of said wiring pattern on the substrate sheet. A draw-in roller (31, 32) is provided to introduce the substrate into the inspection zone. Associated with the draw-in roller is a draw-out roller (32, 33) which draws out the substrate sheet from the inspection zone and is positioned to define the inspection zone between the draw-in roller and the draw-out roller as well as to give a tension to the substrate sheet for extending the substrate sheet straight through the inspection zone. A controller (60) is provided to control a position of the substrate sheet passing through the inspection zone based upon a position signal detected by the camera means as indicative of the position of the individual wiring patterns on the substrate sheet within the inspection zone. Thus, the wiring pattern can be exactly positioned within the inspection zone relative to the camera means for reliable inspection thereby.

## LIST OF REFERENCE NUMERALS

|    |                  |    |                   |
|----|------------------|----|-------------------|
| 10 | substrate sheet  | 51 | position camera   |
| 11 | glass-sheet      | 52 | field of view     |
| 12 | copper layer     | 54 | inspection camera |
| 14 | wiring pattern   | 55 | camera unit       |
| 16 | position marking |    |                   |
| 18 | protective film  | 60 | controller        |
|    |                  | 61 | position detector |
| 20 | feeder           | 62 | speed detector    |
| 21 | unwinder         | 63 | processor         |
| 22 | feed roller      | 64 | image inspector   |
| 23 | feed roller      | 65 | speed controller  |
| 24 | feed roller      | 66 | memory            |
| 25 | dancing winder   |    |                   |
| 26 | recovery roller  | 70 | suction table     |
| 27 | guide roller     | 71 | press roller      |
| 28 | frame            | 72 | base frame        |
| 29 | base             | 73 | cylinder          |
|    |                  | 74 | guide rail        |
| 30 | inspection zone  |    |                   |
| 31 | drive roller     | 80 | display           |
| 32 | pinch roller     |    |                   |
| 33 | drive roller     | 90 | backup table      |
| 34 | pinch roller     | 91 | inlet             |
| 35 | rotary encoder   | 92 | outlet            |
| 36 | guide table      | 93 | riser roller      |
|    |                  | 94 | foot              |
| 40 | collector        | 95 | cylinder          |
| 41 | winder           |    |                   |
| 42 | feed roller      |    |                   |
| 43 | feed roller      |    |                   |
| 44 | feed roller      |    |                   |
| 45 | dancing winder   |    |                   |
| 46 | supply roller    |    |                   |
| 48 | frame            |    |                   |
| 49 | base             |    |                   |