

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
3 January 2003 (03.01.2003)

PCT

(10) International Publication Number
WO 03/001280 A2

(51) International Patent Classification⁷: **G02F**

(21) International Application Number: PCT/US02/19506

(22) International Filing Date: 20 June 2002 (20.06.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/299,886 21 June 2001 (21.06.2001) US

(71) Applicant: **CORNING PRECISION LENS INCORPORATED** [US/US]; 4000 McMann Road, Cincinnati, OH 45245 (US).

(72) Inventors: **MAGARILL, Simon**; 9836 Orchardclub Drive, Cincinnati, OH 45242 (US). **RUTHEFORD, Todd S.**; 3302 Lookout Drive, Cincinnati, OH 45208 (US).

(74) Agent: **KLEE, Maurice M.**; 191 Burr Street, Fairfield, CT 06430 (US).

(81) Designated States (*national*): AE, AG, AL, AU, BA, BB, BG, BR, BZ, CA, CN, CO, CR, CU, CZ, DM, DZ, EC, EE, GD, GE, HR, HU, ID, IL, IN, IS, JP, KP, KR, LC, LK, LR, LT, LV, MA, MG, MK, MN, MX, NO, NZ, OM, PH, PL, RO, RU, SG, SI, SK, TN, TT, UA, UZ, VN, YU, ZA.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: SCROLLING COLOR SEQUENTIAL ILLUMINATION SYSTEM



(57) **Abstract:** Illumination systems (11) are disclosed which provide scrolling progressive color change on a liquid crystal panel (21), such as a LcoS panel. The systems use transmissive color filters (30, 31, 33) which form an assembly (13) which is rotated about a rotation axis (37). Incident light from a light source (15, 17) passes through the filters and reflects from a reflecting surface (39). As a result of this reflection, the system's optical axis (41, 43) is turned from an orientation substantially perpendicular to the rotation axis to an orientation which does not intersect a filter. Such turning of the optical axis allows colored light to be easily removed from the assembly and avoids problems with color mixing at boundaries between filters as occurs for systems in which light passes through two filters.



WO 03/001280 A2