CLAIMS

1. A patch for relieving cancer pain, the patch comprising a backing layer and an adhesive layer laminated on the backing layer, wherein

the adhesive layer comprises an adhesive base and 75 mg of diclofenac sodium and the adhesive base comprises at least one selected from the group consisting of a styrene-isoprene-styrene block copolymer and polyisobutylene, and

the patch is used by applying two or three patches ~~the patch~~ once a day ~~and is used such that a dose of diclofenac sodium is 150 mg to 225 mg per application~~.

~~2. The patch according claim 1, wherein the adhesive layer comprises 75 mg of diclofenac sodium, and two or three patches are applied once a day.~~

~~3. The patch according to claim 1 or 2, wherein the adhesive base comprises at least one selected from the group consisting of a styrene-isoprene-styrene block copolymer and polyisobutylene.~~

2~~4~~. The patch according to claim 1 ~~or 2~~, wherein the adhesive base comprises a styrene-isoprene-styrene block copolymer and polyisobutylene.

3~~5~~. The patch according to claim 1 or 2~~any one of claims 1 to 4~~, wherein the adhesive layer comprises dimethyl sulfoxide.

4~~6~~. The patch according to any one of claims 1 to 3~~5~~, wherein the adhesive layer comprises an organic acid.

5~~7~~. The patch according to claim 4~~6~~, wherein the organic acid is oleic acid.

6~~8~~. The patch according to any one of claims 1 to 5~~7~~, wherein the

adhesive layer comprises a tackifier.

79. The patch according to claim 68, wherein the tackifier is an alicyclic saturated hydrocarbon resin and a hydrogenated rosin glycerin ester.

810. The patch according to any one of claims 1 to 79, wherein the adhesive layer comprises a plasticizer.

911. The patch according to claim 810, wherein the plasticizer is liquid paraffin.

1012. The patch according to any one of claims 1 to 911, wherein the backing is polyethylene terephthalate knitted fabric having a water vapor transmission rate of 1,000 g/m^2·24 hours or more.

1113. The patch according to any one of claims 1 to 1012, wherein an application area is 50 to 150 cm^2.