

**HEAT-DISSIPATING STRUCTURE HAVING EMBEDDED
SUPPORT TUBE TO FORM INTERNALLY RECYCLING
HEAT TRANSFER FLUID AND APPLICATION
APPARATUS**

5

BACKGROUND OF THE INVENTION

(a) Field of the Invention

The present invention provides a heat-dissipating structure having embedded support tube to form internally recycling heat transfer fluid and application apparatus, which is installed in the ground soil or liquid of a shallow ground natural thermal energy body for performing temperature equalizing operation with the external gaseous or solid or liquid environment and/or the soil or liquid of the shallow ground natural thermal energy body, the interior of a support tube (101) is installed with an inner tube (103) for being penetrated through, the inner diameter of the support tube (101) is greater than the outer diameter of the inner tube (103), the partitioned space formed through the diameter differentiation allows a fluid path to be formed, the distal end of the support tube (101) is sealed, the distal end of the inner tube (103) is shorter than the distal end of the support tube (101) or preformed with fluid holes, the distal ends of both tubes are formed with a flow returning segment allowing the heat transfer fluid to be returned;

The front tube port of the support tube (101) and the front tube port of the inner tube (103) allow the heat transfer fluid passing an electric energy application device assembly (108) and/or a heat dissipater thereof to be transferred, wherein one of the tube ports allows the heat transfer fluid to be transferred for passing the electric energy application device assembly (108) and/or the heat dissipater thereof, and the other tube port allows the heat transfer fluid which already passed the electric energy application device assembly (108) and/or the heat dissipater thereof to be

returned;

One or more than one of fluid pumps (105) are serially installed on the mentioned closed recycling heat transfer fluid path, the flowing direction thereof can be selected from one flowing direction or two
5 flowing directions enabled to be switched or periodically changed;

The gaseous or liquid heat transfer fluid pumped by the fluid pump (105) passes the support tube (101) of the closed recycling heat transfer fluid path and the exposed portion of the relevant structure, thereby enabling to perform temperature equalizing operation with the external
10 gaseous or solid or liquid environment and/or the soil or liquid of the shallow ground natural thermal energy body.

(b) Description of the Prior Art

A conventional electric energy application device assembly, e.g. an illumination device utilizing electric energy being converted into photo
15 energy, an illumination device adopting LED, a photovoltaic, a wind power generator, a transformer or a motor, generates thermal energy while being operated, so over-heating prevention or anti-freezing for the mentioned assembly is very important.

20 SUMMARY OF THE INVENTION

The present invention provides a heat-dissipating structure having embedded support tube to form internally recycling heat transfer fluid and application apparatus, which is installed in the ground soil or liquid of a shallow ground natural thermal energy body for performing temperature
25 equalizing operation with the external gaseous or solid or liquid environment and/or the soil or liquid of the shallow ground natural thermal energy body, the interior of a support tube (101) is installed with an inner tube (103) for being penetrated through, the inner diameter of the support tube (101) is greater than the outer diameter of the inner tube
30 (103), the partitioned space formed through the diameter differentiation

allows a fluid path to be formed, the distal end of the support tube (101) is sealed, the distal end of the inner tube (103) is shorter than the distal end of the support tube (101) or preformed with fluid holes, the distal ends of both tubes are formed with a flow returning segment allowing the heat transfer fluid to be returned;

The front tube port of the support tube (101) and the front tube port of the inner tube (103) allow the heat transfer fluid passing an electric energy application device assembly (108) and/or a heat dissipater thereof to be transferred, wherein one of the tube ports allows the heat transfer fluid to be transferred for passing the electric energy application device assembly (108) and/or the heat dissipater thereof, and the other tube port allows the heat transfer fluid which already passed the electric energy application device assembly (108) and/or the heat dissipater thereof to be returned;

One or more than one of fluid pumps (105) are serially installed on the mentioned closed recycling heat transfer fluid path, the flowing direction thereof can be selected from one flowing direction or two flowing directions enabled to be switched or periodically changed;

The structure of the heat transfer fluid path formed between the mentioned electric energy application device assembly (108) and/or the heat dissipater thereof and the support tube (101) and the inner tube (103) includes one or more than one of followings:

(a) the interior of the electric energy application device assembly (108) is formed with one or more than one of penetrating heat transfer fluid paths connected in serial or in parallel, the fluid inlet port and the fluid outlet port are respectively communicated with the tube port of the support tube (101) and the tube port of the inner tube (103);

(b) the heat dissipater installed in the electric energy application device assembly (108) is formed with one or more than one of

penetrating heat transfer fluid paths connected in parallel, the fluid inlet port and the fluid outlet port are respectively communicated with the tube port of the support tube (101) and the tube port of the inner tube (103);

- 5 (c) one or more than one of heat transfer fluid paths formed in the interior of the electric energy application device assembly (108) are connected in serial or in parallel with the heat transfer fluid paths formed in the heat dissipater thereof, the fluid inlet port and the fluid outlet port are respectively communicated with the
- 10 tube port of the support tube (101) and the tube port of the inner tube (103);
- (d) the electric energy application device assembly (108) is formed with two or more than two of heat transfer fluid paths connected through external tubes so as to form the fluid inlet port and the
- 15 fluid outlet port respectively communicated with the tube port of the support tube (101) and the tube port of the inner tube (103), or the interior thereof is bent to the U-like shape or L-like shape, the fluid inlet port and the fluid outlet port at the same or different sides are respectively communicated with the tube port
- 20 of the support tube (101) and the tube port of the inner tube (103);
- (e) the exterior of the electric energy application device assembly (108) is installed with a sealed housing, thereby forming a space between the above two for allowing the heat transfer fluid to
- 25 pass, the electric energy application device assembly (108) is formed with one or more than one of heat transfer fluid paths connected in serial or in parallel, one end thereof is formed with a heat transfer fluid inlet/outlet port which is leaded to the tube port of the inner tube (103), the tube port at the other end is
- 30 leaded to the space formed between the housing and the electric

energy application device assembly (108), a heat transfer fluid connection port is formed on the sealed housing for being communicated with the tube port of the support tube (101);

(f) a sealed space allowing the heat transfer fluid to pass is formed between the electric energy application device assembly (108) and the heat dissipater thereof and the installed housing, the electric energy application device assembly (108) and/or the heat dissipater thereof is formed with one or more than one of heat transfer fluid paths connected in serial or in parallel, one end thereof is formed with a heat transfer fluid inlet/outlet port which is leaded to the tube port of the inner tube (103), the tube port at the other end is leaded to the space formed between the housing and the electric energy application device assembly (108) and/or the heat dissipater thereof, a heat transfer fluid inlet/outlet port is formed on the sealed housing for being communicated with the tube port of the support tube (101);

(g) a sealed housing is jointly formed by the exterior of the electric energy application device assembly (108) and/or the heat dissipater thereof and the matched housing, the interior of the electric energy application device assembly (108) and/or the heat dissipater thereof and the matched housing is formed with a space allowing the heat transfer fluid to pass and leaded to the tube port of the support tube (101), the electric energy application device assembly (108) and/or the heat dissipater thereof is formed with one or more than one of heat transfer fluid paths connected in serial or in parallel, one end thereof is formed with a heat transfer fluid connection port which is leaded to the tube port of the inner tube (103), the tube port at the other end is leaded to the space formed between the housing and the electric energy application device assembly (108)

and/or the heat dissipater thereof, a heat transfer fluid connection port is formed on the sealed housing for being communicated with the tube port of the support tube (101);

The gaseous or liquid heat transfer fluid pumped by the fluid pump (105) passes the support tube (101) of the closed recycling heat transfer fluid path and the exposed portion of the relevant structure, thereby enabling to perform temperature equalizing operation with the external gaseous or solid or liquid environment and/or the soil or liquid of the shallow ground natural thermal energy body.

The mentioned electric energy application device assembly (108) includes an illumination device utilizing electric energy being converted into photo energy, e.g. an illumination device adopting LED and/or a photovoltaic, e.g. a solar panel and/or a wind power generator and/or a transformer and/or a motor driven by electric energy, and peripheral devices, control circuits devices, overload protecting devices and/or temperature protection devices are optionally installed according to actual needs for assisting the operation of the electric energy application device assembly (108).

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic view showing the main structure according to the present invention.

FIG. 2 is a cross section view of FIG. 1 taken along X-X.

FIG. 3 is a schematic view showing the main structure shown in FIG. 1 installed with a housing according to the present invention.

FIG. 4 is a cross section view of FIG. 3 taken along X-X.

FIG. 5 is a schematic structural view illustrating the illumination device utilizing electric energy being converted into photo energy (109) being adopted as the electric energy application device assembly (108) according to the present invention.

FIG. 6 is a cross sectional view of FIG. 5 taken along X-X.

FIG. 7 is a schematic structural view illustrating the photovoltaic (110) being adopted as the electric energy application device assembly (108) according to the present invention.

5 FIG. 8 is a cross sectional view of FIG. 7 taken along X-X.

FIG. 9 is a schematic structural view illustrating the wind power generating device (111) being adopted as the electric energy application device assembly (108) according to the present invention.

FIG. 10 is a schematic structural view illustrating the transformer
10 (444) being adopted as the electric energy application device assembly (108) according to the present invention.

FIG. 11 is a schematic structural view illustrating the motor (333) driven by electric energy being adopted as the electric energy application device assembly (108) according to the present invention.

15 FIG. 12 is a schematic structural view showing the upper portion of the support tube (101) being formed by a manifold structure for being installed with plural electric energy application device assemblies (108) which sharing the mid tube body and the lower tube body of the support tube (101), according to the present invention.

20 FIG. 13 is a first schematic view showing the tube structure according to the present invention.

FIG. 14 is a cross sectional view of FIG. 13 taken along X-X.

FIG. 15 is a second schematic view showing the tube structure according to the present invention.

25 FIG. 16 is a cross sectional view of FIG. 15 taken along X-X.

FIG. 17 is a third schematic view showing the tube structure according to the present invention.

FIG. 18 is a cross sectional view of FIG. 17 taken along X-X.

FIG. 19 is a fourth schematic view showing the tube structure
30 according to the present invention.

FIG. 20 is a cross sectional view of FIG. 19 taken along X-X.

FIG. 21 is a fifth schematic view showing the tube structure according to the present invention.

FIG. 22 is a cross sectional view of FIG. 21 taken along X-X.

5 FIG. 23 is a schematic structural view showing the lower end of the inner tube (103) shown in FIG. 13 and FIG. 14 being shortened and not extended to the lower portion of the support tube (101) according to one embodiment of the present invention.

10 FIG. 24 is a schematic structural view showing the lower end of the inner tube (103) shown in FIG. 17 and FIG. 18 being shortened and not extended to the lower portion of the support tube (101) according to one embodiment of the present invention.

15 FIG. 25 is a schematic structural view showing the lower end of the inner tube (103) shown in FIG. 19 and FIG. 20 being shortened and not extended to the lower portion of the support tube (101) according to one embodiment of the present invention.

FIG. 26 is a first schematic structural view showing the support tube being formed as a U-shaped tube post (301), (302) according to one embodiment of the present invention.

20 FIG. 27 is a cross sectional view of FIG. 26 taken along X-X.

FIG. 28 is a second schematic structural view showing the support tube being formed as a U-shaped tube post (301), (302) according to one embodiment of the present invention.

25 FIG. 29 is a cross sectional view of the U-shaped tube post shown in FIG. 28.

FIG. 30 is a cross sectional view of FIG. 28 taken along X-X.

30 FIG. 31 is a schematic structural view showing a heat transfer fluid path allowing the gaseous or liquid heat transfer fluid to pass being formed by the space defined between the heat dissipater (104) of the electric energy application device assembly (108) and the housing (106)

and the heat transfer fluid path of heat dissipater (1041) of the heat dissipater (104) according to the present invention.

FIG. 32 is a schematic structural view showing a heat transfer fluid path allowing the gaseous or liquid heat transfer fluid to pass being
5 formed by at least two heat transfer fluid paths (1041) of the heat dissipater (104) of the electric energy application device assembly (108) being connected with a U-shaped connection tube (1042) according to the present invention.

FIG. 33 is a schematic structural view showing a heat transfer fluid
10 path allowing the gaseous or liquid heat transfer fluid to pass being formed by the space defined between the electric energy application device assembly (108) and the housing (106) and the heat transfer fluid path (1081) of the electric energy application device assembly (108) according to the present invention.

15 FIG. 34 is a schematic structural view showing a heat transfer fluid path allowing the gaseous or liquid heat transfer fluid to pass being formed by at least two heat transfer fluid paths (1081) of the electric energy application device assembly (108) being connected in serial with a U-shaped connection tube (1042) according to the present invention.

20 FIG. 35 is a schematic structural view showing a heat transfer fluid path allowing the gaseous or liquid heat transfer fluid to pass being formed by a U-shaped connection tube (1042) being connected in serial between at least one heat transfer fluid path (1081) of the electric energy application device assembly (108) and at least one heat transfer fluid path
25 (1041) of the heat dissipater (104) thereof according to the present invention.

FIG. 36 is a schematic structural view showing a fluid inlet/outlet path being formed through a space allowing fluid to flow freely and formed in the interior of the heat dissipater (104) installed with the
30 electric energy application device assembly (108), the heat transfer fluid

path (1081), and the heat transfer fluid path (107) formed between the interior of the support tube (101) and the exterior of the sleeved heat transfer fluid path (1081) according to the present invention.

FIG. 37 is a front view of FIG. 36.

5 FIG. 38 is another schematic structural view showing a fluid inlet/outlet path being formed through a space allowing fluid to flow freely and formed in the interior of the heat dissipater (104) installed with the electric energy application device assembly (108), the heat transfer fluid path (1081), and the heat transfer fluid path (107) formed between
10 the interior of the support tube (101) and the exterior of the biasedly-sleeved heat transfer fluid path (1081) according to the present invention.

FIG. 39 is a front view of FIG. 38

FIG. 40 is a schematic structural view showing a fluid inlet/outlet
15 path being formed through a configuration formed in the heat dissipater (104) installed with the electric energy application device assembly (108) and having a central path (570) extended outwardly towards two lateral sides for respectively forming a circular path (580) and a circular path (590) along the inner side of the outer periphery of the heat dissipater (104)
20 and leaded to the heat transfer fluid path (1081), and the heat transfer fluid path (107) formed between the interior of the support tube (101) and the exterior of the sleeved heat transfer fluid path (1081) according to the present invention.

FIG. 41 is a front view of FIG. 40.

25 FIG. 42 is a schematic structural view showing a fluid inlet/outlet path being formed through a configuration formed in the heat dissipater (104) installed with the electric energy application device assembly (108) and having a central path (570) extended outwardly towards two lateral sides for respectively forming a circular path (580) and a circular path
30 (590) extended along the inner side of the outer periphery of the heat

dissipater (104) and led to the heat transfer fluid path (1081), and the heat transfer fluid path (107) formed between the interior of the support tube (101) and the exterior of the biasedly-sleeved heat transfer fluid path (1081) according to the present invention.

5 FIG. 43 is a front view of FIG. 42.

FIG. 44 is a schematic structural view showing a fluid inlet/outlet path being formed through a configuration formed in the heat dissipater (104) installed with the electric energy application device assembly (108) and having a central penetrated hole (610) of a central shunting piece (600) outwardly extended towards two lateral sides for respectively forming a circular path (580) and a circular path (590) extended along the inner side of the outer periphery of the heat dissipater (104) and led to the heat transfer fluid path (1081), and the heat transfer fluid path (107) formed between the interior of the support tube (101) and the exterior of the
10 sleeved heat transfer fluid path (1081) according to the present invention.
15

FIG. 45 is a front view of FIG. 44.

FIG. 46 is a schematic structural view showing a fluid inlet/outlet path being formed through a configuration formed in the heat dissipater (104) installed with the electric energy application device assembly (108) and having a central penetrated hole (610) of a central shunting piece (600) outwardly extended towards two lateral sides for respectively forming a circular path (580) and a circular path (590) extended along the inner side of the outer periphery of the heat dissipater (104) and led to the heat transfer fluid path (1081), and the heat transfer fluid path (107) formed
20 between the interior of the support tube (101) and the exterior of the biasedly-sleeved heat transfer fluid path (1081) according to the present invention.
25

FIG. 47 is a front view of FIG. 46.

FIG. 48 is a schematic structural view showing the electric energy application device assembly (108) being upwardly installed, and a fluid
30

inlet/outlet path being formed through the heat transfer fluid path (1081) composed of an axial central penetrated hole (700) and annularly-arranged holes (710) and leaded to the electric energy application device assembly, and the heat transfer fluid path (107) formed between the support tube
5 (101) and the heat transfer fluid path (1081) of the electric energy application device assembly according to the present invention.

FIG. 49 is a front view of FIG. 48.

FIG. 50 is a schematic structural view showing a locked-on heat dissipation ring (800) being optionally installed at the outer side of the
10 heat dissipater (104) according to the present invention.

FIG. 51 is a schematic structural view showing a sleeved-on heat dissipation ring (900) being optionally installed at the outer side of the heat dissipater (104) according to the present invention.

15 **DESCRIPTION OF MAIN COMPONENT SYMBOLS**

- 100: Shallow ground natural thermal energy body
- 101: Support tube
- 102: Temperature protecting device
- 103: Inner tube
- 20 1031: Transversal hole
- 1032: Notch
- 1033: Supporter
- 104: Heat dissipater
- 1041: Heat transfer fluid path of heat dissipater
- 25 1042: U-shaped connection tube
- 105: Fluid pump
- 106: Housing
- 1061: Light-pervious member
- 107: Heat transfer fluid path
- 30 108: Electric energy application device assembly

- 1081: Heat transfer fluid path
- 109: Illumination device utilizing electric energy being converted into photo energy
- 110: Photovoltaic
- 5 111: Wind power generating device
- 222: Wind power generator
- 112: Electric controlling device
- 200: Bending portion of U-shaped tube
- 201 、 202: U-shaped tube post
- 10 301 、 302: U-shaped tube post
- 333: Motor
- 334: Motor driving load
- 444: Transformer
- 445: Transformer support rack
- 15 570 : Central path
- 580 、 590 : Circular Path
- 600 : Central shunting piece
- 610 : Central penetrated hole
- 700 : Axial central penetrated hole
- 20 710 : Annularly-arranged hole
- 800 : Locked-on heat dissipation ring
- 900 : Sleeved-on heat dissipation ring
- 2001: Heat transfer fin
- 2002: Heat transfer covering member
- 25 2003: Spiral flow guiding structure

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

A conventional electric energy application device assembly, e.g. an illumination device utilizing electric energy being converted into photo

30 energy, an illumination device adopting LED, a photovoltaic, a wind

power generator, a transformer or a motor, generates thermal energy while being operated, so over-heating prevention or anti-freezing for the mentioned assembly is very important;

The present invention provides a heat-dissipating structure having
5 embedded support tube to form internally recycling heat transfer fluid and application apparatus, which is installed in the ground soil or liquid of a shallow ground natural thermal energy body for performing temperature equalizing operation with the external gaseous or solid or liquid environment and/or the soil or liquid of the shallow ground natural
10 thermal energy body, the interior of a support tube (101) is installed with an inner tube (103) for being penetrated through, the inner diameter of the support tube (101) is greater than the outer diameter of the inner tube (103), the partitioned space formed through the diameter differentiation allows a fluid path to be formed, the distal end of the support tube (101) is
15 sealed, the distal end of the inner tube (103) is shorter than the distal end of the support tube (101) or preformed with fluid holes, the distal ends of both tubes are formed with a flow returning segment allowing the heat transfer fluid to be returned;

The front tube port of the support tube (101) and the front tube port
20 of the inner tube (103) allow the heat transfer fluid passing an electric energy application device assembly (108) and/or a heat dissipater thereof to be transferred, wherein one of the tube ports allows the heat transfer fluid to be transferred for passing the electric energy application device assembly (108) and/or the heat dissipater thereof, and the other tube port
25 allows the heat transfer fluid which already passed the electric energy application device assembly (108) and/or the heat dissipater thereof to be returned;

One or more than one of fluid pumps (105) are serially installed on the mentioned closed recycling heat transfer fluid path, the flowing
30 direction thereof can be selected from one flowing direction or two

flowing directions enabled to be switched or periodically changed;

The structure of the heat transfer fluid path formed between the mentioned electric energy application device assembly (108) and/or the heat dissipater thereof and the support tube (101) and the inner tube (103)

5 includes one or more than one of followings:

(a) the interior of the electric energy application device assembly (108) is formed with one or more than one of penetrating heat transfer fluid paths connected in serial or in parallel, the fluid inlet port and the fluid outlet port are respectively
10 communicated with the tube port of the support tube (101) and the tube port of the inner tube (103);

(b) the heat dissipater installed in the electric energy application device assembly (108) is formed with one or more than one of penetrating heat transfer fluid paths connected in parallel, the
15 fluid inlet port and the fluid outlet port are respectively communicated with the tube port of the support tube (101) and the tube port of the inner tube (103);

(c) one or more than one of heat transfer fluid paths formed in the interior of the electric energy application device assembly (108)
20 are connected in serial or in parallel with the heat transfer fluid paths formed in the heat dissipater thereof, the fluid inlet port and the fluid outlet port are respectively communicated with the tube port of the support tube (101) and the tube port of the inner tube (103);

(d) the electric energy application device assembly (108) is formed with two or more than two of heat transfer fluid paths connected through external tubes so as to form the fluid inlet port and the fluid outlet port respectively communicated with the tube port of the support tube (101) and the tube port of the inner tube
25 (103), or the interior thereof is bent to the U-like shape or L-like
30

shape, the fluid inlet port and the fluid outlet port at the same or different sides are respectively communicated with the tube port of the support tube (101) and the tube port of the inner tube (103);

- 5 (e) the exterior of the electric energy application device assembly (108) is installed with a sealed housing, thereby forming a space between the above two for allowing the heat transfer fluid to pass, the electric energy application device assembly (108) is formed with one or more than one of heat transfer fluid paths
- 10 connected in serial or in parallel, one end thereof is formed with a heat transfer fluid inlet/outlet port which is leaded to the tube port of the inner tube (103), the tube port at the other end is leaded to the space formed between the housing and the electric energy application device assembly (108), a heat transfer fluid
- 15 connection port is formed on the sealed housing for being communicated with the tube port of the support tube (101);
- (f) a sealed space allowing the heat transfer fluid to pass is formed between the electric energy application device assembly (108) and the heat dissipater thereof and the installed housing, the
- 20 electric energy application device assembly (108) and/or the heat dissipater thereof is formed with one or more than one of heat transfer fluid paths connected in serial or in parallel, one end thereof is formed with a heat transfer fluid inlet/outlet port which is leaded to the tube port of the inner tube (103), the tube
- 25 port at the other end is leaded to the space formed between the housing and the electric energy application device assembly (108) and/or the heat dissipater thereof, a heat transfer fluid inlet/outlet port is formed on the sealed housing for being communicated with the tube port of the support tube (101);
- 30 (g) a sealed housing is jointly formed by the exterior of the electric

energy application device assembly (108) and/or the heat dissipater thereof and the matched housing, the interior of the electric energy application device assembly (108) and/or the heat dissipater thereof and the matched housing is formed with a space allowing the heat transfer fluid to pass and led to the tube port of the support tube (101), the electric energy application device assembly (108) and/or the heat dissipater thereof is formed with one or more than one of heat transfer fluid paths connected in serial or in parallel, one end thereof is formed with a heat transfer fluid connection port which is led to the tube port of the inner tube (103), the tube port at the other end is led to the space formed between the housing and the electric energy application device assembly (108) and/or the heat dissipater thereof, a heat transfer fluid connection port is formed on the sealed housing for being communicated with the tube port of the support tube (101);

The gaseous or liquid heat transfer fluid pumped by the fluid pump (105) passes the support tube (101) of the closed recycling heat transfer fluid path and the exposed portion of the relevant structure, thereby enabling to perform temperature equalizing operation with the external gaseous or solid or liquid environment and/or the soil or liquid of the shallow ground natural thermal energy body;

The mentioned electric energy application device assembly (108) includes an illumination device utilizing electric energy being converted into photo energy, e.g. an illumination device adopting LED and/or a photovoltaic, e.g. a solar panel and/or a wind power generator and/or a transformer and/or a motor driven by electric energy, and peripheral devices, control circuits devices, overload protecting devices and/or temperature protection devices are optionally installed according to actual needs for assisting the operation of the electric energy application device

assembly (108);

Main components of the heat-dissipating structure having embedded support tube to form internally recycling heat transfer fluid and application apparatus are illustrated as followings:

5 FIG. 1 is a schematic view showing the main structure according to the present invention.

FIG. 2 is a cross section view of FIG. 1 taken along X-X.

As shown in FIG. 1 and FIG. 2, mainly consists:

-- support tube (101): related to a hollow tube member constituted by the
10 material having mechanical strength, the tube body is divided into an upper tube body, a mid tube body and a lower tube body, wherein:

The upper tube body is mainly served to allow the electric energy application device assembly (108) to be installed;

The mid tube body is served to provide a support function and to
15 transfer the thermal energy between the interior and the exterior of the tube;

The lower tube body is served to be installed in the stratum or liquid of the shallow ground natural thermal energy body for transferring thermal energy;

20 The support tube (101) includes being formed in a tube member with round shape or other geometric shapes, and being made of a material having mechanical strength and better heat conductivity or a material having heat insulation property; the mentioned support tube (101) can be optionally installed with heat transfer fins (2001) at the exterior of the
25 tube member according to actual needs;

-- inner tube (103): constituted by a tube member having an outer diameter smaller than the inner diameter of the support tube (101) and made of a hard material, e.g. metal, or a flexible material or a soft material, e.g. plastic, or a fabric or other materials having similar properties, the
30 inner tube (103) is formed in a linear or bended or curved shaped or can

be freely deformed if being made of the flexible material or the soft material thereby being enabled to be installed in the support tube (101) without affecting the smoothness of the heat transfer fluid path, the upper end thereof is leaded to the heat transfer fluid path of the electric energy application device assembly (108) or the heat dissipater (104) thereof installed at the upper portion of the support tube (101), the lower end thereof is leaded to the mid portion or extended to the lower portion of the support tube (101), a diameter differentiation is formed between the outer diameter of the inner tube (103) and the inner diameter of the support tube (101) thereby forming a reversed space which can be served as the heat transfer fluid path, so the fluid path allowing the heat transfer fluid to pass is formed through the inner tube and two tube ports at two ends of the inner tube and the reserved space formed between the outer diameter of the inner tube and the inner diameter of the outer tube, and selected locations on the mentioned fluid path can be serially installed with one or more than one of fluid pumps (105), the space defined between the upper end of the inner tube (103) and the upper portion of the support tube (101) is served to allow the electric energy application device assembly (108) to be installed;

20 The inner tube (103) includes being formed in a tube member with round shape or other geometric shapes, and being made of (a) a hard material or flexible material or soft material having heat insulation property, or (b) a hard material or flexible material or soft material having better heat conductivity, and the exterior of the tube member is provided with a heat insulation material, or (c) a hard material or flexible material or soft material having better heat conductivity, and the interior of the tube member is provided with a heat insulation material, or (d) a hard material or flexible material or soft material having better heat conductivity;

-- fluid pump (105): constituted by a pump driven by an electric motor for being used to pump the gaseous or liquid heat transfer fluid with respect

to the controlled flowing direction and flowing rate of the fluid to be pumped;

-- electric energy application device assembly (108): constituted by an illumination device driven by electric energy, and/or a power generator
5 driven by the kinetic power provided by external gaseous or liquid fluid, and/or a device driven by photo energy for generating electric energy and also generating thermal loss, and/or a transformer and/or a motor driven by electric energy, and peripheral devices, control circuits devices, overload protecting devices and/or temperature protection devices are
10 optionally installed according to actual needs for assisting the operation of the electric energy application device assembly (108).

According to the heat-dissipating structure having embedded support tube to form internally recycling heat transfer fluid and application apparatus, with the pumping operation provided by the fluid pump (105),
15 the gaseous or liquid heat transfer fluid is allowed to pass the heat transfer fluid outlet port at the upper end of the inner tube (103), then pass the heat transfer fluid path of the electric energy application device assembly (108) which generates thermal loss during operation and the heat dissipater (104) thereof, then pass the heat transfer fluid path formed by the partitioned
20 space defined between the interior of the support tube (101) and the inner tube (103) thereby being leaded to the lower tube body of the support tube (101) then returned from the heat transfer fluid inlet port at the lower end of the inner tube (103), thereby forming a closed recycling heat transfer fluid loop, or the heat transfer fluid pumped by the adapted fluid pump
25 (105) can pass the mentioned paths in a reverse order and in the reverse flowing direction thereby forming a closed recycling heat transfer fluid loop having reverse order and reverse flowing direction, so through the heat transfer fluid passing the outer surface of the electric energy application device assembly (108) and the heat dissipater (104) thereof,
30 and/or the exposed portion at the outer surface of the support tube (101),

temperature equalizing operation is enabled to be performed with the external gaseous or liquid or solid environment, and/or the heat transfer fluid pumped by the fluid pump (105) is enabled to further transfer thermal energy to the stratum or liquid through the embedded portion of the support tube (101) installed in the stratum or liquid of the shallow ground natural thermal energy body.

According to the heat-dissipating structure having embedded support tube to form internally recycling heat transfer fluid and application apparatus, the upper tube body of the support tube (101) which allows the electric energy application device assembly (108) to be installed can be further installed with a housing (106) for protecting the electric energy application device assembly (108), and the space formed by the surface of the electric energy application device assembly (108) or the surface of the heat dissipater (104) thereof can be served as a heat transfer fluid path (107) for transferring the heat transfer fluid;

FIG. 3 is a schematic view showing the main structure shown in FIG. 1 installed with a housing according to the present invention.

FIG. 4 is a cross section view of FIG. 3 taken along X-X.

As shown in FIG. 3 and FIG. 4, mainly consists:

-- support tube (101): related to a hollow tube member constituted by the material having mechanical strength, the tube body is divided into an upper tube body, a mid tube body and a lower tube body, wherein:

The upper tube body is mainly served to allow the electric energy application device assembly (108) and the housing (106) to be installed;

The mid tube body is served to provide a support function and to transfer the thermal energy between the interior and the exterior of the tube;

The lower tube body is served to be installed in the stratum or liquid of the shallow ground natural thermal energy body for transferring thermal energy;

The support tube (101) includes being formed in a tube member with round shape or other geometric shapes, and being made of a material having mechanical strength and better heat conductivity or a material having heat insulation property; the mentioned support tube (101) can be optionally installed with heat transfer fins (2001) at the exterior of the tube member according to actual needs;

-- inner tube (103): constituted by a tube member having an outer diameter smaller than the inner diameter of the support tube (101) and made of a hard material, e.g. metal, or a flexible material or a soft material, e.g. plastic, or a fabric or other materials having similar properties, the inner tube (103) is formed in a linear or bended or curved shaped or can be freely deformed if being made of the flexible material or the soft material thereby being enabled to be installed in the support tube (101) without affecting the smoothness of the heat transfer fluid path, the upper end thereof is leaded to the heat transfer fluid path of the electric energy application device assembly (108) or the heat dissipater (104) thereof installed at the upper portion of the support tube (101), the lower end thereof is leaded to the mid portion or extended to the lower portion of the support tube (101), a diameter differentiation is formed between the outer diameter of the inner tube (103) and the inner diameter of the support tube (101) thereby forming a reversed space which can be served as the heat transfer fluid path, so the fluid path allowing the heat transfer fluid to pass is formed through the inner tube and two tube ports at two ends of the inner tube and the reserved space formed between the outer diameter of the inner tube and the inner diameter of the outer tube, and selected locations on the mentioned fluid path can be serially installed with one or more than one of fluid pumps (105), the space defined between the upper end of the inner tube (103) and the upper portion of the support tube (101) is served to allow the electric energy application device assembly (108) to be installed;

The inner tube (103) includes being formed in a tube member with round shape or other geometric shapes, and being made of (a) a hard material or flexible material or soft material having heat insulation property, or (b) a hard material or flexible material or soft material having better heat conductivity, and the exterior of the tube member is provided with a heat insulation material, or (c) a hard material or flexible material or soft material having better heat conductivity, and the interior of the tube member is provided with a heat insulation material, or (d) a hard material or flexible material or soft material having better heat conductivity;

-- fluid pump (105): constituted by a pump driven by an electric motor for being used to pump the gaseous or liquid heat transfer fluid with respect to the controlled flowing direction and flowing rate of the fluid to be pumped;

-- housing (106): made of a material having heat conductive or heat insulation property and used for covering the exterior of the electric energy application device assembly (108) so as to be sealed relative to the exterior, the heat transfer fluid is pumped by the fluid pump (105) for flowing from the heat transfer fluid outlet port at the upper end of the inner tube (103) to the space formed between the housing (106) and the electric energy application device assembly (108), then passing the heat transfer fluid path formed through the partitioned space defined by the inner diameter of the support tube (101) and the outer diameter of the inner tube (103), then flowing towards the lower tube body of the support tube (101), then returning via the heat transfer fluid inlet port at the lower end of the inner tube (103), thereby forming a closed recycling heat transfer fluid loop, or forming a closed recycling heat transfer fluid loop having opposite flowing direction through changing the fluid flowing direction in which the fluid pump (105) is pumping;

-- electric energy application device assembly (108): constituted by an illumination device driven by electric energy, and/or a power generator

driven by the kinetic power provided by external gaseous or liquid fluid, and/or a device driven by photo energy for generating electric energy and also generating thermal loss, and/or a transformer and/or a motor driven by electric energy, and peripheral devices, control circuits devices, 5 overload protecting devices and/or temperature protection devices are optionally installed according to actual needs for the operation of assisting the electric energy application device assembly (108).

-- electric controlling device (112): constituted by solid-state or electromechanical components, or chips and relevant operation software, 10 the electric controlling device (112) is optionally installed;

-- temperature protecting device (102): constituted by electromechanical thermal actuated switch or thermal braking fuse, or solid-state temperature detecting units or solid-state temperature switch unit, served to directly or through the control of the electric controlling device (120) terminate the 15 load or partially terminate the load or reduce the load power, when the load is overheated, and the temperature protecting device (102) is optionally installed.

Through the fluid pumps (105) serially installed on the heat transfer fluid path pumping the heat transfer fluid to flow from the heat transfer 20 fluid outlet port at the upper end of the inner tube (103) and pass the space formed at the interior of the electric energy application device assembly (108) and/or the space defined between the exterior of the electric energy application device assembly (108) and the sealed housing, then pass the partitioned space of the fluid path defined between the inner diameter of 25 the support tube (101) and the outer diameter of the inner tube (103), then return via the heat transfer fluid inlet port at the lower end of the inner tube (103) thereby forming the closed recycling flow, or forming a closed recycling heat transfer fluid loop having opposite flowing direction through changing the fluid flowing direction in which the fluid pump (105) 30 is pumping, the thermal energy of the gaseous or liquid heat transfer fluid

pumped by the fluid pump (105) is enabled to perform temperature equalizing operation with the external gaseous or liquid or solid environment through the outer surface of the electric energy application device assembly (108) and/or the surface of the sealed housing (106) installed at the exterior of the electric energy application device assembly (108) and/or the exposed portion at the outer surface of the support tube (101), and/or the heat transfer fluid pumped by the fluid pump (105) is enabled to further transfer thermal energy to the stratum or liquid through the embedded portion of the support tube (101) installed in the stratum or liquid of the shallow ground natural thermal energy body.

According to the heat-dissipating structure having embedded support tube to form internally recycling heat transfer fluid and application apparatus, the electric energy application device assembly (108) includes an illumination device utilizing electric energy being converted into photo energy (109), e.g. an illumination device adopting LED, and/ or a photovoltaic (110), e.g. a solar panel and/or a wind power generating device (111), and/or a transformer (444), and/or a motor (333) driven by electric energy, and peripheral devices, control circuits devices, overload protecting devices, temperature protecting devices are optionally installed according to actual needs for assisting the operation of the electric energy application device assembly (108), embodiments provided by the present invention are illustrated as followings:

FIG. 5 is a schematic structural view illustrating the illumination device utilizing electric energy being converted into photo energy (109) being adopted as the electric energy application device assembly (108) according to the present invention.

FIG. 6 is a cross sectional view of FIG. 5 taken along X-X.

As shown in FIG. 5 and FIG. 6, the main configuration includes the support tube (101), the inner tube (103), the fluid pump (105), and the electric energy application device assembly (108) is designed to adopt the

illumination device utilizing electric energy being converted into photo energy (109) which generates thermal loss and/or the light emitting diode (LED), and peripheral devices, control circuits devices, overload protecting devices, and temperature protection devices are optionally
5 installed according to actual needs for assisting the operation of the illumination device utilizing electric energy being converted into photo energy (109);

Wherein: the heat transfer fluid pumped by the fluid pump (105) passes the heat transfer fluid path (107) formed on the surface or the
10 interior of the illumination device utilizing electric energy being converted into photo energy (109) or the heat dissipater (104) thereof, the thermal energy transferred through the heat transfer fluid path (107) is enabled to perform temperature equalizing operation with the external gaseous or liquid or solid environment through the exposed portion at the
15 outer surface of the support tube (101), and/or the heat transfer fluid pumped by the fluid pump (105) is enabled to further transfer thermal energy to the stratum or liquid through the embedded portion of the support tube (101) installed in the stratum or liquid of the shallow ground natural thermal energy body;

20 -- illumination device utilizing electric energy being converted into photo energy (109): constituted by an illumination device utilizing electric energy being converted into photo energy which is composed of various gaseous lamps, solid-state LED or OLED and other peripheral devices e.g. a light-pervious member (1061), and further including a display screen, a
25 billboard, a signal or a warning sign operated through the photo energy of the illumination device utilizing electric energy being converted into photo energy (109);

-- fluid pump (105): constituted by a pump driven by an electric motor for being used to pump the gaseous or liquid heat transfer fluid with respect
30 to the controlled flowing direction and flowing rate of the fluid to be

pumped;

- electric controlling device (112): constituted by solid-state or electromechanical components, or chips and relevant operation software; according to this embodiment, the electric controlling device (112) is served to control the input voltage, the current and the working temperature of the illumination device utilizing electric energy being converted into photo energy (109) and to control the operation timing of the fluid pump (105);
- temperature protecting device (102): constituted by electromechanical thermal actuated switch or thermal braking fuse, or solid-state temperature detecting units or solid-state temperature switch unit, installed in the illumination device utilizing electric energy being converted into photo energy (109) or the heat dissipater (104) thereof, and served to directly or through the control of the electric controlling device (112) to terminate the load or partially terminate the load or reduce the load power or control the fluid pump (105), when the temperature is abnormal; the temperature protecting device (102) is optionally installed.

FIG. 7 is a schematic structural view illustrating the photovoltaic (110) being adopted as the electric energy application device assembly (108) according to the present invention.

FIG. 8 is a cross sectional view of FIG. 7 taken along X-X.

As shown in FIG. 7 and FIG. 8, the main configuration includes the support tube (101), the inner tube (103), the fluid pump (105), and the electric energy application device assembly (108) is designed to adopt the photovoltaic (110) capable of converting photo energy into electric energy and generating thermal loss, and peripheral devices, control circuits devices, overload protecting devices, and temperature protection devices are optionally installed according to actual needs for assisting the photovoltaic (110);

Wherein: the heat transfer fluid pumped by the fluid pump (105)

passes the heat transfer fluid path (107) at the backside of the photovoltaic (110) or the surface or the interior of the heat dissipater (104) thereof, the thermal energy transferred through the heat transfer fluid path (107) is enabled to perform temperature equalizing operation with the external

5 gaseous or liquid or solid environment through the exposed portion at the outer surface of the support tube (101), and/or the heat transfer fluid pumped by the fluid pump (105) is enabled to further transfer thermal energy to the stratum or liquid through the embedded portion of the support tube (101) installed in the stratum or liquid of the shallow ground

10 natural thermal energy body;

- photovoltaic (110): constituted by various types of photovoltaic which receives lights for generating and outputting electric energy, e.g. a solar panel, and other relevant peripheral devices;
- fluid pump (105): constituted by a pump driven by an electric motor for

15 being used to pump the gaseous or liquid heat transfer fluid with respect to the controlled flowing direction and flowing rate of the fluid to be pumped;

- electric controlling device (112): constituted by solid-state or electromechanical components, or chips and relevant operation software;

20 according to this embodiment, the electric controlling device (112) is served to control the output voltage, the current and the working temperature of the photovoltaic (110) and to control the operation timing of the fluid pump (105);

- temperature protecting device (102): constituted by electromechanical

25 thermal actuated switch or thermal braking fuse, or solid-state temperature detecting units or solid-state temperature switch unit, served to directly or through the control of the electric controlling device (112) terminate the load or partially terminate the load or reduce the load power or control the fluid pump (105), when the temperature of the photovoltaic (110) is

30 abnormal; the temperature protecting device (102) is optionally installed.

FIG. 9 is a schematic structural view illustrating the wind power generating device (111) being adopted as the electric energy application device assembly (108) according to the present invention.

As shown in FIG. 9, the main configuration includes the support tube (101), the inner tube (103) and the fluid pump (105) installed in the shallow ground natural thermal energy body (100), and the electric energy application device assembly (108) is designed to adopt a wind power generator (222) of the wind power generating device (111), and peripheral devices, control circuits devices, overload protecting devices and/or temperature protection devices are optionally installed according to actual needs for assisting the operation of the wind power generating device (111);

Wherein: the heat transfer fluid pumped by the fluid pump (105) passes the heat transfer fluid path in the wind power generator (222) of the wind power generating device (111) and/or in the heat dissipater thereof, or further including the heat transfer fluid path in the electric controlling device (112) and/or in the heat dissipater thereof, and jointly with the inner tube (103) and the partitioned space formed between the inner tube (103) and the interior of the support tube (101) to form a sealed heat transfer fluid path, thereby allowing the heat transfer fluid to flow therein, and the temperature equalizing operation is enabled to be performed with the external gaseous or liquid or solid environment and/or the soil or liquid of the shallow ground natural thermal energy body through the exposed portion at the outer surface of the support tube (101);

-- wind power generating device (111): constituted by wind turbine blades and the wind power generator (222) driven thereby and/or the electric controlling device (112) and other relevant peripheral devices, wherein the wind power generator (222) and/or the electric controlling device (112) are the main components receiving the heat dissipating operation;

-- fluid pump (105): constituted by a pump driven by a wind power driven

shaft or by an electric motor, used for pumping the gaseous or liquid heat transfer fluid with respect to the controlled flowing direction and flowing rate of the fluid to be pumped;

-- electric controlling device (112): constituted by solid-state or electromechanical components, or chips and relevant operation software, used for controlling the system operation of the wind power generating device (111), including the output voltage, the current and the working temperature of the wind power generator (222), AC and DC converting, parallel controlling of AC output electric energy and public electricity system, and controlling the operation timing of the fluid pump (105);

-- temperature protecting device (102): constituted by electromechanical thermal actuated switch or thermal braking fuse, or solid-state temperature detecting units or solid-state temperature switch unit, and served to directly or through the electric controlling device (112) control the system operation of the wind power generator (222) and/or the wind power generating device (111), as well as control the fluid pump (105) when the temperature of the wind power generating device (111) is abnormal; the temperature protecting device (102) is optionally installed.

FIG. 10 is a schematic structural view illustrating the transformer (444) being adopted as the electric energy application device assembly (108) according to the present invention.

As shown in FIG. 10, the main configuration includes the support tube (101), the inner tube (103) and the fluid pump (105), and the electric energy application device assembly (108) is designed to adopt a transformer (444), and peripheral devices, control circuits devices, overload protecting devices and/or temperature protection devices are optionally installed according to actual needs for assisting the operation of the transformer (444);

Wherein: the heat transfer fluid pumped by the fluid pump (105) passes the heat transfer fluid path (107) formed on the surface or the

- interior of the transformer (444) or the heat dissipater (104) thereof, the thermal energy transferred through the heat transfer fluid path (107) is enabled to perform temperature equalizing operation with the external gaseous or liquid or solid environment through the exposed portion at the outer surface of the support tube (101), and/or the heat transfer fluid pumped by the fluid pump (105) is enabled to further transfer thermal energy to the stratum or liquid through the embedded portion of the support tube (101) installed in the stratum or liquid of the shallow ground natural thermal energy body;
- 10 -- transformer (444): including winding sets, magnetic conductive wirings and an enclosure, used for outputting and inputting single-phase or three-phase (including multiple-phase) AC electric energy, or inputting and outputting pulse electric energy; the transformer includes the self-coupled or separated-winding transformer having a dry structure containing gas or wet structure containing cooling fluid, the surface or the exterior of the transformer is formed with a pipeline heat dissipating structure allowing the fluid to pass, or formed with a fluid inlet/outlet port allowing the fluid to flow in or out of the internal space of the transformer; the transformer is combined on the support tube (101) through a transformer support rack (445);
- 15 -- fluid pump (105): constituted by a pump driven by electric energy, used for pumping the gaseous or liquid heat transfer fluid with respect to the controlled flowing direction and flowing rate of the fluid to be pumped;
- electric controlling device (112): constituted by solid-state or electromechanical components, or chips and relevant operation software; according to this embodiment, the electric controlling device (112) is used for controlling the output voltage, the current and the working temperature of the transformer (444), and controlling the operation timing of the fluid pump (105);
- 25 -- temperature protecting device (102): constituted by electromechanical
- 30

thermal actuated switch or thermal braking fuse, or solid-state temperature detecting units or solid-state temperature switch unit, served to directly or through the control of the electric controlling device (112) terminate the load or partially terminate the load or reduce the load power and control
5 the fluid pump (105), when the temperature of the transformer (444) is abnormal; the temperature protecting device (102) is optionally installed.

FIG. 11 is a schematic structural view illustrating the motor (333) driven by electric energy being adopted as the electric energy application device assembly (108) according to the present invention.

10 As shown in FIG. 11, the main configuration includes the support tube (101), the inner tube (103) and the fluid pump (105), and the electric energy application device assembly (108) is designed to adopt a motor (333) driven by electric energy, and peripheral devices, control circuits devices, overload protecting devices and/or temperature protection
15 devices are optionally installed according to actual needs for assisting the operation of the motor (333);

Wherein: the heat transfer fluid pumped by the fluid pump (105) passes the heat transfer fluid path (107) formed on the surface or the interior of the motor (333) driven by electric energy or the heat dissipater
20 (104) thereof, the thermal energy transferred through the heat transfer fluid path (107) is enabled to perform temperature equalizing operation with the external gaseous or liquid or solid environment through the exposed portion at the outer surface of the support tube (101), and/or the heat transfer fluid pumped by the fluid pump (105) is enabled to further
25 transfer thermal energy to the stratum or liquid through the embedded portion of the support tube (101) installed in the stratum or liquid of the shallow ground natural thermal energy body;

-- motor (333): constituted by a revolving electromechanical device driven by AC or DC electric energy for outputting rotational kinetic energy
30 thereby driving the motor driven load (334);

- fluid pump (105): constituted by a pump driven by electric energy, used for pumping the gaseous or liquid heat transfer fluid with respect to the controlled flowing direction and flowing rate of the fluid to be pumped;
- electric controlling device (112): constituted by solid-state or electromechanical components, or chips and relevant operation software; according to this embodiment, the electric controlling device (112) is used for controlling the input voltage, the current and the working temperature of the motor (333) driven by electric energy, and controlling the operation timing of the fluid pump (105);
- temperature protecting device (102): constituted by electromechanical thermal actuated switch or thermal braking fuse, or solid-state temperature detecting units or solid-state temperature switch unit, served to directly or through the control of the electric controlling device (112) terminate the load or partially terminate the load or reduce the load power and control the fluid pump (105), when the temperature of the motor (333) driven by electric energy is abnormal; the temperature protecting device (102) is optionally installed.

According to the heat-dissipating structure having embedded support tube to form internally recycling heat transfer fluid and application apparatus, the upper portion of the support tube (101) and the inner tube (103) can be further formed by a manifold structure for being installed with plural the same or different electric energy application device assemblies (108) which share the mid tube body and the lower tube body of the support tube;

FIG. 12 is a schematic structural view showing the upper portion of the support tube (101) being formed by a manifold structure for being installed with plural electric energy application device assemblies (108) which sharing the mid tube body and the lower tube body of the support tube (101), according to the present invention.

As shown in FIG. 12, the main configuration includes the mentioned

support tube (101), the inner tube (103), the fluid pump (105), wherein the upper portion of the support tube (101) is formed with a manifold structure allowing plural electric energy application device assemblies (108) to be installed thereon, and peripheral devices, control circuits
5 devices, overload protecting devices and/or temperature protection devices are optionally installed according to actual needs for assisting the electric energy application device assembly (108), the plural electric energy application device assemblies (108) share the mid tube body and the lower tube body of the support tube (101), and same or different
10 electric energy application device assemblies (108) are respectively installed on the manifold formed on the upper portion of the support tube (101), and correspondingly installed with an inner tube (103) in the support tube (101);

Wherein: the heat transfer fluid pumped by the fluid pump (105)
15 passes the heat transfer fluid path (107) formed on the surface or the interior of the individual electric energy application device assembly (108) or the heat dissipater (104) thereof, the thermal energy transferred through the heat transfer fluid path (107) is enabled to perform temperature equalizing operation with the external gaseous or liquid or solid
20 environment, and/or the heat transfer fluid pumped by the fluid pump (105) is enabled to further transfer thermal energy to the stratum or liquid through the embedded portion of the support tube (101) installed in the stratum or liquid of the shallow ground natural thermal energy body.

According to the heat-dissipating structure having embedded support
25 tube to form internally recycling heat transfer fluid and application apparatus, there are many ways to form the heat transfer fluid path through the lower portion of the support tube (101) and the inner tube (103), followings are examples for illustration and shall not be seen as a limitation to the present invention, structures having the same functional
30 operations are all within the scope of the present invention: wherein the

structure formed by the support tube (101) and the inner tube (103) includes one or more than one of followings:

FIG. 13 is a first schematic view showing the tube structure according to the present invention.

5 FIG. 14 is a cross sectional view of FIG. 13 taken along X-X.

As shown in FIG. 13 and FIG. 14, the main configuration is that the support tube (101) and the inner tube (103) are coaxially arranged or arranged in a substantially parallel manner, the space defined by the periphery of the inner tube (103) and between the support tube (101) and the inner tube (103) is served to allow the heat transfer fluid to pass, the inner tube (103) installed in the support tube (101) is shorter than the support tube (101), a length differentiation is formed between the lower end thereof and the sealed part at the lower portion of the support tube (101) and a supporter (1033) is provided for fastening, thereby forming the space allowing the heat transfer fluid to pass.

FIG. 15 is a second schematic view showing the tube structure according to the present invention.

FIG. 16 is a cross sectional view of FIG. 15 taken along X-X.

As shown in FIG. 15 and FIG. 16, the main configuration is that the support tube (101) and the inner tube (103) are installed in parallel, the lower end of the inner tube (103) in the support tube (101) is combined with the sealed part at the bottom of the lower portion of the support tube (101), the lower end or the lower portion of the inner tube (103) is formed with a transversal hole (1031) or a notch (1032) penetrating the inner tube thereby allowing the heat transfer fluid to pass.

FIG. 17 is a third schematic view showing the tube structure according to the present invention.

FIG. 18 is a cross sectional view of FIG. 17 taken along X-X.

As shown in FIG. 17 and FIG. 18, the main configuration is that the support tube (101) and the inner tube (103) are eccentrically combined

arranged, the lower end of the inner tube (103) in the support tube (101) is shorter, a length differentiation is formed between the lower end thereof and the sealed part at the bottom of the lower portion of the support tube (101) thereby forming a space allowing the heat transfer fluid to pass.

5 FIG. 19 is a fourth schematic view showing the tube structure according to the present invention.

FIG. 20 is a cross sectional view of FIG. 19 taken along X-X.

As shown in FIG. 19 and FIG. 20, the main configuration is that the support tube (101) and two or more than two of the inner tubes (103) are
10 installed in parallel, the lower ends of the inner tubes (103) in the support tube (101) are shorter, a length differentiation is formed between the lower end thereof and the sealed part at the bottom of the lower portion of the support tube (101) thereby forming a space allowing the heat transfer fluid to pass.

15 FIG. 21 is a fifth schematic view showing the tube structure according to the present invention.

FIG. 22 is a cross sectional view of FIG. 21 taken along X-X.

As shown in FIG. 21 and FIG. 22, the main configuration is that the support tube (101) and the inner tube (103) are coaxially arranged or
20 arranged in a substantially parallel manner, the space defined by the periphery of the inner tube (103) and between the support tube (101) and the inner tube (103) is served to allow the heat transfer fluid to pass, the inner tube (103) installed in the support tube (101) is shorter than the support tube (101), a length differentiation is formed between the lower
25 end thereof and the sealed part at the bottom of the lower portion of the support tube (101) thereby forming a space allowing the heat transfer fluid to pass, a spiral flow guiding structure (2003) is further installed between the support tube (101) and the inner tube (103) thereby increasing the length of the heat transfer fluid path formed between the support tube
30 (101) and the inner tube (103).

According to the heat-dissipating structure having embedded support tube to form internally recycling heat transfer fluid and application apparatus, the inner tube (103) in the support tube (101) can also be shortened and only the upper end being extended to the upper portion or the mid portion of the support tube (101) and not extended to the lower portion, including:

FIG. 23 is a schematic structural view showing the lower end of the inner tube (103) shown in FIG. 13 and FIG. 14 being shortened and not extended to the lower portion of the support tube (101) according to one embodiment of the present invention.

As shown in FIG. 23, the main configuration is that the support tube (101) and the inner tube (103) are coaxially arranged or arranged in a substantially parallel manner, the space defined by the periphery of the inner tube (103) and between the support tube (101) and the inner tube (103) is served to allow the heat transfer fluid to pass, the inner tube (103) installed in the support tube (101) is shorter than the support tube (101), and only extended to the upper portion or the mid portion of the support tube (101) and not extended to the lower portion, thereby shortening the length of the heat transfer fluid path.

FIG. 24 is a schematic structural view showing the lower end of the inner tube (103) shown in FIG. 17 and FIG. 18 being shortened and not extended to the lower portion of the support tube (101) according to one embodiment of the present invention.

As shown in FIG. 24, the main configuration is that the support tube (101) and the inner tube (103) are eccentrically combined arranged, the lower end of the inner tube (103) installed in the support tube (101) is shorter than the support tube (101), and only extended to the upper portion or the mid portion of the support tube (101) and not extended to the lower portion, thereby shortening the length of the heat transfer fluid path.

FIG. 25 is a schematic structural view showing the lower end of the

inner tube (103) shown in FIG. 19 and FIG. 20 being shortened and not extended to the lower portion of the support tube (101) according to one embodiment of the present invention.

As shown in FIG. 25, the main configuration is that the support tube (101) and two or more than two of the inner tubes (103) are arranged in parallel, the lower end of the inner tubes (103) installed in the support tube (101) are shorter than the support tube (101), and only extended to the upper portion or the mid portion of the support tube (101) and not extended to the lower portion, thereby shortening the length of the heat transfer fluid path.

According to the heat-dissipating structure having embedded support tube to form internally recycling heat transfer fluid and application apparatus, the support tube for transferring the internally recycling heat transfer fluid can be further formed as a U-shaped tube member, illustrated as followings:

FIG. 26 is a first schematic structural view showing the support tube being formed as a U-shaped tube post (301), (302) according to one embodiment of the present invention.

FIG. 27 is a cross sectional view of FIG. 26 taken along X-X.

As shown in FIG. 26 and FIG. 27, the main configuration is that the U-shaped tube posts (201), (202) are leaded to the electric energy application device assembly (108) with a manner of one tube post higher than the other, the U-shaped tube posts (201), (202) are respectively leaded to the inlet and the outlet of the heat transfer fluid path of the electric energy application device assembly (108) and/or the heat dissipater (104) thereof, or leaded to the inlet and the outlet of the heat transfer fluid path formed in the internal space jointly defined by the outer surface of the electric energy application device assembly (108) and/or the heat dissipater (104) thereof and the housing (106), wherein the U-shaped tube post (201) is leaded to the mentioned inlet port, the U-shaped tube

post (202) is leaded to the mentioned outlet port, and the lower portion of the U-shaped tube is formed with a bending portion (200) of U-shaped tube thereby forming a heat transfer fluid loop, and one or more than one of the fluid pumps (105) serially installed on the mentioned heat transfer
5 fluid path are operated to pump in a selected direction, the bending portion (200) of U-shaped tube and the adjacent lower portion are directly embedded in the shallow ground natural thermal energy body (100); or the bending portion (200) of U-shaped tube and the adjacent lower portion can be further embedded in a columnar heat transfer
10 covering member (2002) installed in the shallow ground natural thermal energy body (100);

In the mentioned U-shaped tube posts (201), (202), the U-shaped tube post (202) includes being formed in a tube member with round shape or other geometric shapes, and being made of a material having
15 mechanical strength and better heat conductivity or a material having heat insulation property; the U-shaped tube post (201) includes being formed in a tube member with round shape or other geometric shapes, and being made of (a) a hard material or flexible material or soft material having heat insulation property, or (b) a hard material or flexible material or soft
20 material having better heat conductivity, and the exterior of the tube member is provided with a heat insulation material, or (c) a hard material or flexible material or soft material having better heat conductivity, and the interior of the tube member is provided with a heat insulation material, or (d) a hard material or flexible material or soft material having better
25 heat conductivity;

The mentioned U-shaped tube posts (201), (202) can be installed with heat transfer fins (2001) between or at the exterior of the tube bodies according to actual needs.

FIG. 28 is a second schematic structural view showing the support
30 tube being formed as a U-shaped tube post (301), (302) according to one

embodiment of the present invention.

FIG. 29 is a cross sectional view of the U-shaped tube post shown in FIG. 28.

FIG. 30 is a cross sectional view of FIG. 28 taken along X-X.

5 As shown in FIG. 28, FIG. 29 and FIG. 30, the main configuration is that the U-shaped tube posts (301), (302) are leaded to the electric energy application device assembly (108) at the left and the right side, the U-shaped tube posts (301), (302) are respectively leaded to the inlet and outlet of the heat transfer fluid path of the electric energy application
10 device assembly (108) and/or the heat dissipater (104) thereof, or leaded to the inlet and outlet of the heat transfer fluid path formed in the internal space jointly defined by the outer surface of the electric energy application device assembly (108) and/or the heat dissipater (104) thereof and the housing (106), wherein the U-shaped tube post (301) is leaded to
15 the mentioned inlet, the U-shaped tube post (302) is leaded to the mentioned outlet, and the lower portion of the U-shaped tube is formed with a bending portion (200) of U-shaped tube thereby forming a heat transfer fluid loop, and one or more than one of the fluid pumps (105) serially installed on the mentioned heat transfer fluid path are operated to
20 pump in a selected direction, the bending portion (200) of U-shaped tube and the adjacent lower portion are directly embedded in the shallow ground natural thermal energy body (100); or the bending portion (200) of U-shaped tube and the adjacent lower portion can be further embedded in a columnar heat transfer covering member (2002) installed in the shallow
25 ground natural thermal energy body (100);

In the mentioned U-shaped tube posts (301), (302), the U-shaped tube post (302) includes being formed in a tube member with round shape or other geometric shapes, and being made of a material having mechanical strength and better heat conductivity or a material having heat
30 insulation property; the U-shaped tube post (301) includes being formed

in a tube member with round shape or other geometric shapes, and being made of (a) a hard material or flexible material or soft material having heat insulation property, or (b) a hard material or flexible material or soft material having better heat conductivity, and the exterior of the tube member is provided with a heat insulation material, or (c) a hard material or flexible material or soft material having better heat conductivity, and the interior of the tube member is provided with a heat insulation material, or (d) a hard material or flexible material or soft material having better heat conductivity;

10 The mentioned U-shaped tube posts (301), (302) can be installed with heat transfer fins (2001) between or at the exterior of the tube bodies according to actual needs.

FIG. 31 is a schematic structural view showing a heat transfer fluid path allowing the gaseous or liquid heat transfer fluid to pass being formed by the space defined between the heat dissipater (104) of the electric energy application device assembly (108) and the housing (106) and the heat transfer fluid path (1041) of heat dissipater of the heat dissipater (104) according to the present invention.

As shown in FIG. 31, the main configuration is that a heat transfer fluid path allowing the gaseous or liquid heat transfer fluid to pass is formed by the space defined between the heat dissipater (104) of the electric energy application device assembly (108) and the housing (106) and the heat transfer fluid path (1041) of heat dissipater of the heat dissipater (104).

25 FIG. 32 is a schematic structural view showing a heat transfer fluid path allowing the gaseous or liquid heat transfer fluid to pass being formed by at least two heat transfer fluid paths (1041) of the heat dissipater (104) of the electric energy application device assembly (108) being connected with a U-shaped connection tube (1042) according to the present invention.

As shown in FIG. 32, a heat transfer fluid path allowing the gaseous or liquid heat transfer fluid to pass is formed by at least two heat transfer fluid paths (1041) of the heat dissipater (104) of the electric energy application device assembly (108) being connected with a U-shaped connection tube (1042).

FIG. 33 is a schematic structural view showing a heat transfer fluid path allowing the gaseous or liquid heat transfer fluid to pass being formed by the space defined between the electric energy application device assembly (108) and the housing (106) and the heat transfer fluid path (1081) of the electric energy application device assembly (108) according to the present invention.

As shown in FIG. 33, the main configuration is that a heat transfer fluid path allowing the gaseous or liquid heat transfer fluid to pass is formed by the space defined between the electric energy application device assembly (108) and the housing (106) and the heat transfer fluid path (1081) of the electric energy application device assembly (108).

FIG. 34 is a schematic structural view showing a heat transfer fluid path allowing the gaseous or liquid heat transfer fluid to pass being formed by at least two heat transfer fluid paths (1081) of the electric energy application device assembly (108) being connected in serial with a U-shaped connection tube (1042) according to the present invention.

As shown in FIG. 34, a heat transfer fluid path allowing the gaseous or liquid heat transfer fluid to pass is formed by at least two heat transfer fluid paths (1081) of the electric energy application device assembly (108) being connected in serial with a U-shaped connection tube (1042).

FIG. 35 is a schematic structural view showing a heat transfer fluid path allowing the gaseous or liquid heat transfer fluid to pass being formed by a U-shaped connection tube (1042) being connected in serial between at least one heat transfer fluid path (1081) of the electric energy application device assembly (108) and at least one heat transfer fluid path

(1041) of the heat dissipater (104) thereof according to the present invention.

As shown FIG. 35, a heat transfer fluid path allowing the gaseous or liquid heat transfer fluid to pass is formed by a U-shaped connection tube (1042) being connected in serial between at least one heat transfer fluid path (1081) of the electric energy application device assembly (108) and at least one heat transfer fluid path (1041) of the heat dissipater (104) thereof.

FIG. 36 is a schematic structural view showing a fluid inlet/outlet path being formed through a space allowing fluid to flow freely and formed in the interior of the heat dissipater (104) installed with the electric energy application device assembly (108), the heat transfer fluid path (1081), and the heat transfer fluid path (107) formed between the interior of the support tube (101) and the exterior of the sleeved heat transfer fluid path (1081) according to the present invention.

FIG. 37 is a front view of FIG. 36.

As shown in FIG. 36 and FIG. 37, the interior of the heat dissipater (104) installed with the electric energy application device assembly (108) is formed a space allowing the fluid to flow freely, and the heat transfer fluid path (1081) and the heat transfer fluid path (107) formed between the interior of the support tube (101) and the exterior of the sleeved heat transfer fluid path (1081) constitute the fluid inlet/outlet path.

FIG. 38 is another schematic structural view showing a fluid inlet/outlet path being formed through a space allowing fluid to flow freely and formed in the interior of the heat dissipater (104) installed with the electric energy application device assembly (108), the heat transfer fluid path (1081), and the heat transfer fluid path (107) formed between the interior of the support tube (101) and the exterior of the biasedly-sleeved heat transfer fluid path (1081) according to the present invention.

FIG. 39 is a front view of FIG. 38.

As shown in FIG. 38 and FIG. 39, the interior of the heat dissipater (104) installed with the electric energy application device assembly (108) is formed a space allowing the fluid to flow freely, and the heat transfer fluid path (1081) and the heat transfer fluid path (107) formed between the interior of the support tube (101) and the exterior of the biasedly-sleeved heat transfer fluid path (1081) constitute the fluid inlet/outlet path.

FIG. 40 is a schematic structural view showing a fluid inlet/outlet path being formed through a configuration formed in the heat dissipater (104) installed with the electric energy application device assembly (108) and having a central path (570) extended outwardly towards two lateral sides for respectively forming a circular path (580) and a circular path (590) along the inner side of the outer periphery of the heat dissipater (104) and leaded to the heat transfer fluid path (1081), and the heat transfer fluid path (107) formed between the interior of the support tube (101) and the exterior of the sleeved heat transfer fluid path (1081) according to the present invention.

FIG. 41 is a front view of FIG. 40.

As shown in FIG. 40 and FIG. 41, the fluid inlet/outlet path is formed through the configuration formed in the heat dissipater (104) installed with the electric energy application device assembly (108) and having the central path (570) extended outwardly towards two lateral sides for respectively forming a circular path (580) and a circular path (590) extended along the inner side of the outer periphery of the heat dissipater (104) and leaded to the heat transfer fluid path (1081), and the heat transfer fluid path (107) formed between the interior of the support tube (101) and the exterior of the sleeved heat transfer fluid path (1081).

FIG. 42 is a schematic structural view showing a fluid inlet/outlet path being formed through a configuration formed in the heat dissipater

(104) installed with the electric energy application device assembly (108) and having a central path (570) extended outwardly towards two lateral sides for respectively forming a circular path (580) and a circular path (590) extended along the inner side of the outer periphery of the heat dissipater (104) and leaded to the heat transfer fluid path (1081), and the heat transfer fluid path (107) formed between the interior of the support tube (101) and the exterior of the biasedly-sleeved heat transfer fluid path (1081) according to the present invention.

FIG. 43 is a front view of FIG. 42.

As shown in FIG. 42 and FIG. 43, the fluid inlet/outlet path is formed through the configuration formed in the heat dissipater (104) installed with the electric energy application device assembly (108) and having the central path (570) extended outwardly towards two lateral sides for respectively forming the circular path (580) and the circular path (590) extended along the inner side of the outer periphery of the heat dissipater (104) and leaded to the heat transfer fluid path (1081), and the heat transfer fluid path (107) formed between the interior of the support tube (101) and the exterior of the biasedly-sleeved heat transfer fluid path (1081).

FIG. 44 is a schematic structural view showing a fluid inlet/outlet path being formed through a configuration formed in the heat dissipater (104) installed with the electric energy application device assembly (108) and having a central penetrated hole (610) of a central shunting piece (600) outwardly extended towards two lateral sides for respectively forming a circular path (580) and a circular path (590) extended along the inner side of the outer periphery of the heat dissipater (104) and leaded to the heat transfer fluid path (1081), and the heat transfer fluid path (107) formed between the interior of the support tube (101) and the exterior of the sleeved heat transfer fluid path (1081) according to the present invention.

FIG. 45 is a front view of FIG. 44.

As shown in FIG. 44 and FIG. 45, the fluid inlet/outlet path is formed through the configuration formed in the heat dissipater (104) installed with the electric energy application device assembly (108) and having the central penetrated hole (610) of the central shunting piece (600) outwardly
5 extended towards two lateral sides for respectively forming the circular path (580) and the circular path (590) extended along the inner side of the outer periphery of the heat dissipater (104) and led to the heat transfer fluid path (1081), and the heat transfer fluid path (107) formed between the interior of the support tube (101) and the exterior of the sleeved heat
10 transfer fluid path (1081).

FIG. 46 is a schematic structural view showing a fluid inlet/outlet path being formed through a configuration formed in the heat dissipater (104) installed with the electric energy application device assembly (108) and having a central penetrated hole (610) of a central shunting piece (600)
15 outwardly extended towards two lateral sides for respectively forming a circular path (580) and a circular path (590) extended along the inner side of the outer periphery of the heat dissipater (104) and led to the heat transfer fluid path (1081), and the heat transfer fluid path (107) formed between the interior of the support tube (101) and the exterior of the
20 biasedly-sleeved heat transfer fluid path (1081) according to the present invention.

FIG. 47 is a front view of FIG. 46.

As shown in FIG. 46 and FIG. 47, the fluid inlet/outlet path is formed through the configuration formed in the heat dissipater (104) installed
25 with the electric energy application device assembly (108) and having the central penetrated hole (610) of the central shunting piece (600) outwardly extended towards two lateral sides for respectively forming the circular path (580) and the circular path (590) extended along the inner side of the outer periphery of the heat dissipater (104) and led to the heat transfer
30 fluid path (1081), and the heat transfer fluid path (107) formed between

the interior of the support tube (101) and the exterior of the biasedly-sleeved heat transfer fluid path (1081).

FIG. 48 is a schematic structural view showing the electric energy application device assembly (108) being upwardly installed, and a fluid inlet/outlet path being formed through the heat transfer fluid path (1081) composed of an axial central penetrated hole (700) and annularly-arranged holes (710) and leaded to the electric energy application device assembly, and the heat transfer fluid path (107) formed between the support tube (101) and the heat transfer fluid path (1081) of the electric energy application device assembly according to the present invention.

FIG. 49 is a front view of FIG. 48.

As shown in FIG. 48 and FIG. 49, the electric energy application device assembly (108) is upwardly installed, and the fluid inlet/outlet path is formed through the heat transfer fluid path (1081) composed of the axial central penetrated hole (700) and the annularly-arranged holes (710) and leaded to the electric energy application device assembly, and the heat transfer fluid path (107) formed between the support tube (101) and the heat transfer fluid path (1081) of the electric energy application device assembly.

FIG. 50 is a schematic structural view showing a locked-on heat dissipation ring (800) being optionally installed at the outer side of the heat dissipater (104) according to the present invention.

As shown in FIG. 50, the locked-on heat dissipation ring (800) is optionally installed at the outer side of the heat dissipater (104), wherein the locked-on heat dissipation ring (800) is made of a material having good heat transferring and radially heat dissipating property.

FIG. 51 is a schematic structural view showing a sleeved-on heat dissipation ring (900) being optionally installed at the outer side of the heat dissipater (104) according to the present invention.

As shown in FIG. 51, the sleeved-on heat dissipation ring (900) is

optionally installed at the outer side of the heat dissipater (104), wherein the sleeved-on heat dissipation ring (900) is made of a material having good heat transferring and radially heat dissipating property.

CLAIMS

1. A heat-dissipating structure having embedded support tube to form internally recycling heat transfer fluid and application apparatus, which is installed in the ground soil or liquid of a shallow ground natural thermal energy body for performing temperature equalizing operation with the external gaseous or solid or liquid environment and/or the soil or liquid of the shallow ground natural thermal energy body, the interior of a support tube (101) is installed with an inner tube (103) for being penetrated through, the inner diameter of the support tube (101) is greater than the outer diameter of the inner tube (103), the partitioned space formed through the diameter differentiation allows a fluid path to be formed, the distal end of the support tube (101) is sealed, the distal end of the inner tube (103) is shorter than the distal end of the support tube (101) or preformed with fluid holes, the distal ends of both tubes are formed with a flow returning segment allowing the heat transfer fluid to be returned;

The front tube port of the support tube (101) and the front tube port of the inner tube (103) allow the heat transfer fluid passing an electric energy application device assembly (108) and/or a heat dissipater thereof to be transferred, wherein one of the tube ports allows the heat transfer fluid to be transferred for passing the electric energy application device assembly (108) and/or the heat dissipater thereof, and the other tube port allows the heat transfer fluid which already passed the electric energy application device assembly (108) and/or the heat dissipater thereof to be returned;

One or more than one of fluid pumps (105) are serially installed on the mentioned closed recycling heat transfer fluid path, the flowing direction thereof can be selected from one flowing direction or two flowing directions enabled to be switched or periodically changed;

The structure of the heat transfer fluid path formed between the

mentioned electric energy application device assembly (108) and/or the heat dissipater thereof and the support tube (101) and the inner tube (103) includes one or more than one of followings:

5 (a) the interior of the electric energy application device assembly (108) is formed with one or more than one of penetrating heat transfer fluid paths connected in serial or in parallel, the fluid inlet port and the fluid outlet port are respectively communicated with the tube port of the support tube (101) and the tube port of the inner tube (103);

10 (b) the heat dissipater installed in the electric energy application device assembly (108) is formed with one or more than one of penetrating heat transfer fluid paths connected in parallel, the fluid inlet port and the fluid outlet port are respectively communicated with the tube port of the support tube (101) and the tube port of the inner tube (103);

15 (c) one or more than one of heat transfer fluid paths formed in the interior of the electric energy application device assembly (108) are connected in serial or in parallel with the heat transfer fluid paths formed in the heat dissipater thereof, the fluid inlet port and the fluid outlet port are respectively communicated with the tube port of the support tube (101) and the tube port of the inner tube (103);

20 (d) the electric energy application device assembly (108) is formed with two or more than two of heat transfer fluid paths connected through external tubes so as to form the fluid inlet port and the fluid outlet port respectively communicated with the tube port of the support tube (101) and the tube port of the inner tube (103), or the interior thereof is bent to the U-like shape or L-like shape, the fluid inlet port and the fluid outlet port at the same or different sides are respectively communicated with the tube port of the support tube (101) and the tube port of the inner tube (103);

30 (e) the exterior of the electric energy application device assembly

(108) is installed with a sealed housing, thereby forming a space between the above two for allowing the heat transfer fluid to pass, the electric energy application device assembly (108) is formed with one or more than one of heat transfer fluid paths connected in serial or in parallel, one end thereof is formed with a heat transfer fluid inlet/outlet port which is leaded to the tube port of the inner tube (103), the tube port at the other end is leaded to the space formed between the housing and the electric energy application device assembly (108), a heat transfer fluid connection port is formed on the sealed housing for being communicated with the tube port of the support tube (101);

(f) a sealed space allowing the heat transfer fluid to pass is formed between the electric energy application device assembly (108) and the heat dissipater thereof and the installed housing, the electric energy application device assembly (108) and/or the heat dissipater thereof is formed with one or more than one of heat transfer fluid paths connected in serial or in parallel, one end thereof is formed with a heat transfer fluid inlet/outlet port which is leaded to the tube port of the inner tube (103), the tube port at the other end is leaded to the space formed between the housing and the electric energy application device assembly (108) and/or the heat dissipater thereof, a heat transfer fluid inlet/outlet port is formed on the sealed housing for being communicated with the tube port of the support tube (101);

(g) a sealed housing is jointly formed by the exterior of the electric energy application device assembly (108) and/or the heat dissipater thereof and the matched housing, the interior of the electric energy application device assembly (108) and/or the heat dissipater thereof and the matched housing is formed with a space allowing the heat transfer fluid to pass and leaded to the tube port of the support tube (101), the electric energy application device assembly (108) and/or the heat dissipater thereof is formed with one or more than one

of heat transfer fluid paths connected in serial or in parallel, one end thereof is formed with a heat transfer fluid connection port which is leaded to the tube port of the inner tube (103), the tube port at the other end is leaded to the space formed between the housing and the electric energy application device assembly (108) and/or the heat dissipater thereof, a heat transfer fluid connection port is formed on the sealed housing for being communicated with the tube port of the support tube (101);

The gaseous or liquid heat transfer fluid pumped by the fluid pump (105) passes the support tube (101) of the closed recycling heat transfer fluid path and the exposed portion of the relevant structure, thereby enabling to perform temperature equalizing operation with the external gaseous or solid or liquid environment and/or the soil or liquid of the shallow ground natural thermal energy body;

The mentioned electric energy application device assembly (108) includes an illumination device utilizing electric energy being converted into photo energy, e.g. an illumination device adopting LED and/or a photovoltaic, e.g. a solar panel and/or a wind power generator and/or a transformer and/or a motor driven by electric energy, and peripheral devices, control circuits devices, overload protecting devices and/or temperature protection devices are optionally installed according to actual needs for assisting the operation of the electric energy application device assembly (108).

2. A heat-dissipating structure having embedded support tube to form internally recycling heat transfer fluid and application apparatus as claimed in claim 1, wherein mainly consists:

-- support tube (101): related to a hollow tube member constituted by the material having mechanical strength, the tube body is divided into an upper tube body, a mid tube body and a lower tube body, wherein:

The upper tube body is mainly served to allow the electric energy

application device assembly (108) to be installed;

The mid tube body is served to provide a support function and to transfer the thermal energy between the interior and the exterior of the tube;

5 The lower tube body is served to be installed in the stratum or liquid of the shallow ground natural thermal energy body for transferring thermal energy;

10 The support tube (101) includes being formed in a tube member with round shape or other geometric shapes, and being made of a material having mechanical strength and better heat conductivity or a material having heat insulation property; the mentioned support tube (101) can be optionally installed with heat transfer fins (2001) at the exterior of the tube member according to actual needs;

-- inner tube (103): constituted by a tube member having an outer
15 diameter smaller than the inner diameter of the support tube (101) and made of a hard material, e.g. metal, or a flexible material or a soft material, e.g. plastic, or a fabric or other materials having similar properties, the inner tube (103) is formed in a linear or bended or curved shaped or can be freely deformed if being made of the flexible
20 material or the soft material thereby being enabled to be installed in the support tube (101) without affecting the smoothness of the heat transfer fluid path, the upper end thereof is leaded to the heat transfer fluid path of the electric energy application device assembly (108) or the heat dissipater (104) thereof installed at the upper portion of the
25 support tube (101), the lower end thereof is leaded to the mid portion or extended to the lower portion of the support tube (101), a diameter differentiation is formed between the outer diameter of the inner tube (103) and the inner diameter of the support tube (101) thereby forming a reversed space which can be served as the heat transfer fluid path, so
30 the fluid path allowing the heat transfer fluid to pass is formed through

the inner tube and two tube ports at two ends of the inner tube and the reserved space formed between the outer diameter of the inner tube and the inner diameter of the outer tube, and selected locations on the mentioned fluid path can be serially installed with one or more than
5 one of fluid pumps (105), the space defined between the upper end of the inner tube (103) and the upper portion of the support tube (101) is served to allow the electric energy application device assembly (108) to be installed;

The inner tube (103) includes being formed in a tube member
10 with round shape or other geometric shapes, and being made of (a) a hard material or flexible material or soft material having heat insulation property, or (b) a hard material or flexible material or soft material having better heat conductivity, and the exterior of the tube member is provided with a heat insulation material, or (c) a hard
15 material or flexible material or soft material having better heat conductivity, and the interior of the tube member is provided with a heat insulation material, or (d) a hard material or flexible material or soft material having better heat conductivity;

-- fluid pump (105): constituted by a pump driven by an electric motor
20 for being used to pump the gaseous or liquid heat transfer fluid with respect to the controlled flowing direction and flowing rate of the fluid to be pumped;

-- electric energy application device assembly (108): constituted by an illumination device driven by electric energy, and/or a power generator
25 driven by the kinetic power provided by external gaseous or liquid fluid, and/or a device driven by photo energy for generating electric energy and also generating thermal loss, and/or a transformer and/or a motor driven by electric energy, and peripheral devices, control circuits devices, overload protecting devices and/or temperature protection
30 devices are optionally installed according to actual needs for assisting

the operation of the electric energy application device assembly (108);

According to the heat-dissipating structure having embedded support tube to form internally recycling heat transfer fluid and application apparatus, with the pumping operation provided by the fluid pump (105), the gaseous or liquid heat transfer fluid is allowed to pass the heat transfer fluid outlet port at the upper end of the inner tube (103), then pass the heat transfer fluid path of the electric energy application device assembly (108) which generates thermal loss during operation and the heat dissipater (104) thereof, then pass the heat transfer fluid path formed by the partitioned space defined between the interior of the support tube (101) and the inner tube (103) thereby being leaded to the lower tube body of the support tube (101) then returned from the heat transfer fluid inlet port at the lower end of the inner tube (103), thereby forming a closed recycling heat transfer fluid loop, or the heat transfer fluid pumped by the adapted fluid pump (105) can pass the mentioned paths in a reverse order and in the reverse flowing direction thereby forming a closed recycling heat transfer fluid loop having reverse order and reverse flowing direction, so through the heat transfer fluid passing the outer surface of the electric energy application device assembly (108) and the heat dissipater (104) thereof, and/or the exposed portion at the outer surface of the support tube (101), temperature equalizing operation is enabled to be performed with the external gaseous or liquid or solid environment, and/or the heat transfer fluid pumped by the fluid pump (105) is enabled to further transfer thermal energy to the stratum or liquid through the embedded portion of the support tube (101) installed in the stratum or liquid of the shallow ground natural thermal energy body.

3. A heat-dissipating structure having embedded support tube to form internally recycling heat transfer fluid and application apparatus as claimed in claims 1 or 2, wherein the upper tube body of the support

5 tube (101) which allows the electric energy application device assembly (108) to be installed can be further installed with a housing (106) for protecting the electric energy application device assembly (108), and the space formed by the surface of the electric energy application device assembly (108) or the surface of the heat dissipater (104) thereof can be served as a heat transfer fluid path (107) for transferring the heat transfer fluid, and mainly consists of:

10 -- support tube (101): related to a hollow tube member constituted by the material having mechanical strength, the tube body is divided into an upper tube body, a mid tube body and a lower tube body, wherein:

The upper tube body is mainly served to allow the electric energy application device assembly (108) and the housing (106) to be installed;

15 The mid tube body is served to provide a support function and to transfer the thermal energy between the interior and the exterior of the tube;

The lower tube body is served to be installed in the stratum or liquid of the shallow ground natural thermal energy body for transferring thermal energy;

20 The support tube (101) includes being formed in a tube member with round shape or other geometric shapes, and being made of a material having mechanical strength and better heat conductivity or a material having heat insulation property; the mentioned support tube (101) can be optionally installed with heat transfer fins (2001) at the exterior of the tube member according to actual needs;

25 -- inner tube (103): constituted by a tube member having an outer diameter smaller than the inner diameter of the support tube (101) and made of a hard material, e.g. metal, or a flexible material or a soft material, e.g. plastic, or a fabric or other materials having similar properties, the inner tube (103) is formed in a linear or bended or
30

curved shaped or can be freely deformed if being made of the flexible material or the soft material thereby being enabled to be installed in the support tube (101) without affecting the smoothness of the heat transfer fluid path, the upper end thereof is leaded to the heat transfer fluid path of the electric energy application device assembly (108) or the heat dissipater (104) thereof installed at the upper portion of the support tube (101), the lower end thereof is leaded to the mid portion or extended to the lower portion of the support tube (101), a diameter differentiation is formed between the outer diameter of the inner tube (103) and the inner diameter of the support tube (101) thereby forming a reversed space which can be served as the heat transfer fluid path, so the fluid path allowing the heat transfer fluid to pass is formed through the inner tube and two tube ports at two ends of the inner tube and the reserved space formed between the outer diameter of the inner tube and the inner diameter of the outer tube, and selected locations on the mentioned fluid path can be serially installed with one or more than one of fluid pumps (105), the space defined between the upper end of the inner tube (103) and the upper portion of the support tube (101) is served to allow the electric energy application device assembly (108) to be installed;

The inner tube (103) includes being formed in a tube member with round shape or other geometric shapes, and being made of (a) a hard material or flexible material or soft material having heat insulation property, or (b) a hard material or flexible material or soft material having better heat conductivity, and the exterior of the tube member is provided with a heat insulation material, or (c) a hard material or flexible material or soft material having better heat conductivity, and the interior of the tube member is provided with a heat insulation material, or (d) a hard material or flexible material or soft material having better heat conductivity;

-- fluid pump (105): constituted by a pump driven by an electric motor for being used to pump the gaseous or liquid heat transfer fluid with respect to the controlled flowing direction and flowing rate of the fluid to be pumped;

5 -- housing (106): made of a material having heat conductive or heat insulation property and used for covering the exterior of the electric energy application device assembly (108) so as to be sealed relative to the exterior, the heat transfer fluid is pumped by the fluid pump (105) for flowing from the heat transfer fluid outlet port at the upper end of

10 the inner tube (103) to the space formed between the housing (106) and the electric energy application device assembly (108), then passing the heat transfer fluid path formed through the partitioned space defined by the inner diameter of the support tube (101) and the outer diameter of the inner tube (103), then flowing towards the lower tube

15 body of the support tube (101), then returning via the heat transfer fluid inlet port at the lower end of the inner tube (103), thereby forming a closed recycling heat transfer fluid loop, or forming a closed recycling heat transfer fluid loop having opposite flowing direction through changing the fluid flowing direction in which the fluid pump

20 (105) is pumping;

-- electric energy application device assembly (108): constituted by an illumination device driven by electric energy, and/or a power generator driven by the kinetic power provided by external gaseous or liquid fluid, and/or a device driven by photo energy for generating electric

25 energy and also generating thermal loss, and/or a transformer and/or a motor driven by electric energy, and peripheral devices, control circuits devices, overload protecting devices and/or temperature protection devices are optionally installed according to actual needs for the operation of assisting the electric energy application device assembly

30 (108);

-- electric controlling device (112): constituted by solid-state or electromechanical components, or chips and relevant operation software, the electric controlling device (112) is optionally installed;

-- temperature protecting device (102): constituted by
5 electromechanical thermal actuated switch or thermal braking fuse, or solid-state temperature detecting units or solid-state temperature switch unit, served to directly or through the control of the electric controlling device (120) terminate the load or partially terminate the load or reduce the load power, when the load is overheated, and the
10 temperature protecting device (102) is optionally installed;

Through the fluid pumps (105) serially installed on the heat transfer fluid path pumping the heat transfer fluid to flow from the heat transfer fluid outlet port at the upper end of the inner tube (103) and pass the space formed at the interior of the electric energy application
15 device assembly (108) and/or the space defined between the exterior of the electric energy application device assembly (108) and the sealed housing, then pass the partitioned space of the fluid path defined between the inner diameter of the support tube (101) and the outer diameter of the inner tube (103), then return via the heat transfer fluid
20 inlet port at the lower end of the inner tube (103) thereby forming the closed recycling flow, or forming a closed recycling heat transfer fluid loop having opposite flowing direction through changing the fluid flowing direction in which the fluid pump (105) is pumping, the thermal energy of the gaseous or liquid heat transfer fluid pumped by
25 the fluid pump (105) is enabled to perform temperature equalizing operation with the external gaseous or liquid or solid environment through the outer surface of the electric energy application device assembly (108) and/or the surface of the sealed housing (106) installed at the exterior of the electric energy application device assembly (108)
30 and/or the exposed portion at the outer surface of the support tube

(101), and/or the heat transfer fluid pumped by the fluid pump (105) is enabled to further transfer thermal energy to the stratum or liquid through the embedded portion of the support tube (101) installed in the stratum or liquid of the shallow ground natural thermal energy body.

- 5 4. A heat-dissipating structure having embedded support tube to form internally recycling heat transfer fluid and application apparatus as claimed in claim 1, wherein includes the illumination device utilizing electric energy being converted into photo energy (109) being adopted as the electric energy application device assembly (108), and the main
10 configuration includes the support tube (101), the inner tube (103), the fluid pump (105), and the electric energy application device assembly (108) is designed to adopt the illumination device utilizing electric energy being converted into photo energy (109) which generates thermal loss and/or the light emitting diode (LED), and peripheral
15 devices, control circuits devices, overload protecting devices, and temperature protection devices are optionally installed according to actual needs for assisting the operation of the illumination device utilizing electric energy being converted into photo energy (109);

Wherein: the heat transfer fluid pumped by the fluid pump (105)
20 passes the heat transfer fluid path (107) formed on the surface or the interior of the illumination device utilizing electric energy being converted into photo energy (109) or the heat dissipater (104) thereof, the thermal energy transferred through the heat transfer fluid path (107) is enabled to perform temperature equalizing operation with the
25 external gaseous or liquid or solid environment through the exposed portion at the outer surface of the support tube (101), and/or the heat transfer fluid pumped by the fluid pump (105) is enabled to further transfer thermal energy to the stratum or liquid through the embedded portion of the support tube (101) installed in the stratum or liquid of
30 the shallow ground natural thermal energy body;

- illumination device utilizing electric energy being converted into photo energy (109): constituted by an illumination device utilizing electric energy being converted into photo energy which is composed of various gaseous lamps, solid-state LED or OLED and other peripheral devices e.g. a light-pervious member (1061), and further including a display screen, a billboard, a signal or a warning sign operated through the photo energy of the illumination device utilizing electric energy being converted into photo energy (109);
- fluid pump (105): constituted by a pump driven by an electric motor for being used to pump the gaseous or liquid heat transfer fluid with respect to the controlled flowing direction and flowing rate of the fluid to be pumped;
- electric controlling device (112): constituted by solid-state or electromechanical components, or chips and relevant operation software; according to this embodiment, the electric controlling device (112) is served to control the input voltage, the current and the working temperature of the illumination device utilizing electric energy being converted into photo energy (109) and to control the operation timing of the fluid pump (105);
- temperature protecting device (102): constituted by electromechanical thermal actuated switch or thermal braking fuse, or solid-state temperature detecting units or solid-state temperature switch unit, installed in the illumination device utilizing electric energy being converted into photo energy (109) or the heat dissipater (104) thereof, and served to directly or through the control of the electric controlling device (112) to terminate the load or partially terminate the load or reduce the load power or control the fluid pump (105), when the temperature is abnormal; the temperature protecting device (102) is optionally installed.
5. A heat-dissipating structure having embedded support tube to form

internally recycling heat transfer fluid and application apparatus as claimed in claim 1, wherein includes the photovoltaic (110) being adopted as the electric energy application device assembly (108), and the main configuration includes the support tube (101), the inner tube (103), the fluid pump (105), and the electric energy application device assembly (108) is designed to adopt the photovoltaic (110) capable of converting photo energy into electric energy and generating thermal loss, and peripheral devices, control circuits devices, overload protecting devices, and temperature protection devices are optionally installed according to actual needs for assisting the photovoltaic (110);

Wherein: the heat transfer fluid pumped by the fluid pump (105) passes the heat transfer fluid path (107) at the backside of the photovoltaic (110) or the surface or the interior of the heat dissipater (104) thereof, the thermal energy transferred through the heat transfer fluid path (107) is enabled to perform temperature equalizing operation with the external gaseous or liquid or solid environment through the exposed portion at the outer surface of the support tube (101), and/or the heat transfer fluid pumped by the fluid pump (105) is enabled to further transfer thermal energy to the stratum or liquid through the embedded portion of the support tube (101) installed in the stratum or liquid of the shallow ground natural thermal energy body;

-- photovoltaic (110): constituted by various types of photovoltaic which receives lights for generating and outputting electric energy, e.g. a solar panel, and other relevant peripheral devices;

-- fluid pump (105): constituted by a pump driven by an electric motor for being used to pump the gaseous or liquid heat transfer fluid with respect to the controlled flowing direction and flowing rate of the fluid to be pumped;

-- electric controlling device (112): constituted by solid-state or electromechanical components, or chips and relevant operation

software; according to this embodiment, the electric controlling device (112) is served to control the output voltage, the current and the working temperature of the photovoltaic (110) and to control the operation timing of the fluid pump (105);

5 -- temperature protecting device (102): constituted by electromechanical thermal actuated switch or thermal braking fuse, or solid-state temperature detecting units or solid-state temperature switch unit, served to directly or through the control of the electric controlling device (112) terminate the load or partially terminate the load or
10 reduce the load power or control the fluid pump (105), when the temperature of the photovoltaic (110) is abnormal; the temperature protecting device (102) is optionally installed.

6. A heat-dissipating structure having embedded support tube to form internally recycling heat transfer fluid and application apparatus as
15 claimed in claim 1, wherein includes the wind power generating device (111) being adopted as the electric energy application device assembly (108), and the main configuration includes the support tube (101), the inner tube (103) and the fluid pump (105) installed in the shallow ground natural thermal energy body (100), and the electric energy
20 application device assembly (108) is designed to adopt a wind power generator (222) of the wind power generating device (111), and peripheral devices, control circuits devices, overload protecting devices and/or temperature protection devices are optionally installed according to actual needs for assisting the operation of the wind power
25 generating device (111);

Wherein: the heat transfer fluid pumped by the fluid pump (105) passes the heat transfer fluid path in the wind power generator (222) of the wind power generating device (111) and/or in the heat dissipater thereof, or further including the heat transfer fluid path in the electric
30 controlling device (112) and/or in the heat dissipater thereof, and

jointly with the inner tube (103) and the partitioned space formed between the inner tube (103) and the interior of the support tube (101) to form a sealed heat transfer fluid path, thereby allowing the heat transfer fluid to flow therein, and the temperature equalizing operation is enabled to be performed with the external gaseous or liquid or solid environment and/or the soil or liquid of the shallow ground natural thermal energy body through the exposed portion at the outer surface of the support tube (101);

-- wind power generating device (111): constituted by wind turbine blades and the wind power generator (222) driven thereby and/or the electric controlling device (112) and other relevant peripheral devices, wherein the wind power generator (222) and/or the electric controlling device (112) are the main components receiving the heat dissipating operation;

-- fluid pump (105): constituted by a pump driven by a wind power driven shaft or by an electric motor, used for pumping the gaseous or liquid heat transfer fluid with respect to the controlled flowing direction and flowing rate of the fluid to be pumped;

-- electric controlling device (112): constituted by solid-state or electromechanical components, or chips and relevant operation software, used for controlling the system operation of the wind power generating device (111), including the output voltage, the current and the working temperature of the wind power generator (222), AC and DC converting, parallel controlling of AC output electric energy and public electricity system, and controlling the operation timing of the fluid pump (105);

-- temperature protecting device (102): constituted by electromechanical thermal actuated switch or thermal braking fuse, or solid-state temperature detecting units or solid-state temperature switch unit, and served to directly or through the electric controlling device

(112) control the system operation of the wind power generator (222) and/or the wind power generating device (111), as well as control the fluid pump (105) when the temperature of the wind power generating device (111) is abnormal; the temperature protecting device (102) is optionally installed.

7. A heat-dissipating structure having embedded support tube to form internally recycling heat transfer fluid and application apparatus as claimed in claim 1, wherein includes the transformer (444) being adopted as the electric energy application device assembly (108) and the main configuration includes the support tube (101), the inner tube (103) and the fluid pump (105), and the electric energy application device assembly (108) is designed to adopt a transformer (444), and peripheral devices, control circuits devices, overload protecting devices and/or temperature protection devices are optionally installed according to actual needs for assisting the operation of the transformer (444);

Wherein: the heat transfer fluid pumped by the fluid pump (105) passes the heat transfer fluid path (107) formed on the surface or the interior of the transformer (444) or the heat dissipater (104) thereof, the thermal energy transferred through the heat transfer fluid path (107) is enabled to perform temperature equalizing operation with the external gaseous or liquid or solid environment through the exposed portion at the outer surface of the support tube (101), and/or the heat transfer fluid pumped by the fluid pump (105) is enabled to further transfer thermal energy to the stratum or liquid through the embedded portion of the support tube (101) installed in the stratum or liquid of the shallow ground natural thermal energy body;

-- transformer (444): including winding sets, magnetic conductive wirings and an enclosure, used for outputting and inputting single-phase or three-phase (including multiple-phase) AC electric

energy, or inputting and outputting pulse electric energy; the transformer includes the self-coupled or separated-winding transformer having a dry structure containing gas or wet structure containing cooling fluid, the surface or the exterior of the transformer is formed with a pipeline heat dissipating structure allowing the fluid to pass, or formed with a fluid inlet/outlet port allowing the fluid to flow in or out of the internal space of the transformer; the transformer is combined on the support tube (101) through a transformer support rack (445);

-- fluid pump (105): constituted by a pump driven by electric energy, used for pumping the gaseous or liquid heat transfer fluid with respect to the controlled flowing direction and flowing rate of the fluid to be pumped;

-- electric controlling device (112): constituted by solid-state or electromechanical components, or chips and relevant operation software; according to this embodiment, the electric controlling device (112) is used for controlling the output voltage, the current and the working temperature of the transformer (444), and controlling the operation timing of the fluid pump (105);

-- temperature protecting device (102): constituted by electromechanical thermal actuated switch or thermal braking fuse, or solid-state temperature detecting units or solid-state temperature switch unit, served to directly or through the control of the electric controlling device (112) terminate the load or partially terminate the load or reduce the load power and control the fluid pump (105), when the temperature of the transformer (444) is abnormal; the temperature protecting device (102) is optionally installed.

8. A heat-dissipating structure having embedded support tube to form internally recycling heat transfer fluid and application apparatus as claimed in claim 1, wherein includes the motor (333) driven by electric energy being adopted as the electric energy application device

assembly (108), and the main configuration includes the support tube (101), the inner tube (103) and the fluid pump (105), and the electric energy application device assembly (108) is designed to adopt a motor (333) driven by electric energy, and peripheral devices, control circuits devices, overload protecting devices and/or temperature protection devices are optionally installed according to actual needs for assisting the operation of the motor (333);

Wherein: the heat transfer fluid pumped by the fluid pump (105) passes the heat transfer fluid path (107) formed on the surface or the interior of the motor (333) driven by electric energy or the heat dissipater (104) thereof, the thermal energy transferred through the heat transfer fluid path (107) is enabled to perform temperature equalizing operation with the external gaseous or liquid or solid environment through the exposed portion at the outer surface of the support tube (101), and/or the heat transfer fluid pumped by the fluid pump (105) is enabled to further transfer thermal energy to the stratum or liquid through the embedded portion of the support tube (101) installed in the stratum or liquid of the shallow ground natural thermal energy body;

-- motor (333): constituted by a revolving electromechanical device driven by AC or DC electric energy for outputting rotational kinetic energy thereby driving the motor driven load (334);

-- fluid pump (105): constituted by a pump driven by electric energy, used for pumping the gaseous or liquid heat transfer fluid with respect to the controlled flowing direction and flowing rate of the fluid to be pumped;

-- electric controlling device (112): constituted by solid-state or electromechanical components, or chips and relevant operation software; according to this embodiment, the electric controlling device (112) is used for controlling the input voltage, the current and the

working temperature of the motor (333) driven by electric energy, and controlling the operation timing of the fluid pump (105);

-- temperature protecting device (102): constituted by electromechanical thermal actuated switch or thermal braking fuse, or solid-state temperature detecting units or solid-state temperature switch unit, served to directly or through the control of the electric controlling device (112) terminate the load or partially terminate the load or reduce the load power and control the fluid pump (105), when the temperature of the motor (333) driven by electric energy is abnormal; the temperature protecting device (102) is optionally installed.

9. A heat-dissipating structure having embedded support tube to form internally recycling heat transfer fluid and application apparatus as claimed in claim 1, wherein the upper portion of the support tube (101) and the inner tube (103) can be further formed by a manifold structure for being installed with plural the same or different electric energy application device assemblies (108) which share the mid tube body and the lower tube body of the support tube, and the main configuration includes the mentioned support tube (101), the inner tube (103), the fluid pump (105), wherein the upper portion of the support tube (101) is formed with a manifold structure allowing plural electric energy application device assemblies (108) to be installed thereon, and peripheral devices, control circuits devices, overload protecting devices and/or temperature protection devices are optionally installed according to actual needs for assisting the electric energy application device assembly (108), the plural electric energy application device assemblies (108) share the mid tube body and the lower tube body of the support tube (101), and same or different electric energy application device assemblies (108) are respectively installed on the manifold formed on the upper portion of the support tube (101), and correspondingly installed with an inner tube (103) in the support tube

(101);

Wherein: the heat transfer fluid pumped by the fluid pump (105) passes the heat transfer fluid path (107) formed on the surface or the interior of the individual electric energy application device assembly (108) or the heat dissipater (104) thereof, the thermal energy transferred through the heat transfer fluid path (107) is enabled to perform temperature equalizing operation with the external gaseous or liquid or solid environment, and/or the heat transfer fluid pumped by the fluid pump (105) is enabled to further transfer thermal energy to the stratum or liquid through the embedded portion of the support tube (101) installed in the stratum or liquid of the shallow ground natural thermal energy body.

10.A heat-dissipating structure having embedded support tube to form internally recycling heat transfer fluid and application apparatus as claimed in claim 1, wherein the structure formed by the support tube (101) and the inner tube (103) includes one or more than one of followings:

the support tube (101) and the inner tube (103) are coaxially arranged or arranged in a substantially parallel manner, the space defined by the periphery of the inner tube (103) and between the support tube (101) and the inner tube (103) is served to allow the heat transfer fluid to pass, the inner tube (103) installed in the support tube (101) is shorter than the support tube (101), a length differentiation is formed between the lower end thereof and the sealed part at the lower portion of the support tube (101) and a supporter (1033) is provided for fastening, thereby forming the space allowing the heat transfer fluid to pass;

the support tube (101) and the inner tube (103) are installed in parallel, the lower end of the inner tube (103) in the support tube (101) is combined with the sealed part at the bottom of the lower portion of

the support tube (101), the lower end or the lower portion of the inner tube (103) is formed with a transversal hole (1031) or a notch (1032) penetrating the inner tube thereby allowing the heat transfer fluid to pass;

5 the support tube (101) and the inner tube (103) are eccentrically combined arranged, the lower end of the inner tube (103) in the support tube (101) is shorter, a length differentiation is formed between the lower end thereof and the sealed part at the bottom of the lower portion of the support tube (101) thereby forming a space allowing the
10 heat transfer fluid to pass;

 the support tube (101) and two or more than two of the inner tubes (103) are installed in parallel, the lower ends of the inner tubes (103) in the support tube (101) are shorter, a length differentiation is formed between the lower end thereof and the sealed part at the bottom
15 of the lower portion of the support tube (101) thereby forming a space allowing the heat transfer fluid to pass;

 the support tube (101) and the inner tube (103) are coaxially arranged or arranged in a substantially parallel manner, the space defined by the periphery of the inner tube (103) and between the
20 support tube (101) and the inner tube (103) is served to allow the heat transfer fluid to pass, the inner tube (103) installed in the support tube (101) is shorter than the support tube (101), a length differentiation is formed between the lower end thereof and the sealed part at the bottom of the lower portion of the support tube (101) thereby forming a space
25 allowing the heat transfer fluid to pass, a spiral flow guiding structure (2003) is further installed between the support tube (101) and the inner tube (103) thereby increasing the length of the heat transfer fluid path formed between the support tube (101) and the inner tube (103).

11.A heat-dissipating structure having embedded support tube to form
30 internally recycling heat transfer fluid and application apparatus as

claimed in claim 1, wherein the inner tube (103) in the support tube (101) can also be shortened and only the upper end being extended to the upper portion or the mid portion of the support tube (101) and not extended to the lower portion, including:

5 the support tube (101) and the inner tube (103) are coaxially arranged or arranged in a substantially parallel manner, the space defined by the periphery of the inner tube (103) and between the support tube (101) and the inner tube (103) is served to allow the heat transfer fluid to pass, the inner tube (103) installed in the support tube (101) is shorter than the support tube (101), and only extended to the upper portion or the mid portion of the support tube (101) and not extended to the lower portion, thereby shortening the length of the heat transfer fluid path; or

15 the support tube (101) and the inner tube (103) are eccentrically combined arranged, the lower end of the inner tube (103) installed in the support tube (101) is shorter than the support tube (101), and only extended to the upper portion or the mid portion of the support tube (101) and not extended to the lower portion, thereby shortening the length of the heat transfer fluid path; or

20 the support tube (101) and two or more than two of the inner tubes (103) are arranged in parallel, the lower end of the inner tubes (103) installed in the support tube (101) are shorter than the support tube (101), and only extended to the upper portion or the mid portion of the support tube (101) and not extended to the lower portion, thereby shortening the length of the heat transfer fluid path.

25 12.A heat-dissipating structure having embedded support tube to form internally recycling heat transfer fluid and application apparatus as claimed in claim 1, wherein the support tube for transferring the internally recycling heat transfer fluid can be further formed as a U-shaped tube member, and the main configuration is that the

30

U-shaped tube posts (201), (202) are leaded to the electric energy application device assembly (108) with a manner of one tube post higher than the other, the U-shaped tube posts (201), (202) are respectively leaded to the inlet and the outlet of the heat transfer fluid path of the electric energy application device assembly (108) and/or the heat dissipater (104) thereof, or leaded to the inlet and the outlet of the heat transfer fluid path formed in the internal space jointly defined by the outer surface of the electric energy application device assembly (108) and/or the heat dissipater (104) thereof and the housing (106), wherein the U-shaped tube post (201) is leaded to the mentioned inlet port, the U-shaped tube post (202) is leaded to the mentioned outlet port, and the lower portion of the U-shaped tube is formed with a bending portion (200) of U-shaped tube thereby forming a heat transfer fluid loop, and one or more than one of the fluid pumps (105) serially installed on the mentioned heat transfer fluid path are operated to pump in a selected direction, the bending portion (200) of U-shaped tube and the adjacent lower portion are directly embedded in the shallow ground natural thermal energy body (100); or the bending portion (200) of U-shaped tube and the adjacent lower portion can be further embedded in a columnar heat transfer covering member (2002) installed in the shallow ground natural thermal energy body (100);

In the mentioned U-shaped tube posts (201), (202), the U-shaped tube post (202) includes being formed in a tube member with round shape or other geometric shapes, and being made of a material having mechanical strength and better heat conductivity or a material having heat insulation property; the U-shaped tube post (201) includes being formed in a tube member with round shape or other geometric shapes, and being made of (a) a hard material or flexible material or soft material having heat insulation property, or (b) a hard material or flexible material or soft material having better heat conductivity, and

the exterior of the tube member is provided with a heat insulation material, or (c) a hard material or flexible material or soft material having better heat conductivity, and the interior of the tube member is provided with a heat insulation material, or (d) a hard material or flexible material or soft material having better heat conductivity;

The mentioned U-shaped tube posts (201), (202) can be installed with heat transfer fins (2001) between or at the exterior of the tube bodies according to actual needs.

13.A heat-dissipating structure having embedded support tube to form internally recycling heat transfer fluid and application apparatus as claimed in claim 1, wherein the main configuration is that the U-shaped tube posts (301), (302) are leaded to the electric energy application device assembly (108) at the left and the right side, the U-shaped tube posts (301), (302) are respectively leaded to the inlet and outlet of the heat transfer fluid path of the electric energy application device assembly (108) and/or the heat dissipater (104) thereof, or leaded to the inlet and outlet of the heat transfer fluid path formed in the internal space jointly defined by the outer surface of the electric energy application device assembly (108) and/or the heat dissipater (104) thereof and the housing (106), wherein the U-shaped tube post (301) is leaded to the mentioned inlet, the U-shaped tube post (302) is leaded to the mentioned outlet, and the lower portion of the U-shaped tube is formed with a bending portion (200) of U-shaped tube thereby forming a heat transfer fluid loop, and one or more than one of the fluid pumps (105) serially installed on the mentioned heat transfer fluid path are operated to pump in a selected direction, the bending portion (200) of U-shaped tube and the adjacent lower portion are directly embedded in the shallow ground natural thermal energy body (100); or the bending portion (200) of U-shaped tube and the adjacent lower portion can be further embedded in a columnar heat

transfer covering member (2002) installed in the shallow ground natural thermal energy body (100);

5 In the mentioned U-shaped tube posts (301), (302), the U-shaped tube post (302) includes being formed in a tube member with round shape or other geometric shapes, and being made of a material having mechanical strength and better heat conductivity or a material having heat insulation property; the U-shaped tube post (301) includes being formed in a tube member with round shape or other geometric shapes, and being made of (a) a hard material or flexible material or soft material having heat insulation property, or (b) a hard material or flexible material or soft material having better heat conductivity, and the exterior of the tube member is provided with a heat insulation material, or (c) a hard material or flexible material or soft material having better heat conductivity, and the interior of the tube member is provided with a heat insulation material, or (d) a hard material or flexible material or soft material having better heat conductivity;

10

15

The mentioned U-shaped tube posts (301), (302) can be installed with heat transfer fins (2001) between or at the exterior of the tube bodies according to actual needs.

20 14.A heat-dissipating structure having embedded support tube to form internally recycling heat transfer fluid and application apparatus as claimed in claim 1, wherein a heat transfer fluid path allowing the gaseous or liquid heat transfer fluid to pass is further formed by the space defined between the heat dissipater (104) of the electric energy application device assembly (108) and the housing (106) and the heat transfer fluid path (1041) of heat dissipater of the heat dissipater (104).

25

15.A heat-dissipating structure having embedded support tube to form internally recycling heat transfer fluid and application apparatus as claimed in claim 1, wherein a heat transfer fluid path allowing the gaseous or liquid heat transfer fluid to pass is further formed by at least

30

two heat transfer fluid paths (1041) of the heat dissipater (104) of the electric energy application device assembly (108) being connected with a U-shaped connection tube (1042).

16.A heat-dissipating structure having embedded support tube to form
internally recycling heat transfer fluid and application apparatus as
claimed in claim 1, wherein a heat transfer fluid path allowing the
gaseous or liquid heat transfer fluid to pass is further formed by the
space defined between the electric energy application device assembly
(108) and the housing (106) and the heat transfer fluid path (1081) of
the electric energy application device assembly (108).

17.A heat-dissipating structure having embedded support tube to form
internally recycling heat transfer fluid and application apparatus as
claimed in claim 1, wherein a heat transfer fluid path allowing the
gaseous or liquid heat transfer fluid to pass is further formed by at least
two heat transfer fluid paths (1081) of the electric energy application
device assembly (108) being connected in serial with a U-shaped
connection tube (1042).

18.A heat-dissipating structure having embedded support tube to form
internally recycling heat transfer fluid and application apparatus as
claimed in claim 1, wherein a heat transfer fluid path allowing the
gaseous or liquid heat transfer fluid to pass is further formed by a
U-shaped connection tube (1042) being connected in serial between at
least one heat transfer fluid path (1081) of the electric energy
application device assembly (108) and at least one heat transfer fluid
path (1041) of the heat dissipater (104) thereof.

19.A heat-dissipating structure having embedded support tube to form
internally recycling heat transfer fluid and application apparatus as
claimed in claim 1 or claim 12, wherein the interior of the heat
dissipater (104) installed with the electric energy application device
assembly (108) is formed a space allowing the fluid to flow freely, and

the heat transfer fluid path (1081) and the heat transfer fluid path (107) formed between the interior of the support tube (101) and the exterior of the sleeved heat transfer fluid path (1081) constitute the fluid inlet/outlet path.

5 20. A heat-dissipating structure having embedded support tube to form internally recycling heat transfer fluid and application apparatus as claimed in claim 1 or claim 12, wherein the interior of the heat dissipater (104) installed with the electric energy application device assembly (108) is formed a space allowing the fluid to flow freely, and
10 the heat transfer fluid path (1081) and the heat transfer fluid path (107) formed between the interior of the support tube (101) and the exterior of the biasedly-sleeved heat transfer fluid path (1081) constitute the fluid inlet/outlet path.

21. A heat-dissipating structure having embedded support tube to form
15 internally recycling heat transfer fluid and application apparatus as claimed in claim 1 or claim 12, wherein the fluid inlet/outlet path is formed through the configuration formed in the heat dissipater (104) installed with the electric energy application device assembly (108) and having the central path (570) extended outwardly towards two
20 lateral sides for respectively forming a circular path (580) and a circular path (590) extended along the inner side of the outer periphery of the heat dissipater (104) and led to the heat transfer fluid path (1081), and the heat transfer fluid path (107) formed between the interior of the support tube (101) and the exterior of the sleeved heat
25 transfer fluid path (1081).

22. A heat-dissipating structure having embedded support tube to form internally recycling heat transfer fluid and application apparatus as claimed in claim 1 or claim 12, wherein the fluid inlet/outlet path is formed through the configuration formed in the heat dissipater (104)
30 installed with the electric energy application device assembly (108)

and having the central path (570) extended outwardly towards two lateral sides for respectively forming the circular path (580) and the circular path (590) extended along the inner side of the outer periphery of the heat dissipater (104) and lead to the heat transfer fluid path (1081), and the heat transfer fluid path (107) formed between the interior of the support tube (101) and the exterior of the biasedly-sleeved heat transfer fluid path (1081).

23. A heat-dissipating structure having embedded support tube to form internally recycling heat transfer fluid and application apparatus as claimed in claim 1 or claim 12, wherein the fluid inlet/outlet path is formed through the configuration formed in the heat dissipater (104) installed with the electric energy application device assembly (108) and having the central penetrated hole (610) of the central shunting piece (600) outwardly extended towards two lateral sides for respectively forming the circular path (580) and the circular path (590) extended along the inner side of the outer periphery of the heat dissipater (104) and lead to the heat transfer fluid path (1081), and the heat transfer fluid path (107) formed between the interior of the support tube (101) and the exterior of the sleeved heat transfer fluid path (1081).

24. A heat-dissipating structure having embedded support tube to form internally recycling heat transfer fluid and application apparatus as claimed in claim 1 or claim 12, wherein the fluid inlet/outlet path is formed through the configuration formed in the heat dissipater (104) installed with the electric energy application device assembly (108) and having the central penetrated hole (610) of the central shunting piece (600) outwardly extended towards two lateral sides for respectively forming the circular path (580) and the circular path (590) extended along the inner side of the outer periphery of the heat dissipater (104) and lead to the heat transfer fluid path (1081), and

the heat transfer fluid path (107) formed between the interior of the support tube (101) and the exterior of the biasedly-sleeved heat transfer fluid path (1081).

25. A heat-dissipating structure having embedded support tube to form internally recycling heat transfer fluid and application apparatus as claimed in claim 1 or claim 12, wherein the electric energy application device assembly (108) is upwardly installed, and the fluid inlet/outlet path is formed through the heat transfer fluid path (1081) composed of the axial central penetrated hole (700) and the annularly-arranged holes (710) and leaded to the electric energy application device assembly, and the heat transfer fluid path (107) formed between the support tube (101) and the heat transfer fluid path (1081) of the electric energy application device assembly.

26. A Heat-dissipating structure having embedded support tube to form internally recycling heat transfer fluid and application apparatus as claimed in claim 1 or claim 12, wherein the locked-on heat dissipation ring (800) is optionally installed at the outer side of the heat dissipater (104), wherein the locked-on heat dissipation ring (800) is made of a material having good heat transferring and radially heat dissipating property.

27. A heat-dissipating structure having embedded support tube to form internally recycling heat transfer fluid and application apparatus as claimed in claim 1 or claim 12, wherein the sleeved-on heat dissipation ring (900) is optionally installed at the outer side of the heat dissipater (104), wherein the sleeved-on heat dissipation ring (900) is made of a material having good heat transferring and radially heat dissipating property.