

What is claimed is:

1. A method for processing data, comprising:

controlling, by a terminal device, a current state of data duplication and transmission function according to first indication information, wherein the first indication information is used for indicating whether the data duplication and transmission function is enabled; and

processing, by the terminal device, each RLC service data unit (SDU) in a first radio link control (RLC) buffer and a second RLC buffer according to the current state of the data duplication and transmission function, wherein the first RLC buffer corresponds to a first RLC entity and the second RLC buffer corresponds to a second RLC entity; wherein the second RLC buffer comprises a second RLC SDU, and the processing, by the terminal device, the each RLC service data unit (SDU) in the first radio link control (RLC) buffer and the second RLC buffer according to the current state of the data duplication and transmission function, comprises:

before the data duplication and transmission function of the second RLC entity is in an off state, transmitting, by the terminal device, a second RLC PDU to a network device or discarding the second RLC PDU if the second RLC SDU has generated the second RLC PDU;

wherein the transmitting, by the terminal device, the second RLC PDU to the network device or discarding the second RLC PDU, comprises:

in a case that the network device has successfully received duplicated data of the second RLC SDU in the first RLC buffer, discarding, by the terminal device, the second RLC PDU; or

in a case that the network device does not successfully receive duplicated data of the second RLC SDU in the first RLC buffer, transmitting, by the terminal device, the second RLC PDU to the network device.

2. The method according to claim 1, wherein the processing, by the terminal device, the each RLC service data unit (SDU) in the first radio link control (RLC) buffer and the second RLC buffer according to the current state of the data duplication and transmission function, comprises:

in a case that the data duplication and transmission function of the second RLC entity is in an off state, discarding each RLC SDU in the second RLC buffer.

3. The method according to any one of claims 1-2, wherein the controlling, by the terminal device, the current state of the data duplication and transmission function according to the first indication information, comprises:

controlling, by the terminal device, to start the data duplication and transmission function if the first indication information indicates enabling the data duplication and transmission function; or

controlling, by the terminal device, to close the data duplication and transmission function if the first indication information indicates disabling the data duplication and transmission function.

4. The method according to any one of claims 1-3, wherein the method further comprises:

receiving, by the terminal device, a MAC control element (CE) sent by a network device, wherein the MAC CE comprises the first indication information.

10 5. The method according to any one of claims 1-4, wherein the method further comprises:

if the data duplication and transmission function is in an on state, duplicating, by a packet data convergence protocol (PDCP) entity of the terminal device, a PDCP packet data unit (PDU) to be transmitted into two units and submitting the two units to the first RLC entity and the second RLC entity respectively; or

15 submitting, by the PDCP entity of the terminal device, the PDCP PDU to be transmitted to the first RLC entity if the data duplication and transmission function is in an off state; or

submitting, by the PDCP entity of the terminal device, a first PDCP PDU to be transmitted to the first RLC entity and submitting a second PDCP PDU to be transmitted to the second RLC entity if the data duplication and transmission function is in an off state, wherein the first PDCP PDU and the second PDCP PDU are different.

6. A device for processing data, comprising:

a controlling module, configured to control a current state of data duplication and transmission function according to first indication information, wherein the first indication information is used for indicating whether the data duplication and transmission function is enabled; and

a processing module, configured to process each RLC service data unit (SDU) in a first radio link control (RLC) buffer and a second RLC buffer according to the current state of the data duplication and transmission function, wherein the first RLC buffer corresponds to a first RLC entity and the second RLC buffer corresponds to a second RLC entity; wherein the second RLC buffer comprises a second RLC SDU, and the processing module is further configured to:

before data duplication and transmission function of the second RLC entity is in an off

state, if the second RLC SDU has generated a second RLC PDU, transmit the second RLC PDU to a network device or discard the second RLC PDU; wherein the processing module is specifically configured to:

discard the second RLC PDU in a case that the network device has successfully received duplicated data of the second RLC SDU in the first RLC buffer; or

transmit the second RLC PDU to the network device if the network device does not successfully receive duplicated data of the second RLC SDU in the first RLC buffer.

7. The device according to claim 6, wherein the processing module is further configured to:

in a case that the data duplication and transmission function of the second RLC entity is in an off state, discard each RLC SDU in the second RLC buffer.

8. The device according to any one of claims 6-7, wherein the controlling module is specifically configured to:

control to start the data duplication and transmission function if the first indication information indicates enabling the data duplication and transmission function; or

control to close the data duplication and transmission function if the first indication information indicates disabling data duplication and transmission function.

9. The device according to any one of claims 6-8, wherein the device further comprises:

a communicating module, configured to receive a MAC control element (CE) sent by a network device, wherein the MAC CE comprises the first indication information.

10. The device according to any one of claims 6-9, wherein the device further comprises:

a submitting module, configured to duplicate a PDCP packet data unit (PDU) to be transmitted into two units in a case that the data duplication and transmission function is in an on state, and submit the two units to the first RLC entity and the second RLC entity respectively; or

in a case that the data duplication and transmission function is in an off state, submitting the PDCP PDU to be transmitted to the first RLC entity; or

in a case that the data duplication and transmission function is in an off state, submitting a first PDCP PDU to be transmitted to the first RLC entity, and submitting a second PDCP PDU to be transmitted to the second RLC entity, wherein the first PDCP PDU and the second PDCP PDU are different.

11. A device for processing data, wherein the device comprises a memory and a processor, the memory is configured to store instructions, and the processor is configured to execute the instructions stored in the memory to implement the method according to any one of claims 1-4.