

Description

1. Field of the Invention

5 The present invention relates to a process for exchanging a dispersing medium of an aliphatic carboxylic acid slurry of terephthalic acid. More specifically, it relates to a process for obtaining an aqueous slurry of terephthalic acid by exchanging, for example, the aliphatic acid, which is the dispersing medium in an aliphatic carboxylic acid slurry of terephthalic acid obtained by an oxidation of p-xylene in an aliphatic carboxylic acid dispersing medium, for water.

2. Description of the Related Art

10 Terephthalic acid is very useful as the starting material for polyester resin, etc., and is usually obtained by an oxidation of p-xylene in an aliphatic carboxylic acid solvent such as acetic acid, and as an aliphatic carboxylic acid slurry from the reaction apparatus. Terephthalic acid is insoluble in solvents such as water, alcohol, ether, chloroform, and acetic acid, and is sublimated without melting by heating to 300°C, and therefore, it is difficult to obtain a high purity terephthalic acid by utilizing conventional methods such as recrystallization or vacuum distillation from an aliphatic carboxylic acid slurry of terephthalic acid discharged from the reaction apparatus.

15 Accordingly, in the purification of terephthalic acid, a method has been employed in which crude crystals of terephthalic acid are separated from an aliphatic carboxylic acid slurry of terephthalic acid obtained from a reaction apparatus, the crude crystals are dispersed in water to obtain an aqueous slurry of terephthalic acid, and the aqueous slurry is hydrogenated by, for example, contact with hydrogen gas, to improve the solubility of the impurities and remove the impurities by dissolution into the solvent. In the steps of this purification method, since crude crystals of terephthalic acid are in the form of a fine powder and have a very low filtration efficiency, it is difficult to use a separation by filtration method, and thus a separation method such as centrifugation is usually adopted.

20 Nevertheless, to effectively separate crude crystals from the aliphatic carboxylic acid slurry of terephthalic acid by a centrifugation device, the centrifugation must be carried out at least two or three times, or more, and further, the crude crystals obtained by centrifugation must be dried to enable a reduction of the terephthalic acid crystals to a powder. Accordingly, a plurality of centrifugation devices, a drying device, and a storage for the particles are required, and therefore, the ratio of equipment cost to production cost becomes very high. Further, a problem arises in that the separation of crystals as described above is very cumbersome. Also, when producing an aqueous slurry by a dispersion of the terephthalic acid obtained as crude crystals in water, a problem arises in that the preparation of the aqueous slurry, such as the stirring of a mixture of the crude crystals and water at a high speed, is very cumbersome.

25 Japanese Unexamined Patent Publication (Kokai) No. 57-53431 discloses a washing process which is primarily characterized by washing crude terephthalic acid in a multi-stage washing column provided with partitioning plates having a plurality of holes arranged therein. This washing entails specifically a process in which terephthalic acid particles are washed when a terephthalic acid slurry in an aqueous mother liquor is introduced into the multi-stage washing column at the top thereof and water is introduced at the bottom thereof to effect a counter current contact therebetween, whereby terephthalic acid particles are sedimented, and the dispersing medium constituting the terephthalic acid slurry and the washing solvent are both the same liquid, i.e., water, although some differences in the purity of both may exist.

30 GB-A-2014985 discloses a process for recovering terephthalic acid from a suspension thereof in a mother liquor containing acetic acid, the process involving bringing the suspension into continuous contact with an ascending flow of hot acetic acid which contains water, and subsequently obtaining the terephthalic acid as a suspension of crystals in acetic acid.

SUMMARY OF THE INVENTION

35 Accordingly, the objects of the present invention are to eliminate the above-mentioned problems of the prior art and to provide a process for obtaining an aqueous slurry of terephthalic acid particles by exchanging an aliphatic carboxylic acid, which is the dispersing medium constituting an aliphatic carboxylic acid slurry of terephthalic acid, for water.

Another object of the present invention is to provide a process by which an aqueous slurry of terephthalic acid can be obtained by exchanging the aliphatic carboxylic acid constituting an aliphatic carboxylic acid slurry of terephthalic acid, by using a multi-stage column, and further, the aliphatic carboxylic acid such as acetic acid constituting the aliphatic carboxylic acid slurry can be recovered at a high concentration.

Other objects and advantages of the present invention will be apparent from the following description.

In accordance with the present invention, there is provided a process for exchanging a dispersing medium of a terephthalic acid slurry, which comprises introducing an aliphatic carboxylic acid slurry of terephthalic acid into a multi-stage column at the upper part thereof and introducing water at the lower part thereof to form an upflowing stream of water at the lower part thereof to form an upflowing stream of water in the multi-stage column, while a sedimentation of terephthalic acid particles is effected, and withdrawing the aqueous aliphatic carboxylic acid solution from the upper part of the multi-stage column and an aqueous slurry of terephthalic acid from the lower part of the column.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will be better understood from the description set forth below with reference to the accompanying drawing of Fig. 1, which schematically illustrates an example of the preparation steps of terephthalic acid including the step of the process for exchanging the dispersing medium of a terephthalic acid slurry according to the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

According to the process for exchanging the dispersing medium of a terephthalic acid slurry of the present invention, by using a multi-stage column, an aliphatic carboxylic acid slurry of terephthalic acid is introduced into the multi-stage column at the upper part thereof and water is introduced at the lower part thereof to form an upflowing stream in the multi-stage column and sedimentate terephthalic acid particles through the solution, whereby an aqueous slurry of terephthalic acid with a low aliphatic carboxylic acid content can be withdrawn from the bottom of the multi-stage column, and an aqueous slurry of terephthalic acid can be prepared easily without a separation of the terephthalic acid particles from the aliphatic carboxylic acid slurry of terephthalic acid.

Therefore, by employing the dispersing medium exchange process of the present invention, terephthalic acid can be handled while dispersed in a liquid, without separation by, for example, centrifugation, to obtain an aqueous slurry of terephthalic acid, and thus it is not necessary to carry out complicated operations such as a separation of terephthalic particles from the aliphatic carboxylic acid slurry followed by a dispersion in water, and accordingly, the amount of equipment required can be greatly reduced.

Further, an aqueous aliphatic carboxylic acid solution can be obtained from the upper part of the multi-stage column, and by removing water from the aqueous aliphatic carboxylic acid solution, the solvent obtained can be circulated as a part of the reaction solvent during the oxidation of p-xylene.

The process for exchanging the dispersing medium of a terephthalic acid slurry of the present invention is described in detail below.

Figure 1 shows an example of the preparation steps for the production of terephthalic acid, including the step of exchanging the dispersing medium of a terephthalic acid slurry of the present invention.

In Fig. 1, p-xylene and an aliphatic carboxylic acid are introduced into a reaction apparatus 1 through a feed pipe 2. The reaction apparatus 1 is filled with catalysts of cobalt, manganese and a bromine compound, a heavy metal catalyst, or a noble catalyst containing oxygen.

Terephthalic acid can be produced in the presence of the above catalysts by bringing the p-xylene into contact with oxygen (usually air). This reaction is usually carried out by setting the reaction temperature to 100°C to 240°C and the reaction pressure to 5 to 60 atm. During the reaction, aldehydes, etc., can be optionally added as a reaction accelerator.

By thus oxidizing the p-xylene, an aliphatic carboxylic acid slurry of terephthalic acid is obtained, and such an aliphatic carboxylic acid slurry of terephthalic acid usually contains 5% to 50% by weight of particulate terephthalic acid, 50% to 95% by weight of aliphatic carboxylic acid, and 15% by weight or less of water.

In the production of terephthalic acid by an oxidation of p-xylene as described above, examples of the aliphatic carboxylic acid usable as the reaction solvent are acetic acid, proionic acid, n-butyric acid, isobutyric acid, n-valeric acid, trimethylacetic acid, caproic acid, and mixtures of these fatty acids with water. These can be used alone or in any combination thereof. Accordingly, the slurry of terephthalic acid to

be used in the dispersing medium exchange process of the present invention is a slurry containing the above aliphatic carboxylic acid as the dispersing medium. The slurry to be used in the present invention can contain other components such as catalyst components, in addition to the above-mentioned aliphatic carboxylic acid. Particularly, since the oxidation reaction of p-xylene is preferably carried out in acetic acid, an acetic acid slurry of terephthalic acid is usually employed in the present invention.

In the present invention, although the aliphatic carboxylic acid slurry of terephthalic acid formed as described above can be directly introduced into the multi-stage column, preferably it is once introduced into a degassing vessel 4, to remove air, etc., contained in the slurry. Also, by thus introducing the slurry into the degassing vessel 4, an advantage is gained in that the amount of the slurry introduced into the multi-stage column can be more easily controlled.

The degassing vessel 4 and the multi-stage column 6 are connected through a pipe 5.

In the present invention, the aliphatic carboxylic acid slurry of terephthalic acid after introduction into the degassing vessel 4, or without introduction therein, is introduced into the upper part of the multi-stage column 6 through the pipe 5, simultaneously with the introduction of water at the lower part of the multi-stage column 6.

The multi-stage column 6 to be used in the present invention basically has the shape of a cylinder having a bottom, and provided at the upper part of the multi-stage column are an aliphatic carboxylic acid slurry introducing inlet 8 for introducing the aliphatic carboxylic acid slurry of terephthalic acid linked to the pipe 5 and an aqueous aliphatic carboxylic acid discharging outlet 9 for dispersing the aqueous aliphatic carboxylic acid solution. Further, at the bottom of the multi-stage column, a water introducing inlet 10 and an aqueous slurry discharging outlet 11 are provided. The aqueous aliphatic carboxylic acid solution discharging outlet 9 is usually provided above the aliphatic carboxylic acid slurry introducing inlet 8 to reduce the amount of terephthalic acid particles in the withdrawn aqueous aliphatic carboxylic acid solution. The aqueous slurry discharging outlet 11 is usually provided below the water introducing inlet 10.

At least one partitioning plate is arranged within the multi-stage column 6, which divides the multi-stage column into at least two vertical stages, so that terephthalic acid particles can be sedimentated from the upper part of the multi-stage column and water can flow from the lower part of the multi-stage column to the upper part thereof. In the present invention, the number of stages in the multi-stage column 6 can be set in accordance with the amount of aliphatic carboxylic acid slurry of terephthalic acid introduced, and the amount of aliphatic carboxylic acid which can be contained in the aqueous slurry of terephthalic acid withdrawn from the lower part of the multi-stage column. For example, when the aliphatic carboxylic acid concentration in the aqueous slurry of terephthalic acid is 10% by weight or less, a multi-stage column having 5 or more stages is usually employed. This partitioning plate allows a control of the falling speed of the terephthalic acid particles or the rising speed of the upflowing stream of water. In the Figure, the multi-stage column 6 is divided into 7 stages by 7 partitioning plates 12a to 12g.

The respective partitioning plates can be set in accordance with the number of stages in the multi-stage column, and the speed of introduction of the aliphatic carboxylic acid slurry of terephthalic acid, but preferably are arranged at intervals of at least 10 cm. If the interval between the partitioning plates is less than 10 cm, the aliphatic carboxylic acid concentration in the aqueous slurry may become undesirably high.

Further, in the present invention, in addition to these partitioning plates, scrapers (scraping blades) 13a to 13g rotating at a low speed can be employed in combination. The scrapers 13a - 13g are linked to a rotating shaft 16 rotated by a rotating means 17 at a speed of, for example, 0.5 to 20 rpm.

The partitioning plates and the scrapers may be provided with a number of fine passing holes through which terephthalic acid particles can pass, to control the speed of sedimentation of the terephthalic acid particles.

In the present invention, an aliphatic carboxylic acid slurry is introduced from the aliphatic carboxylic acid introducing inlet 8 provided at the upper part of the multi-stage column 6 as described above, and water is fed through the water introducing inlet 10 at the lower part of said multi-stage column 6. The water fed from the water introducing inlet 10 forms an upflowing stream inside the multi-stage column 6, and the terephthalic acid particles are sedimentated inside the multi-stage column 6. At this time, aliphatic carboxylic acid is also diffused downward in the multi-stage column 6, but the concentration of aliphatic carboxylic acid is lowered as the acid descends in the multi-stage column, and thus the concentration of aliphatic carboxylic acid at the lower part of the multi-stage column 6 is very low.

More specifically, the terephthalic acid particles have a specific gravity of about 1.5 g/cm³, and are sedimentated naturally by the force of gravity. Particularly, in the present invention, terephthalic acid can be effectively sedimentated by using an aliphatic carboxylic acid slurry of terephthalic acid in which at least 90% by weight of the terephthalic acid particles have particle sizes of from 5 to 600 μ m, preferably from 20 to 300 μ m. Namely, if the aliphatic acid slurry contains a large amount of terephthalic acid particles with

smaller particle sizes, the sedimentation of the terephthalic acid particles will be too slow, and thus the amount of the terephthalic acid particles in the aqueous aliphatic carboxylic acid solution recovered from the upper part of the multi-stage column will be increased. On the other hand, when a large amount of particles with larger particle sizes are contained, the sedimentation speed is too rapid, and thus the aliphatic carboxylic acid will contain sedimentated terephthalic acid particles and the aliphatic carboxylic acid concentration in the obtained aqueous slurry of terephthalic acid may become higher.

In the present invention, the amount of water for forming the upflowing stream of water is desirably about 0.01 to 5-fold relative to the weight of the terephthalic acid particles sedimentated in the multi-stage column. More specifically, since a multi-stage column having a large height/diameter (L/D) ratio is usually employed, it is theoretically possible to form an upflowing stream approximate to the piston flow by the elevation of a small amount of water, and due to this upflow, no aliphatic carboxylic acid should reach the lower part of multi-stage column. In practice, however, a small amount of aliphatic carboxylic acid will reach the lower part of the multi-stage column together with the sedimentated terephthalic acid particles, and therefore, the upflowing stream should contain a certain amount of water to prevent this phenomenon. If the amount of water is too high, however, the aqueous aliphatic carboxylic acid solution recovered from the aqueous aliphatic carboxylic acid solution discharging outlet 9 has a lower concentration, and therefore, the cost, of the operation for removing water when reusing the aqueous aliphatic carboxylic acid solution as the reaction solvent for terephthalic acid will be increased. Accordingly, preferably the weight of the terephthalic acid particles sedimentated in the multi-stage column and the weight of the water for forming the upflowing stream are as specified above.

The flow rate of the upflowing stream of water is desirably 2×10^{-2} m/sec. or lower in the vicinity of the aqueous aliphatic carboxylic acid solution discharging outlet 9, preferably 2×10^{-4} to 5×10^{-3} m/sec. If the flow rate at this portion is too high, a large amount of the terephthalic acid particles is discharged from the aqueous aliphatic carboxylic acid discharging outlet 9. Further, in the process of the present invention, desirably the flow rate in the vicinity of the partitioning plate is 1×10^{-2} m/sec. or lower, preferably 1×10^{-4} or 3×10^{-3} m/sec. The flow rates at the respective portions can be controlled by, for example, varying the number or shape of the partitioning plates.

The sedimentation of the terephthalic acid particles in the multi-stage column 6 having an upflowing stream of water as described allows an aqueous slurry of terephthalic acid to be formed at the lower part of the multi-stage column. The aqueous slurry of terephthalic acid can be withdrawn from the aqueous slurry discharging outlet 11.

According to the dispersing medium exchange process of the present invention, the aliphatic carboxylic acid concentration in the aqueous slurry of terephthalic acid obtained is usually 10% by weight or less, and further, the aliphatic carboxylic acid concentration in the aqueous slurry can be made 1% by weight or less by suitably setting the number of stages in the multi-stage column, and the height of the multi-stage column.

The aqueous slurry of terephthalic acid obtained by the present invention is led to the subsequent step through a pipe 14. For example, the slurry can be introduced into a hydrogenation reaction apparatus for a selective hydrogenation of impurities in the aqueous slurry to improve the solubility of the impurities, followed by a removal thereof by dissolution, whereby a terephthalic acid having a very high purity can be produced.

The water slurry of terephthalic acid obtained by the present invention has a low aliphatic carboxylic acid concentration, and therefore, subsequent operations can be carried out without a specific separation of aliphatic carboxylic acid, and thus the loss of aliphatic carboxylic acid in the dispersing medium exchange is small. Also, even if the aqueous slurry is used as such in a later step, little corrosion of the apparatus used in the later step will occur.

On the other hand, aliphatic carboxylic acid diluted with water which has formed the upflowing stream can be obtained from the aqueous aliphatic carboxylic acid solution discharging outlet 9 at the upper part of the multi-stage column 6. This aqueous aliphatic carboxylic acid solution, after the water is removed therefrom, can be reused as a part of the reaction solvent during the production of terephthalic acid by an oxidation of p-xylene.

According to the dispersing medium exchange process of terephthalic acid slurry of the present invention, an aliphatic carboxylic acid slurry of terephthalic acid is introduced into the multi-stage column at the upper part thereof simultaneously with an introduction of water at the lower part thereof, to form an upflowing stream of water in the multi-stage column and thus effect sedimentation of terephthalic acid particles, whereby an aqueous slurry of terephthalic acid with very low aliphatic carboxylic acid content can be formed at the bottom of the multi-stage column, and by withdrawing this slurry, an aqueous slurry of terephthalic acid can be easily produced from an aliphatic carboxylic acid slurry.

Accordingly, by employing the dispersing medium exchange process of the present invention, without a separation of terephthalic acid powder by, for example, centrifugation, an aqueous slurry of terephthalic acid can be obtained, and thus the usual cumbersome operations and separation devices required for the separation of terephthalic acid particles can be omitted.

Further, according to the present invention, an aqueous slurry of terephthalic acid can be obtained directly from an aliphatic carboxylic acid slurry of terephthalic acid, and therefore, it is not necessary to separate the terephthalic acid particles or disperse the particles in water in the preparation of an aqueous slurry of terephthalic acid.

Also, an aqueous aliphatic carboxylic acid with a low water content can be obtained from the upper part of the multi-stage column, and if the water is removed from the aqueous carboxylic acid solution, the remaining solvent can be circulated as part of the reaction solvent during an oxidation of p-xylene.

EXAMPLES

The present invention will now be further illustrated by, but is by no means limited to, the following Examples.

Example 1

The reaction apparatus 1, degassing vessel 4, and multi-stage column 6 as shown in Fig. 1 were arranged as shown in Fig. 1.

Twenty partitioning plates were arranged at intervals of 20 cm in the multi-stage column, and 20 scrapers were also arranged therein. The scrapers were rotated at a speed of 1 rpm, and a stirring blade was provided at the tip end of the shaft for rotating the scrapers along the inner wall at the lower end of the multi-stage column.

From the pipe 2 of the above reaction apparatus 1 were introduced p-xylene and acetic acid, and terephthalic acid was produced by an air oxidation of p-xylene in an acetic acid solvent in the presence of cobalt acetate, manganese acetate, and tetrabromoethane catalysts.

The reaction conditions at this time were as follows:

Reaction temperature	190 °C
Reaction pressure (gauge)	14 atm.

The acetic acid slurry of terephthalic acid was withdrawn from the reaction apparatus 1 and introduced into the degassing vessel 4, to effect degassing for 5 minutes.

Next, the acetic acid slurry of terephthalic acid was introduced from the degassing vessel 4 into the multi-stage column 6 in an amount of 925 kg per hour, and 766 kg per hour of water was introduced from the lower part of the multi-stage column 6. The flow rate of the upflowing stream of water near the partitioning plates was 7×10^{-4} m/sec.

The temperature of the water and the acetic acid slurry of terephthalic acid was 190 °C. The acetic acid slurry contained 97% by weight of terephthalic acid particles within the particles size range of 20 to 300 μ m. The acetic acid slurry had the composition shown below:

Composition of acetic acid slurry of terephthalic acid	
Terephthalic acid particles	27.6 parts by weight
Acetic acid	67.1 parts by weight
Water	5.3 parts by weight.

While introducing the acetic acid slurry of terephthalic acid and water as described above, an aqueous acetic acid solution was withdrawn in an amount of 713 kg per hour from the aqueous aliphatic carboxylic acid discharge outlet 9 provided at the upper part of the multi-stage column, and an aqueous slurry withdrawn in an amount of 978 kg per hour from the aqueous slurry discharging outlet 11 provided at the lower part. The flow rate of water at the tower top was 6×10^{-3} m/sec.

The compositions of the obtained aqueous acetic acid solution and the aqueous slurry are shown below.

Composition of aqueous acetic acid solution	
Terephthalic acid particles	1.9 parts by weight
Acetic acid	87.0 parts by weight
Water	11.1 parts by weight
Composition of aqueous slurry of terephthalic acid	
Terephthalic acid particles	24.7 parts by weight
Acetic acid	0.03 parts by weight
Water	75.27 parts by weight

As shown above, by employing the dispersing medium exchange process of the present invention, an aqueous slurry of terephthalic acid containing substantially no acetic acid was obtained by an exchange of the dispersing medium constituting the slurry without a separation of terephthalic acid particles from the acetic acid slurry of terephthalic acid. Further, an aqueous acetic acid solution with a low water content was recovered from the upper part of the multi-stage column, and the aqueous acetic acid solution, after the water was removed, was effectively reused as the reaction solvent during the oxidation reaction of p-xylene.

Claims

1. A process for exchanging a dispersing medium of a terephthalic acid slurry, which comprises introducing an aliphatic carboxylic acid slurry of terephthalic acid into a multi-stage column at the upper part thereof and water at the lower part thereof to form an upflowing stream of water in the multi-stage column, while a sedimentation of terephthalic acid particles is effected inside the multi-stage column, and withdrawing an aqueous aliphatic carboxylic acid solution from the upper part of the multi-stage column and an aqueous slurry of terephthalic acid from the lower part of the multi-stage column.
2. A process as claimed in Claim 1, wherein at least 90% by weight of the terephthalic acid particles in the aliphatic carboxylic acid slurry have a particle diameter of from 5 to 600 μm .
3. A process as claimed in Claim 1 or 2, wherein the aliphatic carboxylic slurry of terephthalic acid comprises from 5% to 50% by weight of particulate terephthalic acid, from 50% to 95% by weight of aliphatic carboxylic acid, and 15% by weight or less of water.
4. A process as claimed in any one of Claims 1 to 3, wherein the aliphatic carboxylic acid is at least one of acetic acid, propionic acid, n-butyric acid isobutyric acid, n-valeric acid, trimethylacetic acid and caproic acid.
5. A process as claimed in any one of Claims 1 to 4, wherein the ratio of the weight of upflowing water to the weight of terephthalic acid particles sedimentated in the multi-stage column is from 0.01:1 to 5:1.
6. A process as claimed in any one of Claims 1 to 5, wherein the flow rate of the upflowing stream of water in the upper part of the multi-stage column is 2×10^{-2} m/sec or less.
7. A process as claimed in any one of Claims 1 to 6, wherein the aliphatic carboxylic acid slurry of terephthalic acid is introduced into a degassing vessel prior to entry into the multi-stage column.
8. A process as claimed in any one of Claims 1 to 7, wherein the aqueous slurry of terephthalic acid withdrawn from the lower part of the multi-stage column is led to a subsequent reaction stage.

Revendications

1. Un procédé pour le changement d'un agent de dispersion dans une suspension de l'acide téréphthalique, qui comprend l'introduction d'une suspension d'acide carboxylique aliphatique de l'acide téréphthalique dans une colonne à plusieurs étages, par la partie supérieure de celle-ci, et d'eau par la partie inférieure de celle-ci, afin de former un courant d'eau ascendant dans la colonne à plusieurs étages, tandis qu'il est créé une précipitation de particules d'acide téréphthalique à l'intérieur de la colonne à



Composition of aqueous acetic acid solution	
Terephthalic acid particles	1.9 parts by weight
Acetic acid	87.0 parts by weight
Water	11.1 parts by weight
Composition of aqueous slurry of terephthalic acid	
Terephthalic acid particles	24.7 parts by weight
Acetic acid	0.03 parts by weight
Water	75.27 parts by weight

As shown above, by employing the dispersing medium exchange process of the present invention, an aqueous slurry of terephthalic acid containing substantially no acetic acid was obtained by an exchange of the dispersing medium constituting the slurry without a separation of terephthalic acid particles from the acetic acid slurry of terephthalic acid. Further, an aqueous acetic acid solution with a low water content was recovered from the upper part of the multi-stage column, and the aqueous acetic acid solution, after the water was removed, was effectively reused as the reaction solvent during the oxidation reaction of p-xylene.

Claims

1. A process for exchanging a dispersing medium of a terephthalic acid slurry, which comprises introducing an aliphatic carboxylic acid slurry of terephthalic acid into a multi-stage column at the upper part thereof and water at the lower part thereof to form an upflowing stream of water in the multi-stage column, while a sedimentation of terephthalic acid particles is effected inside the multi-stage column, and withdrawing an aqueous aliphatic carboxylic acid solution from the upper part of the multi-stage column and an aqueous slurry of terephthalic acid from the lower part of the multi-stage column.
2. A process as claimed in Claim 1, wherein at least 90% by weight of the terephthalic acid particles in the aliphatic carboxylic acid slurry have a particle diameter of from 5 to 600 μm .
3. A process as claimed in Claim 1 or 2, wherein the aliphatic carboxylic slurry of terephthalic acid comprises from 5% to 50% by weight of particulate terephthalic acid, from 50% to 95% by weight of aliphatic carboxylic acid, and 15% by weight or less of water.
4. A process as claimed in any one of Claims 1 to 3, wherein the aliphatic carboxylic acid is at least one of acetic acid, propionic acid, n-butyric acid isobutyric acid, n-valeric acid, trimethylacetic acid and caproic acid.
5. A process as claimed in any one of Claims 1 to 4, wherein the ratio of the weight of upflowing water to the weight of terephthalic acid particles sedimentated in the multi-stage column is from 0.01:1 to 5:1.
6. A process as claimed in any one of Claims 1 to 5, wherein the flow rate of the upflowing stream of water in the upper part of the multi-stage column is 2×10^{-2} m/sec or less.
7. A process as claimed in any one of Claims 1 to 6, wherein the aliphatic carboxylic acid slurry of terephthalic acid is introduced into a degassing vessel prior to entry into the multi-stage column.
8. A process as claimed in any one of Claims 1 to 7, wherein the aqueous slurry of terephthalic acid withdrawn from the lower part of the multi-stage column is led to a subsequent reaction stage.

Revendications

1. Un procédé pour le changement d'un agent de dispersion dans une suspension de l'acide téréphtalique, qui comprend l'introduction d'une suspension d'acide carboxylique aliphatique de l'acide téréphtalique dans une colonne à plusieurs étages, par la partie supérieure de celle-ci, et d'eau par la partie inférieure de celle-ci, afin de former un courant d'eau ascendant dans la colonne à plusieurs étages, tandis qu'il est créé une précipitation de particules d'acide téréphtalique à l'intérieur de la colonne à



plusieurs étages, et le prélèvement de la solution aqueuse d'acide carboxylique aliphatique par la partie supérieure de la colonne à plusieurs étages et d'une suspension aqueuse de l'acide téréphtalique par la partie inférieure de la colonne à plusieurs étages.

2. Un procédé suivant la revendication 1, dans lequel au moins 90% en poids des particules d'acide téréphtalique dans la suspension d'acide carboxylique aliphatique ont un diamètre de particule de 5 à 600 μm .
3. Un procédé suivant la revendication 1 ou 2, dans lequel la suspension carboxylique aliphatique de l'acide téréphtalique comprend de 5% à 50% en poids de particules d'acide téréphtalique, de 50% à 95% en poids d'acide carboxylique aliphatique et 15% en poids ou moins d'eau.
4. Un procédé suivant l'une ou l'autre des revendications 1 à 3, dans lequel l'acide carboxylique aliphatique est au moins l'un parmi l'acide acétique, l'acide propionique, l'acide n-butyrique, l'acide isobutyrique, l'acide n-valérique, l'acide triméthylacétique et l'acide caproïque.
5. Un procédé suivant l'une ou l'autre des revendications 1 à 4, dans lequel le rapport entre le poids de l'eau ascendante et le poids des particules d'acide téréphtalique précipitées dans la colonne à plusieurs étages est de 0,01:1 à 5:1.
6. Un procédé suivant l'une ou l'autre des revendications 1 à 5, dans lequel le débit du courant d'eau ascendant dans la partie supérieure de la colonne à plusieurs étages est de 2×10^{-2} m/sec. ou moins.
7. Un procédé suivant l'une ou l'autre des revendications 1 à 6, dans lequel la suspension d'acide carboxylique aliphatique de l'acide téréphtalique est introduite dans un récipient de dégazage avant d'entrer dans la colonne à plusieurs étages.
8. Un procédé suivant l'une ou l'autre des revendications 1 à 7, dans lequel la suspension aqueuse de l'acide téréphtalique prélevée à la partie inférieure de la colonne à plusieurs étages est amenée à un étage de réaction ultérieur.

Patentansprüche

1. Verfahren zum Austausch eines Dispersionsmediums einer Terephthalsäureaufschäumung, das das Einführen einer aliphatischen Carbonsäureaufschäumung von Terephthalsäure in eine mehrstufige Säule an ihrem oberen Teil und Wasser an ihrem unteren Teil, um einen aufwärtsfließenden Wasserstrom in der mehrstufigen Säule zu bilden, wobei die Sedimentation der Terephthalsäureteilchen innerhalb der mehrstufigen Säule durchgeführt wird, und das Abziehen der wässrigen aliphatischen Carbonsäurelösung vom oberen Teil der mehrstufigen Säule und der wässrigen Aufschäumung von Terephthalsäure vom unteren Teil der mehrstufigen Säule umfaßt.
2. Verfahren nach Anspruch 1, worin mindestens 90 Gew.-% der Terephthalsäureteilchen in der aliphatischen Carbonsäureaufschäumung einen Teilchendurchmesser von 5 bis 600 μm aufweisen.
3. Verfahren nach Anspruch 1 oder 2, worin die aliphatische Carbonsäureaufschäumung von Terephthalsäure von 5 bis 50 Gew.-% teilchenförmige Terephthalsäure, von 50 bis 95 Gew.-% aliphatische Carbonsäure und 15 Gew.-% oder weniger an Wasser umfaßt.
4. Verfahren nach einem der Ansprüche 1 bis 3, worin die aliphatische Carbonsäure mindestens eine Verbindung aus Essigsäure, Propionsäure, n-Buttersäure, Isobuttersäure, n-Valeriansäure, Trimethyl-essigsäure und Capronsäure ist.
5. Verfahren nach einem der Ansprüche 1 bis 4, worin das Verhältnis des Gewichtes des nach oben strömenden Wassers zum Gewicht der Terephthalsäureteilchen, die in der mehrstufigen Säule sedimentiert sind, von 0,01:1 bis 5:1 beträgt.
6. Verfahren nach einem der Ansprüche 1 bis 5, worin die Strömungsgeschwindigkeit des nach oben fließenden Wasserstroms im oberen Teil der mehrstufigen Säule 2×10^{-2} m/s oder weniger beträgt.



7. Verfahren nach einem der Ansprüche 1 bis 6, worin die aliphatische Carbonsäureaufschäumung von Terephthalsäure vor dem Eintritt in die mehrstufige Säule in ein Entgasungsgefäß eingeführt wird.
8. Verfahren nach einem der Ansprüche 1 bis 7, worin die wässrige Aufschäumung von Terephthalsäure, die vom unteren Teil der mehrstufigen Säule abgezogen wird, einer nachfolgenden Reaktionsstufe zugeführt wird.

5

10

15

20

25

30

35

40

45

50

55

