

TORIC OPHTHALMIC LENS

[Field]

[0001] The embodiments discussed herein pertain to a toric ophthalmic lens for correcting astigmatism.

[Background]

[0002] As examples of an ophthalmic lens for correcting astigmatism, eyeglasses, contact lenses, intraocular lenses and the like are named. These ophthalmic lenses have an optical surface referred to as a toric surface. It is noted that "toric surface" is a surface shape of a lens where radii of curvature of at least two meridians differ from each other as in the case of a side surface of a rugby ball or a doughnut. Accordingly, a lens having such a toric surface is referred to as a toric lens (circular annular lens).

[0003] Due to a toric surface, the refractivity of a lens differs between directions orthogonal to each other which are set on the toric surface. Astigmatism can be corrected by making use of the difference in refractivity. In general, this difference in refractivity is referred to as cylindrical refractivity. On a toric surface, a meridian in a direction where refractivity is large is referred to as a steep meridian, and a meridian in a direction where refractivity is small is referred to as a flat meridian. Further, an average value of refractivities on these two meridians is

referred to as spherical equivalent power (or simply referred to as spherical power). Usually, in an ophthalmic lens for correcting astigmatism, as indexes indicative of optical performances, equivalent spherical power and cylindrical refractivity are used. Conventionally, there has been proposed a lens where, with respect to optical surfaces disposed in front of and behind the lens, a function of correcting astigmatic abnormality in vision is imparted to one optical surface, and a function of correcting spherical aberration is imparted to the other optical surface (patent literature 1).

[Citation List]

[Patent Literature]

[0004]

[PTL 1] JP-A-2009-544059

[Summary]

[Technical Problem]

[0005] Recently, along with the development of measuring instruments in ophthalmology, cornea astigmatism in an eyeball can be accurately measured. For example, in an anterior eye part shape analyzer such as Pentacam (registered trademark) (made by OCULUS) or TMS-5 (made by TOMEY CORPORATION), a shape of cornea can be measured, and the distribution of refractive power from the center to the periphery of the cornea can be measured. The substantially same measurement

can be also applied to an eye having astigmatism so that amounts of astigmatism ranging from the center to the periphery of a cornea can be also measured.

[0006] However, in the conventional ophthalmic lens for correcting astigmatism, only the configuration where one optical surface of the lens is used as a toric surface is disclosed, and a control of cylindrical refractivity on the toric surface is not taken into consideration. Accordingly, even when amounts of astigmatism ranging from the center to the periphery of a cornea can be grasped by the above-mentioned measurement, astigmatism components cannot be properly removed over the whole cornea in the conventional ophthalmic lens for correcting astigmatism whereby the proper improvement of visual functions is limited.

[0007] The technique of this disclosure is made in view of the above-mentioned circumstances, and it is an object of this disclosure to realize a toric ophthalmic lens capable of more properly correcting amounts of astigmatism of a cornea.

[Solution to Problem]

[0008] According to an embodiment, it is provided A toric ophthalmic lens wherein refractivity of the lens differs between a first direction on a plane perpendicular to an optical axis of the lens and a second direction which differs from the first direction on the plane, wherein refractivity difference which is the

difference between the refractivity in the first direction and the refractivity in the second direction varies depending on a position of the lens in a radial direction. Further, according to the toric ophthalmic lens of the present embodiment, the refractivity difference varies so as to attenuate a variation in refractivity with respect to a radial direction or a circumferential direction in a cornea of an eyeball in which the lens is mounted. With such a configuration, by controlling a amounts of astigmatism in the center portion of the lens and a amounts of astigmatism in the peripheral portion of the lens respectively, it is possible to provide a toric ophthalmic lens which can more properly perform correction of astigmatism compared to a prior art.

[0009] In addition, the toric ophthalmic lens according to the present disclosure is the toric ophthalmic lens wherein with respect to first refractivity in a paraxial portion of the lens in the first direction, second refractivity in a peripheral portion of the lens in the first direction, third refractivity in the paraxial portion of the lens in the second direction, and fourth refractivity in the peripheral portion of the lens in the second direction, the difference between the first refractivity and the third refractivity is refractivity difference in the paraxial portion of the lens and the difference between

the second refractivity and the fourth refractivity is refractivity difference in the peripheral portion of the lens, and the refractivity difference in the paraxial portion of the lens and the refractivity difference in the peripheral portion of the lens are controlled to be different from each other. Alternatively, there is provided the toric ophthalmic lens, wherein amounts of first spherical aberration in the first direction and amounts of second spherical aberration in the second direction are controlled individually.

[Advantageous Effects of Invention]

[0010] According to the technique of this disclosure, it is possible to realize a toric ophthalmic lens capable of more properly correcting amounts of astigmatism of an eyeball.

[Brief Description of Drawings]

[0011]

FIG. 1 is a schematic diagram illustrating spherical aberration of a lens;

FIG. 2A and FIG. 2B are schematic diagrams illustrating spherical aberration of a toric lens;

FIG. 3 is a table illustrating one example of a simulation result of a toric intraocular lens according to this embodiment and a conventional toric intraocular lens;

FIG. 4 is a diagram illustrating the schematic

constitution of a schematic eye prepared for evaluating the toric intraocular lens;

FIG. 5 is a table illustrating one example of the evaluation result of the schematic eye illustrated in FIG. 4;

FIGS. 6A to 6C are graphs illustrating one example of a measurement result of an MTF of the toric intraocular lens according to this embodiment; and

FIGS. 7A to 7C are graphs illustrating one example of a measurement result of an MTF of a conventional toric intraocular lens.

[Description of Embodiments]

[0012] Hereinafter, an embodiment of the present invention is described with reference to drawings. Although a toric intraocular lens will be described in the description made hereinafter, the present invention is not limited to the intraocular lens and is also applicable to various ophthalmic lenses including contact lenses.

[0013] Firstly, spherical aberration which is one of Seidel's five aberrations is described with reference to FIG. 1. When spherical aberration occurs, power difference is generated between a center portion (paraxial portion) and a peripheral portion of a rotation-symmetry-type lens. Spherical aberration is a phenomenon where a light which passes through the center portion of the lens and a light which passes

through the peripheral portion of the lens do not converge on the same focal point.

[0014] As illustrated in FIG. 1, assuming a rear principal point of a lens L1 as H', a paraxial focal point as F, a focal length as f, and a distance from the rear principal point H' to a focal point of a peripheral light beam (a light which passes through a peripheral portion of the lens) as f', paraxial refractivity of the lens L1 P is expressed by the following formula (1) using the focal length f. Although the description is made with respect to the case where air is present in front of and behind the lens and a refractive index is set to 1, the present invention is not limited to such a case.

$$P = \frac{1}{f} \quad (1)$$

[0015] In this embodiment, the case where spherical aberration is generated means the case where the position of a focal point F' of a peripheral light beam and the position of the paraxial focal point F differ from each other, and refractivity P' of a peripheral portion of the lens L1 is expressed by the following formula (2) using the distance f'.

$$P' = \frac{1}{f'} \quad (2)$$

[0016] In FIG. 1, the focal point F' of the peripheral light beam is closer to the rear principal point H' than the paraxial focal point F is and hence, the following formula (3) is established. That is, when spherical aberration is generated in the lens $L1$, difference is generated in refractivity between the center portion and the peripheral portion of the lens $L1$.

$$P < P' \quad (3)$$

[0017] Next, spherical aberration generated in a toric lens $L2$ is described with reference to FIG. 2A and FIG. 2B. For the sake of convenience of description, the description is made by assuming that an optical axis of the toric lens $L2$ is taken on a Z axis, an XY plane orthogonal to the optical axis is set and an X axis and a Y axis are orthogonal to each other. However, the X axis and the Y axis may not be always orthogonal to each other, and may be configured such that the X axis extends in a first direction on the XY plane and the Y axis extends in a second direction which differs from the first direction. FIG. 2A and FIG. 2B illustrate states where light beams in the X axis direction and Y axis direction of the toric lens $L2$ converge respectively. As illustrated in FIG. 2A, it is assumed that a rear principal point of the toric lens $L2$ is H' , a paraxial focal point in the X axis direction of the lens is F_x , a focal length in the X axis direction of

the lens is f_x , and a distance from a rear principal point H' to a focal point of a peripheral light beam in the X axis direction of the lens is f_x' . In the same manner, as illustrated in FIG. 2B, F_y , f_y , f_y' are respectively set also with respect to the Y axis direction of the lens.

[0018] In this case, as described with reference to FIG. 1, the following formulas (4) to (7) are established.

$$P_x = \frac{1}{f_x} \quad (4)$$

$$P_x' = \frac{1}{f_x'} = \frac{1}{f_x + SA_x} \quad (5)$$

$$P_y = \frac{1}{f_y} \quad (6)$$

$$P_y' = \frac{1}{f_y'} = \frac{1}{f_y + SA_y} \quad (7)$$

[0019] Here, SA_x , SA_y indicate a distance of amounts of spherical aberration in the X axis direction of the lens and a distance of amounts of spherical aberration in the Y axis direction of the lens respectively. For example, SA_x , SA_y in the toric lens L2 illustrated in FIG. 2A and FIG. 2B take negative values.

[0020] Cylindrical refractivity P_c in a paraxial portion of the toric lens L2 and cylindrical refractivity P_c' in a peripheral portion of the toric lens L2 are expressed by the following formulas (8) and (9). Both cylindrical refractivities P_c , P_c' correspond to the difference between refractivity in the first direction and refractivity in the second direction. Further, P_x , P_x' , P_y and P_y' respectively correspond to the first refractivity, second refractivity, third refractivity and fourth refractivity.

$$P_c = P_x - P_y \quad (8)$$

$$P_c' = P_x' - P_y' \quad (9)$$

[0021] In this embodiment, for the purpose of alleviating astigmatism of a cornea in the radial direction or in the circumferential direction by measuring a shape of an eyeball, a toric intraocular lens is manufactured by determining P_c and P_c' on a lens side such that cylindrical refractivities of a paraxial portion and a peripheral portion of an eye into which the intraocular lens is inserted cancel each other in the formulas (8) and (9). Alternatively, a toric intraocular lens is manufactured by individually determining S_{Ax} , S_{Ay} such that cylindrical refractivities of a paraxial portion and a peripheral

portion of an eye into which the intraocular lens is inserted cancel each other in the formulas (5) and (7). Accordingly, not only amounts of astigmatism in the center portion of the lens but also amounts of astigmatism in the peripheral portion of the lens can be controlled, and hence, it is possible to provide a lens having a more favorable astigmatism correcting function compared to a conventional toric intraocular lens. The toric intraocular lens according to the present invention is not limited to the configuration where the difference in refractivity differs in two stages between a paraxial portion and a peripheral portion, and the toric intraocular lens may be configured such that the difference in refractivity continuously varies in a stepless manner from the center to the periphery of the lens.

[0022] Next, in this embodiment, with reference to FIG. 3, the description is made with respect to a simulation result on Landolt ring images acquired by a toric intraocular lens when the toric intraocular lens is designed using the formulas (8) and (9). FIG. 3 illustrates Landolt ring images in so-called best focusing where a conventional toric lens and a toric lens according to this embodiment are applied to an astigmatic eye under a predetermined condition as intraocular lenses, Landolt ring images acquired when an image plane is moved away from the lens by 0.04 mm

(+) in the simulation, and Landolt ring images when the image plane is made to approach the lens by 0.04 mm (-).

[0023] As can be understood from the Landolt rings in best focusing illustrated in FIG. 3, in the toric intraocular lens according to this embodiment, astigmatism is favorably reduced so that a clear Landolt ring image is acquired. On the other hand, in the conventional toric intraocular lens, although a Landolt ring image is confirmed to an extent that the image is recognizable, so-called blurring is generated around the Landolt ring.

[0024] Further, the difference in Landolt ring image appears also when an image plane is moved so that the image is defocused. As illustrated in FIG. 3, in the toric intraocular lens according to this embodiment, even when an image plane is displaced from the position for best focusing, blurring having a rotation symmetrical shape is generated. That is, it is safe to say that astigmatism is substantially completely eliminated. On the other hand, in the conventional toric intraocular lens, blurring extends in a longitudinal direction (vertical direction on a paper on which FIG. 3 is drawn) (image plane: +0.04 mm) or extends in a lateral direction (left-and-right direction on the paper on which FIG. 3 is drawn) (image plane: -0.04 mm) and, hence, it is understood that astigmatism is not completely eliminated. From the

above, it is safe to say that the toric intraocular lens according to this embodiment can acquire more effective astigmatism correction effect compared to the prior art.

[0025] Next, the description is made on an evaluation result with respect to the case where an astigmatism cornea lens which differs in amounts of astigmatism between a center portion and a peripheral portion of the lens is manufactured. FIG. 4 illustrates the schematic configuration of a schematic eye used for the evaluation. In the schematic eye illustrated in FIG. 4, an astigmatism cornea lens L3 is suitably rotatable about an optical axis. Accordingly, it is possible to make an astigmatism axis of the astigmatism cornea lens L3 and an astigmatism axis of a toric intraocular lens L4 agree with each other. In FIG. 4, the astigmatism cornea lens L3 is formed of a biconvex lens. However, the astigmatism cornea lens L3 may be a meniscus lens or a biconcave lens.

[0026] In the schematic eye illustrated in FIG. 4, the toric intraocular lens L4 is arranged in water by estimating the case where the toric intraocular lens L4 is disposed inside the eye. However, the schematic eye may be configured such that the toric intraocular lens L4 is arranged in air. As indices to be observed with respect to the schematic eye illustrated in FIG. 4, Landolt rings described on a visual acuity chart having a length of 3 m are used. An index to be imaged

is an optotype of 1.0 vision. A filter which allows light of 546 nm to pass therethrough is mounted on a halogen lamp which forms a light source, and light which passes through the filter is irradiated to the visual acuity chart from a back side of the visual acuity chart. A camera 10 can move back-and-forth in a direction with respect to an optical axis of the toric intraocular lens L4 for focusing. As illustrated in FIG. 4, the toric intraocular lens L4 is positioned inside an approximately rectangular parallelepiped casing 100 where both surfaces of the casing 100 are formed of planar glasses 101, 101. As described previously, the inside of the casing 100 is filled with water, and a stop S is mounted on an astigmatism cornea lens L3 side of the toric intraocular lens L4.

[0027] FIG. 5 illustrates a result obtained by imaging Landolt rings which are indexes by a camera when the schematic eye illustrated in FIG. 4 is used. As illustrated in FIG. 5, in the same manner as the simulation result illustrated in FIG. 3, in the toric intraocular lens L4 of this embodiment, Landolt rings are clearly imaged in best focusing. Further, also with respect to images which are intentionally defocused by moving the camera 10 in an optical axis direction of the toric intraocular lens L4, blurring occurs in rotation symmetry. Accordingly, it is understood that astigmatism is favorably reduced. On the other hand,

in the conventional toric intraocular lens, although Landolt rings are recognized in best focusing, images are remarkably degraded when the images are intentionally defocused. Accordingly, it is understood that astigmatism is not sufficiently reduced.

[0028] FIGS. 6A to 6C illustrate a result obtained by measuring MTF (Modulation Transfer Function) of the toric intraocular lens of this embodiment using the configuration of the schematic eye illustrated in FIG. 5. In the drawings, spatial frequency indicative of a distance of stripes of a stripe pattern used as an object to be imaged is taken on an axis of abscissas, and a value of MTF of an image of the stripe pattern focused on a light receiving surface of a camera by the toric intraocular lens is illustrated on an axis of ordinates. A solid line indicates numerical values in a sagittal (radiation) direction of the toric intraocular lens (0 degree direction in this case), and a broken line indicates numerical values in a meridional (concentric) direction of the toric intraocular lens (90 degree direction in this case). As illustrated in FIGS. 6A to 6C, in the case of the schematic eye into which the toric intraocular lens of this embodiment is inserted, it is understood that MTF exhibits favorable values both in the 0 degree direction and in the 90 degree direction in best focusing. Further, even in

defocusing, although values of MTF are lowered, MTF exhibits substantially the same change both in the 0 degree direction and in the 90 degree direction, and hence, it is understood that astigmatism is substantially not generated.

[0029] Next, FIGS. 7A to 7C illustrate a result obtained by measuring MTF of a conventional toric intraocular lens using the configuration of the schematic eye illustrated in FIG. 5. As illustrated in FIGS. 7A to 7C, in the conventional toric intraocular lens, MTF at spatial frequency of 100 lines/mm is 0.2 or more in best focusing, and hence, it is considered that the schematic eye can see the vision of 1.0. However, as can be understood from FIGS. 6A to 6C, MTF exhibits low values compared to the toric intraocular lens of this embodiment. Further, as illustrated in FIGS. 7A to 7C, in the conventional toric intraocular lens, MTF exhibits different changes in the 0 degree direction and in the 90 degree direction even at the time of defocusing. Accordingly, it is safe to say that astigmatism still remains in the conventional toric intraocular lens. As has been set forth above, with the use of the toric intraocular lens which is designed in the above-mentioned manner by taking into account not only amounts of astigmatism at a center portion of the lens but also amounts of astigmatism at a peripheral portion of the lens in accordance with this embodiment,

the correction of astigmatism can be performed more favorably compared to the prior art.

[Reference Signs List]

[0030]

- L1 lens
- L2 toric lens
- L3 astigmatism cornea lens
- L4 toric intraocular lens

CLAIMS

What is claimed is:

1. A toric ophthalmic lens wherein refractivity of the lens differs between a first direction on a plane perpendicular to an optical axis of the lens and a second direction which differs from the first direction on the plane, wherein

refractivity difference which is the difference between the refractivity in the first direction and the refractivity in the second direction varies depending on a position of the lens in a radial direction.

2. The toric ophthalmic lens according to claim 1, wherein the refractivity difference is controlled based on a measurement of an eyeball in which the lens is mounted to vary so as to attenuate a variation in refractivity with respect to a radial direction or a circumferential direction in a cornea of the eyeball.

3. The toric ophthalmic lens according to claim 1 or claim 2, wherein with respect to first refractivity in a paraxial portion of the lens in the first direction, second refractivity in a peripheral portion of the lens in the first direction, third refractivity in the paraxial portion of the lens in the second direction, and fourth refractivity in the peripheral portion of

the lens in the second direction, the difference between the first refractivity and the third refractivity is refractivity difference in the paraxial portion of the lens and the difference between the second refractivity and the fourth refractivity is refractivity difference in the peripheral portion of the lens, and the refractivity difference in the paraxial portion of the lens and the refractivity difference in the peripheral portion of the lens are controlled to be different from each other.

4. The toric ophthalmic lens according to any one of claims 1 to 3, wherein amounts of first spherical aberration in the first direction and amounts of second spherical aberration in the second direction are controlled individually.

5. A toric ophthalmic lens wherein refractivity of the lens differs between a first direction on a plane perpendicular to an optical axis of the lens and a second direction which differs from the first direction on the plane, wherein the following formulas (1) to (6) are established,

$$P_1 = \frac{1}{f_1} \quad (1)$$

$$P_1' = \frac{1}{f_1'} = \frac{1}{f_1 + SA_1} \quad (2)$$

$$P_2 = \frac{1}{f_2} \quad (3)$$

$$P_2' = \frac{1}{f_2'} = \frac{1}{f_2 + SA_2} \quad (4)$$

$$P_C = P_1 - P_2 \quad (5)$$

$$P_C' = P_1' - P_2' \quad (6)$$

wherein P_1 is first refractivity in a paraxial portion of the lens in the first direction, P_1' is second refractivity in a peripheral portion of the lens in the first direction, P_2 is third refractivity in the paraxial portion of the lens in the second direction, P_2' is fourth refractivity in the peripheral portion of the lens in the second direction, f_1 is a focal length in the first direction of the lens, SA_1 is a distance of amounts of spherical aberration in the first direction of the lens, f_2 is a focal length in the second direction of the lens, SA_2 is a distance of amounts of spherical aberration in the second direction of the lens, and

P_C and P_C' are determined based on a measurement of an eyeball in which the lens is mounted so as to cancel

a refractivity in the paraxial portion of the eyeball and a refractivity in the peripheral portion of the eyeball, respectively.