

Description

The invention relates to a connector intended for attachment to the end of a cable consisting of one or more insulated conductors enclosed by a jacket, said connector comprising two housing parts which in the assembled state together define a passage having — viewed from the insertion end — a first section designed to take the jacketed end of the cable, and a second section situated further in to take the insulated conductors projecting from the jacket, both housing parts being provided at the first section with first strain relief elements acting on the cable jacket in the assembled state, and being provided on the second section with second strain relief elements acting on the insulated conductors, and one of the housing parts is provided at the second section with a pierce contact for each conductor, which pierce contact can move from a position in which the insulated conductors can be introduced unimpeded into the second section of the passage to a position in which the pierce contact is at least partially pierced through the conductor.

Such a connector is known from US patent 3,998,514. Each of the housing parts is provided with first strain relief elements in the form of ribs which in the assembled state of the connector are pressed into the cable jacket, locally deform the cable jacket and thereby tightly grip the cable jacket. This releases the strain on the cable jacket. Furthermore this prior art connector is provided with second strain relief elements, also embodied as a ridge which is pressed into the inner bend of a curved section of the insulated conductor. During assembly, each of the pierce contacts is pushed in in such a way that the conductor in question is at least partially pierced through by the pierce contact.

A disadvantage of the second strain relief elements used in this prior art connector is that all the insulated conductors are pressed by a relatively sharp ridge into a curved passageway, whereas simultaneously the jacket is gripped by the first strain relief means. This results in heavy deformation of the cable and of the individual insulated conductors. Furthermore because of the meandering passage the actual conductors are subjected to a certain strain in longitudinal direction which is considered undesirable.

The object of the invention is now to improve this type of connector in such a way that for each of the individually insulated conductors a further strain relief is provided acting to grip each insulated conductor firmly without imposing a strain on the actual conductor in longitudinal direction thereof.

This object is achieved with a connector of the type referred to in the preamble by the second strain relief elements embodied as cone-shaped teeth which project from the wall of the one housing part into the second section of said passage, at right angles to the conductors at

least in the cross sectional direction, and which in the assembled state of the connector extend out to the passage wall of the other housing part in such a way that in the assembled state in the said second section of the passage each of the individual insulated conductors is pressed in between the sides of two adjacent teeth, the wall part of the one housing part therebetween and the underlying wall part of the second housing part resulting into a firm grip on the insulation of the conductors in order to form a strain relief for each of the insulated conductors.

According to a preferred embodiment of the invention, the connector is characterised in that the length of the abovementioned teeth from the passage wall in question is greater than the corresponding cross section dimension of the second passage section, and apertures are provided in the wall of the other housing part which are of sufficient depth to take the ends of the teeth when the connector is in the assembled state. The dimensioning of the teeth is preferably chosen in such a way that the clamping action on the insulation of the conductors in question does not actually begin until the ends of the teeth go into the above-mentioned apertures in the wall of the other housing part. So individual apertures are first formed for each of the insulated conductors before the clamping action on the conductors begins, and jamming of any insulation part between the teeth ends and the opposite passage wall is therefore avoided.

It is preferable to design the projecting teeth as conical bodies of revolution, which ensures that no cutting into the insulation of the conductors occurs, but at most a deformation of it. Moreover, conically shaped teeth in an injection moulding process are advantageous from the point of view of shaping the moulds and detaching the particular housing part from the used mould.

According to a further preferred embodiment of the invention, the above-mentioned apertures in the other housing part are designed as blind bores, running from the outside wall of the housing part up to a very short distance from the second passage section, the thickness of the partition between the end of each blind bore and the second passage section being small enough to permit it to be pierced through by the projecting teeth during assembly of the connector.

This means that the wall of the second passage section is smooth and continuous during the introduction of the insulated conductors, so that this introduction can take place easily without obstructions.

The invention will be discussed in greater detail below with reference to the attached drawings.

Fig. 1 shows the two housing parts of the connector according to the invention and indicates schematically the way in which these housing parts must fit into each other.

Fig. 2 shows an assembled connector according to the invention.

Fig. 3 shows a cross section through a connector according to the invention.

Fig. 4 indicates schematically the way in which a connector according to the invention can be fitted to the end of a multicore cable.

Fig. 1 shows schematically the two housing parts of the connector according to the invention: the base part 10 and the lid part 20. The base part 10 consists in general of a rectangular block of suitable material in which - again seen generally - there is a recess which is bounded by the upright walls 11 and 12 and by the bottom 13. As can be seen in Fig. 1, there is no further wall on the left side, while on the right side in fig. 1 there is a relatively thick wall part in which a number of parallel apertures are provided, one of which is indicated by 14. These apertures can either be designed as blind apertures which do not run through completely to the right side of the base part, or they can also be designed as through-running passages. These apertures 14 are intended to take the individual insulated conductors of a jacketed cable. For better guiding of these conductors during the insertion, and for better positioning of them, provision is made immediately in front of the apertures 14 for a number of guide ribs, one of which is indicated by 15.

In the relatively wide wall section at the right end of the base part 10, provision is made for elongated apertures, in each of which a pierce contact is placed. One of these pierce contacts is indicated by 16 in the figure. For better guidance of these pierce contacts, upright partitions 17 are placed between the contacts. In Fig. 1, the contacts are shown in an upright position, in such a way that the piercing points on the underside of these pierce contacts 16 do not project into the corresponding apertures 14.

Disposed in the side walls 11 and 12 are grooves 18 and 19 running in the longitudinal direction, and the top part of the walls 11 and 12 is bevelled above these grooves 18 and 19.

The lid part 20 is provided, in the manner shown in Fig. 1, on the opposite longitudinal side walls with projecting ribs 21 and 22, the shape of which corresponds to that of the grooves 18 and 19. It will be clear from the figure that the lid part 20 on the top side can be pressed into the base part 10, in which case the bevelled edges 21 and 22 slide along the top bevelled parts of the walls 11 and 12 and snap into the grooves 18 and 19.

When the lid part 20 is joined to the base part 10, the two define in the left part of the assembled connector a passage to take the jacketed part of a cable. This jacketed part is gripped by strain relief elements consisting of a rib 23 on the underside of the lid 20 pointing towards a cavity 24 provided in the bottom 13 of the base part 10. This cavity 24 can consist of a blind cavity, in which case the base part 10 therefore has a closed underside, but it can also consist of a through-running passage, as shown schematically in Fig. 3. From Fig. 3 one

can also see the way in which the jacket of the cable is gripped on the one side by the rib 23 of the lid 20 and, as a result, is partially deformed on the one side, while it is pushed down locally on the other side into the aperture 24. This provides a release of the strain on the cable jacket of the cable 30.

The lid part 20 is also provided with means for releasing the strain on the individual insulated conductors of the cable, in the form of a series of projecting teeth, one of which is specifically indicated by 25. These teeth 25 are positioned so that they are aligned with the ribs 15, in other words, positioned in such a way that the individual insulated conductors of the cable 30 which have to be inserted into the apertures 14 are between these teeth when the connector is in the assembled state. The length of these teeth 25 can be selected in such a way that when the connector is in the assembled state they end in a stub on or near the bottom wall 13 of the base part 10 of the connector. Such a design with stub teeth can, however, be used only if the individual insulated conductors are physically separated from one another at least where these teeth are located and, on the other hand, if stub teeth are used, one runs the risk that, during assembly of the connector, part of the insulation of one or more of the conductors in one way or another will become jammed between the underside of these teeth and the bottom 13 of the base part 10, which makes assembly of the connector difficult or impossible.

It is therefore preferable to have an embodiment in which the teeth 25 are longer than the distance between the underside of the lid part 20 and the top side of the bottom 13 of the base part 10 in the assembled state, said teeth in the assembled state projecting into the apertures 26 in the bottom 13 of the base part 10. In Fig. 1 only one of these apertures is indicated by the reference figure 26. Such an embodiment of the teeth has, on the one hand, the advantage that no clamping action whatsoever is exerted on the individual conductors at the time when the bottom tooth point penetrates into the corresponding aperture 26, so that good guidance of the teeth between the individual conductors, and thus good positioning of the conductors, is ensured while, on the other hand, it is possible to use these teeth in insulated conductors which are still connected to each other by means of thin material bridges, such as is the case, for example, with various types of flat cables. In that case the teeth must be designed in such a way that they are capable of penetrating these thin material bridges during assembly of the connector.

The lid part 20 will have to have a certain rigidity, on the one hand, in order to ensure that during pressing down of the lid part 20 into the base part 10 no inadmissible deformations do occur and, on the other hand, in the pressed-down state 20 the strain relief elements must perform their function with equal effect over the entire width of the connector without the lid

bulging out as a result of the counterpressure exerted by the cable jacket or by the individual conductors and the effect of the strain relief element in the middle of the connector being considerably less than near the side edges of the connector. In order to prevent this, the lid is profiled in cross section in such a way that sufficient rigidity is obtained. As can be seen clearly from Fig. 1 and Fig. 3, at the cable jacket strain relief elements, and in particular at the rib 23, the lid already essentially has adequate rigidity as far as shape is concerned, and no additional precautionary measures need to be taken here. At the teeth 25, however, the lid could in principle run flat, but a flat lid part has little rigidity and, in order to improve the rigidity at the teeth 25, a number of reinforcement ribs are integrally formed on the top side of the lid part 20. The figures illustrate two reinforcement ribs, indicated by 27 and 28.

It will now be indicated schematically with reference to Fig. 4 how a cable end can be provided with a connector according to the invention. Fig. 4, (a) illustrates a cable 30 consisting of a number of insulated conductors 31 which are enclosed by a jacket 32. In this specific embodiment, the jacket 32 is also provided with an individual shield layer 33 which is partially exposed. Over a length L the jacket 32 (including the shield layer 33) is stripped from the individual conductors 31.

If the cable 30 is a flat cable, its individual conductors can by nature be at distances from one another which correspond to the distances between the apertures 14 in the base part 10 of the connector. However, if this is not the case, the individual conductors can be held in the correct position as indicated in Fig. 4 at (b), for example with the aid of a separate clamping tool 34 in the form of a sort of clip. The clip must be positioned in such a way that the length L' of the ends of the insulated conductors is sufficient to be inserted completely into the apertures 14. If all or some of the apertures 14 are blind, in other words, if the ends of the insulated conductors cannot come out again at the back of the connector, the ends of the insulated conductors must then be shortened to the length L' indicated in Fig. 4-b.

In Fig. 4, (c) indicates the way in which the parallel-running end parts of the insulated conductors are then inserted into the apertures of the base part 10. It is pointed out that at this point in the assembly process all pierce elements 16 are in the upright position in which the piercing points at the bottom ends of these pierce elements 16 constitute no obstacle whatsoever for the insertion of the conductor ends into the apertures 14. The ribs 15 which can be seen in Fig. 1 serve as guide elements for the insulated conductor ends.

It will be clear from Fig. 4-c that the apertures 26 in the bottom 13 of the base part 10 could in some circumstances be an obstacle during insertion of the conductor ends. It is possible that the conductor ends could become jammed against the edges of these apertures. In order to avoid this, it is

preferable for the apertures 26 to be designed as blind apertures running from the outside of the base part 10 and ending at a thin partition or a thin membrane which ensures a smooth surface on the inside of the bottom 16. The thickness of this thin partition or membrane must be chosen in such a way that the teeth 25 are easily able to penetrate this partition or membrane during pressing down of the lid. Fig. 3 shows the remainder of this membrane 29 after it has been pierced by a tooth 25.

In Fig. 4, at stage (d) the cable is positioned in such a way that its jacket 32 is located in the correct position on the floor of the base part 10.

In a subsequent stage, indicated in Fig. 4 at (e), the lid part 20 is pressed downwards into the base part 10 until the snap edges 21 and 22 snap into the grooves 18 and 19. During pressing down of the lid part 20, the teeth 25, after piercing through any partitions or membranes 29, will be guided into the apertures 26 in the floor 13. The teeth, at least when seen in the crosswise direction of the connector, have preferably a conical shape, in other words, the free space between the teeth decreases as the section of the finally remaining space between each pair of teeth is smaller than the cross section of the insulated conductor and therefore the side edges of each pair of teeth facing one another in each case penetrate into the insulation of the conductor which is clamped between the teeth in question. As a result, this insulation is partially deformed and a firm grip is obtained on the conductor in question, which means that the strain is released from this conductor.

Although various embodiments of the teeth are possible, it is preferable for the teeth to be designed entirely conical, so that the walls penetrating into the insulation of the individual conductors have a smooth shape and there is no cutting into the insulation in question. Furthermore, if an injection moulding process or similar process is used to produce the connector housing parts, smooth conical teeth are an advantage from the point of view of shaping the moulds required for such an injection moulding process, and they will also be advantageous when detaching the shaped housing part from the injection mould.

The next stage in the assembly process, indicated in Fig. 4 at (f), consists of pressing the piercing elements 16 into the position which is illustrated in Fig. 3. In this position the points 16a and 16b are piercing through the insulating layer 35 of the conductor 31 and through its central conducting element 34, so that good contact is made between the conducting pierce element 16 and the conducting inside element 34 of the insulated conductor 31. The position finally reached is also shown schematically in Fig. 4 at (g).

In Fig. 3, reference figure 40 indicates a conducting layer which is provided on at least part of the surface of the lid part 20, and which can also be present on at least part of the surface of the

base part 10. As can be seen from Fig. 3, the strain relief rib 23 will penetrate during the assembly process so far into the cable jacket 32 of the cable 30 that this rib comes into contact with the shield layer 33. If this rib is now provided at least locally with a conducting layer, contact can be made in this way between a shielding part of the connector and the shield layer in the cable jacket.

Figs. 1 and 2 also show a clamping element 39 on the side edge of the connector, but it will not be discussed in detail. This clamping element 39 serves to hold the connector in a matching connector housing. Details of such holding elements can be found, for example, in the earlier mentioned publications.

Claims

1. Connector intended for attachment to the end of a cable (30) consisting of one or more insulated conductors (31) enclosed by a jacket (32), said connector comprising two housing parts (10, 20) which in the assembled state together define a passage having - viewed from the insertion end - a first section designed to take the jacketed end of the cable, and a second section situated further in to take the insulated conductors projecting from the jacket, both housing parts being provided at the first section with first strain relief elements (23, 24) acting on the cable jacket in the assembled state, and being provided on the second section with second strain relief elements acting on the insulated conductors, and one of the housing parts is provided at the second section with a pierce contact (16) for each conductor, which pierce contact can move from a position in which the insulated conductors can be introduced unimpeded into the second section of the passage to a position in which the pierce contact is at least partially pierced through the conductor, characterized in that the second strain relief elements are embodied as cone-shaped teeth (25) which project from the wall of the one housing part (20) into the second section of said passage, at right angles to the conductors at least in the cross sectional direction, and which in the assembled state of the connector extend out to the passage wall of the other housing part (10) in such a way that in the assembled state in the said second section of the passage each of the individual insulated conductors is pressed in between the sides of two adjacent teeth, the wall part of the one housing part (10) therebetween and the underlying wall part of the second housing part resulting into a firm grip on the insulation of the conductors in order to form a strain relief for each of the insulated conductors.

2. Connector according to claim 1, characterized in that the length of the said teeth (25) from the passage wall is greater than the corresponding cross sectional dimension of the second passage section, and that disposed in the wall of the other housing part (10) are apertures (26) of sufficient depth to take the ends of the teeth (25) when the connector is in the assembled state.

3. Connector according to claim 1 or 2, characterized in that the projecting teeth (25) are designed as conical bodies of revolution.

4. Connector according to claim 2 or 3, characterized in that the said apertures (26) in the other housing part are designed as blind bores running from the outside wall of the housing part (10) to a very short distance from the second passage section, the thickness of the partition wall (29) between the end of each blind bore and the second passage section being small enough to be pierced through by the projecting teeth during assembly of the connector.

5. Connector according to one of the preceding claims, for attachment to the end of a flat cable, characterized in that the distance between the projecting teeth corresponds to the distance between the conductors of the flat cable, and that the dimensions of the teeth pass through the material bridges between the various conductors without coming into contact with the actual conductors.

6. Connector according to one of the preceding claims, characterized in that the first housing part (20) which is provided with the projecting teeth (25) is provided with one or more reinforcement ribs (28) on the outside wall approximately opposite the teeth projecting from the inside wall.

Patentansprüche

1. Verbinder, der zum Anbringen an dem Ende eines Kabels (30) bestimmt ist, das aus ein oder mehreren isolierten Leitern (31) besteht, die von einem Mantel (32) umgeben sind, wobei der Verbinder zwei Gehäuseteile (10, 20) aufweist, die im zusammengebauten Zustand miteinander einen Durchgang bilden, der — gesehen vom Einführungsende — einen ersten Querschnitt hat, der derart beschaffen ist, daß er das ummantelte Ende des Kabels aufnimmt, und einen zweiten Querschnitt hat, welcher weiter innen liegt und die isolierten Leiter aufnimmt, die über den Mantel vorstehen, wobei die Gehäuseteile am ersten Querschnitt mit ersten Zugentlastungselementen (23, 24) versehen sind, die auf den Kabelmantel im zusammengebauten Zustand wirken, und wobei an dem zweiten Querschnitt zweite Zugentlastungselemente vorgesehen sind, die auf die isolierten Leiter wirken, bei dem eines der Gehäuseteile am zweiten Querschnitt mit einem Durchstechkontakt (16) für jeden Leiter versehen ist, wobei der Durchstechkontakt von einer position, in der die isolierten Leiter unbehindert in dem zweiten Querschnitt des Durchganges eingeführt werden können, zu einer Position bewegt werden kann, in der der Durchstechkontakt wenigstens teilweise durch den Leiter geht, dadurch gekennzeichnet, daß die zweiten Zugentlastungselemente als konusförmige Zähne (25) ausgebildet sind, die von der Wand des einen Gehäuseteils (20) in den zweiten Querschnitt des Durchganges rechtwinklig zu den Leitern wenigstens in Querschnittsrichtung ragen, und die im zusammengebauten Zustand des Verbinders nach außen zu

base part 10. As can be seen from Fig. 3, the strain relief rib 23 will penetrate during the assembly process so far into the cable jacket 32 of the cable 30 that this rib comes into contact with the shield layer 33. If this rib is now provided at least locally with a conducting layer, contact can be made in this way between a shielding part of the connector and the shield layer in the cable jacket.

Figs. 1 and 2 also show a clamping element 39 on the side edge of the connector, but it will not be discussed in detail. This clamping element 39 serves to hold the connector in a matching connector housing. Details of such holding elements can be found, for example, in the earlier mentioned publications.

Claims

1. Connector intended for attachment to the end of a cable (30) consisting of one or more insulated conductors (31) enclosed by a jacket (32), said connector comprising two housing parts (10, 20) which in the assembled state together define a passage having - viewed from the insertion end - a first section designed to take the jacketed end of the cable, and a second section situated further in to take the insulated conductors projecting from the jacket, both housing parts being provided at the first section with first strain relief elements (23, 24) acting on the cable jacket in the assembled state, and being provided on the second section with second strain relief elements acting on the insulated conductors, and one of the housing parts is provided at the second section with a pierce contact (16) for each conductor, which pierce contact can move from a position in which the insulated conductors can be introduced unimpeded into the second section of the passage to a position in which the pierce contact is at least partially pierced through the conductor, characterized in that the second strain relief elements are embodied as cone-shaped teeth (25) which project from the wall of the one housing part (20) into the second section of said passage, at right angles to the conductors at least in the cross sectional direction, and which in the assembled state of the connector extend out to the passage wall of the other housing part (10) in such a way that in the assembled state in the said second section of the passage each of the individual insulated conductors is pressed in between the sides of two adjacent teeth, the wall part of the one housing part (10) therebetween and the underlying wall part of the second housing part resulting into a firm grip on the insulation of the conductors in order to form a strain relief for each of the insulated conductors.

2. Connector according to claim 1, characterized in that the length of the said teeth (25) from the passage wall is greater than the corresponding cross sectional dimension of the second passage section, and that disposed in the wall of the other housing part (10) are apertures (26) of sufficient depth to take the ends of the teeth (25) when the connector is in the assembled state.

3. Connector according to claim 1 or 2, characterized in that the projecting teeth (25) are designed as conical bodies of revolution.

4. Connector according to claim 2 or 3, characterized in that the said apertures (26) in the other housing part are designed as blind bores running from the outside wall of the housing part (10) to a very short distance from the second passage section, the thickness of the partition wall (29) between the end of each blind bore and the second passage section being small enough to be pierced through by the projecting teeth during assembly of the connector.

5. Connector according to one of the preceding claims, for attachment to the end of a flat cable, characterized in that the distance between the projecting teeth corresponds to the distance between the conductors of the flat cable, and that the dimensions of the teeth pass through the material bridges between the various conductors without coming into contact with the actual conductors.

6. Connector according to one of the preceding claims, characterized in that the first housing part (20) which is provided with the projecting teeth (25) is provided with one or more reinforcement ribs (28) on the outside wall approximately opposite the teeth projecting from the inside wall.

Patentansprüche

1. Verbinder, der zum Anbringen an dem Ende eines Kabels (30) bestimmt ist, das aus ein oder mehreren isolierten Leitern (31) besteht, die von einem Mantel (32) umgeben sind, wobei der Verbinder zwei Gehäuseteile (10, 20) aufweist, die im zusammengebauten Zustand miteinander einen Durchgang bilden, der — gesehen vom Einführungsende — einen ersten Querschnitt hat, der derart beschaffen ist, daß er das ummantelte Ende des Kabels aufnimmt, und einen zweiten Querschnitt hat, welcher weiter innen liegt und die isolierten Leiter aufnimmt, die über den Mantel vorstehen, wobei die Gehäuseteile am ersten Querschnitt mit ersten Zugentlastungselementen (23, 24) versehen sind, die auf den Kabelmantel im zusammengebauten Zustand wirken, und wobei an dem zweiten Querschnitt zweite Zugentlastungselemente vorgesehen sind, die auf die isolierten Leiter wirken, bei dem eines der Gehäuseteile am zweiten Querschnitt mit einem Durchstechkontakt (16) für jeden Leiter versehen ist, wobei der Durchstechkontakt von einer position, in der die isolierten Leiter unbehindert in dem zweiten Querschnitt des Durchganges eingeführt werden können, zu einer Position bewegt werden kann, in der der Durchstechkontakt wenigstens teilweise durch den Leiter geht, dadurch gekennzeichnet, daß die zweiten Zugentlastungselemente als konusförmige Zähne (25) ausgebildet sind, die von der Wand des einen Gehäuseteils (20) in den zweiten Querschnitt des Durchganges rechtwinklig zu den Leitern wenigstens in Querschnittsrichtung ragen, und die im zusammengebauten Zustand des Verbinders nach außen zu



der Durchgangswand des anderen Gehäuseteils (10) derart verlaufen, daß im zusammengebauten Zustand im zweiten Querschnitt des Durchgangs jeder d. einzelnen, isolierten Leiter zwischen den Seiten zweier benachbarter Zähne, dem Wandteil des einen Gehäuseteils (10) dazwischen und dem darunterliegenden Wandteil des zweiten Gehäuseteils eingepreßt wird, was zu einem festen Ergreifen der Isolierung der Leiter führt, um eine Zugentlastung für jeden der isolierten Leiter zu bilden.

2. Verbinder nach Anspruch 1, dadurch gekennzeichnet, daß die Länge der Zähne (25) von der Durchgangswand größer als die entsprechende Querschnittsabmessung des zweiten Durchgangsquerschnittes ist, und daß in der Wand des anderen Gehäuseteils (10) Öffnungen (26) mit einer so ausreichenden Tiefe angeordnet sind, daß die Enden der Zähne (25) aufgenommen sind, wenn der Verbinder im zusammengebauten Zustand ist.

3. Verbinder nach Anspruch 1 oder 2, dadurch gekennzeichnet, daß die vorspringenden Zähne (25) als konische Rotationskörper ausgebildet sind.

4. Verbinder nach Anspruch 2 oder 3, dadurch gekennzeichnet, daß die Öffnungen (26) in dem anderen Gehäuseteil als Blindbohrungen ausgelegt sind, die von der Außenseitenwand des Gehäuseteils (10) um einen sehr kleinen Abstand von dem zweiten Querschnitt verlaufen, und daß die Dicke der Trennwand (29) zwischen dem Ende jeder Blindbohrung und dem zweiten Durchgangsquerschnitt so ausreichend klein ist, daß sie durch die vorspringenden Zähne beim Zusammenbau des Verbinders durchdrungen werden kann.

5. Verbinder nach einem der vorangehenden Ansprüche zum Anbringen des Endes eines Flachkabels, dadurch gekennzeichnet, daß der Abstand zwischen den vorspringenden Zähnen dem Abstand zwischen den Leitern des Flachkabels entspricht, und daß die Abmessungen der Zähne durch das Material gehen, welches brückenförmig zwischen den verschiedenen Leitern vorgesehen ist, ohne daß sie in Kontakt mit den tatsächlichen Leitern kommen.

6. Verbinder nach einem der vorangehenden Ansprüche, dadurch gekennzeichnet, daß das erste Gehäuseteil (20), das mit den vorspringenden Zähnen (25) versehen ist, mit ein oder mehreren Verstärkungsrippen (28) auf der Außenseitenwand etwa zu den von der Innenseitenwand vorspringenden Zähnen gegenüberliegend versehen ist.

Revendications

1. Connecteur destiné à être attaché à l'extrémité d'un câble (30) consistant en un ou plusieurs conducteurs (31) isolés enfermés dans une gaine (32), ledit connecteur comprenant deux parties (10, 20) de boîtier qui, dans l'état assemblé, définissent ensemble un passage qui présente, vu à partir de l'extrémité d'insertion, une première

section destinée à recevoir l'extrémité gainée du câble, et une deuxième section située plus loin à l'intérieur pour recevoir les conducteurs isolés faisant saillie hors de la gaine, les deux parties de boîtier comportant, à la première section des premiers organes (23, 24) de transfert de contrainte agissant sur la gaine de câble dans l'état assemblé et comportant, à la deuxième section, des deuxièmes organes de transfert de contrainte agissant sur les conducteurs isolés, et l'une des parties de boîtier comporte à la deuxième section un contact (16) à perçage pour chaque conducteur, contact à perçage qui peut être déplacé d'une position où les conducteurs isolés peuvent être introduits sans empêchement dans la deuxième section du passage à une position dans laquelle le contact à perçage traverse au moins partiellement le conducteur, caractérisé en ce que les deuxièmes organes de transfert de contrainte sont réalisés comme des dents (25) en forme de cônes qui font saillie à partir de la paroi de ladite partie (20) de boîtier dans la deuxième section dudit passage, à angle droit par rapport aux conducteurs au moins dans la direction d'une coupe transversale, et qui, dans l'état assemblé du connecteur, font saillie vers la paroi de passage de l'autre partie (10) de boîtier de telle façon que, dans ladite deuxième section du passage, chacun des conducteurs isolés individuels est pressé entre les faces de deux dents adjacentes, la partie de paroi de la première partie (10) de boîtier située entre elles et la partie sous-jacente de paroi de la deuxième partie de boîtier, ce qui entraîne une saisie ferme sur l'isolation des conducteurs afin de procurer une transmission de contrainte pour chacun des conducteurs isolés.

2. Connecteur selon la revendication 1, caractérisé en ce que la longueur desdites dents (25) à partir de la paroi de passage est supérieure à la dimension correspondante, en coupe transversale, de la deuxième section de passage, et en ce que la paroi de l'autre partie (10) de boîtier présente des ouvertures (26) de profondeur suffisante pour recevoir les extrémités des dents (25) quand le connecteur est dans pour recevoir les extrémités des dents (25) quand le connecteur est dans l'état assemblé.

3. Connecteur selon la revendication 1 ou 2, caractérisé en ce que les dents (25) en saillie sont réalisées comme des corps coniques de révolution.

4. Connecteur selon la revendication 2 ou 3, caractérisé en ce que lesdites ouvertures (26) dans l'autre partie de boîtier sont réalisées comme des alésages borgnes partant de la paroi extérieure de la partie (10) de boîtier jusqu'à une très faible distance de la deuxième section de passage, l'épaisseur de la paroi (29) de partition entre l'extrémité de chaque alésage borgne et la deuxième section de passage étant suffisamment faible pour être percée par les dents en saillie pendant l'assemblage du connecteur.

5. Connecteur selon l'une des précédentes revendications, destiné à être attaché à l'extrémité d'un câble plat, caractérisé en ce que la



distance entre les dents en saillie correspond à la distance entre les conducteurs du câble plat, et en ce que les dimensions des dents sont telles qu'elles passent à travers les ponts de matière entre les divers conducteurs sans venir en contact avec les conducteurs eux-mêmes.

6. Connecteur selon l'une des précédentes

revendications, caractérisé en ce que la première partie (20) de boîtier, qui comporte les dents (25) en saillie, comporte une ou plusieurs nervures (28) de renforcement sur la paroi extérieure approximativement à l'opposé des dents faisant saillie à partir de la paroi intérieure.

10



15

20

25

30

35

40

45

50

55

60

65

7