

IN-BODY POWER SOURCE HAVING HIGH SURFACE AREA ELECTRODE

CROSS-REFERENCE TO RELATED APPLICATIONS

5 Pursuant to 35 U.S.C. § 119 (e), this application claims priority to the filing date of United States Provisional Patent Application Serial No. 60/889,870 filed on February 14, 2007; the disclosure of which application is herein incorporated by reference.

INTRODUCTION

10 As medical technology advances, many diagnostic and therapeutic activities are carried out with increasingly small implantable medical or ingestible medical devices. Implantable and ingestible medical devices can be configured to perform a variety of different functions, including but not limited to: diagnostic functions, e.g., where the devices include one or more sensors; therapeutic
15 functions, e.g., where the devices enable therapeutic action, such as delivery of electrical pulse, delivery of a pharmaceutically active agent; etc.

With implantable and ingestible medical and related technologies, there is always a desire to make the devices smaller, e.g., to provide for increased ease of use, etc. To decrease size, individual components of the devices must be
20 designed with a reduced overall physical size, and yet maintain functionality.

One type of component that is present in many implantable and ingestible devices is a power source, e.g., batteries, capacitors, etc. There is continued interest in the development of smaller and smaller power sources that nonetheless have adequate and reliable functionality such that they can be
25 employed with in-body devices, such as implantable and ingestible devices.

SUMMARY

Power sources that enable in-body devices, such as implantable and ingestible devices, are provided. Aspects of the in-body power sources of the
30 invention include a solid support, a first high surface area electrode and a second electrode. Embodiments of the in-power sources are configured to emit a

detectable signal upon contact with a target physiological site. Also provided are methods of making and using the power sources of the invention.

BRIEF DESCRIPTION OF THE FIGURES

5 **FIG. 1** shows one embodiment of a battery having a porous cathode under-layer according to one embodiment of the invention.

FIG. 2 provides detail of certain implementations of an electronic circuit of various embodiments of the invention.

10 DETAILED DESCRIPTION

 Power sources that enable in-body devices, such as implantable and ingestible devices, are provided. Aspects of the in-body power sources of the invention include a solid support, a first high surface area electrode and a second electrode. Embodiments of the in-power sources are configured to emit a
15 detectable signal upon contact with a target physiological site. Also provided are methods of making and using the power sources of the invention.

 In further describing the invention in greater detail, embodiments of the in-body power sources and in body devices that include the same are reviewed first,
20 followed by a discussion of systems having devices that include the in-body power sources, and methods of using such devices and systems. Also reviewed in greater detail below are kits that include the devices having the in-body power sources of the invention.

25 *IN-BODY POWER SOURCES AND DEVICES INCLUDING THE SAME*

 As summarized above, the invention provides power sources configured for use with in-body devices. An in-body device is a device that is configured to be used inside of a living body. Examples of in-body devices include, but are not limited to: implantable devices, e.g., implantable therapeutic devices, implantable
30 diagnostic devices, e.g., sensors, etc; and ingestible devices, e.g., ingestible event markers (e.g., as described in greater detail below), etc.

 In body power sources according to embodiments of the invention include a solid support; a first high surface electrode present on a surface of said solid

support; and a second electrode. The solid support may vary depending on the nature of the device with which the in-body power source is to be employed. In certain embodiments, the solid support is small, e.g., where it is dimensioned to have a width ranging from about 0.01 mm to about 100 mm, e.g., from about 0.1 mm to about 20 mm, including from about 0.5 mm to about 2 mm; a length ranging from about 0.01 mm to about 100 mm, e.g., from about 0.1 mm to about 20 mm, including from about 0.5 mm to about 2 mm, and a height ranging from about 0.01 mm to about 10 mm, e.g., from about 0.05 mm to about 2 mm, including from about 0.1 mm to about 0.5 mm. The solid support element may take a variety of different configurations, such as but not limited to: a chip configuration, a cylinder configuration, a spherical configuration, a disc configuration, etc, where a particular configuration may be selected based on intended application, method of manufacture, etc. While the material from which the solid support is fabricated may vary considerably depending on the particular device for which the in-body power source is configured for use, in certain embodiments the solid support is made up of a semiconductor material, e.g., silicon. To provide for production of the porous underlayer, e.g., as described below, portions of the solid support surface may include a conductive material, e.g., metal or metal alloy, such as but not limited to gold, and the like.

In certain embodiments, the solid support is a semiconductor support that includes one or more circuit elements, where in certain embodiments the support is an integrated circuit. When present, integrated circuits include a number of distinct functional blocks, i.e., modules. Within a given solid support, at least some of, e.g., two or more, up to an including all of, the functional blocks, e.g., power source, processor, transmitter, etc., may be present in a single integrated circuit. By single integrated circuit is meant a single circuit structure that includes all of the different desired functional blocks for the device. In these embodiments, the integrated circuit is a monolithic integrated circuit (also known as IC, microcircuit, microchip, silicon chip, computer chip or chip) that is a miniaturized electronic circuit (which may include semiconductor devices, as well as passive components) that has been manufactured in the surface of a thin substrate of semiconductor material. The integrated circuits of certain embodiments of the present invention may be hybrid integrated circuits, which are miniaturized

electronic circuits constructed of individual semiconductor devices, as well as passive components, bonded to a substrate or circuit board.

As mentioned above, one type of in-body device in which the power sources of the invention find use is an ingestible event marker. For ease of described, the in-body power sources will now be further described in terms of embodiments where the in body power source is part of an identifier of an ingestible event marker. However, as indicated above, the in-body power sources of the invention find use in devices other than ingestible event markers, and therefore in-body power sources of the invention are not limited to those configured for use in ingestible event markers (IEM).

The identifier of the IEM compositions is one that generates (i.e., emits) a detectable signal upon contact of the identifier with a target physiological sight. The identifiers of the present compositions may vary depending on the particular embodiment and intended application of the composition so long as they are activated (i.e., turned on) upon contact with a target physiological location, e.g., stomach. As such, the identifier may be an identifier that emits a signal when it contacts a target body (i.e., physiological) site. The identifier may be any component or device that is capable of providing a detectable signal following activation, e.g., upon contact with the target site. In certain embodiments, the identifier emits a signal once the composition comes into contact with a physiological target site, e.g., the stomach. Depending on the embodiment, the target physiological site or location may vary, where representative target physiological sites of interest include, but are not limited to: a location in the gastrointestinal tract, such as the mouth, esophagus, stomach, small intestine, large intestine, etc. In certain embodiments, the identifier is configured to be activated upon contact with fluid in the target site, regardless of the particular composition of the target site.

Depending on the needs of a particular application, the signal obtained from the identifier may be a generic signal, e.g., a signal that merely identifies that the composition has contacted the target site, or a unique signal, e.g., a signal which in some way uniquely identifies that a particular ingestible event marker from a group or plurality of different markers in a batch has contacted a target physiological site. As such, the identifier may be one that, when employed with a batch of unit dosages, e.g., a batch of tablets, emits a signal which cannot

be distinguished from the signal emitted by the identifier of any other unit dosage member of the batch. In yet other embodiments, the identifier emits a signal that uniquely identifies that particular identifier. Accordingly, in certain embodiments the identifier emits a unique signal that distinguishes one class of identifier from other types of identifiers. In certain embodiments, the identifier emits a unique signal that distinguishes that identifier from other identifiers. In certain embodiments, the identifier emits a signal that is unique, i.e., distinguishable, from a signal emitted by any other identifier ever produced, where such a signal may be viewed as a universally unique signal (e.g., analogous to a human fingerprint which is distinct from any other fingerprint of any other individual and therefore uniquely identifies an individual on a universal level). In one embodiment, the signal may either directly convey information about a given event, or provide an identifying code, which may be used to retrieve information about the event from a database, i.e., a database linking identifying codes with compositions.

The identifier may generate a variety of different types of signals, including but not limited to: RF signals, magnetic signals, conductive (near field) signals, acoustic signals, etc. Of interest in certain embodiments are the specific signals described in pending PCT application serial no. PCT/US2006/16370 filed on April 28, 2006; the disclosures of various types of signals in this application being specifically incorporated herein by reference. The transmission time of the identifier may vary, where in certain embodiments the transmission time may range from about 0.1 μ sec to about 48 hours or longer, e.g., from about 0.1 μ sec to about 24 hours or longer, such as from about 0.1 μ sec to about 4 hours or longer, such as from about 1 sec to about 4 hours, including about 1 minute to about 10 minutes. Depending on the given embodiment, the identifier may transmit a signal once or transmit a signal two or more times, such that the signal may be viewed as a redundant signal.

The identifiers of the present compositions may vary depending on the particular embodiment and intended application of the composition so long as they are activated (i.e., turned on) upon contact with a target physiological location, e.g., stomach. As such, the identifier may be an identifier that emits a signal when it contacts a target body (i.e., physiological) site. In addition or

alternatively, the identifier may be an identifier that emits a signal when interrogated after it has been activated. Identifier components of embodiments of the invention have: (a) an activation component; and (b) a signal generation component, where the signal generation component is activated by the activation component to produce an identifying signal, e.g., as described above.

The activation component is a component that activates the signal generation element of the identifier to provide a signal, e.g., by emission or upon interrogation, following contact of the composition with a target physiological site of interest, such as the stomach. As reviewed in co-pending PCT application serial no. PCT/US2006/016370, activation of the identifier may be achieved in a number of different ways, where such approaches include, but are not limited to: battery completion, battery connection, etc. The different activation approaches disclosed in this co-pending application may be readily adapted to provide activation, as described herein, and as such are herein incorporated by reference in their entirety.

Embodiments of activation elements based on battery completion formats employ in body battery sources of the invention, where when activated the in-body battery power source includes, a cathode, an anode, and an electrolyte. In such embodiments, when the cathode and anode come into contact with stomach fluid, the stomach fluid acts as the electrolyte component of the battery, such that the added component of the stomach fluid thus completes the battery.

In certain embodiments, the battery that is employed is one that comprises two dissimilar electrochemical materials which constitute the two electrodes (e.g., anode and cathode) of the battery. When the electrode materials come in contact with the body fluid, such as stomach acid or other types of fluid (either alone or in combination with a dried conductive medium precursor), a potential difference, i.e., a voltage, is generated between the electrodes as a result of the respective oxidation and reduction reactions occurring at the two electrodes (such that a voltaic cell or battery is produced). Accordingly, in embodiments of the invention, in-body power sources are configured such that when the two dissimilar materials are exposed to the target site, e.g., the stomach, the digestive tract, etc., a voltage is generated. The two dissimilar materials in an electrolyte are at different potentials. In certain of these embodiments, the in-body battery power source

may be viewed as a power source that exploits electrochemical reaction in an ionic solution such as gastric fluid, blood, or other bodily fluids and some tissues.

The dissimilar materials making up the electrodes can be made of any two materials appropriate to the environment in which the identifier will be operating.

- 5 The active materials are any pair of materials with different electrochemical potentials. For instance, in some embodiments where the ionic solution comprises stomach acids, electrodes may be made of a noble metal (e.g., gold, silver, platinum, palladium or the like) so that they do not corrode prematurely. Alternatively, the electrodes can be fabricated of aluminum or any other
- 10 conductive material whose survival time in the applicable ionic solution is long enough to allow the identifier to perform its intended function. Suitable materials are not restricted to metals, and in certain embodiments the paired materials are chosen from metals and non-metals, e.g., a pair made up of a metal (such as Mg) and a salt (such as CuI). With respect to the active electrode materials, any
- 15 pairing of substances – metals, salts, or intercalation compounds - with suitably different electrochemical potentials (voltage) and low interfacial resistance are suitable.

- A variety of different materials may be employed as the battery electrodes. In certain embodiments, electrode materials are chosen to provide for a voltage
- 20 upon contact with the target physiological site, e.g., the stomach, sufficient to drive the signal generation element of the identifier. In certain embodiments, the voltage provided by the electrode materials upon contact of the metals of the power source with the target physiological site is 0.001 V or higher, including 0.01 V or higher, such as 0.1 V or higher, e.g., 0.3 V or higher, including 0.5 volts or
- 25 higher, and including 1.0 volts or higher, where in certain embodiments, the voltage ranges from about 0.001 to about 10 volts, such as from about 0.01 to about 10 V.

Materials and pairings of interest include, but are not limited to those reported in Table 1 below.

30

TABLE 1		
	Anode	Cathode
Metals	Magnesium, Zinc Sodium (†), Lithium (†) Iron and alloys thereof, e.g., Al and Zn alloys of Mg	
Salts		Copper salts: iodide, chloride, bromide, sulfate, formate, (other anions possible) Fe ³⁺ salts: e.g. orthophosphate, pyrophosphate, (other anions possible) Oxygen or hydrogen (††) on platinum, gold or other catalytic surfaces
Intercalation compounds	Graphite with Li, K, Ca, Na, Mg	Vanadium oxide Manganese oxide

† Protected anodes: certain high energy anode material such as Li, Na, and other alkali metals are unstable in their pure form in the presence of water or oxygen. These may however be used in an aqueous environment if stabilized. One example of this stabilization is the so-called "protected lithium anode" developed by Polyplus Corporation (Berkeley, CA), where a polymer film is deposited on the surface of lithium metal to protect it from rapid oxidation and allow its use in aqueous environment or air ambient. (Polyplus has IP pending on this).

†† Dissolved oxygen can also serve as a cathode. In this case, the dissolved oxygen in the bodily fluids would be reduced to OH⁻ at a suitable catalytic surface such as Pt or gold. Also of interest dissolved hydrogen in a hydrogen reduction reaction.

In certain embodiments, one or both of the metals may be doped with a non-metal, e.g., to enhance the voltage output of the battery. Non-metals that may be used as doping agents in certain embodiments include, but are not limited to: sulfur, iodine and the like.

In certain embodiments, the electrode materials are cuprous iodine (CuI) or cuprous chloride (CuCl) as the cathode and magnesium (Mg) metal or magnesium alloy as the anode. Embodiments of the present invention use electrode materials that are not harmful to the human body.

As summarized above, in-body power sources of the invention, such as batteries that include electrodes of two dissimilar materials (as reviewed immediately above) include at least one a high surface area electrode, e.g., a high surface area cathode and/or high surface area anode. By high surface area electrode is meant an electrode having a surface area that is about 2-fold or greater, such as about 10-fold or greater, than the area of the surface of a solid support that is covered by the electrode in the power source, e.g., battery. In

certain embodiments, the surface area of the electrode ranges from about 0.01 mm² to about 100 mm², such as from about 0.1 mm² to about 50 mm² and including from about 1 mm² to about 10 mm². In certain embodiments, the high surface area electrode is obtained by having an electrode that is made up of an active electrode material (e.g., where illustrative active cathode and anode materials are provided above) present on a porous under-layer. In certain

5 other embodiments, all of the electrodes are high surface area electrodes, while in other embodiments only some of the electrodes, e.g., one of the electrodes, is a high surface area electrode.

10 Depending on the particular embodiment, the cathode and anode may be present on the same support or different supports, e.g., where two or more different supports are bonded together to produce the battery structure, e.g., as is present in a "flip-chip" embodiment. Similarly, the number of cathodes and anodes in a given battery may vary greatly depending on the embodiment, e.g.,

15 where a given embodiment may include a single battery having one anode and cathode, a single battery having multiple anodes and/or cathodes, or two or more distinct batteries each made up of one or more cathodes and/or anodes. Battery configurations of interest include, but are not limited to, those disclosed in PCT application serial no. PCT/US2006/016370 filed on April 28, 2006 and titled

20 "Pharma-Informatics System"; PCT application serial no. PCT/ US2007/022257 filed on October 17, 2007 and titled "In-vivo Low Voltage Oscillator for Medical Devices"; PCT application serial no. PCT/ US US2007/82563 filed on October 25, 2007 and titled "Controlled Activation Ingestible Identifier"; United States Patent Application Serial No. 11/776,480 filed July 11, 2007 entitled "Acoustic Pharma

25 Informatics System"; and PCT/ US US2008/ 52845 filed on February 1, 2008 and titled "Ingestible Event Marker Systems"; the disclosures of which applications (and particularly battery configurations disclosed therein) are herein incorporated by reference.

FIG. 1 provides a schematic illustration of battery power source according to an embodiment of the invention that includes a high surface area electrode, and specifically a high surface area cathode. The battery **100** shown in **FIG. 1** includes a solid support **120** having an upper surface **140**. Present on the upper surface **140** is cathode **160** and anode **180**. Cathode **160** includes porous under-layer **150** and active cathode material **170**. Each of these elements is now

described in greater detail below. While the embodiment depicted is where the cathode includes a porous under-layer, in certain embodiments it is the anode that includes a porous underlay, while in yet other embodiments both a cathode and anode have the porous under-layer. Both the cathode and anode are present on a surface of a solid support. In certain embodiments such as that shown in FIG. 1, the two electrodes are present on the same surface of the solid support. In yet other embodiments, the two electrodes may be present on different surfaces of the support, e.g., opposite surfaces of the support.

The porous under-layer **150** is a layer that mechanically supports the active electrode (e.g., cathode) material **170**, improves adhesion and/or increases the surface area of the electrode, and provides for current passage between the cathode material and elements, e.g., circuitry, present on the solid support **120** (described in greater detail below). The porous under-layer may be fabricated from a variety of different materials, such as conductive materials, e.g., copper, titanium, aluminum, graphite, gold, platinum, iridium, etc., where the materials may be pure materials or materials made up of two or more elements, e.g., as found in alloys, etc. With respect to a cathode, materials of interest for a cathode porous underlayer include, but are not limited to: Au, Cu, Pt, Ir, Pd, Rh, Ru, as well as binary and ternary alloys thereof. With respect to an anode, materials of interest for an anode porous underlayer include, but are not limited to: Ti and alloys thereof (e.g., Ti-W, Ti-Cr, TiN), W, W-C, etc. The thickness of the under-layer may vary, where in certain embodiments the thickness ranges from about 0.01 to about 100 μm , such as from about 0.05 to about 50 μm and including from about 0.01 to about 10 μm . The dimensions of the porous under-layer with respect to length and width on the surface of the solid support may or may not be coextensive with the same dimensions of the active cathode material, as desired.

As summarized above, the under-layer may be rough or porous. The porosity or roughness of the under-layer may vary, so long as it imparts the desired surface area to the electrode, e.g., cathode. In certain embodiments, the porosity or roughness of the under-layer is chosen to provide an effective surface area enhancement of about 1.5 times or more to about 1000 times or more, e.g., from about 2 to about 100 times or more, such as from about 2 to about 10 times

or more, greater than that obtained from a comparable electrode that lacks the porous underlayer. Surface area enhancement can be determined by comparing the electrochemical capacitance or cyclic voltammogram of the rough or porous electrode with that of a smooth electrode of the same material. Roughness may
5 also be determined by other techniques, such as atomic force microscopy (AFM), electron microscopy, electrochemical impedance spectroscopy or Brunauer–Emmett–Teller (BET) analysis.

The porous cathode under-layer may be produced using any convenient protocol. In certain embodiments, planar processing protocols are employed.
10 Planar processing techniques, such as Micro-Electro-Mechanical Systems (MEMS) fabrication techniques, including surface micromachining and bulk micromachining techniques, may be employed. Deposition techniques that may be employed in certain embodiments of fabricating the structures include, but are not limited to: electrodeposition (e.g., electroplating), cathodic arc deposition,
15 plasma spray, sputtering, e-beam evaporation, physical vapor deposition, chemical vapor deposition, plasma enhanced chemical vapor deposition, etc. Material removal techniques included, but are not limited to: reactive ion etching, anisotropic chemical etching, isotropic chemical etching, planarization, e.g., via chemical mechanical polishing, laser ablation, electronic discharge machining
20 (EDM), electrodisolution/electropolishing (a metal is deposited, then selective areas are dissolved to make it rough and porous), etc. Another protocol of interest is electroless plating as a deposition method. In these deposition protocols, metal is deposited out of solution by a reducing agent. The deposited metal layer can be used to coat an already existing rough nonconductive / poorly
25 conductive surface layer or particles such as carbon, alumina, polymers, zeolite, silicon oxide, amorphous carbon and nanotubes. The nonconductive layer can be deposited via any suitable planar processing method, such as cathodic arc, electrophoretic deposition, or a paste / glue containing particles. Also of interest are lithographic protocols. Of interest in certain embodiments is the use of planar
30 processing protocols, in which structures are built up and/or removed from a surface or surfaces of an initially planar substrate using a variety of different material removal and deposition protocols applied to the substrate in a sequential manner. Illustrative fabrication methods of interest are described in greater detail

in copending PCT application serial no. PCT/US2006/ 016370; the disclosure of which is herein incorporated by reference.

For the porous under-layer, in certain embodiments an electrodeposition protocol is employed. Where the porous cathode under-layer comprises a metal(s), electroplating (electrodeposition of metals) may be employed. In certain
5 embodiments, the electroplating protocol employed is one in which the current density and/or agitation of the solution is selected so as to impart the desired roughness or porosity to the deposited porous cathode under-layer. In certain embodiments, the metal, e.g., copper, film is deposited in an electroplating bath
10 at the mass-transfer limit. The phrase "mass transfer limit" means that the current density is optimized along with the metal ion concentration in the bath and the flow rate of the bath, such that depositing occurs at substantially the maximum limit at which metal ions can arrive at the surface. Deposition at the mass transfer limit yields, in certain embodiments, a dendritic form of deposited material.
15 Depending on the particular metal and ion concentration thereof, the current density may vary. In certain of the embodiments, the selected current density ranges from about 5 to about 2000 mAmps/cm², such as from about 50 to about 400 mAmps/cm², e.g., about 200 mAmps/cm². Plate up may be carried out in a suitable plating cell, such as a plating tank with agitation, a paddle cell, or a
20 fountain cell. The fluid flow may be selected in conjunction with the applied current density to achieve the desired porosity or roughness. In a plating tank with a rotary mixer, the stirring rate may be between about 0 and about 200 rpm, such as between about 50 to about 500 rpm. With respect to the metal ion concentration, a relatively lower metal ion concentration may be employed to
25 obtain a rough deposit at a lower current density while relatively higher ion concentration may be employed to obtain a rough deposit at a higher current density. In certain embodiments, the metal ion concentration ranges from 0.001 mol/L to 4 mol/L, such as from 0.05 mol/L to 1 mol/L. Flow rate employed during deposition also impacts the nature of the film that is deposited. Lower flow rates
30 can be used lower current densities.

Where desired, various additives may be included in the electroplating fluid to enhance the desired porosity. Additives that may be included in the solution include, but are not limited to: organic acids, e.g., acetic acid, citric acid, e.g., polymers, e.g., PEG, etc. The plating up solution may also contain alcohols,

e.g., ethanol), amines and thiols (e.g., thiourea). Typical copper plating bath compositions (such as acidic, e.g., sulfuric acid/copper sulfate) and alkaline (e.g., pyrophosphate or chromate solutions) may also be used. Where polymers are added, the polymers may be linear or branched water-soluble polymers, such as

5 a poly(alkylene glycol), such as poly(ethylene glycol) (PEG). Other related polymers are also suitable for use in the practice of this invention and that the use of the term PEG or poly(ethylene glycol) is intended to be inclusive and not exclusive in this respect. In some embodiments, the polymer has from 2 to about 300 termini. In some embodiments, the polymer is clear, colorless, odorless,

10 soluble in water, stable to heat, inert to many chemical agents, does not hydrolyze or deteriorate, and is nontoxic. In some embodiments, the polymer is biocompatible, which is to say that the polymer is capable of coexistence with living tissues or organisms without causing harm. In some embodiments, the polymer is non-immunogenic, which is to say that the polymer does not produce

15 an immune response in the body. In some embodiments, the polymer is a PEG comprising the formula $Ra-(CH_2CH_2O)_m-CH_2CH_2-$, where m is from about 3 to about 4000, or from about 3 to about 2000, and Ra is a hydrogen, $-OH$, CH_3-O- , CH_2CH_2-O- or $CH_3CH_2CH_2-O-$. The polymer can be linear or branched. In some embodiments, a branched polymer has a central branch core moiety and a

20 plurality of linear polymer chains linked to the central branch core. PEG includes branched forms that can be prepared by addition of ethylene oxide to various polyols, such as glycerol, pentaerythritol and sorbitol. The branched PEGs can be represented in general form as $Rb(-PEG-OH)_n$ in which Rb represents the core moiety, such as glycerol or pentaerythritol, and n represents the number of arms and is from 2 to 300. In some embodiments, the PM is a linear or branched PEG.

25 Suitable polymers that can be employed include, but are not limited to, poly(alkylene glycol), such as poly(ethylene glycol) (PEG) and poly(propylene glycol) (PPG), copolymers of ethylene glycol and propylene glycol and the like, poly(oxyethylated polyol), poly(olefinic alcohol), poly(vinylpyrrolidone), poly(hydroxypropylmethacrylamide), poly(α -hydroxy acid), poly(vinyl alcohol),

30 polyphosphazene, polyoxazoline, and copolymers, terpolymers, derivatives and mixtures thereof. The molecular weight of each chain of the polymer can vary in the range of from about 100 Da to about 100,000 Da, or from about 6,000 Da to about 80,000 Da. Suitable PEGs include, but are not limited to, PEG(100),

PEG(200), PEG(300), PEG(400), PEG(600), PEG(1000), PEG(1500), PEG(2000), PEG(3000), PEG(3350), PEG(4000), PEG(5000), PEG(6000), PEG(8000), and PEG(10000), and methoxy and ethoxy derivatives thereof, and any PEG having a molecular size within and inclusive of any of the above indicated molecular weights. The polymer component may be synthesized using any convenient protocol or purchased from a commercial source, as desired. Suitable PEGs are commercially available from many sources, such as Sigma-Aldrich Corp. (St. Louis, MO).

Additives of interest include, but are not limited to, accelerator, suppressors, wetting agents, levelers and bath stabilizers. Accelerators of interest include, but are not limited to: thiols, such as thiourea and 3-sulfopropyl disulfide, where accelerators of interest, either by themselves or in combination with other additives, accelerate metal, e.g., copper, deposition rate. In certain embodiments, the accelerator additive is present at a concentration ranging from 1 ppb to 1000 ppm, such as 10 ppb to 500ppm. In certain embodiments, the concentration of additive is employed in combination with a flow rate that provides for dendritic nodules that grow at a substantially exponential rate, e.g., where the end of the dendrite is present in a relatively rich accelerator environment and the opposite end of the dendrite proximal to the surface is present in a relatively poor accelerator environment. In certain of these embodiments, the flow rate is set to have a certain diffusion layer thickness which provides for this type of growth, where the diffusion layer thickness may range from 0.01 to 500 μm , such as 1 to 100 μm .

In certain embodiments, accelerating additives are employed in combination with suppressing additives. Suppressing additives of interest are compounds that physically block the surface of the metal, where such additives include, but are not limited to: polyethylene glycol, amino compounds and organic compounds. By physically blocking the surface of the solid support, growth at the surface distal ends of the deposited structures may be enhanced relative to growth at the surface proximal ends.

In these embodiments, concentrations and types of accelerating additives may be employed that eliminate the impact of suppressing additives, where the accelerators dislodge the suppressors. In certain of these embodiments, a

solution is employed that has a suppressing additive and an accelerating additive, where the concentration of the suppressing additive is mass-transfer limited. Any part of the solution that gets a little bit of a nodule going will reach into a higher concentration region of accelerant and then will grow exponentially to provide a desired amount of roughness. In these embodiments, the area close to the surface is heavily suppressed by the suppressor agent. The parts of the growing nodules that stick up into the solution come into contact with an accelerating agent that can come in and dislodge the suppressing agent, and provide the desired dendritic format or nodules.

An alternative to employing a suppressing agent, e.g., as described above, is to employ a protocol that includes co-evolution of gas, where blocking gas bubbles are produced at the surface of the solid support during deposition. In these embodiments, the deposition conditions are chosen that generate a gas, e.g., hydrogen gas, at the surface of the solid support upon which the metal is being deposited. Where desired, the size of the bubbles that are produced in these protocols may be modulated by employing a surface tension agent, e.g., acetic acid, polyethylene glycol, or other agents that control the wetting properties in a manner that provides for bubbles of desired dimension. Relatively less wetting agent can be employed to provide for larger, e.g., micron, sized pores, while relatively more wetting agent can be employed for smaller sized pores.

The gas coevolution protocol may be employed with appropriate accelerator agents in a manner analogous that described above with respect to suppressor agents, as both approaches physically block the surface of the solid support and the presence of the accelerator may be employed to enhance growth at the surface distal ends of the deposited structures. Accordingly, when current to the entire surface of the solid support, the metal, e.g., copper will preferentially plate where there is accelerating species as opposed to in the regions, e.g., valleys between deposited structure, where there is no accelerating species, e.g., because of presence of physical blocking agent, such as a bubble or suppressor species.

In yet another embodiment, a self-assembled monolayer, or an electro-grafted layer, which is an organic, diazonium containing species that can actually covalently bond to the surface of the solid support may be employed. In manner similar to the bubbles and suppressors described above, such deposited species

can also physically block the surface to modulate the form of the plated structures and provide the desired porous structure. By controlling the concentration of the nuclei of the electrographic layer, or the density of the self-assembled mono layer, one can modulate the nature of the deposited metal structures. In certain
5 embodiments, these protocols are employed where a metal different from that of the solid support is being deposited on the solid support. In certain embodiments, a masking approach is employed to further modulate the nature of the deposited structures on the surface of the solid support.

10 In yet other embodiments, a cathodic arc deposition protocol is employed to produce the desired porous cathode under-layer. In such protocols, a cathodic arc generated metallic ion plasma is contacted with a surface of a substrate under conditions sufficient to produce the desired structure of the porous cathode under-layer, e.g., as described above. The cathodic arc generated ion plasma beam of metallic ions may be generated using any convenient protocol. In
15 generating an ion beam by cathodic arc protocols, an electrical arc of sufficient power is produced between a cathode and one or more anodes so that an ion beam of cathode material ions is produced. Prior to deposition of the cathodic arc metal, a seed metal layer is produced from at least one, but often two or more, conformal metal underlayers. These underlayers start with a thin adhesion layer
20 that contains metals including but not limited to TiN, Ti, W, Cr or alloys of these metals. This first metal layer improves adhesion of the thicker cathodic arc metal and may be sealed with a noble metal that includes, but is not limited to, Au, Pt, Ag, Cu, Pt, Ir, Pd, Rh, or Ru or alloys of these metals. The cap metal seals the adhesion metal chemically and is chosen to also adhere well to the thicker metal
25 deposited by the cathodic arc process. The cathodic arc can be run in a variety of conditions, including but not limited to higher pressure of inert gas (gas could be Ar, Ne, He, Xe or a simple mixture of these; pressures can range over 50mT up to 1000mT) and a neutral (unbiased) target. In the case of a higher pressure and a neutral target, this suppresses small ionized metal particles in favor of larger
30 macro particles at the target surface during film growth, resulting in a film that can have peak-to-peak roughness values ranging from 0.2 to 10 times the average deposited film thickness. Films grown can be as thin as 0.25um and up to 25um, and in certain embodiments are in the range of 3 to 10um thick before they achieve a desired roughness for the underlying electrode structure. Other

convenient protocols for producing a structure via cathodic arc deposition may be employed, where protocols known in the art which may be adapted for use in the present invention include, but are not limited to those described in U.S. Patent Nos. 6,929,727; 6,821,399; 6,770,178; 6,702,931; 6,663,755; 6,645,354; 5 6,608,432; 6,602,390; 6,548,817; 6,465,793; 6,465,780; 6,436,254; 6,409,898; 6,331,332; 6,319,369; 6,261,421; 6,224,726; 6,036,828; 6,031,239; 6,027,619; 6,026,763; 6,009,829; 5,972,185; 5,932,078; 5,902,462; 5,895,559; 5,518,597; 5,468,363; 5,401,543; 5,317,235; 5,282,944; 5,279,723; 5,269,896; 5,126,030; 4,936,960; and Published U.S. Application Nos.: 20050249983; 20050189218; 10 20050181238; 20040168637; 20040103845; 20040055538; 20040026242; 20030209424; 20020144893; 20020140334 and 20020139662; the disclosures of which are herein incorporated by reference. Such protocols are of interest in the deposition of a variety of different materials, e.g., copper, titanium, aluminum, etc. Additional cathodic arc protocols and structures produced thereby include, 15 but are not limited to, those described in published PCT application No. WO 2007/149546 titled "Implantable Medical Devices Comprising Cathodic Arc Produced Structures," the disclosure of which is herein incorporated by reference.

In yet other embodiments an electrophoretic deposition protocol may be 20 employed. Electrophoretic deposition (EPD) is a term for a broad range of industrial processes which includes electrocoating, electrophoretic coating, or electrophoretic painting. In EPD, colloidal particles suspended in a liquid medium migrate under the influence of an electric field (electrophoresis) and are deposited onto a conductive surface. All colloidal particles that can be used to 25 form stable suspensions and that can carry a charge can be used in electrophoretic deposition. This includes material classes such as polymers, pigments, dyes, ceramics and metals. For example, where the material to be deposited is graphite, a suspension of graphite particles may be produced, where surfactants may be included in the suspension to impart a desired charge to the 30 graphite particles. Sizes for the graphite particles may vary, and in certain embodiments may range from about 0.1 to about 100 μm , such as from about 0.1 to about 2 μm . Any convenient surfactant may be included that is capable of imparting the desired charge to the graphite particles in suspension, including

ionic and non-ionic surfactants. An electric field may then be applied to the suspension, where the applied electric field is sufficient to cause the graphite particles to migrate to the surface of the support and be deposited in the form of the desired porous under-layer.

5 In yet other embodiments, the solid support surface is electrochemically modified, e.g., via electrochemical dissolution, where portions of the surface are selectively removed to provide for the desired porous structure. For example, an anodic potential may be applied to a metal surface to dissolve the metal surface. Such an approach may be employed in combination with a patterning photo-
10 resist layer and/or with additives to generate a desired roughness or pattern of nodules on the surface. In certain of these embodiments, a metal layer is first deposited, e.g., by any convenient deposition protocol. Next, additives and/or masking (e.g., photoresist) is employed to selectively dissolve certain areas of the surface and make the surface rough.

15 In certain embodiments, a metal codeposition and dissolution approach is employed. In these embodiments, two metals are simultaneously deposited, e.g., via cathodic arc, evaporation, sputtering, etc.) to make a composite layer, where the metals are (1) an inert electrode metal, such as Pt, PtIr, Ir, Au, or Cu and (2) a highly oxidizable and soluble metal, such as Mg, Zn, Li. The resulting deposited
20 layer is a composite, consisting of mostly metal 1, but with isolated domains of metal 2. The layer is then immersed in an electrolytic solution (e.g., a solvent such as water or an organic acid (such as sulfuric, nitric or hydrochloric acids), bases (such as NaOH, aluminum etchant), neutral salts (such as NaCl, KCl, CuSO₄, magnesium, lithium, zinc salts), or organic additives and surfactants
25 (such as polyethylene glycol). Upon immersion, metal 2 dissolves away leaving behind a film of metal 1 that includes pores. The size of the pores will be that of the particles of metal (2). In certain embodiments, e.g., where one does not wish to leave any of metal 2 behind inside the film, the second metal's deposition conditions (deposition current, filtering, cathode temperature, etc) are set to yield
30 particles that are on the order of the total desired film thickness. The first metal particles may be selected to be smaller and more compact than those of the second metal. Cathodic arc is particularly suitable for the composite film deposition because it allows deposition of particles with controlled particle size. The dissolution step may be carried out with an applied current (anodic

dissolution), or it can be done without an applied current in which case it is a result of the chemical reaction between metal 2 and solution components and / or a galvanic couple between metal 1 and metal 2 that forces metal 2 to corrode. The above approach can also be applied to non-metallic rough films, e.g., any pair of materials deposited via cathodic arc where one of them can be selectively dissolved or etched away leaving behind a porous layer. Also, the above approach is not limited to two metals, i.e. 2 or more metals (or alloys) can be included in the composite film.

Present on top of the porous under-layer is the active electrode (e.g., cathode) material. As reviewed above, the active electrode material may comprise a variety of different materials. Where the electrode is a cathode, in certain embodiments, the cathode material includes copper, where of particular interest in certain embodiments are cuprous iodide (CuI) or cuprous chloride (CuCl) as the cathode material. Where desired, e.g., to enhance voltage of the battery, the active material may be doped with additional elements, e.g., sulfur, etc.

The active cathode material may be provided onto the porous under-layer using any convenient protocol. In certain embodiments, a deposition protocol is employed, such as electrodeposition, e.g., electroplating, or evaporation, e.g., chemical vapor deposition.

Also present in the battery is at least one anode. As reviewed above, the anode material may comprise a variety of different materials. In certain embodiments, the anode material includes magnesium (Mg) metal or magnesium alloy. The active anode material may be provided onto the porous under-layer using any convenient protocol. In certain embodiments, a deposition protocol is employed, such as electrodeposition, e.g., electroplating, or evaporation, e.g., chemical vapor deposition.

As reviewed above, in certain embodiments, the solid support **120** is a circuitry support element. The circuitry support element may take any convenient configuration, and in certain embodiments is an integrated circuit (IC) chip. The surface upon which the electrode elements are positioned may be the top surface, bottom surface or some other surface, e.g., side surface, as desired, where in certain embodiments the surface upon which the electrode elements are at least partially present is a top surface of an IC chip.

In addition to the battery component of the identifier, described above, identifiers of the invention also include a signal generation component. The signal generation component of the identifier element is a structure that, upon activation by the activation component, emits a detectable signal, e.g., that can be received
5 by a receiver, e.g., as described in greater detail below. The signal generation component of certain embodiments can be any convenient device that is capable of producing a detectable signal and/or modulating transduced broadcast power, upon activation by the activation component. Detectable signals of interest include, but are not limited to: conductive signals, acoustic signals, etc. As
10 reviewed above, the signals emitted by the signal generator may be generic or unique signals, where representative types of signals of interest include, but are not limited to: frequency shift coded signals; amplitude modulation signals; frequency modulation signals; etc.

In certain embodiments, the signal generation element includes circuitry,
15 as developed in more detail below, which produces or generates the signal. The type of circuitry chosen may depend, at least in part, on the driving power that is supplied by the power source of the identifier. For example, where the driving power is 1.2 volts or above, standard CMOS circuitry may be employed. In other embodiments where the driving power ranges from about 0.7 to about 1.2 V, sub-
20 threshold circuit designs may be employed. For driving powers of about 0.7 V or less, zero-threshold transistor designs may be employed.

In certain embodiments, the signal generation component includes a voltage-controlled oscillator (VCO) that can generate a digital clock signal in response to activation by the activation component. The VCO can be controlled
25 by a digital circuit, which is assigned an address and which can control the VCO with a control voltage. This digital control circuit can be embedded onto a chip that includes the activation component and oscillator. Using amplitude modulation or phase shift keying to encode the address, an identifying signal is transmitted.

The signal generation component may include a distinct transmitter
30 component that serves to transmit the generated signal to a remote receiver, which may be internal or external to the patient, as reviewed in greater detail below. The transmitter component, when present, may take a number of different configurations, e.g., depending on the type of signal that is generated and is to be emitted. In certain embodiments, the transmitter component is made up of one or

more electrodes. In certain embodiments, the transmitter component is made up of one or more wires, e.g., in the form of antenna(e). In certain embodiments, the transmitter component is made up of one or more coils. As such, the signal transmitter may include a variety of different transmitters, e.g., electrodes, antennas (e.g., in the form of wires) coils, etc. In certain embodiments, the signal is transmitted either by one or two electrodes or by one or two wires. A two-electrode transmitter is a dipole; a one electrode transmitter forms a monopole. In certain embodiments, the transmitter only requires one diode drop of power. In some embodiments, the transmitter unit uses an electric dipole or electric monopole antenna to transmit signals.

FIG. 2 shows the detail of one implementation of an electronic circuit that can be employed in an identifier according to the present invention. On the left side are the two battery electrodes, metal 1 and metal 2 (**32** and **33**). These metals, when in contact with an electrolyte (produced upon contact with target site fluid, either alone or in combination with dried conductive medium precursor, as reviewed above), form a battery that provides power to an oscillator **61**, in this case shown as a schematic. The metal 1 **32** provides a low voltage, (ground) to the oscillator **61**. Metal 2 **33** provides a high voltage (V_{high}) to the oscillator **61**. As the oscillator **61** becomes operative, it generates a clock signal **62** and an inverted clock signal **63**, which are opposites of each other. These two clock signals go into the counter **64** which simply counts the number of clock cycles and stores the count in a number of registers. In the example shown here, an 8 bit counter is employed. Thus, the output of counter **64** begins with a value of "00000000," changes to "00000001" at the first clock cycle, and continues up to "11111111." The 8-bit output of counter **64** is coupled to the input of an address multiplexer (mux) **65**. In one embodiment, mux **65** contains an address interpreter, which can be hard-wired in the circuit, and generates a control voltage to control the oscillator **61**. Mux **65** uses the output of counter **64** to reproduce the address in a serial bit stream, which is further fed to the signal-transmission driving circuit. Mux **65** can also be used to control the duty-cycle of the signal transmission. In one embodiment, mux **65** turns on signal transmission only one sixteenth of the time, using the clock counts generated by counter **64**. Such a low duty cycle conserves power and also allows other devices to transmit without jamming their signals. The address of a given chip can be 8 bits, 16 bits

or 32 bits. Where desired, more than 8 bits may be used in a product, e.g., where the identifiers are employed with different types of pharmaceutical agents and each pharmaceutical is desired to have its own specific address.

According to one embodiment, mux **65** produces a control voltage, which encodes the address serially and is used to vary the output frequency of oscillator **61**. By example, when the control voltage is low, that is, when the serial address bit is at a 0, a 1 megahertz signal is generated by the oscillator. When the control voltage is high, that is, when the address bit is a 1, a 2 megahertz signal is generated the oscillator. Alternately, this can be 10 megahertz and 20 megahertz, or a phase shift keying approach where the device is limited to modulating the phase. The purpose of mux **65** is to control the frequency of the oscillator or an AC alternative embodiment of the amplified signal of oscillation.

The outputs of mux **65** are coupled to electrode drive **66** which can drive the electrodes to impose a differential potential to the solution, drive an oscillating current through a coil to generate a magnetic signal, or drive a single electrode to push or pull charge to or from the solution. In this manner, the device broadcasts the sequence of 0's and 1's which constitute the address stored in mux **65**. That address would be broadcast repeatedly, and would continue broadcasting until metal 1 or metal 2 (**32** and **33**) is consumed and dissolved in the solution, when the battery no longer operates.

Other configurations for the signal generation component are of course possible. Other configurations of interest include, but are not limited to, those described in PCT application serial no. PCT/US2006/016370 filed on April 28, 2006 and titled "Pharma-Informatics System"; PCT application serial no. PCT/US2007/022257 filed on October 17, 2007 and titled "In-vivo Low Voltage Oscillator for Medical Devices"; PCT application serial no. PCT/US2007/82563 filed on October 25, 2007 and titled "Controlled Activation Ingestible Identifier"; United States Patent Application Serial No. 11/776,480 filed July 11, 2007 entitled "Acoustic Pharma Informatics System"; and PCT application serial no. PCT/US2008/52845 filed on February 1, 2008 and titled "Ingestible Event Marker Systems"; the disclosures of which applications (and particularly signal generation components thereof) are herein incorporated by reference.

The identifiers may be fabricated using any convenient processing technology. In certain embodiments, planar processing protocols are employed to fabricate power sources having surface electrodes, where the surface electrodes include at least an anode and cathode at least partially on the same surface of a circuitry support element. In certain embodiments, planar processing protocols are employed in a wafer bonding protocol to produce a battery source. Planar processing techniques, such as Micro-Electro-Mechanical Systems (MEMS) fabrication techniques, including surface micromachining and bulk micromachining techniques, may be employed. Deposition techniques that may be employed in certain embodiments of fabricating the structures include, but are not limited to: electrodeposition (e.g., electroplating), cathodic arc deposition, plasma spray, sputtering, e-beam evaporation, physical vapor deposition, chemical vapor deposition, plasma enhanced chemical vapor deposition, etc. Material removal techniques included, but are not limited to: reactive ion etching, anisotropic chemical etching, isotropic chemical etching, planarization, e.g., via chemical mechanical polishing, laser ablation, electronic discharge machining (EDM), etc. Also of interest are lithographic protocols. Of interest in certain embodiments is the use of planar processing protocols, in which structures are built up and/or removed from a surface or surfaces of an initially planar substrate using a variety of different material removal and deposition protocols applied to the substrate in a sequential manner. Illustrative fabrication methods of interest are described in greater detail in copending PCT application serial no. PCT/US2006/016370; the disclosure of which is herein incorporated by reference.

Optional Physiologically Acceptable Carrier Component

Identifiers of the invention that include in-body power sources as described above may be present in (i.e., combined with) a physiologically acceptable carrier component, e.g., a composition or vehicle that aids in ingestion of the identifier and/or protects the identifier until it reaches the target site of interest. By "physiologically acceptable carrier component" is meant a composition, which may be a solid or fluid (e.g., liquid), which has is ingestible.

Common carriers and excipients, such as corn starch or gelatin, lactose, dextrose, sucrose, microcrystalline cellulose, kaolin, mannitol, dicalcium

phosphate, sodium chloride, and alginic acid are of interest. Disintegrators commonly used in the formulations of the invention include croscarmellose, microcrystalline cellulose, corn starch, sodium starch glycolate and alginic acid.

5 A liquid composition may comprise a suspension or solution of the compound or pharmaceutically acceptable salt in a suitable liquid carrier(s), for example, ethanol, glycerine, sorbitol, non-aqueous solvent such as polyethylene glycol, oils or water, with a suspending agent, preservative, surfactant, wetting agent, flavoring or coloring agent. Alternatively, a liquid formulation can be prepared from a reconstitutable powder. For example, a powder containing active
10 compound, suspending agent, sucrose and a sweetener can be reconstituted with water to form a suspension; and a syrup can be prepared from a powder containing active ingredient, sucrose and a sweetener.

A composition in the form of a tablet or pill can be prepared using any suitable pharmaceutical carrier(s) routinely used for preparing solid compositions.
15 Examples of such carriers include magnesium stearate, starch, lactose, sucrose, microcrystalline cellulose and binders, for example, polyvinylpyrrolidone. The tablet can also be provided with a color film coating, or color included as part of the carrier(s). In addition, active compound can be formulated in a controlled release dosage form as a tablet comprising a hydrophilic or hydrophobic matrix.

20 "Controlled release", "sustained release", and similar terms are used to denote a mode of active agent delivery that occurs when the active agent is released from the delivery vehicle at an ascertainable and controllable rate over a period of time, rather than dispersed immediately upon application or injection. Controlled or sustained release may extend for hours, days or months, and may
25 vary as a function of numerous factors. For the pharmaceutical composition of the present invention, the rate of release will depend on the type of the excipient selected and the concentration of the excipient in the composition. Another determinant of the rate of release is the rate of hydrolysis of the linkages between and within the units of the polyorthoester. The rate of hydrolysis in turn may be
30 controlled by the composition of the polyorthoester and the number of hydrolysable bonds in the polyorthoester. Other factors determining the rate of release of an active agent from the present pharmaceutical composition include particle size, acidity of the medium (either internal or external to the matrix) and physical and chemical properties of the active agent in the matrix.

A composition in the form of a capsule can be prepared using routine encapsulation procedures, for example, by incorporation of active compound and excipients into a hard gelatin capsule. Alternatively, a semi-solid matrix of active compound and high molecular weight polyethylene glycol can be prepared and
5 filled into a hard gelatin capsule; or a solution of active compound in polyethylene glycol or a suspension in edible oil, for example, liquid paraffin or fractionated coconut oil can be prepared and filled into a soft gelatin capsule.

Tablet binders that can be included are acacia, methylcellulose, sodium carboxymethylcellulose, poly-vinylpyrrolidone (Povidone), hydroxypropyl methyl-
10 cellulose, sucrose, starch and ethylcellulose. Lubricants that can be used include magnesium stearate or other metallic stearates, stearic acid, silicone fluid, talc, waxes, oils and colloidal silica.

Flavoring agents such as peppermint, oil of wintergreen, cherry flavoring or the like can also be used. Additionally, it may be desirable to add a coloring
15 agent to make the dosage form more attractive in appearance or to help identify the product.

Other components suitable for use in the formulations of the present invention can be found in Remington's Pharmaceutical Sciences, Mace Publishing Company, Philadelphia, Pa., 17th ed. (1985).

20

Optional Active Agent

In certain embodiments, the identifier is not associated with a pharmaceutically active agent. As such, the identifier, and any carrier or other component that make up the ingestible event marker, do not include an active
25 agent.

In yet other embodiments, the identifier is associated with an active agent, e.g., where the active agent is present in the carrier composition that includes the identifier. By "active agent/carrier component" is meant a composition, which may be a solid or fluid (e.g., liquid), which has an amount of active agent, e.g., a
30 dosage, present in a pharmaceutically acceptable carrier. The active agent/carrier component may be referred to as a "dosage formulation."

"Active agent" includes any compound or mixture of compounds which produces a physiological result, e.g., a beneficial or useful result, upon contact with a living organism, e.g., a mammal, such as a human. Active agents are

distinguishable from such components as vehicles, carriers, diluents, lubricants, binders and other formulating aids, and encapsulating or otherwise protective components. The active agent may be any molecule, as well as binding portion or fragment thereof, that is capable of modulating a biological process in a living
5 subject. In certain embodiments, the active agent may be a substance used in the diagnosis, treatment, or prevention of a disease or as a component of a medication. In certain embodiments, the active agent may be a chemical substance, such as a narcotic or hallucinogen, which affects the central nervous system and causes changes in behavior.

10 The active agent (i.e., drug) is capable of interacting with a target in a living subject. The target may be a number of different types of naturally occurring structures, where targets of interest include both intracellular and extracellular targets. Such targets may be proteins, phospholipids, nucleic acids and the like, where proteins are of particular interest. Specific proteinaceous
15 targets of interest include, without limitation, enzymes, e.g., kinases, phosphatases, reductases, cyclooxygenases, proteases and the like, targets comprising domains involved in protein-protein interactions, such as the SH2, SH3, PTB and PDZ domains, structural proteins, e.g., actin, tubulin, etc., membrane receptors, immunoglobulins, e.g., IgE, cell adhesion receptors, such
20 as integrins, etc., ion channels, transmembrane pumps, transcription factors, signaling proteins, and the like.

The active agent (i.e., drug) may include one or more functional groups necessary for structural interaction with the target, e.g., groups necessary for hydrophobic, hydrophilic, electrostatic or even covalent interactions, depending
25 on the particular drug and its intended target. Where the target is a protein, the drug moiety may include functional groups necessary for structural interaction with proteins, such as hydrogen bonding, hydrophobic-hydrophobic interactions, electrostatic interactions, etc., and may include at least an amine, amide, sulfhydryl, carbonyl, hydroxyl or carboxyl group, such as at least two of the
30 functional chemical groups.

Drugs of interest may include cyclical carbon or heterocyclic structures and/or aromatic or polyaromatic structures substituted with one or more of the above functional groups. Also of interest as drug moieties are structures found among biomolecules, including peptides, saccharides, fatty acids, steroids,

purines, pyrimidines, derivatives, structural analogs or combinations thereof. Such compounds may be screened to identify those of interest, where a variety of different screening protocols are known in the art.

The active agent may be derived from a naturally occurring or synthetic compound that may be obtained from a wide variety of sources, including libraries of synthetic or natural compounds. For example, numerous means are available for random and directed synthesis of a wide variety of organic compounds and biomolecules, including the preparation of randomized oligonucleotides and oligopeptides. Alternatively, libraries of natural compounds in the form of bacterial, fungal, plant and animal extracts are available or readily produced. Additionally, natural or synthetically produced libraries and compounds are readily modified through conventional chemical, physical and biochemical means, and may be used to produce combinatorial libraries. Known pharmacological agents may be subjected to directed or random chemical modifications, such as acylation, alkylation, esterification, amidification, etc. to produce structural analogs.

As such, the active agent may be obtained from a library of naturally occurring or synthetic molecules, including a library of compounds produced through combinatorial means, i.e., a compound diversity combinatorial library. When obtained from such libraries, the drug moiety employed will have demonstrated some desirable activity in an appropriate screening assay for the activity. Combinatorial libraries, as well as methods for producing and screening such libraries, are known in the art and described in: 5,741,713; 5,734,018; 5,731,423; 5,721,099; 5,708,153; 5,698,673; 5,688,997; 5,688,696; 5,684,711; 5,641,862; 5,639,603; 5,593,853; 5,574,656; 5,571,698; 5,565,324; 5,549,974; 5,545,568; 5,541,061; 5,525,735; 5,463,564; 5,440,016; 5,438,119; 5,223,409, the disclosures of which are herein incorporated by reference.

Broad categories of active agents of interest include, but are not limited to: cardiovascular agents; pain-relief agents, e.g., analgesics, anesthetics, anti-inflammatory agents, etc.; nerve-acting agents; chemotherapeutic (e.g., anti-neoplastic) agents; etc.

A variety of manufacturing protocols may be employed to produce compositions as described above, e.g., where an identifier is present in pharmaceutically acceptable carrier or vehicle, where the carrier or vehicle may

further include one or more active agents. In manufacturing such compositions, an identifier is stably associated with the pharmaceutical dosage form in some manner. By stably associated is meant that the identifier and the dosage form do not separate from each other, at least until administered to the subject in need thereof, e.g., by ingestion. The identifier may be stably associated with the pharmaceutical carrier/active agent component of the composition in a number of different ways. In certain embodiments, where the carrier/active agent component is a solid structure, e.g., such as a tablet or pill, the carrier/active agent component is produced in a manner that provides a cavity for the identifier. The identifier is then placed into the cavity and the cavity sealed, e.g., with a biocompatible material, to produce the final composition. For example, in certain embodiments a tablet is produced with a die that includes a feature which produces a cavity in the resultant compressed tablet. The identifier is placed into the cavity and the cavity sealed to produce the final tablet. In a variation of this embodiment, the tablet is compressed with a removable element, e.g., in the shape of a rod or other convenient shape. The removable element is then removed to produce a cavity in the tablet. The identifier is placed into the cavity and the cavity sealed to produce the final tablet. In another variation of this embodiment, a tablet without any cavity is first produced and then a cavity is produced in the tablet, e.g., by laser drilling. The identifier is placed into the cavity and the cavity sealed to produce the final tablet. In yet other embodiments, a tablet is produced by combining the identifier with subparts of the tablet, where the subparts may be pre-made subparts or manufactured sequentially. For example, in certain embodiments tablets are produced by first making a bottom half of the tablet, placing the signal generation element on a location of the bottom half of the tablet, and then placing top portion of the tablet over the bottom half and signal generation element to produce the final desired composition. In certain embodiments, a tablet is produced around an identifier such that the identifier is located inside of the produced tablet. For example, an identifier, which may or may not be encapsulated in a biocompatible compliant material, e.g., gelatin (to protect the signal generation element), is combined with carrier/active agent precursor, e.g., powder, and compressed or molded into a tablet in a manner such that the identifier is located at an internal position of the tablet. Instead of molding or compressing, the carrier/active agent component is, in

certain embodiments, sprayed onto an identifier in a manner that builds up the tablet structure. In yet another embodiment, the active agent/carrier component precursor may be a liquid formulation which is combined with the identifier and then solidified to produce the final composition. In yet other embodiments, pre-made tablets may be fitted with an identifier by stably attaching an identifier to the tablet. Of interest are protocols that do not alter the properties of the tablet, e.g., dissolution etc. For example, a gelatin element that snap fits onto one end of a tablet and has an identifier integrated with it is employed in certain embodiments. The gelatin element is colored in certain embodiments to readily identify tablets that have been fitted with the signal generation element. Where the composition has an active agent/carrier composition filled capsule configuration, e.g., such as a gelatin capsule filled configuration, an identifier may be integrated with a capsule component, e.g., top or bottom capsule, and the capsule filled with the active agent/carrier composition to produce the final composition. The above reviewed methods of manufacture are merely illustrative of the variety of different ways in which the compositions of the invention may be manufactured.

In certain embodiments, the identifiers are disrupted upon administration to a subject. As such, in certain embodiments, the compositions are physically broken, e.g., dissolved, degraded, eroded, etc., following delivery to a body, e.g., via ingestion, injection, etc. The compositions of these embodiments are distinguished from devices that are configured to be ingested and survive transit through the gastrointestinal tract substantially, if not completely, intact.

SYSTEMS

Also provided are systems that include the subject compositions. Systems of the subject invention include, in certain embodiments, one or more devices that include an in-body power source of the invention, e.g., an identifier as reviewed above, as well as a signal detection component, e.g., in the form of a receiver. The signal detection component may vary significantly depending on the nature of the signal that is generated by the signal generation element of the composition, e.g., as reviewed above.

Signal receivers of systems of embodiments of the invention are those that are configured to receive a signal from an identifier, e.g., to receive a signal emitted by an identifier upon contact of the identifier with the target physiological

site following ingestion of the identifier. The signal receiver may vary significantly depending on the nature of the signal that is generated by the signal generation element, e.g., as reviewed below. As such, the signal receiver may be configured to receive a variety of different types of signals, including but not limited to: RF signals, magnetic signals, conductive (near field) signals, acoustic signals, etc., as indicated above. In certain embodiments, the receiver is configured to receive a signal conductively from another component, e.g., the identifier, such that the two components use the body of the patient as a communication medium. As such, the signal that is transferred between identifier o and the receiver travels through the body, and requires the body as the conduction medium. The identifier emitted signal may be transmitted through and received from the skin and other body tissues of the subject body in the form of electrical alternating current (a.c.) voltage signals that are conducted through the body tissues. As a result, such embodiments do not require any additional cable or hard wire connection, or even a radio link connection for transmitting the sensor data from the autonomous sensor units to the central transmitting and receiving unit and other components of the system, since the sensor data are directly exchanged via the skin and other body tissues of the subject. This communication protocol has the advantage that the receivers may be adaptably arranged at any desired location on the body of the subject, whereby the receivers are automatically connected to the required electrical conductor for achieving the signal transmission, i.e., the signal transmission is carried out through the electrical conductor provided by the skin and other body tissues of the subject. In certain embodiments, the signal detection component is one that is activated upon detection of a signal emitted from an identifier. In certain embodiments, the signal receiver is capable of (i.e., configured to) simultaneously detecting multiple different signals, e.g., 2 or more, 5 or more, 10 or more, etc.

The signal receiver may include a variety of different types of signal receiver elements, where the nature of the receiver element necessarily varies depending on the nature of the signal produced by the signal generation element. In certain embodiments, the signal receiver may include one or more electrodes (e.g., 2 or more electrodes, 3 or more electrodes, includes multiple, e.g., 2 or more, 3 or more, 4 or more pairs of electrodes, etc.) for detecting signal emitted by the signal generation element. In certain embodiments, the receiver device will

be provided with two electrodes that are dispersed at a distance, e.g., a distance that allows the electrodes to detect a differential voltage. This distance may vary, and in certain embodiments ranges from about 0.1 to about 5 cm, such as from about 0.5 to about 2.5 cm, e.g., about 1 cm. In an alternative embodiment, a receiver that utilizes a single electrode is employed. In certain embodiments, the signal detection component may include one or more coils for detecting signal emitted by the signal generation element. In certain embodiments, the signal detection component includes an acoustic detection element for detecting signal emitted by the signal generation element. In certain embodiments, multiple pairs of electrodes (e.g., as reviewed above) are provided, for example to increase detection probability of the signal.

The signal receivers of interest include both external and implantable signal receivers. In external embodiments, the signal receiver is *ex vivo*, by which is meant that the receiver is present outside of the body during use. Where the receiver is implanted, the signal receiver is *in vivo*. The signal receiver is configured to be stably associated with the body, e.g., either *in vivo* or *ex vivo*, at least during the time that it receives the emitted signal from the IEM.

Signal receivers of interest include, but are not limited to, those receivers disclosed in: PCT application serial no. PCT/US2006/016370 filed on April 28, 2006 and titled "Pharma-Informatics System"; and PCT application serial no. PCT/US 2008/ 52845 filed on February 1, 2008 and titled "Ingestible Event Marker Systems"; the disclosures of which applications (and particularly signal receiver components thereof) are herein incorporated by reference.

In certain embodiments, the signal receiver is configured to provide data of a received signal to a location external to said subject. For example, the signal receiver may be configured to provide data to an external data receiver, e.g., which may be in the form of a monitor (such as a bedside monitor), a computer (e.g., PC or MAC), a personal digital assistant (PDA), phone, messaging device, smart phone, etc. In one embodiment, if a signal receiver failed to detect a signal indicating that a pill had been ingested, the signal receiver could transmit a reminder to take the pill to the subject's PDA or smart phone, which could then provide a prompt to the user to take the medication, e.g., a display or alarm on the PDA, by receiving a phone call on the smart phone (e.g., a recorded message) etc. The signal receiver may be configured to retransmit data of a

received signal to the location external to said subject. Alternatively, the signal receiver according may be configured to be interrogated by an external interrogation device to provide data of a received signal to an external location.

As such, in certain embodiments the systems include an external device
5 which is distinct from the receiver (which may be implanted or topically applied in certain embodiments), where this external device provides a number of functionalities. Such an apparatus can include the capacity to provide feedback and appropriate clinical regulation to the patient. Such a device can take any of a number of forms. By example, the device can be configured to sit on the bed
10 next to the patient, e.g., a bedside monitor. Other formats include, but are not limited to, PDAs, smart phones, home computers, etc. The device can read out the information described in more detail in other sections of the subject patent application, both from pharmaceutical ingestion reporting and from physiological sensing devices, such as is produced internally by a pacemaker device or a
15 dedicated implant for detection of the pill. The purpose of the external apparatus is to get the data out of the patient and into an external device. One feature of the external apparatus is its ability to provide pharmacologic and physiologic information in a form that can be transmitted through a transmission medium, such as a telephone line, to a remote location such as a clinician or to a central
20 monitoring agency.

METHODS

Aspects of the invention further include methods of using in-body devices that include in-body power sources of the invention. Generally, methods of the
25 invention will include placing the in-body device in some manner in the body of the subject, e.g., by implanting the device in a subject, by ingesting the device, etc. The devices may be employed with a variety of subjects. Generally such subjects are "mammals" or "mammalian," where these terms are used broadly to describe organisms which are within the class mammalia, including the orders
30 carnivore (e.g., dogs and cats), rodentia (e.g., mice, guinea pigs, and rats), and primates (e.g., humans, chimpanzees, and monkeys). In certain embodiments, the subjects will be humans. Following placement of the devices in the body of a subject, the devices are employed for a variety of purposes, e.g., to sense one or

more physiological parameters, to deliver one or more therapies, to mark a personal event of interest, etc.

In certain embodiments, the in body devices are ingestible devices, where the in body power source is part of an identifier of the device. In such
5 embodiments, the identifier is ingested and a signal emitted by the identifier is detected, e.g., with a receiver as described above. Such methods are further described in PCT application serial no. PCT/US2006/016370 filed on April 28, 2006 and titled "Pharma-Informatics System"; and PCT application serial no. PCT/ US US2008/ 52845 filed on February 1, 2008 and titled "Ingestible Event
10 Marker Systems"; the disclosures of which applications (and particularly signal receiver components thereof) are herein incorporated by reference.

UTILITY

Devices that include the in-body power sources of the invention may be
15 employed in a variety of different applications, including both therapeutic and non-therapeutic applications. Specific applications of interest include, but are not limited to: those applications described in PCT application serial no. PCT/US2006/016370 filed on April 28, 2006 and titled "Pharma-Informatics System"; and PCT application serial no. PCT/ US US2008/ 52845 filed on
20 February 1, 2008 and titled "Ingestible Event Marker Systems"; the disclosures of which applications (and particularly signal receiver components thereof) are herein incorporated by reference.

IEM in body devices of the invention may be employed in a variety of different applications, which applications may be both medical and non-medical in
25 nature. Different illustrative applications are now reviewed below in greater detail below.

Certain applications involve the use of IEMs by themselves to mark a personal event of interest, e.g., onset of a physiological parameter (such as a symptom(s) of interest), onset of an activity, etc. For example, in certain
30 embodiments, event markers are employed to mark the onset of a symptom of interest. In such instances, when an individual becomes aware of a symptom of interest, e.g., begins to feel flushed, nauseous, excited, etc., , e.g., the individual may ingest an IEM to mark the occurrence of the symptom of interest. For example, the patient may begin to not feel well, and ingest an event marker in

response to this ill feeling. Upon ingestion, the marker sends a signal to a receiver, which may then record receipt of the signal for further use, e.g., to combine with physiological data, etc. In certain embodiments, the received signal is employed to provide context for any physiological data that is obtained from the patient, e.g., by sensors on the receiver, from an implantable recorder, etc.

Another symptom of interest is pain. In these embodiments, the ingestible event marker may be employed as a pain marker. For example, where a patient is being monitored for pain, if a patient feels no pain, the patient may ingest a first type of marker. If the patient feels pain, the patient may ingest a second type of marker. Different types of markers may be differentiated, such as color coded, where desired, to assist in their identification and proper use by the patient. For example, markers to be ingested when the patient does not feel pain may be color coded blue, while markers that are to be ingested when the patient does have pain may be color coded yellow. Instead of having different types of markers, a protocol may be employed in which the amount of markers ingested, and therefore the signal obtained, e.g., from a single marker or two or more markers, is employed to denote scale of symptom of interest, such as pain. So, if an individual is having intense pain, the individual takes four of the positive pain pills at the same time, while in response to mild pain the individual may take only one marker.

In such embodiments, the onset of the symptom of interest, as marked by the ingestion of the event marker and detection of the signal by the receiver, may be employed as relevant point at which to begin recording one or more physiological parameters of interest, e.g., by using an implantable physiological monitor. In these instances, the emitted signal from the marker is received by the receiver, which then causes a physiological parameter recorder (such as a Reveal® Plus Insertable Loop Recorder (ILR), Medtronic Corporation) to begin recording data and saving the data, e.g., for later use. For example, an implantable physiological parameter recorder may have only a limited possible amount of time for recording (such as 42 minutes). In such situations, the data may be automatically overwritten unless somehow flagged or marked for protection. In the present methods, an IEM may be ingested to mark the onset of a symptom of interest, as perceived by the patient, and receiver upon receipt of the signal may act with the recorder to protect the data obtained around the time

of the signal (after, or even some time before) to be protected and not overwritten. The system may be further configured to work in response not only to the ingestion of the event marker, but also in response to physiological sensed parameters, e.g., pH. As such, the methods find use as an event recorder in
5 terms of flagging a diagnostic stream of information, and protecting it from being overwritten, so a physician can look at it at a later date.

In certain embodiments, the event marker provides the context for interpreting a given set of physiological data at a later time. For example, if one is employing an activity sensor and one co-administers and event marker with a
10 particular drug, one can note any change in activity that is brought about by that drug. If a drop in activity is observed after a person takes both the event marker and a drug, the drop indicates the drug is probably causing the person to reduce their activity, e.g., by making them feel sleepy or actually causing them to fall asleep. Such data may be employed to adjust the does of a drug or be the basis
15 for a decision to switch to an alternative medication.

In certain embodiments the event marker is employed to construct a database of multiple events. Such a database may be employed to find commonality between the multiple marked events. Simple or complex protocols for finding commonality among multiple marked events may be employed. For
20 example, multiple events may be averaged. Alternatively techniques such as impulse response theory may be employed, where such techniques provide information on what exactly are the common features in a set of multiple sensor streams that are tied to a particular event.

The IEM systems of the invention enable one to use subjective symptoms,
25 such as "I'm feeling funny," to impart context and background to obtained objective measures of what's really going on physiologically. So, if every time somebody felt abnormal they took an event marker, one could reference a database of the objective sensor data, and find common features in the database. Such an approach may be employed to discover the underlying causes
30 of the subjective feeling. For example, such an approach may be employed to determine that every time a person is feeling funny, they have some change in their blood pressure, and that link between a subjective symptom and objective physiological data can be used in their diagnosis. As such, a generalizable event marker brings context to discrete data from any other source. As such, use of the

oral medication event markers provides context for any other associated health monitoring information or health event.

In certain embodiments, the event marker can be an alert marker, such that ingestion of the marker causes an alarm signal to be sent from the patient, e.g., indicating that the patient needs medical assistance. For example, when a patient feels an onset of a symptom of interest, such as chest pain, shortness of breath, etc., the patient may ingest an event marker. The signal emitted from the event marker may be received by the receiver, which may then cause an alarm to be generated and distributed to a medical professional.

In certain embodiments, the event marker is employed to instigate or start a therapeutic action, e.g., activate an implantable pulse generator to deliver electrical therapy, activate an implanted drug delivery device to administer a dosage of drug, activate a physiological sensor to begin acquiring data, etc. For example, where a patient has a neural stimulator for treating migraines, upon perception of the onset of aura, the patient could ingest an IEM. The emitted signal would then activate neural stimulator into stimulus mode, and thereby cause the implant to deliver therapy. Alternatively, if one has an implanted drug deliver device, e.g., a device that delivers an oncotic agent, ingestion of the IEM could cause the implanted device to deliver the active agent.

In certain embodiments, the event marker is employed to deliver information to an implanted medical device in the patient. For example, an ingestible event marker may send a signal that includes update data for an implanted medical devices, such as firmware upgrade data for an implantable pulse generator, e.g., a pace maker. In such instances, the signal may include the upgrade code which is broadcast from the IEM conductively to the medical device, where upon receipt of the signal and code, the firmware of the medical device is upgraded.

Other applications where event markers may be employed by themselves is to mark or note the start of non-medical personal event, such as a commute time, the start of an exercise regimen, sleep time, smoking (e.g., so one can log how much one smokes) etc.

As indicated above, embodiments of the invention are characterized in that the event markers are co-ingested with another composition of matter, e.g., a pharmaceutical composition, food, etc, where the event marker may or may not

be present in the same composition as the co-ingested matter. For example, the event markers may be employed to track ingesting a pharmaceutical agent, where one co-administers the marker with the drug of interest. Applications where co-administration of a drug and marker is of interest include, but are not limited to, clinical studies, titration of medicine, e.g., blood pressure medicine, etc. Where desired, the IEM could be provided as just another pill when the fill at the pharmacy essentially.

Instead of co-ingesting the event marker with another composition, e.g., a drug, food, etc., the marker and the other composition may be compounded together, e.g., by the end user. For example, an IEM in the form of a capsule can be opened by the end user and filled with a pharmaceutical composition. The resultant compounded capsule and active agent may then be ingested by the end user. Instead of an end user, the pharmacist or a health care provider may perform the compounding step.

In yet other embodiments, the marker is present already compounded with the other composition at the source of manufacture of the other composition, e.g., the manufacturer or producer of a pharmaceutical composition. An example of such compositions includes those described in PCT application serial no. PCT/US2006/ 016370; the disclosure of which is herein incorporated by reference.

In certain embodiments, the IEMs of the invention are employed to allow one to look at, on an individual basis, what a given result is with respect to what drugs an individual is taking versus their impact on indicators that correlate to the desired effect. For example, where a given patient is prescribed a regimen of multiple pharmaceutical agents and there are multiple different physiological parameters that are monitored as indicators of how the patient is responding to the prescribed therapeutic regimen, a given drug as marked by a given marker can be assessed in terms of its impact on a one or more of the physiological parameters of interest. Following this assessment, adjustments can be made accordingly. In this manner, automation may be employed to tailor therapies based on individual responses. For example, where a patient is undergoing oncotic therapy, the event marker can be used to provide real time context to obtained physiological parameter data. The resultant annotated real time data

can be used to make decisions about whether or not to continue therapy, or change to a new therapy.

In certain embodiments, a dosing event (as marked by the IEM) is correlated with sensor data to develop a profile for how a given drug acts, e.g., in terms of a pharmacokinetic and/or pharmacodynamic model. Sensors are employed with the IEM marking of the dosing event to obtain a pharmacokinetic model. Once one has the pharmacokinetic model, one can use the dosing event to drive that model and predict serum drug levels and response. One might find, as determined from various sensors, that this patient is not doing so well at this time. One might look back at the pharmacokinetic model and say the levels of this drug in the blood are getting low when the patient is sensed as not doing well. This data is then used to make a determination to increase the dosing frequency or increase the dose at a given dosing event. The event marker provides a way to develop a model and then apply it.

Where the IEMs are co-administered with a pharmaceutical agent, e.g., as two separate compositions or a single composition (as described above), the systems of the invention, such as the one shown in FIG. 12, enable a dynamic feedback and treatment loop of tracking medication timing and levels, measuring the response to therapy, and recommending altered dosing based on the physiology and molecular profiles of individual patients. For example, a symptomatic heart failure patient takes multiple drugs daily, primarily with the goal of reducing the heart's workload and improving patient quality of life. Mainstays of therapy include angiotensin converting enzyme (ACE) inhibitors, β -blockers and diuretics. For pharmaceutical therapy to be effective, it is vital that patients adhere to their prescribed regimen, taking the required dose at the appropriate time. Multiple studies in the clinical literature demonstrate that more than 50% of Class II and III heart failure patients are not receiving guideline-recommended therapy, and, of those who are titrated appropriately, only 40-60% adhere to the regimen. With the subject systems, heart failure patients can be monitored for patient adherence to therapy, and adherence performance can be linked to key physiologic measurements, to facilitate the optimization of therapy by physicians.

In certain embodiments, the systems of the invention may be employed to obtain an aggregate of information that includes sensor data and administration data. For example, one can combine the heart rate, the respiration rate, multi-axis acceleration data, something about the fluid status, and something about temperature, and derive indices that will inform about the total activity of the subject, that can be used to generate a physiological index, such as an activity index. For instance, when there is a rise in temperature, heart rate goes up a bit, and respiration speeds up, which may be employed as an indication that the person is being active. By calibrating this, the amount of calories the person is burning at that instant could be determined. In another example, a particular rhythmic set of pulses or multi-axis acceleration data can indicate that a person is walking up a set of stairs, and from that one can infer how much energy they are using. In another embodiment, body fat measurement (e.g. from impedance data) could be combined with an activity index generated from a combination of measured biomarkers to generate a physiological index useful for management of a weight loss or cardiovascular health program. This information can be combined with cardiac performance indicators to get a good picture of overall health, which can be combined with pharmaceutical therapy administration data. In another embodiment, one might find for example that a particular pharmaceutical correlates with a small increase in body temperature, or a change in the electrocardiogram. One can develop a pharmacodynamic model for the metabolism of the drug, and use the information from the receiver to essentially fit the free parameters in that model to give much more accurate estimation of the levels actually present in the serum of the subject. This information could be fed back to dosing regimes. In another embodiment, one can combine information from a sensor that measures uterine contractions (e.g. with a strain gauge) and that also monitors fetal heart rate, for use as a high-risk pregnancy monitor.

In certain embodiments, the subject specific information that is collected using the systems of the invention may be transmitted to a location where it is combined with data from one or more additional individuals to provide a collection of data which is a composite of data collected from 2 or more, e.g., 5 or more, 10 or more, 25 or more, 50 or more, 100 or more, 1000 or more, etc., individuals. The composite data can then be manipulated, e.g., categorized according to different criteria, and made available to one or more different types of groups,

e.g., patient groups, health care practitioner groups, etc., where the manipulation of data may be such as to limit the access of any given group to the type of data that group can access. For example, data can be collected from 100 different individuals that are suffering from the same condition and taking the same medication. The data can be processed and employed to develop easy to follow displays regarding patient compliance with a pharmaceutical dosage regimen and general health. Patient members of the group can access this information and see how their compliance matches with other patient members of the group, and whether they are enjoying the benefits that others are experiencing. In yet another embodiment, doctors can also be granted access to a manipulation of the composite data to see how their patients are matching up with patients of other doctors, and obtain useful information on how real patients respond to a given therapeutic treatment regiment. Additional functionalities can be provided to the groups given access to the composite data, where such functionalities may include, but are not limited to: ability to annotate data, chat functionalities, security privileges, etc.

The inventive pharmacokinetic model allows for drug dosing regimens to be adjusted in real time in response to varying serum levels in the body. The pharmacokinetic model can predict or measure the serum level of a given medication in the body. This data can then be used to calculate when the next dose of medication should be taken by the patient. An alarm can be triggered at that time to alert the patient to take a dose. If the serum level remains high, an alarm can be triggered to alert the patient not to take the next dose at the originally prescribed time interval. The pharmacokinetic model can be used in conjunction with a medication ingestion monitoring system that includes an IEM, such as that described above. Data from this system can be incorporated into the model, as well as population data, measured data, and data input by the patient. Utilizing data from multiple sources, a very powerful and accurate tool can be developed.

In some embodiments, the data gathered by the receiver can be used directly by the pharmacokinetic model to determine when a medication was administered, what medication it was and in what amount. This information can be used to calculate an estimate of the serum level of the medication in the patient. Based on the calculated serum level, the pharmacokinetic model can

send an alert to the patient to say either that the serum level is too high and is near or above the toxic level, or that the serum level is too low and they should take another dose. The pharmacokinetic model can be run on the implanted receiver itself or on an external system which receives data from the implanted

5 receiver.

A simple form of the pharmacokinetic model can assume that every patient is the same, and use average population data to model the serum level. A more complex and more accurate model can be obtained by inputting other information about the patient. This information can be inputted by the user, such as a
10 physician, or gathered by the receiver from associated sensors. Information that can be used to adjust the model include other medications being taken, diseases the patient suffers from, patient's organ function, enzyme levels, metabolism, body weight, and age, among other factors. Information can also be inputted by the patient themselves, such as if they feel hypoglycemic, or have pain or
15 dizziness. This can be used as further evidence to validate the predictions of the model.

Examples of food applications include the following. In certain disease conditions, such as diabetes, it can be important what a patient ate and when. In such instances, event markers of the invention are keyed or linked to the type of
20 food a patient eats. For example, one can have a set of event markers for different food items, and one can co-administer them with the food items. From the resultant data, one can do a complete individual metabolic profile on an individual. One knows how many calories the patient is consuming. By obtaining activity and heart rate and ambient temperature versus body temperature data,
25 one can calculate how many calories one is expending. As a result, guidance can be provided to the patient as to what foods to eat and when. Non disease patients may also track food ingestion in this manner. For example, athletes adhering to a strict training diet may employ IEMs to better monitor food ingestion and the effect of the food ingestion on one or more physiological parameters of
30 interest.

As reviewed in the above discussion, IEM systems of the invention find use in both therapeutic and non-therapeutic applications. In therapeutic applications, the IEM may or may not be compounded with a pharmaceutically active agent. In those embodiments where the IEM is compounded with active

agent, the resultant compounded composition may be viewed as a pharma-informatics enabled pharmaceutical composition.

In such pharma-informatics embodiments, an effective amount of a composition that includes an IEM and an active agent is administered to a subject in need of the active agent present in the composition, where "effective amount" means a dosage sufficient to produce the desired result, e.g. an improvement in a disease condition or the symptoms associated therewith, the accomplishment of a desired physiological change, etc. The amount that is administered may also be viewed as a therapeutically effective amount. A "therapeutically effective amount" means the amount that, when administered to a subject for treating a disease, is sufficient to effect treatment for that disease.

The composition may be administered to the subject using any convenient means capable of producing the desired result, where the administration route depends, at least in part, on the particular format of the composition, e.g., as reviewed above. As reviewed above, the compositions can be formatted into a variety of formulations for therapeutic administration, including but not limited to solid, semi solid or liquid, such as tablets, capsules, powders, granules, ointments, solutions, suppositories and injections. As such, administration of the compositions can be achieved in various ways, including, but not limited to: oral, buccal, rectal, parenteral, intraperitoneal, intradermal, transdermal, intracheal, etc., administration. In pharmaceutical dosage forms, a given composition may be administered alone or in combination with other pharmaceutically active compounds, e.g., which may also be compositions having signal generation elements stably associated therewith.

The subject methods find use in the treatment of a variety of different conditions, including disease conditions. The specific disease conditions treatable by with the subject compositions are as varied as the types of active agents that can be present in the subject compositions. Thus, disease conditions include, but are not limited to: cardiovascular diseases, cellular proliferative diseases, such as neoplastic diseases, autoimmune diseases, hormonal abnormality diseases, infectious diseases, pain management, and the like.

By treatment is meant at least an amelioration of the symptoms associated with the disease condition afflicting the subject, where amelioration is used in a broad sense to refer to at least a reduction in the magnitude of a parameter, e.g.

symptom, associated with the pathological condition being treated. As such, treatment also includes situations where the pathological condition, or at least symptoms associated therewith, are completely inhibited, e.g. prevented from happening, or stopped, e.g. terminated, such that the subject no longer suffers from the pathological condition, or at least the symptoms that characterize the pathological condition. Accordingly, "treating" or "treatment" of a disease includes preventing the disease from occurring in an animal that may be predisposed to the disease but does not yet experience or exhibit symptoms of the disease (prophylactic treatment), inhibiting the disease (slowing or arresting its development), providing relief from the symptoms or side-effects of the disease (including palliative treatment), and relieving the disease (causing regression of the disease). For the purposes of this invention, a "disease" includes pain.

In certain embodiments, the subject methods, as described above, are methods of managing a disease condition, e.g., over an extended period of time, such as 1 week or longer, 1 month or longer, 6 months or longer, 1 year or longer, 2 years or longer, 5 years or longer, etc. The subject methods may be employed in conjunction with one or more additional disease management protocols, e.g., electrostimulation based protocols in cardiovascular disease management, such as pacing protocols, cardiac resynchronization protocols, etc; lifestyle, such a diet and/or exercise regimens for a variety of different disease conditions; etc.

In certain embodiments, the methods include modulating a therapeutic regimen based data obtained from the compositions. For example, data may be obtained which includes information about patient compliance with a prescribed therapeutic regimen. This data, with or without additional physiological data, e.g., obtained using one or more sensors, such as the sensor devices described above, may be employed, e.g., with appropriate decision tools as desired, to make determinations of whether a given treatment regimen should be maintained or modified in some way, e.g., by modification of a medication regimen and/or implant activity regimen. As such, methods of invention include methods in which a therapeutic regimen is modified based on signals obtained from the composition(s).

In certain embodiments, also provided are methods of determining the history of a composition of the invention, where the composition includes an

active agent, an identifier element and a pharmaceutically acceptable carrier. In certain embodiments where the identifier emits a signal in response to an interrogation, the identifier is interrogated, e.g., by a wand or other suitable interrogation device, to obtain a signal. The obtained signal is then employed to
5 determine historical information about the composition, e.g., source, chain of custody, etc.

In certain embodiments, a system is employed that is made up of a multiple different IEMs, e.g., 2 or more distinct IEMs, 3 or more distinct IEMs, 4 or more distinct IEMs, etc., including 5 or more, 7 or more, 10 or more distinct
10 IEMs. The distinct IEMs may be configured to provide distinguishable signals, e.g., where the signals may be distinguishable in terms of nature of the signal itself, in terms of timing of emission of the signal, etc. For example, each IEM in such sets may emit a differently coded signal. Alternatively, each IEM may be configured to emit the signal at a different physiological target site, e.g., where
15 each IEM is configured to be activated at a different target physiological site, e.g., where an first IEM is activated in the mouth, a second is activated in the esophagus, a third is activated in the small intestine and a fourth is activated in the large intestine. Such sets of multiple different distinguishable IEMs find use in a variety of different applications. For example, where one has the above
20 described 4 IEM set, one can use the set in a diagnostic application to determine function of the digestive system, e.g., motility through the digestive tract, gastric emptying etc. For example, by noting when each IEM emits its respective signal, a plot of signal time may be generated from which information regarding digestive tract functioning may be obtained.

25 The present invention provides the clinician an important new tool in their therapeutic armamentarium: automatic detection and identification of pharmaceutical agents actually delivered into the body. The applications of this new information device and system are multi-fold. Applications include, but are not limited to: (1) monitoring patient compliance with prescribed therapeutic
30 regimens; (2) tailoring therapeutic regimens based on patient compliance; (3) monitoring patient compliance in clinical trials; (4) monitoring usage of controlled substances; and the like. Each of these different illustrative applications is reviewed in greater detail below in copending PCT Application Serial No.

PCT/US2006/016370; the disclosure of which is herein incorporated by reference.

Additional applications in which the subject systems find use include those described in U.S. Patent No. 6,804,558, the disclosure of which is herein incorporated by reference. For example, the subject systems may be used in a medical information communication system which permits monitoring the performance of an implantable medical device (IMD) implanted within a body of a patient, monitoring the health of the patient, and/or remotely delivering a therapy to the patient through the IMD. A signal receiver of the invention, e.g., in an external format such as a bandaid or implanted format, communicates with the IMD and is capable of bi-directional communication with a communication module, a mobile telephone and/or a Personal Data Assistant (PDA) located outside the patient's body. The system may comprise the IMD, the signal receiver with the communication module and/or a mobile telephone and/or a PDA, a remote computer system, and a communication system capable of bi-directional communication, where the communication module, the mobile telephone and/or the PDA are capable of receiving information from the IMD or relaying information thereto via the signal receiver, which is internal or external to the patient, as reviewed above.

Additional applications in which receivers of the invention may find use include, but are not limited to: fertility monitoring, body fat monitoring, satiety monitoring, satiety control, total blood volume monitoring, cholesterol monitoring, smoking detecting, etc.

KITS

Also provided are kits that include one or more in-body devices of the invention. Kits may include one or more in-body devices, e.g., as described above. In those embodiments having multiple in body devices, such may be packaged in a single container, e.g., a single tube, bottle, vial, and the like, or one or more dosage amounts may be individually packaged such that certain kits may have more than one container of an in body device. In certain embodiments the kits may also include a signal receiving element, as reviewed above. In certain embodiments, the kits may also include an external monitor device, e.g., as described above, which may provide for communication with a remote location,

e.g., a doctor's office, a central facility etc., which obtains and processes data obtained about the usage of the composition.

The subject kits may also include instructions for how to practice the subject methods using the components of the kit. The instructions may be recorded on a suitable recording medium or substrate. For example, the instructions may be printed on a substrate, such as paper or plastic, etc. As such, the instructions may be present in the kits as a package insert, in the labeling of the container of the kit or components thereof (i.e., associated with the packaging or sub-packaging) etc. In other embodiments, the instructions are present as an electronic storage data file present on a suitable computer readable storage medium, e.g. CD-ROM, diskette, etc. In yet other embodiments, the actual instructions are not present in the kit, but means for obtaining the instructions from a remote source, e.g. via the internet, are provided. An example of this embodiment is a kit that includes a web address where the instructions can be viewed and/or from which the instructions can be downloaded. As with the instructions, this means for obtaining the instructions is recorded on a suitable substrate.

Some or all components of the subject kits may be packaged in suitable packaging to maintain sterility. In many embodiments of the subject kits, the components of the kit are packaged in a kit containment element to make a single, easily handled unit, where the kit containment element, e.g., box or analogous structure, may or may not be an airtight container, e.g., to further preserve the sterility of some or all of the components of the kit.

It is to be understood that this invention is not limited to particular embodiments described, as such may vary. It is also to be understood that the terminology used herein is for the purpose of describing particular embodiments only, and is not intended to be limiting, since the scope of the present invention will be limited only by the appended claims.

Where a range of values is provided, it is understood that each intervening value, to the tenth of the unit of the lower limit unless the context clearly dictates otherwise, between the upper and lower limit of that range and any other stated or intervening value in that stated range, is encompassed within the invention. The upper and lower limits of these smaller ranges may independently be

included in the smaller ranges and are also encompassed within the invention, subject to any specifically excluded limit in the stated range. Where the stated range includes one or both of the limits, ranges excluding either or both of those included limits are also included in the invention.

5 Unless defined otherwise, all technical and scientific terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs. Although any methods and materials similar or equivalent to those described herein can also be used in the practice or testing of the present invention, representative illustrative methods and materials are
10 now described.

All publications and patents cited in this specification are herein incorporated by reference as if each individual publication or patent were specifically and individually indicated to be incorporated by reference and are incorporated herein by reference to disclose and describe the methods and/or
15 materials in connection with which the publications are cited. The citation of any publication is for its disclosure prior to the filing date and should not be construed as an admission that the present invention is not entitled to antedate such publication by virtue of prior invention. Further, the dates of publication provided may be different from the actual publication dates which may need to be
20 independently confirmed.

It is noted that, as used herein and in the appended claims, the singular forms "a", "an", and "the" include plural referents unless the context clearly dictates otherwise. It is further noted that the claims may be drafted to exclude any optional element. As such, this statement is intended to serve as antecedent
25 basis for use of such exclusive terminology as "solely," "only" and the like in connection with the recitation of claim elements, or use of a "negative" limitation.

Certain ranges have been presented herein with numerical values being preceded by the term "about." The term "about" is used herein to provide literal support for the exact number that it precedes, as well as a number that is near to
30 or approximately the number that the term precedes. In determining whether a number is near to or approximately a specifically recited number, the near or approximating unrecited number may be a number which, in the context in which it is presented, provides the substantial equivalent of the specifically recited number.

As will be apparent to those of skill in the art upon reading this disclosure, each of the individual embodiments described and illustrated herein has discrete components and features which may be readily separated from or combined with the features of any of the other several embodiments without departing from the scope or spirit of the present invention. Any recited method can be carried out in the order of events recited or in any other order which is logically possible.

Although the foregoing invention has been described in some detail by way of illustration and example for purposes of clarity of understanding, it is readily apparent to those of ordinary skill in the art in light of the teachings of this invention that certain changes and modifications may be made thereto without departing from the spirit or scope of the appended claims.

Accordingly, the preceding merely illustrates the principles of the invention. It will be appreciated that those skilled in the art will be able to devise various arrangements which, although not explicitly described or shown herein, embody the principles of the invention and are included within its spirit and scope. Furthermore, all examples and conditional language recited herein are principally intended to aid the reader in understanding the principles of the invention and the concepts contributed by the inventors to furthering the art, and are to be construed as being without limitation to such specifically recited examples and conditions. Moreover, all statements herein reciting principles, aspects, and embodiments of the invention as well as specific examples thereof, are intended to encompass both structural and functional equivalents thereof. Additionally, it is intended that such equivalents include both currently known equivalents and equivalents developed in the future, i.e., any elements developed that perform the same function, regardless of structure. The scope of the present invention, therefore, is not intended to be limited to the exemplary embodiments shown and described herein. Rather, the scope and spirit of present invention is embodied by the appended claims.

It is noted that, as used herein and in the appended claims, the singular forms “a”, “an”, and “the” include plural referents unless the context clearly dictates otherwise. It is further noted that the claims may be drafted to exclude any optional element. As such, this statement is intended to serve as antecedent basis for use of such exclusive terminology as “solely,” “only” and the like in connection with the recitation of claim elements, or use of a “negative” limitation.

As will be apparent to those of skill in the art upon reading this disclosure, each of the individual embodiments described and illustrated herein has discrete components and features which may be readily separated from or combined with the features of any of the other several embodiments without departing from the scope or spirit of the present invention. Any recited method can be carried out in the order of events recited or in any other order which is logically possible.

Although the foregoing invention has been described in some detail by way of illustration and example for purposes of clarity of understanding, it is readily apparent to those of ordinary skill in the art in light of the teachings of this invention that certain changes and modifications may be made thereto without departing from the spirit or scope of the appended claims.

Accordingly, the preceding merely illustrates the principles of the invention. It will be appreciated that those skilled in the art will be able to devise various arrangements which, although not explicitly described or shown herein, embody the principles of the invention and are included within its spirit and scope. Furthermore, all examples and conditional language recited herein are principally intended to aid the reader in understanding the principles of the invention and the concepts contributed by the inventors to furthering the art, and are to be construed as being without limitation to such specifically recited examples and conditions. Moreover, all statements herein reciting principles, aspects, and embodiments of the invention as well as specific examples thereof, are intended to encompass both structural and functional equivalents thereof. Additionally, it is intended that such equivalents include both currently known equivalents and equivalents developed in the future, i.e., any elements developed that perform the same function, regardless of structure. The scope of the present invention, therefore, is not intended to be limited to the exemplary embodiments shown and described herein. Rather, the scope and spirit of present invention is embodied by the appended claims.

WHAT IS CLAIMED IS:

1. An in-body power source comprising:
 - 5 (a) a solid support;
 - (b) a first high surface electrode present on a surface of said solid support; and
 - (c) a second electrode.
- 10 2. The in-body power source according to Claim 1, wherein said solid support comprises a semiconductor material.
3. The in-body power source according to Claim 2, wherein said solid support comprises an integrated circuit.
- 15 4. The in-body power source according to Claim 1, wherein said first high surface area electrode is a cathode.
5. The in-body power source according to Claim 1, wherein said first high
20 surface area electrode is an anode.
6. The in-body power source according to Claim 1, wherein said second electrode is present on a surface of said solid support.
- 25 7. The in-body power source according to Claim 6, wherein said first and second electrodes are present on a same surface of said solid support.
8. The in-body power source according to Claim 6, wherein said first and second electrodes are present on opposite surfaces of said solid support.
- 30 9. The in-body power source according to Claim 8, wherein said high surface area electrode comprises an active electrode material present on a porous electrode under-layer.

10. The in-body power source according to Claim 9, wherein said porous electrode under-layer is electrodeposited.
11. The in-body power source according to Claim 9, wherein said porous
5 electrode under-layer is produced by cathodic arc.
12. The in-body power source according to Claim 9, wherein said porous electrode under-layer is produced using electrophoretic deposition.
- 10 13. The in-body power source according to Claim 1, wherein said in body power source is configured to emit a detectable signal upon contact with a target physiological site.
14. The in-body power source according to Claim 13, wherein said in body
15 power source is present in a pharmaceutically acceptable carrier composition.
15. The in-body power source according to Claim 14, wherein said pharmaceutically acceptable carrier composition is a tablet.
- 20 16. The in-body power source according to Claim 14, wherein said pharmaceutically acceptable carrier composition is a capsule.
17. A system comprising:
 (a) an in-body power source according to any of Claims 13 to 16; and
25 (b) a receiver for detecting a signal produced by said identifier.
18. The system according to Claim 17, wherein said receiver is an in vivo receiver.
- 30 19. The system according Claim 17, wherein said receiver is an ex vivo receiver.
20. The system according to any of Claims 17 to 19, wherein said system further comprises at least one of a data storage element, a data processing

element, a data display element, data transmission element, a notification mechanism, and a user interface.

21. A method comprising:

- 5 ingesting an in-body power source according to any of Claims 13 to 16;
and
 detecting a signal emitted by said in body power source.

22. A kit comprising:

- 10 an in-body power source according to any of Claims 1 to 16.

23. The kit according to Claim 22, wherein said kit comprises a plurality of said in-body power sources.

- 15 24. The kit according to Claim 22, wherein said kit further comprises a receiver.

25. The kit according to Claim 22, wherein said kit further comprises at least one of a data storage element, a data processing element, a data display
20 element, data transmission element, a notification mechanism, and a user interface.