

- 1 -

BLEACHING PROCESS AND COMPOSITION

The present application relates to an improved process for carrying out bleaching and/or limescale
5 removal at a surface.

The use of oxygen bleaches in compositions for bleaching household surfaces has been known for a long time and many such compositions are available. However a
10 common difficulty in formulating such a composition is to ensure that it remains stable during storage but is sufficiently active on use. This is particularly difficult to achieve in liquid bleaching compositions. Many solutions have been proposed to this problem but
15 most of these require the use of expensive stabilising components or of complex formulation processes.

One solution has been to formulate liquid peroxygen bleaches at pHs between about 3 and 7 to produce a stable
20 composition, but in practice such compositions do not provide sufficient bleaching power to be useful for many household situations. Attempts have therefore also been made to formulate liquid peroxygen bleach compositions at pHs above this range to improve the bleaching power.
25 However these generally require expensive stabilising compounds to prevent loss of activity after manufacturing.

The present invention provides a peroxide bleach
30 product which has acceptable stability after manufacture, but which is capable of providing effective bleaching power when used by the consumer.

-2-

Commercial products capable of removing limescale from domestic surfaces are well known. Most of these products are based on acids which simply dissolve the limescale. Many surfaces require both limescale removal and bleaching, but no commercially available products are truly capable of both functions.

Furthermore, it would be convenient to the consumer to purchase one product which could be used either for limescale removal or bleaching as required, even when both functions are not required simultaneously.

The present invention provides a product which is capable of carrying out effective bleaching and/or limescale removal at a surface.

According to the invention, there is provided a process for bleaching and/or providing limescale removal at a surface, comprising applying to that surface an aqueous composition of hydrogen peroxide or an organic peracid, which composition has a pH of 2 or less and comprises a mixture of:

a) an aqueous composition comprising hydrogen peroxide or an organic peracid having a pH of greater than 2 but less than 7 (hereinafter component (a)), and

b) an acidic composition (hereinafter component (b)),

wherein components (a) and (b) are mixed not more than two hours before being applied to the surface requiring bleaching and/or limescale removal.

Compositions suitable for carrying out the invention may be provided in ready-to-use form or, preferably, may

be provided as separate components suitable for mixing by the consumer. Where the compositions are suitable for mixing they may be mixed either directly at the surface or remote from the surface before application.

5

According to a further aspect of the invention, there is provided a process for preparing an aqueous bleaching and/or limescale removing composition having a pH of 2 or less by mixing

10

a) an aqueous composition comprising hydrogen peroxide or an organic peracid having a pH of greater than 2 but less than 7 (hereinafter component (a)), and

15

b) an acidic composition (hereinafter component (b)),

wherein components (a) and (b) are mixed not more than two hours before being applied to the surface requiring bleaching and/or limescale removal.

20

The organic peracids are preferably compounds of the formula XC(O)OOH , wherein X is H or $\text{CH}_3(\text{CH}_2)_n$ and n is from 0 to 8, most preferably peracetic acid (n=0), peroxy propionic acid (n=1) or peroxy hexanoic acid (n=4).

25

By "acidic composition" is meant a composition comprising at least one acid (in liquid or solid form), such that when mixed in suitable proportions with the aqueous composition comprising hydrogen peroxide or an organic peracid the resultant mixture has a pH of 2 or less.

30

Component (a) preferably comprises hydrogen peroxide or peracetic acid.

35

-4-

Component (b) may be a solid (ie granular or powder) acidic composition or, preferably, an aqueous liquid acidic composition.

5 Where component (b) is an aqueous liquid, it preferably comprises hydrochloric acid, sulphamic acid, tartaric acid, phosphoric acid, oxalic acid, citric acid or salicylic acid; most preferably hydrochloric acid, sulphuric acid, phosphoric acid or citric acid.

10

Where component (b) is solid, it preferably comprises tartaric acid, phosphoric acid, ascorbic acid, oxalic acid, citric acid or salicylic acid; most preferably phosphoric acid or citric acid.

15

In accordance with the invention, the two components (a) and (b) may be mixed in any suitable proportions, depending upon their initial concentrations, suitably such that the finally applied mixture comprises 0.01-30% w/w of hydrogen peroxide or an organic peracid.
20 Preferably, the ratio of component (a) to component (b) is from 10:1 to 1:10, most preferably from 2:1 to 1:2.

It is preferred that the two components (a) and (b)
25 are mixed no more than 10 minutes before application to the surface requiring bleaching and/or limescale removal.

It is most preferred that the two components (a) and (b) are mixed at the surface requiring bleaching and/or
30 limescale removal, so that the improved bleaching effect may occur immediately.

In this aspect component (a) may be applied to the surface followed by component (b) or vice versa.
35 Alternatively (and preferably) components (a) and (b) are applied to the surface requiring bleaching and/or limescale removal substantially simultaneously.

- 5 -

According to a preferred embodiment of the present invention, the concentration of hydrogen peroxide or organic peracid in the composition immediately after
5 mixing is from 0.01 to 10% w/w. This would mean for example in a 1:1 mix of component (a) to (b) that component (a) prior to the mixing would contain from 0.02 to 20% w/w of hydrogen peroxide or an organic peracid.

10 Where component (a) comprises hydrogen peroxide it is most preferred that the concentration of hydrogen peroxide in the mixture immediately after mixing should be from 1.5 to 5% w/w. For example, if a 1:1 mixture of components (a) and (b) is to be mixed, then component (a)
15 should comprise from 3 to 10% w/w hydrogen peroxide.

The concentration of the acid in component (b) will be chosen such that the pH of the mixture of components (a) and (b) will be 2 or less. Accordingly this will
20 depend upon the acid chosen, the proportion of components (a) and (b) to be mixed, the initial pH of the component (a), and the intended pH of the mixture of components (a) and (b).

25 The process of the present invention alleviates the need to use further stabilising components when preparing commercial products.

The compositions suitable for use in the process
30 according to the invention may further include any other conventional additives known to the art. Examples of these include fragrances, surfactants (for example anionic, cationic, nonionic, amphoteric or mixtures thereof), thickeners, dyes, sequesterants, chelating
35 agents, germicides, preservatives, corrosion inhibitors or antioxidants. Most preferably the compositions

-6-

suitable for carrying out the present invention will contain at least one of the following:

- an anionic surfactant (e.g. sodium xylene sulphonate),
- 5 - a nonionic surfactant (e.g. an alkyl alcohol ethoxylate),
- a cationic surfactant (e.g. a quaternary ammonium surfactant),
- a thickener (e.g. xanthan gum),
- 10 - a dye,
- a fragrance.

The above auxiliary components may be included in the compositions suitable for use in the process of the
15 present invention at concentrations of from 0.01% w/w to 10% w/w. These auxiliary ingredients may be included in either component (a), or component (b) or both if appropriate.

20 According to a further aspect of the present invention, there is provided the use of an aqueous composition of hydrogen peroxide or an organic peracid, which composition has a pH of 2 or less, to remove limescale at a surface or to both bleach and remove
25 limescale at a surface.

Compositions suitable for use in the process according to the present invention may be stored in any appropriate containers known to the art. For example,
30 the two components may be stored in two-compartment packs suitable for sequential or simultaneous dispensing.

Where both components (a) and (b) are liquids, most preferably they may be stored in a two-compartment
35 dispenser, one compartment containing each component and the dispenser being adapted to dispense each component on

-7-

to a surface, either sequentially or, preferably, simultaneously.

According to a further aspect of the invention,
5 there is provided a two-compartment dispenser comprising

a first compartment containing an aqueous composition comprising hydrogen peroxide or an organic peracid and having a pH of greater than 2 but less than
10 7;

a second compartment containing an acidic component;
and

15 dispensing means adapted to dispense the contents (or a part thereof) of the compartments on to a surface either sequentially or simultaneously to form a mixture thereof; whereby the pH of the acidic component is so selected, and/or the dispensing means is so adapted that
20 the mixture has a pH of less than 2.

Preferably, the first compartment contains an aqueous composition comprising 3 to 10% w/w hydrogen peroxide; and the second compartment contains an aqueous
25 composition comprising hydrochloric acid.

A process according to the present invention may be used to bleach and/or remove limescale from any suitable acid-resistant household surface, for example ceramic
30 surfaces such as lavatory surfaces or tiles.

The invention will now be illustrated by the following Examples.

Example 1

The following two aqueous compositions are prepared.

5

Composition (a)

Hydrogen peroxide (35% aqueous solution)	9g
Water	91g

10

Composition (b)

Hydrochloric acid (36 Twaddle)	25g
Water	75g

15

The two compositions (a) and (b) are mixed together in a beaker and the resulting composition has a pH of approximately 0.

20

Samples of the composition are immediately applied to surfaces requiring bleaching, and left in contact for 20 minutes. The surfaces are then rinsed with water. The mixed composition produces improved bleaching of the surface compared to either composition (a) or (b) alone when diluted with an equal volume of water.

25

Example 2

The following compositions are prepared.

30

parts w/wComposition (a)

Hydrogen peroxide (35% aqueous solution)	9.00
Sodium xylene sulphonate (30%)	2.40
35 Hexadecyl trimethylammonium chloride (30%)	3.77
Citric acid	0.31
Fragrance	0.20

-9-

Dye	0.005
Water	84.315

pH 2.6

5

<u>Composition (b)</u>	<u>Parts w/w</u>
------------------------	------------------

Hydrochloric acid (36 Twaddle)	25.00
Tallow trimethyl ammonium chloride (50% in	
10 IPA/water)	0.60
Tallow bis (2-hydroxyethyl) amine	1.20
Fatty (C12/C14) alcohol ethoxylate (12 mole)	0.27
Water	72.93

15 Equal proportions of the two compositions are mixed to give a composition having an initial hydrogen peroxide concentration of 1.55% and an initial pH of approximately 0.

20 Example 3

The following compositions are prepared

<u>Composition (a)</u>	<u>Parts w/w</u>
Hydrogen Peroxide (35% aqueous solution)	9.00
Surfactants-	
Arquad 16/29 (AKZO)	3.77
Sodium Xylene Sulphonate(30%)	2.40
Citric Acid (Anhydrous)	0.31
Fragrance (Parfex 43174 (Givaudan Roure))	0.20
Dye (Sandolun Turquoise EVS (Sandoz dyes))	0.006
Water	84.31

Composition (b)

<u>Pre-mix</u>	<u>Parts w/w</u>
Soft Water	83.83
Surfactants -	
Arquad T-50	3.86
Ethomeen T12	8.00
Lutensol (80%)	1.78
Dye (Flexonyl B2G (Hoechst))	0.0253
<u>Main Mix</u>	
Hydrochloric Acid (36 Twaddle)	25.00
Pre-mix	15.00
Soft Water	60.00

- 5 Equal proportions of the two compositions (a) and (b) are mixed to give a composition having an initial hydrogen peroxide concentration of 1.575% and an initial pH of less than 1.

10 Example 4

The improved bleaching performance of the compositions of the invention is tested by the following procedure.

15

Three ceramic tiles are covered in blue absorbent laboratory paper (Kimberley Clarke). Three mls of one of the following compositions are applied to the tiles.

- 20 i) Example 1, Composition (a), diluted to 50% w/w with water (1.575% w/w hydrogen peroxide);
- ii) Example 1, Composition (b), diluted to 50% w/w with water (4.5% w/w active hydrochloric acid);

- 11 -

iii) Example 1, a 1:1 mixture of Composition (a) and Composition (b) (1.575% w/w hydrogen peroxide and 4.5% active hydrochloric acid).

5

The tiles are photographed every hour to record any bleaching of the paper. Composition iii) (the mixture of Compositions (a) and (b) demonstrates good bleaching with compositions i) and ii) showing very little or no
10 bleaching.

Example 5

The improved limescale dissolving performance of
15 compositions of the invention is tested by the following procedure.

Pre-weighed 1 inch marble cubes are placed into 150 ml samples of the three compositions i), ii) and iii) described in Example 4. The cubes are removed from the
20 compositions after five minutes, washed, dried, weighed and replaced into the original compositions. This process is repeated after 30, 60 and 120 minutes. The average (over 3 repetitions) weight loss in each
25 composition is:

Average % weight loss

	0 mins	5 mins	30 mins	60 mins	120 mins
Composition					
i)	0.0	0.013	0.013	0.043	0.06
ii)	0.0	8.09	29.95	38.74	41.29
iii)	0.0	10.4	33.13	47.04	50.55

**CLAIMS**

1. A process for bleaching and/or providing limescale
5 removal at a surface, comprising applying to that surface
an aqueous composition of hydrogen peroxide or an organic
peracid, which composition has a pH of 2 or less and
comprises a mixture of

10 (a) an aqueous composition comprising hydrogen
peroxide or an organic peracid having a pH of greater
than 2 but less than 7 (hereinafter component (a)), and

15 (b) an acidic composition (hereinafter component
(b)),

wherein components (a) and (b) are mixed not more than
two hours before being applied to the surface requiring
bleaching and/or limescale removal.

20

2. A process according to claim 1, wherein components
(a) and (b) are mixed on the surface requiring bleaching
and/or limescale removal.

25 3. A process for preparing an aqueous bleaching and/or
limescale removing composition having a pH of 2 or less
by mixing

30 (a) an aqueous composition comprising hydrogen
peroxide or an organic peracid having a pH of greater
than 2 but less than 7 (hereinafter component (a)), and

(b) an acidic composition (hereinafter component
(b)),

35



wherein components (a) and (b) are mixed not more than two hours before being applied to the surface requiring bleaching and/or limescale removal.

- 5 4. A process according to claim 1, 2 or 3, wherein component (a) is hydrogen peroxide or peracetic acid.
5. A process according to any of claims 1 to 4, wherein component (b) is hydrochloric acid, sulphamic acid,
10 tartaric acid, phosphoric acid, oxalic acid, citric acid, salicyclic acid or ascorbic acid.
6. A process according to any of claims 1 to 5, wherein the concentration of hydrogen peroxide or organic peracid
15 in the composition after mixing is from 0.01 to 10% w/w.
7. A two-compartment dispenser comprising
- a first compartment containing an aqueous
20 composition comprising hydrogen peroxide or an organic peracid having a pH of greater than 2 but less than 7;
 a second compartment containing an acidic component;
 and
 a dispensing means adapted to dispense the contents
25 (or a part thereof) of the compartments on to a surface either sequentially or simultaneously to form a mixture thereof; whereby the pH of the acidic component is so selected and/or the dispensing means is so adapted that the mixture has a pH of 2 or less.
- 30
8. A dispenser according to claim 7, wherein the first compartment contains an aqueous composition comprising 3 to 10% w/w hydrogen peroxide.
- 35 9. A dispenser according to claim 7 or 8, wherein the second compartment contains an aqueous composition comprising hydrochloric acid.



10. The use of an aqueous composition of hydrogen peroxide or an organic peracid, which composition has a pH of 2 or less, to remove limescale at a surface or to
5 both bleach and remove limescale at a surface.

11. A process substantially as herein described with reference to any of the accompanying Examples.