

OPTICAL PROJECTION SYSTEM INCLUDING PROJECTION DOME

Field of the Invention

The present invention relates to visual projection systems and, more
5 particularly, to visual projection systems including projection domes.

Background of the Invention

Hemispherical optical projection systems are used to project images onto the
inner surfaces of domes. Hemispherical optical projection systems are used in
10 planetariums, commercial and military flight simulators, and in various hemispherical
theaters. With the present interest in virtual reality and three-dimensional rendering
of images, hemispherical optical projection systems are being investigated for
projecting images which simulate a real environment.

Typically, hemispherical optical projection systems include relatively large
15 domes having maximum diameters from about 4 meters to more than 30 meters. Such
systems are well-suited for displays to large audiences. However, such systems may
be large and cumbersome and often cost several hundreds of thousands of dollars,
thus making them prohibitively expensive for many uses.

Summary of the Invention

Embodiments of visual workstations according to the present invention are adapted for use by a viewer and include a dome having an open front end and a truncated spherical inner dome surface. A work surface is disposed in front of and adjacent the dome front end. The work surface defines a viewer area on a side of the work surface opposite the dome. The viewer area is sized and configured to receive the viewer and is positioned relative to the spherical inner dome surface such that the viewer, when located in the viewer area, may view the spherical inner dome surface. A projector is disposed between the viewer area and the dome. The projector is operative to project a truncated spherical projection onto the inner dome surface.

According to other embodiments of the present invention, a visual presentation system for use by a viewer includes a dome having an open front end and a truncated spherical inner dome surface. A support surface is disposed in front of the dome front end. The system is configured to maintain a prescribed distance between the support surface and the inner dome surface. A projector is supported by the support surface. The projector is operative to project a truncated spherical projection onto the inner dome surface.

According to other embodiments of the present invention, a visual presentation system for use by a viewer includes a dome having an open front end and a truncated spherical inner dome surface. A projector is operative to project a truncated spherical projection onto the inner dome surface. The truncated spherical inner dome surface has a maximum diameter of no more than two meters.

According to other embodiments of the present invention, a visual presentation system for use by a viewer includes a dome having an open front end and

a truncated spherical inner dome surface. The system further includes an image source comprising an array of image pixels. A projector is operative to project the array of image pixels onto the inner dome surface as a truncated spherical projection. The number of pixels of the array of image pixels which are projected by the projector
5 onto the inner dome surface is adjustable.

Preferably, the truncated spherical projection has constant angular separation among adjacent pixels. Preferably, the truncated spherical projection includes an axially asymmetric, truncated spherical primary image. Preferably, the array of image pixels defines an array center, the projector includes a lens assembly having an optical
10 axis, and the relative positions of the optical axis and the array center are adjustable.

According to other embodiments of the present invention, a visual presentation system for use by a viewer includes a dome having an open front end and a truncated spherical inner dome surface. An image source displays a source image. The source image includes a primary image and a secondary image adjacent the
15 primary image. A projector is provided which is selectively operable to project the source image onto the inner dome surface as a truncated spherical projection such that both the primary and the secondary image are projected onto the inner dome surface and, alternatively, such that only the primary image is projected onto the inner dome surface.

20 Preferably, the projector is selectively operable to project the entirety of the source image onto the inner dome surface. Preferably, the source image has a center, the projector includes a lens assembly having an optical axis, and the system includes means for adjusting the relative positions of the optical axis and the center of the source image. Preferably, the primary image is truncated circularly shaped.

25 Additionally, the source image is preferably rectangular.

According to other embodiments of the present invention, a method of displaying an image on a dome having an open front end and a truncated spherical inner dome surface includes providing a source image including a primary image and a secondary image adjacent the primary image. The source image is projected such that only the primary image is projected onto the inner dome surface as a truncated spherical projection. Thereafter, the source image is projected such that both the primary image and the secondary image are projected onto the inner dome surface as a truncated spherical projection.

Preferably, each of the steps of projecting includes projecting the source image using a lens assembly having an optical axis, and the method further includes adjusting the relative positions of the optical axis and a center of the source image. Preferably, the primary image is truncated circularly shaped and the step of projecting the source image such that only the primary image is projected includes spacing the optical axis and the center of the source image apart.

Objects of the present invention will be appreciated by those of ordinary skill in the art from a reading of the Figures and the detailed description of the preferred embodiments which follow, such description being merely illustrative of the present invention.

20

Brief Description of the Drawings

Figure 1 is a front, perspective view of an optical projection system according to the present invention;

Figure 2 is a fragmentary, top view of the optical projection system of **Figure 1**;

Figure 3 is a fragmentary, front, perspective view of the optical projection system of **Figure 1**;

Figure 4 is a rear, perspective view of the optical projection system of **Figure 1**;

5 **Figure 5** is a front elevational view of the optical projection system of **Figure 1**;

Figure 6 is a side elevational view of the optical projection system of **Figure 1**;

10 **Figure 7** is a fragmentary, side view of the optical projection system of **Figure 1**;

Figure 8 is a schematic block diagram representing the optical projection system of **Figure 1**;

15 **Figure 9** is a schematic representation of a two-dimensional image plate forming a part of the optical projection system of **Figure 1** and displaying a first image;

Figure 10 is a schematic representation of the two-dimensional image plate of **Figure 9** displaying a second, alternative image;

Figure 11 is a front view of the dome of the optical projection system of **Figure 1** with a first optical projection displayed thereon;

20 **Figure 12** is a front view of the dome of the optical projection system of **Figure 1** with a second, alternative optical projection displayed thereon;

Figure 13 is a front, perspective view of an optical projection system according to an alternative embodiment of the present invention;

25 **Figure 14** is a front, perspective view of an optical projection system according to a further alternative embodiment of the present invention;

Figure 15 is a left, front, perspective view of an optical projection system according to a further alternative embodiment the present invention;

Figure 16 is a right, front, perspective view of the optical projection system of **Figure 15**;

5 **Figure 17** is a front elevational view of the optical projection system of **Figure 15**;

Figure 18 is a side elevational view of the optical projection system of **Figure 15**; and

Figure 19 is a front, perspective view of an optical projection system according to a further alternative embodiment of the present invention;

Figure 20 is a front, perspective view of an optical projection system according to a further alternative embodiment of the present invention; and

Figure 21 is a fragmentary, front, perspective view of an optical projection system according to a further alternative embodiment of the present invention.

15

Detailed Description of the Preferred Embodiments

The present invention now will be described more fully hereinafter with reference to the accompanying drawings, in which preferred embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein; rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art. Like numbers refer to like elements throughout.

With reference to **Figures 1-7**, a visual presentation system or workstation
25 **100** according to a first embodiment of the present invention is shown therein. The

workstation includes a dome **110**, a desktop **130**, a supporting framework generally designated **150**, a projector **120**, an image generator **124** (see **Figure 2**) and a seat **140** (preferably a chair as shown). The projector **120** includes a projection lens assembly **122**. The workstation is adapted for use by a user or viewer **U**. The image generator **124** may be a general purpose computer, a video player, a digital camera or any other suitable device. As will be more apparent from the description that follows, the workstation **100** provides the viewer **U** with a visually immersive experience. Additionally, the workstation **100** provides a convenient and effective work environment and may include individual modularized components which may be further broken down to be portable.

As used herein, the “front” of the dome **110** is the open end of the dome **110**. “Left” and “right” are indicated from the perspective of the viewer **U**.

As shown in **Figures 1** and **2**, the workstation **100** can also include various peripheral components to enhance its utility as workstation. A keyboard **144**, a pair of speakers **142**, a telephone **146** and a mouse **148** are provided. Some or all of these devices may be omitted. For example, the optical projection system **100** may be used as a presentation-only system or as a limited interaction workstation. For clarity, the foregoing devices are not shown in **Figures 3-7**.

The dome **110** is preferably formed of molded LEXANTM, KYDEXTM, CELTECTM, SINTRATM, acrylic or other suitable rigid, lightweight material. The dome **110** has an interior truncated spherical projection surface **112**. The projection surface **112** terminates at a front peripheral edge **114**. As indicated in **Figure 2**, the front edge **114** defines a vertical front plane **F-F**. The front plane **F-F** is preferably substantially perpendicular to the horizontal center axis **X-X** of the dome **110** and the projection surface **112**. The dome **110** also has a surrounding fascia **115** attached to

the front edge 114. The projection surface 112 is adapted to reflect incident light for display of projections to the viewer U. Although the surface 112 may be white, it is preferably tinted or coated with a layer of substantially opaque paint. More preferably, the tint or paint is between about 5% and 20% gray. The dome 110 may
5 be formed of or coated on its outer surface with an opaque material. The screen surface may also be formed of polarization preserving material.

The dome 110 is a truncated sphere, preferably a hemisphere, and is preferably axially symmetric about its horizontal center axis X-X (see Figure 7) as shown. Preferably, the dome 110 has horizontal and vertical sweeps of between about 140°
10 and 180°, and more preferably of about 150°. With reference to Figure 7, the interior projection surface 112 of the dome 110 should have a maximum diameter D (i.e., at the front edge 114) of no more than 2 meters. More preferably, the maximum diameter D is between about 0.5 and 2 meters and, most preferably, the maximum diameter D is about 1.5 meters.

15 The dome 110 is supported in an upright orientation by a T-shaped pedestal 154 forming a part of the supporting framework 150. Other supporting elements may be used in place of or in addition to the pedestal 154. For many applications, the dome 110 is preferably detachably fastened to or interlocked with the pedestal 154 to allow breakdown for shipping and moving of the workstation 100. Optionally (not
20 shown), the dome 110 may be formed of multiple attachable and detachable segments. The pedestal 154 may be formed of wood, fiberboard, plastic or any other suitable material.

The desktop 130 is supported, for example, by legs 152 forming a part of the supporting framework 150. For many applications, the desktop 130 and the legs 152

are preferably detachably connected. The desktop **130** may be formed of wood, plastic, metal or any other suitable material.

As best seen in **Figures 1-3**, the desktop **130** has a main section **132** which provides a work surface for the viewer **U** and a support surface for the projector **120**.

- 5 The work surface is preferably horizontally oriented as shown. A front edge **131A** of the main section **132** is disposed adjacent the front of the dome **110**. Optionally (not shown), the front edge **131A** may abut the front face (i.e., the fascia **115**) of the dome **110**. A cutout **133** in the desktop **130** forms side wings **134** and a rear edge **131B** of the main section **132**. A viewer area **135** is defined adjacent the rear edge **131B** on
- 10 the side of the desktop **130** opposite the dome **110**. As shown, the viewer area **135** is further defined by the side wings **134**, which are optional. Preferably, the distance **G** between the front plane **F-F** and the rear edge **131B** is no more than 25 inches. More preferably the distance **G** is between about 5 and 15 inches, and most preferably about 10 inches. Preferably, the length **L** of the rear edge **131B** is at least 40 inches.
- 15 Preferably, the desktop **130** provides a work surface area of at least 1000 square inches.

As will be appreciated from the drawings, the viewer area **135** is configured and sized to receive a viewer **U** of a size and dimensions within a prescribed range in a seated position and such that a prescribed orientation and relative position between

20 the viewer **U** and the dome **110**, and more particularly, the projection surface **112**, are provided, as discussed below. The prescribed viewer range may include, for example, the expected sizes and dimensions for typical adults or the expected sizes and dimensions for typical children in a prescribed age group, depending on the desired application for the workstation **100**.

The seat **140** is preferably a chair. As shown, the seat **140** has a supporting pedestal and is not connected to the remainder of the system **100**. Alternatively, the seat **140** may be attached or integrally formed with the dome **110**, the desktop **130** and/or the supporting framework **150**.

5 In the embodiment as shown, the workstation **100** is arranged for use by a seated viewer **U**. Alternatively (not shown), the workstation **100** may be adapted for use by a standing viewer. In such case, the supporting framework **150** may be vertically extended to raise the desktop **130** and the dome **110**, and the viewer area **135** may be reconfigured to provide the desired orientation and relative position
10 between the standing viewer **U** and the dome **110** and the projection surface **112**.

 With reference to **Figures 2, 3, and 5-8**, the workstation **100** includes an optical projection system **121** including the projector **120**, the lens assembly **122** (including a terminal lens **122A**) and the computer **124**. The projector **120** includes an image plate **101** and suitable electronics **103** (see **Figure 8**) for receiving,
15 interpreting and/or converting signals from the computer **124**.

 The image plate **101** may be any suitable two-dimensional image source the resolution of which is defined by a limiting unit area. The term “pixel” as used herein refers to any such unit area. Preferably, the image plate **101** includes an array of defined image pixels, for example, as may be provided in a liquid crystal display.
20 However, non-segmented image sources or other segmented image sources (for example, having scan lines) may be used as well, in which case the resolutions thereof may be defined by other unit areas.

 Preferably, and as shown, the projector **120** is secured to the underside of the desktop main section **132**. Alternatively (not shown), the projector **120** may fixedly
25 or loosely mounted on top of the desktop **130**. Alternatively (not shown), the

projector may be mounted on its own stand independent of the desk. The computer 124 is preferably located beneath the desktop 130 and is connected to the projector 120 by a suitable connector (not shown).

With reference to **Figures 2, 3 and 7**, most of the lens assembly 122 is
5 disposed within a casing 120A with the terminal lens 122A extending forwardmost and beyond the casing 120A. Most or all of the remaining components of the projector 120 are disposed in the casing 120A and leftward of the lens assembly 122. This arrangement provides a relatively compact projector, particularly along the length between the viewer and the dome.

10 The projector 120, the lens assembly 122 (including the lens 122A) and the computer are preferably as described in U.S. Patent 5,762,413 to Colucci et al., filed January 29, 1996, entitled "*Tiltable Hemispherical Optical Projection Systems and Methods Having Constant Angular Separation of Projected Pixels*", which is assigned to the assignee of the present application, the disclosure of which is incorporated
15 herein by reference in its entirety. Suitable projectors include the Epson PowerLite 710c available from Epson Corp. of Long Beach, CA, and the LP330 DragonFly available from InFocus Systems Inc. of Wilsonville, OR. The optical projection system of the present invention may also employ the dual polarization optical projection systems and methods described in copending application Serial No.
20 08/618,442 to Colucci et al., filed March 19, 1996, entitled "*Dual Polarization Optical Projection Systems and Methods*", which is assigned to the assignee of the present application, the disclosure of which is incorporated herein by reference in its entirety. The optical projection system of the present invention may employ the systems, methods and computer program products described in copending application Serial
25 No. 08/806,788 to Idaszak et al., filed February 26, 1997, entitled "*Systems, Methods*

and Computer Program Products for Converting Image Data to Nonplanar Image Data”, which is assigned to the assignee of the present application, the disclosure of which is incorporated herein by reference in its entirety. Suitable modifications to the optical projection systems described herein will be apparent to those of ordinary skill
5 in the art upon reading the description herein and the cited disclosures.

With reference to **Figure 8**, the optical projection system **121** projects a truncated spherical projection **10** onto the interior projection surface **112** of the truncated spherical dome **110**. The projection **10** has constant angular separation among adjacent pixels as indicated by angle $d\theta$ which is constant among adjacent
10 pixels **10A-10N**. The constant angular separation truncated spherical optical projection system **121** is an inverse telephoto system having an $f\text{-}\theta$ focal distribution. The image height is proportional to $f\text{-}\theta$, where f is the focal length of the lens and θ is the projected angle at the image location. The preferred construction and attributes of the optical projection system **121** will be further appreciated from the disclosure of
15 U.S. Patent No. 5,762,413 to Colucci et al.

Preferably and as shown, the front surface of the terminal lens **122A** is substantially coincident with the front plane **F-F** of the projection surface **112**. Alternatively, the terminal lens **122A** may be disposed forwardly of the plane **F-F** and within the interior volume defined by the projection surface **112** of the dome **110**.
20 The projection **10** preferably extends across a full field of view of about 180° . However, if the terminal lens **122A** is positioned within the interior volume of the projection surface **112**, a field of view greater than 180° should be used.

Notably, the projector **120** and the lens assembly **122** are positioned between the viewer **U** and the projection surface **112**. The terminal lens **122A** is located
25 beneath the vertical midpoint **VMP** (see **Figure 7**) of the dome **110**. The viewer **U** is

preferably positioned such that his/her head **H** is located above the vertical midpoint **VMP** of the dome **110** when the viewer **U** is seated in the viewer area **135**.

The desktop **130** and the viewer area **135** tend to position the viewer **U** such that the viewer's head **H** stays between about zero and 15 inches from the projection surface front edge **114**, and more preferably about 10 inches. This positioning, along with the preferred dimensions, configurations and relative arrangements of the
5
aforedescribed components, provide the viewer **U** with a realistic three-dimensional visual environment with minimal distortion or inconsistency in the image as a function of the viewer's position within the viewer area **135**. The workstation **100**
10
provides a particularly immersive visual environment in that, when the viewer **U** is looking directly forward into the dome **110**, the projected image extends substantially fully across the viewer's range of peripheral vision in all directions.

Alternatively (not shown), the front plane of the projection surface may be defined by the front edge of the dome **110**. For example, the fascia **115** may be
15
omitted or the projection **10** may extend to the inwardly facing surface of the fascia **115**.

Optionally, the workstation **100** may be adapted to display stereographic images. The viewer **U** may wear shuttered glasses which alternately open and close the left and right eye views in synchrony with projections of corresponding left and
20
right images. Using polarization preserving screen material, stereo images may be projected. A suitable method is described in application Serial No. 08/618,442 to Colucci et al., filed March 19, 1996, entitled "*Dual Polarization Optical Projection Systems and Methods*".

With reference to **Figures 9 and 10**, the image which is projected onto the
25
dome **110** is preferably modified to provided enhanced image resolution. The

following discussion describes embodiments of mapping and projecting an image and, thereafter a preferred, alternative embodiments of mapping and projecting the image to achieve greater resolution using the same equipment and area of projection surface.

Figure 9 shows a display of an image **20A** on the two-dimensional image plate **101**. The display on the image plate **101** corresponds to the manner in which the image **20A** would be displayed on a planar display device such as a conventional CRT or other two-dimensional screen. The image plate **101** may be, for example, an active matrix liquid crystal display such as an Epson 0.9 inch Poly-silicon, TFT. It will be appreciated, however, that the image plate **101** may be any suitable two-dimensional image display device.

According to the first embodiments, the image **20A** includes a circular primary image **22A** which is mapped fully within the bounds of the image plate **101**. The lens assembly **122** is configured and arranged relative to the image plate **101** such that the entire circular primary image **22A** is projected onto the truncated spherical dome interior projection surface **112**. The center **C1** of the image **20A** is coincident with the center of the dome **110**. The primary image **22A** is mapped onto a prescribed number of pixels of the image plate **101**, which is limited by the graphics software and hardware employed. The primary image **22A** is magnified by the lens assembly **122** by the amount necessary to make the periphery of the primary image **22A** as projected substantially coextensive with the front edge **114** of the projection surface **112**.

According to the preferred, alternative embodiments, the resolution of the projected primary image **22A** is increased by both enlarging and truncating the image as shown in **Figure 10**. The preferred, alternative image **20** as displayed on the two-dimensional image plate **101** includes a truncated primary image **22** which is enlarged

as compared to the primary image 22A. The primary image 22 has the shape of a truncated circle. A lower truncated portion 23 corresponding to a lower part of the primary image 22A is outside the range of the image plate 101 and therefore is not mapped onto the pixels thereof by the graphics software and hardware.

5 When the primary image 22 is projected by the projection system 121 (**Figure 8**) as the projection 10 onto the three-dimensional projection surface 112, the primary image 22 appears as shown in **Figure 11**. This is accomplished by configuring and manipulating the lens assembly 122 as follows. In a conventional projection system, the optical axis of the projecting lens is maintained coincident with the center C1 of
10 the image plate 101 (which is also the center of the image 20). By contrast, according to the present invention, the lens assembly 122 is moved vertically relative to the image plate 101 or the image plate 101 is moved vertically relative to the lens assembly 122 such that the optical axis of the lens assembly 122 coincides with the center C2 of the primary image 22. As a result, the center C2 of the primary image
15 22 as projected onto the projection surface 112 is coincident with the center C3 (see **Figure 11**) of the dome 110.

 The primary image 22 is magnified by the lens assembly 122 by the amount necessary to make the periphery of the primary image 22 as projected substantially coextensive with the front edge 114 of the projection surface 112. Preferably, the lens
20 assembly 122 is constructed and configured such that a portion, and preferably substantially all, of the image 20 outside of the primary image 22 is clipped by the lens assembly 122 (i.e., is not projected). The projection 10 includes a lower, non-imaged, truncated region 12 (defined between the lower edge T of the image 22 and the lower periphery of the projection surface 112) which corresponds to the truncated
25 portion 23 of the primary image 22. The region 12 is preferably black. The lower

edge **T** corresponds to the lower edge of the image **20** as mapped and displayed on the image plate **101**. Accordingly, the primary image **22** is projected onto the projection surface **112** as a truncated spherical projection which is axially asymmetric (the horizontal center axis of the dome **110** being the reference axis).

5 By enlarging the size of the primary image **22** as compared to the primary image **22A** on the image plate **101**, less magnification of the image **22** is required to project it over the desired projection area. As a result, greater resolution is achieved (i.e., the ratio of pixels (or other unit area of the image plate **101**) per unit area of projection is higher).

10 Preferably, the primary image **22** is sized and the desktop **130** is positioned such that the lower edge **T** of the image **22** in the projection **10** is located a distance **K** (see **Figure 7**) below the upper surface of the desktop **130** of between about 12 and 20 inches. In this manner, any recognition by the viewer **U** that the image has been truncated is substantially reduced or eliminated.

15 With reference to **Figure 10**, many computer program interface displays are designed for use on conventional, two-dimensional, rectangular displays such as the display **101**. For example, the MicrosoftTM Windows 98TM operating system may locate secondary images **26** such as various icons, menus, other desktop controls and window control buttons in the displayed image region **24** outside of the primary
20 image **22**. Because, the projection **10** includes only the primary image **22**, these secondary images **26** and the image region **24** cannot be viewed in the dome **110**. In order to allow the viewer to view these outlying portions of the image **20**, the workstation **100** may be provided with a second, two-dimensional display monitor adapted to display the full image **20**.

Alternatively, and preferably, the workstation **100** solves the foregoing problem by providing means for adjusting the projection **10** to selectively project some or all of the image region **24** onto the projection surface **112** so that a secondary display is not needed. More particularly, the lens assembly **122** may be readjusted to zoom in (i.e., provide less magnification of the image plate **101**), thereby reducing the area of the projection surface **112** dedicated to the primary image **22**. As a result, some or all of the image region **24** may be projected onto the projection surface **112**. Restated, the lens assembly **122** projects a greater number of the pixels of the array of pixels of the image plate onto the projection surface **112**. The viewer may thereafter zoom out to return to the projection **10** wherein the primary image **22** fills the projection surface **112**. The lens assembly **122** may be zoomed in and out by hand or by using a lever (not shown) or a suitably connected servo-motor (not shown), for example.

In order to reduce the degree of zoom in required to display a given amount of the image region **24** on the projection surface **112**, the lens assembly **122** is preferably further adjusted as follows. To convert from the projection **10** (**Figure 11**) to the projection **10A** (**Figure 12**), the lens assembly **122** is zoomed in as just discussed. Additionally, the lens assembly **122** is moved vertically relative to the image plate **101** or the image plate is moved vertically relative to the lens assembly **122** such that the optical axis of the lens assembly **122** is coincident with the center **C1** of the image plate (and, hence, the image **20**). The center of the image **20** is thereby projected onto the center **C3** of the dome **110**. As a result, the diagonal maximum length of the image **24** extends across the full diameter of the projection surface **112**.

The projection **10A** includes the primary image **22**, a portion or all of the image region **24** (including the secondary images **26**) and an enlarged truncated

region **12A**. The viewer may view and manipulate the secondary images **26** and then return to the original projection **10** for better viewability. It will be appreciated that, if desired, the lens assembly **122** may be zoomed in an amount less than necessary to view the entire image **20**. It will also be appreciated that the optical axis of the lens assembly may be relocated vertically relative to the image plate **101** less than the amount necessary to register the image center **C1** with the dome center **C3**.

With reference to **Figure 13**, a workstation **200** according to a further embodiment of the present invention is shown therein. The workstation **200** corresponds to the workstation **100** except as follows. The workstation **200** differs from the workstation **100** in that the desktop **230** is attached to the dome **210** by means of the supporting framework **250**. More particularly, the feet **253** on the legs **252** are secured to the front dome pedestal plate **254A** by tabs **253A** and bolts **255** to form connections **256**. The feet **253** have a prescribed length. In this way, the distance between the desktop **230** and the projection surface **212** is fixed at a prescribed distance. The distance between the viewer (not shown) and the projection surface **212** and the distance between the projector **220** and the projection surface **212** are thereby fixed. The workstation **200** may be modified, supplemented and used in any of the ways set forth above with regard to the workstation **100**.

With reference to **Figure 14**, a workstation **300** according to a further embodiment of the present invention is shown therein. The workstation **300** corresponds to the workstation **100** except as follows. The workstation **300** differs from the workstation **100** in that the desktop **330** is directly attached to and supports the dome **310**. Slots **317** are formed in the fascia **315** of the dome **310**. Portions **337** of the desktop **330** are inserted into the slots **317** such that the front edge **331A** of the desktop **330** is disposed in the slots to form connections **356**. The portions **337** may

be retained in the slots 317 by adhesive, press fitting or other suitable means. The dome 310 is suspended from the desktop 330 at the connections 356. The distance between the desktop 330 and the projection surface 312 is fixed. The distance between the viewer (not shown) and the projection surface 312 and the distance
5 between the projector 320 and the projection surface 312 are thereby fixed as well. The workstation 300 may be modified, supplemented and used in any of the ways set forth above with regard to the workstation 100.

With reference to **Figures 15-18**, an optical presentation system 400 according to a further embodiment is shown therein. The system 400 is adapted for displaying
10 images to a standing viewer and does not provide a work surface. The system 400 includes a dome 410, a projector 420, a terminal lens 422A (**Figures 17 and 18**) and a computer or other image generating means (not shown) corresponding to the dome 110, the projector 120, the lens 122A and the computer 124, respectively. An extended pedestal 450 supports the dome 410. Preferably, the center of the dome is
15 positioned at a height of between about 48 and 72 inches from the ground. A support 460 positions the projector 420 and the lens 122A relative to the dome 410 in the same manner and configuration as in the workstation 100. The support 460 includes a plurality of support arms 462 affixed to the dome 410 and a platform 464. The optical presentation system 400 may be modified, supplemented and used in any of the ways
20 set forth above with regard to the workstation 100.

With reference to **Figure 19**, an optical presentation system 500 according to a further embodiment is shown therein. The system 500 corresponds to the system 400 except as follows. The system 500 is adapted for displaying images to a group of seated viewers and provides a tabletop or work surface 530. The tabletop 530 is
25 attached to the dome 510. Slots 517 are formed in the fascia 515 of the dome 510.

Portions **537** of the tabletop **530** are inserted into the slots **517** such that the front edge **531** of the tabletop **530** is disposed in the slots to form connections **556**. The portions **537** may be retained in the slots **517** by adhesive, press fitting or other suitable means. The dome **510** is supported by a pedestal **550** that is reduced in height as compared to the pedestal **450**. Alternatively (not shown), the system **500** may be free and unattached to the tabletop **530**. The system **500** may be modified, supplemented and used in any of the ways set forth above with regard to the workstation **100**.

With reference to **Figure 20**, an optical presentation system **600** according to a further embodiment of the present invention is shown therein. The system **600** includes a separate pedestal **652** which is separate from the pedestal **654** which supports the dome **610**. A projector **620** is supported on a support platform **630** at the top of the pedestal **652**.

With reference to **Figure 21**, an optical projection system **700** according to a further embodiment is shown therein. The system **700** corresponds to the workstation **100** except as follows. The projector **720** depends from the desktop **730** and is vertically disposed (i.e., rotated 90° about a transverse, horizontal axis as compared to the projector **120**) such that the lens assembly **722** is vertically oriented. An elbow-shaped mirror element **727** is interposed between the horizontally oriented terminal lens **722A** and the remainder of the lens assembly **722**. The arrangement of the system **700** may allow for greater legroom beneath the desktop **730**.

The foregoing is illustrative of the present invention and is not to be construed as limiting thereof. Although a few exemplary embodiments of this invention have been described, those skilled in the art will readily appreciate that many modifications are possible in the exemplary embodiments without materially departing from the novel teachings and advantages of this invention. Accordingly, all such modifications

are intended to be included within the scope of this invention as defined in the claims.

In the claims, means-plus-function clauses are intended to cover the structures described herein as performing the recited function and not only structural equivalents but also equivalent structures. Therefore, it is to be understood that the foregoing is

5 illustrative of the present invention and is not to be construed as limited to the specific embodiments disclosed, and that modifications to the disclosed embodiments, as well as other embodiments, are intended to be included within the scope of the appended claims. The invention is defined by the following claims, with equivalents of the claims to be included therein.

10

What is Claimed is:

1. A visual workstation for use by a viewer, said workstation comprising:
 - a) a dome having an open front end and a truncated spherical inner dome surface;
 - b) a work surface disposed in front of and adjacent said dome front end, said work surface defining a viewer area on a side of said work surface opposite said dome, said viewer area sized and configured to receive the viewer and positioned relative to said spherical inner dome surface such that the viewer, when located in said viewer area, may view said spherical inner dome surface; and
 - c) a projector disposed between said viewer area and said dome, said projector operative to project a truncated spherical projection onto said inner dome surface.
2. The workstation of Claim 1 wherein said spherical inner dome surface has a maximum diameter of no more than two meters.
3. The workstation of Claim 1 wherein said dome has a horizontal center axis and said work surface is horizontally disposed.
4. The workstation of Claim 1 wherein said work surface and said viewer area are configured for use by a seated viewer.

5. The workstation of Claim 4 including a seat disposed in said viewer area.
6. The workstation of Claim 1 wherein said work surface and said viewer area are configured for use by a standing viewer.
7. The workstation of Claim 1 wherein said workstation is configured to maintain a prescribed distance between said inner dome surface and work surface.
8. The workstation of Claim 1 wherein said work surface is attached to said dome.
9. The workstation of Claim 8 wherein said work surface is directly attached to said dome.
10. The workstation of Claim 9 wherein said dome is suspended from said work surface.
11. The workstation of Claim 8 including a supporting framework supporting each of said work surface and said dome, wherein said supporting framework connects said work surface and said dome to one another.
12. The workstation of Claim 1 including at least one of a keyboard, a telephone, a speaker and a computer input device.

13. The workstation of Claim 1 wherein said spherical inner dome surface is gray.

14. The workstation of Claim 1 wherein:
5 said dome has a vertical midpoint;
said projector includes a terminal lens;
said terminal lens is located below said vertical midpoint; and
the viewer's head is disposed above said vertical midpoint when the
viewer is seated in said viewer area.

10

15. The workstation of Claim 1 wherein:
said spherical inner dome surface defines a front plane;
said projector includes a terminal lens; and
said terminal lens is disposed within said front plane or within said
15 dome.

16. The workstation of Claim 1 wherein said truncated spherical projection extends across at least 180 degrees.

20 17. The workstation of Claim 1 wherein said spherical inner dome surface has vertical and horizontal sweeps of between about 140 and 180 degrees.

18. The workstation of Claim 1 wherein said truncated spherical projection includes an axially asymmetric, truncated spherical image.

25

19. The workstation of Claim 18 including an image source having a center and wherein:

said projector includes a lens assembly having an optical axis; and
said optical axis is spaced apart from said center of said image source.

5

20. The workstation of Claim 19 wherein said image source comprises an array of image pixels and said projector is operative to project said array of image pixels onto said inner dome surface as a truncated spherical projection having constant angular separation among adjacent image pixels.

10

21. The workstation of Claim 1 including:

an image source comprising an array of image pixels, wherein said projector is operative to project said array of image pixels onto said inner dome surface as a truncated spherical projection; and

15 the number of pixels of said array of image pixels which are projected by said projector onto said inner dome surface is adjustable.

22. The workstation of Claim 1 wherein said projector includes a vertically oriented lens assembly, a horizontally oriented terminal lens and a mirror element
20 between the lens assembly and the terminal lens.

23. A visual presentation system for use by a viewer, said system comprising:

a) a dome having an open front end and a truncated spherical inner dome
25 surface;

- b) a support surface disposed in front of said dome front end; and
- c) a projector supported by said support surface, said projector operative to project a truncated spherical projection onto said inner dome surface;
- 5 d) wherein said system is configured to maintain a prescribed distance between said inner dome surface and said support surface.

24. The system of Claim 23 including a support arm extending between said dome and said support surface, wherein said support arm maintains said
10 prescribed distance between said inner dome surface and said support surface.

25. The system of Claim 23 wherein said system is configured for use by a standing viewer.

15 26. The system of Claim 23 including a pedestal supporting said dome.

27. The system of Claim 23 wherein said dome has a horizontal center axis.

20 28. A visual presentation system for use by a viewer, said system comprising:

- a) a dome having an open front end and a truncated spherical inner dome surface; and
- b) a projector operative to project a truncated spherical projection onto
25 said inner dome surface;

- c) wherein said truncated spherical inner dome surface has a maximum diameter of no more than two meters.

29. The system of Claim 28 wherein said dome has a horizontal center
5 axis.

30. The system of Claim 28 including a supporting framework supporting
said dome.

10 31. The system of Claim 28 wherein said spherical inner dome surface is
gray.

32. The system of Claim 28 defining a prescribed viewer area and wherein:
said dome has a vertical midpoint;
15 said projector includes a terminal lens;
said terminal lens is located below said vertical midpoint; and
the viewer's head is disposed above said vertical midpoint when the
viewer is seated in said viewer area.

20 33. The system of Claim 28 wherein:
said spherical inner dome surface defines a front plane;
said projector includes a terminal lens; and
said terminal lens is disposed within said front plane or within said
dome.

25

34. The system of Claim 28 wherein said truncated spherical projection extends across at least 180 degrees.

35. The system of Claim 28 wherein said spherical inner dome surface has
5 vertical and horizontal sweeps of between about 140 and 180 degrees.

36. The system of Claim 28 wherein said truncated spherical projection includes an axially asymmetric, truncated spherical image.

10 37. The system of Claim 36 including an image source having a center and wherein:

said projector includes a lens assembly having an optical axis; and
said optical axis is spaced apart from said center of said image source.

15 38. The system of Claim 37 wherein said image source comprises an array of image pixels and said projector is operative to project said array of image pixels onto said inner dome surface as a truncated spherical projection having constant angular separation among adjacent image pixels.

20 39. The workstation of Claim 28 including an image source comprising an array of image pixels, and wherein:

said projector is operative to project said array of image pixels onto
said inner dome surface as a truncated spherical projection; and

the number of pixels of said array of image pixels which are projected
25 by said projector onto said inner dome surface is adjustable.

40. The workstation of Claim 28 wherein said projector includes a vertically oriented lens assembly, a horizontally oriented terminal lens and a mirror element between the lens assembly and the terminal lens.

5

41. A visual presentation system for use by a viewer, said system comprising:

- a) a dome having an open front end and a truncated spherical inner dome surface;
- 10 b) an image source comprising an array of image pixels;
- c) a projector operative to project said array of image pixels onto said inner dome surface as a truncated spherical projection; and
- d) wherein the number of pixels of said array of image pixels which are projected by said projector onto said inner dome surface is adjustable.

15

42. The system of Claim 41 wherein said truncated spherical projection has constant angular separation among adjacent pixels.

43. The system of Claim 41 wherein:
20 said array of image pixels defines an array center;
said projector includes a lens assembly having an optical axis; and
the position of said optical axis relative to said array center is adjustable.

44. The system of Claim 41 wherein said truncated spherical projection includes an axially asymmetric, truncated spherical primary image.

45. A visual presentation system for use by a viewer, said system
- 5 comprising:
- a) a dome having an open front end and a truncated spherical inner dome surface;
 - b) an image source displaying a source image, said source image including a primary image and a secondary image adjacent said
 - 10 primary image;
 - c) a projector selectively operable to project said source image onto said inner dome surface as a truncated spherical projection such that both said primary and said secondary image are projected onto said inner dome surface and, alternatively, such that only said primary image is
 - 15 projected onto said inner dome surface.

46. The system of Claim 45 wherein said projector is selectively operable to project the entirety of said source image onto said inner dome surface.

- 20 47. The system of Claim 45 wherein:
- said source image has a center;
- said projector includes a lens assembly having an optical axis; and
- the position of said optical axis relative to said center is adjustable.

48. The system of Claim 45 wherein said primary image is truncated circularly shaped.

49. The system of Claim 48 wherein said source image is rectangular.

5

50. A method of displaying an image on a dome having an open front end and a truncated spherical inner dome surface, said method comprising the steps of:

providing a source image including a primary image and a secondary image adjacent said primary image;

10

projecting the source image such that only the primary image is projected onto the inner dome surface as a truncated spherical projection;

thereafter, projecting the source image such that both the primary image and the secondary image are projected onto the inner dome surface as a truncated spherical projection.

15

51. The method of Claim 50 wherein each of the steps of projecting includes projecting the source image using a lens assembly having an optical axis, said method further including the step of adjusting the relative positions of the optical axis and a center of the source image.

20

52. The method of Claim 51 wherein said primary image is truncated circularly shaped and said step of projecting the source image such that only the primary image is projected includes spacing the optical axis and the center of the source image apart.

25

53. A visual workstation for use by a viewer, said workstation comprising:
- a) a dome having an open front end and a truncated spherical inner dome surface; and
 - b) a work surface disposed in front of and adjacent said dome front end,
5 said work surface defining a viewer area on a side of said work surface opposite said dome, said viewer area sized and configured to receive the viewer and positioned relative to said spherical inner dome surface such that the viewer, when located in said viewer area, may view said spherical inner dome surface.
- 10
54. A visual presentation system for use by a viewer, said system comprising:
- a) a dome having an open front end and a truncated spherical inner dome surface;
 - 15 b) a support surface disposed in front of said dome front end, said support surface adapted to support a projector; and
 - c) wherein said system is configured to maintain a prescribed distance between said inner dome surface and said support surface.
- 20
55. A method of displaying an image, said method comprising the steps of:
- providing an upright dome having an open front end and a truncated spherical inner dome surface, the inner dome surface defining a horizontal center axis and having a maximum diameter of no more than two meters; and
- projecting the image as a truncated spherical projection onto the inner dome
- 25 surface.