I.V. INFUSION OR BLOOD COLLECTION APPARATUS

PRIORITY CLAIM

This application claims priority from United States Provisional Patent Application Serial No. 61/399,629 filed July 15, 2010, which is incorporated by reference herein in its entirety.

FIELD OF THE INVENTION

This invention relates generally to the field of medical devices and more particularly to the field of safety products used for blood collection or infusion to prevent accidental needle sticks.

BACKGROUND OF THE INVENTION

The collection of blood from a patient or infusion into a patient are two of the most commonly performed medical procedures in the world. Blood collection is necessary in order to evaluate the chemical constituency of the bodily functions in order to diagnose medical conditions and to validate treatment plans and infusion is necessary to deliver pharmaceuticals, ringers or other preparations in liquid form. Notwithstanding the foregoing, injuries caused by needles and other sharp medical devices and the related risk of potentially fatal disease transmission remain a major threat to the health and safety of health care workers around the world. In addition, the distress, sickness and absenteeism resulting from sharps injuries constitute a considerable strain on the already limited human resources in the medical profession.

The majority of sharps injuries are suffered by nurses and occur in patient rooms and the operating theatre, but doctors, dentists and other medical staff are also victims. Ancillary staff such as cleaners and laundry staff and other downstream workers, are also at risk.

The term "needle stick" injury has come to be the term used to describe inadvertent penetration of the skin by a previously used, contaminated catheter, needle or other percutaneous device. A combination of training, safer working practices and the use of medical devices incorporating needle stick protection technology can prevent many of these potentially serious injuries.

The U.S. Congress took action in response to growing concerns over blood borne pathogen exposures from sharps injuries and in response to recent technological developments that increased employee protection. On November 6, 2000, the "Needle Stick Safety and Prevention Act" was signed into law, requiring that all health care facilities in the U.S. evaluate, purchase and provide medical devices incorporating needle protection for their staff. Health care employers in the U.S. are also now required to maintain a sharps injury log and involve non-managerial potentially exposed health care workers in the evaluation and implementation of work practice controls and devices incorporating needle protection.

Thus, safe disposal of sharp medical instruments, such as scalpel blades and syringe needles has become an important issue, addressed at the highest level of the U.S. government, due to the possible transmission of disease by accidental skin-penetrating contact during disposal of sharp medical instruments, commonly known as "medical sharps."

There are several scenarios that describe the accidental needle stick injury: First, a handler may be stuck by a syringe needle while attempting to re-cap the needle after it has been used. Second, a handler may be stuck by a syringe needle while transporting it to a proper "Sharps Container." Third, a handler or other individuals may be stuck when contacting a syringe and needle that has been left unprotected and unattended. Fourth, individuals that transport medical waste may be stuck by unprotected, uncapped or improperly stored syringes and needles.

In general, it is considered "unsafe" to re-cap a syringe needle due to the extreme possibility that the handler will be stuck by the needle while re-capping and the present invention presents an improved safety system for preventing sharps injuries in connection with blood collection sets.

It is thus an object of the invention to provide an improved I.V. infusion or blood collection apparatus.

It is a further object of the present invention to provide an improved I.V. infusion or blood collection apparatus having enhanced safety features.

A still further object of the present invention is to provide an improved I.V. infusion or blood collection apparatus that is easy to use and inexpensive to produce.

These and other objects will become apparent when taken in connection with the accompanying drawings.

DESCRIPTION OF THE DRAWINGS

Figure 1 is a perspective view of the blood collection set according to the present invention illustrating the needle in the extended position.

Figure 2 is a front or needle end view of the blood collection set according to the present invention illustrating the needle in the extended position.

Figure 3 is a plan view of the blood collection set according to the present invention illustrating the needle in the extended position.

Figure 4 is an underside view of the blood collection set according to the present invention illustrating the needle in the extended position.

Figure 5 is a side view of the blood collection set according to the present invention illustrating the needle in the extended position.

Figure 6A is a plan view, partially broken away of the blood collection set according to the present invention illustrating the needle in the retracted position.

Figure 6B is a sectional view of the blood collection set according to the present invention taken along line A-A of Figure 6A illustrating the needle in the retracted position.

Figure 7 is a side view of the blood collection set according to the present invention illustrating the needle in the retracted position.

Figure 8 is a perspective view of the wing body according to the present invention.

Figure 9 is a front or needle end view of the wing body according to the present invention.

Figure 10 is a side view of the wing body according to the present invention.

Figure 11A is a plan view of the wing body according to the present invention.

Figure 11B is an enlarged view of area A of Figure 11A showing the wings and grip portions of the wing body according to the present invention.

Figure 11C is a sectional view taken along line C-C of Figure 11A and showing the wing body according to the present invention.

Figure 12A is a side view of the wing body according to the present invention.

Figure 12B is an enlarged view of area B of Figure 12A showing the wings and grip portion of the wing body.

Figure 13 is a side view of the safety shield according to the present invention in the folded and locked position.

Figure 14 is a side view of the safety shield according to the present invention in the unfolded position.

Figure 15 is a plan view of the safety shield according to the present invention in the unfolded position.

Figure 16 is an enlarged view of the locking mechanism portion of the safety shield according to the present invention.

Figure 17A is a plan view of a second embodiment of the present invention and illustrating an alternate embodiment of the locking mechanism with the needle in the extended position.

Figure 17B is an enlarged view of the locking mechanism of Figure 17A according to the present invention.

Figure 18A is a perspective view of the second embodiment of the present invention and showing the needle in the retracted safety position with the grip in locked position.

Figure 18B is an enlarged view of the locking mechanism with the needle retracted in the safety position with the grip in the locked position.

Figure 19 is a side view of the second embodiment of the present invention and showing the needle in the retracted position with the grip locked.

Figure 20 is a plan view of the second embodiment of the present invention showing the needle in the retracted position with the grip locked.

Figure 21 is a side view of the second embodiment of the present invention showing the needle in the extended position

SUMMARY OF THE INVENTION

An I.V. infusion or blood collection apparatus comprises an I.V. infusion set and a safety shield adapted to surround the I.V. infusion set or blood collection apparatus. The I.V. infusion or blood collection apparatus comprise a wing body having a central portion having a proximal end to which a needle is connected, a distal end to which tubing is connected. Also provided is a bore extending through the wing body to permit the flow of fluid between the needle and the medical tubing. The wing body includes a pair of substantially coplanar wings extending horizontally outward from the opposite sides of the central portion and a grip extending upwardly from the central portion substantially perpendicular to the wings.

The safety shield is adapted to surround the wing body and comprises a lower shield section adapted to overlie the patient's skin and an upper shield section. The respective lower shield section and the upper shield section are hingedly connected at a first end and adapted to be connected to each other at the respective opposite ends to form a chamber. The chamber is adapted to receive the infusion set therein. The safety shield includes a front end through which the needle of the IV set extends for use and a rear end through which the IV infusion set tubing extends. The side walls of said safety shield include a pair of opposing slots through which the respective wings of the IV infusion set are adapted to be slidably received.

An elongate slot is positioned in the top wall of the safety shield through which the grip extends. The elongate slot includes a locking means proximate the rear end of the safety shield for maintaining the needle in a permanently locked position upon retraction of the needle into the chamber. Thus, when the pair of opposing slots and the elongate slot are of sufficient length to enable the IV infusion set to move from an operative position wherein the needle is exposed for use to a safety position wherein the needle is fully retracted into the chamber and the grip is lockingly received in the locking means.

DETAILED DESCRPITION OF THE PREFERRED EMBODIMENT

While the present invention will be described more fully hereinafter, it is to be understood at the outset that persons of skill in the art may modify the present invention herein described while still achieving the favorable results of the invention. Accordingly the description which follows is to be understood as a broad teaching disclosure directed to persons of skill in the appropriate arts, and not as limiting upon the present invention.

For ease of reading, in the description that follows the I.V. infusion or blood collection apparatus will at times be referred to as the "BCS", blood collection set.

As shown in the figures, the BCS 50 according to the present invention comprises an I.V. infusion set 100 and a safety shield 200.

I.V. infusion set 100 comprises a wing body 105 having a central portion 110 with a proximal end 115 to which a needle 120 is connected and a distal end 125 to which tubing 130 is connected. A longitudinal bore 135 extends through the central portion 110 of wing body 105 to permit the flow of fluid between the medical tubing 130 and needle 120. Wing body 105 further includes a pair of substantially coplanar wings 140 that extend horizontally outward from opposite sides of central portion 110. A grip 145 extends upwardly from the central portion 110 substantially perpendicular to the wings140. According to convention in the industry, the wing body 105 and wings 140 are referred to as a "butterfly". It will be noted that generally, the wings 140, central portion 110, bore 135 and grip 145 are molded as a single unit. The area where the respective wings140 connect to wing body105 is thinner than the wings such that the wings 140 are bendable with respect to the wing body 105. Fabrication techniques and materials for the wing body 105 are well known to those skilled in the art. Further, the needle 120 and medical tubing 130 are connected to wing body 105 by suitable means, again well known to those skilled in the art, such as glue, cyanoacrylate, heat bond or other type of bonding.

As briefly mentioned herein above, grip 145 is integrally molded with wing body 105 and extends upwardly there from between approximately 80% the width and 33% the length thereof. The top of grip 145 is angled upward from the proximal 115 end to the

distal end 120 and includes a series of axially extending ridges 150 which aid in handling the BCS as will be explained in further detail herein below.

Safety shield generally indicated at 200 is adapted to overlie the patient's skin and comprises an upper shield section 210 having a first hinge end 215 and a lower shield section 220 having a second hinge end 225 that are adapted to be connected together to form a chamber 227. In the illustrated embodiment, the respective first and second ends 215, 225 terminate in living hinge 222 and the respective opposite upper shield end 230 and lower shield opposite end 240 are adapted to be snapped together as best shown in figure 16. The snap closure 244 is a standard cantilever beam type of snap fit connection. Those skilled in the art will note that other types of closure mechanisms may be employed such as a post and hold, glue together method or other types of closures, well known to those skilled in the art.

The sides of the safety shield are contoured to form elongate slots or grooves 250 in opposite sides thereof when the respective shield sections 210, 220 are connected to form chamber 225. Additionally, an elongate longitudinal slot 255 is located in upper shield section 210 and terminates in a widened zone 260 which acts to lock the I.V. infusion set in the locked position after use. In another embodiment of the invention, the terminating end of slot 255 additionally includes a pair of flexible "fingers" 242, which extend from the opposite sides of slot 235 and point towards the medical tubing end of the safety shield 200 and collectively form a locking means for maintaining the I.V. infusion set in a locked position after use. It will be noted that the rear end of I.V. shield should be of sufficient length to enable single handed retraction of the needle 120 into the "safety" or locked position. More specifically, the distance from the tubing end of the

safety shield 200 to the terminating end of the locking means should be long enough to permit the safety shield to be gripped with the thumb and middle finger of the user while the pointer finger engages the needle end of the grip 145 and slides the needle 120 into the safety shield 200 until the locking means fully engages the grip whereupon the needle will be fully retracted and permanently locked within the safety shield for safe disposal.

Elongate slots 250 and 255 are constructed and arranged to enable the wings 140 of the IV infusion set to move from an operative position wherein the needle 120 is exposed for use to a safety position wherein the needle 120 is fully retracted into the chamber 225. Upon full retraction, the wings 140 are positioned proximate the tubing end of the safety shield and the grip 145 is lockingly received in the locking means portion of the elongate slot in the top wall of the safety shield.

While certain illustrative embodiments have been described, it is evident that many alternatives, modifications, permutations and variations will become apparent to those skilled in the art in light of the foregoing description.

THAT WHICH IS CLAIMED IS:

1. An I.V. infusion or blood collection apparatus comprising, in combination:

an I.V. infusion set comprising:

a wing body having a central portion having a proximal end to which a needle is connected, a distal end to which tubing is connected and further including a bore there through to permit the flow of fluid between said needle and said medical tubing, and wherein the wing body includes a pair of opposing wings extending outward from said central portion in a first direction, wherein said central portion includes and a grip extending outward from said central portion in a second direction; and

a safety shield constructed and arranged to surround said wing body and comprising;

a lower shield section adapted to overlie the patient's skin;

an upper shield section, said lower shield section and said upper shield section adapted to be connected at a first end and adapted to be connected to each other at said respective opposite ends to form a chamber, said chamber having a top, a bottom and opposing side walls, said safety shield being adapted to received within said chamber said I.V. infusion set and further, wherein said safety shield includes a front end through which the needle of the I.V. infusion set is extendable for use and a rear end through which the IV infusion set tubing extends; and

a pair of opposing slots in the respective side walls of said safety shield through which the respective wings of said I.V. infusion set are adapted to be postioned for slidable movement;

an elongate slot in the top wall of said safety shield through which said grip is adapted to be positioned for slidable movement of said central portion; and

wherein said pair of opposing slots and said elongate slot are constructed and arranged to enable said I.V. infusion set to move from an operative position wherein said needle is exposed for use to a safety position wherein said needle is fully retracted into said chamber.

2. The I.V. infusion or blood collection apparatus according to claim 1 further including:

means for locking said I.V. infusion set in the safety position operatively associated with said top wall slot and being positioned proximate the rear end thereof,

whereby upon movement of said I.V. infusion set to the retracted position, the grip is engaged by the locking means and the needle is permanently locked within said chamber.

3. The I.V. infusion or blood collection apparatus according to claim 2 wherein said means for locking comprises a pair of flexible fingers extending from opposite sides of said slot and further, wherein said fingers point towards the medical tubing end of the safety shield.

4. The I.V. infusion or blood collection apparatus according to claim 3 wherein said grip is substantially perpendicular to said wings.

5. The I.V. infusion or blood collection apparatus according to claim 1 wherein said lower shield section and said upper shield section are connected at one end with a living hinge.

6. The I.V. infusion or blood collection apparatus according to claim 1 wherein said top wall slot is tapered, the wide end being proximate the needle end of said safety shield and the narrow end being proximate the tubing end of the safety shield.

7. The I.V. infusion or blood collection apparatus according to claim 6 wherein the narrow end of said top wall slot terminates at a means for locking said I.V. infusion set in the safety position,

whereby upon movement of said I.V. infusion set to the retracted position, the grip is engaged by the locking means and the needle is permanently locked within said chamber.

8. An I.V. infusion or blood collection apparatus comprising, in combination: an I.V. infusion set comprising:

a wing body having a central portion having a proximal end to which a needle is connected, a distal end to which tubing is connected and further including a bore there through to permit the flow of fluid between said needle and said medical tubing, and wherein the wing body includes a pair of flexible

opposing wings extending horizontally outward from said central portion and a grip extending vertically outward from said central portion; and

a safety shield constructed and arranged to surround said wing body and comprising;

a lower shield section adapted to overlie the patient's skin;

an upper shield section, said respective lower shield section and said upper shield section connected to each other with a living hinge at a first end and adapted to be connected to each other at said respective opposite ends to form a chamber, said chamber having a top, a bottom and opposing side walls, said safety shield being adapted to received within said chamber said I.V. infusion set and further, wherein said safety shield includes a front end through which the needle of the I.V. infusion set is extendable for use and a rear end through which the IV infusion set tubing extends; and

a pair of opposing slots in the respective side walls of said safety shield through which the respective wings of said I.V. infusion set are adapted to be postioned for slidable movement;

an elongate slot in the top wall of said safety shield through which said grip is adapted to be positioned for slidable movement;

a locking means for locking said needle in the retracted position operatively associated with said elongate slot; and

wherein said pair of opposing slots and said elongate slot are constructed and arranged to enable said I.V. infusion set to move from an operative position wherein said needle is exposed for use to a safety position wherein said needle is fully retracted into said chamber.

9. The I.V. infusion or blood collection apparatus according to claim 8 wherein said locking means is positioned at the needle end of said slot and is adapted to lockingly receive said grip.

10. The I.V. infusion or blood collection apparatus according to claim 9 wherein said locking means further includes a pair of flexible fingers extending from opposite sides of said slot and further, wherein said fingers point towards the medical tubing end of the safety shield.