

5

TITLE

PLASMA OXIDATION OF AN EXHAUST GAS STREAM FROM
CHLORINATING TITANIUM-CONTAINING MATERIAL

CROSS-REFERENCE TO RELATED APPLICATIONS

10

This application claims the benefit of U. S.
Provisional Application No. 60/008,272 filed December 6,
1995.

15

BACKGROUND OF THE INVENTIONField of the Invention

This invention relates to a process of contacting an
20 exhaust gas, comprising carbonyl sulfide (COS) which arises
from chlorinating titanium-containing material, with a cold
plasma and more particularly selectively oxidizing COS to
SO_x (x = 2 or 3).

25 Description of the Related Art

Use of a plasma formed by a corona discharge for
treating toxic organic compounds is known. For example,
U. S. Patent 5,254,231 demonstrates reduction of
30 trichloroethylene.

U. S. Patent 3,783,116 discloses decomposition of
carbonyl sulfide in a silent (corona) electric discharge to
sulfur (S_x) and CO. This process is useful to reduce COS
35 from petroleum refineries and in processes involving
reactions between sulfur and carbonaceous materials. It is
further disclosed that the COS can be oxidized to CO₂ after

5 removal of the elemental sulfur. There is no oxygen present during the COS decomposition.

Heretofore, plasma-generating devices have not been used to treat an exhaust gas stream arising from
10 chlorinating titanium-containing material. The process for chlorinating titanium-containing materials in a fluidized bed reactor is known. Suitable processes are disclosed in the following U.S. Patents: 2,701,179; 3,883,636;
3,591,333; and 2,446,181 which are hereby incorporated by
15 reference. In such processes, particulate coke, particulate titanium bearing materials, chlorine and optionally oxygen or air, wherein at least one of these contains sulfur, are fed into a reaction chamber. Gaseous titanium tetrachloride, other metal chlorides and non-condensable
20 gases are exhausted from the reaction chamber. The gaseous titanium tetrachloride so produced can then be separated from the other metal chlorides and exhaust gas comprising COS and CO.

25 In this chlorination process, it is desirable to convert COS to SO_x since removal of COS from the exhaust gas is difficult and costly. For example, one previous method used to remove COS is hydrolysis of COS to H_2S and oxidization to sulfur. However, COS hydrolysis and sulfur
30 production are expensive and involve multiple steps. Another previous method used to remove COS is thermal oxidation, i.e., heating the exhaust gas in an incinerator which requires fuel, costly equipment and additional processing steps. Similarly, catalytic incinerators also
35 require heating, and the COS and other constituents in the exhaust gas could chemically and physically foul the catalyst. There is a need to remove COS from the exhaust gas without incurring substantial cost for downstream

5 abatement with incinerators. Concomitantly, there is a need
for a process that promotes COS oxidation where the CO
neither diminishes the COS conversion rate nor is
significantly converted relative to the COS. A simple and
economical process is therefore needed. The present
10 invention meets these needs.

SUMMARY OF THE INVENTION

15 The present invention provides a process for treating
an exhaust gas stream comprising COS, wherein the exhaust
gas stream is produced from the chlorination of titanium-
bearing material, comprising the steps of:

- 20 (a) contacting the exhaust gas with a cold plasma at a
temperature within the range of about -20°C to
about 500°C in the presence of oxygen, and
- (b) oxidizing COS to SO_x , wherein x is 2 or 3.

25 The exhaust gas stream can further comprise CO. In
such an event, the COS is selectively oxidized with minimal
oxidation of the CO. When the exhaust gas stream comprises
COS and CO, the COS is selectively oxidized to SO_x and CO_z ,
wherein x is 2 or 3, and z is 1 or 2. Preferably, the
temperature of the cold plasma is in the range of about 0°C
to about 300°C and more preferably about 0° to about 150°C .
30 The oxidation of COS to SO_x may occur in the presence or
absence of an oxidation catalyst.

35 The cold plasma may be generated by ionizing radiation
selected from the group consisting of alpha-rays, beta-rays,
gamma-rays, ultraviolet light, x-rays and high energy
electron beam. The cold plasma may also be generated by
electrical discharge selected from the group consisting of
radio frequency, microwave, laser induced discharge, dc or

5 ac glow discharge, dc or ac corona, arc discharge, silent discharge and streamer corona.

The process of this invention is characterized by the following advantages which cumulatively render this process
10 preferable to processes previously employed:

1. COS is oxidized without significantly heating the exhaust gas;
2. COS emissions are reduced;
3. lower energy requirements and less investment to
15 effect COS removal are achieved;
4. the SO_x formed can be scrubbed from the exhaust gas at low temperatures without removing the heat that would result from substantial CO oxidation; and
- 20 5. the process is more tolerant of potential foulants than catalytic incineration.

Surprisingly, it has been found that COS is selectively oxidized in the presence of CO at lower temperatures even in
25 the absence of catalysts. Further, it has been found that COS is converted to SO_x with minimal oxidation of the CO. Oxidizing COS without extensively oxidizing CO minimizes the temperature increase from exothermic oxidation and allows easier removal of SO_x by low temperature, downstream
30 processing steps.

DETAILED DESCRIPTION OF THE INVENTION

In the manufacture of titanium tetrachloride, titanium-
35 bearing material, carbonaceous material, chlorine, and optionally oxygen or air, wherein at least one of these contains sulfur, are fed into a fluidized bed reactor. The titanium-containing material can be any suitable titanium

5 source material such as titanium-containing ores including
rutile, ilmenite or anatase ore; beneficiates thereof;
titanium-containing byproducts or slags; and mixtures
thereof. Suitable carbonaceous material for use in this
invention is any carbonaceous material which has been
10 subjected to a coking process or is substantially free of
hydrogen.

Gaseous reaction products from the fluidized bed
reactor are cooled in stages to first condense and remove
15 metal chlorides other than titanium tetrachloride, such as
iron chlorides. The remaining product from the reactor is
then cooled to condense titanium tetrachloride leaving a
non-condensable exhaust gas stream comprising COS and CO.

20 In carrying out the invention, the exhaust gas stream
is contacted with a plasma in the presence of an oxygen-
containing gas at a temperature in the range of about -20°C
to about 500°C, preferably about 0°C to about 300°C, and
more preferably about 0°C to about 150°C. Typically, the
25 plasma is created by either ionizing radiation or electrical
discharge. Alpha-rays, beta-rays, gamma-rays, ultraviolet
light, x-rays, high energy electron beams, and the like are
used in the ionizing radiation generated plasma. Electrical
discharges at low, high and atmospheric gas pressures may be
30 used in the electrical discharge generated plasma. Examples
include but are not limited to radio frequency, microwave or
laser induced discharges; and dc or ac glow discharges.
Electrical discharges at high, low or atmospheric pressures
typically include dc or ac coronas, arc discharges, silent
35 discharges and streamer coronas and the like. More
specifically, the plasmas are ionized gases made up of free
electrons, charged ions, neutral molecules, atoms and
radicals as described in greater detail in H. Brachhold, R.

5 Muller and G. Pross, "Plasma Reactions", Ullmann's Encyclopedia of Industrial Chemistry, vol. A20, pp. 427-428, (VCH Publishers, Inc., Weinheim, FRG, 1992), the teachings of which are hereby incorporated by reference.

10 Plasmas are electrically conductive, but, generally, have equal concentrations of positive and negative charge carriers and are electrically quasi-neutral. "Cold", "non-thermal" or "non-equilibrium" plasmas are used herein interchangeably and are distinguished from thermal or
15 equilibrium plasmas in that their free electrons have a much higher temperature than their heavy ions and neutral particles. The plasma is used herein to collectively refer to a discharge formed from a plasma generating device as described above. For example, a corona discharge reactor as
20 described in U.S. Patents 4,695,358, 4,954,320, 5,236,672, 5,254,231, a radio frequency plasma reactor (inductively-coupled or capacitively-coupled), a silent electrical discharge from a fluidized bed as described in U. S. Patent 3,734,846, a micro-wave generated plasma reactor as
25 described in "Chemical Engineering Progress", November, 1995, pp. 36-48 and references therein, and the like are contemplated. The entire disclosures of the above teachings are incorporated herein by reference. One established industrial process utilizing cold plasmas is the generation
30 of ozone in a corona discharge.

It will be appreciated by those skilled in the art that the exhaust gas contacts the plasma by passing through a zone where a plasma is generated. Alternatively, the
35 exhaust gas can contact excited species, generated by passing gases such as air, oxygen and the like, through the plasma.

5

If the exhaust gas does not contain oxygen, an oxygen-containing gas such as air, oxygen or the like, needs to be added. The oxygen concentration, on a molar basis, can be about 1 to 100 times the COS concentration, preferably about 10 1 to 10 times and most preferably about 2 to 5 times the COS concentration. Optionally, water can be added to an oxygen-containing gas or the exhaust stream.

Pressures of 1 to 200 kilopascals (0.01 to 2 15 atmospheres), preferably 10-200 kilopascals (0.1 to 2 atmospheres) and more preferably 20-200 kilopascals (0.2 to 2 atmospheres) can be used. An oxidation catalyst may be employed. It has been found in the present invention that the process can be advantageously carried out in the absence 20 of an oxidation catalyst.

The COS is selectively oxidized in the presence of CO at lower temperatures. The COS is converted to SO_x wherein $x = 2$ or 3 , which can then be scrubbed at lower temperatures 25 from combustion products, optionally after quenching or heat recovery. The oxidation of COS to SO_x may occur in the presence or absence of any oxidation catalyst. Typical catalysts include, for example, supported chromia, and certain base metal or supported precious metal catalysts. 30 If necessary, CO and COS emissions can be further controlled by thermal incinerators without an additional scrubbing step. Thereafter, the remaining gases can be vented to the atmosphere.

35 The present invention is further illustrated by the following examples, but these examples should not be construed as limiting the scope of the invention.

5

EXAMPLESExample 1

10 A Sander Ozonizer, model 100, available from Aquarium
Stock Company Products, Bayonne, NJ, was tested as a COS
oxidation promoter. The Ozonizer, i.e., Ozonator was
designed to generate up to 100 mg/hr of O₃ from air with a
power rating of 4 Watts. It was tested with air and air/He
15 mixtures for O₃ capacity using iodide oxidation to detect
the ozone. The effect of its corona discharge electrodes on
the COS/CO - O₂ reactions was tested by passing mixtures of
COS/air/He/CO directly through the device at ambient
temperatures and analyzing the reaction products by gas
20 chromatography. COS was oxidized to predominately SO₂, CO
and CO₂ with up to 26% conversion and good selectivity
relative to CO. H₂S, a contaminant, was removed with
much higher efficiency. The Ozonizer performed in the range
of 80 to 180 kWh/lb of COS converted. CO was also oxidized
25 but to a lesser extent (<2%) and with little interference
with COS oxidation.

Results are shown in Table 1 below. Feed rates were
250 milliliters/minute of primarily air (runs A-C) or air-He
30 mixture (runs D-F) including the oxygen and with the
additional components as tabulated below, given in micro-
moles/minute. The ozone production before treatment of the
COS containing gas at a setting of 100mg/hr measured 88 and
96 mg/hr, at a setting of 50mg/hr measured 60 mg/hr, and at
35 a setting of 100mg/hr but only 10% air in He, measured 5
mg/hr. Ozone production after treatment of the COS
containing gas at a setting of 100mg/hr (air) measured 88

- 5 mg/hr. COS removal persisted or improved at a given Ozonizer setting at lower air concentrations where it is unlikely much ozone formed.

TABLE 1

Run	O ₂	COS	O ₃	H ₂ S	CO	COS conv.	kWh/ lb-COS	H ₂ S conv.
A	2200	35	35	1	0	12%	120	>95%
B	2200	35	18	1	0	6%	120	>90%
C	2200	12	35	0.3	0	16%	260	>90%
15 D	70	35	35*	1	0	13%	110	~55%
E	70	12	35*	ND**	0	26%	161	
F	70	12	35*	ND**	313	23%	183	

*Based on Ozonizer setting.

20 **ND means not detected.

Example 2

An experimental ozone generator based on a radio frequency plasma was employed. The device was designed to generate ozone more efficiently than commercially available corona discharge units. A series of screening tests similar to those outlined above with this larger capacity (70 Watt) unit were run. Results were observed with COS conversions of about 50% at 170 kWh/lb COS converted and 40 % at 90 kWh/lb COS converted and with less than 5 % CO converted.

Having thus described and exemplified the invention with a certain degree of particularity, it should be appreciated that the following Claims are not to be limited but are to be afforded a scope commensurate with the wording of each element of the Claims and equivalents thereof.



5

CLAIMSWhat is Claimed is:

1. A process for treating an exhaust gas stream
10 comprising COS, wherein the exhaust gas stream is produced
from the chlorination of titanium-containing material,
comprising the steps of:
- (a) contacting the exhaust gas stream with a cold
plasma at a temperature within the range of about
15 -20°C to about 500°C in the presence of oxygen, and
(b) oxidizing COS to SO_x, wherein x is 2 or 3.
2. The process of claim 1, wherein the exhaust gas
stream comprises COS and CO, and COS is selectively oxidized
20 to SO_x and CO_z, wherein x is 2 or 3 and z is 1 or 2.
3. The process of claim 1 or claim 2, wherein the
temperature of the cold plasma is within the range of about
0°C to about 300°C.
- 25 4. The process of claim 3, wherein the temperature of
the cold plasma is within the range of about 0°C to about
150°C.
- 30 5. The process of claim 1, claim 2, claim 3, or
claim 4, wherein the plasma is generated by ionizing
radiation selected from the group consisting of alpha-rays,
beta-rays, gamma-rays, ultraviolet light, x-rays and high
energy electron beam.
- 35 6. The process of claim 1, claim 2, claim 3, or
claim 4, wherein the plasma is generated by electrical
discharge selected from the group consisting of radio



5 frequency, microwave, laser induced discharge, dc or ac glow
discharge, dc or ac corona, arc discharge, silent discharge
and streamer corona.

7. The process of claim 1 or claim 2, wherein step (b)
10 occurs in the absence of an oxidation catalyst.

8. The process of claim 1 or claim 2, wherein step
(b) occurs in the presence of an oxidation catalyst.

15