

Document Title: Specification

Title of Invention: Bucket Crane with Conveyor

Technical Field

0001

5 The present invention pertains to a crane, and more particularly to a crane for unloading freight such as coal, iron ore, and the like, using a bucket.

Background Art

0002

10 Freight such as coal or iron ore carried by barges or the like is unloaded with the barge moored along a wharf. The unloaded coal, etc. is carried to a predetermined location by a conveyor installed on land. Jib cranes of the type set forth in Patent Citation 1, for example, are widely used for such unloading work.

15

Prior Art References

0003

Patent References

20 Patent Citation 1: Japanese Patent Application Unexamined Publication 2002-53290

Summary of the Invention

Problems the Invention Seeks to Resolve

0004

25 When unloading shipboard coal or the like onto a conveyor using a jib crane, it is necessary to lower a bucket attached at the end of a jib crane wire by feeding out the wire, fill the shipboard coal into the bucket, raise the bucket by hoisting the wire, and move the bucket over the conveyor by rotating the arm in the horizontal direction.

30 However, because of the extremely long time required for this wire

outfeeding/hoisting, horizontal rotation of the arm, and so forth, unloading of coal or the like is time consuming.

0005

5 The present invention was undertaken in light of the above problems, and enables the work of unloading coal or the like with a crane to be performed in a short time.

Means for Resolving the Problem

10 0006

0007

15

20

25

30

0008

0009

5 The crane of the present invention is a crane for unloading freight using
a bucket, comprising a base portion; a crane main unit portion erected on the
base portion; an arm extending in approximately the horizontal direction from the
crane main unit; a conveyor mechanism extending in approximately the
horizontal direction from the crane main unit below the arm; a wire support
10 portion attached to the arm and capable of advancing and retracting along said
arm; a wire an end portion of which is suspended from the wire support portion
and which is connected at its end portion to the bucket; and a wire outfeed

15

20

25

30

device capable of outfeeding and winding wire; wherein the arm and conveyor mechanism are rotatable in the horizontal direction around the same axis so that, in plan view, the direction in which the arm extends at all times matches the direction in which the conveyor mechanism extends.

5 In the present invention thus constituted, the arm and conveyor mechanism are rotatable in the horizontal direction around the same axis so that, in plan view, the direction in which the arm extends at all times matches the direction in which the conveyor mechanism extends, therefore the bucket can be moved between the position at which coal is filled and a position over the
10 conveyor, simply by manipulating the wire support portion and the wire outfeed device, without rotating the arm in the horizontal direction. Rotation of the arm in the horizontal direction, which was previously extremely time-consuming in the coal unloading operation, can thus be omitted, and the coal unloading operation carried out in a short time.

15

0010

In the present invention the conveyor mechanism may also extend and retract in the longitudinal direction.

 In the present invention thus constituted, even if the coal is in a position
20 separated from the crane main unit, by extending the conveyor mechanism in the longitudinal direction, the unloading operation can be accomplished without advancing or retracting the wire support portion.

0011

25

30

0012

0013

5

10

15

20

25

30

0014

0015

5

0016

10 Note that "approximately horizontal direction" above refers to the fact
that the wire support portion can be easily advanced and retracted, or to being
within a range of inclination angles such that coal or the like on the conveyor
does not roll off.

15

20

25

30

Effect of the Invention

0017

Using the present invention, the work of unloading coal or the like can be
5 performed in a short time.

Brief Description of Figures

0018

Fig. 1: A plan view of a transport vessel on which is mounted a bucket
10 crane according to a first embodiment of the present invention.

Fig. 2: A front elevation of a transport vessel on which is mounted a
bucket crane according to the first embodiment of the present invention.

Fig. 3: A side elevation showing the state in which the bucket in a bucket
crane according to the first embodiment of the present invention is in a lowered
15 state.

Fig. 4: A side elevation showing the state in which the bucket in a bucket
crane according to the first embodiment of the present invention is in a raised
state.

Fig. 5: A front elevation of a bucket crane in the state shown in Fig. 4.

20 Fig. 6: A side elevation of a bucket crane according to a second
embodiment of the present invention.

Fig. 7: A side elevation showing the state in which the bucket in a bucket
crane according to the second embodiment of the present invention is in a
lowered state.

25 Fig. 8: A side elevation showing the state in which the bucket in a bucket
crane according to the second embodiment of the present invention is in a raised
state.

Fig. 9: A side elevation of a bucket crane in an embodiment in which the
receiver member is omitted.

30

Embodiments of the Invention

0019

Below, referring to figures, we discuss details of a bucket crane with attached conveyor according to a first embodiment of the present invention.

5 Fig. 1 is a plan view of a transport vessel furnished with a bucket crane according to a first embodiment of the present invention for moving coal from a barge onto a wharf.

Fig. 2 is a front elevation of the transport vessel shown in Fig. 1.

10 As shown in Fig. 1, a transport vessel 1 is moored between a wharf 2 and a barge 6 loaded with coal 4; the coal 4 on the barge 6 is conveyed up to the wharf 2.

0020

15 As shown in Figs. 1 and 2, the transport vessel 1 is furnished with two bucket cranes 10 spaced apart with each other along the one longitudinal side edge of an approximately rectangular deck 8, a first conveyor 12 erected horizontally along the one longitudinal side edge of the deck 8, a second conveyor 14 erected inclinatory along the approximately diagonal direction on the deck 8, and a third conveyor 16 erected on the other longitudinal side edge
20 of the deck 8.

0021

25 As shown in Fig. 2, the first conveyor 12 passes horizontally through the base section 18 of each of the bucket cranes 10, and the downstream end portion is positioned above the upstream end portion of the second conveyor 14. Coal loaded onto the first conveyor 12 is fed toward the end portion on the bottom side of the second conveyor 14 and then falls from the end portion on the downstream side onto the second conveyor 14.

30 0022

The downstream end portion of the second conveyor 14 is positioned over the base portion 20 of the third conveyor 16. Coal falling from the first conveyor 12 onto the second conveyor 14 is fed in a diagonal upward direction by the second conveyor 14, and falls from above the base portion 20 of the third conveyor 16 onto the third conveyor 16.

0023

The third conveyor 16 is furnished with a base portion 20 and a conveyor main unit portion 22 erected on the base portion 20 and capable of rotational movement in the horizontal direction around the base portion 20. In the present embodiment, the end of the conveyor main unit portion 22 rotates and is positioned on the wharf 2 in order to carry the coal 4 on the barge 6 to the wharf 2. Coal falling from the downstream end portion of the second conveyor 14 onto the third conveyor 16 is carried to the wharf 2 by the conveyor main unit portion 22.

0024

Figs. 3 and 4 are side elevations of the bucket crane 10 of the present embodiment, respectively showing the state in which a bucket 24 has been lowered in order to fill the coal 4 on the barge 6 into the bucket 24, and the state in which the bucket 24 is raised in order to load the coal held in the bucket 24 onto a conveyor mechanism 26. Fig. 5 is a front elevation of a bucket crane 10 in the state shown in Fig. 4.

0025

As shown by Figs. 3 and 4, the bucket crane 10 is furnished with similar constituent elements to bucket cranes of the conventional art, such as a base portion 18 erected on the deck 8 of a transport vessel, a main unit 28 installed over the base portion 18, an arm 30 attached to the main unit 28, a wire 32 suspended from the end of the arm 30, a bucket 24 attached to the end of the

wire 32, and a wire outfeed device 34 for outfeeding the wire 32. The bucket crane 10 in the present embodiment is furnished with a conveyor mechanism 26 attached to the main unit 28 so as to extend in approximately the horizontal direction. Note that "approximately horizontal direction" here refers to being within a range of inclination angles such that the coal on the conveyor mechanism 26 does not fall off.

0026

The base portion 18 is formed of steel pipe, within which a through-holes 18A vertically extending is formed. As shown in Fig. 5, the first conveyor 12 passes horizontally through the midway portion of the base portion 18, and the first conveyor 12 is exposed within the through-hole 18A.

0027

The main unit 28 is erected above the base portion 18 so as to be rotatable in the horizontal direction around the center axis of the base portion 18. As shown in Fig. 5, the main unit 28 is furnished with two leg portions separated in the lateral direction, and a conveyor housing space 28A formed between them communicates with the base portion 18 through-hole 18A.

0028

The conveyor mechanism 26 is a member formed, for example, from a truss framework and including a conveyor main unit portion 26A; the back end portion thereof is held in an inserted state in the conveyor housing space 28A.

The conveyor main unit portion 26A of the conveyor mechanism 26 is terminated at the top of through-hole 18A in the base portion 18. Using a method such as hoisting a wire attached to the end of the conveyor mechanism 26 with a winch, the conveyor mechanism 26 is rotatable in a predetermined angular range of motion in the up/down direction relative to the main unit 28 around the position at which the conveyor main unit portion 26A terminates.

0029

The arm 30 is attached to the main unit 28 at the bottom end in a state whereby it is inclined frontward and upward. The arm 30 can be rotated in only a
5 predetermined angular range of rotation in the up/down direction around the bottom end attached to the main unit 28. Note that in this embodiment what is shown is the case in which the bottom end of the arm 30 is attached to the main unit 28, but there is no limitation to this form, and the intermediate portion of the arm may be attached to the main unit, with a counterweight attached to the
10 bottom end portion of the arm.

0030

The wire outfeed device 34 is formed, for example, of a winch; it is attached to the main unit 28, and feeds out or pulls in the wire 32 in response to
15 controls by an operator.

The bucket 24 can also be opened and closed by remote control so that coal can be placed therein, and coal contained therein can be discharged.

0031

20 As explained above, in the bucket crane 10 of the present embodiment the arm 30 and conveyor mechanism 26 are connected to the main unit 28 which is rotatable in the horizontal direction around the center axis of the base portion 18, therefore the arm 30 and the conveyor mechanism 26 are able to rotate in a horizontal direction as an integral unit around the center axis of the base portion
25 18 so as to be at all times in a state of extension in the same direction as the horizontal direction as seen in plan view.

0032

Below we discuss a method for transporting coal from a barge 6 to a
30 wharf 2 using a transport vessel 1 including the bucket crane 10 described

above.

First, as shown in Fig. 3, the arm 30 is rotated downward. This causes the bucket 24 to move in the forward direction and to descend toward the pile of coal 4 inside the hold of the barge 6. When the bucket 24 has descended to the coal pile, the bucket 24 is released and its interior filled with coal, whereupon the bucket 24 is again closed.

0033

Next, as shown in Fig. 4, the arm 30 is rotated upward. At this point there is no need to pull in the wire 32 using the wire outfeed device 34. By rotating the arm 30 in the upward direction, the bucket 24 moves upward and toward the main unit 28. As described above, in the bucket crane 10, the arm 30 and the conveyor mechanism 26 are at all times oriented at the same angle in the horizontal direction, therefore by rotating the arm 30 upward, the bucket 24 moves to a position over the conveyor mechanism 26 conveyor main unit portion 26A.

0034

Thus in the bucket crane 10 of the present embodiment, the bucket 24 can be moved between a coal pile 4 and a position over the conveyor main unit portion 26A by rotating the arm 30 in the up/down direction, without feeding out or pulling in the wire 32 with the wire outfeed device 34, and without rotation in the horizontal direction of the arm 30. Therefore the outfeeding/pulling in by the wire outfeed device 34 of the wire 32, and the rotation of the arm 30 in the horizontal direction, which were previously extremely time-consuming tasks, can be omitted; in addition, the work of rotating the arm 30 in the up/down direction can be done in an extremely short time compared to the outfeeding/pulling in by wire outfeed device 34 of the wire 32 and the rotation of the arm 30 in the horizontal direction, therefore the time required for loading coal onto the conveyor mechanism 26 can be extremely curtailed.

0035

Next, the bucket 24 is opened in this state, and the coal held within it is dropped. Coal which has fallen from the bucket 24 is loaded onto the conveyor main unit portion 26A of the conveyor mechanism 26. Coal loaded onto the conveyor main unit portion 26A of the conveyor mechanism 26 is carried toward the main unit 28, and falls from the end portion of the conveyor main unit portion 26A in the conveyor housing space 28A. As described above, the conveyor housing space 28A and the through-hole 18A of the base portion 18 communicate, and the end portion of the conveyor main unit portion 26A is positioned over the through-hole 18A of the base portion 18, therefore coal falling from the conveyor main unit portion 26A falls toward the base portion 18 through-hole 18A, and is loaded onto the first conveyor 12 extending in the horizontal direction within the through-hole 18A.

0036

Note that when the unloading of coal on the barge 6 progresses and the height of the pile of coal 4 on the barge 6 diminishes, it is sufficient that the wire 32 is fed out by the wire outfeed device 34 so that the length of the wire 32 suspended from the end of the arm 30 is lengthened, and the conveyor mechanism 26 is rotated in the downward direction. By doing so, coal can be loaded onto the conveyor mechanism 26 in the same manner described above, even if the height of the coal pile 4 diminishes. Conversely, when the height of the coal pile 4 is high, it is sufficient for the wire outfeed device 34 to pull in the wire 32, thereby shortening the length of the wire 32 suspended from the end of the arm 30, and to rotate the conveyor mechanism 26 upward.

0037

In this way the coal transferred from the barge 6 onto the first conveyor 12 is carried to a position over the downstream end portion of the second

conveyor 14 along the edge of the transport vessel deck 8 by the first conveyor 12 and dropped onto the second conveyor 14 from the downstream end portion. Coal which has fallen onto the second conveyor 14 is carried upward in the diagonal direction of the transport vessel 1 by the second conveyor 14, and falls from the downstream end portion of the second conveyor 14 onto the conveyor main unit portion 22 of a third conveyor 16. Coal which has fallen onto conveyor main unit portion 22 of the third conveyor 16 is carried to the wharf by the third conveyor 16.

0038

As explained above, with the bucket crane 10 of the present embodiment, the arm 30 and the conveyor mechanism 26 are rotated in the horizontal direction so that the direction in which the arm 30 extends and the direction in which the conveyor mechanism 26 extends at all times match in plan view, therefore the bucket 24 can be moved between the position at which coal is held on the barge and a position above the conveyor mechanism 26 simply by rotating the arm 30 downward.

0039

Therefore the outfeeding/pulling in the wire 32 by wire outfeed device 34 and the rotation of the arm 30 in the horizontal direction which were previously extremely time-consuming can be omitted; in addition, the work of rotating the arm 30 in the up/down direction can be done in an extremely short time compared to the outfeeding/pulling in the wire 32 by wire outfeed device 34 and rotation of the arm 30 in the horizontal direction, therefore the work of moving coal from a barge 6 to a wharf 2 can be extremely curtailed. In particular, the wire outfeed/hoisting operation by wire outfeed device and the rotation of the arm in the horizontal direction were repeated many times in the coal unloading work, therefore coal unloading time can be cut significantly.

0040

Because the conveyor mechanism 26 can be rotated up and down, when the amount of coal 4 loaded onto the deck of the barge 6 is reduced and thus the height of the coal pile is lowered, by rotating the conveyor mechanism 26 into a downward-rotated state, and feeding out the wire 32 using the wire outfeed device 34 to lengthen the wire 32 suspended from the end of the arm 30, coal can be moved from the barge 6 to a position over the conveyor mechanism 26 simply by rotating the arm 30 up and down. Conversely, when the height of the coal pile 4 is high, by pulling in the wire 32 using the wire outfeed device 34 to shorten the length of the wire 32 suspended from the end of the 30, as well as rotating the conveyor mechanism 26 upward, coal can be moved from the barge 6 to a position over the conveyor mechanism 26 simply by rotating the arm 30 up and down.

15 0041

Note that in the present embodiment we explained the case of unloading coal, but the present invention is not limited thereto, and could be applied to a crane of the present invention for the work of unloading cargo such as iron ore, chips, and the like.

20 Also, in the present embodiment we explained a bucket crane 10 affixed to a transport vessel 1, but the invention is not limited thereto, and may be applied to a movable bucket crane.

0042

25 In the present embodiment there is no feeding out or pulling in whatsoever of the wire 32 by the wire outfeed device 34 during unloading, but the invention is not limited thereto, and outfeeding/pulling in of the wire 32 by the wire outfeed device 34 may also be performed. In such cases, as well, because the length of the wire 32 outfed/pulled in by the wire outfeed device 34 is much shorter when compared to the conventional method, work time can be reduced.

30

0043

In the present embodiment a constitution was adopted whereby the arm 30 and the conveyor mechanism 26 are rotated in the horizontal direction by rotation of the main unit 28 relative to the base portion 18, but the invention is not limited thereto, and it is also acceptable to provide respective rotation mechanisms for the arm 30 and the conveyor mechanism 26. In such cases, by synchronizing the rotational angles of the various rotation mechanisms, the arm 30 and the conveyor mechanism 26 are at all times in a state of extension in the same lateral direction when seen in plan view.

Further, in the above present embodiment we explained the case in which coal or the like is moved from a barge to a wharf, but the present invention is not limited thereto, and may be applied to cases in which coal or the like is moved from a barge to another vessel, or cases in which coal or the like is moved from a wharf to a barge.

0044

Below, referring to figures, we discuss details of a bucket crane with conveyor according to a second embodiment of the present invention. Note that in the present embodiment, for the constituent elements which are the same as in the first embodiment we assign the same reference numerals in the figures and omit an explanation thereof.

Fig. 6 is a side elevation of a bucket crane 110 according to the present embodiment.

As shown in Fig. 6, the bucket crane 110 is furnished with a base portion 18 vertically erected on a transport vessel or on land, a main unit 128 installed above the base portion 18, an arm 130 attached to the top end of the main unit 128 so as to extend in the horizontal direction, a wire 132A suspended from the end of the arm 130, a bucket 24 attached to the end of the wire 132A, and wire outfeed mechanisms 134A, 134B, and 134C capable of winding up and feeding

out wires 132A, 132B, and 132C. The bucket crane 110 is further furnished with a conveyor member 126 attached to the main unit 128.

0045

5 In the present embodiment, as well, the base portion 18 is formed of steel pipe, within which a vertically-extending through-hole 18A is formed. The first conveyor 12 passes horizontally through the midway portion of the base portion 18, and this first conveyor 12 is exposed within the through-hole 18A.

10 0046

 The main unit 128 is erected above the base portion 18 so as to be rotatable in the horizontal direction (the direction of arrow A) around the center axis of the base portion 18; by this means the arm 130 and conveyor member 126 attached to the main unit 128 can rotate in synchrony. The main unit 128 is
15 furnished with two leg portions, separated in the lateral direction as in the first embodiment, and the conveyor housing space formed between them communicates with the base portion 18 through-hole 18A.

0047

20 The conveyor member 126 is furnished with: a conveyor base portion 140 capable of ascending and descending within the conveyor housing space, a first conveyor member 142 supported by the conveyor base portion 140 so as to extend in the same direction as the arm 130 seen in plan view, a second conveyor member 144 connected so as to be able to slide in the axial direction
25 on the top portion of the first conveyor member 142, a hopper 146 attached to the end of the second conveyor member 144, and a receiver member 148 attached so as to be able to rotate forward and backward on the end portion of the hopper 146.

30 0048

The conveyor base portion 140 is capable of ascending and descending in the direction of arrow F relative to the main unit 128 in the conveyor housing space by means, for example, of uptake using a winch, or by use of a rack and pinion mechanism.

5 The first and second conveyor members 142 and 144 are members composed, for example, of truss frames including conveyor main unit portions 142A and 144A, formed of conveyor belts. The first conveyor member 142 is supported so as to be able to rotate within a predetermined angular range in an up/down direction (the direction of arrow G) relative to the conveyor base portion
10 140, around the position at which the belt main unit 142A terminates.

The second conveyor member 144 is able to slide along the longitudinal direction of the first conveyor member 142. The conveyor member 126 is thus able to advance and retract.

15 0049

Note that in the present embodiment, the bottom end of the wire extending from the wire support portion 150 mounted on the arm 130 is connected to the second conveyor member 144. The second conveyor member 144 thus synchronizes with movement of the wire support portion 150 and
20 advances and retracts relative to the first conveyor member 142.

0050

The hopper 146 is formed so that its width narrows in the downward direction so that coal inserted into its top portion drops to the top of the conveyor
25 main unit portion 144A on the second conveyor member 144.

The receiver member 148 is formed from steel material with a "U-shaped" cross section open at the top. The receiver member 148 is attached rotatably to the end of the hopper 146 at its base end portion; the bottom end of wire 132B suspended from the wire support portion 150 is connected to the end
30 portion thereof. By winding and outfeeding of the wire outfeed mechanism 134B,

the receiver member 148 is thus able to rotate in a predetermined angular range between a forward upward inclined state and an upright state.

0051

5 The arm 130 extends in the horizontal direction from the top end of the main unit 128; a wire support portion 150 is mounted on the top portion thereof so as to be able to slide in the axial direction. A wire extending from the wire outfeed mechanism 134C is connected to the wire support portion, which advances and retracts along the arm 130 through the winding or outfeeding of
10 the wire 132C by the wire outfeed mechanism 134C.

0052

 The wire outfeed mechanisms 134A, 134B, and 134C formed by winches, for example, are attached to the main unit 128, and are able to feed out
15 and pull in the wires 132A, 132B, and 132C in response to controls by an operator.

0053

 The wire 132A extending from the wire feed mechanism 134A extends to
20 the wire support portion 150, and the end portion thereof is suspended from the wire support portion 150. The bucket 24 is connected to the end of the wire 132A.

 The wire 132B extending from the wire outfeed mechanism 134B extends to the wire support portion 150, and the end portion thereof is
25 suspended from the wire support portion 150. As described above, the end of the wire 132B is connected to the end of the receiver member 148.

0054

 The wire 132C extending from the wire outfeed mechanism 134C is
30 loop-shaped, and is disposed along the arm 130. The wire support portion 150 is

attached to a midway portion of the wire 132C, and the wire support portion 150 can be advanced and retracted along the arm 130 by outfeeding and winding up using the wire outfeed mechanism 134C.

5 0055

Below we discuss a method for dropping coal loaded in a barge, for example, onto the conveyor 12 using the above-described bucket crane 10.

First, as shown by arrow A in Fig. 6, the main unit 128 is rotated relative to the base portion 18 so that the arm 130 faces the loaded pile of coal. Thus not only
10 the arm 130, but also the conveyor member 126 rotates so as to face the loaded pile.

0056

Next, by feeding or winding the wire 132C using the wire outfeed
15 mechanism 134C, the wire support portion 150 is advanced and retracted along the arm 130 so as to be positioned over the pile of coal loaded by the bucket 24, as shown by arrow B in Fig. 6. At this point it is advisable to feed out or wind up the wire 132A connected to the bucket 24 and the wire 132B connected to the receiver member 148 using the wire feed mechanisms 134A and 134B by just
20 the same amount as the movement distance of the wire support portion 150 (i.e., the outfeed or windup length of the wire 132C by the wire outfeed mechanism 134C).

0057

25 Also, the second conveyor member 144 is connected to the wire support portion 150 via the wire 132D, therefore as shown by the arrow E in Fig. 6, by moving the wire support portion 150, the second conveyor member 144 can advance and retract on the first conveyor member 142 in synchronization with said wire support portion 150 so that the hopper 146 is positioned close to the
30 bucket 24 in the horizontal direction.

0058

Then, as shown by arrow F in Fig. 6, the conveyor base portion 140 is raised or lowered relative to the main unit 128 so that the end of the second conveyor member 144 is positioned slightly above the position at which the coal is loaded.

0059

Next, as shown in Fig. 7, the wire 132A is fed out by the wire outfeed mechanism 134A so that the bucket 24 is lowered as shown by the arrow C in Fig. 6. At this point, the wire 132B is wound up by the wire outfeed mechanism 134B so that the receiver member 148 is rotated until it faces upward to prevent interference by the bucket 24 and the receiver member 148.

When the bucket 24 descends to the coal pile, the bucket 24 is opened and filled with coal.

0060

Next, as shown in Fig. 8, the wire 132A is wound up by the wire outfeed mechanism 134A, and the bucket 24 is elevated to above the receiver member 148. Then, as shown by arrow D in Fig. 6, the wire 132B is fed out by the wire outfeed mechanism 134B so that the receiver member 148 is turned until it inclines to face diagonally upward. The receiver member 148 is thus positioned below the bucket 24.

25 0061

Next, with the receiver member 148 positioned below the bucket 24, the bucket 24 is opened and the coal held within it is caused to drop. Coal from the bucket 24 falls on the receiver member 148 and is guided by this receiver member, passing through the hopper 146 and falling on the second conveyor member 144 conveyor main unit portion 144A.

0062

Coal which has fallen on the conveyor main unit portion 144A of the second conveyor member 144 is transported by the conveyor main unit portion 144A and falls from its end close to the main unit 128 onto conveyor main unit portion 142A or the first conveyor member 142. Coal which has thus fallen on the first conveyor member 142 conveyor main unit portion 142A is transported by the conveyor main unit portion 142A and falls into the conveyor housing space. As described above, the conveyor housing space 28A and the through-hole 18A of the base portion 18 communicate, and the end portion of the conveyor main unit portion 142A of the first conveyor member 142 is positioned above through-hole 18A of the base portion 18, therefore coal which has fallen from the conveyor main unit portion 142A falls into through-hole 18A of the base portion 18, and falls onto the first conveyor 12 extending in the horizontal direction within the through-hole 18A.

0063

Thus large amounts of coal can be fed to the first conveyor 12 by repeating the processes whereby with the receiver member 148 rotated to a vertical state, the bucket 24 is caused to drop and to receive coal in its interior, and whereby the bucket 24 is raised and, with the receiver member 148 rotated and inclined in a horizontal direction, the coal in the bucket 24 is dropped onto a receiver.

25 0064

Note that when the work of unloading coal on a barge advances and the height of the coal pile on the barge diminishes, it is advisable to rotate the conveyor member 126 downward, as shown by arrow G in Fig. 6. The work of unloading coal can thus be continued without increasing the ascent/descent distance of the bucket 24 (e.g., the outfeed and windup length of the wire by the

wire outfeed mechanism 134A).

0065

As explained above, according to the bucket crane 110 of the present
5 embodiment, as same as the first embodiment, the arm 130 and the conveyor
member 126 are rotated in the horizontal direction in plan view so that the
direction in which the arm 130 extends and the direction in which the conveyor
member 126 extends are at all times matched, therefore the work of unloading
coal can be carried out simply by the pulling in of the bucket 24 and rotation of
10 the receiver member 148.

0066

Moreover, because of the provision of the receiver member 148, simply
by lowering and raising the bucket 24 by the wire outfeed mechanism 134A and
15 rotating the receiver member 148 using the wire outfeed mechanism 134B, the
work of unloading coal can thus be carried out without rotating the arm 130 or
moving the wire support portion 150. Time spent unloading coal can thus be
shortened.

20 0067

Moreover, because the conveyor member 126 can be raised and
lowered relative to the main unit 128, the work of unloading coal can be
performed even when the height of the coal for unloading rises relative to the
bucket crane 110 due to high tide or to a rising of the vessel owing to a reduction
25 in the amount of coal on the vessel, by raising and lowering the conveyor
member 126 to match that height change, without lengthening the bucket 24
ascent/descent length.

0068

30 Note that in the present embodiment the wire support portion 150 does

not necessarily have to be capable of advancing and retracting along the arm 130.

0069

5 In the present embodiment, a receiver member 148 was provided at the end of the hopper 146, however as shown in Fig. 9, the receiver member 148 may also be omitted.

 In such cases, in stead of the rotational movement of the receiver member 148, it is advisable that when the bucket 24 is lowered and the interior
10 thereof filled with coal, the wire support portion 150 is advanced until the bucket 24 is positioned in front of the conveyor member 126, and the bucket is raised, following which the wire support portion 150 is retracted until the bucket 24 is in a position above the hopper 146 and the coal is caused to drop from the bucket 24. Note that for the bucket crane 110 in this case, it is not necessary for the
15 conveyor member 126 to be able to advance and retract; it is sufficient for the wire support portion 150 to be able to advance and retract in the axial direction of the arm 130.

0070

20 In such cases, when the bucket 24 is lowered and the interior thereof is filled with coal in place of the rotational movement of the receiver member 148, the second conveyor member 144 may also be retracted and the bucket 24 filled with coal and raised to above the conveyor member 126, following which the second conveyor member 144 is advanced. In such cases it is not necessarily
25 required that a receiver member 148 be provided, nor is there a requirement that the wire support portion 150 be able to advance and retract along the arm 130.

Explanation of Reference Numerals

0071

30 10, 110: bucket crane

- 18: base portion
- 24: bucket
- 26, 126: conveyor mechanism
- 28, 128: main unit
- 5 30, 130: arm
- 32, 132A, 132B, 132C, 132D: wire
- 34, 134A, 134B, 134C, 134D: wire outfeed device
- 148: receiver member
- 150: wire support portion

Document Title: Claims

Claim 1

A crane for unloading freight using a bucket, comprising:

a base portion;

5 a crane main unit portion erected on the base portion;

an arm extending in approximately the horizontal direction from the crane main unit;

a conveyor mechanism extending in approximately the horizontal direction from the crane main unit below the arm;

10 a wire support portion capable of advancing and retracting along said arm;

a wire an end portion of which is suspended from the wire support portion and which is connected at its end portion to the bucket;

15 and a wire outfeed device capable of feeding out and winding up the wire;

wherein the arm and the conveyor mechanism can be rotated in the horizontal direction around the same axis so that in plan view the direction in which the arm extends at all times matches the direction in which the conveyor mechanism extends.

20

Claim 2

The crane set forth in Claim 1, wherein the conveyor mechanism is capable of extending and retracting in the longitudinal direction.

Bucket Crane with Conveyor

Abstract

5

Problem: To enable the work of unloading coal or the like to performed in a short time.

Resolution Means: A bucket crane 10 includes a base portion 18; a main unit 28 mounted on the base portion 18; an arm 30 connected to the main unit 28 so as
10 to be rotatable in the up/down direction, extending to diagonally upward; a conveyor mechanism 26 extending laterally [horizontally] from the main unit 28; and a wire 32 suspended from the end of the arm 30, connected at its end to a bucket 24; whereby the arm 30 and the conveyor mechanism 26 are able to rotate in the horizontal direction around the same axis so that at all times the
15 direction in which the arm 30 extends matches the direction in which the conveyor 26 extends.

Figure 3